

Package ‘BoutrosLab.plotting.general’

August 5, 2020

Version 6.0.1

Type Package

Title Functions to Create Publication-Quality Plots

Date 2020-08-03

Maintainer Paul Boutros <PBoutros@mednet.ucla.edu>

Depends R (>= 3.0.2), lattice (>= 0.20-27), latticeExtra (>= 0.6-26),
cluster (>= 1.14.4), hexbin (>= 1.26.3), grid

Imports gridExtra, tools, gtable, e1071, MASS(>= 7.3-29)

Suggests Cairo (>= 1.5-1), knitr, testthat

Description

Contains several plotting functions such as barplots, scatterplots, heatmaps, as well as functions to combine plots and assist in the creation of these plots. These functions will give users great ease of use and customization options in broad use for biomedical applications, as well as general purpose plotting. Each of the functions also provides valid default settings to make plotting data more efficient and producing high quality plots with standard colour schemes simpler. All functions within this package are capable of producing plots that are of the quality to be presented in scientific publications and journals. P'ng et al.; BPG: Seamless, automated and interactive visualization of scientific data; BMC Bioinformatics 2019 <doi: 10.1186/s12859-019-2610-2>.

License GPL-2

LazyLoad yes

LazyData yes

VignetteBuilder knitr

NeedsCompilation yes

Author Paul Boutros [aut, cre],
Christine P'ng [ctb],
Jeff Green [ctb],
Stephenie Prokopec [ctb],
Ontario Institute for Cancer Research [cph],
The R Core Team [cph],
The R Foundation [cph],
Robert Gentleman [ctb],

Ross Ihaka [ctb],
 Caden Bugh [ctb]

Repository CRAN

Date/Publication 2020-08-05 09:52:26 UTC

R topics documented:

BoutrosLab.plotting.general-package	3
auto.axis	4
CNA	5
colour.gradient	6
covariates.grob	6
create.barplot	11
create.boxplot	35
create.colourkey	49
create.dendrogram	51
create.densityplot	53
create.dotmap	63
create.gif	79
create.heatmap	81
create.hexbinplot	110
create.histogram	123
create.lollipopplot	130
create.manhattanplot	140
create.multipanelplot	151
create.multiplot	170
create.polygonplot	197
create.qqplot.comparison	211
create.qqplot.fit	218
create.qqplot.fit.confidence.interval	227
create.scatterplot	229
create.segplot	252
create.stripplot	263
create.violinplot	272
default.colours	283
display.colours	284
display.statistical.result	285
dist	286
force.colour.scheme	289
generate.at.final	296
get.corr.key	296
get.correlation.p.and.corr	299
get.defaults	300
get.line.breaks	301
ks.test.critical.value	302
legend.grob	302
microarray	307

panel.BL.bwplot	307
patient	308
pcawg.colours	309
scientific.notation	310
show.available.palettes	311
SNV	312
thousands.split	313
write.metadata	314
write.plot	315

Index	318
--------------	------------

BoutrosLab.plotting.general-package*Boutros Lab general plotting functions***Description**

Functions for creating publication-quality plots

Details

Package:	BoutrosLab.plotting.general
Type:	Package
Version:	5.3.4
Date:	2015-07-31
License:	GPL-2
LazyLoad:	yes
LazyData:	yes

```
append.footnote(); colour.gradient(); covariates.grob(); create.colourkey(); create.barplot(); create.boxplot(); create.dendrogram(); create.densityplot(); create.dotmap(); create.heatmap(); create.hexbinplot(); create.histogram(); create.manhattanplot(); create.multiplot(); create.polygonplot(); create.qqplot.comparison(); create.qqplot.fit(); create.scatterplot(); create.segplot(); create.stripplot(); create.violinplot(); default.colours(); display.colours(); display.statistical.result(); force.colour.scheme(); general.at.final(); get.corr.key(); get.defaults(); get.line.breaks(); legend.grob(); scientific.notation(); show.available.palettes(); write.metadata(); write.plot(); gleason.score.colour();
```

Author(s)

Author: Paul C. Boutros <Paul.Boutros@oicr.on.ca> Maintainer: Paul C. Boutros <Paul.Boutros@oicr.on.ca>

auto.axis*Create ideal labels and values for a given dataset (detects log scales)*

Description

Takes a dataset and several parameters and outputs an object with values and labels ideal for that dataset

Usage

```
auto.axis(
  x,
  pretty = TRUE,
  log.scaled = NA,
  log.zero = 0.1,
  max.factor = 1,
  min.factor = 1,
  include.origin = TRUE,
  num.labels = 5,
  max.min.log10.diff = 2
)
```

Arguments

<code>x</code>	The dataset that is intended to be used for the labels and redistributed data
<code>pretty</code>	Parameter flag for if output should be in pretty format
<code>log.scaled</code>	parameter set to determine if scaling is logarithmic or not
<code>log.zero</code>	log 0 starting point
<code>max.factor</code>	maximum factor for y variable
<code>min.factor</code>	minimum factor for y variable
<code>include.origin</code>	flag to include the origin value or not
<code>num.labels</code>	number of labels to output
<code>max.min.log10.diff</code>	the max and min diffrence for dataset to be determined logarithmic

Author(s)

Takafumi Yamaguchi

See Also

[stripplot](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(223);
simple.data <- data.frame(
  x = sample(1:15, 10),
  y = LETTERS[1:10]
);

auto.axis(simple.data$x)

data2 <- c(1,10,100,1000)

auto.axis(data2)
```

CNA

Copy number aberration (CNA) data from colon cancer patients

Description

CNA calls from 30 genes across 58 colon cancer patients. Additional data on the patient samples is found in the patient dataset. The same patient samples are described in the `microarray` and `SNV` datasets.

Usage

`CNA`

Format

A data frame with 58 columns and 30 rows. The columns indicate the patient sample, and the rows indicate the gene. The contents of the data frame are encoded such that 0 indicates no CNA, -1 indicates a CNA loss, and 1 indicates a CNA gain.

Author(s)

Christine P'ng

Examples

```
data(CNA);
create.dotmap(
  filename = tempfile(pattern = 'Using_CNA_dataset', fileext = '.tiff'),
  x = CNA[1:15, 1:15],
  main = 'CNA data',
  xaxis.cex = 0.8,
  yaxis.cex = 0.8,
  xaxis.rot = 90,
  description = 'Dotmap created by BoutrosLab.plotting.general',
  resolution = 50
);
```

colour.gradient	<i>Creates a colour gradient</i>
-----------------	----------------------------------

Description

Creates a sequential palette of colours.

Usage

```
colour.gradient(
  colour,
  length
);
```

Arguments

colour	A single colour to be used as the center value of the sequence
length	The number of colours to include in the palette

Author(s)

Ren Sun & Christine P'ng

Examples

```
display.colours(colour.gradient('dodgerblue2', 6));
display.colours(colour.gradient(default.colours(1), 3));
```

covariates.grob	<i>Create one or more covariate bars</i>
-----------------	--

Description

Takes a list of covariate bar annotates and creates a grid graphical object for them

Usage

```
covariates.grob(
  covariates,
  ord,
  side = 'right',
  size = 1,
  grid.row = NULL,
  grid.col = NULL,
  grid.border = NULL,
  row.lines = NULL,
  col.lines = NULL,
  reorder.grid.index = FALSE,
  x = 0.5,
  y = 0.5
);
```

Arguments

<code>covariates</code>	Any covariate annotate to add to the plot, as a fully formed list.
<code>ord</code>	A vector of integer indices indicating the order of the items in the covariate bars.
<code>side</code>	Intended position of the covariate bar when added as a legend. Allowed positions are “right” and “top”.
<code>size</code>	The size of each covariate bar in units of “lines”.
<code>grid.row</code>	A list of parameters to be passed to <code>gpar</code> specifying the behaviour of row lines in the covariate bars. See Notes for details.
<code>grid.col</code>	A list of parameters to be passed to <code>gpar</code> specifying the behaviour of column lines in the covariate bars.
<code>grid.border</code>	A list of parameters to be passed to <code>gpar</code> specifying the behaviour of the border around the covariate bars.
<code>row.lines</code>	Vector of row indices where grid lines should be drawn. If <code>NULL</code> (default), all row lines are drawn. Ignored if <code>grid.row</code> is not specified.
<code>col.lines</code>	Vector of column indices where grid lines should be drawn. If <code>NULL</code> (default), all column lines are drawn. Ignored if <code>grid.col</code> is not specified.
<code>reorder.grid.index</code>	Boolean specifying whether grid line indices should be re-ordered according to the <code>ord</code> argument. Defaults to <code>FALSE</code> .
<code>x</code>	<code>x</code> coordinate in npc coordinate system
<code>y</code>	<code>y</code> coordinate in npc coordinate system

Value

A grid graphical object (grob) representing the covariate bar(s)

Notes

This code is an adaptation of the `dendrogramGrob` function in the `latticeExtra` package. It uses functions of the `grid` package.

By default, the covariate bar grid is drawn via borders around individual rectangles using the parameters specified in the `covariates` argument (`col`, `lwd`, etc.). If `grid.row`, `grid.col`, or `grid.border` are specified by the user, additional grid lines are drawn over any existing ones using the parameters in these lists.

Author(s)

Lauren Chong

See Also

[gpar](#)

Examples

```
# create temp data
set.seed(1234567890);

x <- outer(-5:5, -5:5, '*') + matrix(nrow = 11, ncol = 11, data = runif(11 * 11));
colnames(x) <- paste('col', 1:11, sep = '-');
rownames(x) <- paste('row', 1:11, sep = '-');

# set covariates
covariate.colours1 <- x[,1]
covariate.colours1[covariate.colours1 >= 0] <- default.colours(3)[1];
covariate.colours1[covariate.colours1 != default.colours(3)[1]] <- default.colours(3)[2];

covariate.colours2 <- x[,1]
covariate.colours2[covariate.colours2 >= 0] <- default.colours(3)[2];
covariate.colours2[covariate.colours2 != default.colours(3)[2]] <- default.colours(3)[3];

# create an object to draw the covariates from
covariates1 <- list(
  rect = list(
    col = 'black',
    fill = covariate.colours1,
    lwd = 1.5
  ),
  rect = list(
    col = 'black',
    fill = covariate.colours2,
    lwd = 1.5
  )
);

# create a covariates grob using a simple incremental ordering and default behaviour
covariates.grob1 <- covariates.grob(
  covariates = covariates1,
```

```
    ord = c(1:ncol(x)),
    side = 'right'
  );
tiff(
  filename = tempfile(pattern = 'covariates_grob1', fileext = '.tiff'),
  type = 'cairo',
  width = 6,
  height = 6,
  units = 'in',
  res = 1000,
  compression = 'lzw'
);
grid.draw(covariates.grob1);
dev.off();

# create a dendrogram for x
cov.dendrogram <- BoutrosLab.plotting.general::create.dendrogram(
  x = x,
  clustering.method = 'average'
);

covariates2 <-list(
  rect = list(
    col = 'black',
    fill = covariate.colours2,
    lwd = 1.5
  )
);

# create a covariates grob using the dendrogram ordering and double the default size
covariates.grob2 <- covariates.grob(
  covariates = covariates2,
  ord = order.dendrogram(cov.dendrogram),
  side = 'top',
  size = 2
);
tiff(
  filename = tempfile(pattern = 'covariates_grob2', fileext = '.tiff'),
  type = 'cairo',
  width = 6,
  height = 6,
  units = 'in',
  res = 1000,
  compression = 'lzw'
);
grid.draw(covariates.grob2);
dev.off();

# add a border of a different colour
covariates.grob3 <- covariates.grob(
  covariates = covariates1,
  ord = c(1:ncol(x)),
  side = 'right',
```

```

grid.border = list(col = 'red', lwd = 1.5)
);
tiff(
  filename = tempfile(pattern = 'covariates_grob3', fileext = '.tiff'),
  type = 'cairo',
  width = 6,
  height = 6,
  units = 'in',
  res = 1000,
  compression = 'lzw'
);
grid.draw(covariates.grob3);
dev.off();

# create covariates with transparent rectangle borders
covariates3 <- list(
  rect = list(
    col = 'transparent',
    fill = covariate.colours1,
    lwd = 1.5
  ),
  rect = list(
    col = 'transparent',
    fill = covariate.colours2,
    lwd = 1.5
  )
);

# add column grid lines and a border with default gpar settings
covariates.grob4 <- covariates.grob(
  covariates = covariates3,
  ord = c(1:nrow(x)),
  side = 'top',
  grid.col = list(col = 'black', lty = 3),
  grid.border = list()
);
tiff(
  filename = tempfile(pattern = 'covariates_grob4', fileext = '.tiff'),
  type = 'cairo',
  width = 6,
  height = 6,
  units = 'in',
  res = 1000,
  compression = 'lzw'
);
grid.draw(covariates.grob4);
dev.off();

# draw a subset of row/column lines
covariates.grob5 <- covariates.grob(
  covariates = covariates3,
  ord = order.dendrogram(cov.dendrogram),
  side = 'right',

```

```
grid.row = list(lineend = 'butt', lwd = 2),
row.lines = 6,
reorder.grid.index = FALSE, # note: this is already set by default
grid.col = list(lty = 2),
col.lines = c(0,1)
);
tiff(
  filename = tempfile(pattern = 'covariates_grob5', fileext = '.tiff'),
  type = 'cairo',
  width = 6,
  height = 6,
  units = 'in',
  res = 1000,
  compression = 'lzw'
);
grid.draw(covariates.grob5);
dev.off();
```

create.barplot*Make a barplot*

Description

Takes a data.frame and creates a barplot

Usage

```
create.barplot(
  formula,
  data,
  groups = NULL,
  stack = FALSE,
  filename = NULL,
  main = NULL,
  main.just = 'center',
  main.x = 0.5,
  main.y = 0.5,
  main.cex = 3,
  xlab.label = tail(sub('`', '', formula[-2]), 1),
  ylab.label = tail(sub('`', '', formula[-3]), 1),
  xlab.cex = 2,
  ylab.cex = 2,
  xlab.col = 'black',
  ylab.col = 'black',
  xlab.top.label = NULL,
  xlab.top.cex = 2,
  xlab.top.col = 'black',
  xlab.top.just = 'center',
```

```
xlab.top.x = 0.5,  
xlab.top.y = 0,  
abline.h = NULL,  
abline.v = NULL,  
abline.lty = 1,  
abline.lwd = NULL,  
abline.col = 'black',  
axes.lwd = 1,  
add.grid = FALSE,  
xgrid.at = xat,  
ygrid.at = yat,  
grid.lwd = 5,  
grid.col = NULL,  
xaxis.lab = TRUE,  
yaxis.lab = TRUE,  
xaxis.col = 'black',  
yaxis.col = 'black',  
xaxis.fontface = 'bold',  
yaxis.fontface = 'bold',  
xaxis.cex = 1.5,  
yaxis.cex = 1.5,  
xaxis.rot = 0,  
yaxis.rot = 0,  
xaxis.tck = 1,  
yaxis.tck = 1,  
xlims = NULL,  
ylims = NULL,  
xat = TRUE,  
yat = TRUE,  
layout = NULL,  
as.table = FALSE,  
x.spacing = 0,  
y.spacing = 0,  
x.relation = 'same',  
y.relation = 'same',  
top.padding = 0.5,  
bottom.padding = 1,  
right.padding = 1,  
left.padding = 1,  
key.bottom = 0.1,  
ylab.axis.padding = 0.5,  
xlab.axis.padding = 0.5,  
col = 'black',  
border.col = 'black',  
border.lwd = 1,  
plot.horizontal = FALSE,  
background.col = 'transparent',  
origin = 0,
```

```
reference = TRUE,
box.ratio = 2,
sample.order = 'none',
group.labels = FALSE,
key = list(text = list(lab = c(''))),
legend = NULL,
add.text = FALSE,
text.labels = NULL,
text.x = NULL,
text.y = NULL,
text.col = 'black',
text.cex = 1,
text.fontface = 'bold',
strip.col = 'white',
strip.cex = 1,
y.error.up = NULL,
y.error.down = y.error.up,
y.error.bar.col = 'black',
error.whisker.width = width/(nrow(data)*4),
error.bar.lwd = 1,
error.whisker.angle = 90,
add.rectangle = FALSE,
xleft.rectangle = NULL,
ybottom.rectangle = NULL,
xright.rectangle = NULL,
ytop.rectangle = NULL,
col.rectangle = 'grey85',
alpha.rectangle = 1,
line.func = NULL,
line.from = 0,
line.to = 0,
line.col = 'transparent',
line.infront = TRUE,
text.above.bars = list(labels = NULL,
padding = NULL,
bar.locations = NULL,
rotation = 0
),
raster = NULL,
raster.vert = TRUE,
raster.just = 'center',
raster.width.dim = unit(2/37, 'npc'),
height = 6,
width = 6,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
description = 'Created with BoutrosLab.plotting.general',
```

```

style = 'BoutrosLab',
preload.default = 'custom',
use.legacy.settings = FALSE,
inside.legend.auto = FALSE,
disable.factor.sorting = FALSE
);

```

Arguments

<code>formula</code>	The formula used to extract the x & y components from the data-frame
<code>data</code>	The data-frame to plot
<code>groups</code>	Optional grouping variable. Expression or variable.
<code>stack</code>	Logical, relevant when groups is non-null. If FALSE (the default), bars for different values of the grouping variable are drawn side by side, otherwise they are stacked
<code>filename</code>	Filename for tiff output, or if NULL returns the trellis object itself
<code>main</code>	The main title for the plot (space is reclaimed if NULL)
<code>main.just</code>	The justification of the main title for the plot, default is centered
<code>main.x</code>	The x location of the main title, default is 0.5
<code>main.y</code>	The y location of the main title, default is 0.5
<code>main.cex</code>	Size of text for main plot title, defaults to 3
<code>xlab.label</code>	The label for the x-axis
<code>ylab.label</code>	The label for the y-axis
<code>xlab.cex</code>	Size of x-axis label, defaults to 2
<code>ylab.cex</code>	Size of y-axis label, defaults to 2
<code>xlab.col</code>	Colour of the x-axis label, defaults to black
<code>ylab.col</code>	Colour of the y-axis label, defaults to black
<code>xlab.top.label</code>	The label for the top x-axis
<code>xlab.top.cex</code>	Size of top x-axis label
<code>xlab.top.col</code>	Colour of the top x-axis label
<code>xlab.top.just</code>	Justification of the top x-axis label, defaults to centered
<code>xlab.top.x</code>	The x location of the top x-axis label
<code>xlab.top.y</code>	The y location of the top y-axis label
<code>abline.h</code>	Specify the superimposed horizontal line(s)
<code>abline.v</code>	Specify the superimposed vertical line(s)
<code>abline.lty</code>	Specify the superimposed line type
<code>abline.lwd</code>	Specify the superimposed line width
<code>abline.col</code>	Specify the superimposed line colour (defaults to black)
<code>axes.lwd</code>	Specify line width of the axes; set to 0 to turn off axes
<code>add.grid</code>	Specify whether to draw grid or not (defaults to FALSE)

xgrid.at	Specify where to draw x-axis grid lines (defaults to xat)
ygrid.at	Specify where to draw y-axis grid lines (defaults to yat)
grid.lwd	Specify width of grid line (defaults to 5)
grid.col	Specify colour of grid line. Currently only supports one colour. Defaults to NULL, which uses the colour of the reference line.
xaxis.lab	Vector listing x-axis tick labels, defaults to automatic
yaxis.lab	Vector listing y-axis tick labels, defaults to automatic
xaxis.col	Colour of the x-axis tick labels, defaults to black
yaxis.col	Colour of the y-axis tick labels, defaults to black
xaxis.fontface	Fontface for the x-axis scales
yaxis.fontface	Fontface for the y-axis scales
xaxis.cex	Size of x-axis tick labels, defaults to 1.2
yaxis.cex	Size of y-axis tick labels, defaults to 1.5
xaxis.rot	Rotation of x-axis tick labels; defaults to 0
yaxis.rot	Rotation of y-axis tick labels; defaults to 0
xaxis.tck	Specifies the length of the tick marks for x-axis, defaults to 1
yaxis.tck	Specifies the length of the tick marks for y-axis, defaults to 1
xlimits	Two-element vector giving the x-axis limits. Useful when plot.horizontal = TRUE
ylimits	Two-element vector giving the y-axis limits
xat	Vector listing where the x-axis labels should be drawn. Useful when plot.horizontal = TRUE
yat	Vector listing where the y-axis labels should be drawn
layout	A vector specifying the number of columns, rows (e.g., c(2,1). Default is NULL; see lattice::xyplot for more details.
as.table	Specifies panel drawing order, default is FALSE which draws panels from bottom left corner, moving right then up. Set to TRUE to draw from top left corner, moving right then down
x.spacing	A number specifying the distance between panels along the x-axis, defaults to 0
y.spacing	A number specifying the distance between panels along the y-axis, defaults to 0
x.relation	Allows x-axis scales to vary if set to "free", defaults to "same"
y.relation	Allows y-axis scales to vary if set to "free", defaults to "same"
top.padding	A number specifying the distance to the top margin, defaults to 0.5
bottom.padding	A number specifying the distance to the bottom margin, defaults to 2
right.padding	A number specifying the distance to the right margin, defaults to 1
left.padding	A number specifying the distance to the left margin, defaults to 1
key.bottom	A number specifying how much space should be left for the key at the bottom, defaults to 0.1

<code>ylab.axis.padding</code>	A number specifying the distance of y-axis label to the y-axis, defaults to 0,
<code>xlab.axis.padding</code>	A number specifying the distance of x-axis label to the x-axis, defaults to 0.5. Named differently than <code>ylab.axis.padding</code> because these are lattice's internal names for these values
<code>col</code>	Filling colour of bars, defaults to black, does a grey-scale spectrum if <code>!is.null(groups)</code>
<code>border.col</code>	Specify border colour (defaults to black)
<code>border.lwd</code>	Specify border width (defaults to 1)
<code>plot.horizontal</code>	Plot the bars horizontally
<code>background.col</code>	Plot background colour, defaults to transparent
<code>origin</code>	The origin of the plot, generally 0
<code>reference</code>	Should the reference line be printed at the origin
<code>box.ratio</code>	Specifies the width of each bar, defaults to 2
<code>sample.order</code>	Should the bars be reordered, accepts values "increasing", "decreasing" or a vector of sample names. Labels will also be reordered
<code>group.labels</code>	Should the labels be grouped to the same amount of bars per column
<code>key</code>	A list giving the key (legend). The default suppresses drawing
<code>legend</code>	Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See <code>xyplot</code> .
<code>add.text</code>	Allow additional text to be drawn, default is FALSE
<code>text.labels</code>	Labels for additional text
<code>text.x</code>	The x co-ordinates where additional text should be placed
<code>text.y</code>	The y co-ordinates where additional text should be placed
<code>text.col</code>	The colour of additional text
<code>text.cex</code>	The size of additional text
<code>text.fontface</code>	The fontface for additional text
<code>strip.col</code>	Strip background colour, defaults to white
<code>strip.cex</code>	Strip title character expansion
<code>y.error.up</code>	A vector specifying the length of the error bar going up from each point. If set to NULL (the default), error bars will not be drawn
<code>y.error.down</code>	A vector specifying the length of the error bar going down from each point. By default, it is set to <code>y.error.up</code>
<code>y.error.bar.col</code>	A string or vector of strings specifying the colour of the error bars. Defaults to black
<code>error.whisker.width</code>	A number specifying the width of the error bars. Defaults to a rough approximation based on the size of the data
<code>error.bar.lwd</code>	The line width of the error bars. Defaults to 1

error.whisker.angle
 The angle of the error bar whiskers, defaults to 90. Can be changed to produce arrow-like bars

add.rectangle Allow a rectangle to be drawn, default is FALSE

xleft.rectangle
 Specifies the left x coordinate of the rectangle to be drawn

ybottom.rectangle
 Specifies the bottom y coordinate of the rectangle to be drawn

xright.rectangle
 Specifies the right x coordinate of the rectangle to be drawn

ytop.rectangle Specifies the top y coordinate of the rectangle to be drawn

col.rectangle Specifies the colour to fill the rectangle's area

alpha.rectangle
 Specifies the colour bias of the rectangle

line.func Function for the line that should be drawn on top of plot

line.from The starting point of the line on the plot

line.to The ending point of the line on the plot

line.col Colour of the line on the plot

line.infront Should the line appear in front of the plot or not

text.above.bars
 Should some form of text appear above the bars; input as a list

raster The image to raster over each bar - see Raster Images in R Graphics by Paul Murrell for full details

raster.vert A logical indicating whether the raster is applied vertically or horizontally

raster.just A word giving the justification of the raster, can be set to "left", "right", "centre", "center", "bottom", or "top"

raster.width.dim
 A unit object giving the width of the raster bar

height Figure height, defaults to 6 in

width Figure width, defaults to 6 in

size.units Figure units, defaults to inches

resolution Figure resolution, defaults to 1600

enable.warnings
 Print warnings if set to TRUE, defaults to FALSE

description Description of image/plot; default NULL

style defaults to "BoutrosLab", also accepts "Nature", which changes parameters according to Nature formatting requirements

preload.default
 ability to set multiple sets of different defaults depending on publication needs

use.legacy.settings
 boolean to set whether or not to use legacy mode settings (font)

inside.legend.auto
 boolean specifying whether or not to use the automatic inside legend function

disable.factor.sorting
 Disable barplot auto sorting factors alphabetically/numerically

Value

If `filename` is `NULL` then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of `create histogram` is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```
Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics
```

Author(s)

Mehrdad Shamsi

See Also

[barchart](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(12345);

simple.data <- data.frame(
  x = sample(1:15, 5),
  y = LETTERS[1:5]
);

# Simple example
create.barplot(
  filename = tempfile(pattern = 'Barplot_Simple', fileext = '.tiff'),
  formula = x ~ y,
  data = simple.data,
  yat = seq(0,16,2),
  resolution = 30
);

# set up the data
total.counts <- apply(SNV[1:15], 2, function(x){ mutation.count <- (30 - sum(is.na(x)))});
count.nonsyn <- function(x){
  mutation.count <- length(which(x == 1));
}
nonsynonymous.SNV <- apply(SNV[1:15], 2, count.nonsyn);
other.mutations <- total.counts - nonsynonymous.SNV;
```

```
# subset the first fifteen samples
barplot.data <- data.frame(
  samples = rep(1:15, 2),
  mutation = c(rep('nonsynonymous', 15), rep('other',15)),
  type = c(rep(1, 15), rep(2,15)),
  values = c(nonsynonymous.SNV, other.mutations),
  sex = rep(patient$sex[1:15], 2),
  stage = rep(patient$stage[1:15], 2),
  msi = rep(patient$msi[1:15], 2)
);

# Minimal input
create.barplot(
  filename = tempfile(pattern = 'Barplot_Minimal_Input', fileext = '.tiff'),
  formula = values ~ samples ,
  data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
  main = 'Minimal input',
  # Editing the metadata
  description = 'Barplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Axes labels & limits
create.barplot(
  filename = tempfile(pattern = 'Barplot_Custom_Axes', fileext = '.tiff'),
  formula = values ~ samples,
  data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
  main = 'Axes labels & limits',
  # Setting axes labels
  xlab.lab = 'Sample',
  ylab.lab = 'Nonsynonymous SNVs',
  # Setting y-axis limits and tick-mark locations
  ylims = c(0,30),
  yat = seq(0,30,5),
  description = 'Barplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Font size and font face
create.barplot(
  filename = tempfile(pattern = 'Barplot_Font_Changes', fileext = '.tiff'),
  formula = values ~ samples,
  data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
  main = 'Font changes',
  xlab.lab = 'Samples',
  ylab.lab = 'Nonsynonymous SNVs',
  ylims = c(0,30),
  yat = seq(0,30,5),
  # Changing font sizes
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
```

```

# Changing font type
xaxis.fontface = 1,
yaxis.fontface = 1,
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 100
);

# Sorting data
create.barplot(
  filename = tempfile(pattern = 'Barplot_Sorted', fileext = '.tiff'),
  formula = values ~ samples,
  data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
  main = 'Sorted bars',
  xlab.lab = 'Samples',
  ylab.lab = 'Nonsynonymous SNVs',
  ylims = c(0,30),
  yat = seq(0,30,5),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  # Order bars either by 'increasing' or 'decreasing'
  sample.order = 'decreasing',
  description = 'Barplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Colour changes
sex.colours <- replace(as.vector(barplot.data$sex), which(barplot.data$sex == 'male'), 'dodgerblue');
sex.colours <- replace(sex.colours, which(barplot.data$sex == 'female'), 'pink');

create.barplot(
  filename = tempfile(pattern = 'Barplot_Colour_Changes', fileext = '.tiff'),
  formula = values ~ samples,
  data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
  main = 'Colour changes',
  xlab.lab = 'Samples',
  ylab.lab = 'Nonsynonymous SNVs',
  ylims = c(0,30),
  yat = seq(0,30,5),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  # Colour bars based on sex
  col = sex.colours,
  description = 'Barplot created by BoutrosLab.plotting.general',
  resolution = 100
)

```

```
);

# Legend
create.barplot(
    filename = tempfile(pattern = 'Barplot_Legend', fileext = '.tiff'),
    formula = values ~ samples,
    data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
    main = 'Legend',
    xlab.lab = 'Samples',
    ylab.lab = 'Nonsynonymous SNVs',
    ylims = c(0,30),
    yat = seq(0,30,5),
    xaxis.cex = 1,
    yaxis.cex = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    col = sex.colours,
    # Adding legend to explain bar colour-coding
    legend = list(
        inside = list(
            fun = draw.key,
            args = list(
                key = list(
                    points = list(
                        col = 'black',
                        pch = 22,
                        cex = 3,
                        fill = c('dodgerblue', 'pink')
                    ),
                    text = list(
                        lab = c('Male', 'Female')
                    ),
                    padding.text = 5,
                    cex = 1
                )
            ),
            # Positioning legend on plot
            x = 0.75,
            y = 0.95
        )
    ),
    description = 'Barplot created by BoutrosLab.plotting.general',
    resolution = 100
);

# Grouped barplot
create.barplot(
    filename = tempfile(pattern = 'Barplot_Grouped', fileext = '.tiff'),
    formula = values ~ samples,
    data = barplot.data,
    main = 'Grouped bar chart',
```

```

xlab.lab = 'Samples',
ylab.lab = 'Mutations',
ylimits = c(0,30),
yat = seq(0,30,5),
xaxis.cex = 1,
yaxis.cex = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
xaxis.fontface = 1,
yaxis.fontface = 1,
# Setting groups
groups = mutation,
col = default.colours(12, is.greyscale = FALSE)[11:12],
legend = list(
  inside = list(
    fun = draw.key,
    args = list(
      key = list(
        points = list(
          col = 'black',
          pch = 22,
          cex = 2,
          fill = default.colours(12, is.greyscale = FALSE)[11:12]
        ),
        text = list(
          lab = c('Nonsynonymous SNV', 'Other SNV')
        ),
        padding.text = 3,
        cex = 1
      )
    ),
    x = 0.55,
    y = 0.95
  )
),
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 100
);

# Grouped labels
create.barplot(
  filename = tempfile(pattern = 'Barplot_Grouped_Labels', fileext = '.tiff'),
  formula = values ~ samples,
  data = barplot.data,
  main = 'Grouped labels',
  xlab.lab = 'Samples',
  ylab.lab = 'Mutations',
  ylimits = c(0,30),
  yat = seq(0,30,5),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,

```

```
xaxis.fontface = 1,
yaxis.fontface = 1,
# Setting groups
groups = mutation,
col = default.colours(12, is.greyscale = FALSE)[11:12],
# Grouped labels
xaxis.lab = rep(c('nonsynonymous', 'other'), 15),
xaxis.rot = 90,
group.labels = TRUE,
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Stacked barplot
create.barplot(
  filename = tempfile(pattern = 'Barplot_Stacked', fileext = '.tiff'),
  formula = values ~ samples,
  data = barplot.data,
  main = 'Stacked bar chart',
  xlab.lab = 'Samples',
  ylab.lab = 'Mutations',
  ylims = c(0,30),
  yat = seq(0,30,5),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  groups = mutation,
  col = default.colours(12, is.greyscale = FALSE)[11:12],
  legend = list(
    inside = list(
      fun = draw.key,
      args = list(
        key = list(
          points = list(
            col = 'black',
            pch = 22,
            cex = 2,
            # reverse order to match stacked bar order
            fill = rev(default.colours(12, is.greyscale = FALSE)[11:12])
          ),
          text = list(
            # reverse order to match stacked bar order
            lab = rev(c('Nonsynonymous SNV','Other SNV'))
          ),
          padding.text = 3,
          cex = 1
        )
      ),
      x = 0.55,
      y = 0.95
    )
  )
)
```

```

        )
    ),
# Changing the plot from a grouped plot to a stacked plot
stack = TRUE,
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Panel organization
create.barplot(
  filename = tempfile(pattern = 'Barplot_Panel_Layout_numeric_conditioning', fileext = '.tiff'),
  # Setting the panel layout
  formula = values ~ samples | type,
  data = barplot.data,
  main = 'Panel layout',
  xlab.lab = 'Samples',
  ylab.lab = 'Mutations',
  ylims = c(0,30),
  yat = seq(0,30,5),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  description = 'Barplot created by BoutrosLab.plotting.general',
  resolution = 200
);

create.barplot(
  filename = tempfile(pattern = 'Barplot_Panel_Layout_character_conditioning', fileext = '.tiff'),
  # Setting the panel layout
  formula = values ~ samples | mutation,
  data = barplot.data,
  main = 'Panel layout',
  xlab.lab = 'Samples',
  ylab.lab = 'Mutations',
  ylims = c(0,30),
  yat = seq(0,30,5),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  description = 'Barplot created by BoutrosLab.plotting.general',
  resolution = 200
);

# Panel organization 2
create.barplot(
  filename = tempfile(pattern = 'Barplot_Panel_Layout_2', fileext = '.tiff'),
  formula = values ~ samples | mutation,

```

```
data = barplot.data,
main = 'Panel layout',
xlab.lab = 'Samples',
ylab.lab = 'Mutations',
ylimits = c(0,30),
yat = seq(0,30,5),
xaxis.cex = 1,
yaxis.cex = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
xaxis.fontface = 1,
yaxis.fontface = 1,
# Adjusting the panel layout
layout = c(1,2),
y.spacing = 1,
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Covariates
# Note: Covariates can also be created using the create.multiplot function

# set covariate colour schemes
covariate.colours.sex <- as.character(barplot.data$sex);
covariate.colours.sex[covariate.colours.sex == 'male'] <- 'dodgerblue';
covariate.colours.sex[covariate.colours.sex == 'female'] <- 'pink';

covariate.colours.stage <- as.character(barplot.data$stage);
covariate.colours.stage[covariate.colours.stage == 'I'] <- 'plum1';
covariate.colours.stage[covariate.colours.stage == 'II'] <- 'orchid1';
covariate.colours.stage[covariate.colours.stage == 'III'] <- 'orchid3';
covariate.colours.stage[covariate.colours.stage == 'IV'] <- 'orchid4';

covariate.colours.msi <- as.character(barplot.data$msi);
covariate.colours.msi[covariate.colours.msi == 'MSS'] <- 'chartreuse4';
covariate.colours.msi[covariate.colours.msi == 'MSI-High'] <- 'chartreuse2';

# create object to draw covariates
covariates.object <- list(
  rect = list(
    col = 'white',
    fill = covariate.colours.sex,
    lwd = 1.5
  ),
  rect = list(
    col = 'white',
    fill = covariate.colours.stage,
    lwd = 1.5
  ),
  rect = list(
    col = 'white',
    fill = covariate.colours.msi,
    lwd = 1.5
  )
);
```

```

        )
);

# see BoutrosLab.plotting.general::covariates.grob() for more information
covariate.object.grob <- covariates.grob(
  covariates = covariates.object,
  ord = c(1:15),
  side = 'top',
  size = 0.8
);

# Create legend to explain covariates
covariates.legends <- list(
  legend = list(
    colours = c('dodgerblue','pink'),
    labels = c('male','female'),
    title = 'Sex',
    border = 'white'
  ),
  legend = list(
    colours = c('plum1', 'orchid1', 'orchid3', 'orchid4'),
    labels = c('I','II','III','IV'),
    title = 'Stage',
    border = 'white'
  ),
  legend = list(
    colours = c('chartreuse4','chartreuse2'),
    labels = c('MSS','MSI-High'),
    title = 'MSI',
    border = 'white'
  )
);

# see BoutrosLab.plotting.general::legend.grob() for more information
covariate.legend.grob <- legend.grob(
  legends = covariates.legends,
  title.just = 'left'
);

create.barplot(
  filename = tempfile(pattern = 'Barplot_Covariates', fileext = '.tiff'),
  formula = values ~ samples,
  data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
  main = 'Covariates',
  ylab.lab = 'Mutations',
  ylims = c(0,30),
  yat = seq(0,30,5),
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  yaxis.fontface = 1,
  # removing x-axis formatting to give space to covariates
  xaxis.tck = 0,
)

```

```
    xaxis.lab = rep('',15),
    xaxis.cex = 0,
    # covariates
    legend = list(
        bottom = list(fun = covariate.object.grob),
        right = list(fun = covariate.legend.grob)
    ),
    key = list(
        x = 1,
        y = -0.028,
        text = list(
            lab = c('Sex','Stage','MSI')
        ),
        padding.text = 1
    ),
    bottom.padding = 4,
    description = 'Barplot created by BoutrosLab.plotting.general',
    resolution = 200
);

create.barplot(
    filename = tempfile(pattern = 'Barplot_Auto_legend', fileext = '.tiff'),
    formula = values ~ samples,
    data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
    main = 'Covariates',
    ylab.lab = 'Mutations',
    ylims = c(0,30),
    yat = seq(0,30,5),
    yaxis.cex = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    yaxis.fontface = 1,
    # removing x-axis formatting to give space to covariates
    xaxis.tck = 0,
    xaxis.lab = rep('',15),
    xaxis.cex = 0,
    # covariates
    legend = list(
        inside = list(fun = covariate.legend.grob)
    ),
    bottom.padding = 4,
    inside.legend.auto = TRUE,
    description = 'Barplot created by BoutrosLab.plotting.general',
    resolution = 200
);

# Horizontal orientation
create.barplot(
    filename = tempfile(pattern = 'Barplot_Horizontal', fileext = '.tiff'),
    # switch formula order
    formula = samples ~ values,
    data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
    main = 'Plot horizontally'
```

```

# Adjusting the panel layout
plot.horizontal = TRUE,
# covariates
legend = list(
  inside = list(fun = covariate.legend.grob)
),
inside.legend.auto = TRUE,
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Change bar thickness and add text labels
create.barplot(
  filename = tempfile(pattern = 'Barplot_Text_Labels', fileext = '.tiff'),
  # switch formula order
  formula = samples ~ values,
  data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
  main = 'Text labels and thin bars',
  # Adjusting the panel layout
  plot.horizontal = TRUE,
  box.ratio = 0.6,
  add.text = TRUE,
  text.x = 27.75,
  text.y = 1:15,
  text.labels = barplot.data[barplot.data$mutation == 'nonsynonymous','values'],
  text.cex = 0.8,
  text.fontface = 'italic',
  description = 'Barplot created by BoutrosLab.plotting.general',
  resolution = 200
);

# Error bars
error.data <- data.frame(
  genes = rownames(microarray)[1:15],
  values = apply(microarray[1:15,1:58], 1, mean),
  error = apply(microarray[1:15,1:58], 1, sd)
);

create.barplot(
  filename = tempfile(pattern = 'Barplot_Error_Bars', fileext = '.tiff'),
  # needs sequential x-axis
  formula = values ~ 1:15,
  data = error.data,
  y.error.up = error.data$error,
  xaxis.lab = error.data$genes,
  main = 'Error bars',
  xlab.lab = 'Gene',
  ylab.lab = 'Change in Expression',
  ylims = c(0,14),
  yat = seq(0,14,2),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.rot = 45,
)

```

```
xlab.cex = 1.5,
ylab.cex = 1.5,
xaxis.fontface = 1,
yaxis.fontface = 1,
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 100
);

create.barplot(
  filename = tempfile(pattern = 'Barplot_Error_Bars_Horizontal', fileext = '.tiff'),
  # needs sequential x-axis
  formula = values ~ 1:15,
  data = error.data,
  y.error.up = error.data$error,
  yaxis.lab = error.data$genes,
  plot.horizontal = TRUE,
  main = 'Error bars',
  xlab.lab = 'Gene',
  ylab.lab = 'Change in Expression',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.rot = 45,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  description = 'Barplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Grid lines
create.barplot(
  filename = tempfile(pattern = 'Barplot_Gridlines', fileext = '.tiff'),
  formula = values ~ samples,
  data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
  main = 'Gridlines',
  xlab.lab = 'Samples',
  ylab.lab = 'Nonsynonymous SNVs',
  ylims = c(0,30),
  yat = seq(0,30,5),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  # Grid lines
  add.grid = TRUE,
  xgrid.at = seq(0,15,2),
  col = sex.colours,
  legend = list(
    inside = list(
```

```

        fun = draw.key,
        args = list(
            key = list(
                points = list(
                    col = 'black',
                    pch = 22,
                    cex = 3,
                    fill = c('dodgerblue', 'pink')
                ),
                text = list(
                    lab = c('Male', 'Female')
                ),
                padding.text = 5,
                cex = 1
            )
        ),
        # Positioning legend on plot
        x = 0.75,
        y = 0.95
    )
),
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Grid lines 2
create.barplot(
    filename = tempfile(pattern = 'Barplot_Gridlines_GreyBG', fileext = '.tiff'),
    formula = values ~ samples,
    data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
    main = 'Gridlines & grey background',
    xlab.lab = 'Samples',
    ylab.lab = 'Nonsynonymous SNVs',
    ylims = c(0,30),
    yat = seq(0,30,5),
    xaxis.cex = 1,
    yaxis.cex = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    # Grid lines
    background.col = 'grey85',
    add.grid = TRUE,
    xgrid.at = seq(0,15,2),
    col = sex.colours,
    legend = list(
        inside = list(
            fun = draw.key,
            args = list(
                key = list(
                    points = list(
                        col = 'black',

```

```
    pch = 22,
    cex = 3,
    fill = c('dodgerblue', 'pink')
  ),
  text = list(
    lab = c('Male', 'Female')
  ),
  padding.text = 5,
  cex = 1
)
),
# Positioning legend on plot
x = 0.75,
y = 0.95
)
),
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Labels
create.barplot(
  filename = tempfile(pattern = 'Barplot_Labels', fileext = '.tiff'),
  formula = values ~ samples,
  data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
  main = 'Labels',
  xlab.lab = 'Samples',
  ylab.lab = 'Nonsynonymous SNVs',
  ylimits = c(0,30),
  yat = seq(0,30,5),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  # Labels
  text.above.bars = list(
    labels = c('*', '27', '15', '*'),
    padding = 0.75,
    bar.locations = c(1, 3, 12, 14),
    rotation = 0
  ),
  col = sex.colours,
  legend = list(
    inside = list(
      fun = draw.key,
      args = list(
        key = list(
          points = list(
            col = 'black',
            pch = 22,
            cex = 3,
```

```

        fill = c('dodgerblue', 'pink')
    ),
    text = list(
        lab = c('Male','Female')
    ),
    padding.text = 5,
    cex = 1
)
),
# Positioning legend on plot
x = 0.75,
y = 0.95
)
),
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 200
);

# lines
create.barplot(
    filename = tempfile(pattern = 'Barplot_Lines', fileext = '.tiff'),
    formula = values ~ samples,
    data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
    main = 'Lines',
    xlab.lab = 'Samples',
    ylab.lab = 'Nonsynonymous SNVs',
    ylims = c(0,30),
    yat = seq(0,30,5),
    xaxis.cex = 1,
    yaxis.cex = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    # Lines
    sample.order = 'increasing',
    line.func = function(x) {0.1*x**2},
    line.from = 0,
    line.to = 16,
    line.col = 'darkgrey',
    abline.h = 10,
    abline.col = 'red',
    col = sex.colours,
    legend = list(
        inside = list(
            fun = draw.key,
            args = list(
                key = list(
                    points = list(
                        col = 'black',
                        pch = 22,
                        cex = 3,
                        fill = c('dodgerblue', 'pink')
                    )
                )
            )
        )
    )
);

```

```
        ),
        text = list(
            lab = c('Male','Female')
        ),
        padding.text = 5,
        cex = 1
    )
),
# Positioning legend on plot
x = 0.75,
y = 0.95
)
),
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Background rectangle
create.barplot(
    filename = tempfile(pattern = 'Barplot_Bg_Rectangle', fileext = '.tiff'),
    formula = values ~ samples,
    data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
    main = 'Background rectangle',
    xlab.lab = 'Samples',
    ylab.lab = 'Nonsynonymous SNVs',
    ylims = c(0,30),
    yat = seq(0,30,5),
    xaxis.cex = 1,
    yaxis.cex = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    sample.order = 'increasing',
    # Background rectangle
    add.rectangle = TRUE,
    xleft.rectangle = seq(0.5, 14.5, 2),
    ybottom.rectangle = 0,
    xright.rectangle = seq(1.5, 15.5, 2),
    ytop.rectangle = 30,
    col.rectangle = 'lightgrey',
    col = sex.colours,
    legend = list(
        inside = list(
            fun = draw.key,
            args = list(
                key = list(
                    points = list(
                        col = 'black',
                        pch = 22,
                        cex = 3,
                        fill = c('dodgerblue', 'pink')
                    ),
                    text = list(
                        lab = c('Male','Female')
                    ),
                    padding.text = 5,
                    cex = 1
                )
            )
        )
    )
);
```

```

        text = list(
            lab = c('Male','Female')
            ),
            padding.text = 5,
            cex = 1
            )
        ),
        # Positioning legend on plot
        x = 0.75,
        y = 0.95
    )
),
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Raster
create.barplot(
    filename = tempfile(pattern = 'Barplot_with_raster', fileext = '.tiff'),
    formula = values ~ samples,
    data = barplot.data[barplot.data$mutation == 'nonsynonymous',],
    main = 'Raster fill',
    xlab.lab = 'Samples',
    ylab.lab = 'Nonsynonymous SNVs',
    ylims = c(0,30),
    yat = seq(0,30,5),
    xaxis.cex = 1,
    yaxis.cex = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    # filling bars with raster
    raster = 1:10/10,
    raster.just = 'bottom',
    description = 'Description of image here',
    resolution = 200
);

# Nature format
create.barplot(
    filename = tempfile(pattern = 'Barplot_Nature_style', fileext = '.tiff'),
    formula = x ~ y,
    data = simple.data,
    yat = seq(0,16,2),
    main = 'Nature style',

    # set style to Nature
    style = 'Nature',

    # demonstrating how to italicize character variables
    ylab.lab = expression(paste('italicized ', italic('a'))),

```

```
# demonstrating how to create en-dashes
xlab.lab = expression(paste('en dashes: 1', '\u2013', '10'^^'\u2013', ''^3)),

resolution = 200
);

# Left Justified Example
create.barplot(
  filename = tempfile(pattern = 'Barplot_TwoTopLabelsLeftJustified', fileext = '.tiff'),
  formula = x ~ y,
  data = simple.data,
  yat = seq(0,16,2),
  ylab.label = NULL,
  # set top label details
  xlab.top.label = 'Sample Label',
  xlab.top.cex = 1.5,
  xlab.top.x = -0.125,
  xlab.top.y = 0.5,
  xlab.top.just = 'left',
  # set main label details
  main = 'Sample Main',
  main.just = 'left',
  main.x = 0,
  main.y = 0.6,
  top.padding = 1,
  resolution = 200
);
```

create.boxplot *Make a boxplot*

Description

Takes a data.frame and creates a boxplot

Usage

```
create.boxplot(
  formula,
  data,
  filename = NULL,
  main = NULL,
  main.just = 'center',
  main.x = 0.5,
  main.y = 0.5,
  main.cex = 3,
  add.stripplot = FALSE,
  jitter.factor = 1,
```

```
jitter.amount = NULL,  
points.pch = 19,  
points.col = 'darkgrey',  
points.cex = 0.5,  
points.alpha = 1,  
abline.h = NULL,  
abline.v = NULL,  
abline.lty = NULL,  
abline.lwd = NULL,  
abline.col = 'black',  
add.rectangle = FALSE,  
xleft.rectangle = NULL,  
ybottom.rectangle = NULL,  
xright.rectangle = NULL,  
ytop.rectangle = NULL,  
col.rectangle = 'transparent',  
alpha.rectangle = 1,  
box.ratio = 1,  
col = 'transparent',  
border.col = 'black',  
symbol.cex = 0.8,  
lwd = 1,  
outliers = TRUE,  
sample.order = 'none',  
order.by = 'median',  
xlab.label = tail(sub('`', '', formula[-2]), 1),  
ylab.label = tail(sub('`', '', formula[-3]), 1),  
xlab.cex = 2,  
ylab.cex = 2,  
xlab.col = 'black',  
ylab.col = 'black',  
xlab.top.label = NULL,  
xlab.top.cex = 2,  
xlab.top.col = 'black',  
xlab.top.just = 'center',  
xlab.top.x = 0.5,  
xlab.top.y = 0,  
xlims = NULL,  
ylims = NULL,  
xat = TRUE,  
yat = TRUE,  
xaxis.lab = TRUE,  
yaxis.lab = TRUE,  
xaxis.cex = 1.5,  
yaxis.cex = 1.5,  
xaxis.col = 'black',  
yaxis.col = 'black',  
xaxis.fontface = 'bold',
```

```
yaxis.fontface = 'bold',
xaxis.rot = 0,
yaxis.rot = 0,
xaxis.tck = c(1,0),
yaxis.tck = 1,
layout = NULL,
as.table = FALSE,
x.spacing = 0,
y.spacing = 0,
x.relation = 'same',
y.relation = 'same',
top.padding = 0.5,
bottom.padding = 2,
right.padding = 1,
left.padding = 2,
ylab.axis.padding = 0,
add.text = FALSE,
text.labels = NULL,
text.x = NULL,
text.y = NULL,
text.anchor = 'centre',
text.col = 'black',
text.cex = 1,
text.fontface = 'bold',
key = NULL,
legend = NULL,
strip.col = 'white',
strip.cex = 1,
strip.fontface = 'bold',
line.func = NULL,
line.from = 0,
line.to = 0,
line.col = 'transparent',
line.infront = TRUE,
height = 6,
width = 6,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
description = 'Created with BoutrosLab.plotting.general',
style = 'BoutrosLab',
preload.default = 'custom',
use.legacy.settings = FALSE,
disable.factor.sorting = FALSE
);
```

Arguments

formula	The formula used to extract the x & y components from the data-frame
---------	--

data	The data-frame to plot
filename	Filename for tiff output, or if NULL returns the trellis object itself
main	The main title for the plot (space is reclaimed if NULL)
main.just	The justification of the main title for the plot, default is centered
main.x	The x location of the main title, default is 0.5
main.y	The y location of the main title, default is 0.5
main.cex	Size of text for main plot title, defaults to 3
add.stripplot	logical whether to plot all points, defaults to FALSE
jitter.factor	Numeric value to apply to jitter, default is 1
jitter.amount	Numeric; amount of noise to add, default is NULL
points.pch	pch value to use for stripplot
points.col	colour to use for stripplot
points.cex	cex value to use for stripplot
points.alpha	alpha value to use for stripplot
abline.h	Specify the horizontal superimpose line
abline.v	Specify the vertical superimpose line
abline.lty	Specify the superimpose line type
abline.lwd	Specify the superimpose line width
abline.col	Specify the superimpose line colour (defaults to black)
add.rectangle	Allow a rectangle to be drawn, default is FALSE
xleft.rectangle	Specifies the left x coordinate of the rectangle to be drawn
ybottom.rectangle	Specifies the bottom y coordinate of the rectangle to be drawn
xright.rectangle	Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle	Specifies the top y coordinate of the rectangle to be drawn
col.rectangle	Specifies the colour of the rectangle to be drawn
alpha.rectangle	Specifies the colour bias of the rectangle to be drawn
box.ratio	ability to change the box width, defaults to 1
col	The colour to fill the interior of the boxplot, defaults to white
border.col	Colour of the boxplot, defaults to black
symbol.cex	Size of the boxplot outlier-symbol
lwd	Line width, defaults to 1
outliers	logical whether to plot outliers, defaults to TRUE
sample.order	String specifying how samples should be ordered. Either none, increasing, or decreasing.

order.by	A string specifying what the sample order should be ordered by, either max, min, median or mean
xlab.label	The label for the x-axis
ylab.label	The label for the y-axis
xlab.cex	Size of x-axis label, defaults to 3
ylab.cex	Size of y-axis label, defaults to 3
xlab.col	Colour of the x-axis label, defaults to “black”
ylab.col	Colour of the y-axis label, defaults to “black”
xlab.top.label	The label for the top x-axis
xlab.top.cex	Size of top x-axis label
xlab.top.col	Colour of the top x-axis label
xlab.top.just	Justification of the top x-axis label, defaults to centered
xlab.top.x	The x location of the top x-axis label
xlab.top.y	The y location of the top y-axis label
xlimits	Two-element vector giving the x-axis limits
ylimits	Two-element vector giving the y-axis limits
xat	Vector listing where the x-axis labels should be drawn
yat	Vector listing where the y-axis labels should be drawn
xaxis.lab	Vector listing x-axis tick labels, defaults to automatic
yaxis.lab	Vector listing y-axis tick labels, defaults to automatic
xaxis.cex	Size of x-axis tick labels, defaults to 2
yaxis.cex	Size of y-axis tick labels, defaults to 2
xaxis.col	Colour of the x-axis tick labels, defaults to “black”
yaxis.col	Colour of the y-axis tick labels, defaults to “black”
xaxis.fontface	Fontface for the x-axis scales
yaxis.fontface	Fontface for the y-axis scales
xaxis.rot	Rotation of x-axis tick labels; defaults to 0
yaxis.rot	Rotation of y-axis tick labels; defaults to 0
xaxis.tck	Specifies the length of the tick marks for x-axis, defaults to 1 (bottom) and 0 (top)
yaxis.tck	Specifies the length of the tick marks for y-axis, defaults to 1
layout	A vector specifying the number of columns, rows (e.g., c(2,1)). Default is NULL; see lattice::xyplot for more details.
as.table	Specifies panel drawing order, default is FALSE which draws panels from bottom left corner, moving right then up. Set to TRUE to draw from top left corner, moving right then down
x.spacing	A number specifying the distance between panels along the x-axis, defaults to 0
y.spacing	A number specifying the distance between panels along the y-axis, defaults to 0

x.relation	Allows x-axis scales to vary if set to “free”, defaults to “same”
y.relation	Allows y-axis scales to vary if set to “free”, defaults to “same”
top.padding	A number specifying the distance to the top margin, defaults to 0.5
bottom.padding	A number specifying the distance to the bottom margin, defaults to 2
right.padding	A number specifying the distance to the right margin, defaults to 1
left.padding	A number specifying the distance to the left margin, defaults to 2
ylab.axis.padding	A number specifying the distance of y-axis label to the y-axis, defaults to 0,
add.text	Allow additional text to be drawn, default is FALSE
text.labels	Labels for additional text
text.x	The x co-ordinates where additional text should be placed
text.y	The y co-ordinates where additional text should be placed
text.anchor	Part of text that should be anchored to x/y coordinates. Defaults to ‘centre’. Use ‘left’ or ‘right’ to left or right-align text.
text.col	The colour of additional text
text.cex	The size of additional text
text.fontface	The fontface for additional text
key	Add a key to the plot. See xyplot.
legend	Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See xyplot.
strip.col	Strip background colour, defaults to “white”
strip.cex	Strip title character expansion
strip.fontface	Strip title fontface, defaults to bold
line.func	Function for the line that should be drawn on top of plot
line.from	The starting point of the line on the plot
line.to	The ending point of the line on the plot
line.col	Colour of the line on the plot
line.infront	Should the line appear in front of the plot or not
height	Figure height, defaults to 6 inches
width	Figure width, defaults to 6 inches
size.units	Figure units, defaults to inches
resolution	Figure resolution in dpi, defaults to 1600
enable.warnings	Print warnings if set to TRUE, defaults to FALSE
description	Description of image/plot; default NULL.
style	defaults to “BoutrosLab”, also accepts “Nature”, which changes parameters according to Nature formatting requirements
preload.default	ability to set multiple sets of diffrent defaults depending on publication needs
use.legacy.settings	boolean to set wheter or not to use legacy mode settings (font)
disable.factor.sorting	Disable barplot auto sorting factors alphabetically/numerically

Value

If `filename` is `NULL` then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of `create.histogram` is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```
Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics
```

Author(s)

Maud H.W. Starmans

See Also

[bwplot](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(12345);

simple.data <- data.frame(
  x = rnorm(1000),
  y = rep('A',1000)
);

create.boxplot(
  filename = tempfile(pattern = 'Boxplot_Simple', fileext = '.tiff'),
  formula = y ~ x,
  data = simple.data,
  main = 'Simple',
  description = 'Boxplot created by BoutrosLab.plotting.general',
  resolution = 50
);

# add stripplot behind boxplot
create.boxplot(
  filename = tempfile(pattern = 'Boxplot_with_Stripplot', fileext = '.tiff'),
  formula = y ~ x,
  data = simple.data,
  main = 'With Stripplot',
  add.stripplot = TRUE,
```

```

description = 'Boxplot created by BoutrosLab.plotting.general',
resolution = 50
);

# format data
reformatted.data <- data.frame(
  x = as.vector(t(microarray[1:10,1:58])),
  y = as.factor(rep(rownames(microarray[1:10,1:58]),each = 58)),
  z = sample(1:10, 580, replace = TRUE)
);

# Minimal Input
create.boxplot(
  filename = tempfile(pattern = 'Boxplot_Minimal_Input', fileext = '.tiff'),
  formula = y ~ x,
  data = reformatted.data,
  main = 'Minimal input',
  description = 'Boxplot created by BoutrosLab.plotting.general',
  resolution = 50
);

# Minimal Input
create.boxplot(
  filename = tempfile(pattern = 'Boxplot_Disable_Factor_Sorting_Input', fileext = '.tiff'),
  formula = y ~ x,
  data = reformatted.data,
  main = 'No Factor Sorting',
  disable.factor.sorting = TRUE,
  description = 'Boxplot created by BoutrosLab.plotting.general',
  resolution = 50
);

# Axes and labels
create.boxplot(
  filename = tempfile(pattern = 'Boxplot_Axes_Labels', fileext = '.tiff'),
  formula = y ~ x,
  data = reformatted.data,
  main = 'Axes & labels',
  # Adjusting axes size
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  # Adding y-axis label
  ylab.label = 'Gene',
  # setting axes limits
  xlims = c(0,13),
  xat = seq(0,12,2),
  description = 'Boxplot created by BoutrosLab.plotting.general',
  resolution = 100
);

```

```
# Sorting
create.boxplot(
  filename = tempfile(pattern = 'Boxplot_Sorted', fileext = '.tiff'),
  formula = y ~ x,
  data = reformatted.data,
  main = 'Sorting',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  ylab.label = 'Gene',
  xlims = c(0,13),
  xat = seq(0,12,2),
  # Reordered by median
  sample.order = 'increasing',
  description = 'Boxplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Colour change
sex.colour <- as.character(patient$sex);
sex.colour[sex.colour == 'male'] <- 'dodgerblue';
sex.colour[sex.colour == 'female'] <- 'pink';

create.boxplot(
  filename = tempfile(pattern = 'Boxplot_Colour_Change', fileext = '.tiff'),
  formula = y ~ x,
  data = reformatted.data,
  main = 'Colour change',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  ylab.label = 'Gene',
  xlims = c(0,13),
  xat = seq(0,12,2),
  # Colour change
  col = sex.colour,
  description = 'Boxplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Legend
create.boxplot(
  filename = tempfile(pattern = 'Boxplot_Legend', fileext = '.tiff'),
  formula = y ~ x,
  data = reformatted.data,
  main = 'Legend',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  ylab.label = 'Gene',
```

```

xlims = c(0,13),
xat = seq(0,12,2),
col = sex.colour,
# legend
legend = list(
  inside = list(
    fun = draw.key,
    args = list(
      key = list(
        points = list(
          col = 'black',
          pch = 22,
          cex = 1.5,
          fill = c('dodgerblue','pink')
        ),
        text = list(
          lab = c('male','female')
        ),
        cex = 1
      )
    ),
    x = 0.03,
    y = 0.97,
    corner = c(0,1),
    draw = FALSE
  )
),
description = 'Boxplot created by BoutrosLab.plotting.general',
resolution = 100
);

# Orientation
create.boxplot(
  filename = tempfile(pattern = 'Boxplot_Orientation', fileext = '.tiff'),
  # switch the order
  formula = x ~ y,
  data = reformatted.data,
  main = 'Orientation',
  xaxis.cex = 1,
  yaxis.cex = 1,
  # adjust the axes
  ylims = c(0,13),
  yat = seq(0,12,2),
  # rotate the labels
  xaxis.rot = 90,
  xlab.label = 'Gene',
  xlab.cex = 1.5,
  col = sex.colour,
  # legend
  legend = list(
    inside = list(
      fun = draw.key,
      args = list(

```

```
key = list(
    points = list(
        col = 'black',
        pch = 22,
        cex = 1.5,
        fill = c('dodgerblue','pink')
    ),
    text = list(
        lab = c('male','female')
    ),
    cex = 1
)
),
x = 0.23,
y = 0.97,
corner = c(0,1),
draw = FALSE
)
),
description = 'Boxplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Background rectangle
create.boxplot(
    filename = tempfile(pattern = 'Boxplot_BG_Rect', fileext = '.tiff'),
    formula = y ~ x,
    data = reformatted.data,
    main = 'Bg rectangle',
    xaxis.cex = 1,
    yaxis.cex = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    ylab.label = 'Gene',
    xlims = c(0,13),
    xat = seq(0,12,2),
    # draw rectangle
    add.rectangle = TRUE,
    xleft.rectangle = 0,
    xright.rectangle = 13,
    ybottom.rectangle = seq(0.5, 8.5, 2),
    ytop.rectangle = seq(1.5, 9.5, 2),
    col.rectangle = 'grey',
    alpha.rectangle = 0.5,
    col = sex.colour,
    # legend
    legend = list(
        inside = list(
            fun = draw.key,
            args = list(
                key = list(
                    points = list(
                        col = 'black',
                        
```

```

    pch = 22,
    cex = 1.5,
    fill = c('dodgerblue','pink')
  ),
  text = list(
    lab = c('male','female')
  ),
  cex = 1
)
),
x = 0.03,
y = 0.97,
corner = c(0,1),
draw = FALSE
)
),
description = 'Boxplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Line
create.boxplot(
  filename = tempfile(pattern = 'Boxplot_Line', fileext = '.tiff'),
  formula = y ~ x,
  data = reformatted.data,
  main = 'Line',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  ylab.label = 'Gene',
  xlims = c(0,13),
  xat = seq(0,12,2),
  # draw line
  line.func = function(x){c(0.5, 10.5)},
  line.from = 11,
  line.to = 11,
  line.col = 'grey',
  description = 'Boxplot created by BoutrosLab.plotting.general',
  resolution = 200
);

# Panel Organization
create.boxplot(
  filename = tempfile(pattern = 'Boxplot_Panels_numeric_conditioning', fileext = '.tiff'),
  formula = ~ x | z,
  data = reformatted.data,
  main = 'Panels',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlims = c(0,13),
  xat = seq(0,12,2),
  # Setting up the layout

```

```
layout = c(2,5),
x.relation = 'free',
x.spacing = 1,
description = 'Boxplot created by BoutrosLab.plotting.general',
resolution = 200
);

create.boxplot(
  filename = tempfile(pattern = 'Boxplot_Panels_factor_conditioning', fileext = '.tiff'),
  formula = ~ x | y,
  data = reformatted.data,
  main = 'Panels',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlims = c(0,13),
  xat = seq(0,12,2),
  # Setting up the layout
  layout = c(2,5),
  x.relation = 'free',
  x.spacing = 1,
  description = 'Boxplot created by BoutrosLab.plotting.general',
  resolution = 200
);

# Nature format
create.boxplot(
  filename = tempfile(pattern = 'Boxplot_Nature_style', fileext = '.tiff'),
  formula = y ~ x,
  data = reformatted.data,
  main = 'Nature style',
  xaxis.cex = 1,
  yaxis.cex = 1,

  # set style to Nature
  style = 'Nature',

  # demonstrating how to italicize character variables
  ylab.lab = expression(paste('italicized ', italic('a'))),

  # demonstrating how to create en-dashes
  xlab.lab = expression(paste('en dashes: 1', '\u2013', '10' '^' '\u2013', ''^3)),
  resolution = 1200
);

# Sorting by mean and multiple filenames
create.boxplot(
  filename = c(
    tempfile(pattern = 'Boxplot_Sorted1', fileext = '.tiff'),
    tempfile(pattern = 'Boxplot_Sorted2', fileext = '.tiff')
  ),
  formula = y ~ x,
  data = reformatted.data,
  main = 'Sorting',
```

```

xaxis.cex = 1,
yaxis.cex = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
ylab.label = 'Gene',
xlims = c(0,13),
xat = seq(0,12,2),
# Reordered by median
sample.order = 'increasing',
order.by = 'mean',
description = 'Boxplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Adding text to plot
# Generate normally distributed variables with two different means
set.seed(779);
groupA <- rnorm(n = 100, mean = 10, sd = 2);
groupB <- rnorm(n = 134, mean = 10.5, sd = 2);

# Create data frame for plotting
to.plot <- data.frame(
y = rep(
c('1', '2'),
times = c(100, 134)
),
x = c(groupA, groupB)
);

# Get difference between means
diff.mean <- round(mean(groupB) - mean(groupA), 2);

# Plot and display difference
create.boxplot(
formula = x ~ y,
filename = tempfile(pattern = 'boxplot_with_text', fileext = '.tiff'),
data = to.plot,
add.stripplot = TRUE,
add.text = TRUE,
text.labels = bquote(mu[B] - mu[A] == .(diff.mean)),
text.x = 2.1,
text.y = 15.3,
text.col = 'black',
text.cex = 1.5,
text.fontface = 'bold',
ylimits = c(
min(to.plot$x) - abs(min(to.plot$x) * 0.1),
max(to.plot$x) + abs(max(to.plot$x) * 0.1)
),
resolution = 200
);

```

create.colourkey *Create Colourkey*

Description

A function for generating and placing a colour key. Good for use in multiplots when a smaller colour key is desired.

Usage

```
create.colourkey(  
  x,  
  scale.data = FALSE,  
  colour.scheme = c(),  
  total.colours = 99,  
  colour.centering.value = 0,  
  colour.alpha = 1,  
  fill.colour = 'darkgray',  
  at = NULL,  
  colourkey.labels.at = NULL,  
  colourkey.labels = colourkey.labels.at,  
  colourkey.labels.cex = 1,  
  placement = NULL  
)
```

Arguments

x	Either a data-frame or a matrix from which the heatmap was created
scale.data	Was the data for the heatmap scaled? Defaults to FALSE.
colour.scheme	Heatmap colouring. Accepts old-style themes, or a vector of either two or three colours that are gradiated to create the final palette.
total.colours	Total number of colours to plot.
colour.centering.value	The center of the colour-map.
colour.alpha	Bias to be added to colour selection (uses $x^{\text{colour.alpha}}$ in mapping).
fill.colour	The background fill (only exposed where missing values are present).
at	A vector specifying the breakpoints along the range of x.
colourkey.labels.at	A vector specifying the tick-positions on the colourkey.
colourkey.labels	A vector specifying tick-labels of the colourkey
colourkey.labels.cex	Size of colourkey labels. Defaults to 1
placement	Location and size of the colourkey.

Value

Returns a key in the format specified in the xyplot documentation.

Author(s)

Stephenie Prokopec

See Also

`xyplot`, `plotmath`

Examples

```
set.seed(1234567890);
x <- outer(-5:5, -5:5, '*') + matrix(nrow = 11, ncol = 11, data = runif(11 * 11));
colnames(x) <- paste('col', 1:11, sep = '-');
rownames(x) <- paste('row', 1:11, sep = '-');

y <- as.data.frame(x);
y$mean <- apply(x, 1, mean);

# example of a simple multiplot with colourkey
heatmap1 <- create.heatmap(
  x = t(x),
  filename = NULL,
  clustering.method = 'none',
  scale.data = FALSE,
  yaxis.lab = NA,
  print.colour.key = FALSE,
  colour.scheme = c('chartreuse3', 'white', 'blue'),
  at = seq(-25, 25, 0.01)
);

barplot1 <- create.barplot(
  1:nrow(y) ~ mean,
  y,
  plot.horizontal = TRUE
);

create.multiplot(
  plot.objects = list(heatmap1, barplot1),
  filename = tempfile(pattern = 'multiplot_with_colourkey', fileext = '.tiff'),
  plot.layout = c(2,1),
  panel.widths = c(2,1),
  yat = list(1:nrow(y), NULL),
  yaxis.labels = rownames(y),
  xlims = list(NULL, c(0,1)),
  xat = list(NULL, seq(0,1,0.5)),
  xaxis.labels = list(NULL, seq(0,1,0.5)),
  x.spacing = 0,
  print.new.legend = TRUE,
  legend = list(
```

```

    inside = list(
      fun = BoutrosLab.plotting.general::create.colourkey(
        x = x,
        colour.scheme = c('chartreuse3', 'white', 'blue'),
        at = seq(-25, 25, 0.01),
        colourkey.labels.at = c(-25, 0, 25),
        placement = viewport(just = 'left', x = 0.55, y = -0.55, width = 0.5)
      )
    ),
    bottom.padding = 4,
    width = 10,
    height = 8,
    resolution = 500
  );

```

`create.dendrogram` *Generate a dendrogram*

Description

Takes a matrix and creates a row-wise or column-wise dendrogram

Usage

```

create.dendrogram(
  x,
  clustering.method = 'diana',
  cluster.dimension = 'col',
  distance.method = 'correlation',
  cor.method = 'pearson',
  force.clustering = FALSE,
  same.as.matrix = FALSE
);

```

Arguments

<code>x</code>	A matrix that is used to create the dendrogram
<code>clustering.method</code>	Method used to cluster the records (can not be none). Accepts all agglomerative clustering methods available in hclust, plus “diana” (which is divisive).
<code>cluster.dimension</code>	Should clustering be performed on the rows or columns of <code>x</code> ?
<code>distance.method</code>	Method name of the distance measure to be used for clustering. Defaults to “correlation”. Other supported methods are same as in ?dist. Also supports “jaccard” which is useful for clustering categorical variables.
<code>cor.method</code>	The method used for calculating correlation. Defaults to “pearson”

```
force.clustering
    Binary to over-ride the control that prevents clustering of too-large matrices
same.as.matrix  Prevents the flipping of the matrix that the function normally does
```

Value

Returns an object of the dendrogram class corresponding to the row-wise or column-wise dendrogram for x

Author(s)

Lauren Chong

Examples

```
# create temp data
x <- outer(-5:5, -5:5, '*') + matrix(nrow = 11, ncol = 11, data = runif(11 * 11));
colnames(x) <- paste('col', 1:11, sep = '-');
rownames(x) <- paste('row', 1:11, sep = '-');

# example of generating a column-wise dendrogram using default values
create.dendrogram(
  x = x
);

# example of generating a column-wise dendrogram using different distance and clustering methods
create.dendrogram(
  x = x,
  clustering.method = 'median',
  cluster.dimension = 'cols',
  distance.method = 'euclidean'
);

# generate row-wise dendrogram using default distance and clustering methods
create.dendrogram(
  x = x,
  cluster.dimension = 'row'
);

# generate row-wise dendrogram using different distance and clustering methods
create.dendrogram(
  x = x,
  clustering.method = 'ward',
  cluster.dimension = 'rows',
  distance.method = 'manhattan'
);
```

create.densityplot *Make a density plot*

Description

Takes a list of vectors and creates a density-plot with each vector as a separate curve

Usage

```
create.densityplot(  
  x,  
  filename = NULL,  
  main = NULL,  
  main.just = 'center',  
  main.x = 0.5,  
  main.y = 0.5,  
  main.cex = 3,  
  xlab.label = NULL,  
  ylab.label = 'Density',  
  xlab.cex = 2,  
  ylab.cex = 2,  
  xlab.col = 'black',  
  ylab.col = 'black',  
  xlab.top.label = NULL,  
  xlab.top.cex = 2,  
  xlab.top.col = 'black',  
  xlab.top.just = 'center',  
  xlab.top.x = 0.5,  
  xlab.top.y = 0,  
  type = 'l',  
  lty = 'solid',  
  cex = 0.75,  
  pch = 19,  
  col = 'black',  
  lwd = 2,  
  bandwidth = 'nrd0',  
  bandwidth.adjust = 1,  
  xlims = NULL,  
  ylims = NULL,  
  xat = TRUE,  
  yat = TRUE,  
  xaxis.lab = NA,  
  yaxis.lab = NA,  
  xaxis.cex = 1.5,  
  yaxis.cex = 1.5,  
  xaxis.rot = 0,  
  yaxis.rot = 0,
```

```
xaxis.col = 'black',
yaxis.col = 'black',
xaxis.fontface = 'bold',
yaxis.fontface = 'bold',
xaxis.tck = 1,
yaxis.tck = 1,
xgrid.at = xat,
ygrid.at = yat,
key = list(text = list(lab = c(''))),
legend = NULL,
top.padding = 0.1,
bottom.padding = 0.7,
left.padding = 0.5,
right.padding = 0.1,
add.axes = FALSE,
abline.h = NULL,
abline.v = NULL,
abline.lty = NULL,
abline.lwd = NULL,
abline.col = 'black',
add.rectangle = FALSE,
xleft.rectangle = NULL,
ybottom.rectangle = NULL,
xright.rectangle = NULL,
ytop.rectangle = NULL,
col.rectangle = 'transparent',
alpha.rectangle = 1,
add.text = FALSE,
text.labels = NULL,
text.x = NULL,
text.y = NULL,
text.anchor = "centre",
text.col = "black",
text.cex = 1,
text.fontface = "bold",
height = 6,
width = 6,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
description = 'Created with BoutrosLab.plotting.general',
style = 'BoutrosLab',
preload.default = 'custom',
use.legacy.settings = FALSE,
inside.legend.auto = FALSE
);
```

Arguments

<code>x</code>	A list of vectors, each of which will be plotted as a separate curve in the final plot
<code>filename</code>	Filename for tiff output, or if NULL returns the trellis object itself
<code>main</code>	The main title for the plot (space is reclaimed if NULL)
<code>main.just</code>	The justification of the main title for the plot, default is centered
<code>main.x</code>	The x location of the main title, default is 0.5
<code>main.y</code>	The y location of the main title, default is 0.5
<code>main.cex</code>	Size of text for main plot title, defaults to 2
<code>xlab.label</code>	The label for the x-axis
<code>ylab.label</code>	The label for the y-axis, defaults to “Density”
<code>xlab.cex</code>	Size of x-axis label, defaults to 2
<code>ylab.cex</code>	Size of y-axis label, defaults to 2
<code>xlab.col</code>	Colour of the x-axis label, defaults to “black”
<code>ylab.col</code>	Colour of the y-axis label, defaults to “black”
<code>xlab.top.label</code>	The label for the top x-axis
<code>xlab.top.cex</code>	Size of top x-axis label
<code>xlab.top.col</code>	Colour of the top x-axis label
<code>xlab.top.just</code>	Justification of the top x-axis label, defaults to centered
<code>xlab.top.x</code>	The x location of the top x-axis label
<code>xlab.top.y</code>	The y location of the top y-axis label
<code>type</code>	Plot type
<code>lty</code>	Line type
<code>cex</code>	Character expansion for plotting symbol
<code>pch</code>	Plotting character
<code>col</code>	Point/line colour
<code>lwd</code>	Thickness of width of any best-fit lines
<code>bandwidth</code>	Smoothing bandwidth, or character string giving rule to choose bandwidth ('nrd0', 'nrd', 'ucv', 'bcv', 'sj', or 'sj-ste'). Passed to base R function density.
<code>bandwidth.adjust</code>	Adjustment parameter for the bandwidth (bandwidth used is bandwidth*bandwidth.adjust). Makes it easy to specify bandwidth as a proportion of the default.
<code>xlimits</code>	Two-element vector giving the x-axis limits, defaults to automatic
<code>ylimits</code>	Two-element vector giving the y-axis limits, defaults to automatic
<code>xat</code>	Vector listing where the x-axis labels should be drawn, defaults to automatic
<code>yat</code>	Vector listing where the y-axis labels should be drawn, defaults to automatic
<code>xaxis.lab</code>	Vector listing x-axis tick labels, defaults to automatic
<code>yaxis.lab</code>	Vector listing y-axis tick labels, defaults to automatic

<code>xaxis.cex</code>	Size of x-axis tick labels, defaults to 1
<code>yaxis.cex</code>	Size of x-axis tick labels, defaults to 1
<code>xaxis.rot</code>	Rotation of x-axis tick labels; defaults to 0
<code>yaxis.rot</code>	Rotation of y-axis tick labels; defaults to 0
<code>xaxis.col</code>	Colour of the x-axis tick labels, defaults to “black”
<code>yaxis.col</code>	Colour of the y-axis tick labels, defaults to “black”
<code>xaxis.fontface</code>	Fontface for the x-axis scales
<code>yaxis.fontface</code>	Fontface for the y-axis scales
<code>xaxis.tck</code>	Specifies the length of the tick marks for x-axis, defaults to 1
<code>yaxis.tck</code>	Specifies the length of the tick marks for y-axis, defaults to 1
<code>xgrid.at</code>	Vector listing where the x-axis grid lines should be drawn, defaults to <code>xat</code>
<code>ygrid.at</code>	Vector listing where the y-axis grid lines should be drawn, defaults to <code>yat</code>
<code>key</code>	A list giving the key (legend). The default suppresses drawing
<code>legend</code>	Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See <code>xyplot</code> .
<code>top.padding</code>	A number giving the top padding in multiples of the lattice default
<code>bottom.padding</code>	A number giving the bottom padding in multiples of the lattice default
<code>left.padding</code>	A number giving the left padding in multiples of the lattice default
<code>right.padding</code>	A number giving the right padding in multiples of the lattice default
<code>add.axes</code>	Allow axis lines to be turned on or off
<code>abline.h</code>	Specify the superimposed horizontal line(s)
<code>abline.v</code>	Specify the superimposed vertical line(s)
<code>abline.lty</code>	Specify the superimposed line type
<code>abline.lwd</code>	Specify the superimposed line width
<code>abline.col</code>	Specify the superimposed line colour (defaults to black)
<code>add.rectangle</code>	Allow a rectangle to be drawn, default is FALSE
<code>xleft.rectangle</code>	Specifies the left x coordinate of the rectangle to be drawn
<code>ybottom.rectangle</code>	Specifies the bottom y coordinate of the rectangle to be drawn
<code>xright.rectangle</code>	Specifies the right x coordinate of the rectangle to be drawn
<code>ytop.rectangle</code>	Specifies the top y coordinate of the rectangle to be drawn
<code>col.rectangle</code>	Specifies the colour to fill the rectangle’s area
<code>alpha.rectangle</code>	Specifies the colour bias of the rectangle to be drawn
<code>add.text</code>	Allow additional text to be drawn, default is FALSE
<code>text.labels</code>	Labels for additional text
<code>text.x</code>	The x co-ordinates where additional text should be placed

<code>text.y</code>	The y co-ordinates where additional text should be placed
<code>text.anchor</code>	Part of text that should be anchored to x/y coordinates. Defaults to 'centre'. Use 'left' or 'right' to left or right-align text.
<code>text.col</code>	The colour of additional text
<code>text.cex</code>	The size of additional text
<code>text.fontface</code>	The fontface for additional text
<code>height</code>	Figure height, defaults to 6 inches
<code>width</code>	Figure width, defaults to 6 inches
<code>size.units</code>	Figure units, defaults to inches
<code>resolution</code>	Figure resolution in dpi, defaults to 1600
<code>enable.warnings</code>	Print warnings if set to TRUE, defaults to FALSE
<code>description</code>	Short description of image/plot; default NULL.
<code>style</code>	defaults to "BoutrosLab", also accepts "Nature", which changes parameters according to Nature formatting requirements
<code>preload.default</code>	ability to set multiple sets of diffrent defaults depending on publication needs
<code>use.legacy.settings</code>	boolean to set wheter or not to use legacy mode settings (font)
<code>inside.legend.auto</code>	boolean specifying whether or not to use the automatic inside legend function

Value

If `filename` is NULL then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of `create.histogram` is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```
Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics
```

Author(s)

Paul C. Boutros

See Also

[xplot](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(12345);

simple.data <- data.frame(
  x = rnorm(1000),
  y = rnorm(1000, mean = 3, sd = 3)
);

create.densityplot(
  filename = tempfile(pattern = 'Densityplot_Simple', fileext = '.tiff'),
  x = simple.data,
  main = 'Simple',
  description = 'Barplot created by BoutrosLab.plotting.general'
);

# format data
format.data <- microarray[1:3,1:58];
format.data <- as.data.frame(t(format.data));

# Minimal Input
create.densityplot(
  filename = tempfile(pattern = 'Densityplot_Minimal_Input', fileext = '.tiff'),
  x = format.data,
  main = 'Minimal input',
  description = 'Barplot created by BoutrosLab.plotting.general',
  resolution = 50
);

# Line type
create.densityplot(
  filename = tempfile(pattern = 'Densityplot_Line_Type', fileext = '.tiff'),
  x = format.data,
  main = 'Line type',
  # Line type
  lty = c('solid','dashed','dotted'),
  description = 'Barplot created by BoutrosLab.plotting.general',
  resolution = 50
);

# Axes & Labels
create.densityplot(
  filename = tempfile(pattern = 'Densityplot_Axes_Labels', fileext = '.tiff'),
  x = format.data,
  main = 'Axes & labels',
  lty = c('solid','dashed','dotted'),
  # Axes & Labels
  ylims = c(-0.1, 2.5),
  ylab.cex = 1.5,
```

```
xat = seq(0, 13, 1),
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 50
);

# Colour change & Legend
create.densityplot(
    filename = tempfile(pattern = 'Densityplot_Colour_Legend', fileext = '.tiff'),
    x = format.data,
    main = 'Colour & legend',
    lty = c('solid','dashed','dotted'),
    ylims = c(-0.1, 2.5),
    ylab.cex = 1.5,
    # Colours
    col = default.colours(3),
    # Legend
    legend = list(
        inside = list(
            fun = draw.key,
            args = list(
                key = list(
                    points = list(
                        col = default.colours(3),
                        pch = 21,
                        cex = 1.5,
                        fill = default.colours(3)
                    ),
                    text = list(
                        lab = colnames(format.data)
                    ),
                    padding.text = c(0,5,0),
                    cex = 1
                )
            ),
            x = 0.65,
            y = 0.97,
            draw = FALSE
        )
    ),
    description = 'Barplot created by BoutrosLab.plotting.general',
    resolution = 50
);

# Correlation key
create.densityplot(
    filename = tempfile(pattern = 'Densityplot_Correlation_Key', fileext = '.tiff'),
    x = format.data[,1:2],
    main = 'Correlation key',
    lty = c('solid','dotted'),
    ylims = c(-0.1, 2.5),
    ylab.cex = 1.5,
    col = default.colours(2),
```

```

legend = list(
  inside = list(
    fun = draw.key,
    args = list(
      key = list(
        points = list(
          col = default.colours(2),
          pch = 21,
          cex = 1.5,
          fill = default.colours(2)
        ),
        text = list(
          lab = colnames(format.data)[1:2]
        ),
        padding.text = c(0,5,0),
        cex = 1
      )
    ),
    x = 0.65,
    y = 0.97,
    draw = FALSE
  ),
  # Correlation key accepts two vectors
  inside = list(
    fun = draw.key,
    args = list(
      key = get.corr.key(
        x = as.numeric(format.data[,1]),
        y = as.numeric(format.data[,2]),
        label.items = c('pearson', 'beta1'),
        alpha.background = 1,
        key.cex = 1.2
      )
    ),
    x = 0.65,
    y = 0.85,
    corner = c(0,1)
  )
),
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Gridlines
create.densityplot(
  filename = tempfile(pattern = 'Densityplot_Gridlines_1', fileext = '.tiff'),
  x = format.data,
  main = 'Gridlines',
  lty = c('solid', 'dashed', 'dotted'),
  ylims = c(-0.1, 2.5),
  ylab.cex = 1.5,
  col = default.colours(3),
  legend = list(

```

```
inside = list(
    fun = draw.key,
    args = list(
        key = list(
            points = list(
                col = default.colours(3),
                pch = 21,
                cex = 1.5,
                fill = default.colours(3)
            ),
            text = list(
                lab = colnames(format.data)
            ),
            padding.text = c(0,5,0),
            cex = 1
        )
    ),
    x = 0.65,
    y = 0.97,
    draw = FALSE
),
# Grid lines
type = c('l','g'),
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Gridlines
create.densityplot(
    filename = tempfile(pattern = 'Densityplot_Gridlines_2', fileext = '.tiff'),
    x = format.data,
    main = 'Gridlines',
    lty = c('solid','dashed','dotted'),
    ylims = c(-0.1, 2.5),
    ylab.cex = 1.5,
    col = default.colours(3),
    legend = list(
        inside = list(
            fun = draw.key,
            args = list(
                key = list(
                    points = list(
                        col = default.colours(3),
                        pch = 21,
                        cex = 1.5,
                        fill = default.colours(3)
                    ),
                    text = list(
                        lab = colnames(format.data)
                    ),
                    padding.text = c(0,5,0),
                    cex = 1
                )
            )
        )
    )
)
```

```

        )
    ),
x = 0.65,
y = 0.97,
draw = FALSE
)
),
# Grid lines
type = c('l','g'),
xgrid.at = seq(0,14,1),
ygrid.at = seq(0,2.5,0.25),
description = 'Barplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Nature style
create.densityplot(
  filename = tempfile(pattern = 'Densityplot_Nature_style', fileext = '.tiff'),
  x = format.data,
  main = 'Nature style',
  lty = c('solid','dashed','dotted'),
  ylims = c(-0.1, 2.5),
  ylab.cex = 1.5,
  xlab.cex = 1.5,
  col = default.colours(3),
  legend = list(
    inside = list(
      fun = draw.key,
      args = list(
        key = list(
          points = list(
            col = default.colours(3),
            pch = 21,
            cex = 1.5,
            fill = default.colours(3)
          ),
          text = list(
            lab = colnames(format.data)
          ),
          padding.text = c(0,5,0),
          cex = 1
        )
      ),
      x = 0.65,
      y = 0.97,
      draw = FALSE
    )
  ),
  # Grid lines
  style = 'Nature',
  # demonstrating how to italicize character variables
  ylab.lab = expression(paste('italicized ', italic('a'))),

```

```
# demonstrating how to create en-dashes
xlab.lab = expression(paste('en dashes: 1', '\u2013', '10' ^ '\u2013', ''^3)),
resolution = 200
);
```

create.dotmap*Make a dotmap with coloured background*

Description

Takes two data.frames and creates a dotmap with a coloured background. A dotmap is an ordered array of evenly-spaced dots whose size and colour can be user-specified to represent characteristics. For example, size gives the absolute magnitude of the correlation and colour gives the sign of the correlation. The coloured background may indicate p-values.

Usage

```
create.dotmap(
  x,
  bg.data = NULL,
  filename = NULL,
  main = NULL,
  main.just = "center",
  main.x = 0.5,
  main.y = 0.5,
  pch = 19,
  pch.border.col = 'black',
  add.grid = TRUE,
  xaxis.lab = colnames(x),
  yaxis.lab = rownames(x),
  xaxis.rot = 0,
  yaxis.rot = 0,
  main.cex = 3,
  xlab.cex = 2,
  ylab.cex = 2,
  xlab.label = NULL,
  ylab.label = NULL,
  xlab.col = 'black',
  ylab.col = 'black',
  xlab.top.label = NULL,
  xlab.top.cex = 2,
  xlab.top.col = 'black',
  xlab.top.just = "center",
  xlab.top.x = 0.5,
  xlab.top.y = 0,
```

```
xaxis.cex = 1.5,
yaxis.cex = 1.5,
xaxis.col = 'black',
yaxis.col = 'black',
xaxis.tck = 1,
yaxis.tck = 1,
axis.top = 1,
axis.bottom = 1,
axis.left = 1,
axis.right = 1,
top.padding = 0.1,
bottom.padding = 0.7,
right.padding = 0.1,
left.padding = 0.5,
key.ylab.padding = 0.1,
key = list(text = list(lab = c(''))),
legend = NULL,
col.lwd = 1.5,
row.lwd = 1.5,
spot.size.function = 'default',
spot.colour.function = 'default',
na.spot.size = 7,
na.pch = 4,
na.spot.size.colour = 'black',
grid.colour = NULL,
colour.scheme = 'white',
total.colours = 99,
at = NULL,
colour.centering.value = 0,
colourkey = FALSE,
colourkey.labels.at = NULL,
colourkey.labels = NULL,
colourkey.cex = 1,
colour.alpha = 1,
bg.alpha = 0.5,
fill.colour = 'white',
key.top = 0.1,
height = 6,
width = 6,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
col.colour = 'black',
row.colour = 'black',
description = 'Created with BoutrosLab.plotting.general',
add.rectangle = FALSE,
xleft.rectangle = NULL,
ybottom.rectangle = NULL,
```

```

xright.rectangle = NULL,
ytop.rectangle = NULL,
col.rectangle = 'transparent',
border.rectangle = NULL,
lwd.rectangle = NULL,
alpha.rectangle = 1,
xaxis.fontface = 'bold',
yaxis.fontface = 'bold',
dot.colour.scheme = NULL,
style = 'BoutrosLab',
preload.default = 'custom',
use.legacy.settings = FALSE,
remove.symmetric = FALSE,
lwd = 2
);

```

Arguments

x	An unstacked data.frame to plot the dotmap
bg.data	An unstacked data.frame to plot the background, of the same size as “x”. Column names specified here may be arbitrary: they are not used in the plot.
filename	Filename for tiff output, or if NULL returns the trellis object itself
pch	Plotting character
pch.border.col	Colour of the dot border if using pch = 21:25
add.grid	Should a grid of black-lines separating each column/row be added?
main	The main title for the plot (space is reclaimed if NULL)
main.just	The justification of the main title for the plot, default is centered
main.x	The x location of the main title, default is 0.5
main.y	The y location of the main title, default is 0.5
xlab.label	The label for the x-axis
ylab.label	The label for the y-axis
xlab.col	Colour of the x-axis label, defaults to “black”
ylab.col	Colour of the y-axis label, defaults to “black”
xlab.top.label	The label for the top x-axis
xlab.top.cex	Size of top x-axis label
xlab.top.col	Colour of the top x-axis label
xlab.top.just	Justification of the top x-axis label, defaults to centered
xlab.top.x	The x location of the top x-axis label
xlab.top.y	The y location of the top y-axis label
main.cex	Size of text for the main title, defaults to 2
xlab.cex	Size of x-axis label, defaults to 2
ylab.cex	Size of y-axis label, defaults to 2

xaxis.lab	Vector listing x-axis tick labels, defaults to colnames(x)
yaxis.lab	Vector listing y-axis tick labels, defaults to rownames(x)
xaxis.cex	Size of x-axis tick labels, defaults to 1.2
yaxis.cex	Size of y-axis tick labels, defaults to 1.5
xaxis.rot	Rotation of x-axis tick labels; defaults to 0
yaxis.rot	Rotation of y-axis tick labels; defaults to 0
xaxis.col	Colour of the x-axis tick labels, defaults to “black”
yaxis.col	Colour of the y-axis tick labels, defaults to “black”
xaxis.tck	Specifies the length of the tick marks for x-axis, defaults to 1
yaxis.tck	Specifies the length of the tick marks for y-axis, defaults to 1
axis.top	Specifies the padding on the top of the plot
axis.bottom	Specifies the padding on the bottom of the plot
axis.left	Specifies the padding on the left of the plot
axis.right	Specifies the padding on the right of the plot
top.padding	A number specifying the distance to the top margin, defaults to 0.1
bottom.padding	A number specifying the distance to the bottom margin, defaults to 0.7
right.padding	A number specifying the distance to the right margin, defaults to 0.1
left.padding	A number specifying the distance to the left margin, defaults to 0.5
key.ylab.padding	a number specifying distance between key and left label
key	A list giving the key (legend). The default suppresses drawing. If the key has a “space” component then extra space will be cleared on that side of the plot for the key
legend	Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See xyplot.
col.lwd	Thickness of column grid lines
row.lwd	Thickness of row grid lines
spot.size.function	The function that translates values in x into dotmap spot-size. The default is $0.1 + (2 * \text{abs}(x))$
spot.colour.function	The function that translates values in x into dotmap spot-colour. The default gives negative values blue, positive values red, and zero white. Parameter also accepts ‘columns’ and ‘rows’, which groups the dot colours by columns or rows (not both), respectively. For column/row grouping, there are 12 unique colours and these colours will start to repeat once there are more than 12 columns/rows.
na.spot.size	The size for plotting character for NA cells. Defaults to 7.
na.pch	The type of plotting character to represent NA cells. Defaults to 4 (‘X’).
na.spot.size.colour	Colour for plotting character representing NA cells. Defaults to black.

grid.colour	The colour for the grid lines. DEPRECATED
colour.scheme	Background colouring. Accepts a vector of colours. Vectors of two or three colours are gradiated to create the final palette. Defaults to “white”.
total.colours	Total number of colours to plot for the Background colours
at	A vector specifying the breakpoints along the range of bg; each interval specified by these breakpoints are assigned to a colour from the palette. Defaults to NULL, which corresponds to the range of bg being divided into total.colours equally spaced intervals. If bg has values outside of the range specified by “at”, those values are shown with colours corresponding to the extreme ends of the colour spectrum and a warning is given.
colour.centering.value	What should be the center of the background key
colourkey	Determines if the colour key should be added or not and sets up its formatting. Defaults to FALSE.
colourkey.labels.at	A vector specifying the tick-positions on the background colourkey
colourkey.labels	A vector specifying tick-labels of the background colourkey
colourkey.cex	Size of the background colourkey label text
colour.alpha	Bias to be added to background colour selection (uses $x^{\text{colour.alpha}}$ in mapping)
bg.alpha	The alpha value of the background colours, defaults to 0.5 so that the background does not compete with the dot colours for attention.
fill.colour	The background fill colour (only exposed where missing values are present). Defaults to white. NOTE: If you change this colour, you may want to set bg.alpha to 1 to avoid the fill colour showing through
key.top	A number specifying the distance at top of key, defaults to 0.1
height	Figure height in size.units
width	Figure width in size.units
size.units	Units of size for the figure
resolution	Figure resolution in dpi
enable.warnings	Print warnings if set to TRUE, defaults to FALSE
col.colour	The colour for the column grid lines, defaults to “black”. Can be a vector.
row.colour	The colour for the row grid lines, defaults to “black”. Can be a vector.
description	Description of image/plot; default NULL.
add.rectangle	Allow a rectangle to be drawn, default is FALSE
xleft.rectangle	Specifies the left x coordinate of the rectangle to be drawn
ybottom.rectangle	Specifies the bottom y coordinate of the rectangle to be drawn

```

xright.rectangle
    Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle
    Specifies the top y coordinate of the rectangle to be drawn
col.rectangle
    Specifies the colour to fill the rectangle's area
alpha.rectangle
    Specifies the colour bias of the rectangle to be drawn
border.rectangle
    Specifies the colour of the rectangle border
lwd.rectangle
    Specifies the thickness of the rectangle border
xaxis.fontface
    Fontface for the x-axis scales
yaxis.fontface
    Fontface for the y-axis scales
dot.colour.scheme
    Colour Scheme for the dots
style
    defaults to "BoutrosLab", also accepts "Nature", which changes parameters according to Nature formatting requirements
preload.default
    ability to set multiple sets of different defaults depending on publication needs
use.legacy.settings
    boolean to set whether or not to use legacy mode settings (font)
remove.symmetric
    boolean to set whether or not to remove the top left half of a symmetrically sized matrix
lwd
    line width for the axis lines

```

Details

It would be nice to have a library of suitable spot.size and spot.colour functions.

Earlier ideas included:

- (1) Changing the dot shape to triangles, so that upward or downward-pointing dots indicated direction
- (2) Adding arrows above or below dots to indicate direction of change. This idea was not used because it
- (3) Adding line(s) in the background set at different angles to show data. This was found to be not int

A future addition may be to add the option of outlining boxes instead of adding a background. This would b

Value

If filename is NULL then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of create histogram is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```
Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
  Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics
```

Author(s)

Paul C. Boutros

See Also

[xyplot](#), [levelplot](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(12345);
simple.data <- data.frame(
  'A' = runif(n = 15, min = -1, max = 1),
  'B' = runif(n = 15, min = -1, max = 1),
  'C' = runif(n = 15, min = -1, max = 1),
  'D' = runif(n = 15, min = -1, max = 1),
  'E' = runif(n = 15, min = -1, max = 1)
);

create.dotmap(
  filename = tempfile(pattern = 'Dotmap_Simple', fileext = '.tiff'),
  x = simple.data,
  main = 'Simple',
  description = 'Dotmap created by BoutrosLab.plotting.general',
  resolution = 100
);

# create a function to determine the spot sizes (default function works best with values < 1)
spot.size.med <- function(x) {abs(x)/3;}

# Minimal Input
create.dotmap(
  filename = tempfile(pattern = 'Dotmap_Minimal_Input', fileext = '.tiff'),
  x = microarray[1:5,1:5],
  main = 'Minimal input',
  spot.size.function = spot.size.med,
  xaxis.rot = 90,
  description = 'Dotmap created by BoutrosLab.plotting.general',
  resolution = 100
);

# Axes & Labels
spot.size.small <- function(x) {abs(x)/5;}

create.dotmap(
  filename = tempfile(pattern = 'Dotmap_Axes_Labels', fileext = '.tiff'),
  x = microarray[1:15,1:15],
```

```

main = 'Axes & labels',
spot.size.function = spot.size.small,
# Adjusting the font sizes and labels
xaxis.cex = 0.8,
yaxis.cex = 0.8,
xaxis.lab = 1:15,
xlab.label = 'Sample',
ylab.label = 'Gene',
xlab.cex = 1,
ylab.cex = 1,
description = 'Dotmap created by BoutrosLab.plotting.general',
resolution = 100
);

# Legend
key.sizes <- seq(2,12,2);

create.dotmap(
  filename = tempfile(pattern = 'Dotmap_Legend', fileext = '.tiff'),
  x = microarray[1:15,1:15],
  main = 'Legend',
  spot.size.function = spot.size.small,
  xaxis.cex = 0.8,
  yaxis.cex = 0.8,
  xaxis.lab = 1:15,
  xlab.label = 'Sample',
  ylab.label = 'Gene',
  xlab.cex = 1,
  ylab.cex = 1,
  # Legend for dots
  key = list(
    space = 'right',
    points = list(
      cex = spot.size.small(key.sizes),
      col = default.colours(2, palette.type = 'dotmap')[2],
      pch = 19
    ),
    text = list(
      lab = as.character(key.sizes),
      cex = 1,
      adj = 1
    ),
    padding.text = 3,
    background = 'white'
  ),
  key.top = 1,
  description = 'Dotmap created by BoutrosLab.plotting.general',
  resolution = 100
);

# Cluster by dots and add dendrogram
plot.data <- microarray[1:15,1:15];

```

```
# cluster data
clustered.data <- diana(plot.data);

# order data by cluster
plot.data <- plot.data[clustered.data$order,];

# create dendrogram
dendrogram.data <- create.dendrogram(x = plot.data, clustering.method = 'diana',
cluster.dimension = 'row');

dendrogram.grob <- latticeExtra::dendrogramGrob(
  x = dendrogram.data,
  side = 'right',
  type = 'rectangle'
);

# create dotmap
create.dotmap(
  x = plot.data,
  filename = tempfile(pattern = 'Dotmap_clustered_dendrogram', fileext = '.tiff'),
  main = 'Clustered & dendrogram',
  spot.size.function = spot.size.small,
  # Adjusting the font sizes and labels
  xaxis.cex = 0.8,
  yaxis.cex = 0.8,
  xaxis.lab = 1:15,
  xlab.label = 'Sample',
  ylab.label = 'Gene',
  xlab.cex = 1,
  ylab.cex = 1,
  legend = list(
    right = list(fun = dendrogram.grob)
  ),
  right.padding = 4,
  description = 'Dotmap created by BoutrosLab.plotting.general',
  resolution = 100
);

# Add background data
key.sizes <- c(-1, 1);

CNA.colour.function <- function(x){
  colours <- rep('white', length(x));
  colours[sign(x) == 1] <- 'Red';
  colours[sign(x) == -1] <- 'Blue';
  colours[x == 0] <- 'transparent';
  return(colours);
}

create.dotmap(
  filename = tempfile(pattern = 'Dotmap_with_Background', fileext = '.tiff'),
  # added new data for the dots
```

```

x = CNA[1:15,1:15],
# Moving the dot-data to be background data
bg.data = microarray[1:15,1:15],
colour.scheme = c('white','black'),
main = 'Background',
spot.size.function = 1,
spot.colour.function = CNA.colour.function,
xaxis.cex = 0.8,
yaxis.cex = 0.8,
xaxis.lab = 1:15,
xlab.label = 'Sample',
ylab.label = 'Gene',
xlab.cex = 1,
ylab.cex = 1,
key = list(
  space = 'right',
  points = list(
    cex = 1,
    col = CNA.colour.function(key.sizes),
    pch = 19
  ),
  text = list(
    lab = c('Gain', 'Loss'),
    cex = 1,
    adj = 1
  ),
  title = 'CNA',
  padding.text = 2,
  background = 'white'
),
# Adding colourkey for background data
colourkey = TRUE,
key.top = 1,
description = 'Dotmap created by BoutrosLab.plotting.general',
resolution = 200
);

# Discrete background colours
create.dotmap(
  filename = tempfile(pattern = 'Dotmap_Discrete_Background', fileext = '.tiff'),
  x = CNA[1:15,1:15],
  bg.data = microarray[1:15,1:15],
  main = 'Discrete background',
  spot.size.function = 1,
  spot.colour.function = CNA.colour.function,
  xaxis.cex = 0.8,
  yaxis.cex = 0.8,
  xaxis.lab = 1:15,
  xlab.label = 'Sample',
  ylab.label = 'Gene',
  xlab.cex = 1,
  ylab.cex = 1,
  key = list(

```

```
space = 'right',
points = list(
  cex = 1,
  col = CNA.colour.function(key.sizes),
  pch = 19
),
text = list(
  lab = c('Gain', 'Loss'),
  cex = 1,
  adj = 1
),
title = 'CNA',
padding.text = 2,
background = 'white'
),
colourkey = TRUE,
key.top = 1,
# Changing background colour scheme
colour.scheme = c('lightyellow','gold','darkorange', 'darkorange3'),
at = seq(0,12,3),
colourkey.labels = seq(0,12,3),
colourkey.labels.at = seq(0,12,3),
bg.alpha = 0.65,
description = 'Dotmap created by BoutrosLab.plotting.general'
);

# Dot outlines
border.colours <- function(x){
  colours <- rep('transparent', length(x));
  colours[x > 0] <- 'black';
  colours[x == 0] <- 'transparent';
  return(colours);
}

create.dotmap(
  filename = tempfile(pattern = 'Dotmap_Outlined_Dots', fileext = '.tiff'),
  x = CNA[1:15,1:15],
  bg.data = microarray[1:15,1:15],
  main = 'Dot outlines',
  spot.size.function = 1,
  spot.colour.function = CNA.colour.function,
  xaxis.cex = 0.8,
  yaxis.cex = 0.8,
  xaxis.lab = 1:15,
  xlab.label = 'Sample',
  ylab.label = 'Gene',
  xlab.cex = 1,
  ylab.cex = 1,
  key = list(
    space = 'right',
    points = list(
      cex = 1,
      col = 'black',
```

```

# Remember to also change the pch in the legend
pch = 21,
fill = CNA.colour.function(key.sizes)
),
text = list(
  lab = c('Gain', 'Loss'),
  cex = 1,
  adj = 1
),
title = 'CNA',
padding.text = 2,
background = 'white'
),
colourkey = TRUE,
key.top = 1,
colour.scheme = c('lightyellow','gold','darkorange', 'darkorange3'),
at = seq(0,12,3),
colourkey.labels = seq(0,12,3),
colourkey.labels.at = seq(0,12,3),
bg.alpha = 0.65,
# Change the plotting character to one which has an outline
pch = 21,
pch.border.col = border.colours(CNA[1:15,1:15]),
description = 'Dotmap created by BoutrosLab.plotting.general'
);

# Covariates & Legend
sex.colours <- patient$sex[1:15];
sex.colours[sex.colours == 'male'] <- 'dodgerblue';
sex.colours[sex.colours == 'female'] <- 'pink';

sample.covariate <- list(
  rect = list(
    col = 'black',
    fill = sex.colours,
    lwd = 1.5
  )
);

cov.grob <- covariates.grob(
  covariates = sample.covariate,
  ord = c(1:15),
  side = 'top'
);

sample.cov.legend <- list(
  legend = list(
    colours = c('dodgerblue', 'pink'),
    labels = c('male','female'),
    title = 'Sex'
  )
);

```

```
cov.legend <- legend.grob(
  legends = sample.cov.legend
);

create.dotmap(
  filename = tempfile(pattern = 'Dotmap_Covariates', fileext = '.tiff'),
  x = CNA[1:15,1:15],
  bg.data = microarray[1:15,1:15],
  main = 'Covariates',
  spot.size.function = 1,
  spot.colour.function = CNA.colour.function,
  xaxis.cex = 0.8,
  yaxis.cex = 0.8,
  xaxis.lab = 1:15,
  xlab.label = 'Sample',
  ylab.label = 'Gene',
  xlab.cex = 1,
  ylab.cex = 1,
  key = list(
    space = 'right',
    points = list(
      cex = 1,
      col = 'black',
      pch = 21,
      fill = CNA.colour.function(key.sizes)
    ),
    text = list(
      lab = c('Gain', 'Loss'),
      cex = 1,
      adj = 1
    ),
    title = 'CNA',
    padding.text = 2,
    background = 'white'
  ),
  colourkey = TRUE,
  key.top = 1,
  colour.scheme = c('lightyellow','gold','darkorange', 'darkorange3'),
  at = seq(0,12,3),
  colourkey.labels = seq(0,12,3),
  colourkey.labels.at = seq(0,12,3),
  bg.alpha = 0.65,
  pch = 21,
  pch.border.col = border.colours(CNA[1:15,1:15]),
  # Insert covariates & legend
  legend = list(
    top = list(
      fun = cov.grob
    ),
    left = list(
      fun = cov.legend
    )
  ),
)
```

```

description = 'Dotmap created by BoutrosLab.plotting.general'
);

# Side covariates with label
chr.cov.colours <- microarray$Chr;
chr.cov.colours[microarray$Chr == 1] <- default.colours(3, palette.type = 'chromosomes')[1];
chr.cov.colours[microarray$Chr == 2] <- default.colours(3, palette.type = 'chromosomes')[2];
chr.cov.colours[microarray$Chr == 3] <- default.colours(3, palette.type = 'chromosomes')[3];

chr.covariate <- list(
  rect = list(
    col = 'white',
    fill = chr.cov.colours,
    lwd = 1.5
  )
);

chr.cov.grob <- covariates.grob(
  covariates = chr.covariate,
  ord = c(1:15),
  side = 'right'
);

# create dot legend
dot.grob <- draw.key(
  list(
    space = 'right',
    points = list(
      cex = 1,
      col = 'black',
      pch = 21,
      fill = CNA.colour.function(key.sizes)
    ),
    text = list(
      lab = c('Gain', 'Loss'),
      cex = 1,
      adj = 1
    ),
    title = 'CNA',
    padding.text = 2,
    background = 'white'
  )
);

# Setting up the layout for the joint legends
right.layout <- grid.layout(
  nrow = 1,
  ncol = 2,
  width = unit(
    x = c(0,1),
    units = rep('lines',2)
  ),
  heights = unit(

```

```
    x = c(1,1),
    units = rep('npc', 1)
  )
);

right.grob <- frameGrob(layout = right.layout);

right.grob <- packGrob(
  frame = right.grob,
  grob = chr.cov.grob,
  row = 1,
  col = 1
);

right.grob <- packGrob(
  frame = right.grob,
  grob = dot.grob,
  row = 1,
  col = 2
);

temp <- create.dotmap(
  filename = tempfile(pattern = 'Dotmap_Covariates_Side', fileext = '.tiff'),
  x = CNA[1:15,1:15],
  bg.data = microarray[1:15,1:15],
  main = 'Both covariates',
  spot.size.function = 1,
  spot.colour.function = CNA.colour.function,
  xaxis.cex = 0.8,
  yaxis.cex = 0.8,
  xaxis.lab = 1:15,
  xlab.label = 'Sample',
  ylab.label = 'Gene',
  xlab.cex = 1,
  ylab.cex = 1,
  colourkey = TRUE,
  key.top = 1,
  colour.scheme = c('lightyellow','gold','darkorange', 'darkorange3'),
  at = seq(0,12,3),
  colourkey.labels = seq(0,12,3),
  colourkey.labels.at = seq(0,12,3),
  bg.alpha = 0.65,
  pch = 21,
  pch.border.col = border.colours(CNA[1:15,1:15]),
  # insert covariates & legend
  legend = list(
    right = list(
      fun = right.grob
    )
  ),
  description = 'Dotmap created by BoutrosLab.plotting.general'
);
```

```

# add side label to covariate
print(temp, position = c(0,0,1,1), more = TRUE);

draw.key(
  key = list(
    text = list(
      lab = 'Covariate Label',
      cex = 1,
      adj = 1
    )
  ),
  # position label on the plot
  vp = viewport(x = 0.86, y = 0.155, height = 1, width = 0.5, angle = 90),
  draw = TRUE
);

dev.off();

# Nature style
create.dotmap(
  filename = tempfile(pattern = 'Dotmap_Nature_style', fileext = '.tiff'),
  x = CNA[1:15,1:15],
  bg.data = microarray[1:15,1:15],
  main = 'Nature style',
  spot.size.function = 1,
  spot.colour.function = CNA.colour.function,
  xaxis.cex = 0.8,
  yaxis.cex = 0.8,
  xaxis.lab = 1:15,
  xlab.cex = 1,
  ylab.cex = 1,
  key = list(
    space = 'right',
    points = list(
      cex = 1,
      col = 'black',
      # Remember to also change the pch in the legend
      pch = 21,
      fill = CNA.colour.function(key.sizes)
    ),
    text = list(
      lab = c('Gain', 'Loss'),
      cex = 1,
      adj = 1
    ),
    title = 'CNA',
    padding.text = 2,
    background = 'white'
  ),
  colourkey = TRUE,
  key.top = 1,
  colour.scheme = c('lightyellow','gold','darkorange', 'darkorange3'),
  at = seq(0,12,3),

```

```
colourkey.labels = seq(0,12,3),
colourkey.labels.at = seq(0,12,3),
bg.alpha = 0.65,
# Change the plotting character to one which has an outline
pch = 21,
pch.border.col = border.colours(CNA[1:15,1:15]),

# set style to Nature
style = 'Nature',

# demonstrating how to italicize character variables
ylab.lab = expression(paste('italicized ', italic('a'))),

# demonstrating how to create en-dashes
xlab.lab = expression(paste('en dashes: 1', '\u2013', '10' '^' '\u2013', ''^3)),

resolution = 200
);

simple.data.sym <- data.frame(
  '1' = runif(n = 7, min = -1, max = 1),
  '2' = runif(n = 7, min = -1, max = 1),
  '3' = runif(n = 7, min = -1, max = 1),
  '4' = runif(n = 7, min = -1, max = 1),
  '5' = runif(n = 7, min = -1, max = 1),
  '6' = runif(n = 7, min = -1, max = 1),
  '7' = runif(n = 7, min = -1, max = 1)
);

create.dotmap(
  filename = tempfile(pattern = 'Dotmap_remove_symmetric', fileext = '.tiff'),
  x = simple.data.sym,
  main = 'Simple',
  xaxis.lab = seq(1,7,1),
  description = 'Dotmap created by BoutrosLab.plotting.general',
  remove.symmetric = TRUE,
  resolution = 200
);
```

create.gif

Make a gif

Description

Takes a function and several sets of parameters and makes a gif of their function calls

Usage

```
create.gif(
  exec.func,
  parameters,
  number.of.frames,
  delay = 40,
  filename)
```

Arguments

<code>exec.func</code>	The function that will be used to make the plots for the gif
<code>parameters</code>	Parameter list to be sent to the exec func at each frame
<code>number.of.frames</code>	Total number of frames to be made (must match number of parameter lists)
<code>delay</code>	Delay between each frame in the gif
<code>filename</code>	Name of output file (must end in .gif)

Author(s)

Jeffrey Green

See Also

[stripplot](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(223);

simple.data1 <- data.frame(
  x = sample(1:15, 10),
  y = LETTERS[1:10]
);

simple.data2 <- data.frame(
  x = sample(1:15, 10),
  y = LETTERS[1:10]
);

simple.data3 <- data.frame(
  x = sample(1:15, 10),
  y = LETTERS[1:10]
);

p = list(
  list(formula = x ~ y,data = simple.data1, yat = seq(0,16,2)),
  list(formula = x ~ y,data = simple.data2, yat = seq(0,16,2)),
  list(formula = x ~ y,data = simple.data3, yat = seq(0,16,2))
)
```

```
create.gif(  
  exec.func = create.barplot,  
  parameters = p,  
  number.of.frames = 3,  
  delay = 20,  
  filename = tempfile(pattern = 'test', fileext = '.gif')  
)
```

create.heatmap *Make a heatmap*

Description

Takes a data.frame and creates a heatmap

Usage

```
create.heatmap(  
  x,  
  filename = NULL,  
  clustering.method = 'diana',  
  cluster.dimensions = 'both',  
  rows.distance.method = 'correlation',  
  cols.distance.method = 'correlation',  
  cor.method = 'pearson',  
  row.dendrogram = list(),  
  col.dendrogram = list(),  
  plot.dendrograms = 'both',  
  force.clustering = FALSE,  
  criteria.list = TRUE,  
  covariates = list(),  
  covariates.grid.row = NULL,  
  covariates.grid.col = NULL,  
  covariates.grid.border = NULL,  
  covariates.row.lines = NULL,  
  covariates.col.lines = NULL,  
  covariates.reorder.grid.index = FALSE,  
  covariates.padding = 0.25,  
  covariates.top = list(),  
  covariates.top.grid.row = NULL,  
  covariates.top.grid.col = NULL,  
  covariates.top.grid.border = NULL,  
  covariates.top.row.lines = NULL,  
  covariates.top.col.lines = NULL,  
  covariates.top.reorder.grid.index = FALSE,  
  covariates.top.padding = 0.25,  
  covariate.legends = list(),
```

```
legend.cex = 1,  
legend.title.cex = 1,  
legend.title.just = 'centre',  
legend.title.fontface = 'bold',  
legend.border = NULL,  
legend.border.padding = 1,  
legend.layout = NULL,  
legend.between.col = 1,  
legend.between.row = 1,  
legend.side = 'left',  
main = list(label = ''),  
main.just = "center",  
main.x = 0.5,  
main.y = 0.5,  
main.cex = 3,  
right.size.add = 1,  
top.size.add = 1,  
right.dendrogram.size = 2.5,  
top.dendrogram.size = 2.5,  
scale.data = FALSE,  
yaxis.lab = NULL,  
xaxis.lab = NULL,  
xaxis.lab.top = NULL,  
xaxis.cex = 1.5,  
xaxis.top.cex = NULL,  
yaxis.cex = 1.5,  
xlab.cex = 2,  
ylab.cex = 2,  
xlab.top.label = NULL,  
    xlab.top.cex = 2,  
xlab.top.col = 'black',  
xlab.top.just = "center",  
xlab.top.x = 0.5,  
xlab.top.y = 0,  
xat = TRUE,  
xat.top = NULL,  
yat = TRUE,  
xaxis.tck = NULL,  
xaxis.top.tck = NULL,  
yaxis.tck = NULL,  
xaxis.col = 'black',  
yaxis.col = 'black',  
col.pos = NULL,  
row.pos = NULL,  
cell.text = '',  
text.fontface = 1,  
text.cex = 1,  
text.col = 'black',
```

```
text.position = NULL,
text.offset = 0,
text.use.grid.coordinates = TRUE,
colourkey.cex = 3.6,
xaxis.rot = 90,
xaxis.rot.top = 90,
yaxis.rot = 0,
xlab.label = '' ,
ylab.label = '',
xlab.col = 'black',
ylab.col = 'black',
axes.lwd = 2,
gridline.order = 'h',
grid.row = FALSE,
grid.col = FALSE,
force.grid.row = FALSE,
force.grid.col = FALSE,
grid.limit = 50,
row.lines = seq(0, ncol(x), 1) + 0.5,
col.lines = seq(0, nrow(x), 1) + 0.5,
colour.scheme = c(),
total.colours = 99,
colour.centering.value = 0,
colour.alpha = 1,
fill.colour = 'darkgray',
at = NULL,
print.colour.key = TRUE,
colourkey.labels.at = NULL,
colourkey.labels = NULL,
top.padding = 0.1,
bottom.padding = 0.5,
right.padding = 0.5,
left.padding = 0.5,
x.alternating = 1,
shrink = 1,
row.colour = 'black',
col.colour = 'black',
row.lwd = 1,
col.lwd = 1,
grid.colour = NULL,
grid.lwd = NULL,
width = 6,
height = 6,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
xaxis.covariates = NULL,
xaxis.covariates.y = 0,
```

```

yaxis.covariates = NULL,
yaxis.covariates.x = NULL,
description = 'Created with BoutrosLab.plotting.general',
xaxis.fontface = 'bold',
yaxis.fontface = 'bold',
symbols = list(borders = NULL,
squares = NULL,
circles = NULL),
same.as.matrix = FALSE,
input.colours = FALSE,
axis.xlab.padding = 0.1,
stratified.clusters.rows = NULL,
stratified.clusters.cols = NULL,
    inside.legend = NULL,
style = 'BoutrosLab',
preload.default = 'custom',
use.legacy.settings = FALSE
);

```

Arguments

- x** Either a data-frame or a matrix from which the heatmap is to created
- filename** Filename for tiff output, or if NULL returns the trellis object itself
- clustering.method** Method used to cluster the records – “none” gives unclustered data. Accepts all agglomerative clustering methods available in hclust, plus “diana” (which is divisive).
- cluster.dimensions** Should clustering be performed on rows, columns, or both – supersedes setting of plot.dendrograms
- rows.distance.method** Method name of the distance measure between rows to be used for clustering. Defaults to “correlation”. Other supported methods are same as in ?dist. Also supports “jaccard” which is useful for clustering categorical variables. “euclidean” is sometimes more robust when ties cause “Unclusterable matrix: some col-distances are null” errors. Note, rows and cols are switched due an internal transposition of the data.
- cols.distance.method** Method name of the distance measure between columns to be used for clustering. Defaults to “correlation”. Other supported methods are same as in ?dist. Also supports “jaccard” which is useful for clustering categorical variables. “euclidean” is sometimes more robust when ties cause “Unclusterable matrix: some col-distances are null” errors. Note, rows and cols are switched due an internal transposition of the data.
- cor.method** The method used for calculating correlation. Defaults to “pearson”
- row.dendrogram** A dendrogram object corresponding to the heatmap rows. If provided, row clustering cannot be performed

col.dendrogram A dendrogram object corresponding to the heatmap columns. If provided, column clustering cannot be performed

plot.dendrograms

- If clustering is performed or dendrograms are provided, which dendrograms should be plotted – “none”, “right”, “top”, or “both”

force.clustering

- Binary to over-ride the control that prevents clustering of too-large matrices

criteria.list A vector indicating which rows should be retained

covariates Any row-wise covariate annotate to add to the plot, as a fully formed list (placed on right side of plot)

covariates.grid.row

- A list of parameters passed to gpar specifying the behaviour of row lines in the right covariate bars

covariates.grid.col

- A list of parameters passed to gpar specifying the behaviour of column lines in the right covariate bars

covariates.grid.border

- A list of parameters passed to gpar specifying the behaviour of the border around the right covariate bars

covariates.row.lines

- Vector of row indices where grid lines should be drawn on the right covariate bars. If NULL (default), all row lines are drawn. Ignored if covariates.grid.row is not specified

covariates.col.lines

- Vector of column indices where grid lines should be drawn on the right covariate bars. If NULL (default), all column lines are drawn. Ignored if covariates.grid.col is not specified

covariates.reorder.grid.index

- Boolean specifying whether grid line indices for the right covariate bars should be re-ordered with clustering

covariates.padding

- Amount of empty space (in “lines”) to place between the right covariate bars and dendrogram

covariates.top Any column-wise covariate annotate to add to the plot, as a fully formed list

covariates.top.grid.row

- A list of parameters passed to gpar specifying the behaviour of row lines in the top covariate bars

covariates.top.grid.col

- A list of parameters passed to gpar specifying the behaviour of column lines in the top covariate bars

covariates.top.grid.border

- A list of parameters passed to gpar specifying the behaviour of the border around the top covariate bars

covariates.top.row.lines

- Vector of row indices where grid lines should be drawn on the top covariate bars. If NULL (default), all row lines are drawn. Ignored if covariates.top.grid.row is not specified

covariates.top.col.lines
 Vector of column indices where grid lines should be drawn on the top covariate bars. If NULL (default), all column lines are drawn. Ignored if covariates.top.grid.col is not specified

covariates.top.reorder.grid.index
 Boolean specifying whether grid line indices for the top covariate bars should be re-ordered with clustering

covariates.top.padding
 Amount of empty space (in “lines”) to place between the top covariate bars and dendrogram

covariate.legends
 A list defining covariate legends to add to the plot. See legends argument of legend.grob for more information

legend.cex
 Size of text labels in covariate legends, defaults to 1

legend.title.cex
 Size of title text in covariate legends, defaults to 1

legend.title.just
 Justification of title text in covariate legends, defaults to “centre”

legend.title.fontface
 Font face of title text in covariate legends – “plain”, “bold”, “italic”, etc.

legend.border
 A list of parameters passed to gpar specifying line options for the legend border, defaults to NULL (no border drawn)

legend.border.padding
 The amount of empty space (split equally on both sides) to add between the legend and its border, in “lines” units

legend.layout
 Numeric vector of length 2 specifying the number of columns and rows for the legend layout, defaults to a logical layout based on legend.side

legend.between.col
 Amount of space to add between columns in the layout, in “lines” units

legend.between.row
 Amount of space to add between rows in the layout, in “lines” units

legend.side
 Side of the plot where the legends should be drawn – “left”, “right”, or “top”

main
 The main title for the plot (space is reclaimed if NULL)

main.just
 The justification of the main title for the plot, default is centered

main.x
 The x location of the main title, default is 0.5

main.y
 The y location of the main title, default is 0.5

main.cex
 Size of text for main plot title, defaults to 2.5

right.size.add
 The size of each extra covariate row in the right dendrogram in units of “lines”

top.size.add
 The size of each extra covariate row in the top dendrogram in units of “lines”

right.dendrogram.size
 Size of right dendrogram

top.dendrogram.size
 Size of top dendrogram

scale.data	TRUE/FALSE to do row-wise scaling with mean-centering and sd-scaling
xaxis.lab	A vector of row labels, NA = use existing rownames, NULL = none
xaxis.lab.top	The label for the top x-axis. Required only if you want to print a top *and* bottom xaxis, otherwise use x.alternating = 2 for top axis only. Defaults to NULL
yaxis.lab	A vector of col labels, NA = use existing colnames, NULL = none
xaxis.cex	Size of x-axis label text - defaults to values found in a look-up table
xaxis.top.cex	Size of top x axis label text
yaxis.cex	Size of y-axis label text - defaults to values found in a look-up table
xaxis.rot	Rotation of x-axis tick labels; defaults to 90
xaxis.rot.top	Rotation of the top x-axis tick labels; defaults to 90
yaxis.rot	Rotation of y-axis tick labels; defaults to 0
xaxis.col	Colour of the x-axis tick labels, defaults to “black”
yaxis.col	Colour of the y-axis tick labels, defaults to “black”
xlab.label	The label for the x-axis
ylab.label	The label for the y-axis
xlab.cex	Size of x-axis label, defaults to 2
ylab.cex	Size of y-axis label, defaults to 2
xlab.col	Colour of the x-axis label, defaults to “black”
ylab.col	Colour of the y-axis label, defaults to “black”
xlab.top.label	The label for the top x-axis
xlab.top.cex	Size of top x-axis label
xlab.top.col	Colour of the top x-axis label
xlab.top.just	Justification of the top x-axis label, defaults to centered
xlab.top.x	The x location of the top x-axis label
xlab.top.y	The y location of the top y-axis label
xat	Vector listing where the x-axis labels should be drawn, defaults to automatic
xat.top	Vector listing where the x-axis labels should be drawn on the top of the plot. Required only when you want bottom and top axis, otherwise use x.alternating = 2, to get top axis only. Defaults to NULL
yat	Vector listing where the y-axis labels should be drawn, defaults to automatic
xaxis.tck	Size of x-axis tick marks. Defaults to NULL for intelligent choice based on covariate size.
xaxis.top.tck	Size of top x-axis tick marks. Defaults to NULL for intelligent choice based on covariate size.
yaxis.tck	Size of y-axis tick marks. Defaults to NULL for intelligent choice based on covariate size.
col.pos	Vector of column positions for adding text to cell, defaults to NULL
row.pos	Vector of row positions for adding text to cell, defaults to NULL

cell.text	Text to add to cell, defaults to an empty string
text.fontface	1 = Plain, 2 = Bold, 3 = Italic, default is 1
text.cex	Text size, default is 1
text.col	Text colour, default is black.
text.position	The position of the text, defaults to center.
text.offset	The offset of the position, defaults to 0.
text.use.grid.coordinates	Indentifier if grid coordinates or npc coordinates should be used
colourkey.cex	Size of colourkey label text
axes.lwd	Width of heatmap border. Note it also changes the colourkey border and ticks
gridline.order	Character specifying order in which to draw interior grid-lines ('h' or 'v'). Defaults to 'h' for horizontal first.
grid.row	Allow turning off of the interior grid-lines. Default FALSE
grid.col	Allow turning off of the interior grid-lines. Default FALSE
force.grid.row	Overrides default behaviour of turning off grid lines when number of rows exceed grid.limit. Defaults to FALSE
force.grid.col	Overrides default behaviour of turning off grid lines when number of columns exceed grid.limit. Defaults to FALSE
grid.limit	Limit set for when to turn off column and row lines if data size exceeds it. Defaults to 50
row.lines	Vector specifying location of lines, default is seq(1, ncol(x), 1) + 0.5. Note: Add 0.5 to customized vector
col.lines	Vector specifying location of lines, default is seq(1, nrow(x), 1) + 0.5. Note: Add 0.5 to customized vector
colour.scheme	Heatmap colouring. Accepts old-style themes, or a vector of either two or three colours that are gradiated to create the final palette.
total.colours	Total number of colours to plot
colour.centering.value	What should be the center of the colour-map
colour.alpha	Bias to be added to colour selection (uses $x^{\text{colour.alpha}}$ in mapping). Set to "automatic" for auto-adjustment.
fill.colour	The background fill (only exposed where missing values are present)
print.colour.key	Should the colour key be printed at all?
at	A vector specifying the breakpoints along the range of x; each interval specified by these breakpoints are assigned to a colour from the palette. Defaults to NULL, which corresponds to the range of x being divided into total.colours equally spaced intervals. If x has values outside of the range specified by "at" those values are shown with the colours corresponding to the extreme ends of the colour spectrum and a warning is given.
colourkey.labels.at	A vector specifying the tick-positions on the colourkey

colourkey.labels	A vector specifying tick-labels of the colourkey
top.padding	A number specifying the distance to the top margin, defaults to 0.1
bottom.padding	A number specifying the distance to the bottom margin, defaults to 0.5
right.padding	A number specifying the distance to the right margin, defaults to 0.5
left.padding	A number specifying the distance to the left margin, defaults to 0.5
x.alternating	A value specifying the position of the col names, defaults to 1. 1 means below the graph, 2 means above the graph. Use 3 to get tick marks below and above graph, but still need to specify xat.top and xaxis.lab.top to get values there
shrink	Allows rectangles to be scaled, defaults to 1
row.colour	Interior grid-line colour, defaults to “black”. Can be a vector
col.colour	Interior grid-line colour, defaults to “black”. Can be a vector
row.lwd	Interior grid-line width, defaults to 1. Setting to zero is equivalent to grid.row = FALSE and grid.col = FALSE. Can be a vector.
col.lwd	Interior grid-line width, defaults to 1. Setting to zero is equivalent to grid.row = FALSE and grid.col = FALSE. Can be a vector.
grid.colour	Interior grid-line colour, defaults to “black”. Can be a vector. Applies to both rows and columns. DEPRECATED
grid.lwd	Interior grid-line width, defaults to 1. Setting to zero is equivalent to grid.row = FALSE and grid.col = FALSE. Applies to both rows and columns. DEPRECATED
width	Figure width in size.units
height	Figure height in size.units
size.units	Units of size for the figure
resolution	Figure resolution in dpi
enable.warnings	Print warnings if set to TRUE, defaults to FALSE
xaxis.covariates	Any column-wise covariate annotate to add to the plot, as a fully formed list
xaxis.covariates.y	The y coordinate of the location of the x axis covariates
yaxis.covariates	Any row-wise covariate annotate to add to the plot, as a fully formed list
yaxis.covariates.x	The x coordinate of the location of the y axis covariates
description	Short description of image/plot; default NULL.
xaxis.fontface	Fontface for the x-axis scales
yaxis.fontface	Fontface for the y-axis scales
symbols	Extra symbols to be added (borders, squares and circles)
same.as.matrix	Prevents the flipping of the matrix that the function normally does

```

input.colours   boolean expressing whether or not the matrix was specified using colours or
                integer values. Defaults to FALSE
axis.xlab.padding
                Padding between axis of plot and x label
stratified.clusters.rows
                the row locations of the rows to be combined into a strata
stratified.clusters.cols
                the column locations of the columns to be combined into a strata
inside.legend   legend specification for the inside legend/key of the heatmap
style          defaults to “BoutrosLab”, also accepts “Nature”, which changes parameters ac-
                cording to Nature formatting requirements
preload.default
                ability to set multiple sets of diffrent defaults depending on publication needs
use.legacy.settings
                boolean to set wheter or not to use legacy mode settings (font)

```

Value

If `filename` is `NULL` then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the heatmap. In particular, if a script that uses such a call of `create heatmap` is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```

Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x,  )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics

```

Note that we would very much like to be able to pass `xaxis.cex` and `yaxis.cex` as vectors of the same length as the actual data-table. However lattice does not support that, because it currently expects them as a two-element vectors to specify left/right or top/bottom axes separately. I've raised a bug report on requesting an enhancement, but this would require an API change so... not sure if it will happen. Here's the bug-report: https://r-forge.r-project.org/tracker/index.php?func=detail&aid=1702&group_id=638&at=1

Author(s)

Paul C. Boutros

See Also

[covariates.grob](#), [create.dendrogram](#), [legend.grob](#)

Examples

```
set.seed(12345);
simple.data <- data.frame(
  x <- rnorm(n = 15),
  y <- rnorm(n = 15),
  z <- rnorm(n = 15),
  v <- rnorm(n = 15),
  w <- rnorm(n = 15)
);

simple.1D.data <- data.frame(x = rnorm(n = 15));

create.heatmap(
  filename = tempfile(pattern = 'Heatmap_1D_Inside_Legend', fileext = '.tiff'),
  x = simple.1D.data,
  clustering.method='none',
  inside.legend = list(fun = draw.key,
    args = list(
      key = list(
        text = list(
          lab = c('test','test','test','test'),
          cex = 1,
          fontface = 'bold'
        ),
        padding.text = 3,
        background = 'white',
        alpha.background = 0
      )
    ),
    x = 0.5,
    y = 0.5
  ),
  resolution = 100
)

create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Simple', fileext = '.tiff'),
  x = simple.data,
  main = 'Simple',
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 100
);

simple.data.col <- data.frame(
  x <- c('blue','green','red','yellow','blue','red','black','white','purple','grey'),
  y <- rep('red',10),
  z <- rep('yellow',10),
  v <- rep('green',10),
  w <- rep('purple',10)
);
```

```
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Simple_Using_Colours', fileext = '.tiff'),
  x = simple.data.col,
  clustering.method = 'none',
  input.colours = TRUE,
  resolution = 100
);

# Minimal Input
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Minimal_Input', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Minimal input',
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 100
);

# Axes and labels
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Axes_Labels', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Axes & labels',
  # Changing axes
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  # Turning on default row and column labels
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  # Adjusting font sizes
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  # Changing colourkey
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 100
);

# Custom Axes
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Custom_Axes', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Customized axes',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
```

```
yaxis.fontface = 1,
colourkey.cex = 1,
# Specify where to place tick marks
colourkey.labels.at = c(3,4, 6, 7, 10, 11),
# Specify label colours (note: this is based on the pre-clustering order)
xaxis.col = c('black', 'red',rep('black',6), 'red','black', 'black','red',rep('black',8)),
description = 'Heatmap created using BoutrosLab.plotting.general',
resolution = 200
);

# Two-sided Colour Scheme
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Colour_Scheme_1', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Colour scheme',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  # Changing the colours
  colour.scheme = c('white','firebrick'),
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

# Three-sided Colour Scheme
# Note: when using a three-sided colour scheme, it is advised to have two-sided data
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Colour_Scheme_2', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Colour scheme',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  # Changing the colours
  colour.scheme = c('red','white','turquoise'),
  # Scale the data to center around the mean
  scale.data = TRUE,
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);
```

```
# Colour Alpha
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Colour_Alpha', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Colours alpha',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  # Adjusting the alpha value of the colours
  colour.alpha = 'automatic',
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

# Clustering
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_No_Clustering', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'No clustering',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  colour.alpha = 'automatic',
  # Turning clustering off
  clustering.method = 'none',
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

# Clustering
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Clustering_Methods', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Clustering methods',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
```

```
xaxis.cex = 0.75,
yaxis.cex = 0.75,
xaxis.fontface = 1,
yaxis.fontface = 1,
colourkey.cex = 1,
colourkey.labels.at = seq(2,12,1),
colour.alpha = 'automatic',
# Clustering method defaults to 'diana', but can be set to other options
clustering.method = 'complete',
# Also setting the distance measures
rows.distance.method = 'euclidean',
cols.distance.method = 'manhattan',
description = 'Heatmap created using BoutrosLab.plotting.general',
resolution = 200
);

# Stratified Clustering
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Stratified_Clustering', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Stratified clustering',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20.,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  colour.alpha = 'automatic',
  # Stratifying the clustering by rows
  stratified.clusters.rows = list(c(1:10), c(11:20)),
  # Adding line to show highlight the division between the two strata
  grid.row = TRUE,
  row.lines = 10.5,
  row.lwd = 2,
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

# Dendrogram provided
col.dendrogram <- BoutrosLab.plotting.general::create.dendrogram(
  x = microarray[1:20, 1:20],
  cluster.dimension = 'col'
);

row.dendrogram <- BoutrosLab.plotting.general::create.dendrogram(
  x = microarray[1:20, 1:20],
  cluster.dimension = 'row'
);
```

```

create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Dendrogram_Provided', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Dendrogram provided',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  colour.alpha = 'automatic',
  # note: row/column dendograms are switched because the function inverts rows and columns
  clustering.method = 'none',
  row.dendrogram = col.dendrogram,
  col.dendrogram = row.dendrogram,
  # Adjusting the size of the dendrogram
  right.dendrogram.size = 3,
  top.dendrogram.size = 2.5,
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

# Covariates and Legends
# Note: covariates can also be added using the create.multiplot function
# set the colour schemes for the covariates
sex.colours <- patient$sex;
sex.colours[sex.colours == 'male'] <- 'dodgerblue';
sex.colours[sex.colours == 'female'] <- 'pink';

stage.colours <- patient$stage;
stage.colours[stage.colours == 'I'] <- 'plum1';
stage.colours[stage.colours == 'II'] <- 'orchid1';
stage.colours[stage.colours == 'III'] <- 'orchid3';
stage.colours[stage.colours == 'IV'] <- 'orchid4';

# create an object to draw the covariates from
sample.covariate <- list(
  rect = list(
    col = 'black',
    fill = sex.colours,
    lwd = 1.5
  ),
  rect = list(
    col = 'black',
    fill = stage.colours,
    lwd = 1.5
  )
);

```

```
# create a legend for the covariates
sample.cov.legend <- list(
  legend = list(
    colours = c('dodgerblue', 'pink'),
    labels = c('male','female'),
    title = 'Sex'
  ),
  legend = list(
    colours = c('plum1', 'orchid1','orchid3', 'orchid4'),
    labels = c('I','II', 'III', 'IV'),
    title = 'Stage'
  )
);

create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Covariates_Simple', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Covariates',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  colour.alpha = 'automatic',
  # adding covariates and corresponding legend
  covariates = sample.covariate,
  covariate.legend = sample.cov.legend,
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

# Top covariate and legend customization
chr.cov.colours <- microarray$Chr;
chr.cov.colours[microarray$Chr == 1] <- default.colours(3, palette.type = 'chromosomes')[1];
chr.cov.colours[microarray$Chr == 2] <- default.colours(3, palette.type = 'chromosomes')[2];
chr.cov.colours[microarray$Chr == 3] <- default.colours(3, palette.type = 'chromosomes')[3];

chr.covariate <- list(
  rect = list(
    col = 'white',
    fill = chr.cov.colours,
    lwd = 1.5
  )
);

# join covariate legends
combo.cov.legend <- list(
  legend = list(
```

```

colours = default.colours(3, palette.type = 'chromosomes'),
labels = c('1','2', '3'),
title = 'Chromosome',
border = 'white'
),
legend = list(
  colours = c('dodgerblue', 'pink'),
  labels = c('male','female'),
  title = 'Sex'
),
legend = list(
  colours = c('plum1', 'orchid1','orchid3', 'orchid4'),
  labels = c('I','II', 'III', 'IV'),
  title = 'Stage'
)
);

create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Covariate_Legend_Custom', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Custom covariates & legend',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  colour.alpha = 'automatic',
  clustering.method = 'none',
  # side covariate
  covariates = sample.covariate,
  # top covariate and covariate border specification
  covariates.top = chr.covariate,
  covariate.legend = combo.cov.legend,
  # making outline of border a matching green
  covariates.top.grid.border = list(col = 'lightblue', lwd = 2),
  # making certain column divisions a different colour
  covariates.top.col.lines = c(5,6),
  covariates.top.grid.col = list(col = 'blue', lwd = 2),
  # legend customization
  legend.side = c('right','left','top'),
  legend.title.cex = 0.75,
  legend.cex = 0.75,
  legend.title.just = 'left',
  legend.border = list(lwd = 1),
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

```

```
# Custom gridlines

create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Gridlines', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Gridlines',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  colour.alpha = 'automatic',
  # colouring gridlines
  grid.row = TRUE,
  grid.col = TRUE,
  row.colour = 'white',
  col.colour = 'white',
  row.lwd = 1.5,
  col.lwd = 1.5,
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

# Label cells
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Labelled_Cells', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Labelled cells',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  colour.alpha = 'automatic',
  grid.row = TRUE,
  grid.col = TRUE,
  row.colour = 'white',
  col.colour = 'white',
  row.lwd = 1.5,
  col.lwd = 1.5,
  clustering.method = 'none',
  # conditionally labelling cells
  # flipping rows and columns because the heatmap function does so
  row.pos = which(microarray[1:20, 1:20] > 11, arr.ind = TRUE)[,2],
  col.pos = which(microarray[1:20, 1:20] > 11, arr.ind = TRUE)[,1],
```

```

cell.text = microarray[1:20, 1:20][microarray[1:20, 1:20] > 11],
text.col = 'white',
text.cex = 0.65,
description = 'Heatmap created using BoutrosLab.plotting.general',
resolution = 200
);
# Label cells
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Labelled_Cells_NPC', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Labelled cells',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  colour.alpha = 'automatic',
  grid.row = TRUE,
  grid.col = TRUE,
  row.colour = 'white',
  col.colour = 'white',
  row.lwd = 1.5,
  col.lwd = 1.5,
  clustering.method = 'none',
  text.use.grid.coordinates = FALSE,
  # conditionally labelling cells
  # flipping rows and columns because the heatmap function does so
  cell.text = c("text1","text2"),
  text.col = 'white',
  text.cex = 0.65,
  text.position = list(c(0.5,0.5),c(0.75,0.75)),
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

# Method 1 of adding symbols (very similar to how text is added)
points <- microarray[1:20, 1:20][microarray[1:20, 1:20] > 11];
size.from <- range(points, na.rm = TRUE);
size.to <- c(1,3);
point.size <- (points - size.from[1])/diff(size.from) * diff(size.to) + size.to[1];
point.colour <- grey(runif(sum(microarray[1:20, 1:20] > 11), max = 0.5));

create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Symbols_1', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Symbols',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,

```

```
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    colourkey.cex = 1,
    colourkey.labels.at = seq(2,12,1),
    colour.alpha = 'automatic',
    clustering.method = 'none',
    # conditionally adding points to cells
    # flipping rows and columns because the heatmap function does so
    row.pos = which(microarray[1:20, 1:20] > 11, arr.ind = TRUE)[,2],
    col.pos = which(microarray[1:20, 1:20] > 11, arr.ind = TRUE)[,1],
    cell.text = rep(expression("\u25CF"), times = sum(microarray[1:20, 1:20] > 11)),
    text.col = point.colour,
    text.cex = point.size,
    description = 'Heatmap created using BoutrosLab.plotting.general',
    resolution = 200
);

# Method 2 of Adding Symbols
# Create matrices to describe the symbols
circle.matrix <- matrix(
  nrow = 20,
  ncol = 20,
  data = FALSE
);

circle.colour.matrix <- matrix(
  nrow = 20,
  ncol = 20,
  data = 'pink'
);

circle.size.matrix <- matrix(
  nrow = 20,
  ncol = 20,
  data = 20
);

border.matrix <- matrix(
  nrow = 20,
  ncol = 20,
  data = FALSE
);

border.colour.matrix <- matrix(
  nrow = 20,
  ncol = 20,
  data = 'black'
);

border.size.matrix <- matrix(
  nrow = 20,
  ncol = 20,
  data = 4
```

```
);

square.matrix <- matrix(
  nrow = 20,
  ncol = 20,
  data = FALSE
);

square.colour.matrix <- matrix(
  nrow = 20,
  ncol = 20,
  data = 'pink'
);

square.size.matrix <- matrix(
  nrow = 20,
  ncol = 20,
  data = 10
);

# setting up the symbols
symbol.locations <- list(
  circles = list(
    list(
      x = circle.matrix,
      col = circle.colour.matrix,
      size = circle.size.matrix
    )
  ),
  borders = list(
    list(
      x = border.matrix,
      col = border.colour.matrix,
      size = border.size.matrix
    ),
    # creating a border encompassing a larger area
    list(
      xright = 12.10,
      xleft = 12,
      ybottom = 1,
      ytop = 20,
      size = 4,
      col = 'pink'
    )
  ),
  squares = list(
    list(
      x = square.matrix,
      col = square.colour.matrix,
      size = square.size.matrix
    )
  )
);
```

```
# Set which items in the matrix will be shown

# symbol.locations$borders[[1]]$x <- FALSE;
# symbol.locations$squares[[1]]$x <- FALSE;
symbol.locations$circles[[1]]$x[which(microarray[1:20,1:20] > 11, arr.ind = TRUE)] <- TRUE;

create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Symbols_2', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Symbols',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  colour.alpha = 'automatic',
  clustering.method = 'none',
  # adding symbols
  symbols = symbol.locations,
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

# Rotate matrix
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Rotated_Matrix', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Rotated matrix',
  # Also flip labels
  ylab.label = 'Genes',
  xlab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = NA,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  colour.alpha = 'automatic',
  grid.row = TRUE,
  grid.col = TRUE,
  row.colour = 'white',
  col.colour = 'white',
  row.lwd = 1.5,
  col.lwd = 1.5,
  # stop heatmap function from rotating matrix
  same.as.matrix = TRUE,
  description = 'Heatmap created using BoutrosLab.plotting.general',
```

```

resolution = 200
);

# Example of using discrete data
discrete.data <- microarray[1:10,1:40];
# Looking for values greater than 10
discrete.data[which(discrete.data < 10, arr.ind = TRUE)] <- 0;
discrete.data[which(discrete.data > 0, arr.ind = TRUE)] <- 1;

sex.colour <- as.character(patient$sex);
sex.colour[sex.colour == 'male'] <- 'dodgerblue';
sex.colour[sex.colour == 'female'] <- 'pink';

stage.colour <- as.character(patient$stage)
stage.colour[stage.colour == 'I'] <- 'plum1'
stage.colour[stage.colour == 'II'] <- 'orchid1'
stage.colour[stage.colour == 'III'] <- 'orchid3'
stage.colour[stage.colour == 'IV'] <- 'orchid4'

msi.colour <- as.character(patient$msi)
msi.colour[msi.colour == 'MSS'] <- 'chartreuse4'
msi.colour[msi.colour == 'MSI-High'] <- 'chartreuse2'

discrete.covariate <- list(
  rect = list(
    col = 'transparent',
    fill = sex.colour,
    lwd = 1.5
  ),
  rect = list(
    col = 'transparent',
    fill = stage.colour,
    lwd = 1.5
  ),
  rect = list(
    col = 'transparent',
    fill = msi.colour,
    lwd = 1.5
  )
);

discrete.covariate.legend <- list(
  legend = list(
    colours = c('dodgerblue', 'pink'),
    labels = c('male','female'),
    title = expression(underline('Sex'))
  ),
  legend = list(
    colours = c('plum1', 'orchid1', 'orchid3', 'orchid4'),
    labels = c('I','II', 'III', 'IV'),
    title = expression(underline('Stage'))
  ),
  legend = list(

```

```
colours = c('chartreuse4', 'chartreuse2'),
labels = c('MSS','MSI-High'),
title = expression(underline('MSI'))
)
);

create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Discrete_Data', fileext = '.tiff'),
  x = discrete.data,
  main = 'Discrete data',
  xlab.label = 'Samples',
  same.as.matrix = TRUE,
  # Customize plot
  clustering.method = 'none',
  total.colours = 3,
  colour.scheme = c('white','black'),
  fill.colour = 'grey95',
  # Changing axes
  xat = seq(0,40,5),
  xaxis.lab = seq(0,40,5),
  yaxis.lab = rownames(microarray)[1:10],
  yaxis.cex = 0.75,
  xaxis.cex = 0.75,
  xaxis.rot = 0,
  xlab.cex = 1,
  # Covariates
  covariates.top = discrete.covariate,
  covariate.legend = discrete.covariate.legend,
  legend.side = 'right',
  legend.title.cex = 0.75,
  legend.cex = 0.75,
  legend.title.just = 'left',
  legend.between.row = 0.2,
  legend.border = list(col = 'transparent'),
  legend.border.padding = 2,
  shrink = 0.7,
  covariates.top.grid.border = list(col = 'black', lwd = 2),
  scale.data = FALSE,
  print.colour.key = FALSE,
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

# Correlation matrix
# Example of how to visualize the relationship between (e.x.) different cellularity estimates
# Generate a correlation matrix
cor.data <- cor(t(microarray[1:10,1:10]), method = 'spearman');
colnames(cor.data) <- colnames(microarray)[1:10];

# ensure that input data matrix is equal to what the heatmap clustering produces
distance.matrix <- as.dist(1 - cor(t(cor.data)), use = "pairwise", method = "pearson");
clustered.order <- hclust(d = distance.matrix, method = "ward")$order;
cor.data <- cor.data[clustered.order, clustered.order];
```

```

# prepare labels
x <- round(cor.data, 2);
x[x == 1] <- colnames(x);
y <- x;
for (i in 1:(ncol(y)-1)) {
  y[i, (i+1):nrow(y)] <- "";
};

create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Cellularity_Estimates', fileext = '.tiff'),
  x = cor.data,
  main = 'Correlation matrix',
  xaxis.lab = NULL,
  yaxis.lab = NULL,
  cell.text = y,
  clustering.method = 'ward',
  plot.dendrograms = 'none',
  rows.distance.method = 'correlation',
  cols.distance.method = 'correlation',
  cor.method = 'pearson',
  col.pos = which(y != '1', arr.ind = TRUE)[,1],
  row.pos = which(y != '1', arr.ind = TRUE)[,2],
  text.fontface = 2,
  text.col = 'white',
  text.cex = 0.70,
  colourkey.cex = 1,
  colour.scheme = c('blue', 'darkgrey', 'brown'),
  colour.centering.value = 0,
  at = seq(-1, 1, 0.001),
  colour.alpha = 1.5,
  grid.row = TRUE,
  grid.col = TRUE,
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

# Discrete sequential colours
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Discrete_Colours_Sequential', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Discrete colours',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  # Adjusting total colours plotted
  colourkey.labels.at = seq(2,12,1),

```

```
at = seq(2,12,1),
# Add one to account for a 'null' colour
total.colours = 11,
description = 'Heatmap created using BoutrosLab.plotting.general',
resolution = 200
);

# Discrete qualitative colours
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Discrete_Colours_Qualitative', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Discrete colours',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  # Adjusting total colours plotted
  colourkey.labels.at = seq(2,12,1),
  colourkey.labels = seq(2,12,1),
  at = seq(2,12,1),
  # Add one to account for a 'null' colour
  total.colours = 11,
  colour.scheme = default.colours(10),
  description = 'Heatmap created using BoutrosLab.plotting.general',
  resolution = 200
);

# Nature style
create.heatmap(
  filename = tempfile(pattern = 'Heatmap_Nature_style', fileext = '.tiff'),
  x = microarray[1:20, 1:20],
  main = 'Nature style',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  # Adjusting total colours plotted
  colourkey.labels.at = seq(2,12,1),
  colourkey.labels = seq(2,12,1),
  at = seq(2,12,1),
  # Add one to account for a 'null' colour
  total.colours = 11,
  colour.scheme = default.colours(10),

  # set style to Nature
```

```

style = 'Nature',

# demonstrating how to italicize character variables
ylab.label = expression(paste('italicized ', italic('a'))),

# demonstrating how to create en-dashes
xlab.label = expression(paste('en dashes: 1','\u2013', '10'^^'\u2013', ''^3)),

description = 'Heatmap created using BoutrosLab.plotting.general',
resolution = 200
);

# create heatmap with key like legend - used to show range of continuous variables

# First create legend with discrete colours
sex.colour <- as.character(patient$sex);
sex.colour[sex.colour == 'male'] <- 'dodgerblue';
sex.colour[sex.colour == 'female'] <- 'pink';

stage.colour <- as.character(patient$stage)
stage.colour[stage.colour == 'I'] <- 'plum1'
stage.colour[stage.colour == 'II'] <- 'orchid1'
stage.colour[stage.colour == 'III'] <- 'orchid3'
stage.colour[stage.colour == 'IV'] <- 'orchid4'

msi.colour <- as.character(patient$msi)
msi.colour[msi.colour == 'MSS'] <- 'chartreuse4'
msi.colour[msi.colour == 'MSI-High'] <- 'chartreuse2'

discrete.covariate <- list(
  rect = list(
    col = 'transparent',
    fill = sex.colour,
    lwd = 1.5
  ),
  rect = list(
    col = 'transparent',
    fill = stage.colour,
    lwd = 1.5
  ),
  rect = list(
    col = 'transparent',
    fill = msi.colour,
    lwd = 1.5
  )
);
discrete.covariate.legend <- list(
  legend = list(
    colours = c('dodgerblue', 'pink'),
    labels = c('male','female'),
    title = expression(underline('Sex'))
  ),

```

```
legend = list(
  colours = c('plum1', 'orchid1', 'orchid3', 'orchid4'),
  labels = c('I', 'II', 'III', 'IV'),
  title = expression(underline('Stage'))
),
legend = list(
  colours = c('chartreuse4', 'chartreuse2'),
  labels = c('MSS', 'MSI-High'),
  title = expression(underline('MSI'))
),
legend = list(
  colours = c('grey0', 'grey100'),
  labels = c('want key like', 'legend here'),
  title = expression(underline('one')),
continuous = TRUE,
height=3
),
legend = list(
  colours = c('grey0', 'grey100'),
  labels = c('want key like', 'legend here'),
  title = expression(underline('two'))
),
legend = list(
  colours = c('grey0', 'grey100'),
  labels = c(0,10),
  title = expression(underline('three')),
continuous = TRUE,
width = 3,
tck = 1,
tck.number = 3,
at = c(0,100),
angle = -90,
just = c("center", "bottom")
)
);

create.heatmap(
  filename = tempfile(pattern = 'Heatmap_ContinuousVariablesKey', fileext = '.tiff'),
  x = patient[1:20, 4:6],
  xlab.label = 'Samples',
  ylab.label = 'Scaled Data',
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  clustering.method = 'none',
  print.colour.key = FALSE,
  scale=TRUE,
  same.as.matrix = FALSE,
  covariates.top = discrete.covariate,
  covariates.top.grid.row = list(lwd = 1),
  covariate.legends = discrete.covariate.legend,
  legend.title.just = 'left',
  colour.scheme = c('gray0', 'grey100'),
  fill.colour = 'grey95',
```

```

axis.xlab.padding = 1.5,
resolution = 200
);

create.heatmap(
  filename = tempfile(pattern = 'Heatmap_borderRemoved', fileext = '.tiff'),
  x = simple.data,
  main = 'Simple',
  description = 'Heatmap created using BoutrosLab.plotting.general',
  axes.lwd = 0,
  resolution = 200
);

```

create.hexbinplot *Make a hexagonally binned plot*

Description

Takes a data.frame and writes a hexagonally binned plot

Usage

```

create.hexbinplot(
  formula,
  data,
  filename = NULL,
  main = NULL,
  main.just = 'center',
  main.x = 0.5,
  main.y = 0.5,
  main.cex = 3,
  aspect = 'xy',
  trans = NULL,
  inv = NULL,
  colour.scheme = NULL,
  colourkey = TRUE,
  colourcut = seq(0, 1, length = 11),
  mincnt = 1,
  maxcnt = NULL,
  xbins = 30,
  legend.title = NULL,
  xlab.label = tail(sub('`', '', formula[-2]), 1),
  ylab.label = tail(sub('`', '', formula[-3]), 1),
  xlab.cex = 2,

```

```
      ylab.cex = 2,
      xlab.col = 'black',
ylab.col = 'black',
xlab.top.label = NULL,
xlab.top.cex = 2,
      xlab.top.col = 'black',
xlab.top.just = 'center',
xlab.top.x = 0.5,
xlab.top.y = 0,
      xlims = NULL,
ylimits = NULL,
xat = TRUE,
yat = TRUE,
xaxis.lab = NA,
yaxis.lab = NA,
      xaxis.cex = 1.5,
yaxis.cex = 1.5,
xaxis.rot = 0,
yaxis.rot = 0,
xaxis.col = 'black',
      yaxis.col = 'black',
xaxis.tck = 1,
yaxis.tck = 1,
xaxis.fontface = 'bold',
yaxis.fontface = 'bold',
      layout = NULL,
as.table = FALSE,
x.relation = 'same',
y.relation = 'same',
x.spacing = 0,
y.spacing = 0,
strip.col = 'white',
      strip.cex = 1,
strip.fontface = 'bold',
add.grid = FALSE,
abline.h = NULL,
abline.v = NULL,
abline.lty = NULL,
      abline.lwd = NULL,
abline.col = 'black',
abline.front = FALSE,
add.xyline = FALSE,
xyline.col = 'black',
      xyline.lwd = 1,
xyline.lty = 1,
add.curves = FALSE,
curves.exprs = NULL,
curves.from = min(data, na.rm = TRUE),
```

```

        curves.to = max(data, na.rm = TRUE),
curves.col = 'black',
curves.lwd = 2,
curves.lty = 1,
      add.text = FALSE,
text.labels = NULL,
text.x = NULL,
text.y = NULL,
text.col = 'black',
text.cex = 1,
      text.fontface = 'bold',
add.axes = FALSE,
top.padding = 0.1,
bottom.padding = 0.7,
      left.padding = 0.5,
right.padding = 0.1,
      add.rectangle = FALSE,
xleft.rectangle = NULL,
ybottom.rectangle = NULL,
xright.rectangle = NULL,
      ytop.rectangle = NULL,
col.rectangle = 'transparent',
alpha.rectangle = 1,
      background.col = 'transparent',
key = NULL,
legend = NULL,
      height = 6,
width = 6,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
      description = 'Created with BoutrosLab.plotting.general',
style = 'BoutrosLab',
preload.default = 'custom',
      use.legacy.settings = FALSE,
inside.legend.auto = FALSE
);

```

Arguments

formula	The formula used to extract the x & y components from the data-frame
data	The data-frame to plot
filename	Filename for tiff output, or if NULL (default value) returns the trellis object itself
main	The main title for the plot (space is reclaimed if NULL)
main.just	The justification of the main title for the plot, default is centered
main.x	The x location of the main title, default is 0.5

main.y	The y location of the main title, default is 0.5
main.cex	Size of the main plot title
aspect	This argument controls the physical aspect ratio of the panels, defaults to “xy”
trans	function specifying a transformation for the counts such as log, defaults to NULL
inv	the inverse transformation of trans, defaults to NULL
colour.scheme	colour scheme to be used, default NULL gives LinGray colour scale
colourkey	logical whether a legend should be drawn, defaults to TRUE
colourcut	Vector of values covering [0, 1] that determine hexagon colour class boundaries and hexagon legend size boundaries. Alternatively, an integer (<= maxcnt) specifying the number of equispaced colourcut values in [0,1].
mincnt	Cells with fewer counts are ignored
maxcnt	Cells with more counts are ignored, defaults to auto-generation
xbins	Number of bins to use in x, defaults to 30
legend.title	character/expression to use in place of default legend title or a named list with elements: lab, x, y; defaults to NULL
xlab.label	X-axis label
ylab.label	Y-axis label
xlab.cex	Size of x-axis label
ylab.cex	Size of y-axis label
xlab.col	Colour of the x-axis label, defaults to “black”
ylab.col	Colour of the y-axis label, defaults to “black”
xlab.top.label	The label for the top x-axis
xlab.top.cex	Size of top x-axis label
xlab.top.col	Colour of the top x-axis label
xlab.top.just	Justification of the top x-axis label, defaults to centered
xlab.top.x	The x location of the top x-axis label
xlab.top.y	The y location of the top y-axis label
xlimits	Two-element vector giving the x-axis limits
ylimits	Two-element vector giving the y-axis limits
xat	Vector listing where the x-axis labels should be drawn
yat	Vector listing where the y-axis labels should be drawn
xaxis.lab	Vector listing x-axis tick labels, defaults to automatic
yaxis.lab	Vector listing y-axis tick labels, defaults to automatic
xaxis.cex	Size of x-axis scales, defaults to 2
yaxis.cex	Size of y-axis scales, defaults to 2
xaxis.rot	Rotation of x-axis tick labels; defaults to 0
yaxis.rot	Rotation of y-axis tick labels; defaults to 0

xaxis.col	Colour of the x-axis tick labels, defaults to “black”
yaxis.col	Colour of the y-axis tick labels, defaults to “black”
xaxis.tck	Specifies the length of the tick marks for x-axis, defaults to 1
yaxis.tck	Specifies the length of the tick marks for y-axis, defaults to 1
xaxis.fontface	Fontface for the x-axis scales
yaxis.fontface	Fontface for the y-axis scales
layout	A vector specifying the number of columns, rows (e.g., c(2,1). Default is NULL.
as.table	Specifies panel drawing order, default is FALSE which draws panels from bottom left corner, moving right then up. Set to TRUE to draw from top left corner, moving right then down
x.relation	Allows x-axis scales to vary if set to “free”, defaults to “same”
y.relation	Allows y-axis scales to vary if set to “free”, defaults to “same”
x.spacing	A number specifying the distance between panels along the x-axis, defaults to 0
y.spacing	A number specifying the distance between panels along the y-axis, defaults to 0
strip.col	Strip background colour, defaults to “white”
strip.cex	Strip title character expansion
strip.fontface	Strip title fontface, defaults to bold
add.grid	Allows grid lines to be turned on or off
abline.h	Specify the superimposed horizontal line(s)
abline.v	Specify the superimposed vertical line(s)
abline.lty	Specify the superimposed line type
abline.lwd	Specify the superimposed line width
abline.col	Specify the superimposed line colour (defaults to black)
abline.front	If an abline and/or a grid has been added, this controls whether they are drawn in front of the hexbins
add.xyline	Allow y=x line to be drawn, default is FALSE
xyline.col	y=x line colour, defaults to black
xyline.lwd	Specifies y=x line width, defaults to 1
xyline.lty	Specifies y=x line style, defaults to 1 (solid)
add.curves	Allow curves to drawn, default is FALSE
curves.exprs	A list of functions, expressions, or calls using “x” as a variable that specify the curves to be drawn
curves.from	Specifies the x co-ordinates at which the start of each curve should be drawn, defaults to drawing the curves to the left edge of the plotting region
curves.to	Specifies the x co-ordinates at which the end of each curve should be drawn, defaults to drawing the curves to the right edge of the plotting region
curves.col	Specifies colours of curves, default is black for each curve
curves.lwd	Specifies width of curves, default is 1 for each curve
curves.lty	Specifies type of curves, default is 1 (solid) for each curve

add.text	Allow additional text to be drawn, default is FALSE
text.labels	Labels for additional text
text.x	The x co-ordinates where additional text should be placed
text.y	The y co-ordinates where additional text should be placed
text.col	The colour of additional text
text.cex	The size of additional text
text.fontface	The fontface for additional text
add.axes	Allow axis lines to be turned on or off
top.padding	A number giving the top padding in multiples of the lattice default
bottom.padding	A number giving the bottom padding in multiples of the lattice default
left.padding	A number giving the left padding in multiples of the lattice default
right.padding	A number giving the right padding in multiples of the lattice default
add.rectangle	Allow a rectangle to be drawn, default is FALSE
xleft.rectangle	Specifies the left x coordinate of the rectangle to be drawn
ybottom.rectangle	Specifies the bottom y coordinate of the rectangle to be drawn
xright.rectangle	Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle	Specifies the top y coordinate of the rectangle to be drawn
col.rectangle	Specifies the colour to fill the rectangle's area
alpha.rectangle	Specifies the colour bias of the rectangle to be drawn
background.col	Specifies the colour for the background of the plot
key	Add a key to the plot. See xyplot.
legend	Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See xyplot.
height	Figure height, defaults to 6 inches
width	Figure width, defaults to 6 inches
size.units	Figure units, defaults to inches
resolution	Figure resolution in dpi, defaults to 1600
enable.warnings	Print warnings if set to TRUE, defaults to FALSE
description	Short description of image/plot; default NULL.
style	defaults to "BoutrosLab", also accepts "Nature", which changes parameters according to Nature formatting requirements
preload.default	ability to set multiple sets of different defaults depending on publication needs
use.legacy.settings	boolean to set whether or not to use legacy mode settings (font)
inside.legend.auto	boolean specifying whether or not to use the automatic inside legend function

Details

WARNING: this function uses highly unusual semantics, different from the rest of the `BoutrosLab.plotting.general` library. The underlying hexbinplot function uses an argument called `maxcnt` to specify the maximum number of counts per cell. The default behaviour is not sensibly encoded via a `NULL` or an `NA`, but instead by using the `missing` function. As a result, we need to use `do.call` semantics to handle this function. This **can mess up anything using `substitute`** including things that generate p-values!

Value

If `filename` is `NULL` then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of `create.histogram` is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```
Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
  Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics
  If 'maxcnt' is passed, make sure it is not smaller than the actual maximum count (value depends on nbins)
```

Author(s)

Maud HW Starmans

See Also

`xypot`, `lattice` or the Lattice book for an overview of the package.

Examples

```
set.seed(12345);

simple.data <- data.frame(
  x = rnorm(10000),
  y = rnorm(10000)
);

create.hexbinplot(
  filename = tempfile(pattern = 'Hexbinplot_Simple', fileext = '.tiff'),
  formula = y ~ x,
  data = simple.data,
  main = 'Simple',
  description = 'Hexbinplot created by BoutrosLab.plotting.general',
```

```
resolution = 50
);

create.hexbinplot(
  filename = tempfile(pattern = 'Hexbinplot_Simple_underlined_legend_title', fileext = '.tiff'),
  formula = y ~ x,
  data = simple.data,
  legend.title = list(lab = expression(bold(underline('Counts')))), x = 1, y = 1.1),
  right.padding = 4,
  description = 'Hexbinplot created by BoutrosLab.plotting.general',
  resolution = 50
);

# Set up data
hexbin.data <- data.frame(
  x = microarray[,1],
  y = microarray[,2]
);

# Minimal Input
create.hexbinplot(
  filename = tempfile(pattern = 'Hexbinplot_Minimal_Input', fileext = '.tiff'),
  formula = y ~ x,
  data = hexbin.data,
  main = 'Minimal input',
  # formatting bins
  colourcut = seq(0, 1, length = 11),
  # this sets the maximum value plotted -- values greater than this will not appear
  maxcnt = 50,
  description = 'Hexbinplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Axes & Labels
create.hexbinplot(
  filename = tempfile(pattern = 'Hexbinplot_Axes_Labels', fileext = '.tiff'),
  formula = y ~ x,
  data = hexbin.data,
  main = 'Axes & labels',
  colourcut = seq(0, 1, length = 11),
  maxcnt = 50,
  # Customize Axes and labels
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xlab.label = 'Sample 1',
  ylab.label = 'Sample 2',
  xlims = c(0,16),
  ylims = c(0,16),
  xat = seq(0,16,2),
```

```
yat = seq(0,16,2),
description = 'Hexbinplot created by BoutrosLab.plotting.general',
resolution = 100
);

# Aspect Ratio
create.hexbinplot(
    filename = tempfile(pattern = 'Hexbinplot_Aspect_Ratio', fileext = '.tiff'),
    formula = y ~ x,
    data = hexbin.data,
    main = 'Aspect ratio',
    xaxis.cex = 1,
    yaxis.cex = 1,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    xlab.label = 'Sample 1',
    ylab.label = 'Sample 2',
    xlims = c(0,16),
    ylims = c(0,16),
    xat = seq(0,16,2),
    yat = seq(0,16,2),
    colourcut = seq(0, 1, length = 11),
    maxcnt = 50,
    # Set the aspect ratio to control plot dimensions
    aspect = 2,
    description = 'Hexbinplot created by BoutrosLab.plotting.general',
    resolution = 200
);

# Colour scheme
create.hexbinplot(
    filename = tempfile(pattern = 'Hexbinplot_Colour_Change', fileext = '.tiff'),
    formula = y ~ x,
    data = hexbin.data,
    main = 'Colour change',
    xaxis.cex = 1,
    yaxis.cex = 1,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    xlab.label = 'Sample 1',
    ylab.label = 'Sample 2',
    xlims = c(0,16),
    ylims = c(0,16),
    xat = seq(0,16,2),
    yat = seq(0,16,2),
    aspect = 1,
    colourcut = seq(0, 1, length = 11),
    maxcnt = 50,
```

```
# Specify colour scheme
colour.scheme = colorRampPalette(c('dodgerblue','paleturquoise','chartreuse','yellow',
  'orange','red')),
description = 'Hexbinplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Bin sizes
create.hexbinplot(
  filename = tempfile(pattern = 'Hexbinplot_Bin_Sizes', fileext = '.tiff'),
  formula = y ~ x,
  data = hexbin.data,
  main = 'Bin sizes',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xlab.label = 'Sample 1',
  ylab.label = 'Sample 2',
  xlims = c(0,16),
  ylims = c(0,16),
  xat = seq(0,16,2),
  yat = seq(0,16,2),
  aspect = 1,
  colour.scheme = colorRampPalette(c('dodgerblue','paleturquoise','chartreuse', 'yellow',
    'orange','red')),
  # Specify bin sizes
  colourcut = seq(0,1,length = 6),
  description = 'Hexbinplot created by BoutrosLab.plotting.general',
  resolution = 200
);

# Correlation Key
create.hexbinplot(
  filename = tempfile(pattern = 'Hexbinplot_Correlation', fileext = '.tiff'),
  formula = y ~ x,
  data = hexbin.data,
  main = 'Correlation',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xlab.label = 'Sample 1',
  ylab.label = 'Sample 2',
  xlims = c(0,16),
  ylims = c(0,16),
  xat = seq(0,16,2),
  yat = seq(0,16,2),
  aspect = 1,
```

```

colourcut = seq(0, 1, length = 11),
maxcnt = 50,
# Correlation Key
legend = list(
  inside = list(
    fun = draw.key,
    args = list(
      key = get.corr.key(
        x = hexbin.data$x,
        y = hexbin.data$y,
        label.items = c('beta1', 'spearman'),
        alpha.background = 0
      )
    ),
    x = 0.05,
    y = 0.95,
    corner = c(0,1),
    draw = FALSE
  )
),
description = 'Hexbinplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Grid lines and diagonal
create.hexbinplot(
  filename = tempfile(pattern = 'Hexbinplot_Gridlines', fileext = '.tiff'),
  formula = y ~ x,
  data = hexbin.data,
  main = 'Gridlines',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xlab.label = 'Sample 1',
  ylab.label = 'Sample 2',
  xlims = c(0,16),
  ylims = c(0,16),
  xat = seq(0,16,2),
  yat = seq(0,16,2),
  aspect = 1,
  colourcut = seq(0, 1, length = 11),
  maxcnt = 50,
  # Grid & diagonal
  add.grid = TRUE,
  add.xyline = TRUE,
  description = 'Hexbinplot created by BoutrosLab.plotting.general',
  resolution = 200
);

# Large range

```

```
# Generate some fake data with both very low and very high values
set.seed(12345);

x <- c(rnorm(100000,0,0.1),rnorm(1000,0,0.5),rnorm(1000,0,sd=0.75));
y <- c(rnorm(100000,0,0.1),rnorm(1000,0,0.5),rnorm(1000,0,sd=0.75));

fake.data <- data.frame(
  x = x,
  y = y,
  z = y + x*(x+1)/4
);

create.hexbinplot(
  filename = tempfile(pattern = 'Hexbinplot_Range', fileext = '.tiff'),
  formula = z ~ x,
  data = fake.data,
  main = 'Range',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xlab.label = 'Sample 1',
  ylab.label = 'Sample 2',
  aspect = 1,
  # Use colourcut to divide the bins appropriately
  colourcut = c(0,0.0002,0.0004,0.0008,0.0016,0.0032,0.0064,0.0128,0.0256,0.0512,0.1024,0.2048,
              0.4096,0.8192,1),
  # Change the colour scheme
  colour.scheme = function(n){BTC(n, beg=1, end=256)},
  background.col = 'grey',
  description = 'Hexbinplot created by BoutrosLab.plotting.general',
  resolution = 200
);

# Outliers
# Generate data with upper bound outlier
set.seed(12345);

x <- c(rnorm(1000,0,0),rnorm(4000,0,0.5));
y <- c(rnorm(1000,0,0),rnorm(4000,0,0.5));

fake.data.outlier <- data.frame(
  x = x,
  y = y,
  z = y + x*(x+1)/4
);

create.hexbinplot(
  filename = tempfile(pattern = 'Hexbinplot_Outlier', fileext = '.tiff'),
  formula = z ~ x,
  data = fake.data.outlier,
```

```

main = 'Outlier',
xaxis.cex = 1,
yaxis.cex = 1,
xaxis.fontface = 1,
yaxis.fontface = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
xlab.label = 'Sample 1',
ylab.label = 'Sample 2',
aspect = 1,
# Use colourcut to divide the bins appropriately
colourcut = c(seq(0,0.01, length = 4),seq(0.0125,0.1,length=4), seq(0.125,1,length=4)),
xbins = 15,
mincnt = 0,
# Change the colour scheme
colour.scheme = function(n){BTC(n, beg=1, end=256)},
background.col = 'grey',
description = 'Hexbinplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Nature style
create.hexbinplot(
  filename = tempfile(pattern = 'Hexbinplot_Nature_style', fileext = '.tiff'),
  formula = y ~ x,
  data = hexbin.data,
  main = 'Nature style',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xlims = c(0,16),
  ylims = c(0,16),
  xat = seq(0,16,2),
  yat = seq(0,16,2),
  aspect = 1,
  colourcut = seq(0, 1, length = 11),
  maxcnt = 50,
  # Grid & diagonal
  add.grid = TRUE,
  add.xyline = TRUE,

  # set style to Nature
  style = 'Nature',

  # demonstrating how to italicize character variables
  ylab.lab = expression(paste('italicized ', italic('a'))),

  # demonstrating how to create en-dashes
  xlab.lab = expression(paste('en dashes: 1', '\u2013', '10'^^'\u2013', ''^3)),
```

```
description = 'Hexbinplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Multiplot different groups
set.seed(73);

# Randomly generate groups
simple.data$groups <- sample(1:2, 10000, replace = TRUE);
simple.data$group.labels <- as.factor(simple.data$groups);

create.hexbinplot(
formula = y ~ x | groups,
filename = tempfile(
    pattern = 'stratified_hexbinplot_numeric_conditioning',
    fileext = '.tiff'
),
data = simple.data,
description = 'Hexbinplot created by BoutrosLab.plotting.general',
strip.col = 'white',
strip.cex = 0.8,
strip.fontface = 'bold',
resolution = 200
);

create.hexbinplot(
formula = y ~ x | group.labels,
filename = tempfile(
    pattern = 'stratified_hexbinplot_factor_conditioning',
    fileext = '.tiff'
),
data = simple.data,
description = 'Hexbinplot created by BoutrosLab.plotting.general',
strip.col = 'white',
strip.cex = 0.8,
strip.fontface = 'bold',
resolution = 200
);
```

create.histogram *Make a histogram*

Description

Takes a vector and creates a histogram

Usage

```
create.histogram(  
  x,  
  data,  
  filename = NULL,  
  main = NULL,  
  main.just = 'center',  
  main.x = 0.5,  
  main.y = 0.5,  
  main.cex = 3,  
  xlab.label = NULL,  
  ylab.label = NULL,  
  xlab.cex = 2,  
  ylab.cex = 2,  
  xlab.col = 'black',  
  ylab.col = 'black',  
  xaxis.lab = TRUE,  
  yaxis.lab = TRUE,  
  xaxis.cex = 1.5,  
  yaxis.cex = 1.5,  
  xlims = NULL,  
  ylims = NULL,  
  xat = TRUE,  
  yat = TRUE,  
  xaxis.rot = 0,  
  yaxis.rot = 0,  
  xaxis.col = 'black',  
  yaxis.col = 'black',  
  xaxis.tck = 1,  
  yaxis.tck = 1,  
  xaxis.fontface = 'bold',  
  yaxis.fontface = 'bold',  
  xlab.top.label = NULL,  
  xlab.top.cex = 2,  
  xlab.top.col = 'black',  
  xlab.top.just = 'center',  
  xlab.top.x = 0.5,  
  xlab.top.y = 0,  
  type = 'percent',  
  breaks = NULL,  
  col = 'white',  
  border.col = 'black',  
  lwd = 2,  
  lty = 1,  
  layout = NULL,  
  x.spacing = 0,  
  y.spacing = 0,  
  x.relation = 'same',
```

```
y.relation = 'same',
strip.col = 'white',
strip.cex = 1,
top.padding = 0.1,
bottom.padding = 0.7,
right.padding = 0.1,
left.padding = 0.5,
ylab.axis.padding = 0,
abline.h = NULL,
abline.v = NULL,
abline.col = 'black',
abline.lwd = 1,
abline.lty = 1,
key = NULL,
legend = NULL,
add.rectangle = FALSE,
xleft.rectangle = NULL,
ybottom.rectangle = NULL,
xright.rectangle = NULL,
ytop.rectangle = NULL,
col.rectangle = 'transparent',
alpha.rectangle = 1,
height = 6,
width = 6,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
description = 'Created with BoutrosLab.plotting.general',
style = 'BoutrosLab',
preload.default = 'custom',
use.legacy.settings = FALSE,
inside.legend.auto = FALSE
);
```

Arguments

x	A formula or a numeric vector (not frequencies!)
data	An optional data source if x is a formula
filename	Filename for tiff output, or if NULL returns the trellis object itself
main	The main title for the plot (space is reclaimed if NULL)
main.just	The justification of the main title for the plot, default is centered
main.x	The x location of the main title, default is 0.5
main.y	The y location of the main title, default is 0.5
main.cex	Size of text for main plot title, defaults to 2
xlab.label	x-axis title
ylab.label	y-axis title

<code>xlab.cex</code>	Size of x-axis label, defaults to 2
<code>ylab.cex</code>	Size of y-axis label, defaults to 2
<code>xlab.col</code>	Colour of the x-axis label, defaults to “black”
<code>ylab.col</code>	Colour of the y-axis label, defaults to “black”
<code>xaxis.lab</code>	Vector listing x-axis tick labels, defaults to automatic
<code>yaxis.lab</code>	Vector listing y-axis tick labels, defaults to automatic
<code>xaxis.cex</code>	Size of x-axis tick labels, defaults to 1
<code>yaxis.cex</code>	Size of y-axis tick labels, defaults to 1
<code>xlimits</code>	Two-element vector giving the x-axis limits
<code>ylimits</code>	Two-element vector giving the y-axis limits
<code>xat</code>	Vector listing where the x-axis ticks should be drawn
<code>yat</code>	Vector listing where the y-axis ticks should be drawn
<code>xaxis.rot</code>	Rotation of x-axis tick labels; defaults to 0
<code>yaxis.rot</code>	Rotation of y-axis tick labels; defaults to 0
<code>xaxis.col</code>	Colour of the x-axis tick labels, defaults to “black”
<code>yaxis.col</code>	Colour of the y-axis tick labels, defaults to “black”
<code>xaxis.tck</code>	Specifies the length of the tick marks for x-axis, defaults to 1
<code>yaxis.tck</code>	Specifies the length of the tick marks for y-axis, defaults to 1
<code>xaxis.fontface</code>	Fontface for the x-axis scales
<code>yaxis.fontface</code>	Fontface for the y-axis scales
<code>xlab.top.label</code>	The label for the top x-axis
<code>xlab.top.cex</code>	Size of top x-axis label
<code>xlab.top.col</code>	Colour of the top x-axis label
<code>xlab.top.just</code>	Justification of the top x-axis label, defaults to centered
<code>xlab.top.x</code>	The x location of the top x-axis label
<code>xlab.top.y</code>	The y location of the top y-axis label
<code>type</code>	Should the plot be of the “percent” (default), “density” or “count”
<code>breaks</code>	A vector listing the break-points of the histogram, or an integer specifying the desired number of breaks.
<code>col</code>	Fill colour for the histograms
<code>border.col</code>	Specify border colour (defaults to black)
<code>lwd</code>	Specifies line width
<code>lty</code>	Specifies line style
<code>layout</code>	A vector specifying the number of columns, rows (e.g., <code>c(2,1)</code>). Default is <code>NULL</code> ; see <code>lattice::xyplot</code> for more details.
<code>x.spacing</code>	A number specifying the distance between panels along the x-axis, defaults to 0
<code>y.spacing</code>	A number specifying the distance between panels along the y-axis, defaults to 0
<code>x.relation</code>	Allows x-axis scales to vary if set to “free”, defaults to “same”

y.relation	Allows y-axis scales to vary if set to “free”, defaults to “same”
strip.col	Strip background colour, defaults to “white”
strip.cex	Strip title character expansion
top.padding	A number specifying the distance to the top margin, defaults to 0.1
bottom.padding	A number specifying the distance to the bottom margin, defaults to 0.7
right.padding	A number specifying the distance to the right margin, defaults to 0.5
left.padding	A number specifying the distance to the left margin, defaults to 0.5
ylab.axis.padding	A number specifying the distance of ylabel to the y-axis, defaults to 0,
abline.h	Allow horizontal line to be drawn, default to NULL
abline.v	Allow vertical line to be drawn, default to NULL
abline.col	Horizontal and vertical line colour, defaults to black
abline.lwd	Specifies horizontal/vertical line width, defaults to 1
abline.lty	Specifies horizontal/vertical line style, defaults to 1 (solid)
key	Add a key to the plot. See xyplot.
legend	Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See xyplot.
add.rectangle	Allow a rectangle to be drawn, default is FALSE
xleft.rectangle	Specifies the left x coordinate of the rectangle to be drawn
ybottom.rectangle	Specifies the bottom y coordinate of the rectangle to be drawn
xright.rectangle	Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle	Specifies the top y coordinate of the rectangle to be drawn
col.rectangle	Specifies the colour to fill the rectangle’s area
alpha.rectangle	Specifies the colour bias of the rectangle to be drawn
height	Figure height, defaults to 6 inches
width	Figure width, defaults to 6 inches
size.units	Figure units, defaults to inches
resolution	Figure resolution in dpi, defaults to 1600
enable.warnings	Print warnings if set to TRUE, defaults to FALSE
description	Short description of image/plot; default NULL.
style	defaults to “BoutrosLab”, also accepts “Nature”, which changes parameters according to Nature formatting requirements
preload.default	ability to set multiple sets of diffrent defaults depending on publication needs
use.legacy.settings	boolean to set wheter or not to use legacy mode settings (font)
inside.legend.auto	boolean specifying whether or not to use the automatic inside legend function

Value

If `filename` is `NULL` then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of `create histogram` is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```
Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics
```

Author(s)

Paul C. Boutros

See Also

[histogram](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(12345);

create.histogram(
  filename = tempfile(pattern = 'Histogram_Simple', fileext = '.tiff'),
  x = rnorm(5000),
  main = 'Simple',
  description = 'Histogram created by BoutrosLab.plotting.general',
  resolution = 50
);

create.histogram(
  filename = tempfile(pattern = 'Histogram_Simple_Count', fileext = '.tiff'),
  x = rnorm(5000),
  main = 'Simple Count',
  description = 'Histogram created by BoutrosLab.plotting.general',
  type = 'count',
  resolution = 50
);

# Minimal Input
create.histogram(
  filename = tempfile(pattern = 'Histogram_Minimal_Input', fileext = '.tiff'),
  x = microarray[,1],
  main = 'Minimal input',
```

```
description = 'Histogram created by BoutrosLab.plotting.general',
resolution = 50
);

# Formula Input - dividing by chromosome
chr.data <- data.frame(
  x = microarray$Chr,
  y = microarray[,1]
);

create.histogram(
  filename = tempfile(pattern = 'Histogram_Formula_Input', fileext = '.tiff'),
  x = y ~ x,
  data = chr.data,
  main = 'Formula input',
  description = 'Histogram created by BoutrosLab.plotting.general',
  resolution = 100
);

# Axes and Labels
create.histogram(
  filename = tempfile(pattern = 'Histogram_Axes_Labels', fileext = '.tiff'),
  x = microarray[,1],
  main = 'Axes & labels',
  # Customizing the axes and labels
  xlab.label = 'Bins',
  ylab.label = 'Counts',
  xlims = c(0, 16),
  xat = seq(0,15,5),
  # set break points for bins
  breaks = seq(floor(min(microarray[,1])), ceiling(max(microarray[,1])), 1),
  description = 'Histogram created by BoutrosLab.plotting.general',
  resolution = 100
);

# Colour change
create.histogram(
  filename = tempfile(pattern = 'Histogram_Colours', fileext = '.tiff'),
  x = microarray[,1],
  main = 'Colours',
  xlab.label = 'Bins',
  ylab.label = 'Counts',
  xlims = c(0, 16),
  xat = seq(0,15,5),
  breaks = seq(floor(min(microarray[,1])), ceiling(max(microarray[,1])), 1),
  # Colours
  col = 'lightgrey',
  description = 'Histogram created by BoutrosLab.plotting.general',
  resolution = 100
);

# Line type
```

```

create.histogram(
  filename = tempfile(pattern = 'Histogram_Line_Type', fileext = '.tiff'),
  x = microarray[,1],
  main = 'Line type',
  xlab.label = 'Bins',
  ylab.label = 'Counts',
  xlims = c(0, 16),
  xat = seq(0,15,5),
  breaks = seq(floor(min(microarray[,1])), ceiling(max(microarray[,1])), 1),
  col = 'lightgrey',
  # Changing the line type
  lty = 2,
  description = 'Histogram created by BoutrosLab.plotting.general',
  resolution = 200
);

# Nature style
create.histogram(
  filename = tempfile(pattern = 'Histogram_Nature_style', fileext = '.tiff'),
  x = microarray[,1],
  main = 'Nature style',
  xlims = c(0, 16),
  xat = seq(0,15,5),
  breaks = seq(floor(min(microarray[,1])), ceiling(max(microarray[,1])), 1),
  col = 'lightgrey',

  # set style to Nature
  style = 'Nature',

  # demonstrating how to italicize character variables
  ylab.label = expression(paste('italicized ', italic('a'))),

  # demonstrating how to create en-dashes
  xlab.label = expression(paste('en dashes: 1', '\u2013', '10' '^' '\u2013', '''^3)),

  description = 'Histogram created by BoutrosLab.plotting.general',
  resolution = 200
);

```

create.lollipopplot *Make a lollipopplot*

Description

Takes a data.frame and creates a lollipopplot

Usage

```
create.lollipopplot()
```

```
formula,
data,
filename = NULL,
groups = NULL,
main = NULL,
main.just = 'center',
main.x = 0.5,
    main.y = 0.5,
main.cex = 3,
xlab.label = tail(sub('`', '', formula[-2]), 1),
ylab.label = tail(sub('`', '', formula[-3]), 1),
    xlab.cex = 2,
ylab.cex = 2,
xlab.col = 'black',
ylab.col = 'black',
    xlab.top.label = NULL,
xlab.top.cex = 2,
xlab.top.col = 'black',
xlab.top.just = 'center',
xlab.top.x = 0.5,
    xlab.top.y = 0,
xlims = NULL,
ylims = NULL,
xat = TRUE,
yat = TRUE,
xaxis.lab = NA,
yaxis.lab = NA,
xaxis.log = FALSE,
yaxis.log = FALSE,
    xaxis.cex = 1.5,
yaxis.cex = 1.5,
xaxis.rot = 0,
yaxis.rot = 0,
xaxis.fontface = 'bold',
yaxis.fontface = 'bold',
xaxis.col = 'black',
yaxis.col = 'black',
xaxis.tck = c(1,1),
yaxis.tck = c(1,1),
add.grid = FALSE,
xgrid.at = xat,
    ygrid.at = yat,
grid.colour = NULL,
horizontal = FALSE,
type = 'p',
cex = 0.75,
pch = 19,
col = 'black',
```

```
col.border = 'black',
lwd = 1,
lty = 1,
alpha = 1,
axes.lwd = 1,
strip.col = 'white',
strip.cex = 1,
strip.fontface = 'bold',
y.error.up = NULL,
y.error.down = y.error.up,
x.error.right = NULL,
x.error.left = x.error.right,
y.error.bar.col = 'black',
x.error.bar.col = y.error.bar.col,
error.whisker.angle = 90,
error.bar.lwd = 1,
error.bar.length = 0.1,
key = list(text = list(lab = c(''))),
legend = NULL,
top.padding = 0.1,
bottom.padding = 0.7,
right.padding = 0.1,
left.padding = 0.5,
key.top = 0.1,
key.left.padding = 0,
ylab.axis.padding = 1,
axis.key.padding = 1,
layout = NULL,
as.table = FALSE,
x.spacing = 0,
y.spacing = 0,
x.relation = 'same',
y.relation = 'same',
add.axes = FALSE,
axes.lty = 'dashed',
add.xyline = FALSE,
xyline.col = 'black',
xyline.lwd = 1,
xyline.lty = 1,
abline.h = NULL,
abline.v = NULL,
abline.col = 'black',
abline.lwd = 1,
abline.lty = 1,
add.curves = FALSE,
curves.exprs = NULL,
curves.from = min(data, na.rm = TRUE),
curves.to = max(data, na.rm = TRUE),
```

```
curves.col = 'black',
curves.lwd = 2,
curves.lty = 1,
add.rectangle = FALSE,
xleft.rectangle = NULL,
ybottom.rectangle = NULL,
xright.rectangle = NULL,
ytop.rectangle = NULL,
col.rectangle = 'transparent',
alpha.rectangle = 1,
add.points = FALSE,
points.x = NULL,
points.y = NULL,
points.pch = 19,
points.col = 'black',
points.col.border = 'black',
points.cex = 1,
add.line.segments = FALSE,
line.start = NULL,
line.end = NULL,
line.col = 'black',
line.lwd = 1,
add.text = FALSE,
text.labels = NULL,
text.x = NULL,
text.y = NULL,
text.col = 'black',
text.cex = 1,
text.fontface = 'bold',
text.guess.labels = FALSE,
text.guess.skip.labels = TRUE,
text.guess.ignore.radius = FALSE,
text.guess.ignore.rectangle = FALSE,
text.guess.radius.factor = 1,
text.guess.buffer.factor = 1,
text.guess.label.position = NULL,
height = 6,
width = 6,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
description = 'Created with BoutrosLab.plotting.general',
style = 'BoutrosLab',
preload.default = 'custom',
group.specific.colouring = TRUE,
use.legacy.settings = FALSE,
inside.legend.auto = FALSE,
regions.labels = c(),
```

```

    regions.start = c(),
regions.stop = c(),
regions.color = c("red"),
regions.cex = 1,
regions.alpha = 1,
      lollipop.bar.y = NULL,
lollipop.bar.color = "gray",
...
);

```

Arguments

formula	The formula used to extract the x & y components from the data-frame
data	The data-frame to plot
filename	Filename for tiff output, or if NULL returns the trellis object itself
groups	The grouping variable in the data-frame
main	The main title for the plot (space is reclaimed if NULL)
main.just	The justification of the main title for the plot, default is centered
main.x	The x location of the main title, default is 0.5
main.y	The y location of the main title, default is 0.5
main.cex	Size of text for main plot title
xlab.label	x-axis label
ylab.label	y-axis label
xlab.cex	Size of x-axis label, defaults to 3
ylab.cex	Size of y-axis label, defaults to 3
xlab.col	Colour of the x-axis label, defaults to "black"
ylab.col	Colour of the y-axis label, defaults to "black"
xlab.top.label	The label for the top x-axis
xlab.top.cex	Size of top x-axis label
xlab.top.col	Colour of the top x-axis label
xlab.top.just	Justification of the top x-axis label, defaults to centered
xlab.top.x	The x location of the top x-axis label
xlab.top.y	The y location of the top y-axis label
xlimits	Two-element vector giving the x-axis limits, defaults to automatic
ylimits	Two-element vector giving the y-axis limits, defaults to automatic
xat	Vector listing where the x-axis labels should be drawn, defaults to automatic
yat	Vector listing where the y-axis labels should be drawn, defaults to automatic
xaxis.lab	Vector listing x-axis tick labels, defaults to automatic
yaxis.lab	Vector listing y-axis tick labels, defaults to automatic
xaxis.log	Logical indicating whether x-variable should be in logarithmic scale (and what base if numeric)

xaxis.log	Logical indicating whether y-variable should be in logarithmic scale (and what base if numeric)
xaxis.cex	Size of x-axis scales, defaults to 2
yaxis.cex	Size of y-axis scales, defaults to 2
xaxis.rot	Counterclockwise rotation of text in x-axis scales in degrees, defaults to 0
yaxis.rot	Counterclockwise rotation of text in y-axis scales in degrees, defaults to 0
xaxis.fontface	Fontface for the x-axis scales
yaxis.fontface	Fontface for the y-axis scales
xaxis.col	Colour of the x-axis tick labels, defaults to “black”
yaxis.col	Colour of the y-axis tick labels, defaults to “black”
xaxis.tck	Specifies the length of the tick mark, defaults to 1 for both top and bottom axes
yaxis.tck	Specifies the length of the tick mark, defaults to 1 for both top and bottom axes
add.grid	Logical stating wheter or not the grid should be drawn on the plot
xgrid.at	Vector listing where the x-axis grid lines should be drawn, defaults to xat
ygrid.at	Vector listing where the y-axis grid lines should be drawn, defaults to yat
grid.colour	ability to set individual grid line colours
horizontal	xyplot-specific function that allows you to change if type='h' draws lines to the vertical or horizontal axis
type	Plot type
cex	Character expansion for plotting symbol
pch	Plotting character
col	Point/line colour
col.border	Colour of border when points pch >= 21. Defaults to “black”
lwd	Specifies line width, defaults to 1
lty	Specifies line style, defaults to 1 (solid)
alpha	Specifies line transparency, defaults to 1 (opaque)
axes.lwd	Thickness of width of axes lines
strip.col	Strip background colour, defaults to “white”
strip.cex	Strip title character expansion
strip.fontface	Strip title fontface, defaults to bold
y.error.up	upward error vector. Defaults to NULL. When y.error.up is NULL, vertical error bar is not drawn
y.error.down	Downward error vector. Defaults to y.error.down to show symmetric error bars
x.error.right	Rightward error vector. Defaults to NULL. When x.error.right is NULL, horizontal error bar is not drawn
x.error.left	Leftward error vector. Defaults to x.error.right to show symmetric error bars
y.error.bar.col	Colour of vertical error bar. Defaults to “black”

x.error.bar.col
 Colour of horizontal error bar. Defaults to “black”
error.whisker.angle
 Angle of the whisker drawn on error bar. Defaults to 90 degree
error.bar.lwd Error bar line width. Defaults to 1
error.bar.length
 Length of the error bar whiskers. Defaults to 0.1
key
 A list giving the key (legend). The default suppresses drawing
legend
 Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See xyplot.
top.padding
 A number specifying the distance to the top margin, defaults to 0.1
bottom.padding
 A number specifying the distance to the bottom margin, defaults to 0.7
right.padding
 A number specifying the distance to the right margin, defaults to 0.1
left.padding
 A number specifying the distance to the left margin, defaults to 0.5
key.top
 A number specifying the distance at top of key, defaults to 0.1
key.left.padding
 Amount of padding to go onto any legend on the left
ylab.axis.padding
 A number specifying the distance of ylabel to the y-axis, defaults to 1
axis.key.padding
 A number specifying the distance from the y-axis to the key, defaults to 1
layout
 A vector specifying the number of columns, rows (e.g., c(2,1)). Default is NULL; see lattice::xyplot for more details
as.table
 Specifies panel drawing order, default is FALSE which draws panels from bottom left corner, moving right then up. Set to TRUE to draw from top left corner, moving right then down
x.spacing
 A number specifying the distance between panels along the x-axis, defaults to 0
y.spacing
 A number specifying the distance between panels along the y-axis, defaults to 0
x.relation
 Allows x-axis scales to vary if set to “free”, defaults to “same”
y.relation
 Allows y-axis scales to vary if set to “free”, defaults to “same”
add.axes
 Allow axis lines to be turned on or off, default is FALSE
axes.lty
 Specifies axis line style, defaults to “dashed”
add.xyline
 Allow y=x line to be drawn, default is FALSE
xyline.col
 y=x line colour, defaults to black
xyline.lwd
 Specifies y=x line width, defaults to 1
xyline.lty
 Specifies y=x line style, defaults to 1 (solid)
abline.h
 Allow horizontal line to be drawn, default to NULL
abline.v
 Allow vertical line to be drawn, default to NULL
abline.col
 Horizontal line colour, defaults to black
abline.lwd
 Specifies horizontal line width, defaults to 1

abline.lty	Specifies horizontal line style, defaults to 1 (solid)
add.curves	Allow curves to drawn, default is FALSE
curves.exprs	A list of functions, expressions, or calls using "x" as a variable that specify the curves to be drawn
curves.from	Specifies the x co-ordinates at which the start of each curve should be drawn, defaults to drawing the curves to the left edge of the plotting region
curves.to	Specifies the x co-ordinates at which the end of each curve should be drawn, defaults to drawing the curves to the right edge of the plotting region
curves.col	Specifies colours of curves, default is black for each curve
curves.lwd	Specifies width of curves, default is 1 for each curve
curves.lty	Specifies type of curves, default is 1 (solid) for each curve
add.rectangle	Allow a rectangle to be drawn, default is FALSE
xleft.rectangle	Specifies the left x coordinate of the rectangle to be drawn
ybottom.rectangle	Specifies the bottom y coordinate of the rectangle to be drawn
xright.rectangle	Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle	Specifies the top y coordinate of the rectangle to be drawn
col.rectangle	Specifies the colour to fill rectangle's area
alpha.rectangle	Specifies the colour bias of the rectangle to be drawn
add.points	Allow additional points to be drawn, default is FALSE
points.x	The x co-ordinates where additional points should be drawn
points.y	The y co-ordinates where additional points should be drawn
points.pch	The plotting character for additional points
points.col	The colour of additional points
points.col.border	Colour of the border of additional points if points.pch >= 21. Defaults to black
points.cex	The size of additional points
add.line.segments	Allow additional line segments to be drawn, default is FALSE
line.start	The y co-ordinates where additional line segments should start
line.end	The y co-ordinates where additional line segments should end
line.col	The colour of additional line segments, default is black
line.lwd	The line width of additional line segments, default is 1
add.text	Allow additional text to be drawn, default is FALSE
text.labels	Labels for additional text
text.x	The x co-ordinates where additional text should be placed
text.y	The y co-ordinates where additional text should be placed

text.col The colour of additional text

text.cex The size of additional text

text.fontface The fontface for additional text

text.guess.labels
 Allows automatic labeling by considering values in text.x and text.y as a data point to be labelled, default is FALSE

text.guess.skip.labels
 Provides an option to disregard automatic labelling algorithm if no space is available around a data point, thus forcing labelling if a collision is likely, default is TRUE

text.guess.ignore.radius
 Allows the automatic labeling algorithm to ignore the radius space of a data point, useful to label a cluster of data points with a single text box, default is FALSE

text.guess.ignore.rectangle
 Allows the automatic labeling algorithm to ignore the rectangle space of multiple potential label positions, default is FALSE

text.guess.radius.factor
 A numeric value to factor the radius value to alter distance from the label and the data point

text.guess.buffer.factor
 A numeric value to factor the buffer value to alter the space which is used to consider if data.points are potentially going to collide

text.guess.label.position
 A numeric value between 0 and 360 to specify the precise angle of a text box center and the positive x-axis. Angles move counter-clockwise beginning at the positive x axis

height Figure height, defaults to 6 inches

width Figure width, defaults to 6 inches

size.units Figure units, defaults to inches

resolution Figure resolution in dpi, defaults to 1600

enable.warnings
 Print warnings if set to TRUE, defaults to FALSE

description Short description of image/plot; default NULL

style defaults to “BoutrosLab”, also accepts “Nature”, which changes parameters according to Nature formatting requirements

preload.default
 ability to set multiple sets of different defaults depending on publication needs

group.specific.colouring
 Variable to specify if group specific multi colouring for error bars is enforced

use.legacy.settings
 boolean to set whether or not to use legacy mode settings (font)

inside.legend.auto
 boolean specifying whether or not to use the automatic inside legend function

```

regions.labels Labels for each of the regions on the lollipop plots bars
regions.start start x value of each of the regions
regions.stop stop value for each of the regions
regions.color color of each of the regions
regions.cex size of the text of each of the regions
regions.alpha alpha of each of the regions
lollipop.bar.y y location of top of the lollipop plot bar – defaults to right above the bottom y
axis
lollipop.bar.color
color of the lollipop plot bar
...
Additional arguments to be passed to xyplot

```

Value

If filename is NULL then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of create histogram is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```

Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics

```

Author(s)

Paul C. Boutros

See Also

[xyplot](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```

set.seed(12345);
lollipop.data <- data.frame(
  y = seq(1,100,1),
  x = rnorm(100)
);

create.lollipopplot(
  filename = tempfile(pattern = 'Lollipop_Simple', fileext = '.tiff'),

```

```

formula = x ~ y,
data = lollipop.data,
main = 'Lollipop plot',
xaxis.cex = 1,
xlims = c(-1,102),
yaxis.cex = 1,
xaxis.fontface = 1,
yaxis.fontface = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
pch = 21,
col = 'black',
fill = 'transparent',
description = 'Scatter plot created by BoutrosLab.plotting.general',
regions.start = c(1,26,48),
regions.stop = c(15,35,72),
regions.labels = c("test 1", "test2", "test 3"),
regions.color = c("#66b3ff", "#5cd65c", "#ff3333")
);

```

create.manhattanplot *Make a Manhattan plot*

Description

Takes a data.frame and creates a Manhattan plot

Usage

```

create.manhattanplot(
  formula,
  data,
  filename = NULL,
  main = NULL,
  main.just = 'center',
  main.x = 0.5,
  main.y = 0.5,
  main.cex = 3,
  xlab.label = tail(sub('`', '', formula[-2]), 1),
  ylab.label = tail(sub('`', '', formula[-3]), 1),
  xlab.cex = 2,
  ylab.cex = 2,
  xlab.col = 'black',
  ylab.col = 'black',
  xlab.top.label = NULL,
  xlab.top.cex = 2,
  xlab.top.col = 'black',
  xlab.top.just = 'center',

```

```
xlab.top.x = 0.5,  
xlab.top.y = 0,  
xlims = NULL,  
ylims = NULL,  
xat = TRUE,  
yat = TRUE,  
xaxis.lab = NA,  
yaxis.lab = NA,  
xaxis.log = FALSE,  
yaxis.log = FALSE,  
xaxis.cex = 1.5,  
yaxis.cex = 1.5,  
xaxis.rot = 0,  
yaxis.rot = 0,  
xaxis.fontface = 'plain',  
yaxis.fontface = 'plain',  
xaxis.col = 'black',  
yaxis.col = 'black',  
xaxis.tck = 0,  
yaxis.tck = c(1,1),  
horizontal = FALSE,  
type = 'p',  
cex = 2,  
pch = '.',  
col = 'black',  
lwd = 1,  
lty = 1,  
alpha = 1,  
strip.col = 'white',  
strip.cex = 1,  
axes.lwd = 1,  
axes.lty = 'dashed',  
key = list(text = list(lab = c(''))),  
legend = NULL,  
layout = NULL,  
as.table = FALSE,  
x.spacing = 0,  
y.spacing = 0,  
x.relation = 'same',  
y.relation = 'same',  
top.padding = 0,  
bottom.padding = 0,  
right.padding = 0,  
left.padding = 0,  
key.top = 0,  
key.left.padding = 0,  
ylab.axis.padding = 1,  
axis.key.padding = 1,
```

```

abline.h = NULL,
abline.col = 'black',
abline.lwd = 1,
abline.lty = 1,
add.rectangle = FALSE,
xleft.rectangle = NULL,
ybottom.rectangle = NULL,
xright.rectangle = NULL,
ytop.rectangle = NULL,
col.rectangle = 'transparent',
alpha.rectangle = 1,
add.points = FALSE,
points.x = NULL,
points.y = NULL,
points.pch = 19,
points.col = 'black',
points.cex = 1,
add.text = FALSE,
text.labels = NULL,
text.x = NULL,
text.y = NULL,
text.col = 'black',
text.cex = 1,
text.fontface = 'bold',
height = 6,
width = 10,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
style = 'BoutrosLab',
description = 'Created with BoutrosLab.plotting.general',
preload.default = 'custom',
use.legacy.settings = FALSE,
inside.legend.auto = FALSE,
...
);

```

Arguments

<code>formula</code>	The formula used to extract the x & y components from the data-frame
<code>data</code>	The data-frame to plot
<code>filename</code>	Filename for tiff output, or if NULL returns the trellis object itself
<code>main</code>	The main title for the plot (space is reclaimed if NULL)
<code>main.just</code>	The justification of the main title for the plot, default is centered
<code>main.x</code>	The x location of the main title, default is 0.5
<code>main.y</code>	The y location of the main title, default is 0.5

main.cex	Size of text for main plot title
xlab.label	x-axis label
ylab.label	y-axis label
xlab.cex	Size of x-axis label, defaults to 2
ylab.cex	Size of y-axis label, defaults to 2
xlab.col	Colour of the x-axis label, defaults to “black”
ylab.col	Colour of the y-axis label, defaults to “black”
xlab.top.label	The label for the top x-axis
xlab.top.cex	Size of top x-axis label
xlab.top.col	Colour of the top x-axis label
xlab.top.just	Justification of the top x-axis label, defaults to centered
xlab.top.x	The x location of the top x-axis label
xlab.top.y	The y location of the top y-axis label
xlimits	Two-element vector giving the x-axis limits, defaults to automatic
ylimits	Two-element vector giving the y-axis limits, defaults to automatic
xat	Vector listing where the x-axis labels should be drawn, defaults to automatic
yat	Vector listing where the y-axis labels should be drawn, defaults to automatic
xaxis.lab	Vector listing x-axis tick labels, defaults to automatic
yaxis.lab	Vector listing y-axis tick labels, defaults to automatic
xaxis.log	Logical indicating whether x-variable should be in logarithmic scale (and what base if numeric)
yaxis.log	Logical indicating whether y-variable should be in logarithmic scale (and what base if numeric)
xaxis.cex	Size of x-axis scales, defaults to 1
yaxis.cex	Size of y-axis scales, defaults to 1
xaxis.rot	Counterclockwise rotation of text in x-axis scales in degrees, defaults to 0
yaxis.rot	Counterclockwise rotation of text in y-axis scales in degrees, defaults to 0
xaxis.fontface	Fontface for the x-axis scales
yaxis.fontface	Fontface for the y-axis scales
xaxis.col	Colour of the x-axis tick labels, defaults to “black”
yaxis.col	Colour of the y-axis tick labels, defaults to “black”
xaxis.tck	Specifies the length of the tick mark, defaults to 1 for both top and bottom axes
yaxis.tck	Specifies the length of the tick mark, defaults to 1 for both top and bottom axes
horizontal	xyplot-specific function that allows you to change if type='h' draws lines to the vertical or horizontal axis
type	Plot type
cex	Character expansion for plotting symbol
pch	Plotting character

col	Point/line colour
lwd	Specifies line width, defaults to 1
lty	Specifies line style, defaults to 1 (solid)
alpha	Specifies line transparency, defaults to 1 (opaque)
strip.col	Strip background colour, defaults to "white"
strip.cex	Strip title character expansion
axes.lwd	Thickness of width of axis lines
axes.lty	Specifies axis line style, defaults to "dashed"
key	A list giving the key (legend). The default suppresses drawing
legend	Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See xyplot.
layout	A vector specifying the number of columns, rows (e.g., c(2,1)). Default is NULL; see lattice::xyplot for more details
as.table	Specifies panel drawing order, default is FALSE which draws panels from bottom left corner, moving right then up. Set to TRUE to draw from top left corner, moving right then downF
x.spacing	A number specifying the distance between panels along the x-axis, defaults to 0
y.spacing	A number specifying the distance between panels along the y-axis, defaults to 0
x.relation	Allows x-axis scales to vary if set to "free", defaults to "same"
y.relation	Allows y-axis scales to vary if set to "free", defaults to "same"
top.padding	A number specifying the distance to the top margin, defaults to 0
bottom.padding	A number specifying the distance to the bottom margin, defaults to 0
right.padding	A number specifying the distance to the right margin, defaults to 0
left.padding	A number specifying the distance to the left margin, defaults to 0
key.top	A number specifying the distance at top of key, defaults to 0
key.left.padding	Amount of padding to go onto any legend on the left
ylab.axis.padding	A number specifying the distance of label to the y-axis, defaults to 1
axis.key.padding	A number specifying the distance from the y-axis to the key, defaults to 1
abline.h	Allow horizontal line to be drawn, default to NULL
abline.col	Horizontal line colour, defaults to black
abline.lwd	Specifies horizontal line width, defaults to 1
abline.lty	Specifies horizontal line style, defaults to 1 (solid)
add.rectangle	Allow a rectangle to be drawn, default is FALSE
xleft.rectangle	Specifies the left x coordinate of the rectangle to be drawn
ybottom.rectangle	Specifies the bottom y coordinate of the rectangle to be drawn

xright.rectangle	Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle	Specifies the top y coordinate of the rectangle to be drawn
col.rectangle	Specifies the colour to fill the rectangle's area
alpha.rectangle	Specifies the colour bias of the rectangle to be drawn
add.points	Allow additional points to be drawn, default is FALSE
points.x	The x co-ordinates where additional points should be drawn
points.y	The y co-ordinates where additional points should be drawn
points.pch	The plotting character for additional points
points.col	The colour of additional points
points.cex	The size of additional points
add.text	Allow additional text to be drawn, default is FALSE
text.labels	Labels for additional text
text.x	The x co-ordinates where additional text should be placed
text.y	The y co-ordinates where additional text should be placed
text.col	The colour of additional text
text.cex	The size of additional text
text.fontface	The fontface for additional text
height	Figure height, defaults to 6 inches
width	Figure width, defaults to 6 inches
size.units	Figure units, defaults to inches
resolution	Figure resolution in dpi, defaults to 1600
enable.warnings	Print warnings if set to TRUE, defaults to FALSE
style	defaults to "BoutrosLab", also accepts "Nature", which changes parameters according to Nature formatting requirements
description	Short description of image/plot; default NULL
preload.default	ability to set multiple sets of different defaults depending on publication needs
use.legacy.settings	boolean to set whether or not to use legacy mode settings (font)
inside.legend.auto	boolean specifying whether or not to use the automatic inside legend function
...	Additional arguments to be passed to xyplot

Value

If filename is NULL then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of create histogram is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```
Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics
```

Author(s)

Christine P'ng, Cindy Q. Yao

See Also

[xyplot](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(12345);
simple.data <- data.frame(
  x = runif(20000, 0, 1),
  y = 1:20000
);

create.manhattanplot(
  filename = tempfile(pattern = 'Manhattan_Simple', fileext = '.tiff'),
  formula = -log10(x) ~ y,
  data = simple.data,
  main = 'Simple',
  description = 'Manhattan plot created using BoutrosLab.plotting.general',
  resolution = 50
);

# set up chromosome covariate colours to use for chr covariate, below
chr.colours <- force.colour.scheme(microarray$Chr, scheme = 'chromosome');

# make chr covariate and chr labels
chr.n.genes      <- vector();
chr.tck           <- vector();
chr.pos.genes     <- vector();
chr.break         <- vector();
chr.break[1]       <- 0;
# get a list of chromosomes to loop
chr <- unique(microarray$Chr);

# loop over each chromosome
for ( i in 1:length(chr) ) {
```

```
# get the number of genes that belong to one chromosome
n <- sum(microarray$Chr == chr[i]);

# calculate where the labels go
chr.n.genes[i]   <- n;
chr.break[i+1] <- n + chr.break[i];
chr.pos.genes[i] <- floor(chr.n.genes[i]/2);
chr.tck[i]       <- chr.pos.genes[i] + which(microarray$Chr == chr[i])[1];
}

# add an indicator function for the data-frame
microarray$ind <- 1:nrow(microarray);

# Minimal input
create.manhattanplot(
  filename = tempfile(pattern = 'Manhattan_Minimal_Input', fileext = '.tiff'),
  formula = -log10(pval) ~ ind,
  data = microarray,
  main = 'Minimal input',
  description = 'Manhattan plot created using BoutrosLab.plotting.general',
  resolution = 100
);

# Custom Axes
create.manhattanplot(
  filename = tempfile(pattern = 'Manhattan_Custom_Axes', fileext = '.tiff'),
  formula = -log10(pval) ~ ind,
  data = microarray,
  main = 'Custom axes',
  xlab.label = expression('Chromosomes'),
  ylab.label = expression('P'['adjusted']),
  xat = chr.tck,
  xaxis.lab = c(1:22, 'X', 'Y'),
  xaxis.tck = 0,
  xaxis.cex = 1,
  yaxis.cex = 1,
  yat = seq(0,5,1),
  yaxis.lab = c(
    1,
    expression(10^-1),
    expression(10^-2),
    expression(10^-3),
    expression(10^-4)
  ),
  description = 'Manhattan plot created using BoutrosLab.plotting.general',
  resolution = 100
);

# Colour scheme
create.manhattanplot(
  filename = tempfile(pattern = 'Manhattan_Colour_Scheme', fileext = '.tiff'),
  formula = -log10(pval) ~ ind,
```

```

data = microarray,
main = 'Colour scheme',
xlab.label = expression('Chromosomes'),
ylab.label = expression('P'['adjusted']),
xat = chr.tck,
xaxis.lab = c(1:22, 'X', 'Y'),
xaxis.tck = 0,
xaxis.cex = 1,
yaxis.cex = 1,
yat = seq(0,5,1),
yaxis.lab = c(
  1,
  expression(10^-1),
  expression(10^-2),
  expression(10^-3),
  expression(10^-4)
),
col = chr.colours,
description = 'Manhattan plot created using BoutrosLab.plotting.general',
resolution = 200
);

# Plotting Character
create.manhattanplot(
  filename = tempfile(pattern = 'Manhattan_Plotting_Character', fileext = '.tiff'),
  formula = -log10(pval) ~ ind,
  data = microarray,
  main = 'Plotting character',
  xlab.label = expression('Chromosomes'),
  ylab.label = expression('P'['adjusted']),
  xat = chr.tck,
  xaxis.lab = c(1:22, 'X', 'Y'),
  xaxis.tck = 0,
  xaxis.cex = 1,
  yaxis.cex = 1,
  yat = seq(0,5,1),
  yaxis.lab = c(
    1,
    expression(10^-1),
    expression(10^-2),
    expression(10^-3),
    expression(10^-4)
  ),
  col = chr.colours,
  # Change plotting character and size of plotting character
  pch = 18,
  cex = 0.75,
  description = 'Manhattan plot created using BoutrosLab.plotting.general',
  resolution = 200
);

# Line

```

```
create.manhattanplot(
    filename = tempfile(pattern = 'Manhattan_Added_Line', fileext = '.tiff'),
    formula = -log10(pval) ~ ind,
    data = microarray,
    main = 'Line',
    xlab.label = expression('Chromosomes'),
    ylab.label = expression('P'['adjusted']),
    xat = chr.tck,
    xaxis.lab = c(1:22, 'X', 'Y'),
    xaxis.tck = 0,
    xaxis.cex = 1,
    yaxis.cex = 1,
    yat = seq(0,5,1),
    yaxis.lab = c(
        1,
        expression(10^-1),
        expression(10^-2),
        expression(10^-3),
        expression(10^-4)
    ),
    col = chr.colours,
    pch = 18,
    cex = 0.75,
    # draw horizontal line
    abline.h = 2,
    abline.lty = 2,
    abline.lwd = 1,
    abline.col = 'black',
    description = 'Manhattan plot created using BoutrosLab.plotting.general',
    resolution = 200
);

# Background shading
create.manhattanplot(
    filename = tempfile(pattern = 'Manhattan_BG', fileext = '.tiff'),
    formula = -log10(pval) ~ ind,
    data = microarray,
    main = 'Bg rectangles',
    xlab.label = expression('Chromosomes'),
    ylab.label = expression('P'['adjusted']),
    xat = chr.tck,
    xaxis.lab = c(1:22, 'X', 'Y'),
    xaxis.tck = 0,
    xaxis.cex = 1,
    yaxis.cex = 1,
    yat = seq(0,5,1),
    yaxis.lab = c(
        1,
        expression(10^-1),
        expression(10^-2),
        expression(10^-3),
        expression(10^-4)
    ),
```

```

col = chr.colours,
pch = 18,
cex = 0.75,
abline.h = 2,
abline.lty = 2,
abline.lwd = 1,
abline.col = 'black',
# Adding rectangles
add.rectangle = TRUE,
xleft.rectangle = chr.break[seq(1, length(chr.break) - 1, 2)],
ybottom.rectangle = 0,
xright.rectangle = chr.break[seq(2, length(chr.break) - 1, 2)],
ytop.rectangle = 4.5,
col.rectangle = 'grey',
alpha.rectangle = 0.5,
description = 'Manhattan plot created using BoutrosLab.plotting.general',
resolution = 200
);

# Nature style
create.manhattanplot(
  filename = tempfile(pattern = 'Manhattan_Nature_style', fileext = '.tiff'),
  formula = -log10(pval) ~ ind,
  data = microarray,
  main = 'Nature style',
  xat = chr.tck,
  xaxis.lab = c(1:22, 'X', 'Y'),
  xaxis.tck = 0,
  xaxis.cex = 1,
  yaxis.cex = 1,
  yat = seq(0,5,1),
  yaxis.lab = c(
    1,
    expression(10^-1),
    expression(10^-2),
    expression(10^-3),
    expression(10^-4)
  ),
  col = chr.colours,
  pch = 18,
  cex = 0.75,
  abline.h = 2,
  abline.lty = 2,
  abline.lwd = 1,
  abline.col = 'black',
  # Adding rectangles
  add.rectangle = TRUE,
  xleft.rectangle = chr.break[seq(1, length(chr.break) - 1, 2)],
  ybottom.rectangle = 0,
  xright.rectangle = chr.break[seq(2, length(chr.break) - 1, 2)],
  ytop.rectangle = 4.5,
  col.rectangle = 'grey',
  alpha.rectangle = 0.5,

```

```
# set style to Nature
style = 'Nature',

# demonstrating how to italicize character variables
ylab.label = expression(paste('italicized ', italic('a'))),

# demonstrating how to create en-dashes
xlab.label = expression(paste('en dashes: 1', '\u2013', '10' '^' '\u2013', '''^3)),

description = 'Manhattan plot created using BoutrosLab.plotting.general',
resolution = 1200
);
```

create.multipanelplot *Joins plots together*

Description

Merges together multiple plots in the specified layout

Usage

```
create.multipanelplot(
  plot.objects = NULL,
  filename = NULL,
  height = 10,
  width = 10,
  resolution = 1000,
  plot.objects.heights = c(rep(1,layout.height)),
  plot.objects.widths = c(rep(1,layout.width)),
  layout.width = 1,
  layout.height = length(plot.objects),
  main = '',
  main.x = 0.5,
  main.y = 0.5,
  x.spacing = 0,
  y.spacing = 0,
  xlab.label = '',
  xlab.cex = 2,
  ylab.label = '',
  ylab.label.right = '',
  ylab.cex = 2,
  main.cex = 3,
  legend = NULL,
  left.padding = 0,
  ylab.axis.padding = c(rep(0, layout.width)),
```

```

xlab.axis.padding = c(rep(0, layout.height)),
bottom.padding = 0,
top.padding = 0,
right.padding = 0,
layout.skip = c(rep(FALSE, layout.width*layout.height)),
left.legend.padding = 2,
right.legend.padding = 2,
bottom.legend.padding = 2,
top.legend.padding = 2,
description = 'Created with BoutrosLab.plotting.general',
size.units = 'in',
enable.warnings = FALSE,
style = "BoutrosLab",
use.legacy.settings = FALSE
);

```

Arguments

<code>plot.objects</code>	A list of plot objects. Goes in this order: Top Left, Top Right, Bottom Left, Bottom Right
<code>filename</code>	Filename to output to
<code>height</code>	Height of resulting file
<code>width</code>	Width of resulting file
<code>resolution</code>	Resolution of resulting file
<code>plot.objects.heights</code>	Heights of each row of the plot. Must be vector of same size as <code>layout.height</code>
<code>plot.objects.widths</code>	Widths of each column of the plot. Must be vector of same size as <code>layout.width</code>
<code>layout.width</code>	how many plots per row.
<code>layout.height</code>	how many plots per column
<code>main</code>	main label text
<code>main.x</code>	main label x coordinate
<code>main.y</code>	main label y coordinate
<code>x.spacing</code>	horizontal spacing between each plot. Can be single value or vector of length <code>layout.width - 1</code>
<code>y.spacing</code>	vertical spacing between each plot. Can be single value or vector of length <code>layout.height - 1</code>
<code>xlab.label</code>	bottom x-axis main label
<code>xlab.cex</code>	bottom x-axis main label cex
<code>ylab.label</code>	left side y-axis label
<code>ylab.label.right</code>	right side y-axis label
<code>ylab.cex</code>	y-axis label cex

```

main.cex      main label cex
legend        legend for the plot
left.padding  padding from the left side of the frame
ylab.axis.padding
              padding between axis and y label of plots. Can be single value or vector of
              length layout.width
xlab.axis.padding
              padding between axis and x label of plots. Can be single value or vector of
              length layout.height
bottom.padding padding from the bottom side of the frame
top.padding   padding from the top side of the frame
right.padding padding from the right side of the frame
layout.skip   list specifying locations to skip plots. Must be vector of length layout.width*layout.height
left.legend.padding
              padding between legend and left side of figure (can use without a legend)
right.legend.padding
              padding between legend and right side of figure (can use without a legend)
bottom.legend.padding
              padding between legend and bottom side of figure (can use without a legend)
top.legend.padding
              padding between legend and top side of figure (can use without a legend)
description   description of what plot is displaying
size.units    the units the height and width of file represent
enable.warnings
              enables warnings to be output
style         defaults to "BoutrosLab", also accepts "Nature", which changes parameters ac-
              cording to Nature formatting requirements
use.legacy.settings
              boolean to set wheter or not to use legacy mode settings (font)

```

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of create histogram is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```

Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x,  )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics

```

Author(s)

Jeff Green

Examples

```

set.seed(12345);
# begin by creating the individual plots which will be combined into a multiplot
dist <- data.frame(
  a = rnorm(100, 1),
  b = rnorm(100, 3),
  c = rnorm(100, 5)
);

simple.data <- data.frame(
  x = c(dist$a, dist$b, dist$c),
  y = rep(LETTERS[1:3], each = 100)
);
fill.squares <- matrix(c(1, 0, 0, 0, 1, 0, 0, 0, 1), ncol = 3, byrow = TRUE);
rownames(fill.squares) <- c("Drug I only", "Drug II only", "Drugs I & II");
colnames(fill.squares) <- levels(factor(simple.data$y));

# Create plot # 1
simple.boxplot <- create.boxplot(
  formula = x ~ y,
  data = simple.data,
  xaxis.lab = c('','',''),
  main.x = 0.57,
  ylab.label = 'Sugar Level',
  xlab.label = '',
  col = 'lightgrey',
  xaxis.tck = c(0,0),
  yaxis.tck = c(1,0),
  yaxis.lab = seq(-1,8,2) ,
  yat = seq(-1,8,2),
  left.padding = 0,
  right.padding = 0,
  lwd = 2
);

# Create plot # 2
simple.heatmap <- create.heatmap(
  x = t(fill.squares),
  clustering.method = 'none',
  shrink = 0.8,
  yaxis.lab = c(3,2,3),
  yaxis.tck = 1,
  xaxis.lab = c('A','B','C'),
  ylab.label = 'Drug Regimen',
  xlab.label = 'Patient Group',
  colour.scheme = c("white", "grey20"),
  fill.colour = "white",
  print.colour.key = FALSE,
  left.padding = 0,
  xaxis.tck = c(1,0),
  right.padding = 0,
  xaxis.rot = 0
)

```

```
);

create.multipanelplot(
  filename = tempfile(pattern = 'Multipanelplot_Simple', fileext = '.tiff'),
  plot.objects = list(simple.boxplot,simple.heatmap),
  y.spacing = 1,
  ylab.axis.padding = 2,
  main = 'Simple',
  top.padding = 2,
  resolution = 200
);

# Create plot # 2
simple.heatmap.with.legends <- create.heatmap(
  x = t(fill.squares),
  shrink = 0.8,
  yaxis.lab = c(3,2,3),
  yaxis.tck = 1,
  xaxis.lab = c('A','B','C'),
  ylab.label = 'Drug Regimen',
  xlab.label = '',
  colour.scheme = c("white", "grey20"),
  fill.colour = "white",
  left.padding = 0,
  xaxis.tck = c(1,0),
  right.padding = 0,
  xaxis.rot = 0
);

create.multipanelplot(
  filename = tempfile(pattern = 'Multipanelplot_Simple_Legends', fileext = '.tiff'),
  plot.objects = list(simple.boxplot,simple.heatmap.with.legends),
  y.spacing = 1,
  ylab.axis.padding = 2,
  main = 'Simple',
  top.padding = 2,
  resolution = 200
);

# Create plot # 1
simple.boxplot2 <- create.boxplot(
  formula = x ~ y,
  data = simple.data,
  ylab.label = 'Sugar Level',
  xlab.label = '',
  col = 'lightgrey',
  xaxis.tck = c(0,0),
  xaxis.lab = c('','',''),
  yaxis.tck = c(1,0),
  yaxis.lab = seq(-1,8,2),
  yat = seq(-1,8,2),
  left.padding = 0,
```

```

    right.padding = 0,
    lwd = 2
  );

simple.violin2 <- create.violinplot(
  formula = x ~ y,
  data = simple.data,
  col = 'lightgrey',
  yaxis.tck = c(0,0),
  xlab.label = '',
  ylab.label = '',
  yaxis.lab = NULL,
  xaxis.lab = c('','',''),
  xaxis.tck = c(0,0)
);

# Create plot # 2
simple.heatmap2 <- create.heatmap(
  x = t(fill.squares),
  clustering.method = 'none',
  shrink = 0.8,
  yaxis.lab = c(1,2,3),
  yaxis.tck = 1,
  xaxis.lab = c('A','B','C'),
  ylab.label = 'Drug Regimen',
  colour.scheme = c("white", "grey20"),
  fill.colour = "white",
  print.colour.key = FALSE,
  left.padding = 0,
  xaxis.tck = c(3,0),
  right.padding = 0,
  xaxis.rot = 0,
  ylab.cex = 2
);

create.multipanelplot(
  filename = tempfile(pattern = 'Multipanelplot_Simple_Layout', fileext = '.tiff'),
  plot.objects = list(simple.boxplot2,
  simple.violin2,simple.heatmap2),
  layout.width = 2,
  layout.height = 2,
  xlab.label = 'Patient Group',
  main = 'Simple Layout',
  top.padding = 2,
  plot.objects.heights = c(3,1),
  x.spacing = 1,
  y.spacing = 1
);

all.data <- data.frame(
  a = rnorm(n = 25, mean = 0, sd = 0.75),
  b = rnorm(n = 25, mean = 0, sd = 0.75),

```

```
c = rnorm(n = 25, mean = 0, sd = 0.75),
d = rnorm(n = 25, mean = 0, sd = 0.75),
e = rnorm(n = 25, mean = 0, sd = 0.75),
f = rnorm(n = 25, mean = 0, sd = 0.75),
x = rnorm(n = 25, mean = 5),
y = seq(1, 25, 1)
);
# create the plot -- this allows for previewing of the individual plot
barplot.formatted <- create.barplot(
  formula = x ~ y,
  data = all.data[,7:8],
  yaxis.tck = c(1,0),
  border.lwd = 0,
  col = 'grey',
  xlab.label = '',
  xat = c(-100),
  ylab.label = '',
  yaxis.lab = seq(1, ceiling(max(all.data$x)), 1),
  yat = seq(1, ceiling(max(all.data$x)), 1),
  yaxis.cex = 1.5
);

heatmap.formatted <- create.heatmap(
  x = all.data[,1:6],
  clustering.method = 'none',
  colour.scheme = c('magenta','white','green'),
  print.colour.key = FALSE,
  xlab.label = '',
  yaxis.tck = c(1,0),
  xaxis.tck = c(1,0),
  xat = c(1:25),
  yaxis.lab = c("BRCA1", "BRCA2", "APC", "TIN", "ARG", "FOO"),
  yat = c(1,2,3,4,5,6),
  xaxis.lab = c(1:25),
  xaxis.rot = 0,
  yaxis.cex = 1.5
);

create.multipanelplot(
  filename = tempfile(pattern = 'Multipanelplot_formatted', fileext = '.tiff'),
  plot.objects = list(barplot.formatted, heatmap.formatted),
  plot.objects.heights = c(1,3),
  y.spacing = -3.75,
  main = 'Formatted',
  top.padding = 0
);

data.bars <- data.frame(
  x = sample(x = 5:35, size = 10),
  y = seq(1,10,1)
);
```

```

data.cov <- data.frame(
  x = rnorm(n = 10, mean = 0, sd = 0.75),
  y = rnorm(n = 10, mean = 0, sd = 0.75),
  z = rnorm(n = 10, mean = 0, sd = 0.75)
);

# Create main barplot
bars <- create.barplot(
  formula = x~y,
  data = data.bars,
  ylims = c(0,35),
  ylab.label = '',
  sample.order = 'increasing',
  border.lwd = 0,
  yaxis.lab = seq(5,35,5),
  yat = seq(5,35,5),
  yaxis.tck = c(0,0),
  xlab.label = ''
);

# Make covariate bars out of heatmaps
cov.1 <- create.heatmap(
  x = as.matrix(data.bars$y),
  clustering.method = 'none',
  scale.data = FALSE,
  colour.scheme = default.colours(4),
  grid.col = TRUE,
  col.colour = 'black',
  # col.lwd = 10,
  total.col = 5,
  print.colour.key = FALSE,
  yaxis.tck = 0,
  axes.lwd = 0
);

cov.2 <- create.heatmap(
  x = as.matrix(data.cov$y),
  clustering.method = 'none',
  scale.data = FALSE,
  colour.scheme = c("lightblue", "dodgerblue2", "dodgerblue4"),
  grid.col = TRUE,
  col.colour = 'black',
  # col.lwd = 10,
  total.col = 4,
  print.colour.key = FALSE,
  yaxis.tck = 0
);

cov.3 <- create.heatmap(
  x = as.matrix(data.cov$z),
  clustering.method = 'none',
  scale.data = FALSE,
  colour.scheme = c("grey", "coral1"),

```

```
grid.col = TRUE,
col.colour = 'black',
# col.lwd = 10,
total.col = 3,
print.colour.key = FALSE,
yaxis.tck = 0
);

legendG <- legend.grob(
list(
  legend = list(
    colours = default.colours(4),
    title = "Batch",
    labels = LETTERS[1:4],
    size = 3,
    title.cex = 1,
    label.cex = 1,
    border = 'black'
  ),
  legend = list(
    colours = c("lightblue","dodgerblue2","dodgerblue4"),
    title = "Grade",
    labels = c("Low","Normal","High"),
    size = 3,
    title.cex = 1,
    label.cex = 1,
    border = 'black'
  ),
  legend = list(
    colours = c("grey","coral1"),
    title = "Biomarker",
    labels = c("Not present","Present"),
    size = 3,
    title.cex = 1,
    label.cex = 1,
    border = 'black'
  )
),
label.cex = 1.25,
title.cex = 1.25,
title.just = 'left',
title.fontface = 'bold.italic',
size = 3,
layout = c(1,3)
);

create.multipanelplot(
filename = tempfile(pattern = 'Multipanelplot_Barchart', fileext = '.tiff'),
plot.objects = list(bars, cov.3, cov.2, cov.1 ),
plot.objects.heights = c(1, 0.1,0.1,0.1),
legend = list(right = list(fun = legendG)),
ylab.label = 'Response to Treatment',
```

```

main = 'Bar Chart',
x.spacing = 0,
y.spacing = 0.1
);

# Set up plots for complex example

# Dotmap
spot.sizes <- function(x) { 0.5 * abs(x); }
dotmap.dot.colours <- c('red','blue');
spot.colours <- function(x) {
  colours <- rep('white', length(x));
  colours[sign(x) == -1] <- dotmap.dot.colours[1];
  colours[sign(x) == 1] <- dotmap.dot.colours[2];
  return(colours);
};

# Dotmap colours
orange <- rgb(249/255, 179/255, 142/255);
blue <- rgb(154/255, 163/255, 242/255);
green <- rgb(177/255, 213/255, 181/255);
bg.colours <- c(green, orange, blue, 'gold', 'skyblue', 'plum');

dotmap <- create.dotmap(
  x = CNA[1:15,1:58],
  bg.data = SNV[1:15,1:58],
  # Set the colour scheme
  colour.scheme = bg.colours,
  # Set the breakpoints for the colour scheme (determined from the data)
  at = c(0,1,2,4,6,7,8),
  # Specify the total number of colours (+1 for the fill colour)
  total.colours = 7,
  col.colour = 'white',
  row.colour = 'white',
  bg.alpha = 1,
  yaxis.tck = c(1,0),
  fill.colour = 'grey95',
  spot.size.function = spot.sizes,
  spot.colour.function = spot.colours,
  xaxis.tck = 0,
  xaxis.lab = c(rep('',100)),
  bottom.padding = 0,
  top.padding = 0,
  left.padding = 0,
  right.padding = 0,
  yaxis.cex = 1
);

# Dotmap legend
dotmap.legend <- list(
  legend = list(
    colours = bg.colours,
    labels = c('Nonsynonymous', 'Stop Gain', 'Frameshift deletion',

```

```
    'Nonframeshift deletion', 'Splicing', 'Unknown'),
    border = 'white',
    title = 'SNV',
    pch = 15
  ),
  legend = list(
    colours = dotmap.dot.colours,
    labels = c('Gain','Loss'),
    border = 'white',
    title = 'CNA',
    pch = 19
  )
);

dotmap.legend.grob <- legend.grob(
  legends = dotmap.legend,
  title.just = 'left',
  label.cex = 0.7,
  title.cex = 0.7
);

# Covariates
cov.colours <- c(
  c('dodgerblue','pink'),
  c('grey','darkseagreen1','seagreen2','springgreen3','springgreen4'),
  c('peachpuff','tan4')
);

# the heatmap expects numeric data
cov.data <- patient[-c(4:9)];
cov.data[cov.data == 'male'] <- 1;
cov.data[cov.data == 'female'] <- 2;
cov.data[is.na(cov.data)] <- 3;
cov.data[cov.data == 'I'] <- 4;
cov.data[cov.data == 'II'] <- 5;
cov.data[cov.data == 'III'] <- 6;
cov.data[cov.data == 'IV'] <- 7;
cov.data[cov.data == 'MSS'] <- 8;
cov.data[cov.data == 'MSI-High'] <- 9;
cov.data$sex <- as.numeric(cov.data$sex);
cov.data$stage <- as.numeric(cov.data$stage);
cov.data$msi <- as.numeric(cov.data$msi);

covariates <- create.heatmap(
  x = cov.data,
  clustering.method = 'none',
  colour.scheme = as.vector(cov.colours),
  total.colours = 10,
  row.colour = 'white',
  col.colour = 'white',
  grid.row = TRUE,
  grid.col = TRUE,
  xaxis.lab = c(rep('',100)),
```

```

yaxis.lab = c('Sex','Stage','MSI'),
yaxis.tck = c(0,0),
xaxis.tck = c(0,0),
xat = c(1:100),
print.colour.key = FALSE,
yaxis.cex = 1,
bottom.padding = 0,
top.padding = 0,
left.padding = 0,
right.padding = 0
);

## Warning: number of columns exceeded limit (50), column lines are
## turned off. Please set "force.grid.col" to TRUE to override this

# Coviate Legends
cov.legends <- list(
  legend = list(
    colours = cov.colours[8:9],
    labels = c('MSS','MSI-High'),
    border = 'white',
    title = 'MSI'
  ),
  legend = list(
    colours = cov.colours[3:7],
    labels = c('NA', 'I','II','III','IV'),
    border = 'white',
    title = 'Stage'
  ),
  legend = list(
    colours = cov.colours[1:2],
    labels = c('Male','Female'),
    border = 'white',
    title = 'Sex'
  )
);

cov.legend.grob <- legend.grob(
  legends = cov.legends,
  title.just = 'left',
  label.cex = 0.7,
  title.cex = 0.7,
  layout = c(3,1)
);

create.multipanelplot(
  filename = tempfile(pattern = 'Multipanelplot_with_heatmap', fileext = '.tiff'),
  plot.objects = list(dotmap,covariates),
  plot.objects.heights = c(1,0.2),
  y.spacing = -0.8,
  main = 'Dotmap',
  top.padding = 2,

```

```
layout.height = 2,
legend = list(
  bottom = list(
    x = 0.10,
    y = 0.50,
    fun = cov.legend.grob
  ),
  right = list(
    x = 0.10,
    y = 0.50,
    fun = dotmap.legend.grob
  )
),
resolution = 300
);

# Add more plots, using more complex layout
# grouped barplot
groupedbar.colours <- c('indianred1','indianred4');

count.SNV <- apply(SNV[1:15,], 2, function(x){length(which(!is.na(x)))});
count.CNA <- apply(CNA[1:15,], 2, function(x){length(which(!(x==0)))});

grouped.data <- data.frame(
  values = c(count.SNV, count.CNA),
  samples = rep(colnames(SNV),2),
  group = rep(c('SNV','CNA'), each = 58)
);

grouped.barplot <- create.barplot(
  formula = values ~ samples,
  data = grouped.data,
  groups = grouped.data$group,
  col = groupedbar.colours,
  top.padding = 0,
  bottom.padding = 0,
  left.padding = 0,
  right.padding = 0,
  border.col = 'white',
  xlab.label = '',
  ylab.label = 'Mutation',
  yaxis.lab = c(0,5,10,15),
  yat = c(0,5,10,15),
  xaxis.lab = c(rep('',100)),
  yaxis.tck = c(0,0),
  xaxis.tck = c(0,0),
  ylab.cex = 1.5,
  yaxis.cex = 1,
  axes.lwd = 2
);

# stacked barplot
col.one <- rgb(255/255, 225/255, 238/255);
```

```

col.two <- rgb(244/255, 224/255, 166/255);
col.thr <- rgb(177/255, 211/255, 154/255);
col.fou <- rgb(101/255, 180/255, 162/255);
col.fiv <- rgb(51/255, 106/255, 144/255);
stackedbar.colours <- c(col.one, col.two, col.thr, col.fou, col.fiv, 'orchid4');
stacked.data.labels <- c('C>A/G>T', 'C>T/G>A', 'C>G/G>C', 'T>A/A>T', 'T>G/A>C', 'T>C/A>G');

stacked.data <- data.frame(
  values = c(patient$prop.CAGT, patient$prop.CTGA, patient$prop.CGGC, patient$prop.TAAT,
             patient$prop.TGAC, patient$prop.TCAG),
  divisions = rep(rownames(patient), 6),
  group = rep(stacked.data.labels, each = 58)
);

# Generate stacked barplot
stacked.barplot <- create.barplot(
  formula = values ~ divisions,
  data = stacked.data,
  groups = stacked.data$group,
  stack = TRUE,
  col = stackedbar.colours,
  border.col = 'white',
  main = '',
  xlab.label = '',
  ylab.label = 'Proportion',
  yaxis.lab = c(0,0.4,0.8),
  yat = c(0,0.4,0.8),
  xaxis.lab = c(rep('',100)),
  yaxis.tck = c(0,0),
  xaxis.tck = c(0,0),
  ylab.cex = 1.5,
  yaxis.cex = 1,
  axes.lwd = 2
);

# barchart legends
stackedbar.legend <- list(
  legend = list(
    colours = rev(stackedbar.colours),
    labels = rev(stacked.data.labels),
    border = 'white'
  )
);

groupedbar.legend <- list(
  legend = list(
    colours = groupedbar.colours,
    labels = c('CNA','SNV'),
    border = 'white'
  )
);

groupedbar.legend.grob <- legend.grob(

```

```
legends = groupedbar.legend,
title.just = 'left',
label.cex = 0.7,
title.cex = 0.7
);

stackedbar.legend.grob <- legend.grob(
  legends = stackedbar.legend,
  title.just = 'left',
  label.cex = 0.7,
  title.cex = 0.7
);

# Expression change Segplot
# locate matching genes
rows.to.keep <- which(match(rownames(microarray), rownames(SNV)[1:15], nomatch = 0) > 0);

segplot.data <- data.frame(
  min = apply(microarray[rows.to.keep,1:58], 1, min),
  max = apply(microarray[rows.to.keep,1:58], 1, max),
  median = apply(microarray[rows.to.keep,1:58], 1, median),
  order = seq(1,15,1)
);

segplot <- create.segplot(
  formula = order ~ min + max,
  data = segplot.data,
  main = '',
  xlab.label = '',
  ylab.label = '',
  centers = segplot.data$median,
  yaxis.lab = c('','','','','',''),
  xaxis.lab = c('0','2','4','6','8'),
  xat = c(0,2,4,6,8),
  yaxis.tck = c(0,0),
  xaxis.tck = c(1,0),
  axes.lwd = 2,

  top.padding = 0,
  left.padding = 0,
  right.padding = 0,
  bottom.padding = 0
);
# Create multiplot

plots <- list(grouped.barplot,stacked.barplot,dotmap, segplot,covariates);
create.multipanelplot(
  main.x = 0.47,
  main.y = 0.5,
  plot.objects = plots,
  plot.objects.heights = c(0.3, 0.3, 1, 0.15),
  plot.objects.widths = c(1,0.2),
  filename = tempfile(pattern = 'Multipanelplot_Complex', fileext = '.tiff'),
```

```

layout.height = 4,
layout.width = 2,
x.spacing = 0.2,
left.padding = 0,
layout.skip = c(FALSE,TRUE,FALSE,TRUE, FALSE, FALSE, TRUE),
y.spacing = c(-1.35,-1.35,-1.5),
ylab.axis.padding = c(1,0),
legend = list(
  left = list(
    fun = dotmap.legend.grob,
    args = list(
      key = list(
        points = list(
          pch = c(15,15,19,19)
        )
      )
    )
  )
),
height = 12,
width = 12,
main = 'Complex',
top.padding = 2
);
# Create a multiplot with a heatmap, key like legend and barplot

# First create a heatmap object
simple.heatmap <- create.heatmap(patient[, 4:6],
  clustering.method = 'none',
  print.colour.key = FALSE,
  same.as.matrix = FALSE,
  colour.scheme = c('gray0','grey100'),
  fill.colour = 'grey95',
  xaxis.lab = c(rep('',100)),
  xat = c(0,1,2,3,4,5,6,7,8),
  yaxis.lab = c('',',',''),
  yat = c(0,1,2),
  xlab.label = ''
);

# and a simple bar plot
pvals <- data.frame(
  order = c(1:3),
  pvalue = -log10(c(0.0004, 0.045, 0.0001)),
  stringsAsFactors = FALSE
)
#create bar plot
simple.bar <- create.barplot(
  formula = order ~ rev(pvalue),
  data = pvals,
  xlims = c(0,5),
  plot.horizontal=TRUE,

```

```
    xlab.label = '',
    ylab.label = '',
    yaxis.lab = c(1,2,3)
  );

# then the covariates heatmap
cov.colours <- c(
  c('dodgerblue','pink'),
  c('grey','darkseagreen1','seagreen2','springgreen3','springgreen4'),
  c('peachpuff','tan4')
);

# the heatmap expects numeric data
cov.data <- patient[-c(4:9)];
cov.data[cov.data == 'male'] <- 1;
cov.data[cov.data == 'female'] <- 2;
cov.data[is.na(cov.data)] <- 3;
cov.data[cov.data == 'I'] <- 4;
cov.data[cov.data == 'II'] <- 5;
cov.data[cov.data == 'III'] <- 6;
cov.data[cov.data == 'IV'] <- 7;
cov.data[cov.data == 'MSS'] <- 8;
cov.data[cov.data == 'MSI-High'] <- 9;
cov.data$sex <- as.numeric(cov.data$sex);
cov.data$stage <- as.numeric(cov.data$stage);
cov.data$msi <- as.numeric(cov.data$msi);

covariates <- create.heatmap(
  x = cov.data,
  clustering.method = 'none',
  colour.scheme = as.vector(cov.colours),
  total.colours = 10,
  row.colour = 'white',
  col.colour = 'white',
  grid.row = TRUE,
  grid.col = TRUE,
  yaxis.tck = 0,
  print.colour.key = FALSE,
  xaxis.lab = c('','',''),
  xlab.label = '',
  xat = c(1,2,3)
);

## Warning: number of columns exceeded limit (50), column
## lines are turned off. Please set "force.grid.col" to TRUE to override this

covariates2 <- create.heatmap(
  x = patient[4],
  clustering.method = 'none',
  colour.scheme = c("#00007F", "#007FFF"),
  row.colour = 'white',
  col.colour = 'white',
  grid.row = TRUE,
```

```

grid.col = TRUE,
yaxis.tck = 0,
print.colour.key = FALSE,
xaxis.lab = c('','',''),
xlab.label = '',
xat = c(1,2,3)
);

## Warning: number of rows exceeded limit (50), row
## lines are turned off. Please set "force.grid.row" to TRUE to override this

cov.legends <- list(
  legend = list(
    colours = c("white", "black"),
    labels = c('0','2'),
    border = 'grey',
    title = 'Tumour Mass (kg)',
    continuous = TRUE,
    height = 3
  ),
  legend = list(
    colours = cov.colours[8:9],
    labels = c('MSS','MSI-High'),
    border = 'white',
    title = 'MST'
  ),
  legend = list(
    colours = cov.colours[3:7],
    labels = c('NA', 'I','II','III','IV'),
    border = 'white',
    title = 'Stage'
  ),
  legend = list(
    colours = cov.colours[1:2],
    labels = c('Male','Female'),
    border = 'white',
    title = 'Sex'
  ),
  legend = list(
    colours = c("#00007F", "#007FFF"),
    labels = c('0.09','0.72'),
    border = 'grey',
    title = 'CAGT',
    continuous = TRUE,
    height = 2,
    width = 3,
    angle = -90,
    tck = 1,
    tck.number = 2,
    at = c(0,100)
  )
);

```

```
cov.legend.grob <- legend.grob(
  legends = cov.legends,
  title.just = 'left',
  label.cex = 0.7,
  title.cex = 0.7
);

# Now bring it was together using multiplot
create.multipanelplot(
  filename = tempfile(pattern = 'Multipanelplot_continousLegend', fileext = '.tiff'),
  plot.objects = list(simple.heatmap, simple.bar,covariates2,covariates),
  plot.objects.heights = c(1,0.1,0.35),
  plot.objects.widths = c(1,0.25),
  layout.height = 3,
  layout.width = 2,
  layout.skip = c(FALSE, FALSE,FALSE,TRUE,FALSE,TRUE),
  y.spacing = -0.1,
  x.spacing = 0.5,
  legend = list(
    left = list(
      fun = cov.legend.grob
    )
  ),
  main = 'Continous Legend',
  top.legend.padding = 4,
  top.padding = -2,
  left.padding = 1
  # This parameter must be set for the legend to appear
);

create.multipanelplot(
  filename = tempfile(pattern = 'Multipanelplot_manyPlots', fileext = '.tiff'),
  main = 'Large Scale',
  plot.objects = list(
    simple.boxplot,
    simple.heatmap,
    simple.bar,
    barplot.formatted,
    dotmap,
    grouped.barplot,
    stacked.barplot,
    covariates,
    covariates2,
    heatmap.formatted
  ),
  plot.objects.heights = c(1,1,1,1),
  plot.objects.widths = c(1,1, 1,1),
  layout.height = 4,
  layout.width = 4,
  top.legend.padding = 3,
  layout.skip = c(FALSE, FALSE,FALSE,TRUE,FALSE,TRUE,
  TRUE,FALSE,FALSE,TRUE,FALSE,FALSE,TRUE,TRUE),
```

```

y.spacing = c(-1,-1,-1),
x.spacing = c(1,2,3),
legend = list(
  left = list(
    fun = cov.legend.grob
  )
),
height = 12,
width = 12
# This parameter must be set for the legend to appear
);

```

create.multiplot *Joins plots together*

Description

Merges together multiple plots in the specified layout

Usage

```

create.multiplot(
  plot.objects,
  filename = NULL,
  panel.heights = c(1,1),
  panel.widths = 1,
  main = NULL,
  main.just = "center",
  main.x = 0.5,
  main.y = 0.5,
  main.cex = 3,
  main.key.padding = 1,
  ylab.padding = 5,
  xlab.padding = 5,
  xlab.to.xaxis.padding = 2,
  right.padding = 1,
  left.padding = 1,
  top.padding = 0.5,
  bottom.padding = 0.5,
  xlab.label = NULL,
  ylab.label = NULL,
  xlab.cex = 2,
  ylab.cex = 2,
  xlab.top.label = NULL,
  xaxis.top.tck.lab = NULL,
  xat.top = TRUE,

```

```
xlab.top.cex = 2,  
xaxis.top.idx = NULL,  
xlab.top.col = 'black',  
xlab.top.just = "center",  
xlab.top.x = 0.5,  
xlab.top.y = 0,  
xaxis.cex = 1.5,  
yaxis.cex = 1.5,  
xaxis.labels = TRUE,  
yaxis.labels = TRUE,  
xaxis.alternating = 1,  
yaxis.alternating = 1,  
xat = TRUE,  
yat = TRUE,  
xlims = NULL,  
ylims = NULL,  
xaxis.rot = 0,  
xaxis.rot.top = 0,  
xaxis.fontface = 'bold',  
y.tck.dist=0.5,  
x.tck.dist=0.5,  
yaxis.fontface = 'bold',  
x.spacing = 1,  
y.spacing = 1,  
x.relation = 'same',  
y.relation = 'same',  
xaxis.tck = c(0.75,0.75),  
yaxis.tck = c(0.75,0.75),  
axes.lwd = 1.5,  
key.right.padding = 1,  
key.left.padding = 1,  
key.bottom.padding = 1,  
xlab.key.padding = 0.5,  
height = 6,  
width = 6,  
size.units = 'in',  
resolution = 1600,  
enable.warnings = FALSE,  
key = list(text = list(list(lab = c('')))),  
legend = NULL,  
print.new.legend = FALSE,  
merge.legends = FALSE,  
plot.layout = c(1,length(plot.objects)),  
layout.skip=rep(FALSE,length(plot.objects)),  
description = 'Created with BoutrosLab.plotting.general',  
plot.labels.to.retrieve = NULL,  
style = 'BoutrosLab',  
remove.all.border.lines = FALSE,
```

```

preload.default = 'custom',
plot.for.carry.over.when.same = 1,
get.dendrogram.from = NULL,
dendrogram.right.size = NULL,
dendrogram.right.x = NULL,
dendrogram.right.y = NULL,
  dendrogram.top.size = NULL,
  dendrogram.top.x = NULL,
  dendrogram.top.y = NULL,
  use.legacy.settings = FALSE
);

```

Arguments

<code>plot.objects</code>	A list of plot objects. Goes in this order: Bottom Left, Bottom Right, Top Left, Top Right
<code>filename</code>	Filename for tiff output, or if NULL returns the trellis object itself
<code>panel.heights</code>	A vector specifying relative heights of the panels. Default is c(1,1)
<code>panel.widths</code>	A vector specifying relative widths of the panels. Default is 1
<code>main</code>	The main title for the plot (space is reclaimed if NULL)
<code>main.just</code>	The justification of the main title for the plot, default is centered
<code>main.x</code>	The x location of the main title, default is 0.5
<code>main.y</code>	The y location of the main title, default is 0.5
<code>main.cex</code>	Size of text for main plot title, defaults to 3
<code>main.key.padding</code>	A number specifying the distance of main to plot, defaults to 1
<code>ylab.padding</code>	A number specifying the distance of y-axis to plot, defaults to 5
<code>xlab.padding</code>	A number specifying the distance of x-axis to plot, defaults to 5
<code>xlab.to.xaxis.padding</code>	A number specifying the distance between xaxis and xlabel, defaults to 2
<code>right.padding</code>	A number specifying the distance to the right margin, defaults to 1
<code>left.padding</code>	A number specifying the distance to the left margin, defaults to 1
<code>top.padding</code>	A number specifying the distance to the top margin, defaults to 0.5
<code>bottom.padding</code>	A number specifying the distance to the bottom margin, defaults to 0.5
<code>xlab.label</code>	The label for the x-axis
<code>ylab.label</code>	The label for the y-axis
<code>xlab.cex</code>	Size of x-axis labels, defaults to 1.5
<code>ylab.cex</code>	Size of y-axis labels, defaults to 1.5
<code>xlab.top.label</code>	The label for the top x-axis
<code>xaxis.top.tck.lab</code>	A vector of tick labels for the top x-axis. Currently only supports labelling a single top x-axis in the plot

xat.top	A vector specifying tick positions for the top x-axis. Currently only supports a single top x-axis in the plot. Note when labelling a top x-axis even if you're not labelling a bottom x-axis labels xat must still be defined (eg as a list of empty vectors) or it will lead to unpredictable labelling
xlab.top.cex	Size of top x-axis label
xaxis.top.idx	Index of the plot for which you want top x-axis tick labels. Defaults to the last plot specified. Currently only supports one plot.
xlab.top.col	Colour of the top x-axis label
xlab.top.just	Justification of the top x-axis label, defaults to centered
xlab.top.x	The x location of the top x-axis label
xlab.top.y	The y location of the top y-axis label
xaxis.cex	Size of x-axis scales, defaults to 2
yaxis.cex	Size of y-axis scales, defaults to 2
xaxis.labels	Names to give the x-axis labels, defaults to lattice default behaviour
yaxis.labels	Names to give the y-axis labels, defaults to lattice default behaviour
xaxis.alternating	Gives control of axis tick marks (1 bottom only, 2 top only, 3 both top and bottom), default to 1 which means only bottom axis tick marks are drawn, set to 0 to remove tick marks
yaxis.alternating	Gives control of axis labelling, defaults to 1 which means only left axis labels are drawn, set to 0 to remove tick marks
xat	Vector listing where the x-axis labels should be drawn
yat	Vector listing where the y-axis labels should be drawn
xlimits	Vector listing where the x-axis limits should be for each subplot. Defaults to NULL to let R figure out the limits
ylimits	Vector listing where the y-axis limits should be for each subplot. Defaults to NULL to let R figure out the limits
xaxis.rot	Rotation of bottom x-axis labels
xaxis.rot.top	Rotation of top x-axis labels
xaxis.fontface	Fontface for the x-axis scales
yaxis.fontface	Fontface for the y-axis scales
x.spacing	A number specifying the horizontal distance between plots, defaults to 1
y.spacing	A number specifying the vertical distance between plots, defaults to 1
x.relation	A character string that determines how x-axis limits are calculated for each panel. Possible values are "same" (default), "free" and "sliced". See ?xyplot
y.relation	A character string that determines how y-axis limits are calculated for each panel. Possible values are "same" (default), "free" and "sliced". See ?xyplot
xaxis.tck	A vector of length 2 that determines the size of x-axis tick marks. Defaults to c(0.75, 0.75).

<code>yaxis.tck</code>	A vector of length 2 that determines the size of y-axis tick marks. Defaults to <code>c(0.75, 0.75)</code> .
<code>x.tck.dist</code>	A number specifying the distance between x-axis labels and tick marks. Defaults to 0.5.
<code>y.tck.dist</code>	A number specifying the distance between y-axis labels and tick marks. Defaults to 0.5.
<code>axes.lwd</code>	Width of border. Note it also changes the colourkey border and ticks
<code>key.right.padding</code>	Space between right-most plot and any keys/legends
<code>key.left.padding</code>	Space between left-most plot and any keys/legends
<code>key.bottom.padding</code>	Space between bottom-most plot and any keys/legends
<code>xlab.key.padding</code>	Space between bottom-most xlab and any keys/legends
<code>height</code>	Figure height, defaults to 6 inches
<code>width</code>	Figure width, defaults to 6 inches
<code>size.units</code>	Figure units, defaults to inches
<code>resolution</code>	Figure resolution in dpi, defaults to 1600
<code>enable.warnings</code>	Print warnings if set to TRUE, defaults to FALSE
<code>key</code>	Add a key to the plot: see <code>xyplot</code> .
<code>legend</code>	Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See <code>?xyplot</code> .
<code>print.new.legend</code>	Override default behaviour of merging legends imported from plots, can specify custom legend, default is FALSE. TRUE will cancel <code>merge.legends</code> functionality
<code>merge.legends</code>	FALSE means only legend from first plot is used, TRUE retrieves legends from all plots. Multiple legends share the same “space”:see <code>c.trellis</code> .
<code>plot.layout</code>	A vector specifying the layout of the plots, defaults to a single column/ <code>c(1,length(plot.objects))</code>
<code>layout.skip</code>	A vector specifying which positions in the layout grid to leave blank/skip, defaults to not skipping any spots in the layout / <code>rep(FALSE,length(plot.objects))</code> . Goes in this order: Bottom Left, Bottom Right, Top Left, Top Right
<code>description</code>	Short description of image/plot; default NULL.
<code>plot.labels.to.retrieve</code>	a vector of the indices referencing which plots in <code>plot.objects</code> should have there limits, at, and axis labels retrived in the multiplot vs using the arguments specified to <code>multiplot</code>
<code>style</code>	defaults to “BoutrosLab”, also accepts “Nature”, which changes parameters according to Nature formatting requirements
<code>remove.all.border.lines</code>	defaults to FALSE. Flag for whether all borders around plots should be removed.

```

preload.default
    ability to set multiple sets of different defaults depending on publication needs
plot.for.carry.over.when.same
    which plot
get.dendrogram.from
    which plot to retrieve dendrogram from
dendrogram.right.size
    size of right side dendrogram
dendrogram.right.x
    x position of right side dendrogram
dendrogram.right.y
    y position of right side dendrogram
dendrogram.top.size
    size of top side dendrogram
dendrogram.top.x
    x position of top side dendrogram
dendrogram.top.y
    y position of top side dendrogram
use.legacy.settings
    boolean to set whether or not to use legacy mode settings (font)

```

Value

If filename is NULL then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of create histogram is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```

Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics

```

Author(s)

Ken Chu and Denise Mak

Examples

```

set.seed(12345);

# begin by creating the individual plots which will be combined into a multiplot

```

```

dist <- data.frame(
  a = rnorm(100, 1),
  b = rnorm(100, 3),
  c = rnorm(100, 5)
);

simple.data <- data.frame(
  x = c(dist$a, dist$b, dist$c),
  y = rep(LETTERS[1:3], each = 100)
);

fill.squares <- matrix(c(1, 0, 0, 0, 1, 0, 0, 0, 1), ncol = 3, byrow = TRUE);
rownames(fill.squares) <- c("Drug I only", "Drug II only", "Drugs I & II");
colnames(fill.squares) <- levels(factor(simple.data$y));

# Create plot # 1
simple.boxplot <- create.boxplot(
  formula = x ~ y,
  data = simple.data,
  col = 'lightgrey'
);

# Create plot # 2
simple.heatmap <- create.heatmap(
  x = t(fill.squares),
  clustering.method = 'none',
  shrink = 0.8,
  colour.scheme = c("white", "grey20"),
  fill.colour = "white",
  print.colour.key = FALSE
);

# Simple example of multiplot
# This example uses the defaults set in simple.heatmap and simple.boxplot
create.multiplot(
  filename = tempfile(pattern = 'Multiplot_Simple', fileext = '.tiff'),
  plot.objects = list(simple.heatmap, simple.boxplot),
  main = "Simple",
  xlab.label = c("Patient Group"),
  # The plotting function throws an error if this is not included
  ylab.label = c("Sugar Level", "Drug Regimen"),
  ylab.padding = 7,
  # Parameters set in the multiplot will override settings in individual plots
  xaxis.cex = 0.7,
  yaxis.cex = 0.7,
  resolution = 100
);

# Simple example of multiplot with adjusted plot sizes
create.multiplot(
  filename = tempfile(pattern = 'Multiplot_Simple_Plot_Sizes', fileext = '.tiff'),
  plot.objects = list(simple.heatmap, simple.boxplot),
  main = "Simple plot sizes",

```

```
xlab.label = c("Patient Group"),
# y-axis labels must be spaced with tabs or spaces to properly align
ylab.label = c("", "Sugar Level", "", "Drug Regimen"),
ylab.padding = 7,
xaxis.cex = 0.7,
yaxis.cex = 0.7,
# Set the relative heights of the plots
panel.heights = c(3,1),
resolution = 100
);

simple.violin <- create.violinplot(
  formula = x ~ y,
  data = simple.data,
  col = 'lightgrey'
);

# Simple example of multiplot with custom layout
create.multiplot(
  filename = tempfile(pattern = 'Multiplot_Simple_Layout', fileext = '.tiff'),
  plot.objects = list(simple.heatmap, simple.boxplot, simple.violin),
  main = "Simple layout",
  xlab.label = c("Patient Group"),
  ylab.label = c("", "Sugar Level", "", "Drug Regimen"),
  ylab.padding = 7,
  xaxis.cex = 0.7,
  yaxis.cex = 0.7,
  panel.heights = c(3,1),
  # Set how many rows & columns are in the layout
  plot.layout = c(2,2),
  # Set whether to plot or not in the space (fills from bottom left to top right)
  layout.skip = c(FALSE, TRUE, FALSE, FALSE),
  # Move plots closer together
  x.spacing = 0,
  # Remove doubled internal axis
  yat = list(
    seq(1,3,1),
    seq(-2, 8, 2),
    c()
  ),
  resolution = 100
);

# Example of how to take parameter values from individual plots
# This programming structure allows for including the individual customization
# of plots to the final multiplot
all_data <- data.frame(
  a = rnorm(n = 25, mean = 0, sd = 0.75),
  b = rnorm(n = 25, mean = 0, sd = 0.75),
  c = rnorm(n = 25, mean = 0, sd = 0.75),
  d = rnorm(n = 25, mean = 0, sd = 0.75),
  e = rnorm(n = 25, mean = 0, sd = 0.75),
  f = rnorm(n = 25, mean = 0, sd = 0.75),
```

```

x = rnorm(n = 25, mean = 5),
y = seq(1, 25, 1)
);

plot.heatmap <- function(all_data){
  # save the parameter values that will be reused in the multiplot
  multiplot_visuals <- list(
    xlab.label = '',
    xaxis.labels = NULL,
    xat = NULL,
    ylab.label = 'Genes of Interest',
    yaxis.labels = c("BRCA1", "BRCA2", "APC", "TIN", "ARG", "FOO"),
    yat = c(1,2,3,4,5,6)
  );

  # create the plot -- this allows for previewing of the individual plot
  heatmap.formatted <- create.heatmap(
    x = all_data[,1:6],
    clustering.method = 'none',
    colour.scheme = c('magenta','white','green'),
    print.colour.key = FALSE,
    xlab.label = multiplot_visuals$xlab.label,
    xaxis.lab = multiplot_visuals$xaxis.labels,
    xat = multiplot_visuals$xat,
    ylab.label = multiplot_visuals$ylab.label,
    yaxis.lab = multiplot_visuals$yaxis.labels,
    yat = multiplot_visuals$yat
  );

  # return both the plot and the relevant parameter values
  return(
    list(
      the_plot = heatmap.formatted,
      visuals = multiplot_visuals
    )
  )
}

plot.barplot <- function(all_data) {

  # save the parameter values that will be reused in the multiplot
  multiplot_visuals <- list(
    xlab.label = '',
    xaxis.labels = NULL,
    xat = NULL,
    ylab.label = 'Importance',
    yaxis.labels = seq(1, ceiling(max(all_data$x)), 1),
    yat = seq(1, ceiling(max(all_data$x)), 1)
  );

  # create the plot -- this allows for previewing of the individual plot
  barplot.formatted <- create.barplot(
    formula = x ~ y,

```

```
    data = all_data[,7:8],
    border.lwd = 0,
    col = 'grey',
    xlab.label = multiplot_visuals$xlab.label,
    xaxis.lab = multiplot_visuals$xaxis.labels,
    xat = multiplot_visuals$xat,
    ylab.label = multiplot_visuals$ylab.label,
    yaxis.lab = multiplot_visuals$yaxis.labels,
    yat = multiplot_visuals$yat
  );

# return both the plot and the relevant parameter values
return(
  list(
    the_plot = barplot.formatted,
    visuals = multiplot_visuals
  )
)
}

plot_functions <- c('plot.heatmap', 'plot.barplot');

# run the functions
all_plots <- lapply(
  plot_functions,
  function(funName){
    eval(parse(text = paste0(funName, '(all_data)')))
  }
);

create.multiplot(
  filename = tempfile(pattern = 'Multiplot_Formatting', fileext = '.tiff'),
  main = "Formatting",
  plot.objects = lapply(all_plots, function(aPlot) aPlot$the_plot),
  panel.heights = c(1,3),
  xaxis.cex = 1,
  yaxis.cex = 1,
  ylab.padding = 8,
  yat = lapply(all_plots,function(aPlot) aPlot$visuals$yat),
  xlab.label = lapply(all_plots,function(aPlot) aPlot$visuals$xlab.label),
  ylab.label = rev(lapply(all_plots,function(aPlot) aPlot$visuals$ylab.label)),
  yaxis.labels = lapply(all_plots,function(aPlot) aPlot$visuals$yaxis.labels),
  resolution = 100
);

data_bars <- data.frame(
  x = sample(x = 5:35, size = 10),
  y = seq(1,10,1)
);

data_cov <- data.frame(
  x = rnorm(n = 10, mean = 0, sd = 0.75),
  y = rnorm(n = 10, mean = 0, sd = 0.75),
```

```

z = rnorm(n = 10, mean = 0, sd = 0.75)
);

# Create main barplot
bars <- create.barplot(
  formula = x~y,
  data = data_bars,
  ylims = c(0,35),
  sample.order = 'increasing',
  border.lwd = 0
);

# Make covariate bars out of heatmaps
cov_1 <- create.heatmap(
  x = as.matrix(data_bars$y),
  clustering.method = 'none',
  scale.data = FALSE,
  colour.scheme = default.colours(4),
  grid.col = TRUE,
  col.colour = 'black',
  # col.lwd = 10,
  total.col = 5,
  print.colour.key = FALSE,
  yaxis.tck = 0,
  axes.lwd = 0
);

cov_2 <- create.heatmap(
  x = as.matrix(data_cov$y),
  clustering.method = 'none',
  scale.data = FALSE,
  colour.scheme = c("lightblue", "dodgerblue2", "dodgerblue4"),
  grid.col = TRUE,
  col.colour = 'black',
  # col.lwd = 10,
  total.col = 4,
  print.colour.key = FALSE,
  yaxis.tck = 0
);

cov_3 <- create.heatmap(
  x = as.matrix(data_cov$z),
  clustering.method = 'none',
  scale.data = FALSE,
  colour.scheme = c("grey", "coral1"),
  grid.col = TRUE,
  col.colour = 'black',
  # col.lwd = 10,
  total.col = 3,
  print.colour.key = FALSE,
  yaxis.tck = 0
);

```

```
# Generate legends outside of individual functions
legend <- legend.grob(
  list(
    legend = list(
      colours = default.colours(4),
      title = "Batch",
      labels = LETTERS[1:4],
      size = 3,
      title.cex = 1,
      label.cex = 1,
      border = 'black'
    ),
    legend = list(
      colours = c("lightblue", "dodgerblue2", "dodgerblue4"),
      title = "Grade",
      labels = c("Low", "Normal", "High"),
      size = 3,
      title.cex = 1,
      label.cex = 1,
      border = 'black'
    ),
    legend = list(
      colours = c("grey", "coral1"),
      title = "Biomarker",
      labels = c("Not present", "Present"),
      size = 3,
      title.cex = 1,
      label.cex = 1,
      border = 'black'
    )
  ),
  title.just = 'left'
);

# Assemble plot using multiplot function
create.multiplot(
  filename = tempfile(pattern = 'Multiplot_Barchart', fileext = '.tiff'),
  main = 'Multiplot with bar chart',
  plot.objects = list(cov_3, cov_2, cov_1, bars),
  ylab.label = c("\t", "Response to treatment", "\t"),
  xlab.label = "Sample characteristics",
  panel.heights = c(1, 0.05, 0.05, 0.05),
  y.spacing = c(-1, -1, -1, 0),
  xaxis.lab = NULL,
  yaxis.lab = list(NULL, NULL, NULL, seq(0, 350, 50)),
  legend = list(right = list(fun = legend)),
  print.new.legend = TRUE,
  xaxis.alternating = 0,
  main.cex = 1,
  ylab.cex = 1,
  xlab.cex = 1,
  xlab.to.xaxis.padding = -2,
  yaxis.cex = 1,
```

```

description = "Multiplot example created by BoutrosLab.plotting.general",
resolution = 200
);

gene_data <- data.frame(
  x = rnorm(n = 25, mean = 0, sd = 0.75),
  y = rnorm(n = 25, mean = 0, sd = 0.75),
  z = rnorm(n = 25, mean = 0, sd = 0.75),
  v = rnorm(n = 25, mean = 0, sd = 0.75),
  w = rnorm(n = 25, mean = 0, sd = 0.75),
  a = rnorm(n = 25, mean = 0, sd = 0.75),
  b = rnorm(n = 25, mean = 0, sd = 0.75),
  c = rnorm(n = 25, mean = 0, sd = 0.75)
);

# main heatmap
main <- create.heatmap(
  x = gene_data,
  xaxis.tck = 0,
  yaxis.tck = 0,
  colourkey.cex = 1,
  clustering.method = 'none',
  axes.lwd = 1,
  ylab.label = 'y',
  xlab.label = 'x',
  yaxis.fontface = 1,
  xaxis.fontface = 1,
  xlab.cex = 1,
  ylab.cex = 1,
  main.cex = 1,
  colour.scheme = c('red','white','turquoise')
);

key_data <- data.frame(
  x <- seq(-50,50,1)
);

# colour key for heatmap
key <- create.heatmap(
  x = key_data,
  clustering.method = 'none',
  scale.data = FALSE,
  colour.scheme = c('turquoise','white','red'),
  print.colour.key = FALSE,
  yaxis.tck = 0,
  xat = c(10,90),
  xaxis.lab = c('low', 'high')
);

top_data <- data.frame(
  x = rnorm(n = 25, mean = 0, sd = 0.75),
  y = seq(1,25,1)
)

```

```
);

# top barplot
top <- create.barplot(
  formula = x~y,
  data = top_data,
  border.lwd = 0
);

side_data <- data.frame(
  x = rnorm(n = 8, mean = 0, sd = 0.75),
  y = seq(1,8,1)
);

# side barplot
side <- create.barplot(
  formula = x~y,
  data = side_data,
  border.lwd = 0,
  sample.order = 'decreasing',
  plot.horizontal = TRUE
);

# assembling final figure
create.multiplot(
  filename = tempfile(pattern = 'Multiplot_with_heatmap', fileext = '.tiff'),
  main = 'Multiplot with heatmap',
  plot.objects = list(key, main, side, top),
  panel.heights = c(0.25, 1, 0.05),
  panel.widths = c(1, 0.25),
  plot.layout = c(2, 3),
  layout.skip = c(FALSE, TRUE, FALSE, FALSE, FALSE, FALSE),
  xaxis.alternating = 0,
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1,
  ylab.cex = 1,
  xlab.label = c('\t', 'Samples', '\t', 'Importance'),
  ylab.label = c('Amount (g)', '\t', '\t', 'Genes', '\t', '\t'),
  ylab.padding = 6,
  xlab.to.xaxis.padding = 0,
  xaxis.lab = list(
    c("", "low", "", "", "high", ""),
    LETTERS[1:25],
    seq(0,5,1),
    NULL
  ),
  yaxis.lab = list(
    NULL,
    replicate(8, paste(sample(LETTERS, 4, replace = TRUE), collapse = "")),
    NULL,
    seq(0,4,0.05)
  ),
```

```

x.spacing = -0.5,
y.spacing = c(0,-1),
xaxis.fontface = 1,
yaxis.fontface = 1
);

# Set up plots for complex example

# Dotmap
spot_sizes <- function(x) { 0.5 * abs(x); }
dotmap_dot_colours <- c('red','blue');
spot_colours <- function(x) {
  colours <- rep('white', length(x));
  colours[sign(x) == -1] <- dotmap_dot_colours[1];
  colours[sign(x) == 1] <- dotmap_dot_colours[2];
  return(colours);
};

# Dotmap colours
orange <- rgb(249/255, 179/255, 142/255);
blue <- rgb(154/255, 163/255, 242/255);
green <- rgb(177/255, 213/255, 181/255);
bg.colours <- c(green, orange, blue, 'gold', 'skyblue', 'plum');

dotmap <- create.dotmap(
  x = CNA[1:15,1:58],
  bg.data = SNV[1:15,1:58],
  # Set the colour scheme
  colour.scheme = bg.colours,
  # Set the breakpoints for the colour scheme (determined from the data)
  at = c(0,1,2,4,6,7,8),
  # Specify the total number of colours (+1 for the fill colour)
  total.colours = 7,
  col.colour = 'white',
  row.colour = 'white',
  bg.alpha = 1,
  fill.colour = 'grey95',
  spot.size.function = spot_sizes,
  spot.colour.function = spot_colours,
  xaxis.tck = 0,
  xaxis.cex = 0.7,
  yaxis.cex = 0.7,
  xaxis.rot = 90
);

# Dotmap legend
dotmap_legend <- list(
  legend = list(
    colours = bg.colours,
    labels = c('Nonsynonymous','Stop Gain','Frameshift deletion',
              'Nonframeshift deletion', 'Splicing', 'Unknown'),
    border = 'white',
    title = 'SNV',

```

```
    pch = 15
),
legend = list(
  colours = dotmap_dot_colours,
  labels = c('Gain','Loss'),
  border = 'white',
  title = 'CNA',
  pch = 19
)
);

dotmap_legend.grob <- legend.grob(
  legends = dotmap_legend,
  title.just = 'left',
  label.cex = 0.7,
  title.cex = 0.7
);

# Covariates
cov.colours <- c(
  c('dodgerblue','pink'),
  c('grey','darkseagreen1','seagreen2','springgreen3','springgreen4'),
  c('peachpuff','tan4')
);

# the heatmap expects numeric data
cov.data <- patient[-c(4:9)];
cov.data[cov.data == 'male'] <- 1;
cov.data[cov.data == 'female'] <- 2;
cov.data[is.na(cov.data)] <- 3;
cov.data[cov.data == 'I'] <- 4;
cov.data[cov.data == 'II'] <- 5;
cov.data[cov.data == 'III'] <- 6;
cov.data[cov.data == 'IV'] <- 7;
cov.data[cov.data == 'MSS'] <- 8;
cov.data[cov.data == 'MSI-High'] <- 9;
cov.data$sex <- as.numeric(cov.data$sex);
cov.data$stage <- as.numeric(cov.data$stage);
cov.data$msi <- as.numeric(cov.data$msi);

covariates <- create.heatmap(
  x = cov.data,
  clustering.method = 'none',
  colour.scheme = as.vector(cov.colours),
  total.colours = 10,
  row.colour = 'white',
  col.colour = 'white',
  grid.row = TRUE,
  grid.col = TRUE,
  yaxis.tck = 0,
  print.colour.key = FALSE
);
```

```

# Coviate Legends
cov_legends <- list(
  legend = list(
    colours = cov.colours[8:9],
    labels = c('MSS','MSI-High'),
    border = 'white',
    title = 'MSI'
  ),
  legend = list(
    colours = cov.colours[3:7],
    labels = c('NA', 'I','II','III','IV'),
    border = 'white',
    title = 'Stage'
  ),
  legend = list(
    colours = cov.colours[1:2],
    labels = c('Male','Female'),
    border = 'white',
    title = 'Sex'
  )
);

cov_legend.grob <- legend.grob(
  legends = cov_legends,
  title.just = 'left',
  label.cex = 0.7,
  title.cex = 0.7,
  layout = c(3,1)
);

# Multiplot of dotmap and covariates
create.multiplot(
  filename = tempfile(pattern = 'Multiplot_Dotmap_Cov', fileext = '.tiff'),
  plot.objects = list(covariates, dotmap),
  main = 'Dotmap & covariates',
  panel.heights = c(1,0.1),
  # Set some of the yat to NULL to let R figure it out
  yat = c(seq(1,15,1), NULL),
  xat = NULL,
  yaxis.lab = list(
    c('Sex','Stage','MSI'),
    rev(rownames(SNV)[1:15])
  ),
  yaxis.cex = 0.7,
  y.spacing = -1,
  legend = list(
    bottom = list(
      x = 0.10,
      y = 0.50,
      fun = cov_legend.grob
    ),
    right = list(
      x = 0.10,

```

```
    y = 0.50,
    fun = dotmap_legend.grob
  )
),
# This parameter must be set for the legend to appear
print.new.legend = TRUE,
# Adding spacing for the legend
bottom.padding = 5
);

# Add more plots, using more complex layout
# grouped barplot
groupedbar_colours <- c('indianred1','indianred4');

count.SNV <- apply(SNV[1:15,], 2, function(x){length(which(!is.na(x)))});
count.CNA <- apply(CNA[1:15,], 2, function(x){length(which(!(x==0)))});

grouped_data <- data.frame(
  values = c(count.SNV, count.CNA),
  samples = rep(colnames(SNV),2),
  group = rep(c('SNV','CNA'), each = 58)
);

grouped_barplot <- create.barplot(
  formula = values ~ samples,
  data = grouped_data,
  groups = grouped_data$group,
  col = groupedbar_colours,
  border.col = 'white'
);

# stacked barplot
col_one <- rgb(255/255, 225/255, 238/255);
col_two <- rgb(244/255, 224/255, 166/255);
col_thr <- rgb(177/255, 211/255, 154/255);
col_fou <- rgb(101/255, 180/255, 162/255);
col_fiv <- rgb(51/255, 106/255, 144/255);
stackedbar_colours <- c(col_one, col_two, col_thr, col_fou, col_fiv, 'orchid4');
stacked_data_labels <- c('C>A/G>T','C>T/G>A','C>G/G>C','T>A/A>T','T>G/A>C', 'T>C/A>G');

stacked_data <- data.frame(
  values = c(patient$prop.CAGT, patient$prop.CTGA, patient$prop.CGGC, patient$prop.TAAT,
             patient$prop.TGAC, patient$prop.TCAG),
  divisions = rep(rownames(patient), 6),
  group = rep(stacked_data_labels, each = 58)
);

# Generate stacked barplot
stacked_barplot <- create.barplot(
  formula = values ~ divisions,
  data = stacked_data,
  groups = stacked_data$group,
  stack = TRUE,
```

```

col = stackedbar_colours,
border.col = 'white'
);

# barchart legends
stackedbar_legend <- list(
  legend = list(
    colours = rev(stackedbar_colours),
    labels = rev(stacked_data_labels),
    border = 'white'
  )
);

groupedbar_legend <- list(
  legend = list(
    colours = groupedbar_colours,
    labels = c('CNA','SNV'),
    border = 'white'
  )
);

groupedbar_legend.grob <- legend.grob(
  legends = groupedbar_legend,
  title.just = 'left',
  label.cex = 0.7,
  title.cex = 0.7
);

stackedbar_legend.grob <- legend.grob(
  legends = stackedbar_legend,
  title.just = 'left',
  label.cex = 0.7,
  title.cex = 0.7
);

# Expression change Segplot
# locate matching genes
rows.to.keep <- which(match(rownames(microarray), rownames(SNV)[1:15], nomatch = 0) > 0);

segplot.data <- data.frame(
  min = apply(microarray[rows.to.keep,1:58], 1, min),
  max = apply(microarray[rows.to.keep,1:58], 1, max),
  median = apply(microarray[rows.to.keep,1:58], 1, median),
  order = seq(1,15,1)
);

segplot <- create.segplot(
  formula = order ~ min + max,
  data = segplot.data,
  main = 'Medians',
  centers = segplot.data$median,
  pch = 15
);

```

```
# Create multiplot
plots <- list(covariates, dotmap, segplot, stacked_barplot, grouped_barplot);

create.multiplot(
  filename = tempfile(pattern = 'Multiplot_Complex', fileext = '.tiff'),
  main = 'Complex',
  # These dimensions make the plot look much more proportional
  width = 12,
  height = 8,
  plot.objects = plots,
  panel.heights = c(0.2, 0.2, 1, 0.1),
  panel.widths = c(1,0.1),
  plot.layout = c(2, 4),
  layout.skip = c(FALSE,TRUE,FALSE,FALSE,FALSE,TRUE,FALSE,TRUE),
  xaxis.lab = list(
    NULL,
    NULL,
    seq(0,14,2),
    NULL,
    NULL),
  yaxis.lab = list(
    c('Sex','Stage','MSI'),
    rownames(SNV)[1:15],
    NULL,
    seq(0.0,1.0,0.2),
    seq(0,16,4)
  ),
  x.spacing = -0.5,
  y.spacing = -1.5,
  xaxis.cex = 0.7,
  yaxis.cex = 0.7,
  xat = list(
    NULL,
    NULL,
    seq(0,10,2.5),
    NULL,
    NULL
  ),
  yat = list(
    seq(1,3,1),
    seq(1,15,1),
    NULL,
    seq(0.0,1.0,0.2),
    seq(0,16,4)
  ),
  ylab.label = c( 'Mutation', 'Proportion','\t','\t','\t','\t','\t','\t'),
  ylab.cex = 0.7,
  xlab.cex = 0.7,
  xlab.to.xaxis.padding = 2,
  key.bottom.padding = 5,
  bottom.padding = 5,
  right.padding = 8,
```

```

legend = list(
  bottom = list(
    x = 0.10,
    y = 0.50,
    fun = cov_legend.grob
  ),
  inside = list(
    x = 0.91,
    y = 0.96,
    fun = groupedbar_legend.grob
  ),
  inside = list(
    x = 0.91,
    y = 0.86,
    fun = stackedbar_legend.grob
  ),
  left = list(
    fun = dotmap_legend.grob,
    args = list(
      key = list(
        points = list(
          pch = c(15,15,19,19)
        )
      )
    )
  )
),
print.new.legend = TRUE,
resolution = 200
);

# Nature style
create.multiplot(
  filename = tempfile(pattern = 'Multiplot_Nature_style', fileext = '.tiff'),
  plot.objects = list(simple.heatmap, simple.boxplot),
  main = "Nature style",
  ylab.padding = 7,
  xaxis.cex = 0.7,
  yaxis.cex = 0.7,

  # set style to Nature
  style = 'Nature',

  # demonstrating how to italicize character variables
  ylab.label = c(expression(paste('italicized ', italic('a'))),
  expression(paste('italicized ', italic('b')))),

  # demonstrating how to create en-dashes
  xlab.label = c(expression(paste('en dashes: 1', '\u2013', '10' '^' '\u2013', '' ^ 3))),
  resolution = 200
);

# Create a multiplot with a heatmap, key like legend and barplot

```

```
# First create a heatmap object
simple.heatmap <- create.heatmap(patient[, 4:6],
  clustering.method = 'none',
  print.colour.key = FALSE,
  scale=TRUE,
  same.as.matrix = FALSE,
  colour.scheme = c('gray0','grey100'),
  fill.colour = 'grey95'
);

# and a simple bar plot
pvals <- data.frame(
  order = c(1:3),
  pvalue = -log10(c(0.0004, 0.045, 0.0001)),
  stringsAsFactors = FALSE
)
#create bar plot
simple.bar <- create.barplot(
  formula = order ~ rev(pvalue),
  data = pvals,
  xlimits = c(0,5),
  plot.horizontal=TRUE
);

# then the covariates heatmap
cov.colours <- c(
  c('dodgerblue','pink'),
  c('grey','darkseagreen1','seagreen2','springgreen3','springgreen4'),
  c('peachpuff','tan4')
);

# the heatmap expects numeric data
cov.data <- patient[-c(4:9)];
cov.data[cov.data == 'male'] <- 1;
cov.data[cov.data == 'female'] <- 2;
cov.data[is.na(cov.data)] <- 3;
cov.data[cov.data == 'I'] <- 4;
cov.data[cov.data == 'II'] <- 5;
cov.data[cov.data == 'III'] <- 6;
cov.data[cov.data == 'IV'] <- 7;
cov.data[cov.data == 'MSS'] <- 8;
cov.data[cov.data == 'MSI-High'] <- 9;
cov.data$sex <- as.numeric(cov.data$sex);
cov.data$stage <- as.numeric(cov.data$stage);
cov.data$msi <- as.numeric(cov.data$msi);

covariates <- create.heatmap(
  x = cov.data,
  clustering.method = 'none',
  colour.scheme = as.vector(cov.colours),
  total.colours = 10,
```

```

row.colour = 'white',
col.colour = 'white',
grid.row = TRUE,
grid.col = TRUE,
yaxis.tck = 0,
print.colour.key = FALSE
);
covariates2 <- create.heatmap(
  x = patient[4],
  clustering.method = 'none',
  colour.scheme = c("#00007F", "#007FFF"),
  row.colour = 'white',
  col.colour = 'white',
  grid.row = TRUE,
  grid.col = TRUE,
  yaxis.tck = 0,
  print.colour.key = FALSE
);

cov_legends <- list(
  legend = list(
    colours = c("white", "black"),
    labels = c('0','2'),
    border = 'grey',
    title = 'Tumour Mass (kg)',
    continuous = TRUE,
    height = 3
  ),
  legend = list(
    colours = cov.colours[8:9],
    labels = c('MSS','MSI-High'),
    border = 'white',
    title = 'MSI'
  ),
  legend = list(
    colours = cov.colours[3:7],
    labels = c('NA', 'I','II','III','IV'),
    border = 'white',
    title = 'Stage'
  ),
  legend = list(
    colours = cov.colours[1:2],
    labels = c('Male','Female'),
    border = 'white',
    title = 'Sex'
  ),
  legend = list(
    colours = c("#00007F", "#007FFF"),
    labels = c('0.09','0.72'),
    border = 'grey',
    title = 'CAGT',
    continuous = TRUE,
    height = 2,

```

```
    width = 3,
    angle = -90,
    tck = 1,
    tck.number = 2,
    at = c(0,100)
        )
    );
}

cov_legend.grob <- legend.grob(
    legends = cov_legends,
    title.just = 'left',
    label.cex = 0.7,
    title.cex = 0.7
);

# Now bring it was together using multiplot
create.multiplot(
    main = 'multiplot with colour key legend',
    main.cex = 1,
    filename = tempfile(pattern = 'MultiPlot_With_ColorKey_Legend', fileext = '.tiff'),
    plot.objects = list(covariates, covariates2, simple.heatmap, simple.bar),
    panel.heights = c(1,0.1,0.35),
    panel.widths = c(1,0.25),
    plot.layout = c(2,3),
    layout.skip = c(FALSE, TRUE, FALSE, TRUE, FALSE, FALSE),
    xaxis.alternating = 1,
    # Set some of the yat to NULL to let R figure it out
    yaxis.lab = list(
        c('Sex','Stage','MSI'),
        NULL,
        c('one','two','three'),
        NULL
    ),
    xaxis.lab = list(
        NULL,
        NULL,
        NULL,
        seq(0,5,1)
    ),
    xat = list(
        NULL,
        NULL,
        NULL,
        seq(0,5,1)
    ),
    yaxis.tck = 0,
    xlab.to.xaxis.padding = 0,
    yaxis.cex = 0.5,
    xaxis.cex = 0.5,
    xlab.cex = 0.75,
    ylab.cex = 0.75,
    xlab.label = c('\t', 'samples', '\t', ' -log10 pval'),
    ylab.label = c("", "Test", "", "CAGT", "covariates"),
```

```

y.spacing = 0,
x.spacing = 0,
legend = list(
  left = list(
    x = 0.10,
    y = 0.50,
    fun = cov_legend.grob
  )
),
left.padding = 2.5,
# This parameter must be set for the legend to appear
print.new.legend = TRUE
);

BarPlotDataRetLabels <- data.frame(x = c("test1","test2","test3","test4"),
y = c(10000,13000,12000,6700))
HeatMapDataRetLabels <- matrix(nrow = 4, ncol = 4, data = rnorm(16,1,1))

bpRet <- create.barplot(
formula = y~x,
data = BarPlotDataRetLabels,
xaxis.lab = NULL,
xat = 0
);
hmRet <- create.heatmap(
x= HeatMapDataRetLabels,
yaxis.lab = c("Gene 1", "Gene 2", "Gene 3", "Gene 4"),
yat = c(1,2,3,4),
clustering.method = 'none'
);

create.multiplot(
filename = tempfile(pattern = 'Multiplot_RetrievePlotLabels', fileext = '.tiff'),
plot.objects = list(hmRet,bpRet,bpRet),
print.new.legend = TRUE,
xlab.label = c('Samples'),
ylab.padding = 12,
y.spacing = c(0,0),
panel.heights = c(0.25,1,0.25),
plot.labels.to.retrieve = c(1,2,3)
);

create.multiplot(
filename = tempfile(pattern = 'Multiplot_Retrieve_Specefic_Labels', fileext = '.tiff'),
plot.objects = list(simple.heatmap, simple.boxplot),
main = "Simple",
xlab.label = c("Patient Group"),
xaxis.labels = c("1","Drug Regimen"),
# The plotting function throws an error if this is not included
ylab.label = c("Sugar Level", "Drug Regimen"),
ylab.padding = 7,
# Parameters set in the multiplot will override settings in individual plots
xaxis.cex = 0.7,

```

```
    yaxis.cex = 0.7,
    yaxis.labels = c(NA,NA),
    xat = list(TRUE,TRUE),
    yat = list(TRUE,TRUE),
    plot.labels.to.retrieve = c(1),
    xlims = list(NULL,c("A","B","C")),
    ylims = list(NULL,c(-3,10))
  );

# Dendrogram provided
dist <- data.frame(
  a = rnorm(100, 1),
  b = rnorm(100, 3),
  c = rnorm(100, 5)
);

simple.data <- data.frame(
  x = c(dist$a, dist$b, dist$c),
  y = rep(LETTERS[1:3], each = 100)
);
col.dendrogram <- BoutrosLab.plotting.general::create.dendrogram(
  x = microarray[1:20, 1:20],
  cluster.dimension = 'col'
);

row.dendrogram <- BoutrosLab.plotting.general::create.dendrogram(
  x = microarray[1:20, 1:20],
  cluster.dimension = 'row'
);

simple.boxplot <- create.boxplot(
  formula = x ~ y,
  data = simple.data,
  col = 'lightgrey'
);

simple.heatmap <- create.heatmap(
  x = microarray[1:20, 1:20],
  main = 'Dendrogram provided',
  xlab.label = 'Genes',
  ylab.label = 'Samples',
  xaxis.lab = NA,
  yaxis.lab = 1:20,
  xaxis.cex = 0.75,
  yaxis.cex = 0.75,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  colourkey.cex = 1,
  colourkey.labels.at = seq(2,12,1),
  colour.alpha = 'automatic',
# note: row/column dendograms are switched because the function inverts rows and columns
  clustering.method = 'none',
  row.dendrogram = col.dendrogram,
```

```

col.dendrogram = row.dendrogram,
# Adjusting the size of the dendrogram
right.dendrogram.size = 3,
top.dendrogram.size = 2.5,
description = 'Heatmap created using BoutrosLab.plotting.general'
);

legend <- legend.grob(
  list(
    legend = list(
      colours = default.colours(4),
      title = "Batch",
      labels = LETTERS[1:4],
      size = 3,
      title.cex = 1,
      label.cex = 1,
      border = 'black'
    ),
    legend = list(
      colours = c("lightblue","dodgerblue2","dodgerblue4"),
      title = "Grade",
      labels = c("Low","Normal","High"),
      size = 3,
      title.cex = 1,
      label.cex = 1,
      border = 'black'
    ),
    legend = list(
      colours = c("grey","coral1"),
      title = "Biomarker",
      labels = c("Not present","Present"),
      size = 3,
      title.cex = 1,
      label.cex = 1,
      border = 'black'
    )
  ),
  title.just = 'left'
);
create.multiplot(
  filename = tempfile(pattern = 'MultiPlot_getDendograms', fileext = '.tiff'),
  plot.objects = list(simple.heatmap, simple.boxplot),
  main = "Simple",
  xlab.label = c("Patient Group"),
  y.spacing = 3,
  # The plotting function throws an error if this is not included
  ylab.label = c("Sugar Level", "Drug Regimen"),
  ylab.padding = 7,
  # Parameters set in the multiplot will override settings in individual plots
  xaxis.cex = 0.7,
  yaxis.cex = 0.7,
  yaxis.lab = list(
    c(1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20),

```

```
c(-2,-1,0,1,2,3,4,5)
),
xaxis.lab = list(c(1,2,3,4,5,6,7,8,9,10,11,12,13,14,15, 16,17,18,19,20),c(1,2,3)),
xaxis.rot = 45,
xaxis.rot.top = 90,
legend = list(right = list(fun = legend)),
print.new.legend = TRUE,
get.dendrogram.from = 1,
dendrogram.right.size = 0.40, dendrogram.right.x = 29, dendrogram.right.y = 67,
dendrogram.top.size = 1, dendrogram.top.x = 110, dendrogram.top.y = -180
);
```

create.polygonplot *Make a polygonplot*

Description

Takes a data.frame and creates a polygon

Usage

```
create.polygonplot(
formula,
data,
filename = NULL,
groups = NULL,
main = NULL,
main.just = 'center',
main.x = 0.5,
main.y = 0.5,
main.cex = 3,
max,
min,
col = 'white',
alpha = 0.5,
border.col = 'black',
xy.col = 'black',
strip.col = 'white',
strip.cex = 1,
type = 'p',
cex = 0.75,
pch = 19,
lwd = 1,
lty = 1,
axes.lwd = 1,
xlab.label = tail(sub('`', '', formula[-2]), 1),
ylab.label = tail(sub('`', '', formula[-3]), 1),
```

```
xlab.cex = 2,  
ylab.cex = 2,  
xlab.col = 'black',  
ylab.col = 'black',  
xlab.top.label = NULL,  
xlab.top.cex = 2,  
xlab.top.col = 'black',  
xlab.top.just = 'center',  
xlab.top.x = 0.5,  
xlab.top.y = 0,  
xaxis.lab = TRUE,  
yaxis.lab = TRUE,  
xaxis.cex = 1.5,  
yaxis.cex = 1.5,  
xaxis.rot = 0,  
yaxis.rot = 0,  
xaxis.log = FALSE,  
yaxis.log = FALSE,  
xaxis.fontface = 'bold',  
yaxis.fontface = 'bold',  
xaxis.col = 'black',  
yaxis.col = 'black',  
xaxis.tck = 1,  
yaxis.tck = 1,  
xlims = NULL,  
ylims = NULL,  
xat = TRUE,  
yat = TRUE,  
layout = NULL,  
as.table = FALSE,  
x.spacing = 0,  
y.spacing = 0,  
x.relation = 'same',  
y.relation = 'same',  
top.padding = 0.5,  
bottom.padding = 2,  
right.padding = 1,  
left.padding = 2,  
ylab.axis.padding = 0,  
add.xy.border = FALSE,  
add.median = FALSE,  
median.lty = 3,  
median.lwd = 1.5,  
use.loess.border = FALSE,  
use.loess.median = FALSE,  
median = NULL,  
median.col = 'black',  
extra.points = NULL,
```

```
extra.points.pch = 21,
extra.points.type = 'p',
extra.points.col = 'black',
extra.points.fill = 'white',
extra.points.cex = 1,
add.rectangle = FALSE,
xleft.rectangle = NULL,
ybottom.rectangle = NULL,
xright.rectangle = NULL,
ytop.rectangle = NULL,
col.rectangle = 'transparent',
alpha.rectangle = 1,
xgrid.at = xat,
ygrid.at = yat,
grid.lty = 1,
grid.col = 'grey',
grid.lwd = 0.3,
add.xyline = FALSE,
xyline.col = 'black',
xyline.lwd = 1,
xyline.lty = 1,
abline.h = NULL,
abline.v = NULL,
abline.col = 'black',
abline.lwd = 1,
abline.lty = 1,
add.text = FALSE,
text.labels = NULL,
text.x = NULL,
text.y = NULL,
text.col = 'black',
text.cex = 1,
text.fontface = 'bold',
key = NULL,
legend = NULL,
height = 6,
width = 6,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
description = 'Created with BoutrosLab.plotting.general',
style = 'BoutrosLab',
preload.default = 'custom',
use.legacy.settings = FALSE,
inside.legend.auto = FALSE
);
```

Arguments

<code>formula</code>	The formula used to extract the boxplot components from the data-frame
<code>data</code>	The data-frame to plot
<code>filename</code>	Filename for tiff output, or if NULL returns the trellis object itself
<code>groups</code>	The grouping variable in the data-frame
<code>main</code>	The main title for the plot (space is reclaimed if NULL)
<code>main.just</code>	The justification of the main title for the plot, default is centered
<code>main.x</code>	The x location of the main title, default is 0.5
<code>main.y</code>	The y location of the main title, default is 0.5
<code>main.cex</code>	Size of text for main plot title
<code>max</code>	Max values for polygon
<code>min</code>	Min values for polygon
<code>col</code>	Fill colour of polygon, defaults to white
<code>alpha</code>	Transparency of polygons when several are plotted, defaults to 0.5.
<code>border.col</code>	Border colour(s) of polygon(s), defaults to black
<code>xy.col</code>	Colour of xy coordinates, defaults to black
<code>strip.col</code>	Strip background colour, defaults to “white”
<code>strip.cex</code>	Strip title character expansion
<code>type</code>	Plot type
<code>cex</code>	Character expansion for plotting symbol
<code>pch</code>	Plotting character
<code>lwd</code>	Specifies line width, defaults to 1
<code>lty</code>	Specifies line style, defaults to 1 (solid)
<code>axes.lwd</code>	Thickness of width of axes lines
<code>xlab.label</code>	The label for the x-axis
<code>ylab.label</code>	The label for the y-axis
<code>xlab.cex</code>	Size of x-axis label, defaults to 3
<code>ylab.cex</code>	Size of y-axis label, defaults to 3
<code>xlab.col</code>	Colour of the x-axis label, defaults to “black”
<code>ylab.col</code>	Colour of the y-axis label, defaults to “black”
<code>xlab.top.label</code>	The label for the top x-axis
<code>xlab.top.cex</code>	Size of top x-axis label
<code>xlab.top.col</code>	Colour of the top x-axis label
<code>xlab.top.just</code>	Justification of the top x-axis label, defaults to centered
<code>xlab.top.x</code>	The x location of the top x-axis label
<code>xlab.top.y</code>	The y location of the top y-axis label
<code>xaxis.lab</code>	Vector listing x-axis tick labels, defaults to automatic

yaxis.lab	Vector listing y-axis tick labels, defaults to automatic
xaxis.cex	Size of x-axis scales, defaults to 2
yaxis.cex	Size of y-axis scales, defaults to 2
xaxis.rot	Rotation of x-axis tick labels; defaults to 0
yaxis.rot	Rotation of y-axis tick labels; defaults to 0
xaxis.log	Logical indicating whether x-variable should be in logarithmic scale (and what base if numeric)
yaxis.log	Logical indicating whether y-variable should be in logarithmic scale (and what base if numeric)
xaxis.fontface	Fontface for the x-axis scales
yaxis.fontface	Fontface for the y-axis scales
xaxis.col	Colour of the x-axis tick labels, defaults to “black”
yaxis.col	Colour of the y-axis tick labels, defaults to “black”
xaxis.tck	Specifies the length of the tick marks for x-axis, defaults to 1
yaxis.tck	Specifies the length of the tick marks for y-axis, defaults to 1
xlimits	Two-element vector giving the x-axis limits
ylimits	Two-element vector giving the y-axis limits
xat	Vector listing where the x-axis labels should be drawn
yat	Vector listing where the y-axis labels should be drawn
layout	A vector specifying the number of columns, rows (e.g., c(2,1). Default is NULL; see lattice::xyplot for more details.
as.table	Specifies panel drawing order, default is FALSE which draws panels from bottom left corner, moving right then up. Set to TRUE to draw from top left corner, moving right then down
x.spacing	A number specifying the distance between panels along the x-axis, defaults to 0
y.spacing	A number specifying the distance between panels along the y-axis, defaults to 0
x.relation	Allows x-axis scales to vary if set to “free”, defaults to “same”
y.relation	Allows y-axis scales to vary if set to “free”, defaults to “same”
top.padding	A number specifying the distance to the top margin, defaults to 0.5
bottom.padding	A number specifying the distance to the bottom margin, defaults to 2
right.padding	A number specifying the distance to the right margin, defaults to 1
left.padding	A number specifying the distance to the left margin, defaults to 2
ylab.axis.padding	A number specifying the distance of ylabel to the y-axis, defaults to 0,
add.xy.border	Add xy border to polygon, default is FALSE
add.median	Add median line, default is FALSE
median.lty	Median line type
median.lwd	Median line width, defaults to 1.5

```

use.loess.border
  Use loess curve for border instead of max/min values, default is FALSE
use.loess.median
  Use loess curve for median values, default is FALSE
median      Median values for median line
median.col   Median line colour, default is black
extra.points If not set to NULL (default), add a set of extra points to the plot. A list of two
             numeric vectors named "x" and "y" giving the co-ordinates of the points to be
             added
extra.points.pch
  A vector specifying the types of extra points to add to the plot. Defaults to 21
extra.points.type
  A vector specifying the plot type. Defaults to "p"
extra.points.col
  A vector specifying the border colours of the extra points to add to the plot.
  Defaults to "black"
extra.points.fill
  A vector specifying the fill colours of the extra points to add to the plot. Defaults
  to "white"
extra.points.cex
  A vector specifying the sizes of the extra points to add to the plot. Defaults to 1
add.rectangle Allow a rectangle to be drawn, default is FALSE
xleft.rectangle
  Specifies the left x coordinate of the rectangle to be drawn
ybottom.rectangle
  Specifies the bottom y coordinate of the rectangle to be drawn
xright.rectangle
  Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle
  Specifies the top y coordinate of the rectangle to be drawn
col.rectangle  Specifies the colour to fill the rectangle's area
alpha.rectangle
  Specifies the colour bias of the rectangle
xgrid.at       A vector listing the co-ordinates at which vertical grid-lines should be drawn.
               Default suppresses drawing of vertical grid-lines
ygrid.at       A vector listing the co-ordinates at which horizontal grid-lines should be drawn.
               Default suppresses drawing of horizontal grid-lines
grid.lty        Specifies the line type to use for the grid-lines. Defaults to 1 (solid lines)
grid.col        Specifies the colour to use for the grid-lines. Defaults to "grey"
grid.lwd        Specifies the width of the grid-lines. Defaults to 0.3
add.xyline     Allow y=x line to be drawn, default is FALSE
xyline.col    y=x line colour, defaults to black
xyline.lwd    Specifies y=x line width, defaults to 1
xyline.lty    Specifies y=x line style, defaults to 1 (solid)

```

abline.h	Allow horizontal line to be drawn, default to NULL
abline.v	Allow vertical line to be drawn, default to NULL
abline.col	Horizontal line colour, defaults to black
abline.lwd	Specifies horizontal line width, defaults to 1
abline.lty	Specifies horizontal line style, defaults to 1 (solid)
add.text	Allow additional text to be drawn, default is FALSE
text.labels	Labels for additional text
text.x	The x co-ordinates where additional text should be placed
text.y	The y co-ordinates where additional text should be placed
text.col	The colour of additional text
text.cex	The size of additional text
text.fontface	The fontface for additional text
key	Add a key to the plot. See xyplot.
legend	Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See xyplot.
height	Figure height, defaults to 6 inches
width	Figure width, defaults to 6 inches
size.units	Figure units, defaults to inches
resolution	Figure resolution in dpi, defaults to 1600
enable.warnings	Print warnings if set to TRUE, defaults to FALSE
description	Short description of image/plot; default NULL.
style	defaults to “BoutrosLab”, also accepts “Nature”, which changes parameters according to Nature formatting requirements
preload.default	ability to set multiple sets of different defaults depending on publication needs
use.legacy.settings	boolean to set whether or not to use legacy mode settings (font)
inside.legend.auto	boolean specifying whether or not to use the automatic inside legend function

Value

If filename is NULL then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of create histogram is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```
Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
      Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics
```

Author(s)

Denise Mak

See Also

[xyplot](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(12345);

temp <- matrix(runif(1010), ncol = 10) + sort(runif(101));

simple.data <- data.frame(
  x = 0:100,
  max = apply(temp, 1, max),
  min = apply(temp, 1, min)
);

create.polygonplot(
  filename = tempfile(pattern = 'Polygon_Simple', fileext = '.tiff'),
  formula = NA ~ x,
  data = simple.data,
  max = simple.data$max,
  min = simple.data$min,
  main = 'Simple',
  xlims = c(0,100),
  ylims = c (0,2),
  col = default.colours(1),
  description = 'Polygon created by BoutrosLab.plotting.general',
  resolution = 100
);

# Compare two genes across increasing numbers of samples
data1 <- microarray[1,1:58];
data2 <- microarray[2,1:58];

gene1 <- as.data.frame(matrix(nrow = 58, ncol = 58));
gene2 <- as.data.frame(matrix(nrow = 58, ncol = 58));

fill.matrix <- function(x, gene, data){
  for(i in x){
    gene[i, 1:i] <- rep(NA, i);
    gene[i, i:58] <- rep(as.numeric(data[i]), 58-i+1);
  }
  return(gene);
}
```

```
};

gene1 <- fill.matrix(1:58, gene1, data1);
gene1 <- t(matrix(unlist(gene1), ncol = 58, byrow = TRUE));

gene2 <- fill.matrix(1:58, gene2, data2);
gene2 <- t(matrix(unlist(gene2), ncol = 58, byrow = TRUE));

# Set up the data
polygon.data.gene1 <- data.frame(
  x = 1:58,
  max = apply(gene1, 2, function(x) {max(x, na.rm = TRUE)}),
  median = apply(gene1, 2, function(x) {median(x, na.rm = TRUE)}),
  min = apply(gene1, 2, function(x) {min(x, na.rm = TRUE)}),
  set = rownames(microarray[1,]),
  extra = apply(microarray[1:58], 2, function(x) {median(x)})
);

polygon.data.two.genes <- rbind(
  polygon.data.gene1,
  data.frame(
    x = 1:58,
    max = apply(gene2, 2, function(x) {max(x, na.rm = TRUE)}),
    median = apply(gene2, 2, function(x) {median(x, na.rm = TRUE)}),
    min = apply(gene2, 2, function(x) {min(x, na.rm = TRUE)}),
    set = rownames(microarray[2,]),
    extra = apply(microarray[1:58], 2, function(x) {median(x)})
  )
)

# Minimal Input
create.polygonplot(
  filename = tempfile(pattern = 'Polygon_Minimal_Input', fileext = '.tiff'),
  formula = NA ~ x,
  data = polygon.data.gene1,
  max = polygon.data.gene1$max,
  min = polygon.data.gene1$min,
  main = 'Minimal input',
  xlims = c(0,58),
  ylims = c (2,5),
  description = 'Polygon created by BoutrosLab.plotting.general',
  resolution = 100
);

# Axes & Labels
create.polygonplot(
  filename = tempfile(pattern = 'Polygon_Axes_Labels', fileext = '.tiff'),
  formula = NA ~ x,
  data = polygon.data.gene1,
  max = polygon.data.gene1$max,
  min = polygon.data.gene1$min,
  main = 'Axes & labels',
  xlims = c(0,58),
```

```

ylimits = c (0,10),
# Axes & Labels
xlab.label = 'Samples',
ylab.label = 'Value',
xaxis.cex = 1,
yaxis.cex = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
xaxis.fontface = 1,
yaxis.fontface = 1,
xat = seq(0, 58, 5),
yat = seq(0, 10, 2),
description = 'Polygon created by BoutrosLab.plotting.general',
resolution = 100
);

# Colour
create.polygonplot(
  filename = tempfile(pattern = 'Polygon_Colour', fileext = '.tiff'),
  formula = NA ~ x,
  data = polygon.data.gene1,
  max = polygon.data.gene1$max,
  min = polygon.data.gene1$min,
  main = 'Colour',
  xlims = c(0,58),
  ylims = c (0,10),
  xlab.label = 'Samples',
  ylab.label = 'Value',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xat = seq(0, 58, 5),
  yat = seq(0, 10, 2),
  # Colour
  col = default.colours(1),
  description = 'Polygon created by BoutrosLab.plotting.general',
  resolution = 100
);

# Add median line and points
create.polygonplot(
  filename = tempfile(pattern = 'Polygon_Median_Points', fileext = '.tiff'),
  formula = NA ~ x,
  data = polygon.data.gene1,
  max = polygon.data.gene1$max,
  min = polygon.data.gene1$min,
  # Median
  median = polygon.data.gene1$median,
  add.median = TRUE,
  main = 'Plotting character',
)

```

```
    xlims = c(0,58),
    ylims = c (0,10),
    xlab.label = 'Samples',
    ylab.label = 'Value',
    xaxis.cex = 1,
    yaxis.cex = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    xat = seq(0, 58, 5),
    yat = seq(0, 10, 2),
    col = default.colours(1),
    # border points
    add.xy.border = TRUE,
    description = 'Polygon created by BoutrosLab.plotting.general',
    resolution = 100
);

# Additional Data
create.polygonplot(
  filename = tempfile(pattern = 'Polygon_Extra_Data', fileext = '.tiff'),
  formula = NA ~ x,
  # divide data
  groups = set,
  data = polygon.data.two.genes,
  max = polygon.data.two.genes$max,
  min = polygon.data.two.genes$min,
  main = 'Two data sets',
  median = polygon.data.two.genes$median,
  add.median = TRUE,
  xlims = c(0,58),
  ylims = c (0,15),
  xlab.label = 'Samples',
  ylab.label = 'Value',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xat = seq(0, 58, 5),
  yat = seq(0, 14, 2),
  # Increasing number of colours
  col = default.colours(2),
  description = 'Polygon created by BoutrosLab.plotting.general',
  resolution = 100
);

# Legend
create.polygonplot(
  filename = tempfile(pattern = 'Polygon_Legend', fileext = '.tiff'),
```

```

formula = NA ~ x,
groups = set,
data = polygon.data.two.genes,
max = polygon.data.two.genes$max,
min = polygon.data.two.genes$min,
main = 'Legend',
median = polygon.data.two.genes$median,
add.median = TRUE,
xlims = c(0,58),
ylims = c (0,15),
xlab.label = 'Samples',
ylab.label = 'Value',
xaxis.cex = 1,
yaxis.cex = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
xaxis.fontface = 1,
yaxis.fontface = 1,
xat = seq(0, 58, 5),
yat = seq(0, 14, 2),
col = default.colours(2),
# Adding legend
key = list(
  text = list(
    lab = rownames(microarray[1:2,]),
    cex = 0.8,
    col = 'black'
  ),
  points = list(
    pch = 15,
    col = default.colours(2),
    cex = 2
  ),
  x = 0.04,
  y = 0.93,
  padding.text = 3,
  columns = 1
),
description = 'Polygon created by BoutrosLab.plotting.general',
resolution = 200
);

# Panel Organisation
create.polygonplot(
  filename = tempfile(pattern = 'Polygon_Panel', fileext = '.tiff'),
  # divide data
  formula = NA ~ x | set,
  data = polygon.data.two.genes,
  max = polygon.data.two.genes$max,
  min = polygon.data.two.genes$min,
  main = 'Panel',
  median = polygon.data.two.genes$median,
  add.median = TRUE,

```

```
    xlims = c(0,58),
    ylims = c (0,15),
    xlab.label = 'Samples',
    ylab.label = 'Value',
    xaxis.cex = 1,
    yaxis.cex = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    xat = seq(0, 58, 5),
    yat = seq(0, 14, 2),
    col = default.colours(1),
    description = 'Polygon created by BoutrosLab.plotting.general',
    resolution = 200
);

# Extra Points
create.polygonplot(
  filename = tempfile(pattern = 'Polygon_Extra_Points', fileext = '.tiff'),
  formula = NA ~ x,
  groups = set,
  data = polygon.data.two.genes,
  max = polygon.data.two.genes$max,
  min = polygon.data.two.genes$min,
  main = 'Extra points',
  median = polygon.data.two.genes$median,
  add.median = TRUE,
  xlims = c(0,58),
  ylims = c (0,15),
  xlab.label = 'Samples',
  ylab.label = 'Value',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xat = seq(0, 58, 5),
  yat = seq(0, 14, 2),
  col = default.colours(2),
  # Add to legend
  key = list(
    text = list(
      lab = c(rownames(microarray[1:2,]), 'All genes'),
      cex = 0.8,
      col = 'black'
    ),
    points = list(
      pch = c(15, 15, 3),
      col = c(default.colours(2), 'red'),
      cex = c(2, 2, 0.7)
    ),
  )
)
```

```

x = 0.04,
y = 0.93,
padding.text = 3,
columns = 1
),
# Extra points
extra.points = list(
  x = polygon.data.two.genes$x,
  y = polygon.data.two.genes$extra
),
extra.points.col = 'red',
extra.points.pch = 3,
extra.points.type = c('p', 'l'),
extra.points.cex = 0.7,
description = 'Polygon created by BoutrosLab.plotting.general',
resolution = 200
);

# Nature style
create.polygonplot(
  filename = tempfile(pattern = 'Polygon_Nature_style', fileext = '.tiff'),
  formula = NA ~ x,
  groups = set,
  data = polygon.data.two.genes,
  max = polygon.data.two.genes$max,
  min = polygon.data.two.genes$min,
  main = 'Nature style',
  median = polygon.data.two.genes$median,
  add.median = TRUE,
  xlims = c(0,58),
  ylims = c (0,15),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xat = seq(0, 58, 5),
  yat = seq(0, 14, 2),
  col = default.colours(2),
  # Adding legend
  key = list(
    text = list(
      lab = rownames(microarray[1:2,]),
      cex = 0.8,
      col = 'black'
    ),
    points = list(
      pch = 15,
      col = default.colours(2),
      cex = 2
    ),
    x = 0.04,
    y = 0.93
  )
)

```

```
y = 0.93,  
padding.text = 3,  
columns = 1  
,  
  
# set style to Nature  
style = 'Nature',  
  
# demonstrating how to italicize character variables  
ylab.label = expression(paste('italicized ', italic('a'))),  
  
# demonstrating how to create en-dashes  
xlab.label = expression(paste('en dashes: 1', '\u2013', '10' '^' '\u2013', ''^3)),  
  
description = 'Polygon created by BoutrosLab.plotting.general',  
resolution = 1200  
);
```

create.qqplot.comparison

Make a quantile-quantile plot of two samples

Description

Takes two samples and creates a qq plot for comparing two distributions, possibly conditioned on other variables

Usage

```
create.qqplot.comparison(  
x,  
data = NULL,  
filename = NULL,  
groups = NULL,  
main = NULL,  
main.just = 'center',  
main.x = 0.5,  
main.y = 0.5,  
main.cex = 3,  
aspect = 'fill',  
prepanel = NULL,  
xlab.label = NULL,  
ylab.label = NULL,  
xlab.cex = 2,  
ylab.cex = 2,  
xlab.col = 'black',  
ylab.col = 'black',
```

```
  xlims = NULL,
  ylims = NULL,
  xat = TRUE,
  yat = TRUE,
  xaxis.lab = NA,
  yaxis.lab = NA,
  xaxis.cex = 1.5,
  yaxis.cex = 1.5,
  xaxis.fontface = 'bold',
  yaxis.fontface = 'bold',
  xaxis.log = FALSE,
  yaxis.log = FALSE,
  xaxis.rot = 0,
  yaxis.rot = 0,
  xaxis.col = 'black',
  yaxis.col = 'black',
  xaxis.tck = 1,
  yaxis.tck = 1,
  xlab.top.label = NULL,
  xlab.top.cex = 2,
  xlab.top.col = 'black',
  xlab.top.just = 'center',
  xlab.top.x = 0.5,
  xlab.top.y = 0,
  add.grid = FALSE,
  xgrid.at = xat,
  ygrid.at = yat,
  type = 'p',
  cex = 0.75,
  pch = 19,
  col = 'black',
  lwd = 1,
  lty = 1,
  axes.lwd = 2.25,
  key = list(text = list(lab = c(''))),
  legend = NULL,
  add.rectangle = FALSE,
  xleft.rectangle = NULL,
  ybottom.rectangle = NULL,
  xright.rectangle = NULL,
  ytop.rectangle = NULL,
  col.rectangle = 'transparent',
  alpha.rectangle = 1,
  top.padding = 3,
  bottom.padding = 0.7,
  left.padding = 0.5,
  right.padding = 0.1,
  height = 6,
```

```

width = 6,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
description = 'Created with BoutrosLab.plotting.general',
style = 'BoutrosLab',
preload.default = 'custom',
use.legacy.settings = FALSE,
inside.legend.auto = FALSE
);

```

Arguments

x	A formula or a list of two numeric vectors
data	An optional data source if x is a formula
filename	Filename for tiff output, or if NULL returns the trellis object itself
aspect	This argument controls the physical aspect ratio of the panels, defaults to “fill”
prepanel	A function that takes the same arguments as the “panel”
add.grid	Default manner of drawing grid lines - for custom grids, use type = c('p','g') and set the xat, yat, xgrid.at, ygrid.at parameters
groups	The grouping variable in the data-frame
main	The main plot title
main.just	The justification of the main title for the plot, default is centered
main.x	The x location of the main title, default is 0.5
main.y	The y location of the main title, default is 0.5
xlab.label	The label for the x-axis
ylab.label	The label for the y-axis
main.cex	Size of the overall plot title, defaults to 3
xlab.cex	Size of x-axis label, defaults to 2.5
ylab.cex	Size of y-axis label, defaults to 2.5
xlab.col	Colour of the x-axis label, defaults to “black”
ylab.col	Colour of the y-axis label, defaults to “black”
xlab.top.label	The label for the top x-axis
xlab.top.cex	Size of top x-axis label
xlab.top.col	Colour of the top x-axis label
xlab.top.just	Justification of the top x-axis label, defaults to centered
xlab.top.x	The x location of the top x-axis label
xlab.top.y	The y location of the top y-axis label
xlimits	Two-element vector giving the x-axis limits, defaults to automatic
ylimits	Two-element vector giving the y-axis limits, defaults to automatic
xat	Vector listing where the x-axis labels should be drawn, defaults to automatic

<code>yat</code>	Vector listing where the y-axis labels should be drawn, defaults to automatic
<code>xgrid.at</code>	Vector listing where the x-axis grid lines should be drawn, defaults to <code>xat</code>
<code>ygrid.at</code>	Vector listing where the y-axis grid lines should be drawn, defaults to <code>yat</code>
<code>xaxis.lab</code>	Vector listing x-axis tick labels, defaults to automatic
<code>yaxis.lab</code>	Vector listing y-axis tick labels, defaults to automatic
<code>xaxis.col</code>	Colour of the x-axis tick labels, defaults to “black”
<code>yaxis.col</code>	Colour of the y-axis tick labels, defaults to “black”
<code>xaxis.cex</code>	Size of x-axis scales, defaults to 1.5
<code>yaxis.cex</code>	Size of y-axis scales, defaults to 1.5
<code>xaxis.fontface</code>	Fontface for the x-axis scales
<code>yaxis.fontface</code>	Fontface for the y-axis scales
<code>xaxis.log</code>	Logical indicating whether x-variable should be in logarithmic scale (and what base if numeric)
<code>yaxis.log</code>	Logical indicating whether y-variable should be in logarithmic scale (and what base if numeric)
<code>xaxis.rot</code>	Counterclockwise rotation of text in x-axis scales in degrees, defaults to 0
<code>yaxis.rot</code>	Counterclockwise rotation of text in y-axis scales in degrees, defaults to 0
<code>xaxis.tck</code>	Specifies the length of the tick marks for x-axis, defaults to 1
<code>yaxis.tck</code>	Specifies the length of the tick marks for y-axis, defaults to 1
<code>type</code>	Plot type
<code>cex</code>	Character expansion for plotting symbol
<code>pch</code>	Plotting character
<code>col</code>	Point/line colour
<code>lwd</code>	Specifies line width, defaults to 1
<code>lty</code>	Specifies line style, defaults to 1 (solid)
<code>axes.lwd</code>	Thickness of width of axes lines
<code>key</code>	A list giving the key (legend). The default suppresses drawing
<code>legend</code>	Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See <code>xyplot</code> .
<code>top.padding</code>	A number giving the top padding in multiples of the lattice default
<code>bottom.padding</code>	A number giving the bottom padding in multiples of the lattice default
<code>left.padding</code>	A number giving the left padding in multiples of the lattice default
<code>right.padding</code>	A number giving the right padding in multiples of the lattice default
<code>height</code>	Figure height, defaults to 6 inches
<code>width</code>	Figure width, defaults to 6 inches
<code>size.units</code>	Figure units, defaults to inches
<code>resolution</code>	Figure resolution in dpi, defaults to 1600

```

enable.warnings
    Print warnings if set to TRUE, defaults to FALSE
description
    Short description of image/plot; default NULL.
add.rectangle
    Allow a rectangle to be drawn, default is FALSE
xleft.rectangle
    Specifies the left x coordinate of the rectangle to be drawn
ybottom.rectangle
    Specifies the bottom y coordinate of the rectangle to be drawn
xright.rectangle
    Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle
    Specifies the top y coordinate of the rectangle to be drawn
col.rectangle
    Specifies the colour to fill the rectangle's area
alpha.rectangle
    Specifies the colour bias of the rectangle to be drawn
style
    defaults to "BoutrosLab", also accepts "Nature", which changes parameters according to Nature formatting requirements
preload.default
    ability to set multiple sets of different defaults depending on publication needs
use.legacy.settings
    boolean to set whether or not to use legacy mode settings (font)
inside.legend.auto
    boolean specifying whether or not to use the automatic inside legend function

```

Value

If filename is NULL then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Author(s)

Ying Wu

See Also

[qq](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```

set.seed(12345);

create.qqplot.comparison(
  filename = tempfile(pattern = 'QQcomparison_Simple', fileext = '.tiff'),
  x = list(rnorm(100), rnorm(100)),
  resolution = 50
);

```

```

# Minimal Input
create.qqplot.comparison(
  filename = tempfile(pattern = 'QQcomparison_Minimal_Input', fileext = '.tiff'),
  x = list(microarray[1:500,2], microarray[1:500,2]),
  main = 'Minimal input',
  description = 'QQplot comparison created by BoutrosLab.plotting.general',
  resolution = 50
);

# Axes & Labels
create.qqplot.comparison(
  filename = tempfile(pattern = 'QQcomparison_Axes_Labels', fileext = '.tiff'),
  x = list(microarray[1:500,2], microarray[1:500,2]),
  main = 'Axes & labels',
  # adding axes and labels
  xlab.label = 'Sample 1',
  ylab.label = 'Sample 2',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  # adding grid for good measure
  add.grid = TRUE,
  description = 'QQplot comparison created by BoutrosLab.plotting.general',
  resolution = 100
);

# Formula input

# 'Formula' format of data
chr.locations <- microarray$Chr[1:500];
chr.locations <- replace(chr.locations, which(chr.locations == 1), 'Chromosome 1');
chr.locations <- replace(chr.locations, which(chr.locations == 2), 'Chromosome 2');

qqplot.data <- data.frame(
  sample = c(rep('Sample 1', 500), rep('Sample 2', 500)),
  value = c(microarray[1:500,1], microarray[1:500,2]),
  chr = chr.locations
);

create.qqplot.comparison(
  filename = tempfile(pattern = 'QQcomparison_Formula', fileext = '.tiff'),
  # Using a different input method
  x = sample ~ value,
  data = qqplot.data,
  main = 'Formula input',
  xlab.label = 'Sample 1',
  ylab.label = 'Sample 2',
  xaxis.lab = seq(0, 15, 5),
  yaxis.lab = seq(0, 15, 5),
  xlims = c(0, 17),
  ylims = c(0, 17),
  xlab.cex = 1.5,
  ylab.cex = 1.5,

```

```
add.grid = TRUE,
description = 'QQplot comparison created by BoutrosLab.plotting.general',
resolution = 200
);

# Groups & Legend
create.qqplot.comparison(
  filename = tempfile(pattern = 'QQcomparison_Groups_Legend', fileext = '.tiff'),
  x = sample ~ value,
  data = qqplot.data,
  # Using fake grouping for the sake of illustration
  groups = qqplot.data$chr,
  # Set colours to differente the gruops
  col = default.colours(3),
  # Setting different plotting characters
  pch = c(15, 16),
  main = 'Groups & legend',
  xlab.label = 'Sample 1',
  ylab.label = 'Sample 2',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  add.grid = TRUE,
  # Adding legend to explain groups
  key = list(
    text = list(
      lab = c('1','2'),
      cex = 1.5,
      col = 'black'
    ),
    points = list(
      pch = c(15, 16),
      col = default.colours(2),
      cex = 1
    ),
    x = 0.04,
    y = 0.95,
    padding.text = 2
  ),
  description = 'QQplot comparison created by BoutrosLab.plotting.general',
  resolution = 200
);

# Multiple qq plots
create.qqplot.comparison(
  filename = tempfile(pattern = 'QQcomparison_Multiple', fileext = '.tiff'),
  x = sample ~ value | chr,
  data = qqplot.data,
  main = 'Multiple plots',
  xlab.label = 'Sample 1',
  ylab.label = 'Sample 2',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
```

```

add.grid = TRUE,
description = 'QQplot comparison created by BoutrosLab.plotting.general',
resolution = 200
);

# Nature style
create.qqplot.comparison(
  filename = tempfile(pattern = 'QQcomparison_Nature_style', fileext = '.tiff'),
  x = sample ~ value,
  data = qqplot.data,
  main = 'Nature style',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  add.grid = TRUE,

# set style to Nature
style = 'Nature',

# demonstrating how to italicize character variables
ylab.label = expression(paste('italicized ', italic('a'))),

# demonstrating how to create en-dashes
xlab.label = expression(paste('en dashes: 1', '\u2013', '10' '^' '\u2013', ''^3)),

description = 'QQplot comparison created by BoutrosLab.plotting.general',
resolution = 200
);

```

create.qqplot.fit *Make a quantile-quantile plot of a sample*

Description

Takes a sample and creates a qq plot against a theoretical distribution, possibly conditioned on other variables.

Usage

```

create.qqplot.fit(
  x,
  data = NA,
  filename = NULL,
  groups = NULL,
  confidence.bands = FALSE,
  conf = 0.95,
    confidence.method = 'both',
  reference.line.method = 'quartiles',
  distribution = qnorm,

```

```
aspect = 'fill',
        prepanel = NULL,
main = NULL,
main.just = 'center',
main.x = 0.5,
main.y = 0.5,
main.cex = 3,
        xlab.label = NULL,
ylab.label = NULL,
xlab.cex = 2,
ylab.cex = 2,
xlab.col = 'black',
ylab.col = 'black',
        xlab.top.label = NULL,
xlab.top.cex = 2,
xlab.top.col = 'black',
xlab.top.just = 'center',
xlab.top.x = 0.5,
        xlab.top.y = 0,
xlimits = NULL,
ylimits = NULL,
xat = TRUE,
yat = TRUE,
xaxis.lab = NA,
yaxis.lab = NA,
        xaxis.cex = 1.5,
yaxis.cex = 1.5,
xaxis.col = 'black',
yaxis.col = 'black',
xaxis.fontface = 'bold',
        yaxis.fontface = 'bold',
xaxis.log = FALSE,
yaxis.log = FALSE,
xaxis.rot = 0,
yaxis.rot = 0,
xaxis.tck = 1,
        yaxis.tck = 1,
add.grid = FALSE,
xgrid.at = xat,
ygrid.at = yat,
type = 'p',
cex = 0.75,
pch = 19,
col = 'black',
        col.line = 'grey',
lwd = 2,
lty = 1,
axes.lwd = 2.25,
```

```

key = list(text = list(lab = c(''))),
legend = NULL,
      add.rectangle = FALSE,
xleft.rectangle = NULL,
ybottom.rectangle = NULL,
xright.rectangle = NULL,
      ytop.rectangle = NULL,
col.rectangle = 'transparent',
alpha.rectangle = 1,
top.padding = 3,
bottom.padding = 0.7,
      left.padding = 0.5,
right.padding = 0.1,
height = 6,
width = 6,
size.units = 'in',
resolution = 1600,
      enable.warnings = FALSE,
description = 'Created with BoutrosLab.plotting.general',
      style = 'BoutrosLab',
preload.default = 'custom',
use.legacy.settings = FALSE,
inside.legend.auto = FALSE
);

```

Arguments

<code>x</code>	A formula or a numeric vector
<code>data</code>	An optional data source if <code>x</code> is a formula
<code>filename</code>	Filename for tiff output, or if <code>NULL</code> returns the trellis object itself
<code>groups</code>	The grouping variable in the data-frame
<code>confidence.bands</code>	Add confidence bands or not, default to <code>FALSE</code> . Note that in this function, the confidence band can only be added to a single plot, not for multi-qq plot.
<code>conf</code>	Confidence level, default to <code>0.95</code>
<code>confidence.method</code>	Methods used to draw confidence bands: “ <code>simultaneous</code> ”, “ <code>pointwise</code> ”, “ <code>both</code> ”, defaults to “ <code>both</code> ”.
<code>reference.line.method</code>	Methods used to draw reference line and must be one of “ <code>quartiles</code> ”(default), “ <code>diagonal</code> ”, “ <code>robust</code> ”. “ <code>quartiles</code> ” will draw a line across 1/4 and 3/4 quantiles, “ <code>diagonal</code> ” will draw a 0-1 line, “ <code>robust</code> ” will draw a best fit line basing on linear model. Note: for multi-panel plot, only the default one is applicable.
<code>distribution</code>	A quantile function that takes a vector of probabilities as argument and produces the corresponding quantiles from a theoretical distribution, defaults to “ <code>qnorm</code> ”, that is normal distribution.
<code>aspect</code>	This argument controls the physical aspect ratio of the panels, defaults to “ <code>fill</code> ”

prepanel	A function that takes the same arguments as the “panel”
main	The main plot title
main.just	The justification of the main title for the plot, default is centered
main.x	The x location of the main title, default is 0.5
main.y	The y location of the main title, default is 0.5
main.cex	Size of the overall plot title, defaults to 3
xlab.label	x-axis title
ylab.label	y-axis title
xlab.cex	Size of x-axis label, defaults to 2.5
ylab.cex	Size of y-axis label, defaults to 2.5
xlab.col	Colour of the x-axis label, defaults to “black”
ylab.col	Colour of the y-axis label, defaults to “black”
xlab.top.label	The label for the top x-axis
xlab.top.cex	Size of top x-axis label
xlab.top.col	Colour of the top x-axis label
xlab.top.just	Justification of the top x-axis label, defaults to centered
xlab.top.x	The x location of the top x-axis label
xlab.top.y	The y location of the top y-axis label
xlimits	Two-element vector giving the x-axis limits, defaults to automatic
ylimits	Two-element vector giving the y-axis limits, defaults to automatic
xat	Vector listing where the x-axis labels should be drawn, defaults to automatic
yat	Vector listing where the y-axis labels should be drawn, defaults to automatic
xaxis.lab	Vector listing x-axis tick labels, defaults to automatic
yaxis.lab	Vector listing y-axis tick labels, defaults to automatic
xaxis.cex	Size of x-axis scales, defaults to 1.5
yaxis.cex	Size of y-axis scales, defaults to 1.5
xaxis.col	Colour of the x-axis tick labels, defaults to “black”
yaxis.col	Colour of the y-axis tick labels, defaults to “black”
xaxis.fontface	Fontface for the x-axis scales
yaxis.fontface	Fontface for the y-axis scales
xaxis.log	Logical indicating whether x-variable should be in logarithmic scale (and what base if numeric)
yaxis.log	Logical indicating whether y-variable should be in logarithmic scale (and what base if numeric)
xaxis.rot	Counterclockwise rotation of text in x-axis scales in degrees, defaults to 0
yaxis.rot	Counterclockwise rotation of text in y-axis scales in degrees, defaults to 0
xaxis.tck	Specifies the length of the tick marks for x-axis, defaults to 1
yaxis.tck	Specifies the length of the tick marks for y-axis, defaults to 1

add.grid	Default manner of drawing grid lines
xgrid.at	Vector listing where the x-axis grid lines should be drawn, defaults to xat
ygrid.at	Vector listing where the y-axis grid lines should be drawn, defaults to yat
type	Plot type
cex	Character expansion for plotting symbol
pch	Plotting character
col	Point colour
col.line	QQ line colour, defaults to grey
lw	Specifies line width, defaults to 2
lty	Specifies line style, defaults to 1 (solid)
axes.lwd	Thickness of width of axes lines
key	A list giving the key (legend). The default suppresses drawing
legend	Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See xyplot.
add.rectangle	Allow a rectangle to be drawn, default is FALSE
xleft.rectangle	Specifies the left x coordinate of the rectangle to be drawn
ybottom.rectangle	Specifies the bottom y coordinate of the rectangle to be drawn
xright.rectangle	Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle	Specifies the top y coordinate of the rectangle to be drawn
col.rectangle	Specifies the colour to fill the rectangle's area
alpha.rectangle	Specifies the colour bias of the rectangle to be drawn
top.padding	A number giving the top padding in multiples of the lattice default
bottom.padding	A number giving the bottom padding in multiples of the lattice default
left.padding	A number giving the left padding in multiples of the lattice default
right.padding	A number giving the right padding in multiples of the lattice default
height	Figure height, defaults to 6 inches
width	Figure width, defaults to 6 inches
size.units	Figure units, defaults to inches
resolution	Figure resolution in dpi, defaults to 1600
enable.warnings	Print warnings if set to TRUE, defaults to FALSE
description	Short description of image/plot; default NULL.
style	defaults to "BoutrosLab", also accepts "Nature", which changes parameters according to Nature formatting requirements
preload.default	ability to set multiple sets of different defaults depending on publication needs
use.legacy.settings	boolean to set whether or not to use legacy mode settings (font)
inside.legend.auto	boolean specifying whether or not to use the automatic inside legend function

Value

If `filename` is `NULL` then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

Note that the confidence band only works for a single panel qq plot, not for grouped data and multi-qq plot. Why? What's missing?

Author(s)

Ying Wu

See Also

[qqmath](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(12345);
create.qqplot.fit(
  filename = tempfile(pattern = 'QQfit_Simple', fileext = '.tiff'),
  x = rnorm(300),
  # choosing to compare against a uniform distribution
  distribution = qunif,
  resolution = 100
);

# Minimal Input
create.qqplot.fit(
  filename = tempfile(pattern = 'QQfit_Minimal_Input', fileext = '.tiff'),
  x = microarray[1:500,1],
  # choosing to compare against a uniform distribution
  distribution = qunif,
  main = 'Minimal input',
  description = 'QQplot fit created by BoutrosLab.plotting.general',
  resolution = 100
);

# Axes and Labels
create.qqplot.fit(
  filename = tempfile(pattern = 'QQfit_Axes_Labels', fileext = '.tiff'),
  x = microarray[1:500,1],
  distribution = qunif,
  main = 'Axes & labels',
  # Adding axes labels
  xlab.label = 'qunif',
  ylab.label = 'sample values',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
```

```
xaxis.cex = 1,
yaxis.cex = 1,
add.grid = TRUE,
description = 'QQplot fit created by BoutrosLab.plotting.general',
resolution = 100
);

# Confidence bands
create.qqplot.fit(
  filename = tempfile(pattern = 'QQfit_Confidence_Bands', fileext = '.tiff'),
  x = microarray[1:500,1],
  distribution = qunif,
  main = 'Confidence bands',
  xlab.label = 'qunif',
  ylab.label = 'sample values',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xaxis.cex = 1,
  yaxis.cex = 1,
  add.grid = TRUE,
  # Adding confidence bands (auto-generates legend)
  confidence.bands = TRUE,
  confidence.method = 'both',
  description = 'QQplot fit created by BoutrosLab.plotting.general',
  resolution = 100
);

# Multiple qq plot conditioned on a variable
# 'Formula' format of data
chr.locations <- microarray$Chr[1:500];
chr.locations <- replace(chr.locations, which(chr.locations == 1), 'Chromosome 1');
chr.locations <- replace(chr.locations, which(chr.locations == 2), 'Chromosome 2');

qqplot.data <- data.frame(
  value = microarray[1:500,1],
  chr = chr.locations
);

create.qqplot.fit(
  filename = tempfile(pattern = 'QQfit_Multiple', fileext = '.tiff'),
  x = ~ value | chr,
  data = qqplot.data,
  distribution = qunif,
  main = 'Multiple plots',
  xlab.label = 'qunif',
  ylab.label = 'sample values',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
```

```
    xaxis.cex = 1,
    yaxis.cex = 1,
    add.grid = TRUE,
    confidence.bands = TRUE,
    confidence.method = 'simultaneous',
    description = 'QQplot fit created by BoutrosLab.plotting.general',
    resolution = 100
);

# Grouped qq plot
create.qqplot.fit(
  filename = tempfile(pattern = 'QQfit_Grouped', fileext = '.tiff'),
  x = ~ value,
  data = qqplot.data,
  # Adding groups
  groups = qqplot.data$chr,
  # Colouring groups
  col = default.colours(2),
  # Setting different plotting characters
  pch = c(15, 19),
  distribution = qunif,
  main = 'Grouped & legend',
  xlab.label = 'qunif',
  ylab.label = 'sample values',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xaxis.cex = 1,
  yaxis.cex = 1,
  add.grid = TRUE,
  confidence.bands = TRUE,
  confidence.method = 'simultaneous',
  # Adding legend for groups
  key = list(
    text = list(
      lab = c('1','2'),
      cex = 1,
      col = 'black'
    ),
    points = list(
      pch = c(15, 19),
      col = default.colours(2),
      cex = 1
    ),
    x = 0.04,
    y = 0.95,
    padding.text = 2
  ),
  description = 'QQplot fit created by BoutrosLab.plotting.general',
  resolution = 100
);
```

```
# Correlation Key
create.qqplot.fit(
  filename = tempfile(pattern = 'QQfit_Correlation_Key', fileext = '.tiff'),
  x = ~ value,
  data = qqplot.data,
  groups = qqplot.data$chr,
  col = default.colours(2),
  pch = c(15, 19),
  distribution = qunif,
  main = 'Correlation key',
  xlab.label = 'qunif',
  ylab.label = 'sample values',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xaxis.cex = 1,
  yaxis.cex = 1,
  add.grid = TRUE,
  confidence.bands = TRUE,
  confidence.method = 'simultaneous',
  # Adjusting legend to contain multiple keys
  legend = list(
    inside = list(
      fun = draw.key,
      args = list(
        key = list(
          text = list(
            lab = c('1', '2'),
            cex = 1,
            col = 'black'
          ),
          points = list(
            pch = c(15, 19),
            col = default.colours(2),
            cex = 1
          ),
          x = 0.14,
          y = 0.80,
          padding.text = 2
        )
      )
    ),
    inside = list(
      fun = draw.key,
      args = list(
        key = get.corr.key(
          x = runif(500),
          y = qqplot.data$value,
          label.items = c('spearman', 'kendall', 'beta1'),
          alpha.background = 0,
          key.cex = 1
        )
      )
    )
  )
)
```

```

),
x = 0.75,
y = 0.20,
corner = c(0,1)
)
),
description = 'QQplot fit created by BoutrosLab.plotting.general',
resolution = 100
);

# Nature style
create.qqplot.fit(
  filename = tempfile(pattern = 'QQfit_Nature_style', fileext = '.tiff'),
  x = microarray[1:500,1],
  distribution = qunif,
  main = 'Nature style',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xaxis.cex = 1,
  yaxis.cex = 1,
  add.grid = TRUE,
  confidence.bands = TRUE,
  confidence.method = 'both',

  # set style to Nature
  style = 'Nature',

  # demonstrating how to italicize character variables
  ylab.label = expression(paste('italicized ', italic('a'))),

  # demonstrating how to create en-dashes
  xlab.label = expression(paste('en dashes: 1', '\u2013', '10' '^' '\u2013', '''^3)),

  description = 'QQplot fit created by BoutrosLab.plotting.general',
  resolution = 1200
);

```

create.qqplot.fit.confidence.interval*Create the confidence bands for a one-sample qq plot***Description**

Returns the values of constructing the confidence bands for a one-sample qq plot

Usage

```
create.qqplot.fit.confidence.interval(x, distribution = qnorm, conf = 0.95,
                                       conf.method = "both", reference.line.method = "quartiles");
```

Arguments

<code>x</code>	A numeric vector
<code>distribution</code>	A quantile function that takes a vector of probabilities as argument and produces the corresponding quantiles from a theoretical distribution, defaults to "qnorm", that is normal distribution.
<code>conf</code>	Confidence level, default to 0.95
<code>conf.method</code>	Methods used to draw confidence bands and must be one of "simultaneous", "pointwise", "both"(default).
<code>reference.line.method</code>	Methods used to draw reference line and must be one of "quartiles"(default), "diagonal", "robust".

Value

Returns the values of creating the upper and lower bands for the qq plot.

Warning

Note that this function works only for a single panel qq plot, not for grouped data and multi-qq plot.

Author(s)

Ying Wu

Examples

```
tmp.x <- rnorm(100);

tmp.confidence.interval <- create.qqplot.fit.confidence.interval(tmp.x);

qqnorm(tmp.x);
qqline(tmp.x);
lines(tmp.confidence.interval$z, tmp.confidence.interval$upper.pw, lty = 2, col = "brown");
lines(tmp.confidence.interval$z, tmp.confidence.interval$lower.pw, lty = 2, col = "brown");
lines(tmp.confidence.interval$z[tmp.confidence.interval$u],
      tmp.confidence.interval$upper.sim, lty = 2, col = "blue");
lines(tmp.confidence.interval$z[tmp.confidence.interval$l],
      tmp.confidence.interval$lower.sim, lty = 2, col = "blue");

legend(1, -1.5, c("simultaneous", "pointwise"), col = c("blue", "brown"), lty = 2, bty = "n");
```

create.scatterplot *Make a scatterplot*

Description

Takes a data.frame and creates a scatterplot

Usage

```
create.scatterplot(  
  formula,  
  data,  
  filename = NULL,  
  groups = NULL,  
  main = NULL,  
  main.just = 'center',  
  main.x = 0.5,  
    main.y = 0.5,  
  main.cex = 3,  
  xlab.label = tail(sub('`', '', formula[-2]), 1),  
  ylab.label = tail(sub('`', '', formula[-3]), 1),  
    xlab.cex = 2,  
  ylab.cex = 2,  
  xlab.col = 'black',  
  ylab.col = 'black',  
    xlab.top.label = NULL,  
  xlab.top.cex = 2,  
  xlab.top.col = 'black',  
  xlab.top.just = 'center',  
  xlab.top.x = 0.5,  
    xlab.top.y = 0,  
  xlims = NULL,  
  ylims = NULL,  
  xat = TRUE,  
  yat = TRUE,  
  xaxis.lab = NA,  
  yaxis.lab = NA,  
  xaxis.log = FALSE,  
  yaxis.log = FALSE,  
    xaxis.cex = 1.5,  
  yaxis.cex = 1.5,  
  xaxis.rot = 0,  
  yaxis.rot = 0,  
  xaxis.fontface = 'bold',  
  yaxis.fontface = 'bold',  
  xaxis.col = 'black',  
  yaxis.col = 'black',
```

```
xaxis.tck = c(1,1),
yaxis.tck = c(1,1),
add.grid = FALSE,
xgrid.at = xat,
      ygrid.at = yat,
grid.colour = NULL,
horizontal = FALSE,
type = 'p',
cex = 0.75,
pch = 19,
col = 'black',
col.border = 'black',
lwd = 1,
lty = 1,
alpha = 1,
axes.lwd = 1,
strip.col = 'white',
strip.cex = 1,
strip.fontface = 'bold',
y.error.up = NULL,
y.error.down = y.error.up,
x.error.right = NULL,
x.error.left = x.error.right,
y.error.bar.col = 'black',
x.error.bar.col = y.error.bar.col,
error.whisker.angle = 90,
error.bar.lwd = 1,
error.bar.length = 0.1,
key = list(text = list(list(lab = c('')))),
legend = NULL,
top.padding = 0.1,
bottom.padding = 0.7,
right.padding = 0.1,
left.padding = 0.5,
key.top = 0.1,
key.left.padding = 0,
ylab.axis.padding = 1,
axis.key.padding = 1,
layout = NULL,
as.table = FALSE,
x.spacing = 0,
y.spacing = 0,
x.relation = 'same',
y.relation = 'same',
add.axes = FALSE,
axes.lty = 'dashed',
add.xyline = FALSE,
xyline.col = 'black',
```

```
xyline.lwd = 1,  
xyline.lty = 1,  
abline.h = NULL,  
abline.v = NULL,  
abline.col = 'black',  
abline.lwd = 1,  
abline.lty = 1,  
add.curves = FALSE,  
curves.exprs = NULL,  
curves.from = min(data, na.rm = TRUE),  
curves.to = max(data, na.rm = TRUE),  
curves.col = 'black',  
curves.lwd = 2,  
curves.lty = 1,  
add.rectangle = FALSE,  
xleft.rectangle = NULL,  
ybottom.rectangle = NULL,  
xright.rectangle = NULL,  
ytop.rectangle = NULL,  
col.rectangle = 'transparent',  
alpha.rectangle = 1,  
add.points = FALSE,  
points.x = NULL,  
points.y = NULL,  
points.pch = 19,  
points.col = 'black',  
points.col.border = 'black',  
points.cex = 1,  
add.line.segments = FALSE,  
line.start = NULL,  
line.end = NULL,  
line.col = 'black',  
line.lwd = 1,  
add.text = FALSE,  
text.labels = NULL,  
text.x = NULL,  
text.y = NULL,  
text.col = 'black',  
text.cex = 1,  
text.fontface = 'bold',  
text.guess.labels = FALSE,  
text.guess.skip.labels = TRUE,  
text.guess.ignore.radius = FALSE,  
text.guess.ignore.rectangle = FALSE,  
text.guess.radius.factor = 1,  
text.guess.buffer.factor = 1,  
text.guess.label.position = NULL,  
height = 6,
```

```

width = 6,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
description = 'Created with BoutrosLab.plotting.general',
style = 'BoutrosLab',
preload.default = 'custom',
group.specific.colouring = TRUE,
use.legacy.settings = FALSE,
inside.legend.auto = FALSE,
regions.labels = c(),
  regions.start = c(),
regions.stop = c(),
regions.color = c("red"),
regions.cex = 1,
regions.alpha = 1,
  lollipop.bar.y = NULL,
lollipop.bar.color = "gray",
...
);

```

Arguments

<code>formula</code>	The formula used to extract the x & y components from the data-frame
<code>data</code>	The data-frame to plot
<code>filename</code>	Filename for tiff output, or if NULL returns the trellis object itself
<code>groups</code>	The grouping variable in the data-frame
<code>main</code>	The main title for the plot (space is reclaimed if NULL)
<code>main.just</code>	The justification of the main title for the plot, default is centered
<code>main.x</code>	The x location of the main title, default is 0.5
<code>main.y</code>	The y location of the main title, default is 0.5
<code>main.cex</code>	Size of text for main plot title
<code>xlab.label</code>	x-axis label
<code>ylab.label</code>	y-axis label
<code>xlab.cex</code>	Size of x-axis label, defaults to 3
<code>ylab.cex</code>	Size of y-axis label, defaults to 3
<code>xlab.col</code>	Colour of the x-axis label, defaults to "black"
<code>ylab.col</code>	Colour of the y-axis label, defaults to "black"
<code>xlab.top.label</code>	The label for the top x-axis
<code>xlab.top.cex</code>	Size of top x-axis label
<code>xlab.top.col</code>	Colour of the top x-axis label
<code>xlab.top.just</code>	Justification of the top x-axis label, defaults to centered
<code>xlab.top.x</code>	The x location of the top x-axis label

xlab.top.y	The y location of the top y-axis label
xlimits	Two-element vector giving the x-axis limits, defaults to automatic
ylimits	Two-element vector giving the y-axis limits, defaults to automatic
xat	Vector listing where the x-axis labels should be drawn, defaults to automatic
yat	Vector listing where the y-axis labels should be drawn, defaults to automatic
xaxis.lab	Vector listing x-axis tick labels, defaults to automatic
yaxis.lab	Vector listing y-axis tick labels, defaults to automatic
xaxis.log	Logical indicating whether x-variable should be in logarithmic scale (and what base if numeric)
yaxis.log	Logical indicating whether y-variable should be in logarithmic scale (and what base if numeric)
xaxis.cex	Size of x-axis scales, defaults to 2
yaxis.cex	Size of y-axis scales, defaults to 2
xaxis.rot	Counterclockwise rotation of text in x-axis scales in degrees, defaults to 0
yaxis.rot	Counterclockwise rotation of text in y-axis scales in degrees, defaults to 0
xaxis.fontface	Fontface for the x-axis scales
yaxis.fontface	Fontface for the y-axis scales
xaxis.col	Colour of the x-axis tick labels, defaults to “black”
yaxis.col	Colour of the y-axis tick labels, defaults to “black”
xaxis.tck	Specifies the length of the tick mark, defaults to 1 for both top and bottom axes
yaxis.tck	Specifies the length of the tick mark, defaults to 1 for both top and bottom axes
add.grid	Logical stating wheter or not the grid should be drawn on the plot
xgrid.at	Vector listing where the x-axis grid lines should be drawn, defaults to xat
ygrid.at	Vector listing where the y-axis grid lines should be drawn, defaults to yat
grid.colour	ability to set individual grid line colours
horizontal	xyplot-specific function that allows you to change if type='h' draws lines to the vertical or horizontal axis
type	Plot type
cex	Character expansion for plotting symbol
pch	Plotting character
col	Point/line colour
col.border	Colour of border when points pch >= 21. Defaults to “black”
lwd	Specifies line width, defaults to 1
lty	Specifies line style, defaults to 1 (solid)
alpha	Specifies line transparency, defaults to 1 (opaque)
axes.lwd	Thickness of width of axes lines
strip.col	Strip background colour, defaults to “white”
strip.cex	Strip title character expansion

strip.fontface Strip title fontface, defaults to bold

y.error.up upward error vector. Defaults to NULL. When y.error.up is NULL, vertical error bar is not drawn

y.error.down Downward error vector. Defaults to y.error.down to show symmetric error bars

x.error.right Rightward error vector. Defaults to NULL. When x.error.right is NULL, horizontal error bar is not drawn

x.error.left Leftward error vector. Defaults to x.error.right to show symmetric error bars

y.error.bar.col Colour of vertical error bar. Defaults to “black”

x.error.bar.col Colour of horizontal error bar. Defaults to “black”

error.whisker.angle Angle of the whisker drawn on error bar. Defaults to 90 degree

error.bar.lwd Error bar line width. Defaults to 1

error.bar.length Length of the error bar whiskers. Defaults to 0.1

key A list giving the key (legend). The default suppresses drawing

legend Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See *xyplot*.

top.padding A number specifying the distance to the top margin, defaults to 0.1

bottom.padding A number specifying the distance to the bottom margin, defaults to 0.7

right.padding A number specifying the distance to the right margin, defaults to 0.1

left.padding A number specifying the distance to the left margin, defaults to 0.5

key.top A number specifying the distance at top of key, defaults to 0.1

key.left.padding Amount of padding to go onto any legend on the left

ylab.axis.padding A number specifying the distance of ylabel to the y-axis, defaults to 1

axis.key.padding A number specifying the distance from the y-axis to the key, defaults to 1

layout A vector specifying the number of columns, rows (e.g., c(2,1)). Default is NULL; see *lattice::xyplot* for more details

as.table Specifies panel drawing order, default is FALSE which draws panels from bottom left corner, moving right then up. Set to TRUE to draw from top left corner, moving right then down

x.spacing A number specifying the distance between panels along the x-axis, defaults to 0

y.spacing A number specifying the distance between panels along the y-axis, defaults to 0

x.relation Allows x-axis scales to vary if set to “free”, defaults to “same”

y.relation Allows y-axis scales to vary if set to “free”, defaults to “same”

add.axes Allow axis lines to be turned on or off, default is FALSE

axes.lty Specifies axis line style, defaults to “dashed”

add.xyline	Allow y=x line to be drawn, default is FALSE
xyline.col	y=x line colour, defaults to black
xyline.lwd	Specifies y=x line width, defaults to 1
xyline.lty	Specifies y=x line style, defaults to 1 (solid)
abline.h	Allow horizontal line to be drawn, default to NULL
abline.v	Allow vertical line to be drawn, default to NULL
abline.col	Horizontal line colour, defaults to black
abline.lwd	Specifies horizontal line width, defaults to 1
abline.lty	Specifies horizontal line style, defaults to 1 (solid)
add.curves	Allow curves to drawn, default is FALSE
curves.exprs	A list of functions, expressions, or calls using "x" as a variable that specify the curves to be drawn
curves.from	Specifies the x co-ordinates at which the start of each curve should be drawn, defaults to drawing the curves to the left edge of the plotting region
curves.to	Specifies the x co-ordinates at which the end of each curve should be drawn, defaults to drawing the curves to the right edge of the plotting region
curves.col	Specifies colours of curves, default is black for each curve
curves.lwd	Specifies width of curves, default is 1 for each curve
curves.lty	Specifies type of curves, default is 1 (solid) for each curve
add.rectangle	Allow a rectangle to be drawn, default is FALSE
xleft.rectangle	Specifies the left x coordinate of the rectangle to be drawn
ybottom.rectangle	Specifies the bottom y coordinate of the rectangle to be drawn
xright.rectangle	Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle	Specifies the top y coordinate of the rectangle to be drawn
col.rectangle	Specifies the colour to fill rectangle's area
alpha.rectangle	Specifies the colour bias of the rectangle to be drawn
add.points	Allow additional points to be drawn, default is FALSE
points.x	The x co-ordinates where additional points should be drawn
points.y	The y co-ordinates where additional points should be drawn
points.pch	The plotting character for additional points
points.col	The colour of additional points
points.col.border	Colour of the border of additional points if points.pch >= 21. Defaults to black
points.cex	The size of additional points
add.line.segments	Allow additional line segments to be drawn, default is FALSE

<code>line.start</code>	The y co-ordinates where additional line segments should start
<code>line.end</code>	The y co-ordinates where additional line segments should end
<code>line.col</code>	The colour of additional line segments, default is black
<code>line.lwd</code>	The line width of additional line segments, default is 1
<code>add.text</code>	Allow additional text to be drawn, default is FALSE
<code>text.labels</code>	Labels for additional text
<code>text.x</code>	The x co-ordinates where additional text should be placed
<code>text.y</code>	The y co-ordinates where additional text should be placed
<code>text.col</code>	The colour of additional text
<code>text.cex</code>	The size of additional text
<code>text.fontface</code>	The fontface for additional text
<code>text.guess.labels</code>	Allows automatic labeling by considering values in <code>text.x</code> and <code>text.y</code> as a data point to be labelled, default is FALSE
<code>text.guess.skip.labels</code>	Provides an option to disregard automatic labelling algorithm if no space is available around a data point, thus forcing labelling if a collision is likely, default is TRUE
<code>text.guess.ignore.radius</code>	Allows the automatic labeling algorithm to ignore the radius space of a data point, useful to label a cluster of data points with a single text box, default is FALSE
<code>text.guess.ignore.rectangle</code>	Allows the automatic labeling algorithm to ignore the rectangle space of multiple potential label positions, default is FALSE
<code>text.guess.radius.factor</code>	A numeric value to factor the radius value to alter distance from the label and the data point
<code>text.guess.buffer.factor</code>	A numeric value to factor the buffer value to alter the space which is used to consider if data.points are potentially going to collide
<code>text.guess.label.position</code>	A numeric value between 0 and 360 to specify the precise angle of a text box center and the positive x-axis. Angles move counter-clockwise beginning at the positive x axis
<code>height</code>	Figure height, defaults to 6 inches
<code>width</code>	Figure width, defaults to 6 inches
<code>size.units</code>	Figure units, defaults to inches
<code>resolution</code>	Figure resolution in dpi, defaults to 1600
<code>enable.warnings</code>	Print warnings if set to TRUE, defaults to FALSE
<code>description</code>	Short description of image/plot; default NULL

style	defaults to “BoutrosLab”, also accepts “Nature”, which changes parameters according to Nature formatting requirements
preload.default	ability to set multiple sets of different defaults depending on publication needs
group.specific.colouring	Variable to specify if group specific multi colouring for error bars is enforced
use.legacy.settings	boolean to set whether or not to use legacy mode settings (font)
inside.legend.auto	boolean specifying whether or not to use the automatic inside legend function
regions.labels	Labels for each of the regions on the lollipop plots bars
regions.start	start x value of each of the regions
regions.stop	stop value for each of the regions
regions.color	color of each of the regions
regions.cex	size of the text of each of the regions
regions.alpha	alpha of each of the regions
lollipop.bar.y	y location of top of the lollipop plot bar – defaults to right above the bottom y axis
lollipop.bar.color	color of the lollipop plot bar
...	Additional arguments to be passed to xyplot

Value

If filename is NULL then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of create histogram is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```
Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics
```

Author(s)

Paul C. Boutros

See Also

[xyplot](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```

set.seed(12345);

simple.data <- data.frame(
  x = rnorm(800),
  y = rnorm(800)
);
create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Simple', fileext = '.tiff'),
  formula = y ~ x,
  data = simple.data,
  resolution = 50
);

scatter.data <- data.frame(
  sample.one = microarray[1:800,1],
  sample.two = microarray[1:800,2],
  chr = microarray$Chr[1:800]
);

# Minimal Input
create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Minimal_Input', fileext = '.tiff'),
  formula = sample.two ~ sample.one,
  data = scatter.data,
  main = 'Minimal Input',
  description = 'Scatter plot created by BoutrosLab.plotting.general',
  resolution = 50
);

# Axes & Labels
create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Axes_Labels', fileext = '.tiff'),
  formula = sample.two ~ sample.one,
  data = scatter.data,
  main = 'Axes & Labels',
  # Axes and labels
  xlab.label = colnames(microarray[1]),
  ylab.label = colnames(microarray[2]),
  xat = seq(0, 16, 2),
  yat = seq(0, 16, 2),
  xlims = c(0, 15),
  ylims = c(0, 15),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  description = 'Scatter plot created by BoutrosLab.plotting.general',
  resolution = 50
);

```

```
# Plotting space
create.scatterplot(
    filename = tempfile(pattern = 'Scatterplot_Plotting_Space', fileext = '.tiff'),
    formula = sample.two ~ sample.one,
    data = scatter.data,
    main = 'Plotting Space',
    xlab.label = colnames(microarray[1]),
    ylab.label = colnames(microarray[2]),
    # change axes accordingly
    xat = 2 ** (0:4),
    yat = seq(0, 16, 2),
    # change axes range accordingly
    xlims = c(2 ** 0,16),
    ylims = c(0, 15),
    # format labels
    xaxis.lab = c(
        expression('2''^'0'),
        expression('2''^'1'),
        expression('2''^'2'),
        expression('2''^'3'),
        expression('2''^'4')
    ),
    xaxis.cex = 1,
    yaxis.cex = 1,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    # Transform the x-axis into log-2 space
    xaxis.log = 2,
    description = 'Scatter plot created by BoutrosLab.plotting.general',
    resolution = 50
);

# Colour & Plotting Character
create.scatterplot(
    filename = tempfile(pattern = 'Scatterplot_Colour_Pch', fileext = '.tiff'),
    formula = sample.two ~ sample.one,
    data = scatter.data,
    main = 'Colour & Pch',
    xlab.label = colnames(microarray[1]),
    ylab.label = colnames(microarray[2]),
    xat = seq(0, 16, 2),
    yat = seq(0, 16, 2),
    xlims = c(0, 15),
    ylims = c(0, 15),
    xaxis.cex = 1,
    yaxis.cex = 1,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
```

```

# setting the colour
col = default.colours(2)[2],
# setting the plotting character type & size
pch = 21,
cex = 1.5,
description = 'Scatter plot created by BoutrosLab.plotting.general',
resolution = 100
);

# Colour depth
# create colour scheme to illustrate adding a colourkey
chr.palette <- colour.gradient(default.colours(2)[2], 800);

create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Colour_Depth', fileext = '.tiff'),
  formula = sample.two ~ sample.one,
  data = scatter.data,
  main = 'Colour Depth',
  xlab.label = colnames(microarray[1]),
  ylab.label = colnames(microarray[2]),
  xat = seq(0, 16, 2),
  yat = seq(0, 16, 2),
  xlims = c(0, 15),
  ylims = c(0, 15),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  # setting the colour
  col = chr.palette,
  # setting the plotting character type & size
  pch = 19,
  cex = 1,
  # adding key for colours
  key.top = 1.5,
  legend = list(
    bottom = list(
      fun = draw.colorkey,
      args = list(
        key = list(
          col = chr.palette,
          at = 1:800,
          tick.number = 3,
          space = 'bottom',
          size = 1,
          width = 1.25,
          height = 1,
          labels = list(
            labels = 1:3,
            cex = 1,
            at = c(1, which(scatter.data$chr == 2)[1], which(scatter.data$chr == 3)[1])

```

```
        )
      )
    )
  ),
description = 'Scatter plot created by BoutrosLab.plotting.general',
resolution = 100
);

# Groups & Legend
create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Groups_Legend', fileext = '.tiff'),
  formula = sample.two ~ sample.one,
  data = scatter.data,
  main = 'Groups & Legend',
  # using arbitrary groups for the sake of illustration
  groups = scatter.data$chr,
  xlab.label = colnames(microarray[1]),
  ylab.label = colnames(microarray[2]),
  xat = seq(0, 16, 2),
  yat = seq(0, 16, 2),
  xlims = c(0, 15),
  ylims = c(0, 15),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  col = default.colours(3),
  # Adding legend for groups
  key = list(
    text = list(
      lab = c('1','2','3'),
      cex = 1,
      col = 'black'
    ),
    points = list(
      pch = 19,
      col = default.colours(3),
      cex = 1
    ),
    x = 0.04,
    y = 0.95,
    padding.text = 2
  ),
  description = 'Scatter plot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Correlation Key
create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Correlation_Key', fileext = '.tiff'),
```

```

formula = sample.two ~ sample.one,
data = scatter.data,
main = 'Correlation Key',
xlab.label = colnames(microarray[1]),
ylab.label = colnames(microarray[2]),
xat = seq(0, 16, 2),
yat = seq(0, 16, 2),
xlims = c(0, 15),
ylims = c(0, 15),
xaxis.cex = 1,
yaxis.cex = 1,
xaxis.fontface = 1,
yaxis.fontface = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
col = 'black',
pch = 21,
# Adding correlation key
legend = list(
  inside = list(
    fun = draw.key,
    args = list(
      key = get.corr.key(
        x = scatter.data$sample.one,
        y = scatter.data$sample.two,
        label.items = c('spearman', 'spearman.p', 'kendall', 'beta1'),
        alpha.background = 0,
        key.cex = 1
      )
    ),
    x = 0.04,
    y = 0.95,
    corner = c(0,1)
  )
),
description = 'Scatter plot created by BoutrosLab.plotting.general',
resolution = 100
);

# Panel Organization
create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Panel_numeric_conditional', fileext = '.tiff'),
  formula = sample.two ~ sample.one | chr,
  data = scatter.data,
  main = 'Panel',
  xlab.label = colnames(microarray[1]),
  ylab.label = colnames(microarray[2]),
  xat = seq(0, 16, 2),
  yat = seq(0, 16, 2),
  xlims = c(0, 15),
  ylims = c(0, 15),
  xaxis.cex = 1,

```

```
yaxis.cex = 1,
xaxis.fontface = 1,
yaxis.fontface = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
pch = 21,
col = 'black',
fill = 'transparent',
# set up panel layout
layout = c(1,3),
yrelation = 'free',
description = 'Scatter plot created by BoutrosLab.plotting.general',
resolution = 100
);

scatter.data$chromosome <- as.character(scatter.data$chr);

create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Panel_character_conditional', fileext = '.tiff'),
  formula = sample.two ~ sample.one | chromosome,
  data = scatter.data,
  main = 'Panel',
  xlab.label = colnames(microarray[1]),
  ylab.label = colnames(microarray[2]),
  xat = seq(0, 16, 2),
  yat = seq(0, 16, 2),
  xlims = c(0, 15),
  ylims = c(0, 15),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  pch = 21,
  col = 'black',
  fill = 'transparent',
  # set up panel layout
  layout = c(1,3),
  yrelation = 'free',
  description = 'Scatter plot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Covariates
cov.colours <- as.character(microarray$Chr[1:800]);
cov.colours[cov.colours == '1'] <- default.colours(3, palette.type = 'chromosomes')[1];
cov.colours[cov.colours == '2'] <- default.colours(3, palette.type = 'chromosomes')[2];
cov.colours[cov.colours == '3'] <- default.colours(3, palette.type = 'chromosomes')[3];

cov <- list(
  rect = list(
    col = 'transparent',
```

```

        fill = cov.colours
    )
);

cov.grob <- covariates.grob(
    covariates = cov,
    ord = c(1:length(cov.colours)),
    side = 'top',
    size = 1
);

cov.legend <- list(
    legend = list(
        colours = default.colours(3, palette.type = 'chromosomes'),
        labels = c('1', '2', '3'),
        title = 'Chromosome',
        border = 'transparent'
    )
);
);

cov.legend.grob <- legend.grob(
    legends = cov.legend
);

create.scatterplot(
    filename = tempfile(pattern = 'Scatterplot_Covariates', fileext = '.tiff'),
    formula = sample.two ~ sample.one,
    data = scatter.data,
    main = 'Covariates',
    xlab.label = colnames(microarray[1]),
    ylab.label = colnames(microarray[2]),
    xat = seq(0, 16, 2),
    yat = seq(0, 16, 2),
    xlims = c(0, 15),
    ylims = c(0, 15),
    xaxis.cex = 1,
    yaxis.cex = 1,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    pch = 21,
    col = 'black',
    fill = 'transparent',
    # Adding covariate & legend
    legend = list(
        bottom = list(fun = cov.grob),
        right = list(fun = cov.legend.grob)
    ),
    # Ensuring sufficient spacing for covariate
    key.top = 3,
    description = 'Scatter plot created by BoutrosLab.plotting.general',
    resolution = 200
)

```

```
);

# Error bars
error.data <- data.frame(
  chr = (microarray$Start)[1:20],
  values = apply(microarray[1:20,1:58], 1, mean),
  error = apply(microarray[1:20,1:58], 1, sd)
);

create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Error_Bars', fileext = '.tiff'),
  formula = values ~ chr,
  data = error.data,
  main = 'Error Bars',
  xlab.label = 'Base pair location on chromosome one',
  ylab.label = 'Gene expression change',
  # xat = seq(0, 16, 2),
  yat = seq(0, 14, 2),
  # xlims = c(0, 15),
  ylims = c(0, 13),
  # Format xaxes
  xaxis.lab = c(
    scientific.notation(0, 1),
    scientific.notation(1000000, 1),
    scientific.notation(2000000, 1),
    scientific.notation(3000000, 1),
    scientific.notation(4000000, 1),
    scientific.notation(5000000, 1),
    scientific.notation(6000000, 1),
    scientific.notation(7000000, 1)
  ),
  xaxis.rot = 90,
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  pch = 19,
  col = 'black',
  fill = 'transparent',
  # Specifying error bars
  error.bar.lwd = 1,
  error.whisker.angle = 120,
  y.error.up = error.data$error,
  y.error.bar.col = 'black',
  description = 'Scatter plot created by BoutrosLab.plotting.general',
  resolution = 200
);

create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Error_Bars_MultiColor', fileext = '.tiff'),
  formula = values ~ chr,
```

```

data = error.data,
main = 'Error Bars',
xlab.label = 'Base pair location on chromosome one',
ylab.label = 'Gene expression change',
# xat = seq(0, 16, 2),
yat = seq(0, 14, 2),
# xlims = c(0, 15),
ylimits = c(0, 13),
# Format xaxes
xaxis.lab = c(
  scientific.notation(0, 1),
  scientific.notation(1000000, 1),
  scientific.notation(2000000, 1),
  scientific.notation(3000000, 1),
  scientific.notation(4000000, 1),
  scientific.notation(5000000, 1),
  scientific.notation(6000000, 1),
  scientific.notation(7000000, 1)
),
xaxis.rot = 90,
xaxis.cex = 1,
yaxis.cex = 1,
xaxis.fontface = 1,
yaxis.fontface = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
pch = 19,
col = 'black',
fill = 'transparent',
# Specifying error bars
error.bar.lwd = 1,
error.whisker.angle = 120,
y.error.up = error.data$error,
y.error.bar.col = c('black','red','blue'),
description = 'Scatter plot created by BoutrosLab.plotting.general',
group.specific.colouring = FALSE,
resolution = 200
);

# Gridlines
create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Gridlines', fileext = '.tiff'),
  formula = sample.two ~ sample.one,
  data = scatter.data,
  main = 'Gridlines',
  xlab.label = colnames(microarray[1]),
  ylab.label = colnames(microarray[2]),
  xat = seq(0, 16, 2),
  yat = seq(0, 16, 2),
  xlims = c(0, 15),
  ylims = c(0, 15),
  xaxis.cex = 1,

```

```
yaxis.cex = 1,
xaxis.fontface = 1,
yaxis.fontface = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
pch = 21,
col = 'black',
fill = 'transparent',
# Adding gridlines
type = c('p','g'),
description = 'Scatter plot created by BoutrosLab.plotting.general',
resolution = 200
);

# lines & background rectangle
create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Lines_BG', fileext = '.tiff'),
  formula = sample.two ~ sample.one,
  data = scatter.data,
  main = 'Lines & BG rectangle',
  xlab.label = colnames(microarray[1]),
  ylab.label = colnames(microarray[2]),
  xat = seq(0, 16, 2),
  yat = seq(0, 16, 2),
  xlims = c(0, 15),
  ylims = c(0, 15),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  pch = 21,
  col = 'black',
  fill = 'transparent',
  type = c('p','g'),
  # add xy line
  add.xyline = TRUE,
  xyline.lty = 3,
  xyline.col = 'red',
  xyline.lwd = 3,
  # add background rectangle
  add.rectangle = TRUE,
  xleft.rectangle = which(scatter.data$chr == 2)[1]/800*15,
  xright.rectangle = which(scatter.data$chr == 3)[1]/800*15,
  ybottom.rectangle = 0,
  ytop.rectangle = 15,
  col.rectangle = 'grey',
  alpha.rectangle = 0.5,
  description = 'Scatter plot created by BoutrosLab.plotting.general',
  resolution = 200
);
```

```

# attach lines to points
create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Lines', fileext = '.tiff'),
  formula = sample.two ~ sample.one | chr,
  data = scatter.data,
  main = 'Lines',
  xlab.label = colnames(microarray[1]),
  ylab.label = colnames(microarray[2]),
  xat = seq(0, 16, 2),
  yat = seq(0, 16, 2),
  xlims = c(0, 15),
  ylims = c(0, 15),
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  pch = 21,
  col = 'black',
  fill = 'transparent',
  # attach lines
  type = c('h','p'),
  layout = c(1,3),
  description = 'Scatter plot created by BoutrosLab.plotting.general',
  resolution = 200
);

# ROC curve
set.seed(123456);

class.values <- runif(50, 0, 1);
observed.values <- sample(c(0,1), size = 50, replace = TRUE);
cutoffs <- seq(1,0,-0.01);
tprs <- c();
fprs <- c();

for (c in cutoffs) {
  roc.classification <- rep(0, length(class.values));
  roc.classification[class.values >= c] <- 1;
  roc.results <- table(
    factor(roc.classification, levels = c(0,1)),
    factor(observed.values, levels = c(0,1)),
    dnn = c('pred', 'obs')
  );
  tprs <- c(tprs, roc.results[2,2] / (roc.results[2,2] + roc.results[1,2]));
  fprs <- c(fprs, roc.results[2,1] / (roc.results[2,1] + roc.results[1,1]));
}

roc.data <- data.frame(cutoff = cutoffs, TPR = tprs, FPR = fprs);
points.x <- roc.data[match(c(0.25, 0.5, 0.75), roc.data$cutoff), 'FPR'];
points.y <- roc.data[match(c(0.25, 0.5, 0.75), roc.data$cutoff), 'TPR'];

```

```

create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_ROC', fileext = '.tiff'),
  formula = TPR ~ FPR,
  data = roc.data,
  main = 'ROC',
  xlab.label = 'False positive rate',
  ylab.label = 'True positive rate',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  type = 's',
  lwd = 3,
  add.xyline = TRUE,
  xyline.col = 'grey',
  add.points = TRUE,
  points.x = points.x,
  points.y = points.y,
  points.col = c('blue', 'darkgreen', 'red'),
  add.text = TRUE,
  text.labels = paste('cutoff = ', c(0.25, 0.5, 0.75), sep = ''),
  #text.x = points.x - 0.14,
  #text.y = points.y + 0.03,
  text.x = points.x,
  text.y = points.y,
  text.guess.labels = TRUE,
  text.guess.label.position = 155,
  text.guess.radius.factor = 2.5,
  description = 'Scatter plot created by BoutrosLab.plotting.general',
  resolution = 200
);

# Volcano Plots
fold.change <- apply(microarray[,1:29], 1, mean) - apply(microarray[,30:58], 1, mean);

fake.microarray <- microarray[,1:58] - log(mean(apply(microarray[,1:58],1, mean)));
fake.microarray[,30:58] <- fake.microarray[,30:58] + mean(fold.change);
fake.microarray[fake.microarray < 0] <- 0;

p.values <- apply(fake.microarray[,1:58], 1, function(x) {t.test(x=x[1:29],y=x[30:58])$p.value} );
fold.change <- apply(fake.microarray[, 1:29], 1, mean) - apply(fake.microarray[, 30:58], 1,mean);
p.values.adjusted <- p.adjust(p.values, 'fdr');

dot.colours <- vector(length=length(p.values));
dot.colours[p.values.adjusted < .05 & fold.change < 0] <- 'green';
dot.colours[p.values.adjusted < .05 & fold.change > 0] <- 'red';
dot.colours[p.values.adjusted > .05] <- 'black';

volcano.data <- data.frame(
  p.values = -log10(p.values.adjusted),

```

```

fold.change = fold.change
);

create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Volcano_Plot', fileext = '.tiff'),
  formula = p.values ~ fold.change,
  data = volcano.data,
  col = dot.colours,
  alpha = .5,
  yat = c(0,2,4,6,8),
  ylims = c(-0.1,8.1),
  yaxis.lab = expression(10^0,10^-2,10^-4,10^-6,10^-8),
  yaxis.cex = 1.5,
  xaxis.cex = 1.5,
  xlab.label = 'foldChange',
  ylab.label = 'pValues',
  xlab.cex = 1.75,
  ylab.cex = 1.75,
  resolution = 200
);

# Automatic Labeling
interesting.fold.change <- (fold.change < -.9 | fold.change > .9);
interesting.p.value <- (-log10(p.values.adjusted) < 8 & -log10(p.values.adjusted) > 2);
interesting.points <- interesting.fold.change & interesting.p.value;

text.x <- fold.change[interesting.points];
text.y <- (-log10(p.values.adjusted))[interesting.points];
text.labels <- rownames(microarray)[interesting.points];

create.scatterplot(
  filename = tempfile(pattern = 'Scatterplot_Volcano_Plot_With_Labels', fileext = '.tiff'),
  formula = p.values ~ fold.change,
  data = volcano.data,
  alpha = .5,
  yat = c(0,2,4,6,8),
  ylims = c(-0.1,8.1),
  xlims = c(-1.5,1.5),
  yaxis.lab = expression(10^0,10^-2,10^-4,10^-6,10^-8),
  yaxis.cex = 1.5,
  xaxis.cex = 1.5,
  xlab.label = 'foldChange',
  ylab.label = 'pValues',
  xlab.cex = 1.75,
  ylab.cex = 1.75,
  add.text = TRUE,
  text.x = text.x,
  text.y = text.y,
  text.labels = text.labels,
  text.guess.labels = TRUE,
  resolution = 200
);

```

```
# With line segments
line.data <- data.frame(
  group = c('A', 'B', 'C'),
  x = sample(1:10,3),
  y = sample(1:10,3),
  z = sample(1:10,3)
);

create.scatterplot(
  (x+y+z) ~ group,
  line.data,
  filename = tempfile(pattern = 'Scatterplot_with_LineSegments', fileext = '.tiff'),
  cex = 0,
  add.line.segments = TRUE,
  line.start = list(
    rep(0,nrow(line.data)),
    line.data$x,
    c(line.data$x + line.data$y)
  ),
  line.end = list(
    line.data$x,
    c(line.data$x + line.data$y),
    c(line.data$x + line.data$y + line.data$z)
  ),
  line.col = list('red','blue','green'),
  line.lwd = list(3,3,3),
  resolution = 200
);

lollipop.data <- data.frame(
  y = seq(1,100,1),
  x = rnorm(100)
);

create.lollipopplot(
  filename = tempfile(pattern = 'Lollipop_Simple', fileext = '.tiff'),
  formula = x ~ y,
  data = lollipop.data,
  main = 'Lollipop plot',
  xaxis.cex = 1,
  xlims = c(-1,102),
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  pch = 21,
  col = 'black',
  fill = 'transparent',
  description = 'Scatter plot created by BoutrosLab.plotting.general',
  regions.start = c(1,26,48),
  regions.stop = c(15,35,72),
  regions.labels = c("test 1", "test2", "test 3"),
```

```
regions.color = c("#66b3ff", "#5cd65c", "#ff3333"),
resolution = 200
);
```

create.segplot *Make a segplot*

Description

Takes a data.frame and creates a segplot

Usage

```
create.segplot(
formula,
data,
filename = NULL,
main = NULL,
main.just = 'center',
main.x = 0.5,
main.y = 0.5,
main.cex = 3,
xlab.label = tail(sub('`', '', formula[-2]), 1),
ylab.label = tail(sub('`', '', formula[-3]), 1),
xlab.cex = 2,
ylab.cex = 2,
xlab.col = 'black',
ylab.col = 'black',
xlab.top.label = NULL,
xlab.top.cex = 2,
xlab.top.col = 'black',
xlab.top.just = 'center',
xlab.top.x = 0.5,
xlab.top.y = 0,
xaxis.lab = TRUE,
yaxis.lab = TRUE,
xaxis.cex = 1.5,
yaxis.cex = 1.5,
xaxis.col = 'black',
yaxis.col = 'black',
xaxis.fontface = 'bold',
yaxis.fontface = 'bold',
xaxis.rot = 0,
yaxis.rot = 0,
xaxis.tck = 1,
yaxis.tck = 1,
```

```
  xlims = NULL,
  ylims = NULL,
  xat = TRUE,
  yat = TRUE,
  abline.h = NULL,
  abline.v = NULL,
  abline.lty = 1,
  abline.lwd = 1,
  abline.col = 'black',
  segments.col = 'black',
  segments.lwd = 1,
  layout = NULL,
  as.table = FALSE,
  x.spacing = 0,
  y.spacing = 0,
  x.relation = 'same',
  y.relation = 'same',
  top.padding = 0.5,
  bottom.padding = 2,
  right.padding = 1,
  left.padding = 2,
  ylab.axis.padding = 0,
  level = NULL,
  col.regions = NULL,
  centers = NULL,
  plot.horizontal = TRUE,
  draw.bands = FALSE,
  pch = 16,
  symbol.col = 'black',
  symbol.cex = 1,
  add.rectangle = FALSE,
  xleft.rectangle = NULL,
  ybottom.rectangle = NULL,
  xright.rectangle = NULL,
  ytop.rectangle = NULL,
  col.rectangle = 'transparent',
  alpha.rectangle = 1,
  axes.lwd = 1,
  key = NULL,
  legend = NULL,
  height = 6,
  width = 6,
  size.units = 'in',
  resolution = 1600,
  enable.warnings = FALSE,
  description = 'Created with BoutrosLab.plotting.general',
  style = 'BoutrosLab',
  preload.default = 'custom',
```

```

use.legacy.settings = FALSE,
inside.legend.auto = FALSE,
disable.factor.sorting = FALSE
)

```

Arguments

formula	The formula used to extract the x & y components from the data-frame
data	The data-frame to plot
filename	Filename for tiff output, or if NULL returns the trellis object itself
main	The main title for the plot (space is reclaimed if NULL)
main.just	The justification of the main title for the plot, default is centered
main.x	The x location of the main title, default is 0.5
main.y	The y location of the main title, default is 0.5
main.cex	Size of text for main plot title, defaults to 3
xlab.label	x-axis label
ylab.label	y-axis label
xlab.cex	Size of x-axis label, defaults to 2
ylab.cex	Size of y-axis label, defaults to 2
xlab.col	Colour of the x-axis label, defaults to “black”
ylab.col	Colour of the y-axis label, defaults to “black”
xlab.top.label	The label for the top x-axis
xlab.top.cex	Size of top x-axis label
xlab.top.col	Colour of the top x-axis label
xlab.top.just	Justification of the top x-axis label, defaults to centered
xlab.top.x	The x location of the top x-axis label
xlab.top.y	The y location of the top y-axis label
xaxis.lab	Vector listing x-axis tick labels, defaults to automatic
yaxis.lab	Vector listing y-axis tick labels, defaults to automatic
xaxis.cex	Size of x-axis scales, defaults to 1.5
yaxis.cex	Size of y-axis scales, defaults to 1.5
xaxis.col	Colour of the x-axis tick labels, defaults to “black”
yaxis.col	Colour of the y-axis tick labels, defaults to “black”
xaxis.fontface	Fontface for the x-axis scales, defaults to “plain”
yaxis.fontface	Fontface for the y-axis scales, defaults to “plain”
xaxis.rot	Counterclockwise rotation of text in x-axis scales in degrees, defaults to 0
yaxis.rot	Counterclockwise rotation of text in y-axis scales in degrees, defaults to 0
xaxis.tck	Specifies the length of the tick mark, defaults to 1 for both top and bottom axes
yaxis.tck	Specifies the length of the tick mark, defaults to 1 for both top and bottom axes

xlimits	Two-element vector giving the x-axis limits, defaults to automatic
ylimits	Two-element vector giving the y-axis limits, defaults to automatic
xat	Vector listing where the x-axis labels should be drawn, defaults to automatic
yat	Vector listing where the y-axis labels should be drawn, defaults to automatic
abline.h	Allow horizontal line to be drawn, default to NULL
abline.v	Allow vertical line to be drawn, default to NULL
abline.lty	Specifies horizontal line style, defaults to 1 (solid)
abline.lwd	Specifies horizontal line width, defaults to 1
abline.col	Horizontal line colour, defaults to black
segments.col	Colour of segments, defaults to “black”
segments.lwd	Line width of segments, defaults to 1
layout	A vector specifying the number of columns, rows (e.g., c(2,1). Default is NULL; see lattice::xyplot for more details
as.table	Specifies panel drawing order, default is FALSE which draws panels from bottom left corner, moving right then up. Set to TRUE to draw from top left corner, moving right then down
x.spacing	A number specifying the distance between panels along the x-axis, defaults to 0
y.spacing	A number specifying the distance between panels along the y-axis, defaults to 0
x.relation	Allows x-axis scales to vary if set to “free”, defaults to “same”
y.relation	Allows y-axis scales to vary if set to “free”, defaults to “same”
top.padding	A number specifying the distance to the top margin, defaults to 0.1
bottom.padding	A number specifying the distance to the bottom margin, defaults to 0.7
right.padding	A number specifying the distance to the right margin, defaults to 0.1
left.padding	A number specifying the distance to the left margin, defaults to 0.5
ylab.axis.padding	A number specifying the distance of ylabel to the y-axis, defaults to 1,
level	Optional covariate that determines colour coding of the segments, if specified overwrites segments.col, can contain actual colors or values to determine colors, then col.regions should be defined
col.regions	Vector of colors, define if level is numeric
centers	Optional vector for centers of segments, defaults to NULL
plot.horizontal	Logical whether segments should be drawn horizontally (default) or vertically
draw.bands	Logical to specify whether to draw lines (default) or rectangles
pch	Plotting character for centers
symbol.col	Colour of plotting character for centers, defaults to “black”
symbol.cex	Size of plotting character for centers, defaults to 1
add.rectangle	Allow a rectangle to be drawn, default is FALSE
xleft.rectangle	Specifies the left x coordinate of the rectangle to be drawn

```

ybottom.rectangle
    Specifies the bottom y coordinate of the rectangle to be drawn
xright.rectangle
    Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle Specifies the top y coordinate of the rectangle to be drawn
col.rectangle Specifies the colour to fill the rectangle's area
alpha.rectangle
    Specifies the colour bias of the rectangle to be drawn
axes.lwd      Specifies axes line width, defaults to 1
key           A list giving the key (legend). The default suppresses drawing
legend        Add a legend to the plot. Helpful for adding multiple keys and adding keys to
              the margins of the plot. See xyplot.
height         Figure height, defaults to 6 inches
width          Figure width, defaults to 6 inches
size.units     Figure units, defaults to inches
resolution     Figure resolution in dpi, defaults to 1600
enable.warnings
    Print warnings if set to TRUE, defaults to FALSE
description   Short description of image/plot; default NULL
style          defaults to "BoutrosLab", also accepts "Nature", which changes parameters ac-
              cording to Nature formatting requirements
preload.default
    ability to set multiple sets of diffrent defaults depending on publication needs
use.legacy.settings
    boolean to set wheter or not to use legacy mode settings (font)
inside.legend.auto
    boolean specifying whether or not to use the automatic inside legend function
disable.factor.sorting
    Disable barplot auto sorting factors alphabetically/numerically

```

Value

If filename is NULL then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of create histogram is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```

Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics

```

Author(s)

Paul C. Boutros

See Also

[levelplot](#), [segplot](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(12345);

simple.data <- data.frame(
  min = runif(10,5,15),
  max = runif(10,15,25),
  labels = as.factor(LETTERS[1:10])
);

create.segplot(
  filename = tempfile(pattern = 'Segplot_simple', fileext = '.tiff'),
  formula = labels ~ min + max,
  data = simple.data,
  resolution = 50
);

# load some data
length.of.gene <- apply(microarray[1:10,60:61], 1, diff);
bin.length <- length.of.gene;
bin.length[which(bin.length < 20000)] <- 'A';
bin.length[which(bin.length < 40000)] <- 'B';
bin.length[which(bin.length < 60000)] <- 'C';

segplot.data <- data.frame(
  min = apply(microarray[1:10,1:58], 1, min),
  max = apply(microarray[1:10,1:58], 1, max),
  median = apply(microarray[1:10,1:58], 1, median),
  gene = rownames(microarray)[1:10],
  # approximating length of gene
  length = as.factor(bin.length)
);

# Minimal Input using real data
create.segplot(
  filename = tempfile(pattern = 'Segplot_Minimal_Input', fileext = '.tiff'),
  formula = gene ~ min + max,
  data = segplot.data,
  main = 'Minimal input',
  description = 'Segplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Axes & Labels
create.segplot(
```

```
filename = tempfile(pattern = 'Segplot_Axes_Labels', fileext = '.tiff'),
formula = gene ~ min + max,
data = segplot.data,
main = 'Axes & labels',
# Formatting axes
xlab.label = 'Change in gene expression',
ylab.label = 'Gene',
xaxis.cex = 1,
yaxis.cex = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
xlims = c(0,13),
xat = seq(0, 12, 2),
description = 'Segplot created by BoutrosLab.plotting.general',
resolution = 100
);

# Bands
create.segplot(
  filename = tempfile(pattern = 'Segplot_Bands', fileext = '.tiff'),
  formula = gene ~ min + max,
  data = segplot.data,
  main = 'Bands',
  xlab.label = 'Change in gene expression',
  ylab.label = 'Gene',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xlims = c(0,13),
  xat = seq(0, 12, 2),
  # drawing rectangles instead of lines
  draw.bands = TRUE,
  description = 'Segplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Colours
create.segplot(
  filename = tempfile(pattern = 'Segplot_Colours', fileext = '.tiff'),
  formula = reorder(gene, median) ~ min + max,
  data = segplot.data,
  main = 'Colours',
  xlab.label = 'Change in gene expression',
  ylab.label = 'Gene',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xlims = c(0,13),
  xat = seq(0, 12, 2),
  draw.bands = FALSE,
```

```
# Changing the colours based on a covariate ('level' parameter)
level = segplot.data$length,
col.regions = default.colours(3),
description = 'Segplot created by BoutrosLab.plotting.general',
resolution = 100
);

# Median
create.segplot(
  filename = tempfile(pattern = 'Segplot_Median', fileext = '.tiff'),
  formula = gene ~ min + max,
  data = segplot.data,
  main = 'Medians',
  xlab.label = 'Change in gene expression',
  ylab.label = 'Gene',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xlims = c(0,13),
  draw.bands = FALSE,
  xat = seq(0, 12, 2),
  level = segplot.data$length,
  col.regions = default.colours(3),
  # Adding center values
  centers = segplot.data$median,
  description = 'Segplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Reorder by center value
create.segplot(
  filename = tempfile(pattern = 'Segplot_Reorder', fileext = '.tiff'),
  formula = reorder(gene, median) ~ min + max,
  data = segplot.data,
  main = 'Reordered',
  xlab.label = 'Change in gene expression',
  ylab.label = 'Gene',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xlims = c(0,13),
  xat = seq(0, 12, 2),
  draw.bands = FALSE,
  centers = segplot.data$median,
  level = segplot.data$length,
  col.regions = default.colours(3),
  description = 'Segplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Legend
```

```

create.segplot(
    filename = tempfile(pattern = 'Segplot_Legend', fileext = '.tiff'),
    formula = reorder(gene, median) ~ min + max,
    data = segplot.data,
    main = 'Legend',
    xlab.label = 'Change in gene expression',
    ylab.label = 'Gene',
    xaxis.cex = 1,
    yaxis.cex = 1,
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    xlims = c(0,13),
    xat = seq(0, 12, 2),
    draw.bands = FALSE,
    centers = segplot.data$median,
    level = segplot.data$length,
    col.regions = default.colours(3),
    # Adding legend to explain colours
    legend = list(
        inside = list(
            fun = draw.key,
            args = list(
                key = list(
                    points = list(
                        col = default.colours(3),
                        pch = 19,
                        cex = 1
                    ),
                    text = list(
                        lab = c('1-20000 bp', '20001-40000 bp', '40001-60000 bp')
                    ),
                    padding.text = 1,
                    cex = 1
                )
            ),
            x = 0.60,
            y = 0.15,
            corner = c(0,1)
        )
    ),
    description = 'Segplot created by BoutrosLab.plotting.general',
    resolution = 100
);

# Background
create.segplot(
    filename = tempfile(pattern = 'Segplot_Background', fileext = '.tiff'),
    formula = reorder(gene, median) ~ min + max,
    data = segplot.data,
    main = 'Background rectangle',
    xlab.label = 'Change in gene expression',
    ylab.label = 'Gene',
    xaxis.cex = 1,

```

```
yaxis.cex = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
xlims = c(0,13),
xat = seq(0, 12, 2),
draw.bands = FALSE,
centers = segplot.data$median,
level = segplot.data$length,
col.regions = default.colours(3),
# Adding legend to explain colours
legend = list(
  inside = list(
    fun = draw.key,
    args = list(
      key = list(
        points = list(
          col = default.colours(3),
          pch = 19,
          cex = 1
        ),
        text = list(
          lab = c('1-20000 bp', '20001-40000 bp', '40001-60000 bp')
        ),
        padding.text = 1,
        cex = 1
      )
    ),
    x = 0.50,
    y = 0.15,
    corner = c(0,1)
  )
),
# adding background shading
add.rectangle = TRUE,
xleft.rectangle = 0,
ybottom.rectangle = seq(0.5, 8.5, 2),
xright.rectangle = 13,
ytop.rectangle = seq(1.5, 9.5, 2),
col.rectangle = 'grey',
alpha.rectangle = 0.5,
description = 'Segplot created by BoutrosLab.plotting.general',
resolution = 100
);

# Nature style
create.segplot(
  filename = tempfile(pattern = 'Segplot_Nature_style', fileext = '.tiff'),
  formula = reorder(gene, median) ~ min + max,
  data = segplot.data,
  main = 'Nature style',
  xaxis.cex = 1,
  yaxis.cex = 1,
  xlab.cex = 1.5,
```

```

ylab.cex = 1.5,
xlims = c(0,13),
xat = seq(0, 12, 2),
draw.bands = FALSE,
centers = segplot.data$median,
level = segplot.data$length,
col.regions = default.colours(3),
legend = list(
  inside = list(
    fun = draw.key,
    args = list(
      key = list(
        points = list(
          col = default.colours(3),
          pch = 19,
          cex = 1
        ),
        text = list(
          lab = c('1-20000 bp', '20001-40000 bp', '40001-60000 bp')
        ),
        padding.text = 1,
        cex = 1
      )
    ),
    x = 0.50,
    y = 0.15,
    corner = c(0,1)
  )
),
add.rectangle = TRUE,
xleft.rectangle = 0,
ybottom.rectangle = seq(0.5, 8.5, 2),
xright.rectangle = 13,
ytop.rectangle = seq(1.5, 9.5, 2),
col.rectangle = 'grey',
alpha.rectangle = 0.5,

# set style to Nature
style = 'Nature',

# demonstrating how to italicize character variables
ylab.label = expression(paste('italicized ', italic('a'))),

# demonstrating how to create en-dashes
xlab.label = expression(paste('en dashes: 1', '\u2013', '10' '^' '\u2013', ''^3)),

description = 'Segplot created by BoutrosLab.plotting.general',
resolution = 100
);

# example of bands and lines
create.segplot(
  filename = tempfile(pattern = 'Segplot_BandsAndLines', fileext = '.tiff'),

```

```
formula = labels ~ min + max,  
data = simple.data,  
draw.bands = c(1,3,5,7,9),  
resolution = 200  
);
```

create.stripplot *Make a strip-plot*

Description

Takes a formula and a data.frame and creates a strip-plot

Usage

```
create.stripplot(  
  formula,  
  data,  
  filename = NULL,  
  groups = NULL,  
  jitter.data = FALSE,  
  jitter.factor = 1,  
  jitter.amount = NULL,  
  main = NULL,  
  main.just = 'center',  
  main.x = 0.5,  
  main.y = 0.5,  
  main.cex = 3,  
  xlab.label = tail(sub('`', '', formula[-2]), 1),  
  ylab.label = tail(sub('`', '', formula[-3]), 1),  
  xlab.cex = 2,  
  ylab.cex = 2,  
  xlab.col = 'black',  
  ylab.col = 'black',  
  xlab.top.label = NULL,  
  xlab.top.cex = 2,  
  xlab.top.col = 'black',  
  xlab.top.just = 'center',  
  xlab.top.x = 0.5,  
  xlab.top.y = 0,  
  xaxis.lab = TRUE,  
  yaxis.lab = TRUE,  
  xaxis.cex = 1.5,  
  yaxis.cex = 1.5,  
  xaxis.col = 'black',  
  yaxis.col = 'black',
```

```
xaxis.fontface = 'bold',
yaxis.fontface = 'bold',
xaxis.rot = 0,
yaxis.rot = 0,
xaxis.tck = 0,
yaxis.tck = 1,
xlims = NULL,
ylims = NULL,
xat = TRUE,
yat = TRUE,
lwd = 1,
pch = 19,
col = 'black',
col.border = 'black',
fill = 'transparent',
colour.alpha = 1,
cex = 0.75,
top.padding = 0.1,
bottom.padding = 0.7,
right.padding = 0.3,
left.padding = 0.5,
ylab.axis.padding = 1,
layout = NULL,
as.table = TRUE,
x.spacing = 0,
y.spacing = 0,
add.median = FALSE,
median.values = NULL,
add.rectangle = FALSE,
xleft.rectangle = NULL,
ybottom.rectangle = NULL,
xright.rectangle = NULL,
ytop.rectangle = NULL,
col.rectangle = 'transparent',
alpha.rectangle = 1,
strip.col = 'white',
strip.cex = 1,
strip.fontface = 'bold',
key = NULL,
legend = NULL,
height = 6,
width = 6,
size.units = 'in',
resolution = 1600,
enable.warnings = FALSE,
description = 'Created with BoutrosLab.plotting.general',
style = 'BoutrosLab',
preload.default = 'custom',
```

```

use.legacy.settings = FALSE,
      inside.legend.auto = FALSE,
disable.factor.sorting = FALSE
)

```

Arguments

formula	The formula used to extract the x & y components from the data-frame
data	The data-frame to plot
filename	Filename for tiff output, or if NULL returns the trellis object itself
groups	The grouping variable in the data-frame
jitter.data	Allow data to be staggered, default is FALSE
jitter.factor	Numeric value to apply to jitter, default is 1
jitter.amount	Numeric; amount of noise to add, default is NULL
main	The main title for the plot (space is reclaimed if NULL)
main.just	The justification of the main title for the plot, default is centered
main.x	The x location of the main title, default is 0.5
main.y	The y location of the main title, default is 0.5
main.cex	Size of text for main plot title
xlab.label	X-axis label
ylab.label	Y-axis label
xlab.cex	Size of x-axis label, defaults to 3
ylab.cex	Size of y-axis label, defaults to 3
xlab.col	Colour of the x-axis label, defaults to "black"
ylab.col	Colour of the y-axis label, defaults to "black"
xlab.top.label	The label for the top x-axis
xlab.top.cex	Size of top x-axis label
xlab.top.col	Colour of the top x-axis label
xlab.top.just	Justification of the top x-axis label, defaults to centered
xlab.top.x	The x location of the top x-axis label
xlab.top.y	The y location of the top y-axis label
xaxis.lab	Vector listing x-axis tick labels, defaults to automatic
yaxis.lab	Vector listing y-axis tick labels, defaults to automatic
xaxis.cex	Size of x-axis scales, defaults to 2
yaxis.cex	Size of y-axis scales, defaults to 2
xaxis.col	Colour of the x-axis tick labels, defaults to "black"
yaxis.col	Colour of the y-axis tick labels, defaults to "black"
xaxis.fontface	Fontface for the x-axis scales
yaxis.fontface	Fontface for the y-axis scales

xaxis.rot	Rotation of y-axis tick labels; defaults to 0
yaxis.rot	Rotation of y-axis tick labels; defaults to 0
xaxis.tck	Specifies the length of the tick marks for x-axis, defaults to 0
yaxis.tck	Specifies the length of the tick marks for y-axis, defaults to 1
xlimits	Two-element vector giving the x-axis limits, default is automatic
ylimits	Two-element vector giving the y-axis limits, default is automatic
xat	Vector listing where the x-axis labels should be drawn, default is automatic
yat	Vector listing where the y-axis labels should be drawn, default is automatic
lwd	Line width, defaults to 1
pch	The plotting character (defaults to filled circles)
col	Colour of the plotting character (defaults to black)
col.border	Colour of border when pch > 21. Defaults to black
fill	Fill colour of the plotting character if pch set to 21:25 (defaults to transparent)
colour.alpha	Bias to be added to colour selection (defaults to 1)
cex	The size of the plotting character
top.padding	A number specifying the distance to the top margin, defaults to 0.1
bottom.padding	A number specifying the distance to the bottom margin, defaults to 0.7
right.padding	A number specifying the distance to the right margin, defaults to 0.3
left.padding	A number specifying the distance to the left margin, defaults to 0.5
ylab.axis.padding	A number specifying the distance of ylabel to the y-axis, defaults to 1
layout	A vector specifying the number of columns, rows (e.g., c(2,1). Default is NULL; see lattice::xyplot for more details.
as.table	Specifies panel drawing order, default is TRUE to draw from top left corner, moving right then down. Set to FALSE to draw panels from bottom left corner, moving right then up
x.spacing	A number specifying the distance between panels along the x-axis, defaults to 0
y.spacing	A number specifying the distance between panels along the y-axis, defaults to 0
add.median	TRUE/FALSE indicating whether lines should be drawn at the group medians, default is FALSE
median.values	A vector of values representing the median of each group, default is NULL
add.rectangle	Allow a rectangle to be drawn, default is FALSE
xleft.rectangle	Specifies the left x coordinate of the rectangle to be drawn
ybottom.rectangle	Specifies the bottom y coordinate of the rectangle to be drawn
xright.rectangle	Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle	Specifies the top y coordinate of the rectangle to be drawn

col.rectangle Specifies the colour to fill the rectangle's area
 alpha.rectangle Specifies the colour bias of the rectangle to be drawn
 strip.col Strip background colour, defaults to "white"
 strip.cex Strip title character expansion
 strip.fontface Strip text fontface, defaults to bold
 key A list giving the key (legend). The default suppresses drawing
 legend Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See xyplot.
 height Figure height, defaults to 6 inches
 width Figure width, defaults to 6 inches
 size.units Figure units, defaults to inches
 resolution Figure resolution in dpi, defaults to 1600
 enable.warnings Print warnings if set to TRUE, defaults to FALSE
 description Short description of image/plot; default NULL
 style defaults to "BoutrosLab", also accepts "Nature", which changes parameters according to Nature formatting requirements
 preload.default ability to set multiple sets of different defaults depending on publication needs
 use.legacy.settings boolean to set whether or not to use legacy mode settings (font)
 inside.legend.auto boolean specifying whether or not to use the automatic inside legend function
 disable.factor.sorting Disable barplot auto sorting factors alphabetically/numerically

Value

If filename is NULL then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of create histogram is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```
Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics
```

Author(s)

Paul C. Boutros

See Also

[stripplot](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(12345);

simple.data <- data.frame(
  x = c(rep(rnorm(50),5)),
  y = as.factor(sample(LETTERS[1:5],250,TRUE)))
);

create.stripplot(
  filename = tempfile(pattern = 'Stripplot_simple', fileext = '.tiff'),
  formula = x ~ y,
  data = simple.data,
  resolution = 50
);

# load real datasets
stripplot.data <- data.frame(
  values = c(t(microarray[1:10, 1:58])),
  genes = rep(rownames(microarray)[1:10], each = 58),
  sex = patient$sex,
  stringsAsFactors = TRUE
);

# Minimal Input using real data
create.stripplot(
  filename = tempfile(pattern = 'Stripplot_Minimal_Input', fileext = '.tiff'),
  formula = genes ~ values,
  data = stripplot.data,
  main = 'Minimal input',
  description = 'Stripplot created by BoutrosLab.plotting.general',
  resolution = 50
);

# Axes & Labels
create.stripplot(
  filename = tempfile(pattern = 'Stripplot_Axes_Labels', fileext = '.tiff'),
  formula = genes ~ values,
  data = stripplot.data,
  main = 'Axes & labels',
  # formatting axes
  xlab.label = 'Change in gene expression',
  ylab.label = 'Gene',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
```

```
    xaxis.cex = 1,
    yaxis.cex = 1,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    xlims = c(0,13),
    xat = seq(0,12,2),
    description = 'Stripplot created by BoutrosLab.plotting.general',
    resolution = 100
);

# Colour & Legend
create.stripplot(
  filename = tempfile(pattern = 'Stripplot_Colour_Legend', fileext = '.tiff'),
  formula = genes ~ values,
  data = stripplot.data,
  main = 'Colour & legend',
  xlab.label = 'Change in gene expression',
  ylab.label = 'Gene',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlims = c(0,13),
  xat = seq(0,12,2),
  # Colour & points adjustment
  groups = stripplot.data$sex,
  col = c('pink', 'skyblue'),
  pch = 19,
  colour.alpha = 0.5,
  cex = 1,
  # Legend
  key = list(
    space = 'right',
    text = list(
      lab = levels(stripplot.data$sex),
      cex = 1,
      col = 'black'
    ),
    points = list(
      pch = 19,
      col = c('pink','skyblue'),
      alpha = 0.5,
      cex = 1
    ),
    padding.text = 3
  ),
  description = 'Stripplot created by BoutrosLab.plotting.general',
  resolution = 100
);
```

```
# Jitter
create.stripplot(
    filename = tempfile(pattern = 'Stripplot_Jitter', fileext = '.tiff'),
    formula = genes ~ values,
    data = stripplot.data,
    main = 'Low Jitter',
    xlab.label = 'Change in gene expression',
    ylab.label = 'Gene',
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    xaxis.cex = 1,
    yaxis.cex = 1,
    xaxis.fontface = 1,
    yaxis.fontface = 1,
    xlims = c(0,13),
    xat = seq(0,12,2),
    groups = stripplot.data$sex,
    col = c('pink', 'skyblue'),
    pch = 19,
    colour.alpha = 0.5,
    cex = 1,
    key = list(
        space = 'right',
        text = list(
            lab = levels(stripplot.data$sex),
            cex = 1,
            col = 'black'
        ),
        points = list(
            pch = 19,
            col = c('pink','skyblue'),
            alpha = 0.4,
            cex = 1
        ),
        padding.text = 3
    ),
    # Custom jitter
    jitter.data = TRUE,
    description = 'Stripplot created by BoutrosLab.plotting.general',
    resolution = 200
);

# Jitter
create.stripplot(
    filename = tempfile(pattern = 'Stripplot_High_Jitter', fileext = '.tiff'),
    formula = genes ~ values,
    data = stripplot.data,
    main = 'High Jitter',
    xlab.label = 'Change in gene expression',
    ylab.label = 'Gene',
    xlab.cex = 1.5,
    ylab.cex = 1.5,
    xaxis.cex = 1,
```

```
yaxis.cex = 1,
xaxis.fontface = 1,
yaxis.fontface = 1,
xlims = c(0,13),
xat = seq(0,12,2),
groups = stripplot.data$sex,
col = c('pink', 'skyblue'),
pch = 19,
colour.alpha = 0.5,
cex = 1,
key = list(
  space = 'right',
  text = list(
    lab = levels(stripplot.data$sex),
    cex = 1,
    col = 'black'
  ),
  points = list(
    pch = 19,
    col = c('pink','skyblue'),
    alpha = 0.4,
    cex = 1
  ),
  padding.text = 3
),
# Custom jitter
jitter.data = TRUE,
jitter.factor = 0.5,
jitter.amount = 0.33,
description = 'Stripplot created by BoutrosLab.plotting.general',
resolution = 200
);

# Nature style
create.stripplot(
  filename = tempfile(pattern = 'Stripplot_Nature_style', fileext = '.tiff'),
  formula = genes ~ values,
  data = stripplot.data,
  main = 'Nature style',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlims = c(0,13),
  xat = seq(0,12,2),
  groups = stripplot.data$sex,
  col = c('pink', 'skyblue'),
  pch = 19,
  colour.alpha = 0.5,
  cex = 1,
  key = list(
```

```

space = 'right',
text = list(
  lab = levels(stripplot.data$sex),
  cex = 1,
  col = 'black'
),
points = list(
  pch = 19,
  col = c('pink','skyblue'),
  alpha = 0.4,
  cex = 1
),
padding.text = 3
),
jitter.data = TRUE,
jitter.factor = 0.5,
jitter.amount = 0.33,

# set style to Nature
style = 'Nature',

# demonstrating how to italicize character variables
ylab.label = expression(paste('italicized ', italic('a'))),

# demonstrating how to create en-dashes
xlab.label = expression(paste('en dashes: 1', '\u2013', '10' '^' '\u2013', ''^3)),

description = 'Stripplot created by BoutrosLab.plotting.general',
resolution = 200
);

```

create.violinplot *Make a violin plot*

Description

This function takes a dataframe and writes a pretty TIFF violin plot

Usage

```

create.violinplot(
  formula,
  data,
  filename = NULL,
  main = NULL,
  main.just = 'center',
  main.x = 0.5,
  main.y = 0.5,

```

```
main.cex = 3,
xlab.label = tail(sub('`', '', formula[-2]), 1),
ylab.label = tail(sub('`', '', formula[-3]), 1),
xlab.cex = 2,
ylab.cex = 2,
xlab.col = 'black',
ylab.col = 'black',
xlab.top.label = NULL,
xlab.top.cex = 2,
xlab.top.col = 'black',
xlab.top.just = 'center',
xlab.top.x = 0.5,
xlab.top.y = 0,
xaxis.lab = TRUE,
yaxis.lab = TRUE,
xaxis.cex = 1.5,
yaxis.cex = 1.5,
xaxis.col = 'black',
yaxis.col = 'black',
xaxis.fontface = 'bold',
yaxis.fontface = 'bold',
xaxis.rot = 0,
yaxis.rot = 0,
xaxis.tck = c(1,0),
yaxis.tck = c(1,1),
ylimits = NULL,
yat = TRUE,
col = 'black',
lwd = 1,
border.lwd = 1,
bandwidth = 'nrd0',
bandwidth.adjust = 1,
extra.points = NULL,
extra.points.pch = 21,
extra.points.col = 'white',
extra.points.border = 'black',
extra.points.cex = 1,
start = NULL,
end = NULL,
scale = FALSE,
plot.horizontal = FALSE,
top.padding = 0.1,
bottom.padding = 0.7,
left.padding = 0.5,
right.padding = 0.3,
key = NULL,
legend = NULL,
add.rectangle = FALSE,
```

```

xleft.rectangle = NULL,
ybottom.rectangle = NULL,
xright.rectangle = NULL,
ytop.rectangle = NULL,
col.rectangle = 'transparent',
alpha.rectangle = 1,
height = 6,
width = 6,
resolution = 1600,
size.units = 'in',
enable.warnings = FALSE,
description = 'Created with BoutrosLab.plotting.general',
style = 'BoutrosLab',
preload.default = 'custom',
use.legacy.settings = FALSE,
disable.factor.sorting = FALSE
)

```

Arguments

<code>formula</code>	The formula used to extract the violin components from the data-frame
<code>data</code>	The data-frame to plot
<code>filename</code>	Filename for tiff output, or if NULL returns the trellis object itself
<code>main</code>	The main title for the plot (space is reclaimed if NULL)
<code>main.just</code>	The justification of the main title for the plot, default is centered
<code>main.x</code>	The x location of the main title, default is 0.5
<code>main.y</code>	The y location of the main title, default is 0.5
<code>main.cex</code>	Size of text for main plot title, defaults to 3
<code>xlab.label</code>	The label for the x-axis
<code>ylab.label</code>	The label for the y-axis
<code>xlab.cex</code>	Size of x-axis label, defaults to 3
<code>ylab.cex</code>	Size of y-axis label, defaults to 3
<code>xlab.col</code>	Colour of the x-axis label, defaults to "black"
<code>ylab.col</code>	Colour of the y-axis label, defaults to "black"
<code>xlab.top.label</code>	The label for the top x-axis
<code>xlab.top.cex</code>	Size of top x-axis label
<code>xlab.top.col</code>	Colour of the top x-axis label
<code>xlab.top.just</code>	Justification of the top x-axis label, defaults to centered
<code>xlab.top.x</code>	The x location of the top x-axis label
<code>xlab.top.y</code>	The y location of the top y-axis label
<code>xaxis.lab</code>	Vector listing x-axis tick labels, defaults to automatic
<code>yaxis.lab</code>	Vector listing y-axis tick labels, defaults to automatic

xaxis.cex	Size of x-axis tick labels, defaults to 2
yaxis.cex	Size of y-axis tick labels, defaults to 2
xaxis.col	Colour of the x-axis tick labels, defaults to “black”
yaxis.col	Colour of the y-axis tick labels, defaults to “black”
xaxis.fontface	Fontface for the x-axis scales
yaxis.fontface	Fontface for the y-axis scales
xaxis.rot	Rotation of x-axis tick labels; defaults to 0
yaxis.rot	Rotation of y-axis tick labels; defaults to 0
xaxis.tck	Specifies the length of the tick marks for x-axis, defaults to c(1,0)
yaxis.tck	Specifies the length of the tick marks for y-axis, defaults to c(1,1)
ylimits	Two-element vector giving the y-axis limits, default is automatic
yat	Vector listing where the y-axis labels should be drawn, default is automatic
col	Colour to use for filling the interior of the violin plots, defaults to “black”
lwd	Line width, defaults to 1
border.lwd	Width of the exterior boundary of the violin plots, defaults to 1
bandwidth	Smoothing bandwidth, or character string giving rule to choose bandwidth ('nrd0', 'nrd', 'ucv', 'bcv', 'sj', or 'sj-ste'). Passed to base R function density, via lattice::bwplot.
bandwidth.adjust	Adjustment parameter for the bandwidth (bandwidth used is bandwidth*bandwidth.adjust). Makes it easy to specify bandwidth as a proportion of the default.
extra.points	A list of numeric vectors, each one of length equal to the number of violins to be plotted. Specifies a set or sets of extra points to be plotted along the vertical spine of each violin plot. Defaults to NULL (no points to be added)
extra.points.pch	A vector of the same length as extra.points specifying the symbol to use for each set of points. Defaults to 21
extra.points.col	A vector of the same length as extra.points specifying the colour to use for each set of points. Defaults to “white”
extra.points.border	A vector of the same length as extra.points specifying the border colour to use for points >=21. Defaults to “black”
extra.points.cex	A vector of the same length as extra.points specifying the size of each set of points. Defaults to 1
start	Start of boundary cutoff, default is NULL for no boundary
end	End of boundary cutoff, default is NULL for no boundary
scale	Logical; Scales the violin plots, see ?panel.violin for more details, default is FALSE

plot.horizontal	Logical; Determines whether to draw violin plot horizontally or vertically; default is FALSE; If horizontal is FALSE, x will be coerced to a factor or shingle, and vice versa.
top.padding	A number giving the top padding in multiples of the lattice default
bottom.padding	A number giving the bottom padding in multiples of the lattice default
left.padding	A number giving the left padding in multiples of the lattice default
right.padding	A number giving the right padding in multiples of the lattice default
key	Add a key to the plot. See xyplot.
legend	Add a legend to the plot. Helpful for adding multiple keys and adding keys to the margins of the plot. See xyplot.
add.rectangle	Allow a rectangle to be drawn, default is FALSE
xleft.rectangle	Specifies the left x coordinate of the rectangle to be drawn
ybottom.rectangle	Specifies the bottom y coordinate of the rectangle to be drawn
xright.rectangle	Specifies the right x coordinate of the rectangle to be drawn
ytop.rectangle	Specifies the top y coordinate of the rectangle to be drawn
col.rectangle	Specifies the colour to fill the rectangle's area
alpha.rectangle	Specifies the colour bias of the rectangle to be drawn
height	Figure height, defaults to 6 inches
width	Figure width, defaults to 6 inches
resolution	Figure resolution in dpi, defaults to 1600
size.units	Figure units, defaults to inches
enable.warnings	Print warnings if set to TRUE, defaults to FALSE
description	Short description of image/plot; default NULL
style	defaults to "BoutrosLab", also accepts "Nature", which changes parameters according to Nature formatting requirements
preload.default	ability to set multiple sets of different defaults depending on publication needs
use.legacy.settings	boolean to set whether or not to use legacy mode settings (font)
disable.factor.sorting	Disable barplot auto sorting factors alphabetically/numerically

Value

If filename is NULL then returns the trellis object, otherwise creates a plot and returns a 0/1 success code.

Warning

If this function is called without capturing the return value, or specifying a filename, it may crash while trying to draw the histogram. In particular, if a script that uses such a call of create histogram is called by reading the script in from the command line, it will fail badly, with an error message about unavailable fonts:

```
Error in grid.Call.graphics("L_text", as.graphicsAnnot(x$label), x$x, )
  Invalid font type
Calls: print ... drawDetails.text -> grid.Call.graphics -> .Call.graphics
```

Author(s)

Paul C. Boutros

See Also

[bwplot](#), [lattice](#) or the Lattice book for an overview of the package.

Examples

```
set.seed(12345);

simple.data <- data.frame(
  x = c(rep(rnorm(50),5)),
  y = as.factor(sample(LETTERS[1:5],250,TRUE)))
);

create.violinplot(
  filename = tempfile(pattern = 'Violinplot_Simple', fileext = '.tiff'),
  formula = x ~ y,
  data = simple.data,
  resolution = 100
);

# load real datasets
violin.data <- data.frame(
  values = c(t(microarray[1:10, 1:58])),
  genes = rep(rownames(microarray)[1:10], each = 58),
  sex = patient$sex
);

# Minimal input
create.violinplot(
  filename = tempfile(pattern = 'Violinplot_Minimal_Input', fileext = '.tiff'),
  formula = values ~ genes,
  data = violin.data,
  main = 'Minimal input',
  xaxis.rot = 90,
  description = 'Violinplot created by BoutrosLab.plotting.general',
```

```
resolution = 100
);

# Axes & Labels
create.violinplot(
  filename = tempfile(pattern = 'Violinplot_Axes_Labels', fileext = '.tiff'),
  formula = values ~ genes,
  data = violin.data,
  main = 'Axes & labels',
  xaxis.rot = 90,
  # Adjusting axes
  xaxis.cex = 1,
  yaxis.cex = 1,
  ylims = c(0, 13),
  yat = seq(0, 12, 2),
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.label = 'Gene',
  ylab.label = 'Change in expression',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  description = 'Violinplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Range
create.violinplot(
  filename = tempfile(pattern = 'Violinplot_Range', fileext = '.tiff'),
  formula = values ~ genes,
  data = violin.data,
  main = 'Range',
  xaxis.rot = 90,
  xaxis.cex = 1,
  yaxis.cex = 1,
  # adjusted y-axis limits
  ylims = c(0, 11),
  yat = seq(0, 10, 2),
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.label = 'Gene',
  ylab.label = 'Change in expression',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  # Specify range
  start = 1,
  end = 10,
  description = 'Violinplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Scaling
create.violinplot(
  filename = tempfile(pattern = 'Violinplot_Scale', fileext = '.tiff'),
```

```
formula = values ~ genes,
data = violin.data,
main = 'Scale',
xaxis.rot = 90,
xaxis.cex = 1,
yaxis.cex = 1,
ylimits = c(0, 13),
yat = seq(0, 12, 2),
xaxis.fontface = 1,
yaxis.fontface = 1,
xlab.label = 'Gene',
ylab.label = 'Change in expression',
xlab.cex = 1.5,
ylab.cex = 1.5,
# Scale
scale = TRUE,
description = 'Violinplot created by BoutrosLab.plotting.general',
resolution = 100
);

# Extra points
median.points <- unlist(tapply(violin.data$values, violin.data$genes, median));
top.points <- unlist(tapply(violin.data$values, violin.data$genes, quantile, 0.90));

create.violinplot(
  filename = tempfile(pattern = 'Violinplot_Points', fileext = '.tiff'),
  formula = values ~ genes,
  data = violin.data,
  main = 'Extra points',
  xaxis.rot = 90,
  xaxis.cex = 1,
  yaxis.cex = 1,
  ylimits = c(0, 13),
  yat = seq(0, 12, 2),
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.label = 'Gene',
  ylab.label = 'Change in expression',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  # Adding median and 90th percentile
  extra.points = list(median.points, top.points),
  extra.points.pch = 21,
  extra.points.col = c('white','grey'),
  extra.points.cex = 0.5,
  description = 'Violinplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# Colours
create.violinplot(
  filename = tempfile(pattern = 'Violinplot_Colour', fileext = '.tiff'),
```

```

formula = values ~ genes,
data = violin.data,
main = 'Colour',
xaxis.rot = 90,
xaxis.cex = 1,
yaxis.cex = 1,
ylimits = c(0, 13),
yat = seq(0, 12, 2),
xaxis.fontface = 1,
yaxis.fontface = 1,
xlab.label = 'Gene',
ylab.label = 'Change in expression',
xlab.cex = 1.5,
ylab.cex = 1.5,
extra.points = list(median.points, top.points),
extra.points.pch = 21,
extra.points.col = c('white','grey'),
extra.points.cex = 0.5,
# Colour
col = 'dodgerblue',
description = 'Violinplot created by BoutrosLab.plotting.general',
resolution = 100
);

# Custom labels
create.violinplot(
  filename = tempfile(pattern = 'Violinplot_Custom_Labels', fileext = '.tiff'),
  formula = values ~ genes,
  data = violin.data,
  main = 'Custom labels',
  xaxis.rot = 90,
  xaxis.cex = 1,
  yaxis.cex = 1,
  ylimits = c(0, 16),
  yat = c(0,1,2,4,8,16),
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.label = 'Gene',
  ylab.label = 'Change in expression',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  extra.points = list(median.points, top.points),
  extra.points.pch = 21,
  extra.points.col = c('white','grey'),
  extra.points.cex = 0.5,
  col = 'dodgerblue',
  # customizing labels
  yaxis.lab = c(
    0,
    expression(paste('2'^'0')),
    expression(paste('2'^'1')),
    expression(paste('2'^'2')),
    expression(paste('2'^'4')),
```

```
    expression(paste('2'^'5'))
  ),
description = 'Violinplot created by BoutrosLab.plotting.general',
resolution = 100
);

# Orientation
create.violinplot(
  filename = tempfile(pattern = 'Violinplot_Orientation', fileext = '.tiff'),
  # switch formula
  formula = genes ~ values,
  data = violin.data,
  main = 'Orientation',
  xaxis.rot = 90,
  xaxis.cex = 1,
  yaxis.cex = 1,
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  ylab.label = 'Gene',
  xlab.label = 'Change in expression',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  extra.points = list(median.points, top.points),
  extra.points.pch = 21,
  extra.points.col = c('white','grey'),
  extra.points.cex = 0.5,
  col = 'dodgerblue',
  # orientation
  plot.horizontal = TRUE,
  description = 'Violinplot created by BoutrosLab.plotting.general',
  resolution = 100
);

# background
create.violinplot(
  filename = tempfile(pattern = 'Violinplot_Background', fileext = '.tiff'),
  formula = values ~ genes,
  data = violin.data,
  main = 'Background rectangle',
  xaxis.rot = 90,
  xaxis.cex = 1,
  yaxis.cex = 1,
  ylims = c(0, 13),
  yat = seq(0, 12, 2),
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.label = 'Gene',
  ylab.label = 'Change in expression',
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  extra.points = list(median.points, top.points),
  extra.points.pch = 21,
  extra.points.col = c('white','grey'),
```

```

extra.points.cex = 0.5,
col = 'dodgerblue',
# background
add.rectangle = TRUE,
xleft.rectangle = seq(0.5, 8.5, 2),
ybottom.rectangle = 0,
xright.rectangle = seq(1.5, 9.5, 2),
ytop.rectangle = 13,
col.rectangle = 'grey',
alpha.rectangle = 0.5,
description = 'Violinplot created by BoutrosLab.plotting.general',
resolution = 100
);

# Nature style
create.violinplot(
  filename = tempfile(pattern = 'Violinplot_Nature_style', fileext = '.tiff'),
  formula = values ~ genes,
  data = violin.data,
  main = 'Nature style',
  xaxis.rot = 90,
  xaxis.cex = 1,
  yaxis.cex = 1,
  ylims = c(0, 13),
  yat = seq(0, 12, 2),
  xaxis.fontface = 1,
  yaxis.fontface = 1,
  xlab.cex = 1.5,
  ylab.cex = 1.5,
  col = 'dodgerblue',
  add.rectangle = TRUE,
  xleft.rectangle = seq(0.5, 8.5, 2),
  ybottom.rectangle = 0,
  xright.rectangle = seq(1.5, 9.5, 2),
  ytop.rectangle = 13,
  col.rectangle = 'grey',
  alpha.rectangle = 0.5,

  # set style to Nature
  style = 'Nature',

  # demonstrating how to italicize character variables
  ylab.lab = expression(paste('italicized ', italic('a'))),

  # demonstrating how to create en-dashes
  xlab.lab = expression(paste('en dashes: 1', '\u2013', '10' '^' '\u2013', ''^3)),

  description = 'Violinplot created by BoutrosLab.plotting.general',
  resolution = 200
);

```

default.colours	<i>Provides default colour schemes.</i>
-----------------	---

Description

Returns colour schemes based on user input. Used to provide default colour schemes for simple cases.

Usage

```
default.colours(  
  number.of.colours = 2,  
  palette.type = 'qual',  
  is.greyscale = TRUE,  
  is.venn = FALSE  
)
```

Arguments

number.of.colours

The number of colours requested for the colour scheme.

palette.type

The type of colour scheme requested. Only palette types of “seq”, “div”, “qual”, “pastel”, “survival”, “dotmap”, “spiral.sunrise”, “spiral.morning”, “spiral.dusk”, “spiral.noon”, “spiral.afternoon”, “spiral.dawn”, and “spiral.night” are accepted. Legacy colour palettes are available under “chromosomes”, “old.qual1”, “old.qual2”, “old.seq”, and “old.div”. “seq” corresponds to sequential colour schemes, “div” corresponds to diverging colour schemes, and “qual” corresponds to qualitative colour schemes - “pastel” is a pastel version of this palette. “survival” is useful for survival plots, as the first two colour are blue and red, following convention. The remaining colour schemes are not tied to a specific use-case.

is.greyscale

Boolean asking whether or the colour scheme should be greyscale-compatible. Defaults to TRUE. The purpose of this parameter is to warn users if they ask for a colour scheme that is not greyscale-compatible. Regardless of the value of is.greyscale, the same colour scheme will be provided.

is.venn

Boolean determining whether or not the colour scheme is to be used for a venn diagram. If TRUE, the palette type should be set to NULL. For venn diagrams, text colours are also provided.

Details

For further information on colour schemes, refer to the plotting guide.)

Author(s)

Christine P'ng

Examples

```
default.colours(number.of.colours = 6, is.greyscale = FALSE, palette.type = 'div')
# Returns:
# [1] "#B32B2B" "#DD4E4E" "#EB7C7C" "#F7BEBE" "#BEF4F7" "#80CDD1"

default.colours(number.of.colours = 3, palette.type = NULL, is.venn = TRUE)
# Returns:
# [1] "red"      "dodgerblue" "yellow"
# [1] "darkred"   "darkblue"   "darkorange"
# The second line of colours is the corresponding text colour

default.colours(number.of.colours = c('2','5','3'), c('binary','seq','seq'))
# Returns:
# [[1]]
# [1] "white"     "chartreuse3"

# [[2]]
# [1] "lavenderblush"  "pink"           "palevioletred1" "violetred1"
# [5] "maroon"

# [[3]]
# [1] "aliceblue"    "lightblue1"    "lightskyblue"

default.colours(5, 'spiral.sunrise');
# Returns:
# [1] "#336A90" "#65B4A2" "#B1D39A" "#F4E0A6" "#FFE1EE"
```

`display.colours` *Function to display R colors, as well as corresponding R grey colours.*

Description

Displays R colors and their corresponding R grey colours.

Usage

```
display.colours(
  cols,
  names = cols
);
```

Arguments

<code>cols</code>	Vector of colours to be displayed.
<code>names</code>	The names of the colours. Defaults to equal the input of <code>cols</code>

Details

For further information on colour schemes, refer to the colour guide (in Resources/general)

Author(s)

Christine P'ng

Examples

```
display.colours('red');
# Red and Grey are displayed

display.colours(default.colours(5));
# Five default colours and their grey values are displayed

test.colours <- force.colour.scheme(c('skin','nerve'), 'tissue');
display.colours(test.colours);
```

display.statistical.result

Utility function to display statistical result in a plot

Description

A utility function to display statistical result in a plot in scientific notation (when appropriate)

Usage

```
display.statistical.result(
  x,
  lower.cutoff = 2.2e-50,
  scientific.cutoff = 0.001,
  digits = 2,
  statistic.type = 'P',
  symbol = ':'
);
```

Arguments

x	Numeric value to be displayed
lower.cutoff	For values of x smaller than lower.cutoff, the return value will be "< lower.cutoff". Defaults to 2.2e-16
scientific.cutoff	For values of x larger or equal to scientific.cutoff, standard notation will be used (rather than scientific notation). Defaults to 0.001

digits Number of decimal places of precision to be shown
statistic.type Type of statistic to be displayed, defaults to “P”.
symbol Symbol prior to statistic to be displayed, defaults to “: ”.

Value

Returns an expression

Author(s)

Nathalie Moon

See Also

`scientific.notation`

Examples

```
set.seed(100);

display.statistical.result(x = 0.0000000000000000000000000000234);
display.statistical.result(x = 0.023, statistic.type = 'Q');
display.statistical.result(x = 0.001, scientific.cutoff = 0.01, symbol = ' = ');
```

dist *Distance Matrix Computation***Description**

This function computes and returns the distance matrix computed by using the specified distance measure to compute the distances between the rows of a data matrix.

Usage

```
dist(x, method = "euclidean", diag = FALSE, upper = FALSE, p = 2)
```

Arguments

x	a numeric matrix, data frame or "dist" object.
method	the distance measure to be used. This must be one of "euclidean", "maximum", "manhattan", "canberra", "binary", "minkowski", or "jaccard". Any unambiguous substring can be given.
diag	logical value indicating whether the diagonal of the distance matrix should be printed by <code>print.dist</code> .
upper	logical value indicating whether the upper triangle of the distance matrix should be printed by <code>print.dist</code> .
p	The power of the Minkowski distance.

Details

Available distance measures are (written for two vectors x and y):

euclidean: Usual square distance between the two vectors (2 norm).

maximum: Maximum distance between two components of x and y (supremum norm)

manhattan: Absolute distance between the two vectors (1 norm).

canberra: $\sum_i |x_i - y_i| / |x_i + y_i|$. Terms with zero numerator and denominator are omitted from the sum and treated as if the values were missing.

This is intended for non-negative values (e.g. counts): taking the absolute value of the denominator is a 1998 R modification to avoid negative distances.

binary: (aka *asymmetric binary*): The vectors are regarded as binary bits, so non-zero elements are ‘on’ and zero elements are ‘off’. The distance is the *proportion* of bits in which only one is on amongst those in which at least one is on.

minkowski: The p norm, the p th root of the sum of the p th powers of the differences of the components.

jaccard: The proportion of items that are not in both sets. For binary data, the output is equal to `dist(method = "binary")`

Missing values are allowed, and are excluded from all computations involving the rows within which they occur. Further, when Inf values are involved, all pairs of values are excluded when their contribution to the distance gave NaN or NA. If some columns are excluded in calculating a Euclidean, Manhattan, Canberra or Minkowski distance, the sum is scaled up proportionally to the number of columns used. If all pairs are excluded when calculating a particular distance, the value is NA.

The “`dist`” method of `as.matrix()` and `as.dist()` can be used for conversion between objects of class “`dist`” and conventional distance matrices.

Value

`dist` returns an object of class “`dist`”.

The lower triangle of the distance matrix stored by columns in a vector, say `do`. If `n` is the number of observations, i.e., `n <- attr(do, "Size")`, then for $i < j \leq n$, the dissimilarity between (row) i and j is $do[n*(i-1) - i*(i-1)/2 + j-i]$. The length of the vector is $n * (n - 1)/2$, i.e., of order n^2 .

The object has the following attributes (besides “`class`” equal to “`dist`”):

<code>Size</code>	integer, the number of observations in the dataset.
<code>Labels</code>	optionally, contains the labels, if any, of the observations of the dataset.
<code>Diag</code> , <code>Upper</code>	logicals corresponding to the arguments <code>diag</code> and <code>upper</code> above, specifying how the object should be printed.
<code>call</code>	optionally, the <code>call</code> used to create the object.
<code>method</code>	optionally, the distance method used; resulting from <code>dist()</code> , the (<code>match.arg()</code> ed) <code>method</code> argument.

References

- Becker, R. A., Chambers, J. M. and Wilks, A. R. (1988) *The New S Language*. Wadsworth & Brooks/Cole.
- Mardia, K. V., Kent, J. T. and Bibby, J. M. (1979) *Multivariate Analysis*. Academic Press.
- Borg, I. and Groenen, P. (1997) *Modern Multidimensional Scaling. Theory and Applications*. Springer.

See Also

[daisy](#) in the cluster package with more possibilities in the case of *mixed* (continuous / categorical) variables. [hclust](#).

Examples

```
x <- matrix(rnorm(100), nrow=5)
dist(x)
dist(x, diag = TRUE)
dist(x, upper = TRUE)
m <- as.matrix(dist(x))
d <- as.dist(m)
stopifnot(d == dist(x))

## Use correlations between variables "as distance"
dd <- as.dist((1 - cor(USJudgeRatings))/2)
round(1000 * dd) # (prints more nicely)
plot(hclust(dd)) # to see a dendrogram of clustered variables

## example of binary and canberra distances.
x <- c(0, 0, 1, 1, 1, 1)
y <- c(1, 0, 1, 1, 0, 1)
dist(rbind(x,y), method= "binary")
## answer 0.4 = 2/5
dist(rbind(x,y), method= "canberra")
## answer 2 * (6/5)
dist(rbind(x,y), method= "jaccard")
## answer 0.4 = 2/5

## To find the names
labels(eurodist)

## Examples involving "Inf" :
## 1)
x[6] <- Inf
(m2 <- rbind(x,y))
dist(m2, method="binary")# warning, answer 0.5 = 2/4
## These all give "Inf":
stopifnot(Inf == dist(m2, method= "euclidean"),
          Inf == dist(m2, method= "maximum"),
          Inf == dist(m2, method= "manhattan"))
## "Inf" is same as very large number:
```

```

x1 <- x; x1[6] <- 1e100
stopifnot(dist(cbind(x ,y), method="canberra") ==
           print(dist(cbind(x1,y), method="canberra")))

## 2)
y[6] <- Inf #-> 6-th pair is excluded
dist(rbind(x,y), method="binary") # warning; 0.5
dist(rbind(x,y), method="canberra") # 3
dist(rbind(x,y), method="maximum") # 1
dist(rbind(x,y), method="manhattan")# 2.4

```

force.colour.scheme *Based on predefined colour schemes, returns a vector of corresponding colours.*

Description

Takes a vector of character strings and an scheme returns the matching colours as a vector.

Usage

```
force.colour.scheme(
  x = NA,
  scheme,
  fill.colour = 'slategrey',
  include.names = FALSE,
  return.factor = FALSE,
  return.scheme = FALSE
);
```

Arguments

x	The input character or numeric vector, defaults to NA incase return.scheme = TRUE.
scheme	A string representing a predefined scheme. Available schemes are: “anno-var.annotation”, “annoVar.annotation.collapsed”, “annoVar.annotation.collapsed2”, “tissue”, “sex”, “stage”, “risk”, “MSI”, “tumour”, “CNV”, “organism”, “chromosome” and “biomolecule”
fill.colour	Value to enter when value of x not present in scheme.
include.names	Should the output be a named vector or not?
return.factor	Should factors (scheme names) be returned?
return.scheme	Should the scheme list be returned?

Details

The input character options for each colour scheme are as follows: annovar.annotation

- nonsynonymous snv
- stopgain snv
- stoploss snv
- frameshift deletion
- frameshift substitution
- splicing
- synonymous snv

annovar.annotation.collapsed

- nonsynonymous snv
- stopgain snv
- stoploss SNV
- frameshift indel
- splicing

annovar.annotation.collapsed2

- nonsynonymous
- stopgain-stoploss
- splicing
- frameshift indel
- synonymous
- utr5-utr3
- nonframeshift indel
- intronic
- intergenic
- other

tissue

- cartilage
- bone
- adipose
- bladder
- kidney
- blood
- heart
- muscle

- hypothalamus
- pituitary
- thyroid
- parathyroid
- skin
- salivary gland
- esophagus
- stomach
- liver
- gallbladder
- pancreas
- intestine
- colon
- pharynx
- larynx
- trachea
- diaphragm
- lung
- nerve
- spine
- brain
- eye
- breast
- ovary
- uterus
- prostate
- testes
- lymph
- leukocyte
- spleen

sex

- male
- female

stage

- I
- II

- III
- IV

risk

- High
- Low

MSI

- MSI-High
- MSI-Low
- MSS

tumour

- Primary
- Metastatic

CNV

- Amplification
- Deletion
- LOH
- Neutral

organism

- Human
- Rat
- Mouse

chromosome

- 1 - 22
- X
- Y

biomolecule

- DNA
- RNA
- Protein
- Carbohydrate
- Lipid

clinicalt3

- t0

- t1
- t2
- t3
- t4
- t5

clinicalt9

- t1a
- t1b
- t1c
- t2a
- t2b
- t2c
- t3a
- t3b
- t3c

gleason.score

- 3+3
- 3+4
- 4+4
- 4+5
- 3+5
- 5+3
- 5+4
- 5+5
- missing
- NA

gleason.sum

- 5
- 6
- 7
- 8
- 9
- missing
- NA

tissue.color

- blood
- frozen
- ffpe

psa.categorical

- 0 - 9.9
- 10 - 19.9
- >= 20

age.categorical.default

- <50
- 50 - 60
- 60 - 70
- >= 70

age.categorical.prostate

- <40
- 40 - 50
- 50 - 65
- 65 - 70
- >= 70

age.gradient

psa.gradient

heteroplasmy

- 0 - 0.2
- 0.2 - 0.4
- 0.4 - 0.6
- 0.6 - 1.0

mt.annotation

- MT-DLOOP
- MT-T*
- MT-RNR*
- MT-ND1
- MT-ND2
- MT-ND3
- MT-ND4L
- MT-ND4L/MT-ND4
- MT-ND4

- MT-ND5
- MT-ND6
- MT-CO1
- MT-CO2
- MT-CO3
- MT-ATP6/MT-CO3
- MT-ATP6
- MT-ATP8/MT-ATP6
- MT-ATP8
- MT-CYB
- MT-NC*
- MT-OL*

isup.grade

- 1
- 2
- 3
- 4
- 5

Value

If multiple returns are requested, outputs a list (return.factor: factor length x with scheme names; scheme: list containing scheme names and colours; colours: vector length x with the required colours).

Author(s)

Nicholas Harding

Examples

```
annovar.output <- c('nonsynonymous snv', 'stopgain snv', 'none', 'stoploss snv',
'frameshift deletion', 'frameshift substitution', 'splicing', 'none');
force.colour.scheme(annovar.output,'annovar.annotation');
force.colour.scheme(annovar.output,'annovar.annotation', 'white');
```

<code>generate.at.final</code>	<i>Generates alternative default tick mark locations for <code>create.densityplot()</code> and <code>create.scatterplot()</code></i>
--------------------------------	--

Description

Generates the tick mark locations for the output graphic of `create.densityplot()`, based on the values to the arguments of that function. This is needed to ensure the grid line and tick mark locations agree with each other.

Usage

```
generate.at.final(
  at.input,
  limits,
  data.vector
);
```

Arguments

<code>at.input</code>	either a logical scalar or a numeric vector
<code>limits</code>	either NULL or a numeric vector of length 2
<code>data.vector</code>	a numeric vector

Value

Returns a numeric vector containing the tick mark locations of the densityplot.

Author(s)

Kenneth C.K. Chu

<code>get.corr.key</code>	<i>Correlation Key</i>
---------------------------	------------------------

Description

A function for adding correlation key legends to scatterplots.

Usage

```
get.corr.key(
  x,
  y,
  label.items = c("spearman", "spearman.p"),
  x.pos = 0.03,
  y.pos = 0.97,
  key.corner = NULL,
  key.cex = 1,
  key.title = NULL,
  title.cex = 1,
  alpha.background = 0,
  num.decimals = 2,
  border = 'white'
)
```

Arguments

x	A vector of values
y	Another vector of values with the same length as x
label.items	A vector of things to include in the key. Any combination of the following can be used. c("spearman", "pearson", "kendall", "beta0", "beta1", "spearman.p", "pearson.p", "kendall.p", "beta1.p", "beta.robust", "beta.robust.p"). "all" is an alternative to the full list.
x.pos	Horizontal position of the key corner
y.pos	Vertical position of the key corner
key.corner	The corner of the key defaults to the closest corner of the plot. This helps overcome some variable character and row sizing.
key.cex	Specifies the size of font for the key, defaults to 1.
key.title	The title of the key. Defaults to NULL
title.cex	The size of the key title. Defaults to 1
alpha.background	A value from 0 to 1 indicating the transparency of the legend box.
num.decimals	Number of decimal places to keep for spearman, pearson and kendall correlations. Defaults to 2.
border	Adds border around the key with the color specified, alpha background cannot be 0. Defaults to White.

Value

Returns a key in the format specified in the xyplot documentation.

Author(s)

Daryl Waggett

See Also

`xypplot`, `plotmath`

Examples

```
# create some temporary data
tmp.data <- data.frame(
  x = c(
    runif(n = 15, min = 0, max = 20),
    runif(n = 15, min = 80, max = 100),
    runif(n = 70, min = 0, max = 100)
  ),
  y = c(
    runif(n = 15, min = 0, max = 20),
    runif(n = 15, min = 80, max = 100),
    runif(n = 70, min = 0, max = 100)
  )
);

# a simple scatterplot with correlation key
BoutrosLab.plotting.general::create.scatterplot(
  formula = y ~ x,
  data = tmp.data,
  filename = tempfile(pattern = 'get.corr.key-scatterplot', fileext = '.tiff'),
  xlab.label = 'X Axis Title',
  ylab.label = 'Y Axis Title',
  xlims = c(0,100),
  ylims = c(0,100),
  xat = seq(0,100,25),
  yat = seq(0,100,25),
  add.axes = FALSE,
  key = BoutrosLab.plotting.general::get.corr.key(
    tmp.data$y,
    tmp.data$x,
    label.items = c('spearman', 'spearman.p', 'kendall', 'beta1', 'beta1.p')
  )
);

# compare beta1 vs a robust estimate of the slope

# add an outlier
tmp.data <- rbind(tmp.data, c(2000,100));

BoutrosLab.plotting.general::create.scatterplot(
  formula = y ~ x,
  data = tmp.data,
  filename = tempfile(pattern = 'get.corr.key.robust-scatterplot', fileext = '.tiff'),
  xlab.label = 'X Axis Title',
  ylab.label = 'Y Axis Title',
  xlims = c(0,100),
  ylims = c(0,100),
```

```
xat = seq(0,100,25),
yat = seq(0,100,25),
add.axes = FALSE,
key = BoutrosLab.plotting.general::get.corr.key(
  tmp.data$y,
  tmp.data$x,
  label.items = c('beta1', 'beta1.robust','beta1.p','beta1.robust.p')
)
);

# see create.scatterplot for an example of creating multiple keys using legends
```

get.correlation.p.and.corr

Calculate a correlation and its statistical significance

Description

Returns the correlation and p-value for two variables using a user-specified correlation metric. P-values are estimated analytically, not via permutation-testing.

Usage

```
get.correlation.p.and.corr(x, y, alternative = 'two.sided', method = 'pearson');
```

Arguments

<code>x</code>	Vector of numbers to analyze
<code>y</code>	Vector of numbers to analyze
<code>alternative</code>	What is the null-hypothesis?
<code>method</code>	The correlation technique to use (passed directly to cor.test)

Value

Returns a two-element vector containing the correlation and its p-value.

Author(s)

Paul C. Boutros

Examples

```
get.correlation.p.and.corr(
  x = runif(100),
  y = runif(100),
  method = 'pearson'
);

get.correlation.p.and.corr(
  x = sample(1:10, 100, replace = TRUE),
  y = runif(100),
  method = 'spearman'
);
```

get.defaults

Get operating system specific default properties

Description

Returns the value for the property requested

Usage

```
get.defaults(
  property = 'fontfamily',
  os.type = .Platform$OS.type,
  add.to.list = NULL,
  use.legacy.settings = FALSE
);
```

Arguments

<code>property</code>	The property to be retrieved
<code>os.type</code>	operating system (optional). valid values are: "windows", "unix"
<code>add.to.list</code>	appends the requested property to this parameter
<code>use.legacy.settings</code>	boolean to set wheter or not to use legacy mode settings (font)

Value

Returns the value (list if add.to.list is passed) for the property requested given the os.type parameter.
If latter is missing, it attempts to find user's operating system

Author(s)

Syed Haider

Examples

```
# returns the fontfamily for current OS  
get.defaults(property = "fontfamily");  
  
# returns the fontfamily for unix  
get.defaults(property = "fontfamily", os.type = 'windows');
```

get.line.breaks	<i>Get line breaks</i>
-----------------	------------------------

Description

Given a vector, returns the indices (and an adjustment to draw lines between cells) where the value is not equal to the preceding value. Main use intended to be in row.lines arguments to create.heatmap

Usage

```
get.line.breaks(  
  x  
)
```

Arguments

x A vector, numeric, factor or character.

Value

A vector of integers representing the break points in the vector x

Author(s)

Nicholas Harding

Examples

```
set.seed(12345);  
values <- sample(  
  default.colours(3),  
  20,  
  replace = TRUE  
);  
get.line.breaks(values);
```

```
ks.test.critical.value
```

Critical Value for Kolmogorov-Smirnov Test

Description

Takes a sample size and a confidence level and computes the corresponding critical value basing on the kolmogorov-smirnov test

Usage

```
ks.test.critical.value(n, conf, alternative = "two.sided");
```

Arguments

n	The sample size
conf	The confidence level
alternative	Indicates the alternative hypothesis and must be one of "two.sided"(default), "one-sided".

Value

The corresponding critical value

Author(s)

Ying Wu

Examples

```
ks.test.critical.value(10, 0.95);
ks.test.critical.value(100, 0.95, alternative = "one-sided");
```

```
legend.grob
```

Generate a legend grob

Description

Takes a list and generates a grob representing one or more legends

Usage

```
legend.grob(
  legends,
  label.cex = 1,
  title.cex = 1,
  title.just = 'centre',
  title.fontface = 'bold',
  font.family = NULL,
  size = 3,
  border = NULL,
  border.padding = 1,
  layout = c(1, length(legends)),
  between.col = 1,
  between.row = 1,
  use.legacy.settings = FALSE,
  x = 0.5,
  y = 0.5,
  background.col = "white",
  background.alpha = 0
);
```

Arguments

<code>legends</code>	A list defining one or more legends. Each must be a separate component called 'legend'. Each component is a list with components 'colours', 'labels', 'border' (optional), 'title' (optional), and 'size' (optional). The 'colours' component is a vector of fill colours to be used for the rectangles, the 'labels' component is a vector of text labels corresponding to the colours, the 'border' component specifies the colours of the rectangle borders (defaults to black), and the 'title' component is a character string representing a title for the legend.
<code>label.cex</code>	Size of text labels in the legends, defaults to 1.
<code>title.cex</code>	Size of titles in the legends, defaults to 1.
<code>title.just</code>	Justification of titles in the legends. Defaults to 'centre'.
<code>title.fontface</code>	Font face of titles in the legends ('plain', 'bold', 'italic', etc.)
<code>font.family</code>	Font to be used for legend text. If <code>NULL</code> , the default font is used.
<code>size</code>	Width of the legend boxes in 'character' units. If a 'size' argument is specified for a legend component, it will override this value.
<code>border</code>	A list of parameters (passed to <code>gpar</code>) specifying line options for the legend border. If <code>NULL</code> , no border is drawn.
<code>border.padding</code>	The amount of empty space (split equally on both sides) to add between the legend and its border, in 'lines' units. Defaults to 1.
<code>layout</code>	Numeric vector of length 2 specifying the number of columns and rows for the legend layout. Defaults to a 1-column layout. Note that legends are added to the layout in a row-wise order.

<code>between.col</code>	Amount of space to add between columns in the layout, in 'lines' units. Defaults to 0.5.
<code>between.row</code>	Amount of space to add between rows in the layout, in 'lines' units. Defaults to 0.5.
<code>use.legacy.settings</code>	boolean to set whether or not to use legacy mode settings (font)
<code>x</code>	x coordinate in npc coordinate system
<code>y</code>	y coordinate in npc coordinate system
<code>background.col</code>	colour for the background of the legend grob
<code>background.alpha</code>	alpha for the background of the legend grob

Value

Returns an grob representing the legend(s)

Implementation

This function was initially created to be called from `create.heatmap` to draw a covariate legend. The decision to use a grob (grid graphical object) to represent the legend was made based on the format of the `levelplot` function in the `lattice` package. Since the `legend` argument of the function requires grobs, it was easiest to create a grob to represent the legend and then, if necessary, add this to any existing grobs (dendograms, etc.) in the `create.heatmap` function using a grid layout.

An alternative method of creating the legend using the `barchart` function was tested, but it was unclear how to merge this barchart with the heatmap since the `c.trellis` function attempts to unify the format of the two images, and the use of viewports required that the plots be drawn, eliminating the possibility of suppressing output and saving the final graph as a trellis object.

Author(s)

Lauren Chong

See Also

[create.heatmap](#), [draw.key](#), [gpar](#)

Examples

```
# create list representing two legends
legends1 <- list(
  legend = list(
    colours = c('orange', 'chartreuse4', 'darkorchid4'),
    labels = c('Group 1', 'Group 2', 'Group 3'),
    border = c('orange', 'chartreuse4', 'darkorchid4'),
    title = 'Legend #1'
  ),
  legend = list(
    colours = c('firebrick3', 'lightgrey'),
```

```
    labels = c('Case', 'Control')
  )
);

# create a legend grob using defaults
legend.grob1 <- legend.grob(
  legends = legends1
);
tiff(
  filename = tempfile(pattern = 'legend_grob1', fileext = '.tiff'),
  type = 'cairo',
  width = 5,
  height = 5,
  units = 'in',
  res = 800,
  compression = 'lzw'
);
grid.draw(legend.grob1);
dev.off();

# create the same legend with some customizations
legend.grob2 <- legend.grob(
  legends = legends1,
  label.cex = 1.25,
  title.cex = 1.25,
  title.just = 'left',
  title.fontface = 'bold.italic',
  size = 4,
  border = list(),
  layout = c(2,1)
);
tiff(
  filename = tempfile(pattern = 'legend_grob2', fileext = '.tiff'),
  type = 'cairo',
  width = 5,
  height = 5,
  units = 'in',
  res = 800,
  compression = 'lzw'
);
grid.draw(legend.grob2);
dev.off();

# create a legend where the title is underlined (see ?plotmath), add space between rows
legends2 <- list(
  legend = list(
    colours = c('orange', 'chartreuse4', 'darkorchid4'),
    labels = c('Group 1', 'Group 2', 'Group 3'),
    title = expression(underline('Legend #1'))
  ),
  legend = list(
    colours = c('firebrick3', 'lightgrey'),
    labels = c('A label', 'A longer label')
```

```

        )
);

# create the new legend and use more complex border
legend.grob3 <- legend.grob(
  legends = legends2,
  border = list(col = 'blue', lwd = 2, lty = 3),
  border.padding = 1.5,
  between.row = 3
);
tiff(
  filename = tempfile(pattern = 'legend_grob3', fileext = '.tiff'),
  type = 'cairo',
  width = 5,
  height = 5,
  units = 'in',
  res = 800,
  compression = 'lzw'
);
grid.draw(legend.grob3);
dev.off();

# Make a legend where the size of boxes is customized
legends3 <- list(
  legend = list(
    colours = c('orange', 'chartreuse4', 'darkorchid4'),
    labels = c('Group 1', 'Group 2', 'Group 3'),
    title = 'Legend #1',
    size = c(3,2,1)
  ),
  legend = list(
    colours = NULL,
    labels = c('+', '-'),
    border = 'transparent',
    title = 'Disease status',
    size = 0.5
  )
);
legend.grob4 <- legend.grob(
  legends = legends3
);
tiff(
  filename = tempfile(pattern = 'legend_grob4', fileext = '.tiff'),
  type = 'cairo',
  width = 5,
  height = 5,
  units = 'in',
  res = 800,
  compression = 'lzw'
);
grid.draw(legend.grob4);
dev.off();

```

microarray*Microarray dataset of colon cancer patients*

Description

Gene expression level changes of 2382 genes across 58 colon cancer patients. Additional data on the genes include chromosomal location and p-values. Additional data on the patient samples is found in the "patient" dataset. The same patient samples are described in the "SNV" and "CNA" datasets.

Usage

```
microarray
```

Format

A data frame with 62 columns and 2383 rows. Columns 1-58 indicate the cancer patient sample. Columns 59-61 indicate the (sorted) chromosomal location by "Chr", "Start", and "End". Column 62 contains adjusted p-values. Each row is a different gene, and the row names are the gene names.

Author(s)

Christine P'ng

Examples

```
create.dotmap(
  filename = tempfile(pattern = 'Using_microarray_dataset', fileext = '.tiff'),
  x = microarray[1:5,1:5],
  main = 'microarray data',
  spot.size.function = function(x) {abs(x)/3;},
  xaxis.cex = 0.8,
  yaxis.cex = 0.8,
  xaxis.rot = 90,
  description = 'Dotmap created by BoutrosLab.plotting.general'
);
```

panel.BL.bwplot*A lattice::panel.bwplot replacement that fixes colouring issues*

Description

Function lattice::bwplot() shows unexpected and unintuitive behaviour when colouring parameters of par.settings are vectors. The function panel.BL.bwplot fixes these issues. It should be called only from lattice::bwplot(). Use with caution. This function is invoked by create.boxplot

Arguments

- ... Pass through argument. See `lattice::bwplot()` for further details.
- `enable.warnings` Print warnings if set to TRUE, defaults to FALSE

Author(s)

Mehrdad Shamsi

See Also

[create.boxplot](#)

patient

Dataset describing qualities of 58 colon cancer patients

Description

A number of qualities describing 58 colon cancer patients. The same patient samples are described in the "microarray", "SNV" and "CNA" datasets.

Usage

`patient`

Format

A data frame with 5 columns and 58 rows. Each row indicates a different patient sample, with the following columns describing a feature of the sample:

- sex** The sex of the patient, either "male" or "female"
- stage** The stage of the patient's cancer, one of "I", "II", "III", "IV", or NA
- msi** The microsatellite instability of the cancer, either "MSS" or "MSI-High"
- prop.CAGT** The proportion of C to A or G to T base changes between the sample and reference genome
- prop.CTGA** The proportion of C to T or G to A base changes between the sample and reference genome
- prop.CGGC** The proportion of C to G or G to C base changes between the sample and reference genome
- prop.TAAT** The proportion of T to A or A to T base changes between the sample and reference genome
- prop.TGAC** The proportion of T to G or A to C base changes between the sample and reference genome
- prop.TCAG** The proportion of T to C or A to G base changes between the sample and reference genome

Author(s)

Christine P'ng

Examples

```
# use sample to set colour scheme
sex.colours <- replace(as.vector(patient$sex), which(patient$sex == 'male'), 'dodgerblue');
sex.colours <- replace(sex.colours, which(patient$sex == 'female'), 'pink');
len <- apply(SNV[1:15], 2, function(x){mutation.count <- length(which(x == 1))});

create.barplot(
  filename = tempfile(pattern = 'Using_patient_dataset', fileext = '.tiff'),
  formula = len ~ colnames(SNV[1:15]),
  data = SNV,
  main = 'patient dataset',
  xaxis.rot = 45,
  ylims = c(0,30),
  yat = seq(0,30,5),
  col = sex.colours,
  description = 'Barplot created by BoutrosLab.plotting.general'
);
```

pcawg.colours

Return standard PCAWG colour palettes.

Description

Return standard PCAWG colour palettes. Case insensitive.

Usage

```
pcawg.colours(
  x = NULL,
  scheme = NULL,
  fill.colour = 'slategrey',
  return.scheme = FALSE);
```

Arguments

x	Character vector with terms to be mapped to colours. Ignored if scheme='all' or return.scheme=TRUE.
scheme	String specifying desired colour scheme. To see all available schemes, use scheme='all', returns.scheme=FALSE.
fill.colour	Unrecognized output will be filled with this colour. Default to 'slategrey'.
return.scheme	TRUE/FALSE. Set to true to return full specified scheme. Set to false to map x to colours.

Details

For further information on colour schemes, refer to the plotting guide.)

Author(s)

Jennifer Aguiar & Constance Li

scientific.notation *Use scientific notation in plots*

Description

Returns an expression or list for plotting data in scientific notation

Usage

```
scientific.notation(  
  x,  
  digits = 1,  
  type = 'expression'  
)
```

Arguments

x	The number we want in scientific notation.
digits	How many decimal places to keep.
type	The format to return the value in. Defaults to 'expression', also accepts 'list'

Value

Generates scientific notation either as an expression or list.

Author(s)

Paul C. Boutros

```
show.available.palettes
```

Display the available colour palettes

Description

Displays the available colour palettes

Usage

```
show.available.palettes(  
  type = 'general',  
  filename = NULL,  
  height = 5,  
  width = 8,  
  resolution = 300  
)
```

Arguments

type	Either “general”, “specific”, or “both” (default)
filename	Filename for tiff output, or if NULL returns the trellis object itself
height	Figure height, defaults to 8 inches – this is optimal for the specific schemes
width	Figure width, defaults to 12 – this is optimal for the specific schemes
resolution	Figure resolution in dpi, defaults to 300

Author(s)

Christine P’ng

Examples

```
show.available.palettes(  
  filename = tempfile(pattern = 'show_case_specific_schemes', fileext = '.tiff'),  
  type = 'specific',  
  width = 10  
)  
  
show.available.palettes(  
  filename = tempfile(pattern = 'default_schemes', fileext = '.tiff'),  
  type = 'general',  
  height = 6,  
  width = 8  
)
```

SNV*Single nucleotide variant (SNV) data from colon cancer patients*

Description

SNV calls from 30 genes across 58 colon cancer patients. Additional data on the patient samples is found in the "patient" dataset. The same patient samples are described in the "microarray" and "CNA" datasets.

Usage

SNV

Format

A data frame with 58 columns and 30 rows. The columns indicate the patient sample, and the rows indicate the gene. The contents of the data frame are either NA (indicating no SNV call was made) or one of:

- 1 - nonsynonymous SNV
- 2 - stopgain SNV
- 3 - frameshift insertion
- 4 - frameshift deletion
- 5 - nonframeshift insertion
- 6 - nonframeshift deletion
- 7 - splicing
- 8 - unknown

Author(s)

Christine P'ng

Examples

```
len <- apply(SNV[1:15], 2, function(x){mutation.count <- length(which(x == 1))});

create.barplot(
  filename = tempfile(pattern = 'Using_SNV_dataset', fileext = '.tiff'),
  formula = len ~ colnames(SNV[1:15]) ,
  data = SNV,
  main = 'SNV dataset',
  xaxis.rot = 45,
  ylims = c(0,30),
  yat = seq(0,30,5),
  description = 'Barplot created by BoutrosLab.plotting.general'
);
```

thousands.split	<i>Divide strings into groups of thousands</i>
-----------------	--

Description

Takes a single number or list, and converts them into a new string with commas to mark the thousand multiples

Usage

```
thousands.split(  
  nums  
)
```

Arguments

nums	The numbers to be divided
------	---------------------------

Author(s)

Jeffrey Green

Examples

```
thousands.split(2344)  
  
nums = c(1,2,34343,56565645645,676756,3434)  
  
thousands.split(nums)  
  
scatter.data <- data.frame(  
  sample.one = microarray[1:800,1],  
  sample.two = microarray[1:800,2],  
  chr = microarray$Chr[1:800]  
);  
  
create.scatterplot(  
  filename = tempfile(pattern = 'Test_Divide_Thousands', fileext = '.tiff'),  
  formula = sample.two ~ sample.one,  
  data = scatter.data,  
  main = 'Axes & Labels',  
  # Axes and labels  
  xlab.label = colnames(microarray[1]),  
  ylab.label = colnames(microarray[2]),  
  yaxis.lab = thousands.split(c(1,2323,4545,567676,454,76767678678,89,787)),  
  xat = seq(0, 16, 2),  
  yat = seq(0, 16, 2),  
  xlims = c(0, 15),
```

```

ylimits = c(0, 15),
xaxis.cex = 1,
yaxis.cex = 1,
xaxis.fontface = 1,
yaxis.fontface = 1,
xlab.cex = 1.5,
ylab.cex = 1.5,
description = 'Scatter plot created by BoutrosLab.plotting.general'
);

```

write.metadata*Writes Metadata***Description**

Utilizes exiftool to write metadata to generated plots. Writes the R version, lattice version, lattice-Extra version, BoutrosLab.plotting.general version, BoutrosLab.plotting.survival version, operating system, machine, author, image description.

Usage

```

write.metadata(
  filename = NULL,
  description = NULL,
  verbose = FALSE
);

```

Arguments

<code>filename</code>	Filename for output, or if <code>NULL</code> (default value) returns image unchanged.
<code>description</code>	Short description of image; default <code>NULL</code>
<code>verbose</code>	Option to standard output; default <code>FALSE</code>

Value

If `filename` is `NULL`, returns the image unchanged. If `description` is `NULL`, then the image is returned without the description tag.

Note: an easy way to view the metadata is by using the exiftool command.

Author(s)

Esther Jung

write.plot	<i>Simplifies plotting by standardizing and centralizing all output-handling</i>
------------	--

Description

Handle various graphics-driver weirdness and writes an output file and returns 1 or returns the trellis.object

Usage

```
write.plot(
  trellis.object,
  filename = NULL,
  additional.trellis.objects = NULL,
  additional.trellis.locations = NULL,
  height = 6,
  width = 6,
  size.units = 'in',
  resolution = 1000,
  enable.warnings = FALSE,
  description = "Created with BoutrosLab.plotting.general"
);
```

Arguments

trellis.object	A trellis object to be plotted
filename	Filename for output, or if NULL (default value) returns the trellis object itself. Will automatically grab the extension used.
additional.trellis.objects	List of additional trellis objects to add to main plot. Default to NULL
additional.trellis.locations	List of coordinates for additional trellis objects. Must be represented using variable names 'xleft', 'ybottom', 'xright' and 'ytop'. Defaults to NULL
height	Figure height, defaults to 6 inches
width	Figure width, defaults to 6 inches
size.units	Figure units, defaults to 'in'
resolution	Figure resolution, defaults to 1000
enable.warnings	Print warnings if set to TRUE, defaults to FALSE
description	Short description of image; default NULL

Value

Returns the trellis.object if filename is NULL or writes the plot to file if a filename is specified.

Author(s)

Paul C. Boutros

Examples

```

set.seed(253647)
# create test data
tmp.data <- data.frame(
  x = c(
    runif(n = 150, min = 0, max = 20),
    runif(n = 150, min = 40, max = 60),
    runif(n = 700, min = 0, max = 40)
  ),
  y = c(
    runif(n = 150, min = 0, max = 20),
    runif(n = 150, min = 40, max = 60),
    runif(n = 700, min = 0, max = 40)
  )
);

main.plot <- create.densityplot(
  x = list(
    X = tmp.data$x,
    Y = tmp.data$y
  ),
  xlab.label = 'X Axis Title',
  ylab.label = 'Y Axis Title',
  xlims = c(-50,150),
  ylims = c(0,0.03),
  xat = seq(-50,150,50),
  yat = seq(0,0.03,0.005),
  description = 'Image description goes here'
);

secondary.plot <- create.densityplot(
  x = list(
    X = tmp.data$x,
    Y = tmp.data$y
  ),
  xlab.label = '',
  ylab.label = '',
  xlims = c(50,75),
  ylims = c(0,0.015),
  xat = seq(0,150,10),
  yat = seq(0,0.015,0.005),
  xaxis.tck = 0,
  description = 'Image description goes here'
);

write.plot(
  filename = tempfile(pattern = 'write_plot_example', fileext = '.tiff'),
  trellis.object = main.plot,

```

```
additional.trellis.objects = list(secondary.plot),
additional.trellis.locations = list(
    xleft = 0.6,
    ybottom = 0.5,
    xright = 0.97,
    ytop = 0.9
),
resolution = 50 # Lowering resolution decreases file size
);
```

Index

- * **RGB**
 - colour.gradient, 6
 - show.available.palettes, 311
- * **aplot**
 - panel.BL.bwplot, 307
- * **cluster**
 - create.dendrogram, 51
 - create.heatmap, 81
 - dist, 286
- * **colour**
 - colour.gradient, 6
 - default.colours, 283
 - display.colours, 284
 - pcawg.colours, 309
 - show.available.palettes, 311
- * **datasets**
 - CNA, 5
 - microarray, 307
 - patient, 308
 - SNV, 312
- * **dissimilarity**
 - dist, 286
- * **grey**
 - colour.gradient, 6
 - display.colours, 284
 - show.available.palettes, 311
- * **hplot**
 - create.barplot, 11
 - create.boxplot, 35
 - create.densityplot, 53
 - create.dotmap, 63
 - create.heatmap, 81
 - create.hexbinplot, 110
 - create.histogram, 123
 - create.lollipopplot, 130
 - create.manhattanplot, 140
 - create.multipanelplot, 151
 - create.multiplot, 170
 - create.polygonplot, 197
- * **create**
 - qqplot.comparison, 211
 - qqplot.fit, 218
 - scatterplot, 229
 - segplot, 252
 - stripplot, 263
 - violinplot, 272
 - display.statistical.result, 285
- * **htest**
 - get.correlation.p.and.corr, 299
 - ks.test.critical.value, 302
- * **iplot**
 - qqplot.fit.confidence.interval, 227
 - generate.at.final, 296
 - get.defaults, 300
 - scientific.notation, 310
 - write.plot, 315
- * **multivariate**
 - dist, 286
- * **package**
 - BoutrosLab.plotting.general-package, 3
- * **scheme**
 - colour.gradient, 6
 - default.colours, 283
 - display.colours, 284
 - pcawg.colours, 309
 - show.available.palettes, 311
- * **write**
 - write.metadata, 314
- * **xyplot**
 - create.colourkey, 49
 - get.corr.key, 296
- auto.axis, 4
- barchart, 18
- BoutrosLab.plotting.general
 - (BoutrosLab.plotting.general-package), 3

BoutrosLab.plotting.general-package, 3
bwplot, 41, 277

call, 287
CNA, 5
color.gradient (colour.gradient), 6
colour.gradient, 6
covariates.grob, 6, 90
create.barplot, 11
create.boxplot, 35, 308
create.colorkey (create.colourkey), 49
create.colourkey, 49
create.dendrogram, 51, 90
create.densityplot, 53
create.dotmap, 63
create.gif, 79
create.heatmap, 81, 304
create.hexbinplot, 110
create.histogram, 123
create.lollipopplot, 130
create.manhattanplot, 140
create.multipanelplot, 151
create.multiplot, 170
create.polygonplot, 197
create.qqplot.comparison, 211
create.qqplot.fit, 218
create.qqplot.fit.confidence.interval,
 227
create.scatterplot, 229
create.segplot, 252
create.stripplot, 263
create.violinplot, 272

daisy, 288
default.colors (default.colours), 283
default.colours, 283
display.colors (display.colours), 284
display.colours, 284
display.statistical.result, 285
dist, 286, 287
do.call, 116
draw.key, 304

force.color.scheme
 (force.colour.scheme), 289
force.colour.scheme, 289

generate.at.final, 296
get.corr.key, 296

get.correlation.p.and.corr, 299
get.defaults, 300
get.line.breaks, 301
gpar, 8, 304

hclust, 288
histogram, 128

ks.test.critical.value, 302

lattice, 4, 18, 41, 58, 69, 80, 116, 128, 139,
 146, 204, 215, 223, 237, 268, 277

legend.grob, 90, 302
levelplot, 69, 257

match.arg, 287
microarray, 307
missing, 116

panel.BL.bwplot, 307
patient, 308
pcawg.colors (pcawg.colours), 309
pcawg.colours, 309

qq, 215
qqmath, 223

scientific.notation, 310
segplot, 257
show.available.palettes, 311
SNV, 312
stripplot, 4, 80, 268
substitute, 116

thousands.split, 313

write.metadata, 314
write.plot, 315

xyplot, 58, 69, 116, 139, 146, 204, 237