

# Package ‘CINNA’

February 25, 2019

**Title** Deciphering Central Informative Nodes in Network Analysis

**Version** 1.1.53

**Date** 2019-02-25

**Description** Functions for computing, comparing and demonstrating top informative centrality measures within a network.

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 6.1.1

**VignetteBuilder** knitr

**Suggests** knitr, rmarkdown

**Imports** igraph, network, sna, centiserve, FactoMineR, factoextra,  
GGally, pheatmap, corrplot, dendextend, viridis, ggplot2,  
Rtsne, qdapTools, plyr, circlize, intergraph

**NeedsCompilation** no

**Author** Minoo Ashtiani [aut, cre],  
Mehdi Mirzaie [ctb],  
Mohieddin Jafari [ctb]

**Maintainer** Minoo Ashtiani <ashtiani.minoo@gmail.com>

**Repository** CRAN

**Date/Publication** 2019-02-25 12:50:14 UTC

## R topics documented:

calculate_centralities . . . . .	2
cortex . . . . .	7
dangalchev_closeness_centrality . . . . .	7
drugTarget . . . . .	8
giant_component_extract . . . . .	9
graph_extract_components . . . . .	10
group_centrality . . . . .	11

harmonic_centrality . . . . .	12
kangaroo . . . . .	13
local_bridging_centrality . . . . .	14
misc_extract_components . . . . .	15
pca_centralities . . . . .	16
print_calculate_centralities . . . . .	17
print_visualize_association . . . . .	17
print_visualize_correlations . . . . .	18
print_visualize_dendrogram . . . . .	19
print_visualize_graph . . . . .	19
print_visualize_heatmap . . . . .	20
print_visualize_pair_correlation . . . . .	21
proper_centralities . . . . .	21
rhesus . . . . .	22
summary_calculate_centralities . . . . .	23
summary_graph_extract_components . . . . .	23
summary_pca_centralities . . . . .	24
summary_tsne_centralities . . . . .	25
tsne_centralities . . . . .	26
visualize_association . . . . .	27
visualize_correlations . . . . .	28
visualize_dendrogram . . . . .	29
visualize_graph . . . . .	30
visualize_heatmap . . . . .	31
visualize_pair_correlation . . . . .	31
wiener_index_centrality . . . . .	32
zachary . . . . .	33

**Index****34**

---

**calculate\_centralities***Centrality measure calculation*

---

**Description**

This function computes multitude centrality measures of an igraph object.

**Usage**

```
calculate_centralities(x, except = NULL, include = NULL,
                      weights = NULL)
```

## Arguments

x	the component of a network as an igraph object
except	A vector containing names of centrality measures which could be omitted from the calculations.
include	A vector including names of centrality measures which should be computed.
weights	A character scalar specifying the edge attribute to use.(default=NULL)

## Details

This function calculates various types of centrality measures which are applicable to the network topology and returns the results as a list. In "except" argument, you can specify centrality measures which is not necessary to calculate.

## Value

A list concluding centrality measure values in which the columns indicate centralities and the rows show the vertices.

## Author(s)

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

## References

- Bonacich, P., & Lloyd, P. (2001). Eigenvector like measures of centrality for asymmetric relations. *Social Networks*, 23(3), 191–201.
- Bonacich, P. (1972). Factoring and weighting approaches to status scores and clique identification. *The Journal of Mathematical Sociology*, 2(1), 113–120.
- Bonacich, P. (1987). Power and Centrality: A Family of Measures. *American Journal of Sociology*, 92(5), 1170–1182.
- Burt, R. S. (2004). Structural Holes and Good Ideas. *American Journal of Sociology*, 110(2), 349–399.
- Batagelj, V., & Zaversnik, M. (2003). An O(m) Algorithm for Cores Decomposition of Networks, 1–9. Retrieved from
- Seidman, S. B. (1983). Network structure and minimum degree. *Social Networks*, 5(3), 269–287.
- Kleinberg, J. M. (1999). Authoritative sources in a hyperlinked environment. *Journal of the ACM*, 46(5), 604–632.
- Wasserman, S., & Faust, K. (1994). Social network analysis : methods and applications. *American Ethnologist* (Vol. 24).
- Barrat, A., Barthélémy, M., Pastor Satorras, R., & Vespignani, A. (2004). The architecture of complex weighted networks. *Proceedings of the National Academy of Sciences of the United States of America* , 101(11), 3747–3752.
- Brin, S., & Page, L. (2010). The Anatomy of a Large Scale Hypertextual Web Search Engine The Anatomy of a Search Engine. *Search*, 30(June 2000), 1–7.
- Freeman, L. C. (1978). Centrality in social networks conceptual clarification. *Social Networks*, 1(3), 215–239.

- Brandes, U. (2001). A faster algorithm for betweenness centrality\*. *The Journal of Mathematical Sociology*, 25(2), 163–177.
- Estrada E., Rodriguez-Velazquez J. A.: Subgraph centrality in Complex Networks. *Physical Review E* 71, 056103.
- Freeman, L. C., Borgatti, S. P., & White, D. R. (1991). Centrality in valued graphs: A measure of betweenness based on network flow. *Social Networks*, 13(2), 141–154.
- Brandes, U., & Erlebach, T. (Eds.). (2005). *Network Analysis* (Vol. 3418). Berlin, Heidelberg: Springer Berlin Heidelberg.
- Stephenson, K., & Zelen, M. (1989). Rethinking centrality: Methods and examples. *Social Networks*, 11(1), 1–37.
- Wasserman, S., & Faust, K. (1994). Social network analysis : methods and applications. *American Ethnologist* (Vol. 24).
- Brandes, U. (2008). On variants of shortest path betweenness centrality and their generic computation. *Social Networks*, 30(2), 136–145.
- Goh, K.-I., Kahng, B., & Kim, D. (2001). Universal Behavior of Load Distribution in Scale Free Networks. *Physical Review Letters*, 87(27), 278701.
- Shimbel, A. (1953). Structural parameters of communication networks. *The Bulletin of Mathematical Biophysics*, 15(4), 501–507.
- Assenov, Y., Ramrez, F., Schelhorn, S.-E., Lengauer, T., & Albrecht, M. (2008). Computing topological parameters of biological networks. *Bioinformatics*, 24(2), 282–284.
- Diekert, V., & Durand, B. (Eds.). (2005). *STACS 2005* (Vol. 3404). Berlin, Heidelberg: Springer Berlin Heidelberg.
- Gräßler, J., Koschützki, D., & Schreiber, F. (2012). CentiLib: comprehensive analysis and exploration of network centralities. *Bioinformatics* (Oxford, England), 28(8), 1178–9.
- Latora, V., & Marchiori, M. (2001). Efficient Behavior of Small World Networks. *Physical Review Letters*, 87(19), 198701.
- Opsahl, T., Agneessens, F., & Skvoretz, J. (2010). Node centrality in weighted networks: Generalizing degree and shortest paths. *Social Networks*, 32(3), 245–251.
- Estrada, E., Higham, D. J., & Hatano, N. (2009). Communicability betweenness in complex networks. *Physica A: Statistical Mechanics and Its Applications*, 388(5), 764–774.
- Hagberg, Aric, Pieter Swart, and Daniel S Chult. Exploring network structure, dynamics, and function using NetworkX. No. LA-UR-08-05495; LA-UR-08-5495. Los Alamos National Laboratory (LANL), 2008.
- Kalinka, A. T., & Tomancak, P. (2011). linkcomm: an R package for the generation, visualization, and analysis of link communities in networks of arbitrary size and type. *Bioinformatics*, 27(14), 2011–2012.
- Faghani, M. R., & Nguyen, U. T. (2013). A Study of XSS Worm Propagation and Detection Mechanisms in Online Social Networks. *IEEE Transactions on Information Forensics and Security*, 8(11), 1815–1826.
- Brandes, U., & Erlebach, T. (Eds.). (2005). *Network Analysis* (Vol. 3418). Berlin, Heidelberg: Springer Berlin Heidelberg.

- Lin, C.-Y., Chin, C.-H., Wu, H.-H., Chen, S.-H., Ho, C.-W., & Ko, M.-T. (2008). Hubba: hub objects analyzer—a framework of interactome hubs identification for network biology. *Nucleic Acids Research*, 36(Web Server), W438–W443.
- Chin, C., Chen, S., & Wu, H. (2009). cyto Hubba: A Cytoscape Plug in for Hub Object Analysis in Network Biology. *Genome Informatics* . . . , 5(Java 5), 2–3.
- Qi, X., Fuller, E., Wu, Q., Wu, Y., & Zhang, C.-Q. (2012). Laplacian centrality: A new centrality measure for weighted networks. *Information Sciences*, 194, 240–253.
- Joyce, K. E., Laurienti, P. J., Burdette, J. H., & Hayasaka, S. (2010). A New Measure of Centrality for Brain Networks. *PLoS ONE*, 5(8), e12200.
- Lin, C.-Y., Chin, C.-H., Wu, H.-H., Chen, S.-H., Ho, C.-W., & Ko, M.-T. (2008). Hubba: hub objects analyzer—a framework of interactome hubs identification for network biology. *Nucleic Acids Research*, 36(Web Server), W438–W443.
- Hubbell, C. H. (1965). An Input Output Approach to Clique Identification. *Sociometry*, 28(4), 377.
- Dangalchev, C. (2006). Residual closeness in networks. *Physica A: Statistical Mechanics and Its Applications*, 365(2), 556–564.
- Brandes, U. & Erlebach, T. (2005). *Network Analysis: Methodological Foundations*, U.S. Government Printing Office.
- Korn, A., Schubert, A., & Telcs, A. (2009). Lobby index in networks. *Physica A: Statistical Mechanics and Its Applications*, 388(11), 2221–2226.
- White, S., & Smyth, P. (2003). Algorithms for estimating relative importance in networks. In *Proceedings of the ninth ACM SIGKDD international conference on Knowledge discovery and data mining KDD '03* (p. 266). New York, New York, USA: ACM Press.
- Cornish, A. J., & Markowitz, F. (2014). SANTA: Quantifying the Functional Content of Molecular Networks. *PLoS Computational Biology*, 10(9), e1003808.
- Scardoni, G., Petterlini, M., & Laudanna, C. (2009). Analyzing biological network parameters with CentiScaPe. *Bioinformatics*, 25(21), 2857–2859.
- Lin, N. (1976). *Foundations of Social Research*. McGraw Hill.
- Borgatti, S. P., & Everett, M. G. (2006). A Graph theoretic perspective on centrality. *Social Networks*, 28(4), 466–484.
- Newman, M. (2010). *Networks*. Oxford University Press.
- Junker, Bjorn H., Dirk Koschützki, and Falk Schreiber(2006). "Exploration of biological network centralities with CentiBiN." *BMC bioinformatics* 7.1 : 219.
- Pal, S. K., Kundu, S., & Murthy, C. A. (2014). Centrality measures, upper bound, and influence maximization in large scale directed social networks. *Fundamenta Informaticae*, 130(3), 317–342.
- Lin, C.-Y., Chin, C.-H., Wu, H.-H., Chen, S.-H., Ho, C.-W., & Ko, M.-T. (2008). Hubba: hub objects analyzer—a framework of interactome hubs identification for network biology. *Nucleic Acids Research*, 36(Web Server), W438–W443.
- Scardoni, G., Petterlini, M., & Laudanna, C. (2009). Analyzing biological network parameters with CentiScaPe. *Bioinformatics*, 25(21), 2857–2859.
- Freeman, L. C. (1978). Centrality in social networks conceptual clarification. *Social Networks*, 1(3), 215–239.

- Chen, D.-B., Gao, H., L?, L., & Zhou, T. (2013). Identifying Influential Nodes in Large Scale Directed Networks: The Role of Clustering. PLoS ONE, 8(10), e77455.
- Jana Hurajova, S. G. and T. M. (2014). Decay Centrality. In 15th Conference of Kosice Mathematicians. Herlany.
- Viswanath, M. (2009). ONTOLOGY BASED AUTOMATIC TEXT SUMMARIZATION. Vishweshwaraiah Institute of Technology.
- Przulj, N., Wigle, D. A., & Jurisica, I. (2004). Functional topology in a network of protein interactions. Bioinformatics, 20(3), 340–348.
- del Rio, G., Koschützki, D., & Coello, G. (2009). How to identify essential genes from molecular networks BMC Systems Biology, 3(1), 102.
- Scardoni, G. and Carlo Laudanna, C.B.M.C., 2011. Network centralities for Cytoscape. University of Verona.
- BOLDI, P. & VIGNA, S. 2014. Axioms for centrality. Internet Mathematics, 00-00.
- MARCHIORI, M. & LATOURA, V. 2000. Harmony in the small-world. Physica A: Statistical Mechanics and its Applications, 285, 539-546.
- OPSAHL, T., AGNEESSENS, F. & SKVORETZ, J. 2010. Node centrality in weighted networks: Generalizing degree and shortest paths. Social Networks, 32, 245-251.
- OPSAHL, T. 2010. Closeness centrality in networks with disconnected components (<http://toreopsahl.com/2010/03/20/closer-centrality-in-networks-with-disconnected-components/>)
- Michalak, T.P., Aadithya, K.V., Szczepanski, P.L., Ravindran, B. and Jennings, N.R., 2013. Efficient computation of the Shapley value for game-theoretic network centrality. Journal of Artificial Intelligence Research, 46, pp.607-650.
- Macker, J.P., 2016, November. An improved local bridging centrality model for distributed network analytics. In Military Communications Conference, MILCOM 2016-2016 IEEE (pp. 600-605). IEEE. DOI: 10.1109/MILCOM.2016.7795393
- DANGALCHEV, C. 2006. Residual closeness in networks. Physica A: Statistical Mechanics and its Applications, 365, 556-564. DOI: 10.1016/j.physa.2005.12.020
- Alain Barrat, Marc Barthelemy, Romualdo Pastor-Satorras, Alessandro Vespignani: The architecture of complex weighted networks, Proc. Natl. Acad. Sci. USA 101, 3747 (2004)

## See Also

```
alpha.centrality, bonpow, constraint, centr_degree, eccentricity, eigen_centrality,
coreness, authority_score, hub_score, transitivity, page_rank, betweenness, subgraph.centrality,
flowbet, infocent, loadcent, stresscent, graphcent, topocoefficient, closeness.currentflow, closeness.l1,
communibet, communitycent, crossclique, entropy, epc, laplacian, leverage, mnc, hubbell,
semilocal, closeness.vitality, closeness.residual, lobby, markovcent, radiality, lincent,
geokpath, katzcent, diffusion.degree, dmnc, centroid, closeness.freeman, clusterrank, decay,
barycenter, bottleneck, averagedis, local_bridging_centrality, wiener_index_centrality, group_centrality,
dangalchev_closeness_centrality, harmonic_centrality, strength
```

## Examples

```
data("zachary")
```

```
p <- proper_centralities(zachary)
calculate_centralities(zachary, include = "Degree Centrality")
```

---

cortex

*Macaque Visual Cortex Network*

---

## Description

A graph describing the macaque visual cortex network. Nodes are neocortical areas, 25 of them are participated in visual function in the macaque, and 7 of which are associated with them

## Usage

```
data("cortex")
```

## Format

an igraph object with "gml" format

## References

D.J. Felleman and D.C. van Essen, "Distributed hierarchical processing in the primate cerebral cortex." Cerebral Cortex 1(1), 1-47 (1991).

## Examples

```
data("cortex")
print(cortex)
```

---

dangalchev\_closeness\_centrality

*Dangalchev Closeness Centrality*

---

## Description

This function computes Dangalchev Closeness Centrality. This can be access by computing a network resistance. More specifically, it measures the closeness by removing nodes and edges. The evaluation of this measure of closeness will be easier and this can be useful for unconnected graphs too.

## Usage

```
dangalchev_closeness_centrality(x, vids = V(x), mode = c("all", "out",
"in"), weights = NULL)
```

**Arguments**

x	An igraph or a network object
vids	Nodes to be considered in the calculation
mode	A Character value, indicating whether the shortest paths "in" or "out" of the nodes in the directed graphs should be considered. For undirected graphs we use "all".
weights	Numeric vector indicating weights of the edges

**Value**

a vector including centrality values for each node

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

**References**

DANGALCHEV, C. 2006. Residual closeness in networks. *Physica A: Statistical Mechanics and its Applications*, 365, 556-564. DOI: 10.1016/j.physa.2005.12.020

**See Also**

[closeness.residual](#)

**Examples**

```
data(zachary)
dangalchev_closeness_centrality(zachary)
```

*drugTarget*

*Drug Target Network*

**Description**

A bipartite graph extracted from DrugBank 1.0 database. The network includes two set of nodes including Food and Drug Administration (FDA)-approved drugs and their corresponding protein targets designated by their Uniprot ID. The 1080 drugs and their 519 target proteins nodes are connected via 3766 interactions. Please note that it is a shrunken network in which metabolizing enzymes, carriers and transporters associated with drug metabolism are filtered and solely targets directly related to their pharmacological effects are included. It is also an example of unconnected graphs.

**Usage**

```
drugTarget
```

**Format**

an igraph object with "gml" format

**References**

Barneh, F., Jafari, M., & Mirzaie, M. (2015). Updates on drug–target network; facilitating polypharmacology and data integration by growth of DrugBank database. *Briefings in Bioinformatics*, bbv094. <https://doi.org/10.1093/bib/bbv094>

**Examples**

```
data("drugTarget")
print(drugTarget)
```

---

```
giant_component_extract
```

*Giant component extraction of a graph*

---

**Description**

This function extracts the largest connected or the giant component of the input graph which can be an "igraph" object or a "network" object and convert them as "igraph" objects. For the bipartite graph, this will apply projection before extracting the components.

**Usage**

```
giant_component_extract(x, directed = TRUE, bipartite_proj = FALSE,
                        num_proj = 1)
```

**Arguments**

x	An igraph or a network object
directed	Whether to create a directed graph(default=TRUE)
bipartite_proj	Whether the bipartite network must be projected or not(default=FALSE)
num_proj	A number which shows the number of projects especifically for bipartite graphs.(default=1)

**Details**

This function distinguishes the largest component of an "igraph" or a "network" object and illustrates them as a list which contains the edgelist of the giant component. If the input graph was bipartite and the "bipartite\_proj" was TRUE, it will project it and you can decide to which project you want to continue to work with that.

**Value**

a list containing the giant component of the input graph. The first element is an igraph object and the second is the edgelist of that.

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

**References**

Newman, M. (2010). Networks. Oxford University Press.

**See Also**

[induced.subgraph](#),[clusters](#)

**Examples**

```
# a graph with 4 vertices
data(zachary)
giant_component_extract(zachary)
```

**graph\_extract\_components**

*Component extraction of a graph*

**Description**

This function extracts all connected components of the input which can be an "igraph" object or a "network" object and convert them as "igraph" objects.

**Usage**

```
graph_extract_components(x, directed = TRUE, bipartite_proj = FALSE,
                        num_proj = 1)
```

**Arguments**

- x An igraph or a network object
- directed Whether to create a directed graph(default=TRUE)
- bipartite\_proj Whether the bipartite network must be projected or not(default=FALSE)
- num\_proj Numbers 1 or 2 which shows the number of projects for bipartite graphs.(default=1)

**Details**

This function separates different components of an "igraph" or a "network" object and illustrates them as a list of independent graphs. If the input graph was bipartite and the "bipartite\_proj" was TRUE, it will project it and you can decide in which project you want to continue to work with.

**Value**

a list including the components of the input as igraph objects

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

**See Also**

[induced.subgraph](#), [components](#)

**Examples**

```
data(zachary)
graph_extract_components(zachary)
```

---

group\_centrality      *Group Centrality*

---

**Description**

This function computes group Centrality. So, it considers a consistent ranking of each node to be calculated such that scores diverse possible synergies among possible groups of vertices.

**Usage**

```
group_centrality(x, vids = V(x))
```

**Arguments**

x	An igraph or a network object
vids	Nodes to be considered in the calculation

**Value**

a vector including centrality values for each node

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

**References**

Michalak, T.P., Aadithya, K.V., Szczepanski, P.L., Ravindran, B. and Jennings, N.R., 2013. Efficient computation of the Shapley value for game-theoretic network centrality. Journal of Artificial Intelligence Research, 46, pp.607-650.

[https://www.civilica.com/Paper-IBIS07-IBIS07\\_127.html](https://www.civilica.com/Paper-IBIS07-IBIS07_127.html)

**Examples**

```
data(zachary)
group_centrality(zachary)
```

**harmonic\_centrality**     *Harmonic Centrality*

**Description**

This function computes Harmonic Centrality. The harmonic metric defines as the denormalized reciprocal of the harmonic mean of all distances.

**Usage**

```
harmonic_centrality(x, vids = V(x), mode = c("all", "out", "in"),
weights = NULL)
```

**Arguments**

x	An igraph or a network object
vids	Nodes to be considered in the calculation
mode	a character value, “out” for out-degree, “in” for in-degree or “total” for the sum of the two. For undirected graphs this argument is ignored. “all” is a synonym of “total”.
weights	Numeric vector indicating weights of the edges

**Value**

a vector including centrality values for each node

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

## References

- BOLDI, P. & VIGNA, S. 2014. Axioms for centrality. *Internet Mathematics*, 00-00.
- MARCHIORI, M. & LATOURA, V. 2000. Harmony in the small-world. *Physica A: Statistical Mechanics and its Applications*, 285, 539-546.
- OPSAHL, T., AGNEESSENS, F. & SKVORETZ, J. 2010. Node centrality in weighted networks: Generalizing degree and shortest paths. *Social Networks*, 32, 245-251.
- OPSAHL, T. 2010. Closeness centrality in networks with disconnected components (<http://toreopsahl.com/2010/03/20/closer-centrality-in-networks-with-disconnected-components/>)

## Examples

```
data(zachary)
harmonic_centrality(zachary)
```

kangaroo

*Kangaroo Network*

## Description

An undirected graph based on interactions between free-ranging grey kangaroos. A node displays a kangaroo and an edge between two kangaroos demonstrates an interaction. The weights indicate the total count of interactions.

## Usage

```
kangaroo
```

## Format

an igraph object with "gml" format

## References

- Kangaroo network dataset – KONECT, October 2016.
- TR Grant. Dominance and association among members of a captive and a free-ranging group of grey kangaroos (*Macropus giganteus*). *Animal Behaviour*, 21(3):449–456, 1973.

## Examples

```
data("kangaroo")
print(kangaroo)
```

---

**local\_bridging\_centrality**  
*Local Bridging Centrality*

---

## Description

This function computes Local Bridging Centrality. This classifies nodes regarding their structural links among the dense components.

## Usage

```
local_bridging_centrality(x, vids = V(x))
```

## Arguments

x	An igraph or a network object
vids	Nodes to be considered in the calculation

## Value

a vector including centrality values for each node

## Author(s)

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

## References

Macker, J.P., 2016, November. An improved local bridging centrality model for distributed network analytics. In Military Communications Conference, MILCOM 2016-2016 IEEE (pp. 600-605). IEEE. DOI: 10.1109/MILCOM.2016.7795393

## See Also

[betweenness](#)

## Examples

```
data(zachary)
local_bridging_centrality(zachary)
```

---

**misc\_extract\_components**

*Component extraction of miscellaneous graph formats*

---

**Description**

This function extracts all components of the input with various formats and convert them as "igraph" objects.

**Usage**

```
misc_extract_components(x, directed = TRUE, mode = "directed",
weighted = NULL, unibipartite = FALSE, diag = TRUE)
```

**Arguments**

x	The input could be an edgelist and an adjacency matrix
directed	Whether to create a directed graph.(default=TRUE)
mode	Character scalar, explain how should demonstrate the supplied matrix. Possible values are: directed, undirected, upper, lower, max, min, plus.(default="directed")
weighted	An argument for specifying whether the graph should be weighted or not. If it is NULL then an unweighted graph is created.(default=NULL)
unibipartite	A boolean parameter describing whether the input edge list is corresponding to a bipartite graph. TRUE value specifies the bipartite graph and vice versa.(default=FALSE)
diag	Logical scalar, whether to consider the diagonal of the matrix or not. If it was FALSE then the diagonal spotted as zeros.(default=TRUE)

**Details**

This function assert components of the input object which can be an edgelist, an adjacency matrix and a graphNEL object. The result would be a list including components as separated graphs.

**Value**

a list including the components of the input graph as igraph objects

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

**See Also**

[induced.subgraph](#), [components](#), [graph\\_from\\_adjacency\\_matrix](#)

**pca\_centralities**      *Ranking centrality measure based on contributions*

## Description

This function demonstrates ranks of centrality measures in order of information levels.

## Usage

```
pca_centralities(x, scale.unit = TRUE, cut.off = 80, ncp = 5,
graph = FALSE, axes = c(1, 2))
```

## Arguments

x	a list containing the computed centrality values
scale.unit	a boolean constant, whether data should be scaled to unit variance(default=TRUE)
cut.off	The intensity that must be exceeded in cumulative percentage of variance of eigen values.(default=80)
ncp	number of dimensions in final results (default=5)
graph	a boolean constant, whether the graph should be displayed
axes	a length 2 vector describing the number of components to plot(default=c(1,2))

## Details

This function represents centralities in the ranking list based on variable contribution to make principal components. PCA is a method for drawing out important variables from a data set. It helps user to reduced the dimensions in high dimensional data. It is more common to use for more than 3 dimensional datasets.

## Value

a plot illustrating significant centralities in the order of contribution

## Author(s)

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

## References

- Husson, F., Lê, S., & Pagès, J. (2010). Exploratory Multivariate Analysis by Example using R. Chapman & Hall/CRC Computer Science & Data Analysis, 40(April), 240.  
<http://www.sthda.com/english/>

## See Also

[PCA](#)

---

**print\_calculate\_centralities**

*Print computed centrality measures results into a file*

---

**Description**

This function prints all centrality measure results into a file

**Usage**

```
print_calculate_centralities(x, file = NULL)
```

**Arguments**

- |      |  |
|------|--|
| x    | a list containing the centrality measure values  |
| file | A character string naming the .pdf file to print into. If NULL the result would be printed to the exist directory.(default=NULL) |

**Value**

Print out `calculate_centralities`function will be saved in the given directory.

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

---

**print\_visualize\_association**

*Print pairwise association plot among centrality measures into a file*

---

**Description**

This function prints regression plot between pair of centrality measures

**Usage**

```
print_visualize_association(x, y, scale = TRUE, file = NULL)
```

**Arguments**

- |       |  |
|-------|--|
| x     | a vector containing a centrality values as independent variable  |
| y     | a vector containing a centrality values as dependent variable  |
| scale | Whether the centrality values should be scaled or not(default=TRUE)  |
| file  | A character string naming the file to print into. If NULL the result would be printed to the exist directory(default=NULL) |

**Value**

The resulted plot of `visualize_association` function will be saved in the given directory.

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

`print_visualize_correlations`  
*Print centrality correlation plot*

**Description**

This function prints a plot including all pairwise correlation between centrality measures

**Usage**

```
print_visualize_correlations(x, scale = TRUE, method = c("pearson",
  "kendall", "spearman"), file = NULL)
```

**Arguments**

- x a list indicating calculated centrality measures which is the output of "calculate\_centralities" function
- scale Whether the centrality values should be scaled or not(default=TRUE)
- method character string describing the type of correlation coefficient (or covariance) to be computed. The proper values are "pearson", "kendall", or "spearman". (default="pearson")
- file A character string naming the .pdf file to print into. If NULL the result would be printed to the exist directory.(default=NULL)

**Value**

The resulted plot of `visualize_correlations` function will be saved in the given directory.#' @importFrom igraph alpha.centrality

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

---

**print\_visualize\_dendrogram***Print dendrogram plot of a graph*

---

**Description**

This function prints dendrogram plot of a graph based on predefined centrality measures.

**Usage**

```
print_visualize_dendrogram(x, centrality.type = "Degree Centrality",
                           computed_centrality_value = NULL, k = 4, file = NULL)
```

**Arguments**

x	an igraph object
centrality.type	The type of centrality which should be calculated(default="Degree Centrality")
computed_centrality_value	A vector containing the values of calculated centrality measure for each node(default=NULL)
k	number of clusters
file	A character string naming the .pdf file to print into. If NULL the result would be printed to the exist directory.(default=NULL)

**Value**

The resulted plot of [visualize\\_dendrogram](#)function will be saved in the given directory.#' @importFrom igraph alpha.centrality

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

---

**print\_visualize\_graph** *Print visualized based on centrality values graph*

---

**Description**

This function prints visualized based on centrality values graph.

**Usage**

```
print_visualize_graph(x, computed_centrality_value = NULL,
                      centrality.type = "Degree Centrality", file = NULL)
```

**Arguments**

- x an igraph object
- computed\_centrality\_value A vector containing the values of calculated centrality measure for each node(default=NULL)
- centrality.type The type of centrality which should be calculated(default="Degree Centrality")
- file A character string naming the .pdf file to print into. If NULL the result would be printed to the exist directory.(default=NULL)

**Value**

The resulted plot of `visualize_graph`function will be saved in the given directory.#' @importFrom igraph alpha.centrality

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

`print_visualize_heatmap`

*Print the heatmap plot of centrality measures*

**Description**

This function prints the heatmap plot

**Usage**

```
print_visualize_heatmap(x, scale = TRUE, file = NULL)
```

**Arguments**

- x a list indicating calculated centrality measures
- scale Whether the centrality values should be scaled or not(default=TRUE)
- file A character string naming the .pdf file to print into. If NULL the result would be printed to the exist directory.(default=NULL)

**Value**

The resulted plot of `visualize_heatmap`function will be saved in the given directory.

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

---

**print\_visualize\_pair\_correlation**

*Print pairwise correlation and histogram plots between two centrality measures*

---

**Description**

This function prints pairwise correlation of centrality measures and histogram plot.

**Usage**

```
print_visualize_pair_correlation(x, y, scale = TRUE, file = NULL)
```

**Arguments**

x	a vector containing a centrality measure
y	a vector containing another centrality measure
scale	Whether the centrality values should be scaled or not(default=TRUE)
file	A character string naming the .pdf file to print into. If NULL the result would be printed to the exist directory.

**Value**

The resulted plot of [visualize\\_pair\\_correlation](#)function will be saved in the given directory.

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

---

**proper\_centralities**      *Proper centrality measure representation*

---

**Description**

This function indicates proper centrality measures of an igraph object based on the network topology

**Usage**

```
proper_centralities(x)
```

**Arguments**

x	an igraph object
---	------------------

## Details

This function represents a list including the names of centrality measures which are applicable for the input graph based on the topology

## Value

a list including the name of centrality measures which are suitable for the input graph

## Author(s)

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

## See Also

[calculate\\_centralities](#)

## Examples

```
data("zachary")
proper_centralities(zachary)
```

*rhesus*

*Moreno Rhesus Network*

## Description

A directed graph including observed grooming episodes between free ranging rhesus macaques (*Macaca mulatta*) in Cayo Santiago during a two month period in 1963. Cayo Santiago is an island off the coast of Puerto Rico, which also is named as Isla de los monos (Island of the monkeys). A node indicates a monkey and a directed edge in which a rhesus macaque groomed another rhesus macaque. The weights of edges demonstrates how often this behaviour was seen.

## Usage

*rhesus*

## Format

an igraph object with "gml" format

## References

Rhesus network dataset – KONECT, October 2016.

DS Sade. Sociometrics of *macaca mulatta* I. linkages and cliques in grooming matrices. *Folia Primatologica*, 18(3-4):196–223, 1972.

## Examples

```
data("rhesus")
print(rhesus)
```

**summary\_calculate\_centralities**  
*Summarize centrality measure calculation results*

## Description

This function computes minimum, first quartile, median, mean, third quartile and maximum values of computed centrality measures.

## Usage

```
summary_calculate_centralities(x)
```

## Arguments

## x centrality measure calculation results

## Value

a list concluding summary results for each centrality measure value

The result values of `calculate_centralities` function will be saved in the given directory.#' @importFrom igraph alpha.centrality

## Author(s)

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

`summary_graph_extract_components`  
*Summarize component extraction of a graph*

## Description

This function summarizes all components of the input which can be an "igraph" object or a "network" object

## Usage

```
summary_graph_extract_components(x, directed = TRUE,  
    bipartite_proj = FALSE, num_proj = 1)
```

**Arguments**

- x An igraph or a network object
- directed a boolean constant, Whether to create a directed graph(default=TRUE)
- bipartite\_proj Whether the bipartite network must be projected or not(default=FALSE)
- num\_proj A number which shows the number of projects especifically for bipartite graphs.(default=1)

**Value**

The result values of `graph_extract_components`function will be saved in the given directory.  
 #' @importFrom igraph alpha.centrality

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

**summary\_pca\_centralities**

*Summarize PCA result related to centrality measures*

**Description**

This function summarizes PCA result related to centrality measures.

**Usage**

```
summary_pca_centralities(x, scale.unit = TRUE, ncp = 5)
```

**Arguments**

- x a list containg the computed centrality values
- scale.unit a boolean constant, whether data should be scaled to unit variance(default=TRUE)
- ncp number of dimensions in final results (default=5)

**Value**

The result values of `pca_centralities`function will be saved in the given directory.  
 #' @importFrom igraph alpha.centrality

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

---

**summary\_tsne\_centralities**

*Summarize t-Distributed Stochastic Neighbor Embedding (t-SNE) on centrality measures*

---

**Description**

This function summarize tsne analysis results on centrality measures

**Usage**

```
summary_tsne_centralities(x, dims = 2, perplexity = 5, scale = TRUE)
```

**Arguments**

x	a list containg the computed cetrality values
dims	integer; number of the outpu dimensions(default=2)
perplexity	numeric; A flexible measure of the efficient number of neighbors. The performance of SNE is fairly robust to changes in the perplexity, and typical values are between 5 and 50.(default=5)
scale	Whether the centrality values should be scaled or not(default=TRUE)

**Value**

It resturns a list containing below values:

Y Matrix containing the new representations for the objects

costs The cost for every object after the final iteration

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

**See Also**

[Rtsne](#)

---

tsne_centralities	<i>t-Distributed Stochastic Neighbor Embedding (t-SNE) on centrality measures</i>
-------------------	---

---

## Description

This function applies t-SNE, dimensionality reduction algorithm, on centrality measures.

## Usage

```
tsne_centralities(x, dims = 2, perplexity = 5, scale = TRUE)
```

## Arguments

x	a list containing the computed centrality values
dims	integer; number of the output dimensions(default=2)
perplexity	numeric; A flexible measure of the efficient number of neighbors. The performance of SNE is fairly robust to changes in the perplexity, and typical values are between 5 and 50.(default=5)
scale	Whether the centrality values should be scaled or not(default=TRUE)

## Details

t-SNE is a non-linear dimensionality reduction algorithm used for exploring high-dimensional data. Here, It maps multi-dimensional centrality measure data to less dimensions suitable to work with it.

## Value

It returns cost plot of tsne results which displays centralities in order of their corresponding costs.

## Author(s)

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

## References

van der Maaten, L. (2014). Accelerating t-SNE using Tree Based Algorithms. *Journal of Machine Learning Research*, 15, 3221–3245. Van Der Maaten, L. J. P., & Hinton, G. E. (2008). Visualizing high dimensional data using t-SNE. *Journal of Machine Learning Research*, 9, 2579–2605.

## See Also

[Rtsne](#)

---

visualize\_association *Pairwise association plot between centrality measures*

---

## Description

This function computes regression between pair of centrality measures to show more details of association among them.

## Usage

```
visualize_association(x, y, scale = TRUE)
```

## Arguments

x	a vector containing a centrality measure as independent variable
y	a vector containing a centrality measure as dependent variable
scale	Whether the centrality values should be scaled or not

## Details

This function applies regression analysis on two different centrality values in order to find out the corresponding association between them. Regression analysis is a kind of statistical method for approximation the association between variables. It asserts that the value of dependent variable changes when the value of independent variable varies.

## Value

The regression plot, and the values resulted by the regression process.

## Author(s)

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

## References

- CHAMBERS, & M., J. (1992). Statistical Models in S. Wadsworth. Pacific Grove, California.  
Retrieved from  
Wilkinson, G. N., & Rogers, C. E. (1973). Symbolic Description of Factorial Models for Analysis of Variance. Applied Statistics, 22(3), 392.

**visualize\_correlations***Correlation plot between centrality measures*

---

**Description**

This function draw correlation plot between pair of centrality measures

**Usage**

```
visualize_correlations(x, scale = TRUE, method = "pearson")
```

**Arguments**

- |        |  |
|--------|--|
| x      | a list indicating calculated centrality measures   |
| scale  | Whether the centrality values should be scaled or not(default=TRUE)  |
| method | a character string describing the type of correlation coefficient (or covariance) to be computed. The proper values are "pearson", "kendall", or "spearman". (default="pearson") |

**Details**

This function illustrates pairwise correlation plot of computed centrality measures. The names of centralities shown in the result plot is abbreviated and complete names can be seen in "proper\_centralities" function. Colors from red to blue indicate the intensity of correlation value. If two centrality measures have an inverse relationship then their corresponding color in plot have to be red and vice versa.

**Value**

The pairwise correlation plot

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

**See Also**

[ggpairs](#)

---

visualize\_dendrogram *Dendrogram plot among centrality measures*

---

## Description

This function demonstrates the vertex dendrogram of a graph based on a centrality type.

## Usage

```
visualize_dendrogram(x, centrality.type = "Degree Centrality",
computed_centrality_value = NULL, k = 4)
```

## Arguments

x	an igraph object
centrality.type	The type of centrality which should be considered.(default="Degree Centrality")
computed_centrality_value	A vector containing the values of calculated centrality measure for each node.(default=NULL)
k	number of clusters(default=4)

## Details

This function represents node dendrogram of a graph based on a centrality measure. If the favor centrality is not computed yet, by specifying the name of that it will compute it and show the result.

## Author(s)

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

## References

Galili, T. (2015). dendextend: an R package for visualizing, adjusting and comparing trees of hierarchical clustering. *Bioinformatics*, 31(22), 3718–3720.

## See Also

[dendrogram](#)

---

**visualize\_graph***Graph visualization based on a specific centrality measure*

---

**Description**

This function demonstrates the input graph in which the size of nodes indicates calculated centrality value.

**Usage**

```
visualize_graph(x, computed_centrality_value = NULL,  
centrality.type = "Degree Centrality")
```

**Arguments**

**x** an igraph object  
**computed\_centrality\_value** A vector containing the values of calculated centrality measure for each node.  
**centrality.type** The type of centrality which should be calculated.

**Details**

This function represents the graph in which size of nodes are based on computed centrality value. If the values of wanted centrality measure were computed then by placing them in `computed_centrality_value` argument to use it for drawing the plot. Otherwise, by only giving the name of favorite centrality measure in `centrality.type` argument, this function will calculate it and then demonstrates the corresponding graph.

**Value**

a plot illustrating the graph

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

---

```
visualize_heatmap      Heatmap plot between centrality measures
```

---

### Description

This function draws heatmap between pair of centrality measures

### Usage

```
visualize_heatmap(x, scale = TRUE)
```

### Arguments

- |       |   |
|-------|---|
| x     | a list indicating calculated centrality measures      |
| scale | Whether the centrality values should be scaled or not |

### Details

This function illustrates the heatmap plot of computed centrality measures.

### Value

The correlation plot

### Author(s)

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

---

```
visualize_pair_correlation
```

*Pairwise correlation plot between two centrality measures*

---

### Description

This function computes and plots correlation between pair of centrality measures and histogram plots.

### Usage

```
visualize_pair_correlation(x, y, scale = TRUE)
```

### Arguments

- |       |   |
|-------|---|
| x     | a vector containing a centrality measure              |
| y     | a vector containing another centrality measure        |
| scale | Whether the centrality values should be scaled or not |

## Details

This function illustrates the correlation value between two centrality measures and their corresponding scatterplot and histograms.

## Value

The correlation plot

## Author(s)

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

## References

Emerson, J. W., Green, W. A., Schloerke, B., Crowley, J., Cook, D., Hofmann, H., & Wickham, H. (2013). The Generalized Pairs Plot. *Journal of Computational and Graphical Statistics*, 22(1), 79–91.

## See Also

[ggpairs](#)

*wiener\_index\_centrality*

*Wiener Index Centrality*

## Description

This function computes Wiener Index Centrality. The Wiener index computes the sum of the all shortest paths between a node v and all other related nodes in the graph. Fundementally, it's like to the closeness but here since the reciprocal is not computed, the value has the opposite meaning.

## Usage

```
wiener_index_centrality(x, vids = V(x), mode = c("all", "out", "in"),
weights = NULL)
```

## Arguments

<code>x</code>	An igraph or a network object
<code>vids</code>	Nodes to be considered in the calculation
<code>mode</code>	A Character value, indicating whether the shortest paths "in" or "out" of the nodes in the directed graphs should be considered. For undirected graphs we use "all".
<code>weights</code>	Numeric vector indicating weights of the edges

**Value**

a vector including centrality values for each node

**Author(s)**

Minoo Ashtiani, Mehdi Mirzaie, Mohieddin Jafari

**References**

Scardoni, G. and Carlo Laudanna, C.B.M.C., 2011. Network centralities for Cytoscape. University of Verona.

**Examples**

```
data(zachary)  
wiener_index_centrality(zachary)
```

---

zachary

*Zachary Karate Club Network*

---

**Description**

A graph describing friendships among members of a university karate club. Includes metadata for faction membership after a social partition.

**Usage**

zachary

**Format**

an igraph object with "gml" format

**References**

W. W. Zachary, "An information flow model for conflict and fission in small groups." Journal of Anthropological Research 33, 452-473 (1977).

**Examples**

```
data("zachary")  
print(zachary)
```

# Index

\*Topic **datasets**  
    cortex, 7  
    drugTarget, 8  
    kangaroo, 13  
    rhesus, 22  
    zachary, 33

alpha.centrality, 6  
authority\_score, 6  
averagedis, 6

barycenter, 6  
betweenness, 6, 14  
bonpow, 6  
bottleneck, 6

calculate\_centralities, 2, 17, 22, 23  
centr\_degree, 6  
centroid, 6  
closeness.currentflow, 6  
closeness.freeman, 6  
closeness.latora, 6  
closeness.residual, 6, 8  
closeness.vitality, 6  
clusterrank, 6  
clusters, 10  
communibet, 6  
communitycent, 6  
components, 11, 15  
constraint, 6  
coreness, 6  
cortex, 7  
crossclique, 6

dangalchev\_closeness\_centrality, 6, 7  
decay, 6  
dendrogram, 29  
diffusion.degree, 6  
dmnc, 6  
drugTarget, 8

eccentricity, 6  
eigen\_centrality, 6  
entropy, 6  
epc, 6

flowbet, 6

geokpath, 6  
ggpairs, 28, 32  
giant\_component\_extract, 9  
graph\_extract\_components, 10, 24  
graph\_from\_adjacency\_matrix, 15  
graphcent, 6  
group\_centrality, 6, 11

harmonic\_centrality, 6, 12  
hub\_score, 6  
hubbell, 6

induced.subgraph, 10, 11, 15  
infocent, 6

kangaroo, 13  
katzcent, 6

laplacian, 6  
leverage, 6  
lincent, 6  
loadcent, 6  
lobby, 6  
local\_bridging\_centrality, 6, 14

markovcent, 6  
misc\_extract\_components, 15  
mnc, 6

page\_rank, 6  
PCA, 16  
pca\_centralities, 16, 24  
print\_calculate\_centralities, 17  
print\_visualize\_association, 17

print\_visualize\_correlations, 18  
print\_visualize\_dendrogram, 19  
print\_visualize\_graph, 19  
print\_visualize\_heatmap, 20  
print\_visualize\_pair\_correlation, 21  
proper\_centralities, 21  
  
radiality, 6  
rhesus, 22  
Rtsne, 25, 26  
  
semilocal, 6  
strength, 6  
stresscent, 6  
subgraph.centrality, 6  
summary\_calculate\_centralities, 23  
summary\_graph\_extract\_components, 23  
summary\_pca\_centralities, 24  
summary\_tsne\_centralities, 25  
  
topocoefficient, 6  
transitivity, 6  
tsne\_centralities, 26  
  
visualize\_association, 18, 27  
visualize\_correlations, 18, 28  
visualize\_dendrogram, 19, 29  
visualize\_graph, 20, 30  
visualize\_heatmap, 20, 31  
visualize\_pair\_correlation, 21, 31  
  
wiener\_index\_centrality, 6, 32  
  
zachary, 33