

# Package ‘Carlson’

March 4, 2020

**Type** Package

**Title** Carlson Elliptic Integrals and Incomplete Elliptic Integrals

**Version** 1.0.0

**Date** 2020-02-26

**Author** Stéphane Laurent

**Maintainer** Stéphane Laurent <laurent\_step@outlook.fr>

**Description** Evaluation of the Carlson elliptic integrals and the incomplete elliptic integrals with complex arguments. The implementations use Carlson's algorithms <[doi.org/10.1007/BF02198293](https://doi.org/10.1007/BF02198293)>. Applications of elliptic integrals include probability distributions, geometry, physics, mechanics, electrodynamics, statistical mechanics, astronomy, geodesy, geodesics on conics, and magnetic field calculations.

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**RxygenNote** 7.0.2

**Suggests** gsl, testthat

**URL** <https://github.com/stla/Carlson>

**BugReports** <https://github.com/stla/Carlson/issues>

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2020-03-04 14:50:02 UTC

## R topics documented:

Carlson_RC . . . . .	2
Carlson_RD . . . . .	3
Carlson_RF . . . . .	3
Carlson_RG . . . . .	4
Carlson_RJ . . . . .	4
elliptic_E . . . . .	5

<i>elliptic_F</i>	6
<i>elliptic_PI</i>	6
<i>elliptic_Z</i>	7

**Index**

8

**Carlson\_RC***Carlson elliptic integral RC***Description**

Evaluate the Carlson elliptic integral  $R_C$ .

**Usage**

```
Carlson_RC(x, y, minerror = 2 * .Machine$double.eps)
```

**Arguments**

x, y	real or complex numbers, with y different from 0
minerror	bound on the relative error passed to <a href="#">Carlson_RF</a>

**Value**

A complex number, the value of the Carlson elliptic integral  $R_C(x, y)$ .

**Note**

The function returns a value when x or y are negative real numbers, but this value is not the one of the Carlson integral.

**Examples**

```
Carlson_RC(5, 2)
gsl::ellint_RC(5, 2)
```

---

Carlson\_RD

*Carlson elliptic integral RD*

---

### Description

Evaluate the Carlson elliptic integral RD.

### Usage

```
Carlson_RD(x, y, z, minerror = 2 * .Machine$double.eps)
```

### Arguments

x, y, z	real or complex numbers; at most one can be 0
minerror	bound on the relative error

### Value

A complex number, the value of the Carlson elliptic integral  $R_D(x, y, z)$ .

### Note

The function returns a value when x, y or z are negative real numbers, but this value is not the one of the Carlson integral.

### Examples

```
Carlson_RD(5, 2, 3)  
gsl::ellint_RD(5, 2, 3)
```

---

Carlson\_RF

*Carlson elliptic integral RF*

---

### Description

Evaluate the Carlson elliptic integral RF.

### Usage

```
Carlson_RF(x, y, z, minerror = 2 * .Machine$double.eps)
```

### Arguments

x, y, z	real or complex numbers; at most one can be 0
minerror	bound on relative error

**Value**

A complex number, the value of the Carlson elliptic integral  $R_F(x, y, z)$ .

**Note**

The function returns a value when  $x, y$  or  $z$  are negative real numbers, but this value is not the one of the Carlson integral.

**Examples**

```
Carlson_RF(5, 2, 3)
gsl::ellint_RF(5, 2, 3)
```

Carlson\_RG

*Carlson elliptic integral RG***Description**

Evaluate the Carlson elliptic integral RG.

**Usage**

```
Carlson_RG(x, y, z, minerror = 2 * .Machine$double.eps)
```

**Arguments**

$x, y, z$	real or complex numbers; they can be zero
minerror	bound on the relative error passed to <a href="#">Carlson_RF</a> and <a href="#">Carlson_RD</a>

**Value**

A complex number, the value of the Carlson elliptic integral  $R_G(x, y, z)$ .

Carlson\_RJ

*Carlson elliptic integral RJ***Description**

Evaluate the Carlson elliptic integral RJ.

**Usage**

```
Carlson_RJ(x, y, z, p, minerror = 2 * .Machine$double.eps)
```

**Arguments**

<code>x, y, z, p</code>	real or complex numbers; at most one can be 0
<code>minerror</code>	bound on the relative error

**Value**

A complex number, the value of the Carlson elliptic integral  $R_J(x, y, z, t)$ .

**Note**

The function returns a value when `x, y, z` or `p` are negative real numbers, but this value is not the one of the Carlson integral.

**Examples**

```
Carlson_RJ(5, 2, 3, 4)
gsl::ellint_RJ(5, 2, 3, 4)
```

**elliptic\_E**

*Incomplete elliptic integral of the second kind*

**Description**

Evaluate the incomplete elliptic integral of the second kind.

**Usage**

```
elliptic_E(phi, m, minerror = 2 * .Machine$double.eps)
```

**Arguments**

<code>phi</code>	amplitude, real or complex number
<code>m</code>	parameter, real or complex number
<code>minerror</code>	the bound on the relative error passed to <a href="#">Carlson_RF</a> and <a href="#">Carlson_RD</a>

**Value**

A complex number, the value of the incomplete elliptic integral  $E(\phi, m)$ .

**Examples**

```
elliptic_E(1, 0.2)
gsl::ellint_E(1, sqrt(0.2))
```

**elliptic\_F***Incomplete elliptic integral of the first kind***Description**

Evaluate the incomplete elliptic integral of the first kind.

**Usage**

```
elliptic_F(phi, m, minerror = 2 * .Machine$double.eps)
```

**Arguments**

phi	amplitude, real or complex number
m	parameter, real or complex number
minerror	the bound on the relative error passed to <a href="#">Carlson_RF</a>

**Value**

A complex number, the value of the incomplete elliptic integral  $F(\phi, m)$ .

**Examples**

```
elliptic_F(1, 0.2)
gsl::ellint_F(1, sqrt(0.2))
```

**elliptic\_PI***Incomplete elliptic integral of the third kind***Description**

Evaluate the incomplete elliptic integral of the third kind.

**Usage**

```
elliptic_PI(phi, n, m, minerror = 2 * .Machine$double.eps)
```

**Arguments**

phi	amplitude, real or complex number
n	characteristic, real or complex number
m	parameter, real or complex number
minerror	the bound on the relative error passed to <a href="#">Carlson_RF</a> and <a href="#">Carlson_RJ</a>

**Value**

A complex number, the value of the incomplete elliptic integral  $\Pi(\phi, n, m)$ .

**Examples**

```
elliptic_PI(1, 0.8, 0.2)
gsl::ellint_P(1, sqrt(0.2), -0.8)
```

---

*elliptic\_Z**Jacobi zeta function*

---

**Description**

Evaluate the Jacobi zeta function.

**Usage**

```
elliptic_Z(phi, m, minerror = 2 * .Machine$double.eps)
```

**Arguments**

phi	amplitude, real or complex number
m	parameter, real or complex number
minerror	bound on relative error passed to <a href="#">elliptic_E</a> and <a href="#">elliptic_F</a>

**Value**

A complex number, the value of the Jacobi zeta function  $Z(\phi, m)$ .

# Index

Carlson\_RC, 2  
Carlson\_RD, 3, 4, 5  
Carlson\_RF, 2, 3, 4–6  
Carlson\_RG, 4  
Carlson\_RJ, 4, 6  
  
elliptic\_E, 5, 7  
elliptic\_F, 6, 7  
elliptic\_PI, 6  
elliptic\_Z, 7