

Package ‘ES’

February 19, 2015

Type Package

Title Edge Selection

Version 1.0

Date 2013-06-13

Author Meng Hwee Victor Ong, Sanjay Chaudhuri

Maintainer Meng Hwee Victor Ong<g0900757@nus.edu.sg>

Description Implementation of the Edge Selection Algorithm

License GPL-2

NeedsCompilation no

Repository CRAN

Date/Publication 2013-08-13 08:06:43

R topics documented:

ES-package	1
cv.ES	2
ES	3
ESpredict	4
marks	5

Index

6

ES-package

Edge Selection for Undirected Graphs

Description

Implementation of the Edge Selection Algorithm

Details

Package: ESpackage
 Type: Package
 Version: 1.0
 Date: 2013-06-13
 License: CRAN

Author(s)

Meng Hwee Victor Ong, Sanjay Chaudhuri

References

Edge Selection for Undirected Graphs

cv.ES

Edge Selection with Cross validation

Description

Computes K-Fold cross validation based on mean squared prediction error.

Usage

```
cv.ES(x,object,K=10,M)
```

Arguments

- x Data Matrix. The columns represent the different variables, while the rows represent identically and independently distributed samples.
- object Lars object, generated from ES function.
- K Number of Folds in cross validation.
- M A vector of values that determine the points where cross validation are done. If not specified, the value of M will be determined using the object

Value

cv.ES picks a model which minimizes the mean squared prediction errors using the input vector M. cv.ES also pick a model with a mean squared prediction error less than or equals to the minimum mean square prediction plus its standard error.

References

Edge Selection for Undirected Graphs

See Also

ES, ESpredict

Examples

```
data(marks)
attach(marks)
object <- ES(marks)
cv.ES(marks,object)
detach(marks)
```

ES

Edge Selection Algorithm

Description

ES generates the entire sequence of coefficient estimates using Edge Selection Algorithm.

Usage

```
ES(u, maxstop)
```

Arguments

- | | |
|---------|---|
| u | Data Matrix. The columns represent the different variables, while the rows represent identically and independently distributed samples. |
| maxstop | Number of edges selected before the algorithm stops. If it is not specified, the algorithm will run until all the variables are added. |

Value

An object is returned, which includes the entire sequence of ES coefficient estimates, OLS estimates and the correlations of the first two edges that is added to the algorithm.

References

Edge Selection for Undirected Graphs

See Also

ESpredict, cv.ES

Examples

```
data(marks)
attach(marks)
object <- ES(marks)
detach(marks)
```

ESpredict

ESpredict

Description

`ESpredict` extract coefficient estimates from a fitted ES object.

Usage

```
ESpredict(object, c)
```

Arguments

- | | |
|---------------------|---|
| <code>object</code> | Fitted ES object |
| <code>c</code> | A vector of values that indexes the path. Values should fall between 0 and the maximum of <code>object\$c1</code> . |

Value

Vector or Matrix of Coefficients estimates.

References

Edge Selection for Undirected Graphs

See Also

`Es`, `cv.ES`

Examples

```
data(marks)
attach(marks)
object <- ES(marks)
ESpredict(object,c=object$c1)
detach(marks)
```

marks

Mathematics Marks

Description

Mathematic Marks from ggm package

Usage

```
data(marks)
```

Format

A data frame with 88 observations on the following 5 variables.

```
mechanics a numeric vector  
vectors a numeric vector  
algebra a numeric vector  
analysis a numeric vector  
statistics a numeric vector
```

Details

Mechanics and Vectors were closed book examinations. Algebra, Analysis and Statistics were open book examinations.

Source

Mardia, K.V., Kent, J.T. and Bibby, (1979). Multivariate analysis. London: Academic Press.

References

Whittaker, J. (1990). Graphical models in applied multivariate statistics. Chichester: Wiley.

Examples

```
data(marks)
```

Index

- *Topic **ESpredict**
 - ES-package, 1
- *Topic **ES**
 - cv.ES, 2
 - ES, 3
 - ES-package, 1
 - ESpredict, 4
- *Topic **cv.ES**
 - ES-package, 1
- *Topic **datasets**
 - marks, 5
- block_cross (ES), 3
- block_multiple (ES), 3
- block_solve (ES), 3
- create.tags (ES), 3
- cv.ES, 2
- ES, 3
- ES-package, 1
- ESpredict, 4
- marks, 5
- MPinverse (ES), 3
- scaledata (ES), 3