

Package ‘EpiReport’

May 11, 2020

Type Package

Title Epidemiological Report

Version 0.1.1

Date 2020-05-11

Description Drafting an epidemiological report in 'Microsoft Word' format for a given disease, similar to the Annual Epidemiological Reports published by the European Centre for Disease Prevention and Control. Through standalone functions, it is specifically designed to generate each disease specific output presented in these reports and includes:

- Table with the distribution of cases by Member State over the last five years;
- Seasonality plot with the distribution of cases at the European Union / European Economic Area level, by month, over the past five years;
- Trend plot with the trend and number of cases at the European Union / European Economic Area level, by month, over the past five years;
- Age and gender bar graph with the distribution of cases at the European Union / European Economic Area level.

Two types of datasets can be used:

- The default dataset of salmonella 2012-2016 data;
- Any dataset specified as described in the vignette.

Depends R (>= 3.4.0)

License EUPL

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

Imports officer, flextable, zoo, png, dplyr, tidyr, ggplot2, extrafont, graphics, utils, knitr (>= 1.20), rmarkdown

VignetteBuilder knitr

URL <https://ecdc.europa.eu/en/annual-epidemiological-reports>

NeedsCompilation no

Author Lore Merdrignac [aut, ctr, cre] (Author of the package and original code),

Tommi Karki [aut, fnd],

Esther Kissling [aut, ctr],

Joana Gomes Dias [aut, fnd] (Project manager)

Maintainer Lore Merdrignac <l.merdrignac@epiconcept.fr>

Repository CRAN

Date/Publication 2020-05-11 16:00:07 UTC

R topics documented:

AERparams	2
cleanECDCTable	4
cleanMeasureCode	4
filterDisease	6
getAER	6
getAgeGender	8
getMap	10
getSeason	11
getTableByMS	13
getTemplate	14
getTrend	15
includeMap	17
MSCode	18
orderQuasinum	18
plotAge	19
plotAgeGender	20
plotSeasonality	22
plotTS12MAvg	23
previewMap	24
SALM2016	24
shapeECDCFlexTable	26
toCapTitle	26
Index	28

AERparams

Dataset describing the parameters for the epidemiological report production

Description

A dataset describing the parameters to be used for each output of each disease report for all 53 health topics included in TESSy

Usage

AERparams

Format

A data frame with 53 rows (corresponding to the 53 health topics) and 24 variables:

HealthTopic Disease code that should match with the health topic code from the disease-specific dataset e.g. ANTH, SALM, etc.

DG (optional) Disease group e.g. FWD

DP (optional) Disease programme e.g. FWD

Label Disease label to be used in the report e.g. salmonellosis, anthrax

FrequencyCategory (optional) Frequency of the disease e.g. VERY RARE, NON-RARE, etc.

MeasurePopulation Type of population presented for this disease i.e. ALL or CONFIRMED cases

DatePublicAtlas Date of latest availability in the public access of the Atlas

TableUse Type of table to present in the report i.e. NO table, ASR table presenting age-standardised rates, RATE table presenting rates or COUNT table presenting the number of cases only.

TableRatesLabel Label to use in the table for rates e.g. RATE PER 100000 POPULATION

TableRatesNoDecimals Number of decimals to use when presenting rates

TableASRNoDecimals Number of decimals to use when presenting ASR

AgeGenderUse Type of age and gender bar graph to present i.e. NO graph, AG-COUNT Bar graph presenting the number of cases by age and gender, AG-RATE Bar graph presenting the rates of cases by age and gender, AG-PROP Bar graph presenting the proportion of cases by age and gender, A-RATE Bar graph presenting the rates of cases by age.

AgeGenderBarGraphLabel Label to use in the age and gender bar graph

AgeGenderGraphNoDecimals Number of decimals to use when presenting rates in the age and gender bar graph

TSTrendGraphUse Logical Y/N specifying whether to include a line graph describing the trend of the disease over the time

TSSeasonalityGraphUse Logical Y/N specifying whether to include a line graph describing the seasonality of the disease

TSSpecific Logical Y/N for specific line graph inclusion

MapNumbersUse Logical Y/N specifying whether to include the map presenting the number of cases by Member State

MapRatesUse Logical Y/N specifying whether to include the map presenting the rates of cases by Member State

MapRatesNoDecimals (optional) Number of decimals to use for presenting maps

MapASRUse Logical Y/N specifying whether to include the map presenting the age-standardised rates of cases by Member State

MapASRNoDecimals (optional) Number of decimals to use for presenting maps

Transmission Not implemented yet

TransmissionNoDecimals Not implemented yet

cleanECDCTable *Cleaning the final table*

Description

Cleaning the final table: identifying missing reports with '-', replacing the Member State codes with Member State names (see correspondence table [MSCode](#)), identifying not reporting Member States with '.'

Usage

```
cleanECDCTable(  
  x,  
  Country = EpiReport::MSCode$Country,  
  GeoCode = EpiReport::MSCode$GeoCode  
)
```

Arguments

x	dataframe, dataset to clean
Country	character vector, full names of the countries / Member States (e.g. Austria, Belgium, etc.) that will replace the GeoCodes included the x dataframe (Default MSCode\$Country)
GeoCode	character vector, corresponding GeoCode of each Member State (e.g. AT, BE, etc.) to replace with the country full names (Default MSCode\$GeoCode)

Value

cleaned ECDC dataframe

See Also

Global function: [getTableByMS](#)
Default dataset [MSCode](#)

cleanMeasureCode *Clean the MeasureCode variable*

Description

Clean the MeasureCode variable and replace the specific codes with the generic ones (e.g. ACCUTE.AGE_GENDER.RATE will be replaced by CONFIRMED.AGE_GENDER.RATE)

Usage

```
cleanMeasureCode(var)
```

Arguments

`var` character string vector variable, variable to clean

Details

- ALL.COUNT will replace the following codes:
 - ALL.DOMESTIC.COUNT
 - AGELT1.COUNT
- ALL.RATE will replace the following codes:
 - ALL.DOMESTIC.AGE.RATE
- ALL.AGE.RATE will replace the following codes:
 - ALL.DOMESTIC.AGE.RATE
- ALL.AGESTANDARDISED.RATE will replace the following codes:
 - ALL.DOMESTIC.AGESTANDARDISED.RATE
- CONFIRMED.COUNT will replace the following codes:
 - ALL.LABCONFIRMED.COUNT
 - CONFIRMED.LABCONFIRMED.COUNT
 - CONFIRMED.AGELT1.COUNT
 - TYPHOID.COUNT
- CONFIRMED.RATE will replace the following codes:
 - CONFIRMED.LABCONFIRMED.RATE
 - CONFIRMED.AGELT1.RATE
 - TYPHOID.RATE
- CONFIRMED.AGESTANDARDISED.RATE will replace the following codes:
 - CONFIRMED.LABCONFIRMED.AGESTANDARDISED.RATE
- CONFIRMED.AGE_GENDER.RATE will replace the following codes:
 - CONFIRMED.LABCONFIRMED.AGE_GENDER.RATE
 - TYPHOID.AGE_GENDER.RATE
 - ACCUTE.AGE_GENDER.RATE

Value

cleaned vector variable

See Also

[SALM2016](#)

Examples

```
x <- EpiReport::SALM2016
x$MeasureCode <- cleanMeasureCode(x$MeasureCode)
```

filterDisease	<i>Filter disease parameters</i>
---------------	----------------------------------

Description

Filter the table of parameters for the report on the given disease

Usage

```
filterDisease(dis, reportParameters)
```

Arguments

`dis` character string, disease code
`reportParameters` dataset of parameters for the report (default AERparams)

Value

dataframe with one row (from the AERparams dataframe) corresponding to the parameters of the selected disease

See Also

[AERparams](#)

Examples

```
disease <- "SALM"  
reportParameters <- EpiReport::AERparams  
reportParameters <- filterDisease(disease, reportParameters)
```

getAER	<i>Get full disease-specific epidemiological report</i>
--------	---

Description

Function to generate the 'Microsoft Word' epidemiological report (similar to the ECDC Annual Epidemiological Report (AER)) including all disease-specific outputs at each output-specific book-marks exact location.

(for further information on the outputs and the corresponding bookmarks, please see the package vignette "The Epidemiological Report Package" with `browseVignettes("EpiReport")`)
(see ECDC AER <https://ecdc.europa.eu/en/annual-epidemiological-reports>)

Usage

```
getAER(
  template = file.path(system.file(package = "EpiReport"),
    "template/AER_template.docx"),
  outputPath = getwd(),
  x = EpiReport::SALM2016,
  disease = "SALM",
  year = 2016,
  reportParameters = EpiReport::AERparams,
  MSCode = EpiReport::MSCode,
  pathPNG = system.file("maps", package = "EpiReport")
)
```

Arguments

template	doc (see 'officer' package), the empty 'Word' document template in which to include the table and plots disease-specific outputs. Default value is the empty template included in the package. See <code>getTemplate()</code> .
outputPath	character string, the full path where to generate the epidemiological report 'Word' output. Default value is the current working directory <code>getwd()</code> .
x	dataframe, raw disease-specific dataset (see specification of the dataset in the package vignette with <code>browseVignettes("EpiReport")</code>) (default SALM2016)
disease	character string, disease code (default "SALM"). Please make sure the disease code is included in the disease-specific dataset x in the HealthTopicCode variable.
year	numeric, year to produce the report for (default 2016). Please make sure the year is included in the disease-specific dataset x in the TimeCode variable.
reportParameters	dataframe, dataset including the required parameters for the report production (default AERparams) (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>)
MSCode	dataframe, correspondence table of GeoCode names and codes (default MSCode) (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>)
pathPNG	character string, the full path to the folder containing the maps (in PNG) to include in the final report

Value

A 'Word' document

See Also

Default template: [getTemplate](#)

Default datasets: [MSCode](#) [AERparams](#) [SALM2016](#)

Disease-specific outputs: [getTableByMS](#) [getSeason](#) [getTrend](#) [getMap](#) [getAgeGender](#)

Examples

```
# --- Generating the AER report using the default Salmonellosis dataset
getAER()

## Not run:
# --- Or using external data (example below)
ZIKV2016 <- read.table("data/ZIKV2016.csv", sep = ",", header = TRUE, stringsAsFactors = FALSE)
output <- "C:/EpiReport/doc/"
pathMap <- "C:/EpiReport/maps/"
getAER(disease = "ZIKV", year = 2016, x = ZIKV2016, outputPath = output, pathPNG = pathMap)

## End(Not run)
```

getAgeGender

Get disease-specific age and gender bar graph

Description

Function returning the age and gender bar graph that will be included in the epidemiological report at the bookmark location 'BARGPH_AGE_GENDER_BOOKMARK' of the template report.

The bar graph presents the distribution of cases at EU/EEA level using either:

- AG-COUNT: The number of cases by age and gender
- AG-RATE: The rate per 100 000 cases by age and gender
- AG-PROP: The proportion of cases by age and gender
- A-RATE: The rate per 100 000 cases by age only

The choice of the type of bar graph is set in the report parameters table AERparams.

(see ECDC reports <https://ecdc.europa.eu/en/annual-epidemiological-reports>)

Usage

```
getAgeGender(
  x = EpiReport::SALM2016,
  disease = "SALM",
  year = 2016,
  reportParameters = EpiReport::AERparams,
  geoCode = "EU_EEA31",
  index = 1,
  doc
)
```


Arguments

x	dataframe, raw disease-specific dataset (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>) (default SALM2016)
disease	character string, disease code (default "SALM"). Please make sure the disease code is included in the disease-specific dataset x in the HealthTopicCode variable.
year	numeric, year to produce the graph for (default 2016). Please make sure the year is included in the disease-specific dataset x in the TimeCode variable.
reportParameters	dataframe, dataset including the required parameters for the graph and report production (default AERparams) (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>)
geoCode	character string, GeoCode to run the analysis on (default "EU_EEA31")
index	integer, figure number
doc	'Word' document (see 'officer' package) in which to add the graph at the bookmark location. If doc is missing, getAgeGender returns the ggplot2 object.

Value

'Word' doc or a ggplot2 object

See Also

Global function for the full epidemiological report: [getAER](#)
Required Packages: [ggplot2](#) [officer](#)
Internal functions: [plotAgeGender](#) [plotAge](#)
Default datasets: [AERparams](#)

Examples

```
# --- Plot using the default dataset
getAgeGender()

# --- Plot using external dataset
# --- Please see examples in the vignette
browseVignettes(package = "EpiReport")
```

getMap

*Get disease-specific map: distribution of cases by Member State***Description**

Function returning the disease-specific PNG map previously created and stored in a specific folder (see `pathPNG` argument) and that will be included in the epidemiological report at the bookmark location of the template report, depending of the type of map. Three type of maps can be included in the report:

- Bookmark 'MAP_NB_BOOKMARK': Distribution of cases by country. An additional caption will be included at the location of the bookmark 'MAP_NB_CAPTION'.
- Bookmark 'MAP_RATE_BOOKMARK': Distribution of cases per 100 000 population by country. An additional caption will be included at the location of the bookmark 'MAP_RATE_CAPTION'.
- Bookmark 'MAP_ASR_BOOKMARK': Distribution of cases using age-strandardised rates per 100 000 population by country. An additional caption will be included at the location of the bookmark 'MAP_ASR_CAPTION'.

(see ECDC reports <https://ecdc.europa.eu/en/annual-epidemiological-reports>)

Usage

```
getMap(
  disease = "SALM",
  year = 2016,
  reportParameters = EpiReport::AERparams,
  index = 1,
  pathPNG = system.file("maps", package = "EpiReport"),
  doc
)
```

Arguments

disease	character string, disease code (default "SALM").
year	numeric, year to produce the map for (default 2016).
reportParameters	dataframe, dataset including the required parameters for the map and report production (default AERparams) (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>)
index	integer, figure number
pathPNG	character string, full path to the folder containing the maps in PNG (default 'maps' folder included in the package <code>system.file("maps", package = "EpiReport")</code>)
doc	'Word' document (see 'officer' package) in which to add the maps at the bookmark location. If doc is missing, <code>getMap</code> returns a preview of the PNG image.

Value

'Word' doc an image preview

See Also

Global function for the full epidemiological report: [getAER](#)

Required Packages: [officer](#)

Internal functions: [includeMap](#) [previewMap](#)

Default datasets: [AERparams](#)

Examples

```
# --- Preview of the PNG map using the default Salmonellosis dataset
getMap()

# --- Plot using external PNG image
# --- Please see examples in the vignette
browseVignettes(package = "EpiReport")
```

getSeason

Get disease-specific seasonality graph: distribution of cases by month

Description

Function returning the plot describing the seasonality of the disease that will be included in the epidemiological report at the bookmark location 'TS_SEASON_BOOKMARK' of the template report.

The graph includes the distribution of cases at EU/EEA level, by month, over the past five years, with:

- The number of cases by month in the reference year (green solid line)
- The mean number of cases by month in the four previous years (grey dashed line)
- The minimum number of cases by month in the four previous years (grey area)
- The maximum number of cases by month in the four previous years (grey area)

(see ECDC reports <https://ecdc.europa.eu/en/annual-epidemiological-reports>)

Usage

```
getSeason(
  x = EpiReport::SALM2016,
  disease = "SALM",
  year = 2016,
  reportParameters = EpiReport::AERparams,
  MSCode = EpiReport::MSCode,
  index = 1,
  doc
)
```

Arguments

x	dataframe, raw disease-specific dataset (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>) (default SALM2016)
disease	character string, disease code (default "SALM"). Please make sure the disease code is included in the disease-specific dataset x in the HealthTopicCode variable.
year	numeric, year to produce the graph for (default 2016). Please make sure the year is included in the disease-specific dataset x in the TimeCode variable.
reportParameters	dataframe, dataset including the required parameters for the graph and report production (default AERparams) (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>)
MSCode	dataframe, correspondence table of GeoCode names and codes (default MSCode) (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>)
index	integer, figure number
doc	'Word' document (see 'officer' package) in which to add the graph at the bookmark location. If doc is missing, getSeason returns the ggplot2 object.

Value

'Word' doc or a ggplot2 object

See Also

Global function for the full epidemiological report: [getAER](#)
 Required Packages: [ggplot2](#) [officer](#)
 Internal functions: [plotSeasonality](#)
 Default datasets: [AERparams](#) [MSCode](#)

Examples

```
# --- Plot using the default dataset
getSeason()

# --- Plot using external dataset
# --- Please see examples in the vignette
browseVignettes(package = "EpiReport")
```

getTableByMS	<i>Get disease-specific table: distribution of cases by Member State (GeoCode)</i>
--------------	--

Description

Function returning the table ('flexible') that will be included in the epidemiological report at the bookmark location 'TABLE1_BOOKMARK' of the template report. An additional caption will be included at the location of the bookmark 'TABLE1_CAPTION'.

(see Table 1 of the ECDC annual reports <https://ecdc.europa.eu/en/annual-epidemiological-reports>)

Usage

```
getTableByMS(
  x = EpiReport::SALM2016,
  disease = "SALM",
  year = 2016,
  reportParameters = EpiReport::AERparams,
  MSCode = EpiReport::MSCode,
  index = 1,
  doc
)
```

Arguments

x	dataframe, raw disease-specific dataset (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>) (default SALM2016)
disease	character string, disease code (default "SALM"). Please make sure the disease code is included in the disease-specific dataset x in the HealthTopicCode variable.
year	numeric, year to produce the table for (default 2016). Please make sure the year is included in the disease-specific dataset x in the TimeCode variable.
reportParameters	dataframe, dataset including the required parameters for the report production (default AERparams) (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>)
MSCode	dataframe, correspondence table of GeoCode names and codes (default MSCode) (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>)
index	integer, figure number
doc	'Word' document (see officer package) in which to add the table at the bookmark location. If doc is missing, getTable returns the flexible table object.

Details

The current version of the 'EpiReport' package includes three types of table (see detailed specification of the tables in the package vignette with `browseVignettes(package = "EpiReport")`):

- COUNT - Table presenting the number of cases by Member State (GeoCode) over a 5-year period;
- RATE - Table presenting the number of cases and rates by Member State (GeoCode) over a 5-year period;
- ASR - Table presenting the number of cases and rates by Member State (GeoCode) over a 5-year period, including age-standardised rates for the most recent year.

Value

'Word' doc or flextable object (see 'flextable' package)

See Also

Global function for the full epidemiological report: [getAER](#)

Required Packages: [flextable](#) [officer](#)

Internal functions: [shapeECDCFlexTable](#) [cleanECDCTable](#)

Default datasets: [AERparams](#) [MSCode](#)

Examples

```
# --- Draft the table using the default Salmonellosis dataset
getTableByMS()
```

getTemplate

Get epidemiological report (empty) template

Description

Function to export the generic 'Microsoft Word' empty template (included in the 'EpiReport' package) used to produce the epidemiological report similar to the ECDC Annual Epidemiological Report (AER). The modified version of the template can then be used to produce the final epidemiological report using `getAER(template = 'NewTemplate.docx', ...)`

(see the package vignette "The Epidemiological Report Package" with `browseVignettes("EpiReport")`)

(see ECDC annual epidemiological reports <https://ecdc.europa.eu/en/annual-epidemiological-reports>)

Usage

```
getTemplate(output_path)
```

Arguments

`output_path` character string, the full path where to create the 'Word' output. Default location will be the current working directory (default `getwd()`)

Value

A 'Word' document

See Also

[getAER](#)

Examples

```
# --- Export the template in the default folder: working directory
getTemplate()

# --- Or specify the full path
getTemplate(output_path = getwd())
```

getTrend

Get disease-specific trend plot: trend and number of cases by month

Description

Function returning the plot describing the trend of the disease over time that will be included in the epidemiological report at the bookmark location 'TS_TREND_BOOKMARK' on the template report.

The graph includes the number of cases at EU/EEA level, by month, over the past five years, with:

- The number of cases by month over the 5-year period (grey solid line)
- The 12-month moving average of the number of cases by month (green solid line)

(see ECDC reports <https://ecdc.europa.eu/en/annual-epidemiological-reports>)

Usage

```
getTrend(
  x = EpiReport::SALM2016,
  disease = "SALM",
  year = 2016,
  reportParameters = EpiReport::AERparams,
  MSCode = EpiReport::MSCode,
  index = 1,
  doc
)
```

Arguments

x	dataframe, raw disease-specific dataset (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>) (default SALM2016)
disease	character string, disease code (default "SALM"). Please make sure the disease code is included in the disease-specific dataset x in the HealthTopicCode variable.
year	numeric, year to produce the graph for (default 2016). Please make sure the year is included in the disease-specific dataset x in the TimeCode variable.
reportParameters	dataframe, dataset including the required parameters for the graph and report production (default AERparams) (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>)
MSCode	dataframe, correspondence table of GeoCode names and codes (default MSCode) (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>)
index	integer, figure number
doc	'Word' document (see officer package) in which to add the graph at the bookmark location. If doc is missing, getTrend returns the ggplot2 object.

Value

'Word' doc or a ggplot2 preview

See Also

Global function for the full epidemiological report: [getAER](#)
 Required Packages: [ggplot2](#) [officer](#)
 Internal functions: [plotTS12MAvg](#)
 Default datasets: [AERparams](#) [MSCode](#)

Examples

```
# --- Plot using the default dataset
getTrend()

# --- Plot using external dataset
# --- Please see examples in the vignette
browseVignettes(package = "EpiReport")
```

includeMap

Including PNG map in the 'Microsoft Word' template

Description

Function including the disease-specific PNG map in the 'Word' document at the specific bookmark location.

Usage

```
includeMap(
  disease,
  year,
  reportParameters,
  index,
  pathPNG,
  doc,
  pop,
  namePNGsuffix,
  unit,
  mapBookmark,
  captionBookmark
)
```

Arguments

disease	character string, disease code (default "SALM").
year	numeric, year to produce the graph for (default 2016).
reportParameters	dataframe, dataset including the required parameters for the graph and report production (default AERparams) (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>)
index	integer, figure number
pathPNG	character string, full path to the folder containing the maps in PNG (default 'maps' folder included in the package system. <code>file("maps", package = "EpiReport")</code>)
doc	'Word' document (see 'officer' package) in which to add the maps at the bookmark location
pop	character string, label of the type of population to use in the caption (e.g. confirmed)
namePNGsuffix	character string, suffix of the PNG file name of the map (i.e. "COUNT", "RATE" or "AGESTANDARDISED".)
unit	character string, label of the unit used in the caption (e.g. "per 100 000 population")
mapBookmark	character string, label of the bookmark where to add the map in the 'Word' document
captionBookmark	character string, label of the bookmark where to add the caption in the 'Word' document

Value

'Word' doc

See Also

Global function: [getMap](#)

MSCode	<i>Dataset correspondence table between country names and country code</i>
--------	--

Description

Dataframe providing the correspondence table of the geographical code GeoCode used in the disease dataset, and the geographical label Country to use throughout the report. Additional information on the EU/EEA affiliation is also available in column EUEEA.

Usage

MSCode

Format

A data frame with 32 rows and 3 variables:

Country Full name of the country / Member State e.g. Austria, Belgium, etc.

GeoCode Associated code (see GeoCode variable on the SALM2016 internal dataset) e.g. AT, BE, BG, etc.

EUEEA For each Member State, variable specifying in the country is part of the EU or EEA.

See Also

[SALM2016](#)

orderQuasinum	<i>Order 'quasinumerical' categorical vectors (increasing order)</i>
---------------	--

Description

A function to order 'quasinumerical' (i.e. categorical with values such as "15-30" or "<18") integer vectors into increasing order. Currently handles away the following non-numerical characters "-", ">", "<", ">=", "<=", "+".

Usage

orderQuasinum(x)

Arguments

x character vector with 'quas numerical' values

Author(s)

Tommi Karki

See Also

Used in [getAgeGender](#) and [plotAgeGender / plotAge](#)

Examples

```
age1 <- c("<1", "1-15", "16-25", ">65", "26-65")
age2 <- c("0-4", "5-10", ">65", "25-64", "11-25")
age3 <- c("5-10", ">65", "25-64", "11-25", "<=4")
age4 <- c(">=65", "<18", "18-64")
age5 <- c("5-10", "+65", "25-64", "11-25", "0-4")

age1
orderQuasinum(age1)
age2
orderQuasinum(age2)
age3
orderQuasinum(age3)
age4
orderQuasinum(age4)
age5
orderQuasinum(age5)
```

plotAge

Age bar graph

Description

This function draws a bar graph by age group (or possibly other grouping).

The bar graph presents the distribution of cases at EU/EEA level using the rate per 100 000 cases by age.

Expects aggregated data.

Usage

```
plotAge(
  data,
  xvar = "XLabel",
  yvar = "YValue",
  fill_color1 = "#65B32E",
  ytitle = "Rate"
)
```

Arguments

data	dataframe containing the variables to plot
xvar	character string, name of the variable to plot on the x-axis in quotes (default "XLabel")
yvar	character string, name of the variable to plot on the y-axis in quotes (default "YValue")
fill_color1	character string, hexadecimal colour to use in the graph; (default to ECDC green "#65B32E")
ytitle	character string, y-axis title; (default "Rate").

See Also

Global function: [getAgeGender](#)

Required Packages: [ggplot2](#)

Examples

```
# --- Create dummy data
mydat <- data.frame(AgeGroup = c("0-25", "26-65", "65+"),
                   NumberOfCases = c(54,32,41))

# --- Plot the dummy data
plotAge(mydat,
        xvar = "AgeGroup",
        yvar = "NumberOfCases",
        ytitle = "Number of cases")
```

plotAgeGender

Age and Gender bar graph

Description

This function draws a bar graph of the distribution of cases by age group and gender (or possibly other grouping).

The bar graph presents the distribution of cases at EU/EEA level using either:

- AG-COUNT: The number of cases by age and gender
- AG-RATE: The rate per 100 000 cases by age and gender
- AG-PROP: The proportion of cases by age and gender

Expects aggregated data.

Usage

```
plotAgeGender(
  data,
  xvar = "XLabel",
  yvar = "ZValue",
  group = "YLabel",
  fill_color1 = "#65B32E",
  fill_color2 = "#7CBDC4",
  ytitle = "Rate"
)
```

Arguments

data	dataframe containing the variables to plot
xvar	character string, name of the variable to plot on the x-axis in quotes (default "XLabel")
yvar	character string, name of the variable to plot on the y-axis in quotes (default "ZValue")
group	character string, name of the grouping variable in quotes, e.g. gender. (default "YLabel")
fill_color1	character string, hexadecimal colour to use in the graph for bar 1; (default to ECDC green "#65B32E")
fill_color2	character string, hexadecimal colour to use in the graph for bar 2; (default to ECDC blue "#7CBDC4")
ytitle	character string, y-axis title; (default "Rate").

See Also

Global function: [getAgeGender](#)

Required Packages: [ggplot2](#)

Examples

```
# --- Create dummy data
mydat <- data.frame(Gender=c("F", "F", "M", "M"),
  AgeGroup = c("0-65", "65+", "0-65", "65+"),
  NumberOfCases = c(54,43,32,41))

# --- Plot the dummy data
plotAgeGender(mydat,
  xvar = "AgeGroup",
  yvar = "NumberOfCases",
  group = "Gender",
  ytitle = "Number of cases")
```

plotSeasonality *Seasonality line graph*

Description

This function draws a line graph describing the seasonality of the selected disease over the past 5 years.

The graph includes the distribution of cases, by month, over the past five years, with:

- yvar: The number of cases by month in the reference year (green solid line)
- mean4years: The mean number of cases by month in the four previous years (grey dashed line)
- min4years: The minimum number of cases by month in the four previous years (grey area)
- max4years: The maximum number of cases by month in the four previous years (grey area)

Expects aggregated data and pre-calculated min, max and mean figures.

Usage

```
plotSeasonality(
  data,
  xvar = "TimeCode",
  yvar = "N",
  min4years = "Min4Years",
  max4years = "Max4Years",
  mean4years = "Mean4Years",
  year = 2016
)
```

Arguments

data	dataframe containing the variables to plot
xvar	character string, name of the time variable on the x-axis in quotes (default "TimeCode")
yvar	character string, name of the variable to plot on the y-axis in quotes (default "N"), number of cases by month in the reference year (green solid line)
min4years	character string, name of the variable to plot in quotes including the minimum number of cases by month over the past 4 years (default "Min4Years")
max4years	character string, name of the variable to plot in quotes including the maximum number of cases by month over the past 4 years (default "Max4Years")
mean4years	character string, name of the variable to plot in quotes including the mean of the number of cases by month over the past 4 years (default "Mean4Years")
year	numeric, year to produce the graph for (default 2016).

See Also

Global function: [getSeason](#)
Required Packages: [ggplot2](#)

plotTS12MAvg *Time series with 12-month moving average*

Description

This function draws a line graph describing the trend of the selected disease over the past 5 years. The graph includes the trend and number of cases at EU/EEA level, by month, over the past five years, with:

- `yvar`: The number of cases by month over the 5-year period (grey solid line)
- `movAverage`: The 12-month moving average of the number of cases by month (green solid line)

Expects aggregated data and pre-calculated 12-month moving average.

Usage

```
plotTS12MAvg(data, xvar = "TimeCode", yvar = "N", movAverage = "MAV")
```

Arguments

<code>data</code>	dataframe containing the variables to plot
<code>xvar</code>	character string, name of the time variable to plot on the x-axis in quotes (default "TimeCode")
<code>yvar</code>	character string, name of the variable to plot on the y-axis in quotes (default "N"), number of cases by month over the 5-year period (grey solid line)
<code>movAverage</code>	character string, name of the variable to plot in quotes including the moving average per each time unit (default "MAV")

See Also

Global function: [getTrend](#)
Required Packages: [ggplot2](#)

```
previewMap          Previewing the PNG map
```

Description

Function previewing the disease-specific PNG map

Usage

```
previewMap(disease, year, reportParameters, pathPNG, namePNGsuffix)
```

Arguments

disease	character string, disease code (default "SALM").
year	numeric, year to produce the graph for (default 2016).
reportParameters	dataframe, dataset including the required parameters for the graph and report production (default AERparams) (see specification of the dataset in the package vignette with <code>browseVignettes(package = "EpiReport")</code>)
pathPNG	character string, full path to the folder containing the maps in PNG (default 'maps' folder included in the package <code>system.file("maps", package = "EpiReport")</code>)
namePNGsuffix	character string, suffix of the PNG file name of the map (i.e. "COUNT", "RATE" or "AGESTANDARDISED".)

Value

Preview

See Also

Global function: [getMap](#)

```
SALM2016          Dataset including Salmonellosis data for 2012-2016
```

Description

A dataset containing the data and indicators required to build the epidemiological report for Salmonellosis 2016 TESSy data (default dataset used throughout EpiReport)

Usage

```
SALM2016
```


Format

A data frame with 60,775 rows and 18 variables:

HealthTopicCode Disease code e.g. ANTH, SALM, etc.

MeasureLabel (optional) Label of the measure indicator

MeasurePopulation Population targeted by the measure indicator

MeasureCode Code of the measure indicator

MeasureId (optional) Measure indicator ID

MeasureType (optional) Type of measure indicator

TimeUnit Unit of the time variable i.e. Y for yearly data or M for monthly data

GeoLevel (optional) Geographical level e.g. 1, 2, etc

TimeCode Time variable including dates in any formats available (according to the unit defined in `TimeUnit`) yearly data (e.g. 2001) or monthly data (e.g. 2001-01)

GeoCode Geographical level in coded format including country names (e.g. AT for Austria, BE for Belgium, BG for Bulgaria, see also the `EpiReport::MSCode` table, correspondence table for Member State labels and codes)

XValue (optional) XValue

XLabel The label associated with the x-axis in the epidemiological report (see `getAgeGender()` and `plotAgeGender()` bar graph for the age variable)

YValue The value associated with the y-axis in the epidemiological report (see `plotAge()` bar graph for the variable age, or `getTableByMS()` for the number of cases, rate or age-standardised rate in the table by Member States by year)

YLabel The label associated with the y-axis in the epidemiological report (see `getAgeGender()` and `plotAgeGender()` bar graph for the grouping variable gender)

ZValue The value associated with the stratification of XLabel and YLabel in the age and gender bar graph (see `getAgeGender()` and `plotAgeGender()`)

N Number of cases (see `getTrend()` and `getSeason()` line graph)

NMissing (optional)

NLowerResolution (optional)

See Also

The correspondence table for Member State labels and codes [MSCode](#) and the functions mentioned above: [getAgeGender](#), [plotAgeGender](#), [plotAge](#), [getTableByMS](#), [getTrend](#) and [getSeason](#).

shapeECDCFlexTable *Shaping the final table (layout, title, color, font)*

Description

Shaping the final table including titles, adding background color, specifying font name and size.

Usage

```
shapeECDCFlexTable(ft, headers, fsize, fname, maincolor)
```

Arguments

ft	flextable (see 'flextable' package), table to shape into ECDC table layout
headers	dataframe including the multiple headers to add to the flextable object. Please note that the column col_keys should contain the names of the flextable object (i.e. col_key = names(x)), accordingly to set_header_df .
fsize	numeric, font to use (Default 7)
fname	character, font name (Default "Tahoma")
maincolor	character string, hexadecimal code for the header background color (Default "#69AE23")

Value

flextable object (see flextable package)

See Also

Global function: [getTableByMS](#)
 Required package [flextable](#)

toCapTitle *Capitalise first letter*

Description

Capitalise the first letter of a character string in order to use it as title

Usage

```
toCapTitle(str)
```

Arguments

str	character string to capitalise as a title
-----	---

Value

character string

Examples

```
my_title <- "number of salmonellosis cases by age group"  
toCapTitle(my_title)
```

Index

- *Topic **age**
 - plotAge, [19](#)
 - plotAgeGender, [20](#)
- *Topic **bargraph**
 - plotAge, [19](#)
 - plotAgeGender, [20](#)
- *Topic **datasets**
 - AERparams, [2](#)
 - MSCode, [18](#)
 - SALM2016, [24](#)
- *Topic **gender**
 - plotAgeGender, [20](#)
- *Topic **order**
 - orderQuasinum, [18](#)
- *Topic **salmonellosis**
 - SALM2016, [24](#)
- *Topic **seasonality**
 - plotSeasonality, [22](#)
- *Topic **trend**
 - plotTS12MAvg, [23](#)

[AERparams](#), [2](#), [6](#), [7](#), [9](#), [11](#), [12](#), [14](#), [16](#)

[cleanECDCTable](#), [4](#), [14](#)

[cleanMeasureCode](#), [4](#)

[filterDisease](#), [6](#)

[flextable](#), [14](#), [26](#)

[getAER](#), [6](#), [9](#), [11](#), [12](#), [14–16](#)

[getAgeGender](#), [7](#), [8](#), [19–21](#), [25](#)

[getMap](#), [7](#), [10](#), [18](#), [24](#)

[getSeason](#), [7](#), [11](#), [23](#), [25](#)

[getTableByMS](#), [4](#), [7](#), [13](#), [25](#), [26](#)

[getTemplate](#), [7](#), [14](#)

[getTrend](#), [7](#), [15](#), [23](#), [25](#)

[ggplot2](#), [9](#), [12](#), [16](#), [20](#), [21](#), [23](#)

[includeMap](#), [11](#), [17](#)

[MSCode](#), [4](#), [7](#), [12](#), [14](#), [16](#), [18](#), [25](#)

[officer](#), [9](#), [11](#), [12](#), [14](#), [16](#)

[orderQuasinum](#), [18](#)

[plotAge](#), [9](#), [19](#), [19](#), [25](#)

[plotAgeGender](#), [9](#), [19](#), [20](#), [25](#)

[plotSeasonality](#), [12](#), [22](#)

[plotTS12MAvg](#), [16](#), [23](#)

[previewMap](#), [11](#), [24](#)

[SALM2016](#), [5](#), [7](#), [18](#), [24](#)

[set_header_df](#), [26](#)

[shapeECDCFlexTable](#), [14](#), [26](#)

[toCapTitle](#), [26](#)