

Package ‘EventStudy’

March 14, 2019

Type Package

Title Event Study Analysis

Description Perform Event Studies from through our <<http://EventStudyTools.com>> Application Programming Interface, parse the results, visualize it, and / or use the results in further analysis.

Author Dr. Simon Mueller

Date 2019-03-05

Version 0.36

Encoding UTF-8

URL <http://eventstudytools.com>

Maintainer Dr. Simon Mueller <simon.mueller@muon-stat.com>

License GPL (>= 2)

Depends ggplot2

Imports shiny, miniUI, rstudioapi, httr, curl, jsonlite, magrittr (>= 1.5), data.table, testthat, dplyr, tidyr, rlang, scales, tidyquant, RColorBrewer, stringr, purrr, readr, openxlsx

Suggests knitr, rmarkdown

BugReports <https://github.com/EventStudyTools/api-wrapper.r/issues>

LazyData true

RoxygenNote 6.1.1

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2019-03-14 12:13:31 UTC

R topics documented:

aarPlot	2
ARCAApplicationInput	3
arPlot	4

AVCApplicationInput	5
AVyCApplicationInput	7
checkFile	8
checkFiles	9
estAPIKey	10
EventStudy	10
EventStudyAddin	10
EventStudyAPI	11
EventStudyApplicationInput	12
getSP500ExampleFiles	13
ResultParser	14

Index	15
--------------	-----------

aarPlot	<i>Averaged Abnormal Return Plot</i>
----------------	--------------------------------------

Description

Averaged abnormal return plots with confidence intervals

For more details see the help vignette: `vignette("parameters_eventstudy", package = "EventStudy")`

Usage

```
aarPlot(ResultParserObj, cumSum = F, group = NULL, window = NULL,
       ciStatistics = NULL, p = 0.95, ciType = "band", xlab = "",
       ylab = "Averaged Abnormal Returns", facet = T, ncol = 4)
```

Arguments

ResultParserObj	An object of class ResultParser
cumSum	plot CAAR
group	set this parameter if just one group should be plotted
window	numeric vector of length 2
ciStatistics	Statistic used for confidence intervals
p	p-value
ciType	type of CI band
xlab	x-axis label
ylab	y-axis label
facet	should each firm get its own plot (default = T)
ncol	number of facet columns

Value

a ggplot2 object

Examples

```
## Not run:
# plot averaged abnormal returns in one plot
aarPlot(resultParser)

# plot averaged abnormal returns with .95-CI
arPlot(resultParser, ciStatistics = "Patell Z", p = .95)

## End(Not run)
```

ARCAApplicationInput *Abnormal Return Calculation Parameters*

Description

This R6 class defines the parameters for the Return Event Study. We recommend to use the set functionality to setup your Event Study, as we check input parameters.

For more details see the help vignette: `vignette("parameters_eventstudy", package = "EventStudy")`

Usage

`ARCAApplicationInput`

Format

An object of class `R6ClassGenerator` of length 24.

Value

a `ESTParameters` R6 object

Methods

- `$new()` Constructor for `ARCAApplicationInput`.
- `$setEMail(eMail)` Set the e-Mail address for reporting. This functionality is currently not working.
- `$setBenchmarkModel(model = 'mm')` Setter for the benchmark model.s
- `$setReturnType(returnType)` Setter for the return type (log or simple)
- `$setTestStatistics(testStatistics)` Setter for the test statistics.

Arguments

- ESTARCPParameters** An `ARCAApplicationInput` object
- eMail** An E-Mail address in String format
- model** A benchmark model in String format
- returnType** A return type in String format
- testStatistics** A String vector with test statistics.

See Also

<https://www.eventstudytools.com/axc/upload>

Examples

```
## Not run:
# get files for our S&P500 example; 3 files are written in the current
# working directory
getSP500ExampleFiles()

# Generate a new parameter object
arcParams <- ARCAplicationInput$new()

# set test statistics
arcParams$setBenchmarkModel("garch")

# Setup API object
apiKey <- "{Your API key}"
estSetup <- EventStudyAPI$new()
estSetup$authentication(apiKey)

# Perform Event Study
estSetup$performEventStudy(estParams = arcParams,
                           dataFiles = c("request_file" = "01_RequestFile.csv",
                                       "firm_data"      = "02_firmData.csv",
                                       "market_data"    = "03_marketData.csv"))

# Download task results and save them in the actual working directory
estSetup$getTaskResults()

## End(Not run)
```

arPlot

Abnormal Return Plot

Description

Plot abnormal returns in the event window of single or multiple firms.

Usage

```
arPlot(ResultParserObj, firm = NULL, window = NULL, xlab = "",
       ylab = "Abnormal Returns", alpha = 0.5, facetVar = NULL,
       ncol = 4, addAAR = F, xVar = "eventTime", yVar = "ar")
```

Arguments

ResultParserObj	An object of class ResultParser
firm	set this parameter if just a subset of firms should be plotted
window	filter event time window
xlab	x-axis label of the plot
ylab	y-axis label
alpha	alpha value
facetVar	should each firm get its own plot. You may plot each firm in an own plot or by each group. (Default: NULL, available: Group and Firm)
ncol	number of facet columns
addAAR	add aar line
xVar	x variable name
yVar	y variable name

Value

a ggplot2 object

Examples

```
## Not run:
# plot abnormal returns in one plot
arPlot(resultParser)

# plot abnormal returns by group
arPlot(resultParser, facetVar = "Group")

## End(Not run)
```

Description

This R6 class defines the parameters for the Abnormal Volume Event Study. We recommend to use the set functionality to setup your Event Study, as we check input parameters.

For more details see the help vignette: `vignette("parameters_eventstudy", package = "EventStudy")`

Usage

`AVCAApplicationInput`

Format

`R6Class` object.

Value

a ESTParameters R6 object

Methods

```
$new() Constructor for AVCAApplicationInput
$setEMail(eMail) Set the e-Mail address for reporting. This functionality is currently not working
$setBenchmarkModel(model = 'mm') Setter for the benchmark models
$setReturnType(returnType) Setter for the return type (log or simple)
$setTestStatistics(testStatistics) Setter for the test statistics
```

Arguments

AVCAApplicationInput An AVCAApplicationInput object
eMail An E-Mail address in String format
model A benchmark model in String format
returnType A return type in String format
testStatistics A String vector with test statistics

See Also

<https://www.eventstudytools.com/axc/upload>

Examples

```
## Not run:
# get files for our S&P500 example; 3 files are written in the current
# working directory
getSP500ExampleFiles()

# Generate a new parameter object
avcParams <- AVCAApplicationInput$new()

# set test statistics
arcParams$setBenchmarkModel("garch")

# Setup API object
apiKey <- "{Your API key}"
estSetup <- EventStudyAPI$new()
estSetup$authentication(apiKey)

# Perform Event Study
estSetup$performEventStudy(estParams = avcParams,
```

```

dataFiles = c("request_file" = "01_RequestFile.csv",
            "firm_data"      = "02_firmData.csv",
            "market_data"    = "03_marketData.csv"))

# Download task results and save them in the actual working directory
estSetup$getTaskResults()

## End(Not run)

```

AVyCApplicationInput Abnormal Volatility Calculation Parameters**Description**

This R6 class defines the parameters for the Abnormal Volatility Volume Event Study. We recommend to use the `set` functionality to setup your Event Study, as we check input parameters.

For more details see the help vignette: `vignette("parameters_eventstudy", package = "EventStudy")`

Usage

`AVyCApplicationInput`

Format

`R6Class` object.

Value

a ESTParameters R6 object

Methods

- `$new()` Constructor for `AVyCApplicationInput`
- `$setEMail(eMail)` Set the e-Mail address for reporting. This functionality is currently not working.
- `$setBenchmarkModel(model = 'mm')` Setter for the benchmark models
- `$setReturnType(returnType)` Setter for the return type (log or simple)
- `$setTestStatistics(testStatistics)` Setter for the test statistics. Per default all available test statistics are applied. You may find all test statistics in the vignette 'parameter_eventstudy'

Arguments

AVyCApplicationInput An `AVyCApplicationInput` object

eMail An E-Mail address in String format

model A benchmark model in String format

returnType A return type in String format

testStatistics A String vector with test statistics

See Also

<https://www.eventstudytools.com/axc/upload>

Examples

```
## Not run:
# get files for our S&P500 example; 3 files are written in the current
# working directory
getSP500ExampleFiles()

# Generate a new parameter object
avycParams <- AVyCApplicationInput$new()

# set test statistics
avycParams$setTestStatistics(c("aarptlz", "aarrankz"))

# Setup API object
apiKey <- "{Your API key}"
estSetup <- EventStudyAPI$new()
estSetup$authentication(apiKey)

# Perform Event Study
estSetup$performEventStudy(estParams = avycParams,
                           dataFiles = c("request_file" = "01_RequestFile.csv",
                                         "firm_data"      = "02_firmData.csv",
                                         "market_data"    = "03_marketData.csv"))

# Download task results and save them in the actual working directory
estSetup$getTaskResults()

## End(Not run)
```

checkFile

Check input data files

Description

Check correct column, date, and shape of the input data files

Usage

```
checkFile(path, type = "request_file")
```

Arguments

path	path to the input data file
type	the type of file to check

Value

```
data.frame
```

Examples

```
## Not run:  
# save example files to current working directory  
getSP500ExampleFiles()  
  
checkFile("01_RequestFile.csv", "request_file")  
  
## End(Not run)
```

```
checkFiles
```

Check EventStudy input files

Description

Check each input file plus inter file relations, whether market index and firm identifier in request file match market index in market_data and firm identifier in firm_data file.

Usage

```
checkFiles(dataFiles = c(request_file = "01_RequestFile.csv", firm_data =  
"02_firmData.csv", market_data = "03_MarketData.csv"), returnData = F)
```

Arguments

dataFiles	A named character vector. The names must be request_file, firm_data, and market_data
returnData	returns the data as list of data.frames

Examples

```
## Not run:  
# save example files to current working directory  
getSP500ExampleFiles()  
  
dataFiles <- c("request_file" = "01_RequestFile.csv",  
"firm_data"      = "02_firmData.csv",  
"market_data"    = "03_MarketData.csv")  
  
checkFiles(dataFiles)  
  
## End(Not run)
```

estAPIKey	<i>Set eventStudy API Key</i>
-----------	-------------------------------

Description

Set eventStudy API Key

Usage

```
estAPIKey(key)
```

Arguments

key	EventStudy API Key
-----	--------------------

EventStudy	<i>EventStudy</i>
------------	-------------------

Description

This package provides functionality for doing Event Studies from R by using EventStudyTools.com API interface, parsing results, and visualize them.

Details

To learn more about EventStudy visit project website: www.eventstudytools.com or start with the vignettes: `browseVignettes(package = "EventStudy")`

EventStudyAddin	<i>RStudio Addin for performing an Event Study</i>
-----------------	--

Description

Call this as an addin to perform an Event Study on an interface in R. The interface is similar to our Event Study web interface www.eventstudytools.com.

Usage

```
EventStudyAddin()
```

Description

R interface for performing Event Studies on www.eventstudytools.com. Please get a free API key from our website: <https://www.eventstudytools.com/api-key>.

For more details see the help vignette: `vignette("introduction_eventstudy", package = "EventStudy")`

Usage

`EventStudyAPI`

Format

`R6Class` object

Usage

For usage details see **Methods, Arguments, and Examples** sections.

Methods

`new(apiServerUrl)` This method is used to create an object of this class with `apiServerUrl` as the url to the EventStudyTools server

`authentication(apiKey)` This method is used to authenticate at `apiServerUrl`. A valid APIkey is required. You can download a free key on our website: www.eventstudytools.com

`performEventStudy(estParam)` This method starts an Event Study. This method does all the analysis work for you

`performDefaultEventStudy()` This method starts a default Event Study. It is a wrapper around `performEventStudy`

`processTask()` This method starts the Event Study calculation on the server (after files are uploaded).

`configureTask(input)` This method configures the Event Study. `input` is an `ApplicationInputInterface` `R6` object, e.g. `ARC` configuration class

`uploadFile(fileKey, fileName)` This method links to the file to upload. `fileKey` is the key of the file. Valid values are: `request_file`, `firm_data`, and `market_data`. `fileName` file name to upload.

`commitData()` This method commits the data to the server

`getTaskStatus()` Check if calculation is finished

`getTaskResults(destDir = getwd())` Downloads the result files of the Event Study to `destDir` (Default: current working directory).

Arguments

eventstudyapi An EventStudyAPI object
apiServerUrl URL to the API endpoint
apiKey Key for authentication
input An ApplicationInputInterface object.
fileKey Type of input file: `request_file`, `firm_data`, and `market_data`
fileName Data filename
destDir Directory for saving result files

Examples

```
## Not run:
apiKey <- "{Please insert your aPI key here}"

The URL is already set by default
options(EventStudy.KEY = apiKey)

# initialize object
estSetup <- EventStudyAPI$new()

# get S&P500 example data
getSP500ExampleFiles()

# set Event Study parameters
estType <- "arc"
dataFiles <- c("request_file" = "01_RequestFile.csv",
            "firm_data"     = "02_firmData.csv",
            "market_data"   = "03_MarketData.csv")
resultPath <- "results"

# Perform Event Study
estResult <- estSetup$performDefaultEventStudy(estType      = estType,
                                                dataFiles   = dataFiles,
                                                destDir    = resultPath)

## End(Not run)
```

EventStudyApplicationInput

Abnormal Return Calculation (ARC) API Wrapper

Description

This R6 class serializes an Event Study parameter class to a list structure. This is an abstract class for Event Study applications (Return, Volatility, and Volume Event Studies). It is not intended to use this class directly. Please use: [ARCAApplicationInput](#).

Usage

```
EventStudyApplicationInput
```

Format

R6Class object.

Methods

\$new() Constructor for EventStudyApplicationInput

\$setup() Setup the parameter list

getSP500ExampleFiles *This function copies the three csv files to the actual working directory. This example data is used as motivation for using Event Studies for Additions / Deletions to market indices.*

Description

For more details see the help vignette: vignette("introduction_eventstudy", package = "EventStudy")

Usage

```
getSP500ExampleFiles(targetDir = getwd())
```

Arguments

targetDir directory to save example files

Details

or on our website: <https://www.eventstudytools.com/mergers-acquisitions>

Examples

```
## Not run:  
getSP500ExampleFiles("data")  
  
## End(Not run)
```

ResultParser	<i>Parses request and results files returned from our Event Study API interface.</i>
--------------	--

Description

This result file parser works currently only with csv files. Please read the vignette for further details (coming soon). We will restructure our result reports soon. So, this function may change dramatically. This object can be used for plotting your results.

Usage

```
ResultParser
```

Format

[R6Class](#) object.

Methods

- `new(dir)` This method is used to create object of this class with `dir` as the directory of result files.
- `parseReport(path = "analysis_report.csv")` This method parses the analysis report file (`analysis_report.csv`).
- `parseAR(path = "ar_results.csv")` This method parses the abnormal return file (`ar_results.csv`). Furthermore, it triggers `parseReport` and join firm and index name.
- `parseCAR(path = "car_results.csv")` This method parses the cumulative abnormal return file (`ar_results.csv`). Furthermore, it triggers `parseReport` and join firm and index name.

Examples

```
## Not run:
# Assume you already performed an Event Study and result files are saved in
# the actual working directory.
estParser <- ResultParser$new()

# parse request file
estParser$parseRequestFile("01_RequestFile.csv")

# parse result files
estParser$parseReport("Analysis report.csv")
estParser$parseAR("AR results.csv")
estParser$parseAAR("AAR results.csv")

## End(Not run)
```

Index

*Topic **datasets**

 ARCAApplicationInput, [3](#)
 AVCApplicationInput, [5](#)
 AVyCApplicationInput, [7](#)
 EventStudyAPI, [11](#)
 EventStudyApplicationInput, [12](#)
 ResultParser, [14](#)

 aarPlot, [2](#)
 ARCAApplicationInput, [3](#), [12](#)
 arPlot, [4](#)
 AVCApplicationInput, [5](#)
 AVyCApplicationInput, [7](#)

 checkFile, [8](#)
 checkFiles, [9](#)

 estAPIKey, [10](#)
 EventStudy, [10](#)
 EventStudy-package (EventStudy), [10](#)
 EventStudyAddin, [10](#)
 EventStudyAPI, [11](#)
 EventStudyApplicationInput, [12](#)

 getSP500ExampleFiles, [13](#)

 R6Class, [6](#), [7](#), [11](#), [13](#), [14](#)
 ResultParser, [14](#)