

Package ‘FiSh’

December 16, 2019

Type Package

Title Fisher-Shannon Method

Version 1.0

Author Fabian Guignard [aut],
Mohamed Laib [aut, cre]

Maintainer Mohamed Laib <laib.med@gmail.com>

Description Proposes non-parametric estimates of the Fisher information measure and the Shannon entropy power. The state-of-the-art studies related to the Fisher-Shannon measures, with new analytical formulas for positive unimodal skewed distributions are presented in Guignard et al. <arXiv:1912.02452>. A 'python' version of this work is available on 'github' and 'PyPi' ('FiShPy').

Imports fda.usc, KernSmooth

License MIT + file LICENSE

URL <https://FiShInfo.github.io/>

Encoding UTF-8

LazyData true

RoxxygenNote 6.1.1

Note The authors are grateful to Mikhail Kanevski, Federico Amato and Luciano Telesca for many fruitful discussions about the use and the application of Fisher-Shannon method.

NeedsCompilation no

Repository CRAN

Date/Publication 2019-12-16 14:00:09 UTC

R topics documented:

FiSh-package	2
nsrk	3
SEP_FIM	3

Index

5

Description

Proposes non-parametric estimates of the Fisher information measure and the Shannon entropy power. The state-of-the-art studies related to the Fisher-Shannon measures, with new analytical formulas for positive unimodal skewed distributions are presented in Guignard et al. <arXiv:1912.02452>. A 'python' version of this work is available on 'github' and 'PyPi' ('FiShPy').

Details

This R code was developed and used for the following paper:

F. Guignard, M. Laib, F. Amato, M. Kanevski, Advanced analysis of temporal data using Fisher-Shannon information: theoretical development and application in geosciences, [arXiv:1912.02452](#).

Author(s)

Fabian Guignard <fabian.guignard@bluemail.ch> and

Mohamed Laib <laib.med@gmail.com>

Maintainer: Mohamed Laib <laib.med@gmail.com>

References

- S. J. Sheather and M. C. Jones (1991). A reliable data-based bandwidth selection method for kernel density estimation. *Journal of the Royal Statistical Society, Series B*, 53, 683 - 690.
- M. P. Wand and M. C. Jones (1995). *Kernel Smoothing*. Chapman and Hall, London.
- C. Vignat, J.F Bercher (2003). Analysis of signals in the Fisher–Shannon information plane, *Physics Letters A*, 312, 190, 27 – 33.
- F. Guignard, M. Laib, F. Amato, M. Kanevski, Advanced analysis of temporal data using Fisher-Shannon information: theoretical development and application in geosciences, [arXiv:1912.02452](#).

See Also

Useful links:

- <https://FiShInfo.github.io/>

nsrk*Normal scale rule for kernel density estimation*

Description

Bandwidth selector for non-parametric estimation. Estimates the optimal AMISE bandwidth using the Normal Scale Rule with Gaussian kernel.

Usage

```
nsrk(x, log_trsf=FALSE)
```

Arguments

- | | |
|----------|--|
| x | Univariate data. |
| log_trsf | Logical flag: if TRUE the data are log-transformed (usually used for skewed positive data). By default log_trsf = FALSE. |

Value

The bandwidth value.

References

M. P. Wand and M. C. Jones, (1995). Kernel Smoothing. Chapman and Hall, London.

Examples

```
x <- rnorm(1000)
h <- nsrk(x)
```

SEP_FIM

Fisher-Shannon method

Description

Non-parametric estimates of the Shannon Entropy Power (SEP), the Fisher Information Measure (FIM) and the Fisher-Shannon Complexity (FSC), using kernel density estimators with Gaussian kernel.

Usage

```
SEP_FIM(x, h, log_trsf=FALSE, resol=1000, tol = .Machine$double.eps)
```

Arguments

<code>x</code>	Univariate data.
<code>h</code>	Value of the bandwidth for the density estimate
<code>log_trsf</code>	Logical flag: if TRUE the data are log-transformed (used for skewed data), in this case the data should be positive. By default, <code>log_trsf = FALSE</code> .
<code>resol</code>	Number of equally-spaced points, over which function approximations are computed and integrated.
<code>tol</code>	A tolerance to avoid dividing by zero values.

Value

A table with one row containing:

- SEP Shannon Entropy Power.
- FIM Fisher Information Measure.
- FSC Fisher-Shannon Complexity

References

F. Guignard, M. Laib, F. Amato, M. Kanevski, Advanced analysis of temporal data using Fisher-Shannon information: theoretical development and application in geosciences, [arXiv:1912.02452](https://arxiv.org/abs/1912.02452).

Examples

```
library(KernSmooth)
x <- rnorm(1000)
h <- dpik(x)
SEP_FIM(x, h)
```

Index

`FiSh` (`FiSh`-package), [2](#)

`FiSh`-package, [2](#)

`nsrk`, [3](#)

`SEP_FIM`, [3](#)