

Package ‘GNAR’

May 31, 2020

Type Package

Title Methods for Fitting Network Time Series Models

Version 1.1.0

Date 2020-06-01

Author Kathryn Leeming [aut],
Guy Nason [aut],
Matt Nunes [aut, cre],
Marina Knight [ctb]

Maintainer Matt Nunes <nunesrpackages@gmail.com>

Description Simulation of, and fitting models for, Generalised Network Autoregressive (GNAR) time series models which take account of network structure. Such models are described in Knight et al. (2016), see <arXiv:1603.03221>.

Depends R (>= 2.10), igraph, wordcloud

License GPL-2

Encoding UTF-8

LazyData true

NeedsCompilation no

Repository CRAN

Date/Publication 2020-05-31 21:10:02 UTC

R topics documented:

AIC.GNARfit	2
as.matrix.GNARnet	3
BIC.GNARfit	4
coef.GNARfit	5
fitted.GNARfit	5
fiveNode	6
gdpVTS	7
GNAR	7
GNARdesign	8

GNARfit	9
GNARsim	10
GNARtoigraph	11
igraphtoGNAR	12
is.GNARfit	13
is.GNARnet	13
logLik.GNARfit	15
matrixtoGNAR	16
na.row	16
nobs.GNARfit	17
NofNeighbours	18
plot.GNARnet	19
predict.GNARfit	19
print.GNARfit	20
print.GNARnet	21
residToMat	21
residuals.GNARfit	22
seed.nos	23
seedToNet	23
simulate.GNARfit	24
summary.GNARfit	25
summary.GNARnet	25
vcov.GNARfit	26
vswind	27
windnetplot	28

Index **29**

AIC.GNARfit *Akaike's Information Criterion for GNAR models*

Description

Function calculating AIC for GNARfit models.

Usage

```
## S3 method for class 'GNARfit'
AIC(object, ..., k=2)
```

Arguments

object	a GNARfit object, output from a GNARfit call.
...	additional arguments, not used here.
k	the penalty for the criterion, the default k = 2 is the standard AIC.

Details

Smaller AIC values correspond to better fit.

Value

A numeric value corresponding to the AIC (or other criterion if *k* is set to something other than 2).

Examples

```
#AIC for two different GNAR fits for fiveNet data
#GNAR(2,[1,1])
AIC(GNARfit())
#GNAR(2,[1,0])
AIC(GNARfit(betaOrder=c(1,0)))
```

as.matrix.GNARnet	<i>Converts a GNAR networks into a weighted adjacency matrix</i>
-------------------	--

Description

Takes an input GNARnet and neighbour stage and outputs the corresponding adjacency matrix.

Usage

```
## S3 method for class 'GNARnet'
as.matrix(x, stage=1, normalise=FALSE, ...)
```

Arguments

x	the network GNARnet object associated with the time series, containing a list with entries \$edges and \$dist.
stage	the neighbour set that the adjacency matrix is created for.
normalise	whether to normalise each to non-zero row to have sum one.
...	additional arguments, unused here.

Details

S3 method for class "GNARnet".

With normalisation this is a non-invertible transform. See [NofNeighbours](#) for neighbour set definition.

Value

as.matrix performed on a GNARnet returns a square matrix with the number of rows and columns equal to the length of the \$edges list. Entry *i*, *j* of the matrix will be non-zero if node *j* is in the stage neighbour set of *i*.

Examples

```
#fiveNet as an adjacency matrix
as.matrix(fiveNet)
```

BIC.GNARfit

Bayesian Information Criterion for GNAR models

Description

Function calculating BIC for GNARfit models.

Usage

```
## S3 method for class 'GNARfit'
BIC(object, ...)
```

Arguments

object a GNARfit object, output from a [GNARfit](#) call.
... additional arguments, not used here.

Details

Smaller BIC values correspond to better fit.

Value

A numeric value corresponding to the BIC.

Examples

```
#BIC for two different GNAR fits for fiveNet data
#GNAR(2,[1,1])
BIC(GNARfit())
#GNAR(2,[1,0])
BIC(GNARfit(betaOrder=c(1,0)))
```

coef.GNARfit	<i>Function to return coefficients of GNARfit objects</i>
--------------	---

Description

coef.GNARfit returns the vector of coefficients from a GNARfit object.

Usage

```
## S3 method for class 'GNARfit'  
coef(object,...)
```

Arguments

object	the output of a GNARfit call
...	additional arguments, unused here.

Details

S3 method for class "GNARfit".

Value

coef.GNARfit returns a vector of coefficient values.

Examples

```
#get the coefficients of the fiveNode data GNAR fit  
coef(GNARfit())
```

fitted.GNARfit	<i>Function to return fitted values of GNARfit objects</i>
----------------	--

Description

fitted.GNARfit returns the fitted values of a GNARfit object as a matrix.

Usage

```
## S3 method for class 'GNARfit'  
fitted(object,...)
```

Arguments

object	the output of a GNARfit call
...	additional arguments, unused here.

Details

S3 method for class "GNARfit".

Value

fitted.GNARfit returns a `ts` object of fitted values, with `t-alphaOrder` rows and `nodes` columns.

Examples

```
#get the fitted values of the fiveNode GNAR fit
fitted(GNARfit())
```

fiveNode

Example Network Time Series

Description

A multivariate time series `fiveVTS` and corresponding network `fiveNet`.

Usage

```
data("fiveNode")
```

Format

This dataset contains two R objects:

`fiveVTS` is a `ts` object with a matrix of 200 rows (`t=200`) and 5 columns (`n=5`) `fiveNet` is a GNAR-net object containing `$edges` and `$dist`.

`edges` is a list of length five, with `edges[[i]]` containing the vertices that node `i` is connected to.

`dist` is a list of length five, with `dist[[i]]` containing the length of the vertices that node `i` is connected to.

Examples

```
plot(fiveNet)
image(fiveVTS)
```

gdpVTS

Differenced GDP values for 35 countries

Description

This dataset is from the OECD (OECD (2018), Quarterly GDP (indicator). <doi:10.1787/b86d1fc8-en> (Accessed on 29 January 2018)) and is differenced annual growth rate for 35 countries for 1962-2013.

Usage

gdpVTS

Format

gdpVTS is a `ts` object with a matrix of 52 rows ($t=52$) and 35 columns ($n=35$)

Examples

```
#Plot using 'ts' S3 function, can only plot up to 10 columns at once
plot(gdpVTS[,1:5])
```

```
#Plot as heatmap
image(gdpVTS)
```

GNAR

GNAR package

Description

A package to fit, predict, and simulate time series using the Generalised Network AutoRegressive (GNAR) model. The main functions are `GNARfit`, which fits the model to a time series and network(s), S3 method `predict.GNARfit` which predicts from a fitted GNAR model, and `GNARsim` which simulates from a GNAR model with specified parameters. For details of the model, see `GNARfit`. The package also contains an example network time series in data file `fiveNode`, with network `fiveNet`, and simulated time series `fiveVTS`.

References

Knight, M.I., Nunes, M.A. and Nason, G.P. (2015) Modelling, detrending and decorrelation of network time series. [arXiv preprint](#).

Knight, M.I., Leeming, K., Nason, G.P. and Nunes, M. A. (2019) Generalised Network Autoregressive Processes and the GNAR package. *Journal of Statistical Software (to appear)*.

GNARdesign

Function to create the GNAR design matrix

Description

Creates the design matrix necessary for fitting the GNAR model.

Usage

```
GNARdesign(vts = GNAR::fiveVTS, net = GNAR::fiveNet, alphaOrder = 2, betaOrder = c(1,1),
  fact.var = NULL, globalalpha=TRUE, tvnets=NULL, netsstart=NULL)
```

Arguments

<code>vts</code>	a matrix or <code>ts</code> object containing the multivariate time series to be modelled. The i, j entry of this matrix should be for time i and vertex/node j .
<code>net</code>	the (first) network associated with the time series, containing a list with entries <code>\$edges</code> and <code>\$dist</code> . This network should have the same number of nodes as the number of columns of the <code>vts</code> matrix.
<code>alphaOrder</code>	a non-negative integer specifying the maximum time-lag to model.
<code>betaOrder</code>	a vector of length <code>alphaOrder</code> specifying the maximum neighbour set to model at each of the time-lags.
<code>fact.var</code>	a vector of factors indicating which nodes belong to each set with different parameters to be fitted.
<code>globalalpha</code>	a TRUE/FALSE value indicating whether to use global alpha parameters.
<code>tvnets</code>	a list of additional networks. Currently only NULL (the static network case) is supported.
<code>netsstart</code>	a vector of times corresponding to the first time points for each network of <code>tvnets</code> . Currently only NULL (the static network case) is supported.

Value

GNARdesign returns a matrix containing $(t - \text{alphaOrder})n_{\text{nodes}}$ rows and a column for each parameter to be fitted. The columns are in time-lag order, eg for GNAR(2,[1,0]) the columns are `alpha1`, `beta1.1`, `alpha2`. When a factor variable is specified the columns are labelled with the factor.

Examples

```
#Design matrix to fit GNAR(2,[1,1]) to the fiveVTS data
GNARdesign()
```


GNARfit

*Fitting function for GNAR models***Description**

Fits the GNAR model to the given inputs using GNARdesign and lm.

Usage

```
GNARfit(vts=GNAR::fiveVTS, net=GNAR::fiveNet, alphaOrder=2, betaOrder=c(1,1),
fact.var=NULL, globalalpha=TRUE, tvnets=NULL, netsstart=NULL, ErrorIfNoNei=TRUE)
```

Arguments

vts	a matrix containing the multivariate time series to be modelled. The i, j entry of this matrix should be for time i and vertex/node j .
net	the (first) network associated with the time series, containing a list with entries \$edges and \$dist. This network should have the same number of nodes as the number of columns of the vts matrix.
alphaOrder	a non-negative integer specifying the maximum time-lag to model.
betaOrder	a vector of length alphaOrder specifying the maximum neighbour set to model at each of the time-lags.
fact.var	a vector of factors indicating which nodes belong to different sets with different parameters to be fitted.
globalalpha	a TRUE/FALSE value indicating whether to use global alpha parameters.
tvnets	a list of additional networks. Currently only NULL (the static network case) is supported.
netsstart	a vector of times corresponding to the first time points for each network of tvnets. Currently only NULL (the static network case) is supported.
ErrorIfNoNei	a TRUE/FALSE value indicating whether to stop the function call with an error if betaOrder specifies more neighbour sets than exist in the network. If FALSE the function will continue and some parameters will be NA.

Details

The GNAR model of order (p, S) is defined as

$$X_{i,t} = \sum_{j=1}^p \left(\alpha_{i,j} X_{i,t-j} + \sum_{c=1}^C \sum_{r=1}^{S_j} \beta_{j,r,c} \sum_{q \in N_t^{(r)}(i)} \omega_{i,q,c}^{(t)} X_{q,t-j} \right) + u_{i,t}$$

where p is the maximum time lag, $S = (S_1, \dots, S_p)$ and S_j is the maximum stage of neighbour dependence for time lag j , $N_t^{(r)}(i)$ is the r th stage neighbour set of node i at time t , $\omega_{i,q,c}^{(t)}$ is the connection weight between node i and node q at time t if the path corresponds to covariate c . Here,

we consider a sum from one to zero to be zero and $\{u_{i,t}\}$, are assumed to be independent and identically distributed at each node i , with mean zero and variance σ_i^2 . Currently, only a single network GNAR model can be fitted. The connection weight, $\omega_{i,q,c}^{(t)}$, is the inverse of the distance between nodes i and q , normalised so that they sum to 1 for each i, t . See [is.GNARnet](#) for GNARnet object information and example construction.

Value

mod	the lm output from fitting the GNAR model.
y	the original response values, with NAs left in.
dd	the output of GNARdesign containing the design matrix, with NAs left in.
frbic	inputs to other GNAR functions.

References

Knight, M.I., Nunes, M.A. and Nason, G.P. Modelling, detrending and decorrelation of network time series. [arXiv preprint](#).

Knight, M.I., Leeming, K., Nason, G.P. (2019) and Nunes, M. A. Generalised Network Autoregressive Processes and the GNAR package. *Journal of Statistical Software (to appear)*.

Examples

```
#Fit the GNAR(2,[1,1]) model to the fiveVTS data
GNARfit()

#Convert the residuals to matrix form
residToMat(GNARfit())$resid
```

GNARsim

Simulates a GNAR process

Description

Simulates a GNAR process with Normally distributed innovations.

Usage

```
GNARsim(n=200, net=GNAR::fiveNet, alphaParams=list(c(rep(0.2,5))),
  betaParams=list(c(0.5)), sigma=1, tvnets=NULL, netsstart=NULL)
```

Arguments

n	time length of simulation.
net	network used for the GNAR simulation.
alphaParams	a list containing vectors of auto-regression parameters for each time-lag.
betaParams	a list of equal length as alphaParams containing the network-regression parameters for each time-lag.
sigma	the standard deviation for the innovations.
tvnets	Only NULL is currently supported.
netsstart	Only NULL is currently supported.

Details

Parameter lists should not be NULL, set unused parameters to be zero. See [GNARfit](#) for model description.

Value

GNARsim returns the multivariate time series as a `ts` object, with n rows and a column for each of the nodes in the network.

References

Knight, M.I., Nunes, M.A. and Nason, G.P. Modelling, detrending and decorrelation of network time series. [arXiv preprint](#).

Knight, M.I., Leeming, K., Nason, G.P. and Nunes, M. A. (2019) Generalised Network Autoregressive Processes and the GNAR package. *Journal of Statistical Software (to appear)*.

Examples

```
#Simulate a GNAR(1,[1]) process with the fiveNet network
GNARsim()
```

GNARtoigraph

Converts a GNAR network to a weighted igraph object

Description

Takes an input network and neighbour stage and returns it in [igraph](#) form.

Usage

```
GNARtoigraph(net=GNAR::fiveNet, stage=1, normalise=FALSE)
```

Arguments

net	a GNARnet object containing \$edges and dist.
stage	the neighbour set that the adjacency matrix is created for.
normalise	whether to normalise each to non-zero row to have sum one.

Details

With normalisation this is a non-invertible transform. See [NofNeighbours](#) for neighbour set definition. See [is.GNARnet](#) for GNARnet object information and example construction.

Value

GNARtoigraph returns an 'igraph' object with weights as the inverse distances of the input network.

Examples

```
#fiveNet as an igraph object
GNARtoigraph()
```

 igraphtoGNAR

Converts an igraph to GNAR network

Description

Converts an 'igraph' to the GNARnet form for use as an input to GNAR functions.

Usage

```
igraphtoGNAR(ig)
```

Arguments

ig	an 'igraph' object.
----	---------------------

Details

The values in the \$dist list are the reciprocal of the values from the weighted adjacency matrix.

Value

igraphtoGNAR returns a GNARnet: a list with elements \$edges and \$dist.

Examples

```
#Convert fiveNet to igraph and back again
igraphtoGNAR(GNARtoigraph(fiveNet))
```

is.GNARfit *Function to check GNARfit objects*

Description

is.GNARfit returns either TRUE or FALSE according to a series of GNARfit checks.

Usage

```
is.GNARfit(x)
```

Arguments

x the object to be tested

Details

The is.GNARfit function checks whether the object passes a series of tests that correspond to it being the output of [GNARfit](#):

- Is it a list containing \$mod and \$frbic
- Does it contain either \$y and \$dd or \$ys and \$ds
- Is \$mod a [lm](#) object
- Does \$frbic have the components to calculate the BIC with [BIC.GNARfit](#)

Value

is.GNARfit returns TRUE or FALSE corresponding to passing the above tests.

Examples

```
#check that the example fit meets the criteria above
is.GNARfit(GNARfit())
```

is.GNARnet *Functions to check and create GNARnet objects*

Description

is.GNARnet returns either TRUE or FALSE according to a series of GNARnet checks. as.GNARnet returns a GNARnet object from an input weights matrix, 'igraph' object, or a GNARnet without assigned class.

Usage

```
is.GNARnet(x)
as.GNARnet(x)
```

Arguments

x the network to be tested or object to be converted

Details

The `is.GNARnet` function checks whether the network passes a series of tests:

- Is it a list containing `$edges` and `$dist`
- Are the `$edges` and `$dist` lists of the same length
- Are each of the elements of `$edges` the same length as the corresponding `$dist` element
- Do the edges only contain valid entries, 1,...,nnodes (or NULL)
- Is it labelled as GNARnet class
- Are no duplicate edges present
- Are all distances positive
- Are there no self-loops in the network

The `as.GNARnet` function converts [igraph](#) objects to GNARnet form, other possible inputs are adjacency matrices, and lists with `$edges` and `$dist` entries of the correct form.

Value

`is.GNARnet` returns TRUE or FALSE corresponding to passing the above tests. `as.GNARnet` returns a GNARnet object.

Examples

```
#check that the example network meets the criteria above
is.GNARnet(fiveNet)

#convert to igraph and back again
as.GNARnet(GNARtoigraph(fiveNet))

#generate a new network with three nodes
#edges 1->2, 2->1, 2->3
#dist 1, 2, 1
#note 1->2 and 2->1 are of different lengths
threeEdge <- list(c(2), c(1,3), NULL)
threeDist <- list(c(1), c(2,1), NULL)
threeNet <- list(edges=threeEdge, dist=threeDist)
#check if this is a GNARnet
is.GNARnet(threeNet)
#use as.GNARnet to change the class
threeNet <- as.GNARnet(threeNet)
#check if this is a GNARnet now
is.GNARnet(threeNet)
```

logLik.GNARfit	<i>Log-likelihood method for GNARfit objects</i>
----------------	--

Description

Returns the log-likelihood for a GNARfit object.

Usage

```
## S3 method for class 'GNARfit'
logLik(object,...)
```

Arguments

object	A GNARfit object generated by a GNARfit call.
...	Optional additional arguments, not used here.

Details

S3 method for the GNARfit class. The function returns the value of

$$-TN/2 \log(2\pi) - T/2 \log(|\Sigma|) - 1/2 \text{trace}(E\Sigma^{-1}E'),$$

where T is the time length of the observations, N is the number of nodes, $\Sigma = EE'/T$ is the estimated covariance matrix and E is the matrix of residuals.

Value

A logLik object.

Examples

```
#calculate log-likelihood for fiveNode data
#global alphas
logLik(GNARfit())
#individual alphas
logLik(GNARfit(globalalpha=FALSE))
```

matrixtoGNAR	<i>Converts an adjacency matrix to GNAR network</i>
--------------	---

Description

Converts an adjacency matrix to the GNARnet form for use as an input to GNAR functions.

Usage

```
matrixtoGNAR(input.mat)
```

Arguments

input.mat	an adjacency matrix whose dimension equals the number of nodes in the resulting network.
-----------	--

Details

The values in the \$dist list are the reciprocal of the values from the weighted adjacency matrix. Any self-loops (diagonal entries) and negatively weighted edges are removed.

Value

matrixtoGNAR returns a GNARnet list with elements \$edges and \$dist.

Examples

```
#Convert fiveNet to an adjacency matrix and back again  
matrixtoGNAR(as.matrix(fiveNet))
```

na.row	<i>Identifies which rows of a matrix have NAs</i>
--------	---

Description

Returns a vector with elements TRUE/FALSE identifying which rows contain NA elements.

Usage

```
na.row(mat)
```

Arguments

mat	a matrix object.
-----	------------------

Details

This function is used in the unstacking of residuals into a residual matrix and replacing NAs where they were previously present.

Value

na.row returns a vector of length equal to the number of rows in mat. Each element is either TRUE or FALSE.

Examples

```
#Check if there are and NAs in fiveVTS
na.row(fiveVTS)
```

nobs.GNARfit	<i>Function to return the number of observations input to GNARfit objects</i>
--------------	---

Description

nobs returns the number of observations (T) of the input multivariate time series in the GNARfit function.

Usage

```
## S3 method for class 'GNARfit'
nobs(object,...)
```

Arguments

object the output of a GNARfit or GNARpredict call
... additional arguments, unused here.

Details

S3 method for class "GNARfit".

Value

An integer specifying the number of rows in the input vts to the [GNARfit](#) function.

Examples

```
#observations of example fiveVTS
nobs(GNARfit())
#check this is the same as number of rows in fiveVTS
all.equal(nobs(GNARfit()), nrow(fiveVTS))
```

NofNeighbours	<i>Calculates stage-neighbours of a network</i>
---------------	---

Description

Calculates neighbour sets of a particular node in the network and their distances.

Usage

```
NofNeighbours(node=1, stage=2, net=GNAR::fiveNet)
```

Arguments

node	is an integer specifying which node to calculate the neighbours of.
stage	is an integer specifying the maximum neighbour-stage to calculate to.
net	a GNARnet object with edge list and distance list.

Details

Note that the distances are calculated as the sum along the shortest path; do not use this with a weights (rather than distance) list. Stage- r neighbours of node i are denoted $N^{(r)}(i)$, and are nodes that are r edges (but no fewer) away from i . Hence stage-1 neighbours are the immediate neighbours, stage-2 neighbours are the neighbours of neighbours and so on.

Value

edges	is a list of length stage, where edges[[i]] is a vector containing the nodes that are stage- i neighbours of node.
dist	is a list of length stage, where dist[[i]] is a vector containing the distances from node to its stage- i neighbours, with ordering as in edges[[i]].

Examples

```
#First and second stage neighbours of node 1 in fiveNet
NofNeighbours()
```

plot.GNARnet	<i>Plot function for GNAR networks</i>
--------------	--

Description

Plots a GNAR network using the 'igraph' package.

Usage

```
## S3 method for class 'GNARnet'
plot(x, ...)
```

Arguments

x	the networkGNARnet object associated with the time series, containing a list with entries \$edges and \$dist.
...	additional arguments for the igraph plotting function, see plot.igraph .

Details

S3 method for class "GNARnet".

Examples

```
#Plot fiveNet
plot(fiveNet)
```

predict.GNARfit	<i>Prediction of a GNARfit object</i>
-----------------	---------------------------------------

Description

Predicts future observations from a GNARfit object, based on the fitted GNAR model.

Usage

```
## S3 method for class 'GNARfit'
predict(object, n.ahead=1, ...)
```

Arguments

object	the output of a GNARfit call
n.ahead	the time length of the predictions
...	further arguments passed to the simulate.GNARfit function, such as seed

Details

S3 method for class "GNARfit". This function calls [simulate.GNARfit](#).

Value

A multivariate time series of dimension `n.ahead` x `nnodes`.

Examples

```
#simulate 5 future observations from fiveVTS
predict(GNARfit(), n.ahead=5)
```

`print.GNARfit`

Function to print the model and coefficients of GNARfit objects

Description

`print.GNARfit` prints model, call, and coefficients of a GNARfit object.

Usage

```
## S3 method for class 'GNARfit'
print(x,...)
```

Arguments

`x` the output of a [GNARfit](#) call
`...` additional arguments, unused here.

Details

S3 method for class "GNARfit".

Examples

```
#print the information of the fiveNode GNAR fit
print(GNARfit())
```

```
print.GNARnet
```

Print function for GNAR networks

Description

Prints information about a GNAR network.

Usage

```
## S3 method for class 'GNARnet'
print(x, ...)
```

Arguments

x the network GNARnet object associated with the time series, containing a list with entries \$edges and \$dist.
 ... additional arguments, unused here.

Details

S3 method for class "GNARnet".

Examples

```
#print fiveNet information
print(fiveNet)
```

```
residToMat
```

Converts the output of a GNARfit call to fitted and residual value matrices

Description

Unstacks the entries of the GNARfit fitted and residual values to return matrices of a similar form to the multivariate time series input.

Usage

```
residToMat(GNARobj=GNARfit(), nnodes=5)
```

Arguments

GNARobj the output from the [GNARfit](#) function
 nnodes the number of nodes in the original network time series

Details

This function also replaces the NAs that were removed in fitting.

Value

`resid` is the matrix of residual values, with `t-alphaOrder` rows and `nnodes` columns.
`fit` is the matrix of fitted values, with `t-alphaOrder` rows and `nnodes` columns.

Examples

```
#Get residual and fitted matrices from GNARpredict fit of fiveVTS
residToMat()
```

`residuals.GNARfit` *Function to return residuals of GNARfit objects*

Description

`residuals.GNARfit` returns the residuals of a GNARfit object as a matrix.

Usage

```
## S3 method for class 'GNARfit'
residuals(object,...)
```

Arguments

`object` the output of a [GNARfit](#) call
`...` additional arguments, unused here.

Details

The function first checks if the object is of GNARfit class, then uses [residToMat](#) to return the residuals.

Value

`residuals.GNARfit` returns a 'ts' object of residuals, with `t-alphaOrder` rows and `nnodes` columns.

Examples

```
#get the residuals of the fiveNode GNAR fit
residuals(GNARfit())
```

seed.nos	<i>Vector of seed numbers</i>
----------	-------------------------------

Description

Seed numbers for reproducible random graphs.

Usage

```
seed.nos
```

Format

seed.nos is a vector of length 10,000 containing integers.

Examples

```
g <- seedToNet(seed.nos[1], nnodes=35, graph.prob=0.15)
plot(g, vertex.label=colnames(gdpVTS), vertex.size=0)
```

seedToNet	<i>Produces a random network from a seed value</i>
-----------	--

Description

Produces a reproducible undirected Erdos-Reyni random network using a particular seed value.

Usage

```
seedToNet(seed.no, nnodes=34, graph.prob=0.5)
```

Arguments

seed.no	a valid number to set the seed to.
nnodes	the number of nodes in the produced network.
graph.prob	the probability that each pair of nodes is connected.

Details

graph.prob effectively controls the sparsity of the network. All distances are set to 1.

Value

A GNARnet object.

Examples

```
#Generate the random graph from seed 10, with 5 nodes and connection prob 0.5
seedToNet(10,nnodes=5,graph.prob=0.5)
```

```
simulate.GNARfit      Function to simulate from a GNARfit object
```

Description

Simulates from a GNARfit object, either creating a new series or future observations of the original series based upon the fitted GNAR model.

Usage

```
## S3 method for class 'GNARfit'
simulate(object, nsim=object$frbic$time.in, seed=NULL,
         future=TRUE, set.noise=NULL, allcoefs=FALSE, ...)
```

Arguments

object	the output of a GNARfit call
nsim	the time length of the simulations
seed	either NULL, or a value to set the seed to
future	whether the simulations follow on from the original time series (TRUE), or if FALSE the simulations are a new series.
set.noise	a value to set the standard deviation of the noise to, or if NULL, the estimated standard deviation from the input series will be used.
allcoefs	if TRUE, all fitted coefficients will be used, if FALSE only the significant (p-val < 0.05) coefficients will be used.
...	additional arguments, unused here.

Details

S3 method for class "GNARfit".

Value

A multivariate time series of dimension nsim x nnodes.

Examples

```
#simulate 5 future observations from fiveVTS
simulate(GNARfit(), nsim=5)
```

summary.GNARfit	<i>Returns model summary for a GNAR model fit</i>
-----------------	---

Description

Returns the summary of a GNARfit object, including BIC.

Usage

```
## S3 method for class 'GNARfit'
summary(object, ...)
```

Arguments

object	output of a GNARfit call.
...	additional arguments, unused here.

Details

The output is the summary of the fit using [summary.lm](#), and BIC calculated using [BIC.GNARfit](#).

Value

summary.GNARfit prints the model summary and the value of the BIC.

Examples

```
#summary for the GNAR(2,[1,1]) model using GNARfit on fiveVTS
summary(GNARfit())
```

summary.GNARnet	<i>Summary function for GNAR networks</i>
-----------------	---

Description

Prints brief information about a GNAR network.

Usage

```
## S3 method for class 'GNARnet'
summary(object, ...)
```

Arguments

object	the networkGNARnet object associated with the time series, containing a list with entries \$edges and \$dist.
...	additional arguments, unused here.

Details

S3 method for class "GNARnet".

Examples

```
#print fiveNet summary information
summary(fiveNet)
```

vcov.GNARfit

Calculate variance-covariance matrix for a fitted GNARfit object

Description

Returns the variance-covariance matrix of the parameters of a GNARfit object.

Usage

```
## S3 method for class 'GNARfit'
vcov(object, ...)
```

Arguments

object a GNARfit object, the output from a [GNARfit](#) call.
... further arguments passed to [vcov](#).

Details

S3 method for class "GNARfit".

Value

A matrix of estimated covariances between the parameter estimates, this is calculated using [vcov](#) for [lm](#) objects.

Examples

```
#covariance matrix of fiveNode fit
vcov(GNARfit())
```

vswind

Wind Speed example network time series

Description

A suite of data objects concerning wind speed analysis. The dataset contains a multivariate time series of wind speeds, two network descriptions, a vector of names for weather stations, and the coordinates of the weather stations.

Usage

```
data("vswind")
```

Format

This dataset contains six R objects:

vswindts is a `ts` object with a matrix of 721 rows ($t=721$) and 102 columns ($n=102$). This corresponds to 721 observations made through time at 102 weather stations. vswindnetD is a GNARnet object containing `$edges` and `$dist`.

edges is a list of length 102, with `edges[[i]]` containing the vertices that node i is connected to.

dist is a list of length 102, with `dist[[i]]` containing the length of the vertices that node i is connected to. vswindnet is the same as vswindnetD except that all the distances are replaced by 1. vswindnames is a character vector of length 102 containing the wind speed site names and vswindcoords is a matrix with 102 rows (one for each wind station) and two columns providing the x and y coordinates of the weather stations.

Source

The base data were obtained from the <http://www.metoffice.gov.uk> UK Met Office Weather Observations Website distributed under the UK Open Government License <http://www.nationalarchives.gov.uk/doc/open-government-licence/version/1/> Contains public sector information licensed under the Open Government Licence v1.0.

See Also

[windnetplot](#)

Examples

```
#  
# The name entry for Bristol  
#  
vswindnames[77]  
#[1] "BRIST"  
#  
# plot the distance network  
#  
## Not run: windnetplot()
```

`windnetplot`*Produce bespoke plot of the wind data network*

Description

Plots the wind speed data network with distance information.

Usage

```
windnetplot()
```

Arguments

None.

Details

The wind speed data is to be found in the [vswind](#) data set. This function contains commands, using functionality from the `wordcloud` package, to plot the network, with node names and edges. Distances between nodes are plotted next to the edges.

See Also

[vswind](#)

Examples

```
## Not run: windplotnet()
```

Index

*Topic **datasets**

- fiveNode, [6](#)
 - vswind, [27](#)
- AIC.GNARfit, [2](#)
as.GNARnet (is.GNARnet), [13](#)
as.matrix.GNARnet, [3](#)
- BIC.GNARfit, [4](#), [13](#), [25](#)
- coef.GNARfit, [5](#)
- fitted.GNARfit, [5](#)
fiveNet, [7](#)
fiveNet (fiveNode), [6](#)
fiveNode, [6](#), [7](#)
fiveVTS, [7](#)
fiveVTS (fiveNode), [6](#)
- gdpVTS, [7](#)
GNAR, [7](#)
GNARdesign, [8](#)
GNARfit, [2](#), [4](#), [5](#), [7](#), [9](#), [11](#), [13](#), [15](#), [17](#), [19–22](#),
[24–26](#)
GNARsim, [7](#), [10](#)
GNARtoigraph, [11](#)
- igraph, [11](#), [14](#)
igraphtoGNAR, [12](#)
is.GNARfit, [13](#)
is.GNARnet, [10](#), [12](#), [13](#)
- lm, [13](#), [26](#)
logLik.GNARfit, [15](#)
- matrixtoGNAR, [16](#)
- na.row, [16](#)
nobs.GNARfit, [17](#)
NofNeighbours, [3](#), [12](#), [18](#)
- plot.GNARnet, [19](#)
plot.igraph, [19](#)
predict.GNARfit, [7](#), [19](#)
print.GNARfit, [20](#)
print.GNARnet, [21](#)
- residToMat, [21](#), [22](#)
residuals.GNARfit, [22](#)
- seed.nos, [23](#)
seedToNet, [23](#)
simulate.GNARfit, [19](#), [20](#), [24](#)
summary.GNARfit, [25](#)
summary.GNARnet, [25](#)
summary.lm, [25](#)
- ts, [6–8](#), [11](#), [27](#)
- vcov, [26](#)
vcov.GNARfit, [26](#)
vswind, [27](#), [28](#)
vswindcoords (vswind), [27](#)
vswindnames (vswind), [27](#)
vswindnet (vswind), [27](#)
vswindnetD (vswind), [27](#)
vswindts (vswind), [27](#)
- windnetplot, [27](#), [28](#)