

Package ‘GSA.UN’

July 10, 2020

Type Package

Title Global Sensitivity Analysis Tool

Version 1.0.0

Maintainer Camila Garcia-Echeverri <cagarciae@unal.edu.co>

Description A tool to sensitivity analysis using SOBOL (Sobol, 1993) and AMA (Dell'Oca et al. 2017 <doi:10.5194/hess-21-6219-2017>) indices.

It allows to identify the most sensitive parameter or parameters of a model.

Depends R (>= 3.4)

Imports stats, e1071, utils

Suggests knitr, rmarkdown

License GPL-2

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

VignetteBuilder knitr

NeedsCompilation no

Author Camila Garcia-Echeverri [aut, cre]
(<<https://orcid.org/0000-0001-8227-7684>>),
Maria Arenas-Bautista [cot] (<<https://orcid.org/0000-0003-1578-5157>>),
Leonardo Donado [cot] (<<https://orcid.org/0000-0002-5479-3419>>)

Repository CRAN

Date/Publication 2020-07-10 09:40:03 UTC

R topics documented:

AMA	2
Bstat	3
CM	4
Cond_Moments	4

data_Bstat	5
GSAtool	6
out_set	7
parameters_set	8
pp_names	8
save_results	9
SOBOL	10

Index	11
--------------	-----------

AMA

AMA indices

Description

This function calculates the AMA indices: AMAE, AMAV, AMAR and AMAK.

Usage

```
AMA(data_Bstat, CM, pp_names, steps = 100)
```

Arguments

data_Bstat	a data frame of dimensions $t \times 6$, here t is the number of temporary steps and each column corresponds to a statistical measure: mean, variance, skewness, kurtosis and excess kurtosis.
CM	A list of arrays, each array corresponds to the conditional moments calculated with the mean, variance, skewness, kurtosis. Each array has dimensions of steps, t , p .
pp_names	vector that contains the names of the parameters (pp)
steps	number of divisions of the parametric range

Value

A list of four matrices, which corresponds to AMAE, AMAV, AMAR and AMAK indices. Each matrix has dimensions of $t \times pp$.

Author(s)

Camila Garcia-Echeverri <cagarciae@unal.edu.co>
 Maria Cristina Areas-Bautista <mcarenasb@unal.edu.co>

Hydrodynamics of the natural media research group - HYDS National University of Colombia - Bogota

References

Dell’Oca, A., Riva, M., & Guadagnini, A. (2017). Moment-based metrics for global sensitivity analysis of hydrological systems. *Hydrology and Earth System Sciences*, 21(12), 6219–6234. <https://doi.org/10.5194/hess-21-6219-2017>

Examples

```
data("data_Bstat", "CM", "pp_names")
AMA_indices <- AMA(data_Bstat, CM, pp_names, steps= 15)
```

Bstat

Basic statistical measures of a mathematical model results

Description

This function calculates the mean, variance, skewness, kurtosis and excess kurtosis of a model output, this output can be given for different temporal periods (days, months or years).

Usage

```
Bstat(out_set)
```

Arguments

`out_set` matrix of dimensions $n \times t$, where n equals the number of runs and t is equal to the number of temporary steps.

Value

a data frame of dimensions $t \times 6$, here t is the number of temporary steps and each column corresponds to a statistical measure: mean, variance, skewness, kurtosis and excess kurtosis.

Author(s)

Camila Garcia-Echeverri <cagarciae@unal.edu.co>

Hydrodynamics of the natural media research group - HYDS National University of Colombia - Bogota

Examples

```
data("out_set")
data_Bstat <- Bstat(out_set)
```

CM	<i>@title First four conditional moments of example data</i>
----	--

Description

@description Data generated by Cond_Moments example

Usage

CM

Format

A list

CM A list of arrays, each array has dimensions of steps, t, pp

Author(s)

Camila Garcia-Echeverri

Cond_Moments	<i>Conditional statistical moments of a model output</i>
--------------	--

Description

This function evaluates the first four statistical moments after grouping the model output by different parametric ranges.

Usage

```
Cond_Moments(parameters_set, out_set, pp_names, steps = 100)
```

Arguments

parameters_set	matrix of dimensions n x pp, where n is the number of runs and pp is the number of parameters.
out_set	matrix of dimensions n x t, where n is the number of runs and t is the number of temporary steps.
pp_names	vector that contains the names of the parameters.
steps	number of divisions of the parametric range.

Value

A list of arrays, each array has dimensions of steps, t, pp.

Author(s)

Camila Garcia-Echeverri <cagarciae@unal.edu.co>
Maria Cristina Areas-Bautista <mcarenasb@unal.edu.co>

Hydrodynamics of the natural media research group - HYDS National University of Colombia -
Bogota

Examples

```
data("parameters_set", "out_set", "pp_names")  
  
CM <- Cond_Moments(parameters_set, out_set, pp_names, steps=15)
```

data_Bstat	<i>@title First four conditional moments of example data</i>
------------	--

Description

@description Data generated with the example of the function Cond_Moments

Usage

```
data_Bstat
```

Format

A data.frame

data_Bstat a data frame of dimensions t x 6

Author(s)

Camila Garcia-Echeverri

Source

Function Bstat

GSAtool

Global Sensitivity Analysis tool

Description

This function performs the global sensitivity analysis starting from the gross results of the model.

Usage

```
GSAtool(  
  parameters_set,  
  out_set,  
  pp_names,  
  steps = 100,  
  save = FALSE,  
  dir = NULL  
)
```

Arguments

<code>parameters_set</code>	matrix of dimensions $n \times pp$, where n is the number of runs and pp is the number of parameters.
<code>out_set</code>	matrix of dimensions $n \times t$, where n is the number of runs and t is the number of temporary steps.
<code>pp_names</code>	a strings vector with the names of the parameters of the model
<code>steps</code>	number of divisions of the parametric range.
<code>save</code>	T to save the results in .csv files, by default <code>save=F</code> .
<code>dir</code>	a directory to save the results

Value

a list containing two outputs: SOBOL and AMA indices.

Author(s)

Camila Garcia-Echeverri <cagarciae@unal.edu.co>
Maria Cristina Areas-Bautista <mcarenasb@unal.edu.co>

Hydrodynamics of the natural media research group - HYDS National University of Colombia - Bogota

References

Dell’Oca, A., Riva, M., & Guadagnini, A. (2017). Moment-based metrics for global sensitivity analysis of hydrological systems. *Hydrology and Earth System Sciences*, 21(12), 6219–6234. <https://doi.org/10.5194/hess-21-6219-2017>

Sobol, I. M. (2001). Global sensitivity indices for nonlinear mathematical models and their Monte Carlo estimates. *Mathematics and Computers in Simulation*, 55(1–3), 271–280. [https://doi.org/10.1016/S0378-4754\(00\)00270-6](https://doi.org/10.1016/S0378-4754(00)00270-6)

Examples

```
data("parameters_set", "out_set", "pp_names")
```

```
GSA_results <- GSAtool(parameters_set, out_set, pp_names, steps = 15, save=FALSE)
```

out_set	<i>@title Results of a sample model</i>
---------	---

Description

@description Output generated with an example mathematical model.

Usage

```
out_set
```

Format

A matrix

out_set a matrix of dimensions 500 x 365 (pp x t), runs of the model x temporary steps (365 days)

References

Arenas-Bautista, M. C. (2020). Integration of Hydrological and Economical Aspects for Water Management in Tropical Regions. Case Study: Middle Magdalena Valley, Colombia. National University of Colombia.

parameters_set *@title Set of parameters randomly generated*

Description

@description It contains 10 parameters

Usage

parameters_set

Format

A matrix

parameters_set a matrix of dimensions 500 x 10 (n x pp), runs of the model x number of parameters

References

Arenas-Bautista, M. C. (2020). Integration of Hydrological and Economical Aspects for Water Management in Tropical Regions. Case Study: Middle Magdalena Valley, Colombia. National University of Colombia.

pp_names *@title Example - parameters names*

Description

@description 10 parameters names.

Usage

pp_names

Format

A value

pp_names a vector of characters

Author(s)

CGE

References

Arenas-Bautista, M. C. (2020). Integration of Hydrological and Economical Aspects for Water Management in Tropical Regions. Case Study: Middle Magdalena Valley, Colombia. National University of Colombia.

save_results	<i>Save GSA results</i>
--------------	-------------------------

Description

This function helps to save the results in .csv format

Usage

```
save_results(  
  SOBOL = NULL,  
  SOBOL_total = NULL,  
  amae = NULL,  
  amav = NULL,  
  amar = NULL,  
  amak = NULL,  
  dir  
)
```

Arguments

SOBOL	SOBOL index
SOBOL_total	SOBOL_total
amae	AMAE index
amav	AMAV index
amar	AMAR index
amak	AMAK index
dir	a directory to save the results

Author(s)

Camila Garcia-Echeverri <cagarciae@unal.edu.co>

Hydrodynamics of the natural media research group - HYDS National University of Colombia - Bogota

SOBOL

*SOBOL indices***Description**

This function calculates the first order and total SOBOL indices.

Usage

```
SOBOL(data_var, CM_mean, CM_var, pp_names)
```

Arguments

data_var	a vector containing the variance of the model output for each modelling time step.
CM_mean	An array containing the conditional mean of each parameter of the model. This array has dimensions of steps x t x pp, where steps is the number of divisions of the parametric range, t is the number of temporary steps and pp the number of parameters of the model.
CM_var	An array containing the conditional variance of each parameter of the model. This array has dimensions of steps x t x pp, where steps is the number of divisions of the parametric range, t is the number of temporary steps and pp the number of parameters of the model.
pp_names	a strings vector with the names of the parameters of the model.

Value

a list containing two matrices. The first contains the first order sobol, the second sobol_total.

Author(s)

Camila Garcia-Echeverri <cagarciae@unal.edu.co>
 Maria Cristina Areas-Bautista <mcarenasb@unal.edu.co>

Hydrodynamics of the natural media research group - HYDS National University of Colombia - Bogota

References

Sobol, I. M. (2001). Global sensitivity indices for nonlinear mathematical models and their Monte Carlo estimates. *Mathematics and Computers in Simulation*, 55(1–3), 271–280. [https://doi.org/10.1016/S0378-4754\(00\)00270-6](https://doi.org/10.1016/S0378-4754(00)00270-6)

Examples

```
data("data_Bstat", "CM", "pp_names")
SOBOL_indices <- SOBOL(data_Bstat[,3], CM$CM_mean, CM$CM_var , pp_names)
```

Index

* datasets

- CM, [4](#)
- data_Bstat, [5](#)
- out_set, [7](#)
- parameters_set, [8](#)
- pp_names, [8](#)

AMA, [2](#)

Bstat, [3](#)

CM, [4](#)

Cond_Moments, [4](#)

data_Bstat, [5](#)

GSAtool, [6](#)

out_set, [7](#)

parameters_set, [8](#)

pp_names, [8](#)

save_results, [9](#)

SOBOL, [10](#)