

Package ‘ILS’

March 6, 2018

Type Package

Title Interlaboratory Study

Version 0.2

Date 2018-03-06

Depends R (>= 3.1.0), lattice, multcomp, depthTools, fda.usc, MASS,
stats

Description It performs interlaboratory studies (ILS) to detect those

laboratories that provide non-consistent results when comparing to others. It permits to work simultaneously with various testing materials, from standard univariate, and functional data analysis (FDA) perspectives. The univariate approach based on ASTM E691-08 consist of estimating the Mandel's h and k statistics to identify those laboratories that provide more significant different results, testing also the presence of outliers by Cochran and Grubbs tests, Analysis of variance (ANOVA) techniques are provided (F and Tukey tests) to test differences in means corresponding to different laboratories per each material. Taking into account the functional nature of data retrieved in analytical chemistry, applied physics and engineering (spectra, thermograms, etc.). ILS package provides a FDA approach for finding the Mandel's k and h statistics distribution by smoothing bootstrap resampling.

License GPL (>= 2)

LazyData yes

Author Miguel Flores [aut, cre],
Ruben Fernandez [aut],
Salvador Naya [aut],
Javier Tarrio-Saavedra [aut],
Roberto Bossano [aut]

Maintainer Miguel Flores <ma.flores@outlook.com>

Repository CRAN

RoxygenNote 6.0.1

NeedsCompilation no

Date/Publication 2018-03-06 21:42:25 UTC

R topics documented:

boot.sim.set	2
cochran.test	3
DSC	4
func.ils.formula	5
Glucose	5
grubbs.test	6
h.qcs	7
IDT	8
ILS	9
ils.fqcdatal	10
ils.fqcs	11
k.qcs	12
lab.aov	13
lab.qcdata	14
lab.qcs	15
mandel.fqcs	16
outliers.ils	17
plot.ils.fqcdatal	18
plot.ils.fqcs	19
plot.lab.qcdata	20
plot.lab.qcs	21
plot.mandel.fqcs	21
TG	22

Index

24

boot.sim.set *Bootstrap samples of a functional statistic*

Description

`data.bootstrap` provides bootstrap samples for functional data.

Usage

```
boot.sim.set(x, smo = 0.05)
```

Arguments

- x A `fdata` object.
- smo The smoothing parameter for the bootstrap samples.

cochran.test	<i>Function to compute the Grubbs test statistic.</i>
--------------	---

Description

Function to estimate the Cochran test statistic.

Usage

```
cochran.test(x, ...)

## Default S3 method:
cochran.test(x, var.index = 1, replicate.index = 2,
             material.index = 3, laboratory.index = 4, data.name = NULL,
             alpha = 0.05, ...)

## S3 method for class 'lab.qcdata'
cochran.test(x, alpha = 0.05, ...)
```

Arguments

<code>x</code>	R object (used to select the method). See details.
<code>...</code>	Arguments passed to or from methods.
<code>var.index</code>	Scalar with the column number corresponding to the observed variable (the critical to quality variable). Alternatively, a string with the name of a quality variable can be provided.
<code>replicate.index</code>	Scalar with the column number corresponding to the index each replicate.
<code>material.index</code>	Scalar corresponding to the replicated number.
<code>laboratory.index</code>	Scalar that defines the index number of each laboratory.
<code>data.name</code>	String specifying the name of the variable which appears on the plots. If name is not provided, it is retrieved from the object.
<code>alpha</code>	The significance level (0.05 by default)

References

- Wilrich Peter-T. (2013), Critical values of mandel's h and k, the grubbs and the Cochran test statistic. Asta-Advances in Statistical Analysis, 97(1):1-10.
- ASTM E 691 (1999), Standard practice for conducting an interlaboratory study to determine the precision of a test method. American Society for Testing and Materials. West Conshohocken, PA, USA.

Examples

```
library(ILS)
data(Glucose)
Glucose.qcdata <- lab.qcdata(Glucose)
str(Glucose.qcdata)
cochran.test(Glucose.qcdata)
```

DSC

Differential Scanning Calorimetry curves

Description

90 samples of calcium oxalate were analyzed by differential scanning calorimetry technique (DSC), obtaining 90 DSC curves showing from an SDT device the difference of heat between a sample and an oxalate reference value depending on the temperature that the samples are heated at a constant temperature rate. The data set consists of 15 TG curves of 1000 observations from each of the 6 laboratories. Laboratory 2 to Laboratory 4 uses the same simultaneous SDT analyzer in similar conditions, Laboratory 6 uses a simultaneous SDT analyzer with an old calibration, and Laboratory 7 uses a simultaneous SDT analyzer with a calibration (2 degrees Celsius displaced from the zinc melting point).

Format

5 x 1000 x 6 dimension array, where each matrix consists of the 15 DSC curves obtained by testing 15 different oxalate samples, and evaluated at 1000 different temperature values. These 15 curves were obtained for each of the 6 laboratories that performed the experiments.

References

Naya, S., Tarrio-Saavedra, J., Lopez-Beceiro, J., Francisco Fernandez, M., Flores, M. and Artigaga, R. (2014), "Statistical functional approach for interlaboratory studies with thermal data". Journal of Thermal Analysis and Calorimetry, 118, 1229-1243.

Examples

```
library(ILS)
data(DSC)
summary(DSC)
```

<code>func.ils.formula</code>	<i>Descriptive measures for functional data.</i>
-------------------------------	--

Description

Central and dispersion measures for functional data.

Usage

```
func.ils.formula(formula, data = NULL, drop = FALSE, func = func.mean)
```

Arguments

<code>formula</code>	a formula, such as <code>y ~ group</code> , where <code>y</code> is a fdata object to be split into groups according to the grouping variable <code>group</code> (usually a factor).
<code>data</code>	List that containing the variables in the formula. The item called "df" is a data frame with the grouping variable. The item called "y" is a fdata object.
<code>drop</code>	logical indicating if levels that do not occur should be dropped (if <code>f</code> is a factor or a list).
<code>func</code>	Measures for functional data.

<code>Glucose</code>	<i>Glucose in Serum</i>
----------------------	-------------------------

Description

Dataset corresponding to serum glucose (measurements of glucose concentration in blood used to control diabetes) testing. Eight laboratories conducted tests to five different blood samples tagged with different references, ranging them from low sugar content to very high. Three replicates were obtained for each sample. It is retrieved from ASTM E 691 standard.

Format

A data frame with 120 observations composed of the following 4 variables:

Glucose Glucose content in Serum

Replicate Number of glucose measurement corresponding to each material

Material Level of glucose, ranging from low content of sugar to very high level of glucose in blood.

Laboratory Laboratories conducted tests

References

ASTM E 691 (1999). Standard practice for conducting an interlaboratory study to determine the precision of a test method. American Society for Testing and Materials. West Conshohocken, PA, USA.

Examples

```
library(ILS)
data(Glucose)
summary(Glucose)
attach(Glucose)
str(Glucose)
table(Replicate,Material,Laboratory)
table(Laboratory,Material)
st <- with(Glucose, tapply(Glucose, list(Material,Laboratory), mean))
st
```

grubbs.test

Function to compute the Grubbs test statistic.

Description

Function to estimate the Grubbs test statistic.

Usage

```
grubbs.test(x, ...)

## Default S3 method:
grubbs.test(x, var.index = 1, replicate.index = 2,
            material.index = 3, laboratory.index = 4, data.name = NULL,
            alpha = 0.05, ...)

## S3 method for class 'lab.qcdata'
grubbs.test(x, alpha = 0.05, ...)
```

Arguments

- x** an R object (used to select the method). See details.
- ...** arguments passed to or from methods.
- var.index** Scalar with the column number corresponding to the observed variable (the critical to quality variable). Alternatively, a string with the name of a quality variable can be provided.
- replicate.index** Scalar with the column number corresponding to the index each replicate.
- material.index** Scalar corresponding to the replicated number.
- laboratory.index** Scalar that defines the index number of each laboratory.
- data.name** String specifying the name of the variable which appears on the plots. If name is not provided, it is retrieved from the object.
- alpha** The significance level (0.05 for default)

References

- Wilrich Peter-T. (2013), Critical values of Mandel's h and k, the Grubbs and the Cochran test statistic. Asta-Advances in Statistical Analysis, 97(1):1-10.
- ASTM E 691 (1999), Standard practice for conducting an interlaboratory study to determine the precision of a test method. American Society for Testing and Materials. West Conshohocken, PA, USA.

Examples

```
library(ILS)
data(Glucose)
Glucose.qcdata<- lab.qcdata(Glucose)
str(Glucose.qcdata)
grubbs.test(Glucose.qcdata)
```

h.qcs

Function to estimate the univariate Mandel's h statistic

Description

This function is used to compute the Mandel's h statistic.

Usage

```
h.qcs(x, ...)

## Default S3 method:
h.qcs(x, var.index = 1, replicate.index = 2,
      material.index = 3, laboratory.index = 4, data.name = NULL,
      alpha = 0.05, ...)

## S3 method for class 'lab.qcdata'
h.qcs(x, alpha = 0.05, ...)
```

Arguments

- | | |
|------------------------|---|
| x | R object (used to select the method). See details. |
| ... | Arguments passed to or from methods. |
| var.index | Scalar with the column number corresponding to the observed variable (the critical to quality variable). Alternatively, a string with the name of a quality variable can be provided. |
| replicate.index | Scalar with the column number corresponding to the index each replicate. |
| material.index | Scalar corresponding to the replicated number. |

laboratory.index

Scalar that defines the index number of each laboratory.

data.name String specifying the name of the variable which appears on the plots. If name is not provided, it is retrieved from the object.

alpha The significance level (0.05 by default)

References

Wilrich Peter-T. (2013), Critical values of Mandel's h and k, the Grubbs and the Cochran test statistic. Asta-Advances in Statistical Analysis, 97(1):1-10.

ASTM E 691 (1999), Standard practice for conducting an interlaboratory study to determine the precision of a test method. American Society for Testing and Materials. West Conshohocken, PA, USA.

Examples

```
library(ILS)
data(Glucose)
Glucose.qcdata <- lab.qcdata(Glucose)
str(Glucose.qcdata)
h<- h.qcs(Glucose.qcdata, alpha = 0.005)
summary(h)
plot(h)
```

IDT

Dataset composed of the initial decomposition temperature (IDT) of different samples of Calcium Oxalate, obtained by 7 different laboratories

Description

Initial decomposition temperature (IDT) is a parameter defined by temperature at which a material loss 5% of its weight when it is heated using a constant rate. One hundred and five calcium oxalate samples were tested by thermogravimetric analysis (TG), obtaining 105 TG curves from which the IDT is extracted. Summarizing, IDT dataset is composed of the IDT values of calcium oxalate obtained by 7 different laboratories that analyze 15 oxalate samples each one.: Laboratory 1 uses a simultaneous thermal analyzer (STA) with an old calibration program, Laboratory 2 to Laboratory 4 use a SDT simultaneous analyzer, Laboratory 6 utilizes a SDT simultaneous analyzer with an old calibration, and Laboratory 7 uses a SDT simultaneous analyzer with a biased calibration (2 degrees Celsius shifted from the zinc melting point).

Format

Dataframe of dimension 105 x 44. The first column corresponds to IDT variable, the second (Sample) is the replicate number, the third is the tested material (Material), and fourth is the laboratory.

References

Naya, S., Tarrio-Saavedra, J., Lopez-Beceiro, J., Francisco Fernandez, M., Flores, M. and Artigaga, R. (2014), "Statistical functional approach for interlaboratory studies with thermal data". Journal of Thermal Analysis and Calorimetry, 118, 1229-1243.

Examples

```
library(ILS)
data(IDT)
summary(IDT)
attach(IDT)
str(IDT)
table(Sample, Run, Laboratory)
table(Laboratory, Run)
st <- with(IDT, tapply(IDT, list(Run, Laboratory), mean))
st
```

ILS

Interlaboratory Study

Description

Interlaboratory Study

Details

It performs interlaboratory studies (ILS) to detect those laboratories that provide non-consistent results when comparing to others. It permits to work simultaneously with various testing materials, from standard univariate, and functional data analysis (FDA) perspectives. The univariate approach based on ASTM E691-08 consist of estimating the Mandel's h and k statistics to identify those laboratories that provide more significant different results, testing also the presence of outliers by Cochran and Grubbs tests, Analysis of variance (ANOVA) techniques are provided (F and Tuckey tests) to test differences in the testing variable means corresponding to test differences in means corresponding to different laboratories per each material. Taking into account the functional nature of data retrieved in analytical chemistry, applied physics and engineering (spectra, thermograms, etc.). ILS package provides a FDA approach for functional Mandel's k and h statistics by smoothing bootstrap resampling of distribution.

ils.fqcd*Functional Quality Control Data***Description**

It Creates an object of class 'ils.fqcd' to perform statistical quality control. This object is used to plot functional data.

Usage

```
ils.fqcd(x, p = NULL, index.laboratory = NULL, argvals = NULL,
rangeval = NULL, names = NULL)
```

Arguments

<i>x</i>	A (n x m) matrix or data-frame. The m is the number of points observed in each curve, and n is the number of curves for each laboratory.
<i>p</i>	the number of laboratories.
<i>index.laboratory</i>	is the laboratory index. The <i>index.laboratory</i> length should be equal a <i>p</i>
<i>argvals</i>	Argvals, by default: 1:m.
<i>rangeval</i>	Range of discretization points, by default: range(<i>argvals</i>).
<i>names</i>	(optional) list with tree components: main an overall title, xlab title for x axis and ylab title for y axis.

References

- Febrero-Bande, M. and Oviedo, M. (2012), "Statistical computing in functional data analysis: the R package fda.usc". Journal of Statistical Software 51 (4), 1-28.
- Naya, S., Tarrio-Saavedra. J., Lopez- Beceiro, J., Francisco Fernandez, M., Flores, M. and Artigaga, R. (2014), "Statistical functional approach for interlaboratory studies with thermal data". Journal of Thermal Analysis and Calorimetry, 118,1229-1243.

Examples

```
library(ILS)
data(TG)
delta <- seq(from = 40 ,to = 850 ,length.out = 1000 )
fqcd <- ils.fqcd(TG, p = 7, argvals = delta)
xlab <- "Temperature (C)"
ylab <- "Mass (%)"
main <- "TG curves obtained from calcium oxalate"
plot(x = fqcd, main = main, xlab=xlab, ylab=ylab,col = 1:7,legend = TRUE)
```

ils.fqcs*It develops an object of class 'ils.fqcs'*

Description

Create an object of class 'ils.fqcs' to perform statistical quality control. This function is used to compute requested FDA.

Usage

```
ils.fqcs(x, ...)

## Default S3 method:
ils.fqcs(x, argvals = NULL, rangeeval = NULL, ...)

## S3 method for class 'ils.fqcdat'
ils.fqcs(x, ...)

## S3 method for class 'ils.fqcs'
print(x, ...)

## S3 method for class 'ils.fqcs'
summary(object, ...)
```

Arguments

x	A ils.fqcs object for which a print is desired.
...	Arguments passed to or from methods.
argvals	Argvals, by default: 1:m.
rangeeval	Range of discretization points, by default: range(argvals).
object	A ils.fqcs object for which a summary is desired.

References

- Frbrero-Bande, M. and Oviedo, M. (2012), "Statistical computing in functional data analysis: the R package fda.usc". Journal of Statistical Software 51 (4), 1-28.
- Cuevas A., Frbrero-Bande, M. and Fraiman, R. (2006), "On the use of the bootstrap for estimating functions with functional data". Computational Statistics & Data Analysis 51, 2, 1063-1074.
- Naya, S., Tarrio-Saavedra. J., Lopez- Beceiro, J., Francisco Fernandez, M., Flores, M. and Artigaga, R. (2014), "Statistical functional approach for interlaboratory studies with thermal data". Journal of Thermal Analysis and Calorimetry, 118, 1229-1243.

Examples

```
library(ILS)
data(TG)
delta <- seq(from = 40 ,to = 850 ,length.out = 1000 )
fqcdata <- ils.fqcdata(TG, p = 7, argvals = delta)
xlab <- "Temperature/ C"
ylab <- "Mass/ %"
fqcstat <- ils.fqcs(fqcdata)
plot(fqcstat, xlab = xlab, ylab = ylab,legend = TRUE)
```

k.qcs

Function to calcute the Mandel's k statistic

Description

This function is used to compute the statistic k of Mandel.

Usage

```
k.qcs(x, ...)

## Default S3 method:
k.qcs(x, var.index = 1, replicate.index = 2,
      material.index = 3, laboratory.index = 4, data.name = NULL,
      alpha = 0.05, ...)

## S3 method for class 'lab.qcdata'
k.qcs(x, alpha = 0.05, ...)
```

Arguments

- x an R object (used to select the method). See details.
- ... arguments passed to or from methods.
- var.index Scalar with the column number corresponding to the observed variable (the critical to quality variable). Alternatively, a string with the name of a quality variable can be provided.
- replicate.index Scalar with the column number corresponding to the index each replicate.
- material.index Scalar corresponding to the replicated number.
- laboratory.index Scalar that defines the index number of each laboratory.
- data.name String specifying the name of the variable which appears on the plots. If name is not provided, it is retrieved from the object.
- alpha The significance level (0.05 by default)

References

- Wilrich Peter-T. (2013), Critical values of Mandel's h and k, the Grubbs and the Cochran test statistic. Asta-Advances in Statistical Analysis, 97(1):1-10.
- ASTM E 691 (1999), Standard practice for conducting an interlaboratory study to determine the precision of a test method. American Society for Testing and Materials. West Conshohocken, PA, USA.

Examples

```
library(ILS)
data(Glucose)
Glucose.qcdata <- lab.qcdata(Glucose)
str(Glucose.qcdata)
k<- k.qcs(Glucose.qcdata, alpha = 0.005)
summary(k)
plot(k)
```

lab.aov

Function to compute the AOV

Description

Function to compute the analysis of variance of ILS data, taking into account the laboratories and material factors.

Usage

```
lab.aov(x, ...)

## Default S3 method:
lab.aov(x, var.index = 1, replicate.index = 2,
        material.index = 3, laboratory.index = 4, data.name = NULL,
        level = 0.95, plot = FALSE, pages = 0, ...)

## S3 method for class 'lab.qcdata'
lab.aov(x, level = 0.95, plot = FALSE, pages = 0,
        ...)
```

Arguments

x	Object lab.qcdata.
...	Arguments passed to or from methods.
var.index	Scalar with the column number corresponding to the observed variable (the critical to quality variable). Alternatively, a string with the name of a quality variable can be provided.

<code>replicate.index</code>	Scalar with the column number corresponding to the index each replicate.
<code>material.index</code>	Scalar corresponding to the replicated number.
<code>laboratory.index</code>	Scalar that defines the index number of each laboratory.
<code>data.name</code>	String specifying the name of the variable which appears on the plots. If name is not provided, it is retrieved from the object.
<code>level</code>	Requested confidence level (0.95 by default)
<code>plot</code>	If TRUE, confidence intervals are plot.
<code>pages</code>	By default 0, it indicates the number of pages over which to spread the output. For example, if pages=1, all terms will be plotted on one page with the layout performed automatically. If pages=0, one plot will be displayed by each tested material.

References

- W Hothorn T., Bretz, F., and Westfall, P. (2008), Simultaneous inference in general parametric models. *Biometrical Journal*, 50(3):346-363.
- Heyden, Y., Smeyers-Verbeke, J. (2007), Set-up and evaluation of interlaboratory studies. *J. Chromatogr. A*, 1158:158-167.

Examples

```
## Not run:
library(ILS)
data(Glucose)
Glucose.qcdata <- lab.qcdata(Glucose)
str(Glucose.qcdata)
lab.aov(Glucose.qcdata, level = 0.95, plot = TRUE, pages = 1)

## End(Not run)
```

Description

It creates a 'lab.qcdata' class object to perform the interlaboratory study. This object is used to plot ILS data and more.

Usage

```
lab.qcdata(data, var.index = 1, replicate.index = 2, material.index = 3,
           laboratory.index = 4, data.name = NULL)
```

Arguments

data	Matrix or data-frame that contains the data, replicate index, type of material, and the laboratory.
var.index	Scalar with the column number corresponding to the observed variable (the critical to quality variable). Alternatively, a string with the name of a quality variable can be provided.
replicate.index	Scalar with the column number corresponding to the index each replicate.
material.index	Scalar corresponding to the replicated number.
laboratory.index	Scalar that defines the index number of each laboratory.
data.name	String specifying the name of the variable which appears on the plots. If name is not provided, it is retrieved from the object.

Examples

```
library(ILS)
data(Glucose)
Glucose.qcdata <- lab.qcdata(Glucose)
str(Glucose.qcdata)
summary(Glucose.qcdata)
```

lab.qcs

Create an object of class 'lab.qcs' to perform statistical quality control. This function is used to compute statistics required for plotting Statistics

Description

It develops an object of `lab.qcs`-codelinkclass to perform statistical quality control. This function is used to compute the requested statistics to be summarized and plotted.

Usage

```
lab.qcs(x, ...)
## S3 method for class 'lab.qcs'
print(x, ...)

## S3 method for class 'lab.qcs'
summary(object, ...)
```

Arguments

x	Object <code>lab.qcdata</code> (Functional Quality Control Data)
...	Arguments passed to or from methods.
object	A <code>lab.qcs</code> object for which a summary is desired.

Examples

```
library(ILS)
data(Glucose)
Glucose.qcdata <- lab.qcdata(Glucose)
str(Glucose.qcdata)
Glucose.qcs <- lab.qcs(Glucose.qcdata)
str(Glucose.qcs)
summary(Glucose.qcs)
```

mandel.fqcs

This function is used to compute the FDA Mandel's h and k statistic.

Description

It develops an object of 'mandel.fqcs' class to perform statistical quality control analysis. This function is used to compute the functional approach of Mandel's h and k statistic. It is specifically designed to deal with experimental data results defined by curves such as thermograms and spectra.

Usage

```
mandel.fqcs(x, ...)

## Default S3 method:
mandel.fqcs(x, p = NULL, index.laboratory = NULL,
            argvals = NULL, rangeval = NULL, names = NULL, ...)

## S3 method for class 'ils.fqcdata'
mandel.fqcs(x, fdep = depth.mode, outlier = TRUE,
            trim = 0.01, alpha = 0.01, nb = 200, smo = 0.05, ...)
```

Arguments

x	A (n x m) matrix or data-frame. The m is the number of points observed in each curve, and n is the number of curves for each laboratory.
...	Further arguments passed to or from other methods.
p	the number of laboratories.
index.laboratory	is the laboratory index. The index.laboratory length should be equal a p
argvals	Argvals, by default: 1:m.
rangeval	Range of discretization points, by default: range(argvals).
names	(optional) list with tree components: main an overall title, xlab title for x axis and ylab title for y axis.
fdep	Type of depth measure, by default depth.mode.
outlier	= TRUE

trim	The alpha of the trimming.
alpha	Significance level, by default 1%.
nb	The number of bootstrap samples.
smo	The smoothing parameter for the bootstrap samples.

References

- Frbrero-Bande, M. and Oviedo, M. (2012), "Statistical computing in functional data analysis: the R package fda.usc". Journal of Statistical Software 51 (4), 1-28.
- Cuevas A., Frbrero-Bande, M. and Fraiman, R. (2006), "On the use of the bootstrap for estimating functions with functional data". Computational Statistics & Data Analysis 51, 2, 1063-1074.
- Naya, S., Tarrio-Saavedra. J., Lopez- Beceiro, J., Francisco Fernandez, M., Flores, M. and Artigaga, R. (2014), "Statistical functional approach for interlaboratory studies with thermal data". Journal of Thermal Analysis and Calorimetry, 118, 1229-1243.

Examples

```
## Not run:
library(ILS)
data(TG)
delta <- seq(from = 40 ,to = 850 ,length.out = 1000 )
fqcdata <- ils.fqcdta(TG, p = 7, argvals = delta)
mandel.tg <- mandel.fqcs(fqcdata.tg,nb = 200)
plot(mandel.tg,legend = F,col=c(rep(3,5),1,1))

## End(Not run)
```

outliers.ils *Detecting outliers for functional dataset*

Description

Procedure for detecting functional outliers.

Usage

```
outliers.ils(x, fdep = depth.FM, trim = 0.01)
```

Arguments

x	A fdata
fdep	Type of depth measure, by default depth.mode.
trim	The percentage of the trimming, by default is 1%

plot.xls.fqcdta *Plotting method for 'xls.fqcdta' objects*

Description

Generic function to plot objects of 'xls.fqcdta' class

Usage

```
## S3 method for class 'xls.fqcdta'
plot(x, type = "l", main = NULL, xlab = NULL,
      ylab = NULL, ylim = NULL, x.co = NULL, y.co = NULL, legend = TRUE,
      col = NULL, ...)
```

Arguments

x	Object xls.fqcdta (Functional Quality Control Data)
type	1-character string giving the type of plot desired. The following values are possible for fdata class object: "l" for lines (by default), "p" for points, , "o" for overplotted points and lines, "b", "c" for (empty if "c") points joined by lines, "s" and "S" for stair steps and "h" for histogram-like vertical lines. Finally, "n" does not produce any points or lines. The following values are possible for fdata2d class object: "image.contour" (by default) to display three-dimensional data and add the contour lines, "image" to display three-dimensional data, "contour" to display a contour plot, "persp" to display a perspective plots of a surface over the x-y plane and "filled.contour" to display a contour plot with the areas between the contours filled in solid color.
main	Main title for the plot
xlab	Title for the x axis
ylab	Title for the y axis
ylim	The y limits of the plot
x.co	It specifies the x co-ordinates to be used to place a legend.
y.co	It specifies the y co-ordinates to be used to place a legend.
legend	Logical argument. Default is TRUE then The legend default is used.
col	Color specifications
...	Further arguments passed to matplot function (for fdata class).

References

- Frbrero-Bande, M. and Oviedo, M. (2012), "Statistical computing in functional data analysis: the R package fda.usc". Journal of Statistical Software 51 (4), 1-28.
- Naya, S., Tarrio-Saavedra, J., Lopez-Beceiro, J., Francisco Fernandez, M., Flores, M. and Artigaga, R. (2014), "Statistical functional approach for interlaboratory studies with thermal data". Journal of Thermal Analysis and Calorimetry, 118, 1229-1243.

Examples

```
## Not run:
library(ILS)
data(TG)
delta <- seq(from = 40 ,to = 850 ,length.out = 1000 )
fqcdata <- xls.fqcdta(TG, p = 7, argvals = delta)
windows()
xlab <- "Temperature (C)"
ylab <- "Mass (%)"
main <- "TG curves obtained from calcium oxalate"
plot(x = fqcdata, main = main, xlab=xlab, ylab=ylab,legend = TRUE)
## End(Not run)
```

plot.xls.fqcs

Plotting method for 'xls.fqcs' objects

Description

Generic function to plot objects of 'xls.fqcs' class. Results of functional ILS studies are graphically shown.

Usage

```
## S3 method for class 'xls.fqcs'
plot(x, type = "l", xlab = NULL, ylab = NULL,
      legend = TRUE, col = NULL, ...)
```

Arguments

x	Object functional data or a list with objects of functional data type
type	1-character string giving the type of plot desired. The following values are possible for fdata class object: "l" for lines (by default), "p" for points, , "o" for overplotted points and lines, "b", "c" for (empty if "c") points joined by lines, "s" and "S" for stair steps and "h" for histogram-like vertical lines. Finally, "n" does not produce any points or lines. The following values are possible for fdata2d class object: "image.contour" (by default) to display three-dimensional data and add the contour lines, "image" to display three-dimensional data, "contour" to display a contour plot, "persp" to display a perspective plots of a surface over the x-y plane and "filled.contour" to display a contour plot with the areas between the contours filled in solid color.
xlab	Title for the x axis
ylab	Title for the y axis
legend	Logical argument. Default is TRUE then The legend default is used.
col	Color specifications
...	arguments to be passed to or from methods

References

- Frbrero-Bande, M. and Oviedo, M. (2012), "Statistical computing in functional data analysis: the R package fda.usc". Journal of Statistical Software 51 (4), 1-28.
- Naya, S., Tarrio-Saavedra, J., Lopez-Beceiro, J., Francisco Fernandez, M., Flores, M. and Artigaga, R. (2014), "Statistical functional approach for interlaboratory studies with thermal data". Journal of Thermal Analysis and Calorimetry, 118, 1229-1243.

Examples

```
library(ILS)
data(TG)
delta <- seq(from = 40 ,to = 850 ,length.out = 1000 )
fqcdata <- ils.fqcdata(TG, p = 7, argvals = delta)
xlab <- "Temperature/ C"
ylab <- "Mass/ %"
fqcstat <- ils.fqcs(fqcdata)
plot(fqcstat, xlab = xlab, ylab = ylab,legend = TRUE)
```

plot.lab.qcdata *Plot method for 'lab.qcdata' objects*

Description

Generic function for plotting objects of 'lab.qcdata' class. Results of univariate ILS studies are graphically shown.

Usage

```
## S3 method for class 'lab.qcdata'
plot(x, xlab = NULL, ylab = NULL, col = "blue", ...)
```

Arguments

x	Functional data object or a list with functional objects
xlab	Title for the x axis
ylab	Title for the y axis
col	Color of type material, when there only one
...	arguments to be passed to or from methods.

Examples

```
library(ILS)
data(Glucose)
Glucose.qcdata <- lab.qcdata(Glucose)
str(Glucose.qcdata)
plot(Glucose.qcdata)
```

plot.lab.qcs	<i>Plot method for 'lab.qcs' objects</i>
--------------	--

Description

Generic function for plotting objects of 'lab.qcs' class. Results of univariate ILS studies are graphically shown.

Usage

```
## S3 method for class 'lab.qcs'  
plot(x, title = NULL, xlab = NULL, ylab = NULL,  
     col = NULL, ylim = NULL, ...)
```

Arguments

x	Functional data object or a list with functional objects
title	Main title for the plot
xlab	Title for the x axis
ylab	Title for the y axis
col	Color specifications
ylim	Numeric vectors of length 2 (coordinates ranges)
...	arguments to be passed to or from methods.

plot.mandel.fqcs	<i>Plotting method for 'mandel.fqcs' objects</i>
------------------	--

Description

Generic function to plot objects of 'mandel.fqcs' class. Results of functional ILS studies are graphically shown.

Usage

```
## S3 method for class 'mandel.fqcs'  
plot(x, xlab = NULL, ylab = NULL, x.co = NULL,  
      y.co = NULL, legend = TRUE, col = NULL, ...)
```

Arguments

x	A mandel.fqcs object
xlab	Title for the x axis
ylab	Title for the y axis
x.co	It specifies the x co-ordinates to be used to place a legend.
y.co	It specifies the y co-ordinates to be used to place a legend.
legend	Logical argument. Default is TRUE then The legend default is used.
col	Color specifications
...	arguments to be passed to or from methods

References

- Frbrero-Bande, M. and Oviedo, M. (2012), "Statistical computing in functional data analysis: the R package fda.usc". Journal of Statistical Software 51 (4), 1-28.
- Naya, S., Tarrio-Saavedra. J., Lopez- Beceiro, J., Francisco Fernandez, M., Flores, M. and Artigaga, R. (2014), "Statistical functional approach for interlaboratory studies with thermal data". Journal of Thermal Analysis and Calorimetry, 118,1229-1243.

Examples

```
## Not run:
library(ILS)
data(TG)
delta <- seq(from = 40 ,to = 850 ,length.out = 1000 )
fqcdata <- ils.fqcdata(TG, p = 7, argvals = delta)
mandel.tg <- mandel.fqcs(fqcdata.tg,nb = 200)
plot(mandel.tg,legend = F,col=c(rep(3,5),1,1))

## End(Not run)
# $H(t)$ y $K(t)$
```

Description

One hundred and five Calcium oxalate samples were tested by thermogravimetric (TG) analysis, obtaining 105 TG curves that shows the mass loss of oxalate depending on time when samples are heated at a constant temperature rate. Dataset is composed by fifteen TG curves of 1000 observations each of overall 7 different laboratories. Laboratory 1 uses a simultaneous thermal analyzer (STA) with an old calibration program, Laboratory 2 to Laboratory 4 use a SDT simultaneous analyzer, Laboratory 6 utilizes a SDT simultaneous analyzer with an old calibration, and Laboratory 7 uses a SDT simultaneous analyzer with a biased calibration (2 degrees Celsius shifted from the zinc melting point).

Format

A 15 x 1000 x 7 dimension array , where each matrix consists of the 15 TG curves obtained testing 15 different oxalate samples, and evaluated in 1000 different values of temperature. These 15 curves were obtained for each of the overall 7 laboratories that have performed the experiments.

References

Naya, S., Tarrio-Saavedra. J., Lopez- Beceiro, J., Francisco Fernandez, M., Flores, M. and Artiga, R. (2014), "Statistical functional approach for interlaboratory studies with thermal data". Journal of Thermal Analysis and Calorimetry, 118,1229-1243.

Examples

```
library(ILS)
data(TG)
summary(TG)
```

Index

*Topic **datasets**

Glucose, 5

boot.sim.set, 2

cochran.test, 3

DSC, 4

func.ils.formula, 5

Glucose, 5

grubbs.test, 6

h.qcs, 7

IDT, 8

ILS, 9

ILS-package (ILS), 9

ils.fqcdatal, 10

ils.fqcs, 11

k.qcs, 12

lab.aov, 13

lab.qcdata, 14

lab.qcs, 15

mandel.fqcs, 16

outliers.ils, 17

plot.ils.fqcdatal, 18

plot.ils.fqcs, 19

plot.lab.qcdata, 20

plot.lab.qcs, 21

plot.mandel.fqcs, 21

print.ils.fqcs(ils.fqcs), 11

print.lab.qcs(lab.qcs), 15

summary.ils.fqcs(ils.fqcs), 11

summary.lab.qcs(lab.qcs), 15

TG, 22