

Package ‘ISRaD’

February 9, 2020

Title Tools and Data for the International Soil Radiocarbon Database

Version 1.2.3

Description This is the central location for data and tools for the development, maintenance, analysis, and deployment of the International Soil Radiocarbon Database (ISRaD). ISRaD was developed as a collaboration between the U.S. Geological Survey Powell Center and the Max Planck Institute for Biogeochemistry. This R package provides tools for accessing and manipulating ISRaD data, compiling local data using the ISRaD data structure, and simple query and reporting functions for ISRaD. For more detailed information visit the ISRaD website at: <<https://soilradiocarbon.org/>>.

Depends R (>= 3.5.0)

Imports openxlsx, devtools, raster, rgdal, dplyr, tidyr, RCurl,
ggplot2, maps, assertthat, rcrossref, pangaeair, tidyverse,
stringr

License GPL-2

Encoding UTF-8

LazyData true

RoxxygenNote 6.1.1

Suggests knitr, rmarkdown

NeedsCompilation no

Author Alison Hoyt [aut],
Jeffrey Beem-Miller [aut, cre],
Shane Stoner [aut],
J. Grey Monroe [aut],
Caitlin Hicks-Pries [aut],
Paul A. Levine [aut]

Maintainer Jeffrey Beem-Miller <jbeem@bgec-jena.mpg.de>

Repository CRAN

Date/Publication 2020-02-09 16:10:05 UTC

R topics documented:

checkTemplateFiles	2
compile	3
future14C	4
Gaudinski_2001	4
graven	4
ISRaD.extra	5
ISRaD.extra.Cstocks	5
ISRaD.extra.delta_delta	6
ISRaD.extra.fill_14c	7
ISRaD.extra.fill_coords	8
ISRaD.extra.fill_dates	9
ISRaD.extra.fill_fm	10
ISRaD.extra.geospatial	11
ISRaD.extra.geospatial.keys	12
ISRaD.flatten	13
ISRaD.getdata	14
ISRaD.rep.count.all	15
ISRaD.rep.count.frc	15
ISRaD.rep.entry.stats	16
ISRaD.rep.site.map	16
ISRaD.report	17
ISRaD.save.xlsx	17
QAQC	18

Index	20
--------------	-----------

checkTemplateFiles *Check ISRaD Template/Info files*

Description

Check that the template information file and the template file match appropriately.

Usage

```
checkTemplateFiles(outfile = "", verbose = T)
```

Arguments

- | | |
|---------|---|
| outfile | file to dump the output report. Defaults to an empty string that will print to standard output. |
| verbose | if TRUE (default) will print output to specified outfile |

Details

Used in compile() function, but primarily a development tool

Value

returns NULL

Examples

```
checkTemplateFiles()
```

compile	<i>Compile ISRaD data product</i>
---------	-----------------------------------

Description

Compiles template files into ISRaD database format.

Usage

```
compile(dataset_directory, write_report = FALSE, write_out = FALSE,  
       return_type = c("none", "list")[2], checkdoi = F, verbose = T)
```

Arguments

dataset_directory	Directory where completed QAQCed template files are stored.
write_report	Boolean flag to write a log file of the compilation. File will be in the specified dataset_directory at "database/ISRaD_log.txt". If a file with this name already exists in this directory it will be overwritten.
write_out	Set to TRUE to write the compiled database file in .xlsx format in dataset_directory
return_type	A string that defines return object. Acceptable values are "none" or "list"; default is "list".
checkdoi	Set to FALSE if you do not want to validate DOIs during QAQC. (Warning: time consuming).
verbose	Set to TRUE to print results of function to console.

Examples

```
# Load example dataset Gaudinski_2001  
database <- ISRaD::Gaudinski_2001  
# Save as .xlsx file  
ISRaD.save.xlsx(database = database,  
                 template_file = system.file("extdata", "ISRaD_Master_Template.xlsx", package = "ISRaD"),  
                 outfile = paste0(tempdir(), "/Gaudinski_2001.xlsx"))  
# Compile .xlsx file/s in dataset_directory into ISRaD database object  
ISRaD.compiled <- compile(tempdir(), write_report = TRUE, write_out = TRUE,  
                           return_type = 'list', checkdoi = FALSE, verbose = TRUE)
```

`future14C`

Future atmospheric 14C dataset for delta delta calculation

Description

Data from: Sierra, C. "Forecasting atmospheric radiocarbon decline to pre-bomb values", Radiocarbon, Vol 60, Nr 4, 2018, p 1055–1066 DOI:10.1017/RDC.2018.33

Usage`future14C`**Format**`dataframe`

`Gaudinski_2001`

Gaudinski Harvard Forest example dataset

Description

Data from Gaudinski, J., 2001, Belowground carbon cycling in three temperate forests of the eastern United States, University of California Irvine, Ph.D. thesis

Usage`Gaudinski_2001`**Format**`list`

`graven`

Graven dataset for delta delta calculation

Description

Data from Graven et al 2017 <https://www.geosci-model-dev.net/10/4405/2017/gmd-10-4405-2017.pdf>

Usage`graven`**Format**`dataframe`

ISRaD.extraISRaD.extra

Description

Fills in transformed and geospatial data where possible, generating an enhanced version of ISRaD.

Usage

```
ISRaD.extra(database, geodata_directory)
```

Arguments

database	ISRaD dataset object
geodata_directory	directory where geospatial data are found

Details

Fills fraction modern, delta 14C, delta-delta, profile coordinates, bulk density, organic C concentration, and SOC stocks from entered data; fills soil and climatic data from external geospatial data products

Value

Returns new ISRaD_extra object with derived, transformed, and filled columns

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
# Fill ISRaD.extra data
database.x <- ISRaD.extra(database,
  geodata_directory = system.file("extdata", "geodata_directory", package = "ISRaD"))
```

ISRaD.extra.Cstocks ISRaD.extra.Cstocks

Description

Calculates soil organic carbon stock

Usage

```
ISRaD.extra.Cstocks(database)
```

Arguments

database ISRaD dataset object.

Details

Function first fills lyr_bd_samp, lyr_c_org, lyr_c_inorg, lyr_coarse_tot. Notes: 1) SOC stocks can only be calculated if organic carbon concentration and bulk density data are available, 2) SOC stocks are calculated for the fine earth fraction (<2mm).

Value

returns ISRaD_data object with filled columns "lyr_coarse_tot_filled", "lyr_bd_samp_filled", "lyr_c_inorg_filled", "lyr_c_org_filled", "lyr_soc_filled"

Author(s)

J. Beem-Miller

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
database.x <- ISRaD.extra.Cstocks(database)
```

ISRaD.extra.delta_delta
ISRaD.extra.delta_delta

Description

Calculates the difference between sample delta 14C and the atmosphere for the year of collection (delta-delta)

Usage

```
ISRaD.extra.delta_delta(database, future = TRUE)
```

Arguments

database ISRaD dataset object

future Project atmospheric radiocarbon into the future? TRUE/FALSE

Details

Creates new column for delta-delta value. Observation year and profile coordinates must be filled (use ISRaD.extra.fill_dates, and ISRaD.extra.fill_coords functions). The relevant atmospheric d14C data (northern or southern hemisphere or tropics) are determined by profile coordinates. Projection for 2016 to 2021 uses the four quarter average projected atmospheric radiocarbon concentration for Central Europe as estimated in Sierra (2019). Notes: Central Europe projection used for northern hemisphere as these projections perform better against observations than northern hemisphere projection; southern hemisphere and tropic atmospheric radiocarbon projection lagged by 2.5 per mille, as this is the mean lag observed from 2000 to 2015 in the Graven (2017) dataset.

Value

returns ISRaD_data object with new delta delta columns in relevant tables

Author(s)

J. Beem-Miller and C. Hicks-Pries

References

Graven et al. 2017 <<https://www.geosci-model-dev.net/10/4405/2017/gmd-10-4405-2017.pdf>>; Sierra, C. "Forecasting atmospheric radiocarbon decline to pre-bomb values", Radiocarbon, Vol 60, Nr 4, 2018, p 1055–1066 DOI:10.1017/RDC.2018.33

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
# Fill profile coordinates
database.x <- ISRaD.extra.fill_coords(database)
# Fill dates
database.x <- ISRaD.extra.fill_dates(database.x)
# Fill delta 14C from fraction modern
database.x <- ISRaD.extra.fill_14c(database.x)
# Fill delta delta
database.x <- ISRaD.extra.delta_delta(database.x)
```

`ISRaD.extra.fill_14c` *ISRaD.extra.fill_14c*

Description

: Fills delta 14C from fraction modern if delta 14C not reported.

Usage

`ISRaD.extra.fill_14c(database)`

Arguments

database ISRaD dataset object.

Details

: Warning: xxx_obs_date_y columns must be filled for this to work!

Value

returns ISRaD_data object with filled delta 14C columns

Author(s)

: J. Beem-Miller & A. Hoyt

References

: Stuiver and Polach, 1977

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
# Note that flx_14c values are NA
is.na(database$flux$flx_14c)
# Fill dates
database.x <- ISRaD.extra.fill_dates(database)
# Fill delta 14C from fraction modern
database.x <- ISRaD.extra.fill_14c(database.x)
# Column flx_14c in the "flux" table is now filled
is.na(database$flux$flx_14c)
```

ISRaD.extra.fill_coords

ISRaD.extra.fill_coords

Description

Fills profile coordinates from site coordinates if profile coordinates not reported.

Usage

`ISRaD.extra.fill_coords(database)`

Arguments

database ISRaD dataset object.

Value

returns ISRaD_data object with filled profile coordinates

Author(s)

J. Beem-Miller

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
# Fill profile coordinates
database.x <- ISRaD.extra.fill_coords(database)
```

ISRaD.extra.fill_dates
ISRaD.extra.fill_dates

Description

Fills frc_obs_date_y and inc_obs_date_y columns from lyr_obs_date_y if not reported.

Usage

```
ISRaD.extra.fill_dates(database)
```

Arguments

database ISRaD dataset object.

Details

QAQC does not require frc_obs_date_y or inc_obs_date_y fields to be filled in. Therefore it is recommended to run this function prior to running the functions ISRaD.extra.fill_14c, ISRaD.extra.fill_fm, and ISRaD.extra.delta_delta, which require xxx_obs_date_y data.

Value

returns ISRaD_data object with filled frc_obs_date_y and inc_obs_date_y fields.

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
# Fill dates
database.x <- ISRaD.extra.fill_dates(database)
# Fraction table now has lyr_obs_date_y values in frc_obs_date_y field
```

ISRaD.extra.fill_fm *ISRaD.extra.fill_fm*

Description

Fills fraction modern from delta 14C if fraction modern not reported.

Usage

```
ISRaD.extra.fill_fm(database)
```

Arguments

database ISRaD dataset object.

Details

: Warning: xxx_obs_date_y columns must be filled for this to work!

Value

returns ISRaD_data object with filled fraction modern columns

Author(s)

: J. Beem-Miller & A. Hoyt

References

: Stuiver and Polach, 1977

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
# Fill dates
database.x <- ISRaD.extra.fill_dates(database)
# Fill fraction modern from delta 14C
database.x <- ISRaD.extra.fill_fm(database.x)
```

ISRaD.extra.geospatial
ISRaD.extra.geospatial

Description

Extracts data from a user-supplied raster file and adds data as a new variable at the profile level

Usage

```
ISRaD.extra.geospatial(database, geodata_directory,
  crs = "+proj=longlat +datum=WGS84 +no_defs +ellps=WGS84 +towgs84=0,0,0",
  fillWorldClim = TRUE)
```

Arguments

database	ISRaD dataset object
geodata_directory	Directory where geospatial data are found
crs	Coordinate reference system used for geospatial datasets
fillWorldClim	Option to fill climate data from the Worldclim dataset (downloads data from web)

Details

Generic function that uses geographic coordinates of profiles to extract data from one or more raster files. Raster data will be added as new variables at the profile level.

The new variable name will be a concatenation of "pro_ ", and the file name (excluding the file extension). The ISRaD recommended file name convention for geospatial files uses a 6 component string, separated by "_". Missing components can be replaced with "x" ("x"s will be dropped before creating variable names). The 6 components are as follows:

- 1) Short description of the data type, e.g. "bd" for bulk density
- 2) Top layer depth or exact depth (numeric, cm)
- 3) Bottom layer depth (numeric, cm)
- 4) Year of data observation (numeric)
- 5) Data units (e.g. mm/yr for mean annual precipitation)
- 6) Any relevant notes

Coordinate reference system can be specified with the "crs" argument; default is WGS84. Note that all files in geodata_directory must use the same crs.

Option "fillWorldClim" fills climate data from worldclim V1.4 at 2.5 resolution (<http://www.worldclim.org/bioclim>).

Variable descriptions are as follows:

- bio1 = Annual Mean Temperature,
- bio2 = Mean Diurnal Range (Mean of monthly (max temp - min temp)),
- bio3 = Isothermality (BIO2/BIO7) (* 100),
- bio4 = Temperature Seasonality (standard deviation *100),
- bio5 = Max Temperature of Warmest Month,

```

bio6 = Min Temperature of Coldest Month,
bio7 = Temperature Annual Range (BIO5-BIO6),
bio8 = Mean Temperature of Wettest Quarter,
bio9 = Mean Temperature of Driest Quarter,
bio10 = Mean Temperature of Warmest Quarter,
bio11 = Mean Temperature of Coldest Quarter,
bio12 = Annual Precipitation,
bio13 = Precipitation of Wettest Month,
bio14 = Precipitation of Driest Month,
bio15 = Precipitation Seasonality (Coefficient of Variation),
bio16 = Precipitation of Wettest Quarter,
bio17 = Precipitation of Driest Quarter,
bio18 = Precipitation of Warmest Quarter,
bio19 = Precipitation of Coldest Quarter

```

Value

returns updated ISRaD_extra object with new columns at the profile level

Examples

```

# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
# Fill profile coordinates
database <- ISRaD.extra.fill_coords(database)
# Run function
# Note that geospatial data in pkg is only for the Gaudinski_2001 dataset
# Users may supply their own geospatial data as long as it can be read by the raster package
database.x <- ISRaD.extra.geospatial(database,
  geodata_directory = system.file("extdata", "geodata_directory", package = "ISRaD"),
  fillWorldClim = TRUE)

```

ISRaD.extra.geospatial.keys
ISRaD.extra.geospatial.keys

Description

Recode numeric values from categorical geospatial data products

Usage

```
ISRaD.extra.geospatial.keys(database, geodata_keys)
```

Arguments

database	ISRaD dataset object
geodata_keys	directory where geospatial data are found

Details

Generic function that reads .csv files paired with categorical raster data and recodes extracted data in the ISRaD_extra object. For the function to work, the .csv filenames must be identical to the corresponding raster filenames (except for the file extension). Additionally, the first column of the .csv file must contain the numeric identifier and the second column the corresponding character value.

Value

returns updated ISRaD_extra object with recoded columns

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
# Fill profile coordinates
database <- ISRaD.extra.fill_coords(database)
# Fill geospatial data
database.x <- ISRaD.extra.geospatial(database,
  geodata_directory = system.file("extdata", "geodata_directory", package = "ISRaD"),
  fillWorldClim = FALSE)
# NB: example geospatial data in the ISRaD package have been clipped
#      to the extent of the Gaudinski_2001 dataset
database.x <- ISRaD.extra.geospatial.keys(database.x,
  geodata_keys = system.file("extdata", "geodata_keys", package = "ISRaD"))
```

Description

: Joins tables in ISRaD based on linking variables and returns "flat" dataframe/s

Usage

```
ISRaD.flatten(database, table)
```

Arguments

database	ISRaD dataset object: e.g. ISRaD_data, or ISRaD_extra
table	ISRaD table of interest ("flux", "layer", "interstitial", "fraction", "incubation"). Must be entered with "".

Details

: ISRaD.extra.flatten generates flat files (2 dimensional matrices) for user-specified ISRaD tables by joining higher level tables (metadata, site, profile, layer) to lower level tables (layer, fraction, incubation, flux, interstitial).

Value

Returns a dataframe with nrow=nrow(table) and ncol=sum(ncol(meta),ncol(site),ncol(profile),...,ncol(table))

Author(s)

: J. Beem-Miller

References

:

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
fractions <- ISRaD.flatten(database, "fraction")
layers <- ISRaD.flatten(database, "layer")
```

ISRaD.getdata

ISRaD.getdata

Description

: Retrieves most recent version of ISRaD data from github

Usage

```
ISRaD.getdata(directory, dataset = "full", extra = F,
force_download = F)
```

Arguments

directory	Location of ISRaD_database_files folder. If not found, it will be created.
dataset	Specify which data you want. Options are c("full", "flux", "interstitial", "incubation", "fraction", "layer")
extra	TRUE/FALSE. If TRUE, the ISRaD_extra object will be returned. If FALSE, ISRaD_data will be returned. Default is FALSE.
force_download	TRUE/FALSE. If ISRaD_database files already exist in the specified directory, new data will not be downloaded by default. If force_download is set to TRUE, the newest data from github will be downloaded and overwrite any existing files.

Value

ISRaD data object

Examples

```
# Return full dataset ("full")
ISRaD_full <- ISRaD.getdata(tempdir(), dataset = "full", extra = FALSE)
# Return full dataset plus "extra" filled data
ISRaD_extra <- ISRaD.getdata(tempdir(), dataset = "full", extra = TRUE)
# Return only fraction data, including filled fraction data
ISRaD_fractions <- ISRaD.getdata(tempdir(), dataset = "fraction", extra = TRUE)
```

ISRaD.rep.count.all *ISRaD.rep.count.all*

Description

Generates a report of counts of observations at each level of the database

Usage

```
ISRaD.rep.count.all(database = NULL)
```

Arguments

database ISRaD data object

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
ISRaD.rep.count.all(database)
```

ISRaD.rep.count.frc *ISRaD.rep.count.frc*

Description

Generates a report of fraction level observations, including fraction scheme and properties

Usage

```
ISRaD.rep.count.frc(database = NULL)
```

Arguments

database ISRaD data object

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
ISRaD.rep.count.frc(database)
```

ISRaD.rep.entry.stats *ISRaD.rep.entry.stats*

Description

Generates a report of metadata statistics for all entries

Usage

```
ISRaD.rep.entry.stats(database = NULL)
```

Arguments

database	ISRaD data object
----------	-------------------

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
ISRaD.rep.entry.stats(database)
```

ISRaD.rep.site.map *ISRaD.rep.site.map*

Description

Generate a world map showing locations of all ISRaD sites

Usage

```
ISRaD.rep.site.map(database = NULL)
```

Arguments

database	ISRaD data object
----------	-------------------

Examples

```
# Obtain current ISRaD data
database <- ISRaD.getdata(tempdir(), dataset = "full", extra = FALSE)
# Generate a map of all ISRaD sites
ISRaD.rep.site.map(database)
```

ISRaD.report*ISRaD.report*

Description

Generate basic summary reports of ISRaD data

Usage

```
ISRaD.report(database, report)
```

Arguments

database	ISRaD data object
report	Parameter to define which type of report you want. The default is "count.all" other options include "entry.stats", "count.frc", or "site.map".

Details

: Wrapper for the simple reporting functions ISRaD.rep.count.all, ISRaD.rep.count.frc, ISRaD.rep.entry.stats, ISRaD.rep.site.map

Examples

```
# Obtain current ISRaD data
database <- ISRaD.getdata(tempdir(), dataset = "full", extra = FALSE)
# Report metadata statistics
ISRaD.report(database, report = "entry.stats")
# Report summary statistics for all levels of the database
ISRaD.report(database, report = "count.all")
# Generate a map of all ISRaD sites
ISRaD.report(database, report = "site.map")
```

ISRaD.save.xlsx

ISRaD.save.xlsx

Description

Saves ISRaD data object as .xlsx file in ISRaD template format

Usage

```
ISRaD.save.xlsx(database, template_file = system.file("extdata",
  "ISRaD_Master_Template.xlsx", package = "ISRaD"), outfile)
```

Arguments

database	ISRaD data object.
template_file	Directory path and name of template file to use (defaults to the ISRaD_Master_Template file built into the package). Not recommended to change this.
outfile	Directory path and file name for saving .xlsx file

Author(s)

J Grey Monroe

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
ISRaD.save.xlsx(database = database,
                 template_file = system.file("extdata", "ISRaD_Master_Template.xlsx", package = "ISRaD"),
                 outfile = paste0(tempdir(),"/Gaudinski_2001.xlsx"))
```

QAQC

QAQC

Description

Checks template files for data coherence, formatting, and data entry errors

Usage

```
QAQC(file, writeQCreport = F, outfile_QAQC = "", summaryStats = T,
      dataReport = F, checkdoi = T, verbose = T)
```

Arguments

file	File path for template file to be checked
writeQCreport	If TRUE, a text report of the QC output will be written to the outfile. Default is FALSE
outfile_QAQC	Filename of the output file (if writeQCreport==TRUE). Default is NULL, with the outfile being written to the directory where the template file is stored and named according to the file being checked.
summaryStats	Prints summary statistics. Default is TRUE.
dataReport	Prints list structure of database. Default is FALSE.
checkdoi	Set to FALSE if you do not want the QAQC check to validate DOIs (if TRUE this will be time consuming). Default is TRUE.
verbose	Set to TRUE to print results of function to console. Default is TRUE.

Details

This function can also be called from the ISRaD website (<<http://soilradiocarbon.org>>).

Examples

```
# Load example dataset Gaudinski_2001
database <- ISRaD::Gaudinski_2001
# Save as .xlsx file
ISRaD.save.xlsx(database =
  template_file = system.file("extdata", "ISRaD_Master_Template.xlsx", package = "ISRaD"),
  outfile = paste0(tempdir(),"/Gaudinski_2001.xlsx"))
# Run QAQC
QAQC(paste0(tempdir(),"/Gaudinski_2001.xlsx"))
```

Index

*Topic **datasets**

- future14C, 4
- Gaudinski_2001, 4
- graven, 4

- checkTemplateFiles, 2
- compile, 3

- future14C, 4

- Gaudinski_2001, 4
- graven, 4

- ISRaD.extra, 5

- ISRaD.extra.Cstocks, 5

- ISRaD.extra.delta_delta, 6

- ISRaD.extra.fill_14c, 7

- ISRaD.extra.fill_coords, 8

- ISRaD.extra.fill_dates, 9

- ISRaD.extra.fill_fm, 10

- ISRaD.extra.geospatial, 11

- ISRaD.extra.geospatial.keys, 12

- ISRaD.flatten, 13

- ISRaD.getdata, 14

- ISRaD.rep.count.all, 15

- ISRaD.rep.count.frc, 15

- ISRaD.rep.entry.stats, 16

- ISRaD.rep.site.map, 16

- ISRaD.report, 17

- ISRaD.save.xlsx, 17

- QAQC, 18