

# Package ‘IntervalSurgeon’

June 15, 2018

**Type** Package

**Title** Operating on Integer-Bounded Intervals

**Version** 1.0

**Date** 2018-06-04

**Author** Daniel Greene

**Maintainer** Daniel Greene <dg333@cam.ac.uk>

**Description** Functions for manipulating integer-bounded intervals including finding overlaps, piling and merging.

**License** GPL (>= 2)

**Imports** Rcpp (>= 0.12.4)

**LinkingTo** Rcpp

**Suggests** knitr

**VignetteBuilder** knitr

**RoxygenNote** 6.0.1

**NeedsCompilation** yes

**Repository** CRAN

**Date/Publication** 2018-06-15 11:02:55 UTC

## R topics documented:

IntervalSurgeon-package . . . . .	2
annotate . . . . .	3
breaks . . . . .	4
depth . . . . .	4
detached_sorted_nonempty . . . . .	5
flatten . . . . .	6
join . . . . .	6
overlaps . . . . .	7
pile . . . . .	8
sections . . . . .	9
stitch . . . . .	9

---

IntervalSurgeon-package

*Operating on Integer-Bounded Intervals*


---

## Description

Functions for manipulating integer-bounded intervals including finding overlaps, piling and merging.

## Details

The DESCRIPTION file:

```

Package:      IntervalSurgeon
Type:        Package
Title:       Operating on Integer-Bounded Intervals
Version:     1.0
Date:        2018-06-04
Author:      Daniel Greene
Maintainer:  Daniel Greene <dg333@cam.ac.uk>
Description: Functions for manipulating integer-bounded intervals including finding overlaps, piling and merging.
License:     GPL (>= 2)
Imports:     Rcpp (>= 0.12.4)
LinkingTo:   Rcpp
Suggests:    knitr
VignetteBuilder: knitr
RoxygenNote: 6.0.1

```

Index of help topics:

IntervalSurgeon-package

```

IntervalSurgeon-package      Operating on Integer-Bounded Intervals
annotate                     Annotate one set of intervals with the names of
                              those which intersect with the other
breaks                        Get break points for set of intervals
depth                         Depth of piled intervals
detached_sorted_nonempty     Check intervals are detached, sorted and
                              non-empty.
flatten                      Flatten a set of intervals
join                          Get all overlapping tuples of intervals from
                              multiple sets
overlaps                      Compute overlaps of two sets of detached and
                              sorted intervals
pile                          Get IDs of intervals covering each sub-interval

```

sections	Get the sections from a set of interval breaks
stitch	Stich together touching intervals and remove empty intervals

IntervalSurgeon presents functions for manipulating integer-bounded sets of intervals. Sets of intervals are represented by two-column matrices, where inclusive start points are stored in the first column, and exclusive end points in the second. A central concept in the package is the ‘sections’ of a set of intervals  $x$ : the non-overlapping, completely-covering set of intervals on the range of  $x$ , formed by making intervals between the consecutive sorted start/end points of the intervals in  $x$ . The function `sections` returns such a set of intervals given an input set.

### Author(s)

Daniel Greene

Maintainer: Daniel Greene <dg333@cam.ac.uk>

### See Also

Optional links to other man pages

### Examples

```
## Optional simple examples of the most important functions
## Use \dontrun{ } around code to be shown but not executed
```

---

annotate	<i>Annotate one set of intervals with the names of those which intersect with the other</i>
----------	---

---

### Description

Create a list of vectors of indices/names of intervals/points in  $y$  (if  $y$  is a two-column matrix/vector respectively) which intersect with each interval/point in  $x$  (if  $x$  is a two-column matrix/vector respectively).

### Usage

```
annotate(x, annotation)
```

### Arguments

$x$	Integer matrix of two columns, the first column giving the (inclusive) start points of intervals and the second column giving the corresponding (exclusive) end points, or, an integer vector specifying the location of points.
annotation	Matrix specifying intervals or vector specifying points with which to annotate $x$ .

**Value**

List of vectors of indices of overlapping intervals/points.

**Examples**

```
annotate(rbind(A=c(1, 100), B=c(50, 100)), rbind(a=c(1, 2), b=c(49, 51), c=c(50, 200)))
annotate(rbind(A=c(1, 100), B=c(50, 100)), c(a=1, b=49, c=51, d=100))
```

---

breaks	<i>Get break points for set of intervals</i>
--------	--

---

**Description**

Get the sorted set start points and end points for a set of intervals specified as an integer matrix.

**Usage**

```
breaks(x)
```

**Arguments**

**x** Integer matrix of two columns, the first column giving the (inclusive) start points of intervals and the second column giving the corresponding (exclusive) end points.

**Value**

Ordered integer vector of unique interval start/end points.

**Examples**

```
breaks(cbind(2*1:5, 3*1:5))
```

---

depth	<i>Depth of piled intervals</i>
-------	---------------------------------

---

**Description**

Get the depth of piled intervals for each section in the sections of `x` (see [sections](#)).

**Usage**

```
depth(x, include_intervals = FALSE)
```

**Arguments**

- `x` Integer matrix of two columns, the first column giving the (inclusive) start points of intervals and the second column giving the corresponding (exclusive) end points.
- `include_intervals` Logical value determining whether the function should return a vector of depths at each 'section' in the range of `x` (see [sections](#)), or a list with properties intervals and depths specifying the intervals of the sections and the corresponding depths respectively.

**Value**

Integer vector giving depth of piled intervals from `x` (within each sub-interval) or list containing a property "intervals", a matrix of sections, and property "depths", giving the corresponding pile depths.

**Examples**

```
depth(cbind(1:10, 11:20))
```

---

```
detached_sorted_nonempty
```

*Check intervals are detached, sorted and non-empty.*

---

**Description**

Check that `x` is an integer matrix specifying intervals, that the specified intervals are detached (i.e. non-overlapping/disjoint and non-touching) and that it is sorted (given that the intervals are detached, sorting by start position gives a unique result), and that the start points are greater than the end points (i.e. that they are non-empty/the lengths of all intervals is greater than zero).

**Usage**

```
detached_sorted_nonempty(x)
```

**Arguments**

- `x` Integer matrix of two columns, the first column giving the (inclusive) start points of intervals and the second column giving the corresponding (exclusive) end points.

**Value**

Boolean value.

**Examples**

```
detached_sorted_nonempty(cbind(1:2, 2:3))
detached_sorted_nonempty(cbind(c(1, 3), c(2, 4)))
detached_sorted_nonempty(cbind(1, 1))
```

---

flatten	<i>Flatten a set of intervals</i>
---------	-----------------------------------

---

**Description**

For a given set of intervals compute the set of intervals where there is overlap with at least one from the given. The resulting intervals are sorted and detached.

**Usage**

```
flatten(x)
```

**Arguments**

x	Integer matrix of two columns, the first column giving the (inclusive) start points of intervals and the second column giving the corresponding (exclusive) end points.
---	---

**Value**

Intervals represented by integer matrix of two columns.

**Examples**

```
flatten(rbind(c(1, 3), c(2, 4), c(5, 6)))
```

---

join	<i>Get all overlapping tuples of intervals from multiple sets</i>
------	---

---

**Description**

Get matrix specifying overlapping tuples of intervals from multiple sets. Each row specifies an overlapping tuple. The *n*th element in a row contains the row index of the interval in the *n*th set of intervals passed to the function. Depending on the value of the output argument, there may two additional columns giving the start and end coordinates of the overlap (the default: output="intervals", no extra columns (output="indices") or one additional column giving the row index of the 'section' of the complete set of intervals (output="sections", see [sections](#)).

**Usage**

```
join(..., output = "intervals")
```

**Arguments**

... Integer matrices of two columns, the first column giving the (inclusive) start points of intervals and the second column giving the corresponding (exclusive) end points.

output Character value, one of "intervals", "indices" and "sections".

**Value**

Integer matrix.

**Examples**

```
join(rbind(c(1, 100), c(50, 100)), rbind(c(1, 2), c(49, 51), c(50, 200)))
```

---

overlaps

*Compute overlaps of two sets of detached and sorted intervals*

---

**Description**

Find intervals satisfying particular conditions, including corresponding base R functions `intersect` (i.e. find intersections of intervals), `union` (i.e. unions of intervals) and `setdiff` (i.e. finding intervals which are contained in one set of intervals but not another).

**Usage**

```
overlaps(x, y, check = TRUE, in_x = TRUE, in_y = TRUE, op = "and")
```

```
intersects(x, y, ...)
```

```
unions(x, y, ...)
```

```
setdiffs(x, y, ...)
```

**Arguments**

x Integer matrix of two columns, the first column giving the (inclusive) start points of intervals and the second column giving the corresponding (exclusive) end points.

y Same as x.

check Boolean value determining whether to check that the intervals specified in arguments x and y are sorted and non-overlapping (uses function [detached\\_sorted\\_nonempty](#)). Defaults to TRUE, but setting to FALSE may allow faster execution.

in\_x Boolean value determining whether to flag TRUE on intervals contained in x.

in\_y Boolean value determining whether to flag TRUE on intervals contained in y.

op Character value specifying operator used to combine flags for each interval, either "and" or "or".

... Additional arguments to be passed to `overlaps`.

**Value**

Intervals represented by integer matrix of two columns.

**Examples**

```
intersects(cbind(1, 3), cbind(2, 4))
setdiffs(cbind(1, 3), cbind(2, 4))
unions(cbind(1, 3), cbind(2, 4))
```

---

pile

*Get IDs of intervals covering each sub-interval*

---

**Description**

Get the intervals overlapping each section as a list.

**Usage**

```
pile(x, interval_names = rownames(x), output = "list")
```

**Arguments**

x	Integer matrix of two columns, the first column giving the (inclusive) start points of intervals and the second column giving the corresponding (exclusive) end points.
interval_names	Character vector of names for each interval, not necessarily unique. If they are not unique, one might wish to lapply unique to the list of members for each sub-interval returned by this function. Defaults to the rownames of x.
output	Character value either "list" or "vector" determining whether a named list of interval index/name vectors or flat vector of members (corresponding to the output of <a href="#">depth</a> ) is returned.

**Value**

See notes on output parameter.

**Examples**

```
pile(cbind(1:10, 11:20))
```



---

`sections`*Get the sections from a set of interval breaks*

---

**Description**

Given a set of interval breaks (see [breaks](#)), generate a new set of intervals, the 'sections', which partitions the full range of the given set, with an interval between every 'break' (i.e. start/end point) in the given set.

**Usage**`sections(x)`**Arguments**

`x` Sorted integer vector.

**Value**

Intervals represented by integer matrix of two columns.

**Examples**`sections(1:10)`

---

`stitch`*Stich together touching intervals and remove empty intervals*

---

**Description**

Given an integer matrix specifying disjoint intervals sorted by start position, merge intervals with matching start and ends, and remove intervals of length zero.

**Usage**`stitch(x)`**Arguments**

`x` Integer matrix of two columns, the first column giving the (inclusive) start points of intervals and the second column giving the corresponding (exclusive) end points.

**Value**

Intervals represented by integer matrix of two columns.

**Examples**

```
stitch(cbind(1:2, 2:3))
```

# Index

## \*Topic **package**

IntervalSurgeon-package, [2](#)

annotate, [3](#)

breaks, [4](#), [9](#)

depth, [4](#), [8](#)

detached\_sorted\_nonempty, [5](#), [7](#)

flatten, [6](#)

intersects (overlaps), [7](#)

IntervalSurgeon

(IntervalSurgeon-package), [2](#)

IntervalSurgeon-package, [2](#)

join, [6](#)

overlaps, [7](#)

pile, [8](#)

sections, [4–6](#), [9](#)

setdiffs (overlaps), [7](#)

stitch, [9](#)

unions (overlaps), [7](#)