

Package ‘MLGL’

January 16, 2020

Type Package

Title Multi-Layer Group-Lasso

Version 0.6.1

Date 2019-12-30

Copyright Inria

Description It implements a new procedure of variable selection in the context of redundancy between explanatory variables, which holds true with high dimensional data (Grimonprez et al. (2018) <<https://hal.inria.fr/hal-01857242>>).

License GPL (>= 2)

Imports gglasso, MASS, Matrix, fastcluster, FactoMineR, parallelDist

RoxygenNote 7.0.2

Encoding UTF-8

Author Quentin Grimonprez [aut, cre],
Samuel Blanck [ctb],
Alain Celisse [ths],
Guillemette Marot [ths],
Yi Yang [ctb],
Hui Zou [ctb]

Maintainer Quentin Grimonprez <quentin.grimonprez@inria.fr>

Repository CRAN

Repository/R-Forge/Project hcglasso

Repository/R-Forge/Revision 48

Repository/R-Forge/DateTimeStamp 2019-12-30 16:01:10

Date/Publication 2020-01-16 08:50:03 UTC

NeedsCompilation no

R topics documented:

MLGL-package	2
bootstrapHclust	3

coef.cv.MLGL	4
coef.MLGL	5
computeGroupSizeWeight	5
cv.MLGL	6
Ftest	8
fullProcess	9
hierarchicalFDR	11
hierarchicalFWER	12
HMT	13
listToMatrix	15
MLGL	16
overlapglasso	18
partialFtest	20
plot.cv.MLGL	21
plot.fullProcess	21
plot.HMT	22
plot.MLGL	23
plot.stability.MLGL	24
predict.cv.MLGL	25
predict.MLGL	26
print.fullProcess	27
print.HMT	28
print.MLGL	28
selFDR	29
selFWER	30
simuBlockGaussian	31
stability.MLGL	32
summary.fullProcess	34
summary.HMT	35
summary.MLGL	35
uniqueGroupHclust	36

Index**38****Description**

This package presents a method combining Hierarchical Clustering and Group-lasso. Usually, a single partition of the covariates is used in the group-lasso. Here, we provides several partition from the hierarchical tree.

A post-treatment method based on statistical test (with FWER and FDR control) for selecting the regularization parameter and the optimal group for this value is provided. This method can be applied for the classical group-lasso and our method.

Details

The function **MLGL** performs the hierarchical clustering and the group-lasso. The post-treatment method can be performed with **hierarchicalFWER** and **selFWER** functions. The whole process can be run with the **fullProcess** function.

Author(s)

Quentin Grimonprez

Maintainer: Quentin Grimonprez <quentin.grimonprez@inria.fr>

References

"MLGL: An R package implementing correlated variable selection by hierarchical clustering and group-Lasso.", Quentin Grimonprez, Samuel Blanck, Alain Celisse, Guillemette Marot (2018).
<https://hal.inria.fr/hal-01857242>

See Also

MLGL, **cv.MLGL**, **fullProcess**, **hierarchicalFWER**

Examples

```
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[,c(2,7,12)] %*% c(2, 2, -2) + rnorm(50, 0, 0.5)
# Apply MLGL method
res <- MLGL(X, y)
```

bootstrapHclust

Hierarchical Clustering with distance matrix computed using bootstrap replicates

Description

Hierarchical Clustering with distance matrix computed using bootstrap replicates

Usage

```
bootstrapHclust(X, frac = 1, B = 50, method = "ward.D2", nCore = NULL)
```

Arguments

X	data
frac	fraction of sample used at each replicate
B	number of replicates
method	desired method: "single", "complete", "average", "mcquitty", "ward.D", "ward.D2", "centroid", "median".
nCore	number of cores

Value

An object of class `hclust`

Examples

```
hc <- bootstrapHclust(USArrests, nCore = 1)
```

`coef.cv.MLGL`

Get coefficients from a `cv.MLGL` object

Description

Get coefficients from a `cv.MLGL` object

Usage

```
## S3 method for class 'cv.MLGL'
coef(object, s = c("lambda.1se", "lambda.min"), ...)
```

Arguments

object	<code>cv.MLGL</code> object
s	Either "lambda.1se" or "lambda.min"
...	Not used. Other arguments to predict.

Value

A matrix with estimated coefficients for given values of s.

Author(s)

Quentin Grimonprez

See Also

[cv.MLGL](#), [predict.cv.MLGL](#)

coef.MLGL *Get coefficients from a MLGL object*

Description

Get coefficients from a [MLGL](#) object

Usage

```
## S3 method for class 'MLGL'  
coef(object, s = NULL, ...)
```

Arguments

object	MLGL object
s	values of lambda. If NULL, use values from object
...	Not used. Other arguments to predict.

Value

A matrix with estimated coefficients for given values of s.

Author(s)

Quentin Grimonprez

See Also

[MLGL](#), [predict.MLGL](#)

computeGroupSizeWeight *Compute the group size weight vector with an authorized maximal size*

Description

Compute the group size weight vector with an authorized maximal size

Usage

```
computeGroupSizeWeight(hc, sizeMax = NULL)
```

Arguments

hc	outup of hclust
sizeMax	maximum size of cluster to consider

Value

the weight vector

Examples

```
set.seed(42)
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[,c(2, 7, 12)] %*% c(2, 2, -2) + rnorm(50, 0, 0.5)
# use 20 as the maximal number of group
hc <- hclust(dist(t(X)))
w <- computeGroupSizeWeight(hc, sizeMax = 20)
# Apply MLGL method
res <- MLGL(X, y, hc = hc, weightSizeGroup = w)
```

cv.MLGL

*Multi-Layer Group-Lasso with cross V-fold validation***Description**

V-fold cross validation for [MLGL](#) function

Usage

```
cv.MLGL(
  X,
  y,
  nfolds = 5,
  lambda = NULL,
  hc = NULL,
  weightLevel = NULL,
  weightSizeGroup = NULL,
  loss = c("ls", "logit"),
  intercept = TRUE,
  sizeMaxGroup = NULL,
  verbose = FALSE,
  ...
)
```

Arguments

X	matrix of size n*p
y	vector of size n. If loss = "logit", elements of y must be in -1,1
nfolds	number of folds

lambda	lambda values for group lasso. If not provided, the function generates its own values of lambda
hc	output of hclust function. If not provided, hclust is run with ward.D2 method
weightLevel	a vector of size p for each level of the hierarchy. A zero indicates that the level will be ignored. If not provided, use 1/(height between 2 successive levels)
weightSizeGroup	a vector
loss	a character string specifying the loss function to use, valid options are: "ls" least squares loss (regression) and "logit" logistic loss (classification)
intercept	should an intercept be included in the model ?
sizeMaxGroup	maximum size of selected groups. If NULL, no restriction
verbose	print some informations
...	Others parameters for cv.glasso function

Details

Hierarchical clustering is performed with all the variables. Then, the partitions from the different levels of the hierarchy are used in the different run of MLGL for cross validation.

Value

a cv.MLGL object containing :

lambda values of lambda.

cvm the mean cross-validated error.

cvsd estimate of standard error of cvm

cvupper upper curve = cvm+cvsd

cvlower lower curve = cvm-cvsd

lambda.min The optimal value of lambda that gives minimum cross validation error cvm.

lambda.1se The largest value of lambda such that error is within 1 standard error of the minimum.

time computation time

Author(s)

Quentin Grimonprez

See Also

[MLGL](#), [stability.MLGL](#), [predict.cv.glasso](#), [coef.cv.MLGL](#), [plot.cv.MLGL](#)

Examples

```
set.seed(42)
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[, c(2,7,12)] %*% c(2, 2, -2) + rnorm(50,0,0.5)
# Apply cv.MLGL method
res <- cv.MLGL(X, y)
```

Ftest

F-test

Description

Perform a F-test

Usage

```
Ftest(X, y, varToTest)
```

Arguments

X	design matrix of size n*p
y	response vector of length n
varToTest	vector containing the index of the column of X to test

Details

$y = X * \beta + \epsilon$

null hypothesis : $\beta_{\text{varToTest}} = 0$ alternative hypothesis : it exists an index k in varToTest such that $\beta_k \neq 0$

The test statistic is based on a full and a reduced model. full : $y = X * \beta_{\text{varToTest}} + \epsilon$
reduced : the null model

Value

a vector of the same length as varToTest containing the p-values of the test.

See Also

[partialFtest](#)

<code>fullProcess</code>	<i>Full process of MLGL</i>
--------------------------	-----------------------------

Description

Run hierarchical clustering following by a group-lasso on all the different partition and a hierarchical testing procedure. Only for linear regression problem.

Usage

```
fullProcess(  
  X,  
  y,  
  control = c("FWER", "FDR"),  
  alpha = 0.05,  
  test = partialFtest,  
  hc = NULL,  
  fractionSampleMLGL = 1/2,  
  BHclust = 50,  
  nCore = NULL,  
  ...  
)  
  
fullProcess.formula(  
  formula,  
  data,  
  control = c("FWER", "FDR"),  
  alpha = 0.05,  
  test = partialFtest,  
  hc = NULL,  
  fractionSampleMLGL = 1/2,  
  ...  
)
```

Arguments

X	matrix of size n*p
y	vector of size n.
control	either "FDR" or "FWER"
alpha	control level for testing procedure
test	test used in the testing procedure. Default is <code>partialFtest</code>
hc	output of <code>hclust</code> function. If not provided, <code>hclust</code> is run with <code>ward.D2</code> method. User can also provide the desired method: "single", "complete", "average", "mcquitty", "ward.D", "ward.D2", "centroid", "median".

fractionSampleMLGL	a real between 0 and 1 : the fraction of individuals to use in the sample for MLGL (see Details).
BHclust	number of replicates for computing the distance matrix for the hierarchical clustering tree
nCore	number of cores used for distance computation. Use all cores by default.
...	Others parameters for MLGL
formula	an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted.
data	an optional data frame, list or environment (or object coercible by <code>as.data.frame</code> to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code>

Details

Divide the n individuals in two samples. Then the three following steps are done : 1) Hierarchical CLustering of the variables of X based on the first sample of individuals 2) MLGL on the second sample of individuals 3) Hierarchical testing procedure on the first sample of individuals.

Value

a list containing :

res output of [MLGL](#) function

lambdaOpt lambda values maximizing the number of rejects

var A vector containing the index of selected variables for the first `lambdaOpt` value

group A vector containing the values index of selected groups for the first `lambdaOpt` value

selectedGroups Selected groups for the first `lambdaOpt` value

reject Selected groups for all lambda values

alpha Control level

test Test used in the testing procedure

control "FDR" or "FWER"

time Elapsed time

Author(s)

Quentin Grimonprez

See Also

[MLGL](#), [hierarchicalFDR](#), [hierarchicalFWER](#), [selFDR](#), [selFWER](#)

Examples

```
# least square loss
set.seed(42)
X <- simuBlockGaussian(50, 12, 5, 0.7)
y <- X[,c(2,7,12)] %*% c(2,2,-2) + rnorm(50, 0, 0.5)
res <- fullProcess(X, y)
```

hierarchicalFDR

Hierachical testing with FDR control

Description

Apply hierarchical test for each hierarchy, and test external variables for FDR control at level alpha

Usage

```
hierarchicalFDR(X, y, group, var, test = partialFtest)
```

Arguments

X	original data
y	associated response
group	vector with index of groups. group[i] contains the index of the group of the variable var[i].
var	vector whith the variables contained in each group. group[i] contains the index of the group of the variable var[i].
test	function for testing the nullity of a group of coefficients in linear regression. 3 parameters : X : design matrix, y response and varToTest : vector of variables to test; return a pvalue

Details

Version of the hierarchical testing procedure of Yekutieli for MLGL output. You can use th [selFDR](#) function to select groups at a desired level alpha.

Value

a list containing :

- pvalues** pvalues of the different test (without correction)
- adjPvalues** adjusted pvalues
- groupId** Index of the group
- hierMatrix** Matrix describing the hierarchical tree.

References

Yekutieli, Daniel. "Hierarchical False Discovery Rate-Controlling Methodology." Journal of the American Statistical Association 103.481 (2008): 309-16.

See Also

[selfFDR](#), [hierarchicalFWER](#)

Examples

```
set.seed(42)
X = simuBlockGaussian(50,12,5,0.7)
y = X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50,0,0.5)
res = MLGL(X,y)
test = hierarchicalFDR(X, y, res$group[[20]], res$var[[20]])
```

hierarchicalFWER

Hierarchical testing with FWER control

Description

Apply hierarchical test for each hierarchy, and test external variables for FWER control at level alpha

Usage

```
hierarchicalFWER(X, y, group, var, test = partialFtest, Shaffer = FALSE)
```

Arguments

X	original data
y	associated response
group	vector with index of groups. group[i] contains the index of the group of the variable var[i].
var	vector whith the variables contained in each group. group[i] contains the index of the group of the variable var[i].
test	function for testing the nullity of a group of coefficients in linear regression. 3 parameters : X : design matrix, y response and varToTest : vector of variables to test; return a pvalue
Shaffer	boolean, if TRUE, a shaffer correction is performed

Details

Version of the hierarchical testing procedure of Meinshausen for MLGL output. You can use the [selfFWER](#) function to select groups at a desired level alph

Value

a list containing :

- pvalues** pvalues of the different test (without correction)
- adjPvalues** adjusted pvalues
- groupId** Index of the group
- hierMatrix** Matrix describing the hierarchical tree.

References

Meinshausen, Nicolai. "Hierarchical Testing of Variable Importance." Biometrika 95.2 (2008): 265-78.

See Also

[selfWER](#), [hierarchicalFDR](#)

Examples

```
set.seed(42)
X = simuBlockGaussian(50,12,5,0.7)
y = X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50,0,0.5)
res = MLGL(X,y)
test = hierarchicalFWER(X, y, res$group[[20]], res$var[[20]])
```

HMT

Hierarchical Multiple Testing procedure Apply Hierarchical Multiple Testing procedure on a [MLGL](#) object

Description

Hierarchical Multiple Testing procedure
Apply Hierarchical Multiple Testing procedure on a [MLGL](#) object

Usage

```
HMT(
  res,
  X,
  y,
  control = c("FWER", "FDR"),
  alpha = 0.05,
  test = partialFtest,
  ...
)
```

Arguments

<code>res</code>	<code>MLGL</code> object
<code>X</code>	matrix of size n*p
<code>y</code>	vector of size n.
<code>control</code>	either "FDR" or "FWER"
<code>alpha</code>	control level for testing procedure
<code>test</code>	test used in the testing procedure. Default is <code>partialFtest</code>
<code>...</code>	extra parameters fpr <code>selFDR</code>

Value

a list containing :

- lambdaOpt** lambda values maximizing the number of rejects
- var** A vector containing the index of selected variables for the first lambdaOpt value
- group** A vector containing the values index of selected groups for the first lambdaOpt value
- selectedGroups** Selected groups for the first lambdaOpt value
- reject** Selected groups for all lambda values
- alpha** Control level
- test** Test used in the testing procedure
- control** "FDR" or "FWER"
- time** Elapsed time
- hierTest** list containing the output of the testing function for each lambda. Each element can be used with the `selFWER` or `selFDR` functions.
- lambda** lambda path
- nGroup** Number of groups before testing
- nSelectedGroup** Numer of groups after testing

See Also

`hierarchicalFWER` `hierarchicalFDR` `selFWER` `selFDR`

Examples

```
set.seed(42)
X <- simuBlockGaussian(50, 12, 5, 0.7)
y <- X[,c(2,7,12)] %*% c(2,2,-2) + rnorm(50, 0, 0.5)
res <- MLGL(X, y)

# perform hierarchical testing with FWER control
out <- HMT(res, X, y, alpha = 0.05)

# test a new value of alpha for a specific lambda
selFWER(out$hierTest[[60]], alpha = 0.1)
```

listToMatrix	<i>Obtain a sparse matrix of the coefficients of the path</i>
--------------	---

Description

Obtain a sparse matrix of the coefficients of the path

Usage

```
listToMatrix(x, row = c("covariates", "lambda"))
```

Arguments

x	MLGL object
row	"lambda" or "covariates". If row="covariates", each row of the output matrix represents a covariates else if row="lambda", it represents a value of lambda.

Details

This function can be used with a [MLGL](#) object to obtain a matrix with all estimated coefficients for the p original variables. In case of overlapping groups, coefficients from repeated variables are summed.

Value

a sparse matrix containing the estimated coefficients for different values of lambda

See Also

[MLGL](#), [overlapglasso](#)

Examples

```
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50,0,0.5)
# Apply MLGL method
res <- MLGL(X,y)
# Convert output in sparse matrix format
beta <- listToMatrix(res)
```

Description

Run hierarchical clustering following by a group-lasso on all the different partitions.

Usage

```
MLGL(
  X,
  y,
  hc = NULL,
  lambda = NULL,
  weightLevel = NULL,
  weightSizeGroup = NULL,
  intercept = TRUE,
  loss = c("ls", "logit"),
  sizeMaxGroup = NULL,
  verbose = FALSE,
  ...
)

MLGL.formula(
  formula,
  data,
  hc = NULL,
  lambda = NULL,
  weightLevel = NULL,
  weightSizeGroup = NULL,
  intercept = TRUE,
  loss = c("ls", "logit"),
  verbose = FALSE,
  ...
)
```

Arguments

X	matrix of size n*p
y	vector of size n. If loss = "logit", elements of y must be in -1,1
hc	output of <code>hclust</code> function. If not provided, <code>hclust</code> is run with <code>ward.D2</code> method. User can also provide the desired method: "single", "complete", "average", "mcquitty", "ward.D", "ward.D2", "centroid", "median".
lambda	lambda values for group lasso. If not provided, the function generates its own values of lambda

weightLevel	a vector of size p for each level of the hierarchy. A zero indicates that the level will be ignored. If not provided, use 1/(height between 2 successive levels). Only if hc is provided
weightSizeGroup	a vector of size 2*p-1 containing the weight for each group. Default is the square root of the size of each group. Only if hc is provided
intercept	should an intercept be included in the model ?
loss	a character string specifying the loss function to use, valid options are: "ls" least squares loss (regression) and "logit" logistic loss (classification)
sizeMaxGroup	maximum size of selected groups. If NULL, no restriction
verbose	print some information
...	Others parameters for gglasso function
formula	an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted.
data	an optional data frame, list or environment (or object coercible by as.data.frame to a data frame) containing the variables in the model. If not found in data, the variables are taken from environment(formula)

Value

a MLGL object containing :

lambda lambda values

b0 intercept values for lambda

beta A list containing the values of estimated coefficients for each values of lambda

var A list containing the index of selected variables for each values of lambda

group A list containing the values index of selected groups for each values of lambda

nVar A vector containing the number of non zero coefficients for each values of lambda

nGroup A vector containing the number of non zero groups for each values of lambda

structure A list containing 3 vectors. var : all variables used. group : associated groups. weight : weight associated with the different groups. level : for each group, the corresponding level of the hierarchy where it appears and disappears. 3 indicates the level with a partition of 3 groups.

time computation time

dim dimension of X

hc Output of hierarchical clustering

call Code executed by user

Author(s)

Quentin Grimonprez

See Also

[cv.MLGL](#), [stability.MLGL](#), [listToMatrix](#), [predict.MLGL](#), [coef.MLGL](#), [plot.cv.MLGL](#)

Examples

```
set.seed(42)
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[,c(2, 7, 12)] %*% c(2, 2, -2) + rnorm(50, 0, 0.5)
# Apply MLGL method
res <- MLGL(X, y)
```

overlapgglasso

Group-lasso with overlapping groups

Description

Group-lasso with overlapping groups

Usage

```
overlapgglasso(
  X,
  y,
  var,
  group,
  lambda = NULL,
  weight = NULL,
  loss = c("ls", "logit"),
  intercept = TRUE,
  ...
)
```

Arguments

X	matrix of size n*p
y	vector of size n. If loss = "logit", elements of y must be in -1,1
var	vector containing the variable to use
group	vector containing the associated groups
lambda	lambda values for group lasso. If not provided, the function generates its own values of lambda
weight	a vector the weight for each group. Default is the square root of the size of each group
loss	a character string specifying the loss function to use, valid options are: "ls" least squares loss (regression) and "logit" logistic loss (classification)
intercept	should an intercept be included in the model ?
...	Others parameters for gglasso function

Details

Use a group-lasso algorithm (see [gglasso](#)) to solve a group-lasso with overlapping groups. Each variable j of the original matrix X is paste $k(j)$ times in a new dataset with $k(j)$ the number of different groups containing the variable j . The new dataset is used to solve the group-lasso with overlapping groups running a group-lasso algorithm.

Value

a MLGL object containing :

lambda lambda values
b0 intercept values for lambda
beta A list containing the values of estimated coefficients for each values of lambda
var A list containing the index of selected variables for each values of lambda
group A list containing the values index of selected groups for each values of lambda
nVar A vector containing the number of non zero coefficients for each values of lambda
nGroup A vector containing the number of non zero groups for each values of lambda
structure A list containing 3 vectors. var : all variables used. group : associated groups. weight : weight associated with the different groups.
time computation time
dim dimension of X

Source

Laurent Jacob, Guillaume Obozinski, and Jean-Philippe Vert. 2009. Group lasso with overlap and graph lasso. In Proceedings of the 26th Annual International Conference on Machine Learning (ICML '09).

See Also

[listToMatrix](#)

Examples

```
# Least square loss
set.seed(42)
X <- simuBlockGaussian(50, 12, 5, 0.7)
y <- X[, c(2, 7, 12)]%*%c(2, 2, -2) + rnorm(50, 0, 0.5)
var <- c(1:60, 1:8, 7:15)
group <- c(rep(1:12, each = 5), rep(13, 8), rep(14, 9))
res <- overlapglasso(X, y, var, group)

# Logistic loss
y <- 2*(rowSums(X[,1:4])>0)-1
var <- c(1:60, 1:8, 7:15)
group <- c(rep(1:12, each = 5), rep(13, 8), rep(14, 9))
res <- overlapglasso(X, y, var, group, loss = "logit")
```

partialFtest*Partial F-test***Description**

Perform a partial F-test

Usage

```
partialFtest(X, y, varToTest)
```

Arguments

X	design matrix of size n*p
y	response vector of length n
varToTest	vector containing the index of the column of X to test

Details

$$y = X * \beta + \epsilon$$

null hypothesis : $\beta_{\text{varToTest}} = 0$ alternative hypothesis : it exists an index k in varToTest such that $\beta_{[k]} \neq 0$

The test statistic is based on a full and a reduced model. full : $y = X * \beta + \epsilon$ reduced : $y = X * \beta[-\text{varToTest}] + \epsilon$

Value

a vector of the same length as varToTest containing the p-values of the test.

See Also

[Ftest](#)

plot.cv.MLGL*Plot the cross-validation obtained from [cv.MLGL](#) function***Description**

Plot the cross-validation obtained from [cv.MLGL](#) function

Usage

```
## S3 method for class 'cv.MLGL'
plot(x, log.lambda = FALSE, ...)
```

Arguments

<code>x</code>	cv.MLGL object
<code>log.lambda</code>	If TRUE, use log(lambda) instead of lambda in abscissa
<code>...</code>	Other parameters for plot function

See Also

[cv.MLGL](#)

Examples

```
set.seed(42)
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50,0,0.5)
# Apply cv.MLGL method
res <- cv.MLGL(X,y)
# Plot the cv error curve
plot(res)
```

plot.fullProcess*Plot the path obtained from [fullProcess](#) function***Description**

Plot the path obtained from [fullProcess](#) function

Usage

```
## S3 method for class 'fullProcess'
plot(
  x,
  log.lambda = FALSE,
  lambda.lines = FALSE,
  lambda.opt = c("min", "max", "both"),
  ...
)
```

Arguments

<code>x</code>	fullProcess object
<code>log.lambda</code>	If TRUE, use <code>log(lambda)</code> instead of <code>lambda</code> in abscissa
<code>lambda.lines</code>	If TRUE, add vertical lines at <code>lambda</code> values
<code>lambda.opt</code>	If there is several optimal <code>lambda</code> s, which one to print "min", "max" or "both"
...	Other parameters for plot function

See Also

[fullProcess](#)

Examples

```
set.seed(42)
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[,c(2, 7, 12)]%*%c(2, 2, -2) + rnorm(50, 0, 0.5)
# Apply MLGL method
res <- fullProcess(X, y)
# Plot the solution path
plot(res)
```

plot.HMT

Plot the path obtained from [HMT](#) function

Description

Plot the path obtained from [HMT](#) function

Usage

```
## S3 method for class 'HMT'
plot(
  x,
  log.lambda = FALSE,
  lambda.lines = FALSE,
  lambda.opt = c("min", "max", "both"),
  ...
)
```

Arguments

x	fullProcess object
log.lambda	If TRUE, use log(lambda) instead of lambda in abscissa
lambda.lines	If TRUE, add vertical lines at lambda values
lambda.opt	If there is several optimal lambdas, which one to print "min", "max" or "both"
...	Other parameters for plot function

See Also

[HMT](#)

Examples

```
set.seed(42)
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[,c(2, 7, 12)]%*%c(2, 2, -2) + rnorm(50, 0, 0.5)
# Apply MLGL method
res <- MLGL(X, y)

out <- HMT(res, X, y)
plot(out)
```

[plot.MLGL](#)

Plot the path obtained from [MLGL](#) function

Description

Plot the path obtained from [MLGL](#) function

Usage

```
## S3 method for class 'MLGL'
plot(x, log.lambda = FALSE, lambda.lines = FALSE, ...)
```

Arguments

<code>x</code>	<code>MLGL</code> object
<code>log.lambda</code>	If TRUE, use <code>log(lambda)</code> instead of <code>lambda</code> in abscissa
<code>lambda.lines</code>	if TRUE, add vertical lines at lambda values
<code>...</code>	Other parameters for plot function

See Also[MLGL](#)**Examples**

```
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
set.seed(42)
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50,0,0.5)
# Apply MLGL method
res <- MLGL(X, y)
# Plot the solution path
plot(res)
```

plot.stability.MLGL *Plot the stability path obtained from [stability.MLGL](#) function*

Description

Plot the stability path obtained from [stability.MLGL](#) function

Usage

```
## S3 method for class 'stability.MLGL'
plot(x, log.lambda = FALSE, threshold = 0.75, ...)
```

Arguments

<code>x</code>	stability.MLGL object
<code>log.lambda</code>	If TRUE, use <code>log(lambda)</code> instead of <code>lambda</code> in abscissa
<code>threshold</code>	Threshold for selection frequency
<code>...</code>	Other parameters for plot function

Value

A list containing :

var Index of selected variables for the given threshold.
group Index of the associated group.
threshold Value of threshold

See Also

[stability.MLGL](#)

Examples

```
set.seed(42)
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)

# Generate a response variable
y <- X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50, 0, 0.5)

# Apply stability.MLGL method
res <- stability.MLGL(X, y)
selected <- plot(res)
print(selected)
```

predict.cv.MLGL

Predict fitted values from a [cv.MLGL](#) object

Description

Predict fitted values from a [cv.MLGL](#) object

Usage

```
## S3 method for class 'cv.MLGL'
predict(
  object,
  newx = NULL,
  s = c("lambda.1se", "lambda.min"),
  type = c("fit", "coefficients"),
  ...
)
```

Arguments

object	cv.MLGL object
newx	matrix with new individuals for prediction. If type="coefficients", the parameter has to be NULL
s	Either "lambda.1se" or "lambda.min"
type	if "fit", return the fitted values for each values of s, if "coefficients", return the estimated coefficients for each s
...	Not used. Other arguments to predict.

Value

A matrix with fitted values or estimated coefficients for given values of s.

Author(s)

Quentin Grimonprez

See Also

[cv.MLGL](#)

[predict.MLGL](#)

Predict fitted values from a [MLGL](#) object

Description

Predict fitted values from a [MLGL](#) object

Usage

```
## S3 method for class 'MLGL'
predict(object, newx = NULL, s = NULL, type = c("fit", "coefficients"), ...)
```

Arguments

object	MLGL object
newx	matrix with new individuals for prediction. If type="coefficients", the parameter has to be NULL
s	values of lambda. If NULL, use values from object
type	if "fit", return the fitted values for each values of s, if "coefficients", return the estimated coefficients for each s
...	Not used. Other arguments to predict.

Value

A matrix with fitted values or estimated coefficients for given values of s.

Author(s)

original code from **gglasso** package Author: Yi Yang <yiyang@umn.edu>, Hui Zou <hzou@stat.umn.edu>
function inspired from predict function from gglasso package by Yi Yang and Hui Zou.

See Also

[MLGL](#)

print.fullProcess *Print Values Print a fullProcess object*

Description

Print Values

Print a **fullProcess** object

Usage

```
## S3 method for class 'fullProcess'  
print(x, ...)
```

Arguments

x	fullProcess object
...	Not used.

See Also

[fullProcess](#) [summary.fullProcess](#)

Examples

```
set.seed(42)  
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5  
X <- simuBlockGaussian(50, 12, 5, 0.7)  
# Generate a response variable  
y <- X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50,0,0.5)  
# Apply MLGL method  
res <- fullProcess(X, y)  
print(res)
```

print.HMT*Print Values Print a HMT object***Description**

Print Values

Print a [HMT](#) object**Usage**

```
## S3 method for class 'HMT'
print(x, ...)
```

Arguments

x	HMT object
...	Not used.

See Also[HMT](#) [summary.HMT](#)**Examples**

```
set.seed(42)
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50,0,0.5)
# Apply MLGL method
res <- MLGL(X, y)
out <- HMT(res, X, y)
print(out)
```

print.MLGL*Print Values Print a MLGL object***Description**

Print Values

Print a [MLGL](#) object**Usage**

```
## S3 method for class 'MLGL'
print(x, ...)
```

Arguments

x	MLGL object
...	Not used.

See Also

[MLGL summary](#).[MLGL](#)

Examples

```
set.seed(42)
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50, 0, 0.5)
# Apply MLGL method
res <- MLGL(X,y)
print(res)
```

selFDR

Selection from hierarchical testing with FDR control

Description

Select groups from hierarchical testing procedure with FDR control ([hierarchicalFDR](#))

Usage

```
selFDR(out, alpha = 0.05, global = TRUE, outer = TRUE)
```

Arguments

out	output of hierarchicalFDR function
alpha	control level for test
global	if FALSE the provided alpha is the desired level control for each family.
outer	if TRUE, the FDR is controlled only on outer node (rejected groups without rejected children) . If FALSE, it is controlled on the full tree.

Details

See the reference for mode details about the method.

If each family is controlled at a level alpha, we have the following control : FDR control of full tree : $\alpha * \delta * 2$ ($\delta = 1.44$) FDR control of outer node : $\alpha * L * \delta * 2$ ($\delta = 1.44$)

Value

a list containing :

toSel vector of boolean. TRUE if the group is selected

groupId Names of groups

local.alpha control level for each family of hypothesis

global.alpha control level for the tree (full tree or outer node)

References

Yekutieli, Daniel. "Hierarchical False Discovery Rate-Controlling Methodology." Journal of the American Statistical Association 103.481 (2008): 309-16.

See Also

[hierarchicalFDR](#)

Examples

```
set.seed(42)
X = simuBlockGaussian(50,12,5,0.7)
y = X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50,0,0.5)
res = MLGL(X,y)
test = hierarchicalFDR(X, y, res$group[[20]], res$var[[20]])
sel = selFDR (test, alpha = 0.05)
```

selFWER

Selection from hierarchical testing with FWER control

Description

Select groups from hierarchical testing procedure with FWER control ([hierarchicalFWER](#))

Usage

```
selFWER(out, alpha = 0.05)
```

Arguments

out	output of hierarchicalFDR function
alpha	control level for test

Details

Only outer nodes (rejected groups without rejected children) are returned as TRUE.

Value

a list containing :

toSel vector of boolean. TRUE if the group is selected

groupId Names of groups

References

Meinshausen, Nicolai. "Hierarchical Testing of Variable Importance." Biometrika 95.2 (2008): 265-78.

See Also

[hierarchicalFWER](#)

Examples

```
set.seed(42)
X = simuBlockGaussian(50,12,5,0.7)
y = X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50,0,0.5)
res = MLGL(X,y)
test = hierarchicalFWER(X, y, res$group[[20]], res$var[[20]])
sel = selfWER (test, alpha = 0.05)
```

simuBlockGaussian	<i>Simulate multivariate Gaussian samples with block diagonal variance matrix</i>
--------------------------	---

Description

simulate n samples from a gaussian multivariate law with 0 vector mean and block diagonal variance matrix with diagonal 1 and block of rho.

Usage

```
simuBlockGaussian(n, nBlock, sizeBlock, rho)
```

Arguments

n	number of samples to simulate
nBlock	number of blocks
sizeBlock	size of blocks
rho	correlation within each block

Value

a matrix of size n *(nBlock*sizeBlock) containing the samples

Author(s)

Quentin Grimonprez

Examples

```
X = simuBlockGaussian(50,12,5,0.7)
```

stability.MLGL

Stability Selection for Multi-Layer Group-lasso

Description

Stability selection for [MLGL](#)

Usage

```
stability.MLGL(
  X,
  y,
  B = 50,
  fraction = 0.5,
  hc = NULL,
  lambda = NULL,
  weightLevel = NULL,
  weightSizeGroup = NULL,
  loss = c("ls", "logit"),
  intercept = TRUE,
  verbose = FALSE,
  ...
)
```

Arguments

X	matrix of size n*p
y	vector of size n. If loss = "logit", elements of y must be in -1,1
B	number of bootstrap sample
fraction	Fraction of data used at each of the B sub-samples
hc	output of hclust function. If not provided, hclust is run with ward.D2 method
lambda	lambda values for group lasso. If not provided, the function generates its own values of lambda
weightLevel	a vector of size p for each level of the hierarchy. A zero indicates that the level will be ignored. If not provided, use 1/(height between 2 successive levels)

weightSizeGroup	a vector
loss	a character string specifying the loss function to use, valid options are: "ls" least squares loss (regression) and "logit" logistic loss (classification)
intercept	should an intercept be included in the model ?
verbose	print some informations
...	Others parameters for gglasso function

Details

Hierarchical clustering is performed with all the variables. Then, the partitions from the different levels of the hierarchy are used in the different run of MLGL for estimating the probability of selection of each group.

Value

a stability.MLGL object containing :

lambda sequence of lambda.

B Number of bootstrap samples.

stability A matrix of size length(lambda)*number of groups containing the probability of selection of each group

var vector containing the index of covariates

group vector containing the index of associated groups of covariates

time computation time

Author(s)

Quentin Grimonprez

References

Meinshausen and Bühlmann (2010). Stability selection. In : Journal of the Royal Statistical Society : Series B (Statistical Methodology) 72.4, p. 417-473.

See Also

[cv.MLGL](#), [MLGL](#)

Examples

```
set.seed(42)
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)

# Generate a response variable
y <- X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50, 0, 0.5)
```

```
# Apply stability.MLGL method
res <- stability.MLGL(X, y)
```

summary.fullProcess *Object Summaries Summary of a [fullProcess](#) object*

Description

Object Summaries
Summary of a [fullProcess](#) object

Usage

```
## S3 method for class 'fullProcess'
summary(object, ...)
```

Arguments

object	fullProcess object
...	Not used.

See Also

[fullProcess](#) [print.fullProcess](#)

Examples

```
set.seed(42)
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50,0,0.5)
# Apply MLGL method
res <- fullProcess(X, y)
summary(res)
```

summary.HMT

Object Summaries Summary of a HMT object

Description

Object Summaries
Summary of a HMT object

Usage

```
## S3 method for class 'HMT'  
summary(object, ...)
```

Arguments

object	HMT object
...	Not used.

See Also

[HMT](#) [print.HMT](#)

Examples

```
set.seed(42)  
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5  
X <- simuBlockGaussian(50, 12, 5, 0.7)  
# Generate a response variable  
y <- X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50,0,0.5)  
# Apply MLGL method  
res <- MLGL(X, y)  
out <- HMT(res, X, y)  
summary(out)
```

summary.MLGL

Object Summaries Summary of a MLGL object

Description

Object Summaries
Summary of a MLGL object

Usage

```
## S3 method for class 'MLGL'  
summary(object, ...)
```

Arguments

- | | |
|--------|-----------------------------|
| object | MLGL object |
| ... | Not used. |

See Also

[MLGL](#) [print.MLGL](#)

Examples

```
set.seed(42)
# Simulate gaussian data with block-diagonal variance matrix containing 12 blocks of size 5
X <- simuBlockGaussian(50, 12, 5, 0.7)
# Generate a response variable
y <- X[,c(2,7,12)]%*%c(2,2,-2) + rnorm(50,0,0.5)
# Apply MLGL method
res <- MLGL(X,y)
summary(res)
```

uniqueGroupHclust *Find all unique groups in [hclust](#) results*

Description

Find all unique groups in [hclust](#) results

Usage

`uniqueGroupHclust(hc)`

Arguments

- | | |
|----|---|
| hc | output of hclust function |
|----|---|

Value

A list containing :

indexGroup Vector containing the index of variables.

varGroup Vector containing the index of the group of each variable.

Author(s)

Quentin Grimonprez

Examples

```
hc <- hclust(dist(USArrests), "ave")
res <- uniqueGroupHclust(hc)
```

Index

*Topic **package**
 MLGL-package, 2

bootstrapHclust, 3

 coef.cv.MLGL, 4, 7
 coef.MLGL, 5, 17
 computeGroupSizeWeight, 5
 cv.gglasso, 7
 cv.MLGL, 3, 4, 6, 17, 21, 25, 26, 33

Ftest, 8, 20

fullProcess, 3, 9, 21–23, 27, 34

gglasso, 17–19, 33

 hclust, 7, 9, 16, 32, 36
 hierarchicalFDR, 10, 11, 13, 14, 29, 30
 hierarchicalFWER, 3, 10, 12, 12, 14, 30, 31
 HMT, 13, 22, 23, 28, 35

listToMatrix, 15, 17, 19

MLGL, 3, 5–7, 10, 13–15, 16, 23, 24, 26–29, 32,
 33, 35, 36

MLGL-package, 2

overlapgglasso, 15, 18

partialFtest, 8, 9, 14, 20

plot.cv.MLGL, 7, 17, 21

plot.fullProcess, 21

plot.HMT, 22

plot.MLGL, 23

plot.stability.MLGL, 24

predict.cv.gglasso, 7

predict.cv.MLGL, 4, 25

predict.MLGL, 5, 17, 26

print.fullProcess, 27, 34

print.HMT, 28, 35

print.MLGL, 28, 36

 selfFDR, 10–12, 14, 29
 selfWER, 3, 10, 12–14, 30
 simuBlockGaussian, 31
 stability.MLGL, 7, 17, 24, 25, 32
 summary.fullProcess, 27, 34
 summary.HMT, 28, 35
 summary.MLGL, 29, 35

uniqueGroupHclust, 36