

Package ‘MultiplierDEA’

April 27, 2018

Type Package

Title Multiplier Data Envelopment Analysis and Cross Efficiency

Version 0.1.18

Date 2018-04-27

Author Aurobindh Kalathil Puthanpura <kalat2@pdx.edu>

Maintainer Aurobindh Kalathil Puthanpura <kalat2@pdx.edu>

Description

Functions are provided for calculating efficiency using multiplier DEA (Data Envelopment Analysis): Measuring the efficiency of decision making units (Charnes et al., 1978 <doi:10.1016/0377-2217(78)90138-8>) and cross efficiency using single and two-phase approach. In addition, it includes some datasets for calculating efficiency and cross efficiency.

License LGPL-2

Repository CRAN

Depends lpSolveAPI

NeedsCompilation no

LazyData true

Date/Publication 2018-04-27 17:24:13 UTC

R topics documented:

Bank_Branch_Operating_Efficiency	2
BenchMark_Tests_And_Microcomputer	3
CrossEfficiency	4
DeaMultiplierModel	5
Departments_Of_Accounting	7
dict.solveStatus	8
Evaluations_Of_NonProfitOrganizations	8
Evaluation_Educational_Program	9
Mal_Ben	11
Metropolitan_And_London_Rates_Departments	13
options.orientation.l	14
options.phase.l	14
options.rts.l	14

Bank_Branch_Operating_Efficiency
Data: Bank Branch Operating Efficiency data

Description

Bank Branch data for Operating Efficiency.

Usage

`Bank_Branch_Operating_Efficiency`

Format

A data frame containing data for 17 Bank Branches.

`Branch_Code` a character vector
`PH` a numeric vector
`OE` a numeric vector
`SQM` a numeric vector
`A` a numeric vector
`B` a numeric vector
`C` a numeric vector
`D` a numeric vector

Source

Giokas DI (1991) Bank branch operating efficiency: A comparative application of DEA and the Loglinear model, OMEGA International Journal of Management Science, 19 (6) 549-557.

References

Giokas DI (1991) Bank branch operating efficiency: A comparative application of DEA and the Loglinear model, OMEGA International Journal of Management Science, 19 (6) 549-557.

Examples

```

data(Bank_Branch_Operating_Efficiency)
attach(Bank_Branch_Operating_Efficiency)
x <- data.frame(PH, OE, SQM)
rownames(x) <- Branch_Code
colnames(x) <- colnames(Bank_Branch_Operating_Efficiency)[2:4]
y <- data.frame(A, B, C, D)
rownames(y) <- Branch_Code
colnames(y) <- colnames(Bank_Branch_Operating_Efficiency)[5:8]

```

```

detach(Bank_Branch_Operating_Efficiency)
# For CRS
result_CRS <- DeaMultiplierModel(x,y,"crs", "input")
# For VRS
result_VRS <- DeaMultiplierModel(x,y,"crs", "input")

```

BenchMark_Tests_And_Microcomputer

Data: Relationship between benchmark tests and Microcomputer price data

Description

The Relationship between benchmark tests and Microcomputer price data.

Usage

`BenchMark_Tests_And_Microcomputer`

Format

A data frame containing data for 22 Microcomputers.

`System` a character vector

`Price` a numeric vector

`MemorySize` a numeric vector

`DiskCapacity` a numeric vector

`CPU` a numeric vector

`IO` a numeric vector

`RL1` a numeric vector

`RL2` a numeric vector

`RL3` a numeric vector

Source

Sircar S. and Dave D (1986) Tbe relationship between benchmark tests and microcomputer price. Communications of the ACM, 29, 212-217.

References

Sircar S. and Dave D (1986) Tbe relationship between benchmark tests and microcomputer price. Communications of the ACM, 29, 212-217.

Examples

```
data(BenchMark_Tests_And_Microcomputer)
attach(BenchMark_Tests_And_Microcomputer)

x <- BenchMark_Tests_And_Microcomputer

detach(BenchMark_Tests_And_Microcomputer)
```

CrossEfficiency	<i>Cross Efficiency Model</i>
-----------------	-------------------------------

Description

Cross Efficiency uses DEA to do peer evaluation of DMUs. Single-phase cross efficiency approach.

Usage

```
CrossEfficiency(x = x, y = y, rts = "crs", orientation = "input", weightRestriction)
```

Arguments

x	Inputs or resources used by each decision making unit.
y	Outputs or resources used by each decision making unit.
rts	Returns to scale for the application, or industry studied. Note the default rts is crs. vrs Variable returns to scale. crs Constant returns to scale.
orientation	Orientation of the DEA model - primary emphasis on input-reduction input or output-augmentation output. Note that unlike the DEA functions, the default is input orientation.
weightRestriction	Weight restriction for the model. Optional parameter.

Value

The function returns a number of values per DMU.

\$ceva_matrix	Returns the cross efficiency matrix. Row is the Rating DMU and Column is the Rated DMU.
\$ce_ave	Returns the cross efficiency score for the DMU.
\$ceva_max	Returns the maximum cross efficiency score for the DMU.
\$ceva_min	Returns the minimum cross efficiency score for the DMU.
\$vx	Input weights from the model.
\$uy	Output weights from the model.
\$Model_Status	Returns the status of the LP model.

Note

ceva_matrix - cross-evaluation matrix. ceva_max - cross-evaluation maximum. ceva_min - cross-evaluation minimum. ce_ave - cross-efficiency scores.

Examples

```
#Example from Kenneth R. Baker: Optimization Modeling with Spreadsheets, Third Edition,p. 176,
#John Wiley and Sons, Inc.

dmu <- c("A", "B", "C", "D", "E", "F")
x <- data.frame(c(150,400,320,520,350,320),c(0.2,0.7,1.2,2.0,1.2,0.7))
rownames(x) <- dmu
colnames(x)[1] <- c("StartHours")
colnames(x)[2] <- c("Supplies")

y <- data.frame(c(14,14,42,28,19,14),c(3.5,21,10.5,42,25,15))
rownames(y) <- dmu
colnames(y)[1] <- c("Reimbursed")
colnames(y)[2] <- c("Private")

# Calculate the efficiency score
result <- CrossEfficiency(x,y,"crs", "input")
# Examine the cross efficiency score for DMUs
print(result$ce_ave)
```

Description

DEA multiplier model calculates the efficiency and reference sets for each DMUs.

Usage

```
DeaMultiplierModel(x = x, y = y, rts = "crs", orientation = "input", weightRestriction)
```

Arguments

x	Inputs or resources used by each decision making unit.
y	Outputs or resources used by each decision making unit.
rts	Returns to scale for the application, or industry studied. Note the default rts is crs. vrs Variable returns to scale. crs Constant returns to scale. Available option: crs, vrs
orientation	Orientation of the DEA model - primary emphasis on input-reduction or output-augmentation output. Note that unlike the DEA functions, the default is input orientation. Available option: input, output.
weightRestriction	Weight restriction for the model. Optional parameter.

Value

The function returns a number of values per DMU. The standardized efficiency (all inefficiencies are between 0 and 1, for input and output orientation). Efficiency, and lambda values are returned.

\$rts	Returns to scale of the model.
\$Orientation	Orientation of the model.
\$InputValues	Input Values (x) passed to the model.
\$OutputValues	Output Values (y) passed to the model.
\$Efficiency	Efficiency of each DMU in the model.
\$Lambda	Lambdas per DMU in the model.
\$HCU_Input	HCU data for inputs.
\$HCU_Output	HCU data for outputs.
\$vx	Input weights from the model.
\$uy	Output weights from the model.
\$Free_Weights	Free weights from the model. Applies only to vrs returns-to-scale.
\$Model_Status	Returns the status of the LP model.

Examples

```
#Example from Kenneth R. Baker: Optimization Modeling with Spreadsheets, Third Edition,p. 176,
#John Wiley and Sons, Inc.

dmu <- c("A", "B", "C", "D", "E", "F")

x <- data.frame(c(150,400,320,520,350,320),c(0.2,0.7,1.2,2.0,1.2,0.7))
rownames(x) <- dmu
colnames(x)[1] <- c("StartHours")
colnames(x)[2] <- c("Supplies")

y <- data.frame(c(14,14,42,28,19,14),c(3.5,21,10.5,42,25,15))
rownames(y) <- dmu
colnames(y)[1] <- c("Reimbursed")
colnames(y)[2] <- c("Private")

#Creating the weight restriction data frame with Upper bound

weightRestriction<-data.frame(lower = c(1), numerator = c("StartHours"),
denominator = c("Supplies"), upper = c(2))

#Creating the weight restriction data frame without Upper bound
weightRestriction<-data.frame(lower = c(1), numerator = c("StartHours"),
denominator = c("Supplies"))

#Creating the weight restriction data frame with Upper bound and Na, Inf or NaN
weightRestriction<-data.frame(lower = c(1,2), numerator = c("StartHours","Reimbursed"),
denominator = c("Supplies","Private"), upper = c(2,Inf))
```

```

# Calculate the efficiency score without weight Restriction
result <- DeaMultiplierModel(x,y,"crs", "input")
# Examine the efficiency score for DMUs
print(result$Efficiency)

# Calculate the efficiency score with weight Restriction
result <- DeaMultiplierModel(x,y,"crs", "input", weightRestriction)
# Examine the efficiency score for DMUs
print(result$Efficiency)

```

Departments_Of_Accounting*Data: UK University Departments Of Accounting Efficiency data.***Description**

Evaluation the Efficiency of UK University Departments Of Accounting Efficiency.

Usage

```
Departments_Of_Accounting
```

Format

A data frame containing data for 20 UK University Departments Of Accounting.

```

Departments a numeric vector
Undergraduates a numeric vector
Research a numeric vector
Taught a numeric vector
Res.Co a numeric vector
OtherRes a numeric vector
OtherIncome a numeric vector
Publications a numeric vector
AcademicStaff a numeric vector
Salaries a numeric vector
OtherExp a numeric vector

```

Source

Tomkins C and Green RH (1988) An experiment in the use of data envelopment analysis for evaluating the efficiency of UK university departments of accounting. Financial Accounting and Management, 4, 147-164.

References

Tomkins C and Green RH (1988) An experiment in the use of data envelopment analysis for evaluating the efficiency of UK university departments of accounting. *Financial Accounting and Management*, 4, 147-164.

Examples

```
data(Departments.Of.Accounting)
attach(Departments.Of.Accounting)

x <- data.frame(AcademicStaff)
rownames(x) <- Departments
colnames(x) <- colnames(Departments.Of.Accounting)[9]

y <- data.frame(Undergraduates, Research, Taught,(Res.Co + OtherRes + OtherIncome))
rownames(y) <- Departments
colnames(y)[1] <- colnames(Departments.Of.Accounting)[2]
colnames(y)[2] <- colnames(Departments.Of.Accounting)[3]
colnames(y)[3] <- colnames(Departments.Of.Accounting)[4]
colnames(y)[4] <- c("Total_Income")

detach(Departments.Of.Accounting)

result <- DeaMultiplierModel(x,y,"crs", "input")
```

`dict.solveStatus` *Provides the solver status codes.*

Description

Provides the solver status codes and description.

Examples

```
#List status codes and description.
```

```
dict.solveStatus
```

`Evaluations.Of.NonProfitOrganizations`
Data: Evaluation of Non-Profit organizations data

Description

Evaluation of Non-Profit organizations efficiency.

Usage

```
Evaluations.Of.NonProfitOrganizations
```

Format

A data frame containing data for 16 Non-Profit organizations.

Hospital a numeric vector

H0 a numeric vector

PercentOccupancy a numeric vector

RevenuePerDay a numeric vector

A/RTurnover a numeric vector

CostPerDay a numeric vector

LengthOfStay a numeric vector

Source

Greenberg R and Nunamaker T (1987) A generalized multiple criteria model for control and evaluation of nonprofit organizations. *Financial Accountability and Management*, 3 (4), 331-342.

References

Greenberg R and Nunamaker T (1987) A generalized multiple criteria model for control and evaluation of nonprofit organizations. *Financial Accountability and Management*, 3 (4), 331-342.

Examples

```
data(Evaluations.Of.NonProfitOrganizations)
attach(Evaluations.Of.NonProfitOrganizations)

x <- Evaluations.Of.NonProfitOrganizations

detach(Evaluations.Of.NonProfitOrganizations)
```

Description

Evaluation of Educational program.

Usage

```
Evaluation_Educational_Program
```

Format

A data frame containing data for 22 educational programs.

```
Program a numeric vector
CCR_EFF a numeric vector
Revenue_Generated a numeric vector
Student_Employed a numeric vector
Employer_Satisfaction a numeric vector
Contact_Hours a numeric vector
Number_of_FTE_Staff a numeric vector
Facility_Allocation a numeric vector
Expenditures a numeric vector
```

Source

Bessent A, Bessent W, Chames A, Cooper WW and Thorgood N (1983) Evaluation of educational program proposals by means of data envelopment analysis. *Educational Administrative Quarterly*, 19, 82-107.

References

Bessent A, Bessent W, Chames A, Cooper WW and Thorgood N (1983) Evaluation of educational program proposals by means of data envelopment analysis. *Educational Administrative Quarterly*, 19, 82-107.

Examples

```
data(Evaluation_Educational_Program)
attach(Evaluation_Educational_Program)

x <- data.frame(Contact_Hours, Number_of_FTE_Staff, Facility_Allocation, Expenditures)
rownames(x) <- Program
colnames(x) <- colnames(Evaluation_Educational_Program)[6:9]

y <- data.frame(Revenue_Generated, Student_Employed, Employer_Satisfaction)
rownames(y) <- Program
colnames(y) <- colnames(Evaluation_Educational_Program)[3:5]

detach(Evaluation_Educational_Program)

result <- DeaMultiplierModel(x,y,"crs", "input")
```

Mal_Ben*Benevolent and Malevolent Model*

Description

Two-Phase Cross efficiency approach.

Usage

```
Mal_Ben(x = x, y = y, rts ="crs", orientation = "input", phase = "mal",
weightRestriction, include = TRUE)
```

Arguments

x	Inputs or resources used by each decision making unit.
y	Outputs or resources used by each decision making unit.
rts	Returns to scale for the application, or industry studied. Note the default rts is crs. vrs Variable returns to scale. crs Constant returns to scale. Available option: crs, vrs.
orientation	Orientation of the DEA model - primary emphasis on input-reduction input or output-augmentation output. Note that unlike the DEA functions, the default is input orientation. Available option: input, output.
weightRestriction	Weight restriction for the model. Optional parameter.
phase	Second phase of the model. Malevolent or Benevolent. Note the default is mal. Available option: mal, ben.
include	In the second phase include evaluating DMU in the calculation. Default is TRUE. Available option: TRUE, FALSE.

Value

The function returns a number of values per DMU. The standardized efficiency (all inefficiencies are between 0 and 1, for input and output orientation) Efficiency, and the lambda values, lambda, are returned.

\$rts	Returns to scale of the model.
\$Orientation	Orientation of the model.
\$InputValues	Input Values (x) passed to the model.
\$OutputValues	Output Values (y) passed to the model.
\$Phase1_Efficiency	Efficiency of each DMU in the model from Phase 1.
\$Phase1_Lambda	Lambdas per DMU in the model from Phase 1.
\$Phase1_vx	Input weights from the model from Phase 1.

\$Phase1_uy Output weights from the model from Phase 1.
 \$Phase1_Free_Weights
 Free weights from the model from Phase 1. Applies only to vrs returns-to-scale.
 \$Phase1_Model_Status
 Returns the status of the phase two LP model.
 \$Phase2_Efficiency
 Efficiency of each DMU in the model from Phase 2.
 \$Phase2_Lambda
 Lambdas per DMU in the model from Phase 2.
 \$Phase2_vx Input weights from the model from Phase 2.
 \$Phase2_uy Output weights from the model from Phase 2.
 \$Phase2_Free_weights
 Free weights from the model from Phase 2. Applies only to vrs returns-to-scale.
 \$Phase2_Model_Status
 Returns the status of the phase two LP model.
 \$ceva_matrix Returns the cross efficiency matrix. Row is the Rating DMU and Column is the Rated DMU.
 \$ce_ave Returns the cross efficiency score for the DMU.
 \$ceva_max Returns the maximum cross efficiency score for the DMU.
 \$ceva_min Returns the minimum cross efficiency score for the DMU.

Note

ceva_matrix - cross-evaluation matrix. ceva_max - cross-evaluation maximum. ceva_min - cross-evaluation minimum. ce_ave - cross-efficiency scores.

Examples

```

#Example from Kenneth R. Baker: Optimization Modeling with Spreadsheets, Third Edition,p. 176,
#John Wiley and Sons, Inc.

dmu <- c("A", "B", "C", "D", "E", "F")
x <- data.frame(c(150,400,320,520,350,320),c(0.2,0.7,1.2,2.0,1.2,0.7))
rownames(x) <- dmu
colnames(x)[1] <- c("StartHours")
colnames(x)[2] <- c("Supplies")
y <- data.frame(c(14,14,42,28,19,14),c(3.5,21,10.5,42,25,15))
rownames(y) <- dmu
colnames(y)[1] <- c("Reimbursed")
colnames(y)[2] <- c("Private")

# Calculate the efficiency score
result <- Mal_Ben(x, y, rts = "crs", orientation = "input",phase = "mal", include = TRUE)
# Examine the cross efficiency score for DMUs
print(result$ce_ave)
  
```

Metropolitan_And_London_Rates_Departments*Data: Metropolitan and London rates departments data*

Description

Relative Efficiency Metropolitan and London rates departments.

Usage

```
Metropolitan_And_London_Rates_Departments
```

Format

A data frame containing data for 62 rates department authority.

Authority a character vector
 TotalCost a numeric vector
 Non-cnl a numeric vector
 Rate a numeric vector
 Summons a numeric vector
 NPV a numeric vector

Source

Dyson RG and Thanassoulis E (1988) Reducing weight flexibility in Data Envelopment Analysis, Journal of the Operational Research Society, 39 (6), 563-576.

References

Dyson RG and Thanassoulis E (1988) Reducing weight flexibility in Data Envelopment Analysis, Journal of the Operational Research Society, 39 (6), 563-576.

Examples

```
data(Metropolitan_And_London_Rates_Departments)
attach(Metropolitan_And_London_Rates_Departments)

x <- data.frame(TotalCost)
rownames(x) <- Authority
colnames(x) <- colnames(Metropolitan_And_London_Rates_Departments)[2]

y <- data.frame(`Non-cnl`, Rate, Summons, NPV)
rownames(y) <- Authority
colnames(y) <- colnames(Metropolitan_And_London_Rates_Departments)[3:6]
```

```
detach(Metropolitan_And_London_Rates_Departments)

result <- DeaMultiplierModel(x,y,"crs", "input")
```

options.orientation.l *Provides the orientation option.*

Description

Provides the orientation option values.

Examples

```
# List the orientation option used as arguments.

options.orientation.l
```

options.phase.l *Provides the second phase options.*

Description

Provides the second phase options available for Mal_Ben function.

Examples

```
# List the phase option used as arguments.

options.phase.l
```

options.rts.l *Provides the rts (returns to scale) option.*

Description

Provides the rts (returns to scale) option values.

Examples

```
# List the returns to scale option used as arguments.

options.rts.l
```

Index

*Topic Assurance Region

CrossEfficiency, 4
DeaMultiplierModel, 5
dict.solveStatus, 8
Mal_Ben, 11
options.orientation.l, 14
options.phase.l, 14
options.rts.l, 14

*Topic Benevolent

CrossEfficiency, 4
DeaMultiplierModel, 5
dict.solveStatus, 8
Mal_Ben, 11
options.orientation.l, 14
options.phase.l, 14
options.rts.l, 14

*Topic Cross Efficiency

CrossEfficiency, 4
DeaMultiplierModel, 5
dict.solveStatus, 8
Mal_Ben, 11
options.orientation.l, 14
options.phase.l, 14
options.rts.l, 14

*Topic DEA

CrossEfficiency, 4
DeaMultiplierModel, 5
dict.solveStatus, 8
Mal_Ben, 11
options.orientation.l, 14
options.phase.l, 14
options.rts.l, 14

*Topic Malevolent

CrossEfficiency, 4
DeaMultiplierModel, 5
dict.solveStatus, 8
Mal_Ben, 11
options.orientation.l, 14
options.phase.l, 14

options.rts.l, 14

*Topic Multiplier DEA Model

CrossEfficiency, 4
DeaMultiplierModel, 5
dict.solveStatus, 8
Mal_Ben, 11
options.orientation.l, 14
options.phase.l, 14
options.rts.l, 14

*Topic Single-Phase Approach

CrossEfficiency, 4
DeaMultiplierModel, 5
dict.solveStatus, 8
Mal_Ben, 11
options.orientation.l, 14
options.phase.l, 14
options.rts.l, 14

*Topic Two-Phase Approach

CrossEfficiency, 4
DeaMultiplierModel, 5
dict.solveStatus, 8
Mal_Ben, 11
options.orientation.l, 14
options.phase.l, 14
options.rts.l, 14

*Topic Weight restrictions

CrossEfficiency, 4
DeaMultiplierModel, 5
dict.solveStatus, 8
Mal_Ben, 11
options.orientation.l, 14
options.phase.l, 14
options.rts.l, 14

*Topic datasets

Bank_Branch_Operating_Efficiency,
2
BenchMark_Tests_And_Microcomputer,
3
Departments_Of_Accounting, 7

Evaluation_Educational_Program, 9
Evaluations_Of_NonProfitOrganizations,
 8
Metropolitan_And_London_Rates_Departments,
 13

Bank_Branch_Operating_Efficiency, 2
BenAndMal (Mal_Ben), 11
BenchMark_Tests_And_Microcomputer, 3

CrossEfficiency, 4

DeaMultiplierModel, 5
Departments_Of_Accounting, 7
dict.solveStatus, 8

Evaluation_Educational_Program, 9
Evaluations_Of_NonProfitOrganizations,
 8

Mal_Ben, 11
Metropolitan_And_London_Rates_Departments,
 13

options.orientation.l, 14
options.phase.l, 14
options.rts.l, 14