

# Package ‘ProcData’

May 12, 2020

**Type** Package

**Title** Process Data Analysis

**Version** 0.2.5

**Date** 2020-05-08

## **Description**

General tools for exploratory process data analysis. Process data refers to the data describing participants' problem solving processes in computer-based assessments. It is often recorded in computer log files. This package provides two action sequence generators and implements two automatic feature extraction methods that compress the information stored in process data, which often has a nonstandard format, into standard numerical vectors. This package also provides recurrent neural network based models that relate response processes with other binary or scale variables of interest. The functions that involve training and evaluating neural networks are wrappers of functions in 'keras'.

**BugReports** <https://github.com/xytangtang/ProcData/issues>

**License** GPL (>= 2)

**Depends** R (>= 3.5)

**Imports** Rcpp (>= 0.12.16), keras (>= 2.2.4)

**LinkingTo** Rcpp

**SystemRequirements** Python (>= 2.7)

**RoxygenNote** 6.1.1

**LazyData** true

**NeedsCompilation** yes

**Author** Xueying Tang [aut, cre],  
Susu Zhang [aut],  
Zhi Wang [aut],  
Jingchen Liu [aut],  
Zhiliang Ying [aut]

**Maintainer** Xueying Tang <xueyingtang1989@gmail.com>

**Repository** CRAN

**Date/Publication** 2020-05-12 10:10:15 UTC

## R topics documented:

ProcData-package . . . . .	3
action_seqs_summary . . . . .	4
aseq2feature_seq2seq . . . . .	5
atseq2feature_seq2seq . . . . .	6
calculate_dist_cpp . . . . .	9
cc_data . . . . .	9
chooseK_mds . . . . .	10
chooseK_seq2seq . . . . .	11
combine_actions . . . . .	12
count_actions . . . . .	13
predict.seqm . . . . .	14
print.proc . . . . .	15
proc . . . . .	15
read.seqs . . . . .	16
remove_action . . . . .	17
remove_repeat . . . . .	17
replace_action . . . . .	18
seq2feature_mds . . . . .	18
seq2feature_mds_large . . . . .	20
seq2feature_mds_stochastic . . . . .	21
seq2feature_seq2seq . . . . .	22
seqm . . . . .	24
seq_gen . . . . .	27
seq_gen2 . . . . .	28
seq_gen3 . . . . .	29
sub_seqs . . . . .	30
summary.proc . . . . .	31
time_seqs_summary . . . . .	32
tseq2feature_seq2seq . . . . .	32
tseq2interval . . . . .	34
write.seqs . . . . .	35
<b>Index</b>	<b>36</b>

## Description

General tools for exploratory process data analysis. Process data refers to the data describing participants' problem solving processes in computer-based assessments. It is often recorded in computer log files. This package a process dataset and functions for reading processes from a csv file, process manipulation, action sequence generators. It also implements two automatic feature extraction methods that compress the information stored in process data, which often has a nonstandard format, into standard numerical vectors. This package also provides recurrent neural network based models that relate response processes with other binary or scale variables of interest. The functions that involve training and evaluating neural networks are based on functions in keras.

## Data structure

ProcData organizes response processes as an object of class `proc`. Some functions are provided for summarizing and manipulating `proc` objects.

- `summary.proc` calculates summary statistics of a `proc` object.
- `remove_action` removes actions and the corresponding timestamps
- `replace_action` replaces an action by another action
- `combine_actions` combines consecutive action into one action.

## Read sequences

- `read.seq` reads response processes from a csv file.

## Sequence generators

- `seq_gen` generates action sequences of an imaginary simulation-based item.
- `seq_gen2` generates action sequences according to a given probability transition matrix.
- `seq_gen3` generates action sequences according to a recurrent neural network.

## Feature extraction methods

- `seq2feature_mds` extracts features from response processes by multidimensional scaling.
- `seq2feature_seq2seq` extracts features from response processes by autoencoder.

## Sequence models

- `seqm` fits a neural network model that relates response processes with a response variable.
- `predict.seqm` makes predictions from the models fitted by `seqm`.

**Author(s)**

**Maintainer:** Xueying Tang <xueyingtang1989@gmail.com>

Authors:

- Susu Zhang <susu.zhang1992@gmail.com>
- Zhi Wang <zhiwpku@gmail.com>
- Jingchen Liu <jcliu@stat.columbia.edu>
- Zhiliang Ying <zying@stat.columbia.edu>

**See Also**

Useful links:

- Report bugs at <https://github.com/xytangtang/ProcData/issues>

---

action\_seqs\_summary    *Summarize action sequences*

---

**Description**

Summarize action sequences

**Usage**

```
action_seqs_summary(action_seqs)
```

**Arguments**

action\_seqs    a list of action sequences.

**Value**

a list containing the following objects:

n_seq	the number of action sequences
n_action	the number of distinct actions
action	the action set
seq_length	sequence lengths
action_freq	action counts
action_seqfreq	the number of sequences that each action appears
trans_count	a length(action) by length(action) matrix whose element in the i-th row and j-th column is the counts of transition from action[i] to action[j].

**See Also**

[time\\_seqs\\_summary](#) for summarizing timestamp sequences.

---

aseq2feature\_seq2seq *Feature Extraction by action sequence autoencoder*

---

## Description

aseq2feature\_seq2seq extract features from action sequences by action sequence autoencoder.

## Usage

```
aseq2feature_seq2seq(aseqs, K, rnn_type = "lstm", n_epoch = 50,
  method = "last", step_size = 1e-04, optimizer_name = "adam",
  samples_train, samples_valid, samples_test = NULL, pca = TRUE,
  gpu = FALSE, parallel = FALSE, seed = 12345, verbose = TRUE,
  return_theta = TRUE)
```

## Arguments

aseqs	a list of n action sequences. Each element is an action sequence in the form of a vector of actions.
K	the number of features to be extracted.
rnn_type	the type of recurrent unit to be used for modeling response processes. "lstm" for the long-short term memory unit. "gru" for the gated recurrent unit.
n_epoch	the number of training epochs for the autoencoder.
method	the method for computing features from the output of an recurrent neural network in the encoder. Available options are "last" and "avg".
step_size	the learning rate of optimizer.
optimizer_name	a character string specifying the optimizer to be used for training. Available options are "sgd", "rmsprop", "adadelta", and "adam".
samples_train	vectors of indices specifying the training, validation and test sets for training autoencoder.
samples_valid	vectors of indices specifying the training, validation and test sets for training autoencoder.
samples_test	vectors of indices specifying the training, validation and test sets for training autoencoder.
pca	logical. If TRUE, the principal components of features are returned. Default is TRUE.
gpu	logical. If TRUE, use gpu for training when available. Default is FALSE.
parallel	logical. If TRUE, allow cpu parallel computing. Default is FALSE.
seed	random seed.
verbose	logical. If TRUE, training progress is printed.
return_theta	logical. If TRUE, extracted features are returned.

## Details

This function trains a sequence-to-sequence autoencoder using keras. The encoder of the autoencoder consists of an embedding layer and a recurrent neural network. The decoder consists of another recurrent neural network and a fully connect layer with softmax activation. The outputs of the encoder are the extracted features.

The output of the encoder is a function of the encoder recurrent neural network. It is the last output of the encoder recurrent neural network if `method="last"` and the average of the encoder recurrent neural network if `method="avg"`.

## Value

`aseq2feature_seq2seq` returns a list containing

<code>theta</code>	a matrix containing K features or principal features. Each column is a feature.
<code>train_loss</code>	a vector of length <code>n_epoch</code> recording the trace of training losses.
<code>valid_loss</code>	a vector of length <code>n_epoch</code> recording the trace of validation losses.
<code>test_loss</code>	a vector of length <code>n_epoch</code> recording the trace of test losses. Exists only if <code>samples_test</code> is not NULL.

## See Also

[chooseK\\_seq2seq](#) for choosing K through cross-validation.

Other feature extraction methods: [atseq2feature\\_seq2seq](#), [seq2feature\\_mds\\_large](#), [seq2feature\\_mds](#), [seq2feature\\_seq2seq](#), [tseq2feature\\_seq2seq](#)

## Examples

```
n <- 50
seqs <- seq_gen(n)
seq2seq_res <- aseq2feature_seq2seq(seqs$action_seqs, 5, rnn_type="lstm", n_epoch=5,
                                  samples_train=1:40, samples_valid=41:50)
features <- seq2seq_res$theta
plot(seq2seq_res$train_loss, col="blue", type="l")
lines(seq2seq_res$valid_loss, col="red")
```

---

`atseq2feature_seq2seq` *Feature Extraction by action and time sequence autoencoder*

---

## Description

`atseq2feature_seq2seq` extract features from action and timestamp sequences by a sequence autoencoder.

**Usage**

```
atseq2feature_seq2seq(atseqs, K, weights = c(1, 0.5),
  cumulative = FALSE, log = TRUE, rnn_type = "lstm", n_epoch = 50,
  method = "last", step_size = 1e-04, optimizer_name = "rmsprop",
  samples_train, samples_valid, samples_test = NULL, pca = TRUE,
  gpu = FALSE, parallel = FALSE, seed = 12345, verbose = TRUE,
  return_theta = TRUE)
```

**Arguments**

atseqs	a list of two elements, first element is the list of n action sequences, Each element is an action sequence in the form of a vector of actions. The second element is the list of n timestamp sequences corresponding to the action sequences. Each element is a numeric sequence in the form of a vector of timestamps associated with actions, with the timestamp of the first event (e.g., "start") of 0.
K	the number of features to be extracted.
weights	a vector of 2 elements for the weight of the loss of action sequences (categorical_crossentropy) and time sequences (mean squared error), respectively. The total loss is calculated as the weighted sum of the two losses.
cumulative	logical. If TRUE, the sequence of cumulative time up to each event is used as input to the neural network. If FALSE, the sequence of inter-arrival time (gap time between an event and the previous event) will be used as input to the neural network. Default is FALSE.
log	logical. If TRUE, for the timestamp sequences, input of the neural net is the base-10 log of the original sequence of times plus 1 (i.e., $\log_{10}(t+1)$ ). If FALSE, the original sequence of times is used.
rnn_type	the type of recurrent unit to be used for modeling response processes. "lstm" for the long-short term memory unit. "gru" for the gated recurrent unit.
n_epoch	the number of training epochs for the autoencoder.
method	the method for computing features from the output of an recurrent neural network in the encoder. Available options are "last" and "avg".
step_size	the learning rate of optimizer.
optimizer_name	a character string specifying the optimizer to be used for training. Available options are "sgd", "rmsprop", "adadelta", and "adam".
samples_train	vectors of indices specifying the training, validation and test sets for training autoencoder.
samples_valid	vectors of indices specifying the training, validation and test sets for training autoencoder.
samples_test	vectors of indices specifying the training, validation and test sets for training autoencoder.
pca	logical. If TRUE, the principal components of features are returned. Default is TRUE.
gpu	logical. If TRUE, use gpu for training when available. Default is FALSE.
parallel	logical. If TRUE, allow cpu parallel computing. Default is FALSE.

seed	random seed.
verbose	logical. If TRUE, training progress is printed.
return_theta	logical. If TRUE, extracted features are returned.

### Details

This function trains a sequence-to-sequence autoencoder using keras. The encoder of the autoencoder consists of a recurrent neural network. The decoder consists of another recurrent neural network followed by a fully connected layer with softmax activation for actions and another fully connected layer with ReLU activation for times. The outputs of the encoder are the extracted features.

The output of the encoder is a function of the encoder recurrent neural network. It is the last latent state of the encoder recurrent neural network if `method="last"` and the average of the encoder recurrent neural network latent states if `method="avg"`.

### Value

`tseq2feature_seq2seq` returns a list containing

theta	a matrix containing K features or principal features. Each column is a feature.
train_loss	a vector of length <code>n_epoch</code> recording the trace of training losses.
valid_loss	a vector of length <code>n_epoch</code> recording the trace of validation losses.
test_loss	a vector of length <code>n_epoch</code> recording the trace of test losses. Exists only if <code>samples_test</code> is not NULL.

### See Also

[chooseK\\_seq2seq](#) for choosing K through cross-validation.

Other feature extraction methods: [aseq2feature\\_seq2seq](#), [seq2feature\\_mds\\_large](#), [seq2feature\\_mds](#), [seq2feature\\_seq2seq](#), [tseq2feature\\_seq2seq](#)

### Examples

```
n <- 50
data(cc_data)
samples <- sample(1:length(cc_data$seqs$time_seqs), n)
atseqs <- sub_seqs(cc_data$seqs, samples)
action_and_time_seq2seq_res <- atseq2feature_seq2seq(atseqs, 5, rnn_type="lstm", n_epoch=5,
  samples_train=1:40, samples_valid=41:50)
features <- action_and_time_seq2seq_res$theta
plot(action_and_time_seq2seq_res$train_loss, col="blue", type="l",
  ylim = range(c(action_and_time_seq2seq_res$train_loss,
    action_and_time_seq2seq_res$valid_loss)))
lines(action_and_time_seq2seq_res$valid_loss, col="red", type = 'l')
```

---

calculate_dist_cpp	<i>calculate dissimilarity matrix</i>
--------------------	---------------------------------------

---

**Description**

calculate dissimilarity matrix

**Usage**

```
calculate_dist_cpp(seqs)
```

**Arguments**

seqs            a list of action sequences

**Value**

calculate\_dist\_cpp returns the "oss\_action" dissimilarity matrix of the action sequences in seqs.

---

cc_data	<i>Data of item CP025Q01 (climate control item 1) in PISA 2012</i>
---------	--

---

**Description**

A dataset containing the response processes and binary response outcomes of 16763 respondents.

**Usage**

```
cc_data
```

**Format**

A list with two elements.

**seqs** An object of class "`proc`" containing the action sequences and the time sequences of the respondents.

**responses** Binary responses of 16763 respondents. The order of the respondents matches that in seqs.

**Source**

item interface: <http://www.oecd.org/pisa/test-2012/testquestions/question3/>

---

 chooseK\_mds

*Choose the number of multidimensional scaling features*


---

### Description

chooseK\_mds choose the number of multidimensional scaling features to be extracted by cross-validation.

### Usage

```
chooseK_mds(seqs = NULL, K_cand, dist_type = "oss_action",
  n_fold = 5, max_epoch = 100, step_size = 0.01, tot = 1e-06,
  return_dist = FALSE, seed = 12345, L_set = 1:3)
```

### Arguments

seqs	a " <a href="#">proc</a> " object or a square matrix. If a squared matrix is provided, it is treated as the dissimilarity matrix of a group of response processes.
K_cand	the candidates of the number of features.
dist_type	a character string specifies the dissimilarity measure for two response processes. See 'Details'.
n_fold	the number of folds for cross-validation.
max_epoch	the maximum number of epochs for stochastic gradient descent.
step_size	the step size of stochastic gradient descent.
tot	the accuracy tolerance for determining convergence.
return_dist	logical. If TRUE, the dissimilarity matrix will be returned. Default is FALSE.
seed	random seed.
L_set	length of ngrams considered

### Value

chooseK\_mds returns a list containing

K	the value in K_cand producing the smallest cross-validation loss.
K_cand	the candidates of the number of features.
cv_loss	the cross-validation loss for each candidate in K_cand.
dist_mat	the dissimilarity matrix. This element exists only if return_dist=TRUE.

### References

Gomez-Alonso, C. and Valls, A. (2008). A similarity measure for sequences of categorical data based on the ordering of common elements. In V. Torra & Y. Narukawa (Eds.) *Modeling Decisions for Artificial Intelligence*, (pp. 134-145). Springer Berlin Heidelberg.

**See Also**

[seq2feature\\_mds](#) for feature extraction after choosing the number of features.

**Examples**

```
n <- 50
seqs <- seq_gen(n)
K_res <- chooseK_mds(seqs, 5:10, return_dist=TRUE)
theta <- seq2feature_mds(K_res$dist_mat, K_res$K)$theta
```

---

chooseK\_seq2seq

*Choose the number of autoencoder features*

---

**Description**

chooseK\_seq2seq chooses the number of features to be extracted by cross-validation.

**Usage**

```
chooseK_seq2seq(seqs, ae_type, K_cand, rnn_type = "lstm", n_epoch = 50,
  method = "last", step_size = 1e-04, optimizer_name = "adam",
  n_fold = 5, cumulative = FALSE, log = TRUE, weights = c(1, 0.5),
  valid_prop = 0.1, gpu = FALSE, parallel = FALSE, seed = 12345,
  verbose = TRUE)
```

**Arguments**

seqs	an object of class "proc".
ae_type	a string specifies the type of autoencoder. The autoencoder can be an action sequence autoencoder ("action"), a time sequence autoencoder ("time"), or an action-time sequence autoencoder ("both").
K_cand	the candidates of the number of features.
rnn_type	the type of recurrent unit to be used for modeling response processes. "lstm" for the long-short term memory unit. "gru" for the gated recurrent unit.
n_epoch	the number of training epochs for the autoencoder.
method	the method for computing features from the output of an recurrent neural network in the encoder. Available options are "last" and "avg".
step_size	the learning rate of optimizer.
optimizer_name	a character string specifying the optimizer to be used for training. Available options are "sgd", "rmsprop", "adadelta", and "adam".
n_fold	the number of folds for cross-validation.

cumulative	logical. If TRUE, the sequence of cumulative time up to each event is used as input to the neural network. If FALSE, the sequence of inter-arrival time (gap time between an event and the previous event) will be used as input to the neural network. Default is FALSE.
log	logical. If TRUE, for the timestamp sequences, input of the neural net is the base-10 log of the original sequence of times plus 1 (i.e., $\log_{10}(t+1)$ ). If FALSE, the original sequence of times is used.
weights	a vector of 2 elements for the weight of the loss of action sequences (categorical_crossentropy) and time sequences (mean squared error), respectively. The total loss is calculated as the weighted sum of the two losses.
valid_prop	the proportion of validation samples in each fold.
gpu	logical. If TRUE, use gpu for training when available. Default is FALSE.
parallel	logical. If TRUE, allow cpu parallel computing. Default is FALSE.
seed	random seed.
verbose	logical. If TRUE, training progress is printed.

### Value

chooseK\_seq2seq returns a list containing

K	the candidate in K_cand producing the smallest cross-validation loss.
K_cand	the candidates of number of features.
cv_loss	the cross-validation loss for each candidate in K_cand.

### See Also

[seq2feature\\_seq2seq](#) for feature extraction given the number of features.

---

combine_actions	<i>Combine consecutive actions into a single action</i>
-----------------	---

---

### Description

Combine the action pattern described in old\_actions into a single action new\_action. The timestamp of the combined action can be the timestamp of the first action in the action pattern, the timestamp of the last action in the action pattern, or the average of the two timestamps.

### Usage

```
combine_actions(seqs, old_actions, new_action, timestamp = "first")
```

**Arguments**

seqs	an object of class "proc"
old_actions	a character vector giving consecutive actions to be replaced.
new_action	a string giving the combined action
timestamp	"first", "last", or "avg", specifying how the timestamp of the combined action should be derived.

**Value**

an object of class "proc"

**Examples**

```
seqs <- seq_gen(100)
new_seqs <- combine_actions(seqs,
                           old_actions=c("OPT1_3", "OPT2_2", "RUN"),
                           new_action="KEY_ACTION")
```

---

count_actions	<i>Count action appearances</i>
---------------	---------------------------------

---

**Description**

This function counts the appearances of each action in actions in action sequence x.

**Usage**

```
count_actions(x, actions)
```

**Arguments**

x	an action sequence.
actions	a set of actions whose number of appearances will be count.

**Value**

an integer vector of counts.

---

predict.seqm	<i>Predict method for sequence models</i>
--------------	---

---

### Description

Obtains predictions from a fitted sequence model object.

### Usage

```
## S3 method for class 'seqm'  
predict(object, new_seqs, new_covariates = NULL,  
        type = "response", ...)
```

### Arguments

object	a fitted object of class "seqm" from seqm.
new_seqs	an object of class " <a href="#">proc</a> " with which to predict.
new_covariates	a new covariate matrix with which to predict.
type	a string specifying whether to predict responses ("response") or features ("feature") or both ("both").
...	further arguments to be passed to <code>predict.keras.engine.training.Model</code> .

### Details

It unserializes `object$model_fit` to obtain a keras model of class "`keras.engine.training.Model`" and then calls `predict` to obtain predictions.

### Value

If `type="response"`, a vector of predictions. The vector gives the probabilities of the response variable being one if `response_type="binary"`. If `type="feature"`, a matrix of rnn outputs. If `type="both"`, a list containing both the vector of response variable prediction and the rnn output matrix.

### See Also

[seqm](#) for fitting sequence models.

---

print.proc	<i>Print method for class "proc"</i>
------------	--------------------------------------

---

**Description**

Print method for class "proc"

**Usage**

```
## S3 method for class 'proc'
print(x, n = 5, index = NULL, quote = FALSE, ...)
```

**Arguments**

x	an object of class "proc"
n	number of processes to be printed.
index	indice of processes to be printed.
quote	logical, indicating whether or not strings should be printed with surrounding quotes.
...	not used.

**Value**

print.proc invisibly returns the "proc" object it prints.

---

proc	<i>Class "proc" constructor</i>
------	---------------------------------

---

**Description**

Create a "proc" object from given action sequences and timestamp sequences

**Usage**

```
proc(action_seqs, time_seqs, ids = NULL)
```

**Arguments**

action_seqs	a list of action sequences.
time_seqs	a list of timestamp sequences.
ids	ids identifiers of response processes.

**Details**

An object of class "proc" is a list containing the following components:

- action\_seqs a list of action sequences.
- time\_seqs a list of timestamp sequences.

The names of the elements in seqs\$action\_seqs and seqs\$time\_seqs are process identifiers.

**Value**

an object of class "proc" containing the provided action and timestamp sequences.

---

read.seqs

*Reading response processes from csv files*

---

**Description**

Reads a csv file and creates response process data.

**Usage**

```
read.seqs(file, style, id_var = NULL, action_var = NULL,
          time_var = NULL, step_sep = ",", ...)
```

**Arguments**

file	the name of the csv file from which the response processes are to be read.
style	the style that the response processes are stored. See 'Details'.
id_var	a string giving the name of the variable storing the process identifier.
action_var	a string giving the name of the variable storing action sequences.
time_var	a string giving the name of the variable storing timestamp sequences.
step_sep	the step separator characters. It is only used if style="single".
...	further arguments to be passed to read.csv.

**Details**

read.seqs calls read.csv to read process data stored in a csv file into R. The csv file to be read should at least include an identifier of distinct response processes, and action sequences. It can also include timestamp sequences.

The response processes (action sequences and timestamp sequences) stored in csv files can be in one of the two styles, "single" and "multiple". In "single" style, each response process occupies a single line. Actions and timestamps at different steps are separated by step\_sep. In "multiple" style, each response process occupies multiple lines with each step taking up one line.

**Value**

read.seqs returns an object of class "proc".

---

remove_action	<i>Remove actions from response processes</i>
---------------	---

---

**Description**

Remove actions in actions and the corresponding timestamps in response processes seqs.

**Usage**

```
remove_action(seqs, actions)
```

**Arguments**

seqs	an object of class "proc"
actions	a character vector. Each element is an action to be removed.

**Value**

an object of class "proc" with actions in actions and the corresponding timestamps removed.

**Examples**

```
seqs <- seq_gen(10)
new_seqs <- remove_action(seqs, c("RUN", "Start"))
```

---

remove_repeat	<i>Remove repeated actions</i>
---------------	--------------------------------

---

**Description**

Remove repeated actions

**Usage**

```
remove_repeat(seqs, ignore = NULL)
```

**Arguments**

seqs	an object of class "proc"
ignore	repeated actions in ignore will not be deleted.

**Value**

an object of class "proc"

replace\_action      *Replace actions in response processes*

---

**Description**

Replace old\_action with new\_action in seqs. Timestamp sequences are not affected.

**Usage**

```
replace_action(seqs, old_action, new_action)
```

**Arguments**

seqs                  an object of class "proc"  
old\_action            a string giving the action to be replaced.  
new\_action            a string giving the action replacing old\_action

**Value**

an object of class "proc"

**Examples**

```
seqs <- seq_gen(10)  
new_seqs <- replace_action(seqs, "Start", "Begin")
```

---

seq2feature\_mds      *Feature extraction via multidimensional scaling*

---

**Description**

seq2feature\_mds extracts K features from response processes by multidimensional scaling.

**Usage**

```
seq2feature_mds(seqs = NULL, K = 2, method = "auto",  
  dist_type = "oss_action", pca = TRUE, subset_size = 100,  
  subset_method = "random", n_cand = 10, return_dist = FALSE,  
  seed = 12345, L_set = 1:3)
```

**Arguments**

seqs	a "proc" object or a square matrix. If a squared matrix is provided, it is treated as the dissimilarity matrix of a group of response processes.
K	the number of features to be extracted.
method	a character string specifies the algorithm used for performing MDS. See 'Details'.
dist_type	a character string specifies the dissimilarity measure for two response processes. See 'Details'.
pca	logical. If TRUE (default), the principal components of the extracted features are returned.
subset_size, n_cand	two parameters used in the large data algorithm. See 'Details' and <a href="#">seq2feature_mds_large</a> .
subset_method	a character string specifying the method for choosing the subset in the large data algorithm. See 'Details' and <a href="#">seq2feature_mds_large</a> .
return_dist	logical. If TRUE, the dissimilarity matrix will be returned. Default is FALSE.
seed	random seed.
L_set	length of ngrams considered

**Details**

Since the classical MDS has a computational complexity of order  $n^3$  where  $n$  is the number of response processes, it is computationally expensive to perform classical MDS when a large number of response processes is considered. In addition, storing an  $n \times n$  dissimilarity matrix when  $n$  is large require a large amount of memory. In `seq2feature_mds`, the algorithm proposed in Paradis (2018) is implemented to obtain MDS for large datasets. `method` specifies the algorithm to be used for obtaining MDS features. If `method = "small"`, classical MDS is used by calling `cmdscale`. If `method = "large"`, the algorithm for large datasets will be used. If `method = "auto"` (default), `seq2feature_mds` selects the algorithm automatically based on the sample size.

`dist_type` specifies the dissimilarity to be used for measuring the discrepancy between two response processes. If `dist_type = "oss_action"`, the order-based sequence similarity (oss) proposed in Gomez-Alonso and Valls (2008) is used for action sequences. If `dist_type = "oss_both"`, both action sequences and timestamp sequences are used to compute a time-weighted oss.

The number of features to be extracted `K` can be selected by cross-validation using [chooseK\\_mds](#).

**Value**

`seq2feature_mds` returns a list containing

theta	a numeric matrix giving the <code>K</code> extracted features or principal features. Each column is a feature.
dist_mat	the dissimilarity matrix. This element exists only if <code>return_dist=TRUE</code> .

## References

Gomez-Alonso, C. and Valls, A. (2008). A similarity measure for sequences of categorical data based on the ordering of common elements. In V. Torra & Y. Narukawa (Eds.) *Modeling Decisions for Artificial Intelligence*, (pp. 134-145). Springer Berlin Heidelberg.

Paradis, E. (2018). Multidimensional scaling with very large datasets. *Journal of Computational and Graphical Statistics*, 27(4), 935-939.

## See Also

[chooseK\\_mds](#) for choosing K.

Other feature extraction methods: [aseq2feature\\_seq2seq](#), [atseq2feature\\_seq2seq](#), [seq2feature\\_mds\\_large](#), [seq2feature\\_seq2seq](#), [tseq2feature\\_seq2seq](#)

## Examples

```
n <- 50
seqs <- seq_gen(n)
theta <- seq2feature_mds(seqs, 5)$theta
```

---

seq2feature\_mds\_large *Feature Extraction by MDS for Large Dataset*

---

## Description

seq2feature\_mds\_large extracts MDS features from a large number of response processes. The algorithm proposed in Paradis (2018) is implemented with minor variations to perform MDS. The algorithm first selects a relatively small subset of response processes to perform the classical MDS. Then the coordinate of each of the other response processes are obtained by minimizing the loss function related to the target response processes and the those in the subset through BFGS.

## Usage

```
seq2feature_mds_large(seqs, K, dist_type = "oss_action", subset_size,
  subset_method = "random", n_cand = 10, pca = TRUE, seed = 12345,
  L_set = 1:3)
```

## Arguments

seqs	an object of class "proc"
K	the number of features to be extracted.
dist_type	a character string specifies the dissimilarity measure for two response processes. See 'Details'.
subset_size	the size of the subset on which classical MDS is performed.
subset_method	a character string specifying the method for choosing the subset. It must be one of "random", "sample_avgmax", "sample_minmax", "full_avgmax", and "full_minmax".

n_cand	The size of the candidate set when selecting the subset. It is only used when subset_method is "sample_avgmax" or "sample_minmax".
pca	logical. If TRUE (default), the principal components of the extracted features are returned.
seed	random seed.
L_set	length of ngrams considered

**Value**

seq2feature\_mds\_large returns an  $n \times K$  matrix of extracted features.

**References**

Paradis, E. (2018). Multidimensional Scaling with Very Large Datasets. *Journal of Computational and Graphical Statistics*, 27, 935–939.

**See Also**

Other feature extraction methods: [aseq2feature\\_seq2seq](#), [atseq2feature\\_seq2seq](#), [seq2feature\\_mds](#), [seq2feature\\_seq2seq](#), [tseq2feature\\_seq2seq](#)

---

seq2feature\_mds\_stochastic

*Feature extraction by stochastic mds*

---

**Description**

Feature extraction by stochastic mds

**Usage**

```
seq2feature_mds_stochastic(seqs = NULL, K = 2,
  dist_type = "oss_action", max_epoch = 100, step_size = 0.01,
  pca = TRUE, tot = 1e-06, return_dist = FALSE, seed = 12345,
  L_set = 1:3)
```

**Arguments**

seqs	a "proc" object or a square matrix. If a squared matrix is provided, it is treated as the dissimilarity matrix of a group of response processes.
K	the number of features to be extracted.
dist_type	a character string specifies the dissimilarity measure for two response processes. See 'Details'.
max_epoch	the maximum number of epochs for stochastic gradient descent.
step_size	the step size of stochastic gradient descent.

pca	a logical scalar. If TRUE, the principal components of the extracted features are returned.
tot	the accuracy tolerance for determining convergence.
return_dist	logical. If TRUE, the dissimilarity matrix will be returned. Default is FALSE.
seed	random seed.
L_set	length of ngrams considered.

### Value

seq2feature\_mds\_stochastic returns a list containing

theta	a numeric matrix giving the K extracted features or principal features. Each column is a feature.
loss	the value of the multidimensional scaling objective function.
dist_mat	the dissimilarity matrix. This element exists only if return_dist=TRUE.

---

seq2feature\_seq2seq     *Feature Extraction by autoencoder*

---

### Description

seq2feature\_seq2seq extract features from response processes by autoencoder.

### Usage

```
seq2feature_seq2seq(seqs, ae_type = "action", K, rnn_type = "lstm",
  n_epoch = 50, method = "last", step_size = 1e-04,
  optimizer_name = "adam", cumulative = FALSE, log = TRUE,
  weights = c(1, 0.5), samples_train, samples_valid,
  samples_test = NULL, pca = TRUE, gpu = FALSE, parallel = FALSE,
  seed = 12345, verbose = TRUE, return_theta = TRUE)
```

### Arguments

seqs	an object of class " <a href="#">proc</a> ".
ae_type	a string specifies the type of autoencoder. The autoencoder can be an action sequence autoencoder ("action"), a time sequence autoencoder ("time"), or an action-time sequence autoencoder ("both").
K	the number of features to be extracted.
rnn_type	the type of recurrent unit to be used for modeling response processes. "lstm" for the long-short term memory unit. "gru" for the gated recurrent unit.
n_epoch	the number of training epochs for the autoencoder.
method	the method for computing features from the output of an recurrent neural network in the encoder. Available options are "last" and "avg".

step_size	the learning rate of optimizer.
optimizer_name	a character string specifying the optimizer to be used for training. Available options are "sgd", "rmsprop", "adadelta", and "adam".
cumulative	logical. If TRUE, the sequence of cumulative time up to each event is used as input to the neural network. If FALSE, the sequence of inter-arrival time (gap time between an event and the previous event) will be used as input to the neural network. Default is FALSE.
log	logical. If TRUE, for the timestamp sequences, input of the neural net is the base-10 log of the original sequence of times plus 1 (i.e., $\log_{10}(t+1)$ ). If FALSE, the original sequence of times is used.
weights	a vector of 2 elements for the weight of the loss of action sequences (categorical_crossentropy) and time sequences (mean squared error), respectively. The total loss is calculated as the weighted sum of the two losses.
samples_train, samples_valid, samples_test	vectors of indices specifying the training, validation and test sets for training autoencoder.
pca	logical. If TRUE, the principal components of features are returned. Default is TRUE.
gpu	logical. If TRUE, use gpu for training when available. Default is FALSE.
parallel	logical. If TRUE, allow cpu parallel computing. Default is FALSE.
seed	random seed.
verbose	logical. If TRUE, training progress is printed.
return_theta	logical. If TRUE, extracted features are returned.

### Details

This function wraps [aseq2feature\\_seq2seq](#), [tseq2feature\\_seq2seq](#), and [atseq2feature\\_seq2seq](#).

### Value

seq2feature\_seq2seq returns a list containing

theta	a matrix containing K features or principal features. Each column is a feature.
train_loss	a vector of length n_epoch recording the trace of training losses.
valid_loss	a vector of length n_epoch recording the trace of validation losses.
test_loss	a vector of length n_epoch recording the trace of test losses. Exists only if samples_test is not NULL.

### See Also

[chooseK\\_seq2seq](#) for choosing K through cross-validation.

Other feature extraction methods: [aseq2feature\\_seq2seq](#), [atseq2feature\\_seq2seq](#), [seq2feature\\_mds\\_large](#), [seq2feature\\_mds](#), [tseq2feature\\_seq2seq](#)

**Examples**

```

n <- 50
data(cc_data)
samples <- sample(1:length(cc_data$seqs$time_seqs), n)
seqs <- sub_seqs(cc_data$seqs, samples)

# action sequence autoencoder
K_res <- chooseK_seq2seq(seqs=seqs, ae_type="action", K_cand=c(5, 10),
                        n_epoch=5, n_fold=2, valid_prop=0.2)
seq2seq_res <- seq2feature_seq2seq(seqs=seqs, ae_type="action", K=K_res$K,
                                  n_epoch=5, samples_train=1:40, samples_valid=41:50)
theta <- seq2seq_res$theta

# time sequence autoencoder
K_res <- chooseK_seq2seq(seqs=seqs, ae_type="time", K_cand=c(5, 10),
                        n_epoch=5, n_fold=2, valid_prop=0.2)
seq2seq_res <- seq2feature_seq2seq(seqs=seqs, ae_type="time", K=K_res$K,
                                  n_epoch=5, samples_train=1:40, samples_valid=41:50)
theta <- seq2seq_res$theta

# action and time sequence autoencoder
K_res <- chooseK_seq2seq(seqs=seqs, ae_type="both", K_cand=c(5, 10),
                        n_epoch=5, n_fold=2, valid_prop=0.2)
seq2seq_res <- seq2feature_seq2seq(seqs=seqs, ae_type="both", K=K_res$K,
                                  n_epoch=5, samples_train=1:40, samples_valid=41:50)
theta <- seq2seq_res$theta
plot(seq2seq_res$train_loss, col="blue", type="l")
lines(seq2seq_res$valid_loss, col="red")

```

---

seqm

*Fitting sequence models*


---

**Description**

seqm is used to fit a neural network model relating a response process with a variable.

**Usage**

```

seqm(seqs, response, covariates = NULL, response_type,
     actions = unique(unlist(seqs$action_seqs)), rnn_type = "lstm",
     include_time = FALSE, time_interval = TRUE, log_time = TRUE,
     K_emb = 20, K_rnn = 20, n_hidden = 0, K_hidden = NULL,
     index_valid = 0.2, verbose = FALSE, max_len = NULL, n_epoch = 20,
     batch_size = 16, optimizer_name = "rmsprop", step_size = 0.001,
     gpu = FALSE, parallel = FALSE, seed = 12345)

```

**Arguments**

seqs	an object of class "proc".
response	response variable.
covariates	covariate matrix.
response_type	"binary" or "scale".
actions	a character vector gives all possible actions. It will be expanded to include all actions appear in seqs if necessary.
rnn_type	the type of recurrent unit to be used for modeling response processes. "lstm" for the long-short term memory unit. "gru" for the gated recurrent unit.
include_time	logical. If the timestamp sequence should be included in the model.
time_interval	logical. If the timestamp sequence is included as a sequence of inter-arrival time.
log_time	logical. If take the logarithm of the time sequence.
K_emb	the latent dimension of the embedding layer.
K_rnn	the latent dimension of the recurrent neural network.
n_hidden	the number of hidden fully-connected layers.
K_hidden	a vector of length n_hidden specifying the number of nodes in each hidden layer.
index_valid	proportion of sequences used as the validation set or a vector of indices specifying the validation set.
verbose	logical. If TRUE, training progress is printed.
max_len	the maximum length of response processes.
n_epoch	the number of training epochs.
batch_size	the batch size used in training.
optimizer_name	a character string specifying the optimizer to be used for training. Available options are "sgd", "rmsprop", "adadelta", and "adam".
step_size	the learning rate of optimizer.
gpu	logical. If TRUE, use gpu for training when available. Default is FALSE.
parallel	logical. If TRUE, allow cpu parallel computing. Default is FALSE.
seed	random seed.

**Details**

The model consists of an embedding layer, a recurrent layer and one or more fully connected layers. The embedding layer takes an action sequence and output a sequences of K dimensional numeric vectors to the recurrent layer. If `include_time = TRUE`, the embedding sequence is combined with the timestamp sequence in the response process as the input the recurrent layer. The last output of the recurrent layer and the covariates specified in `covariates` are used as the input of the subsequent fully connected layer. If `response_type="binary"`, the last layer uses the sigmoid activation to produce the probability of the response being one. If `response_type="scale"`, the last layer uses the linear activation. The dimension of the output of other fully connected layers (if any) is specified by `K_hidden`.

The action sequences are re-coded into integer sequences and are padded with zeros to length `max_len` before feeding into the model. If the provided `max_len` is smaller than the length of the longest sequence in `seqs`, it will be overridden.

**Value**

seqm returns an object of class "seqm", which is a list containing

structure	a string describing the neural network structure.
coefficients	a list of fitted coefficients. The length of the list is $6 + 2 * n\_hidden$ . The first element gives the action embedding. Elements 2-4 are parameters in the recurrent unit. The rest of the elements are for the fully connected layers. Elements $4 + (2 * i - 1)$ and $4 + 2 * i$ give the parameters for the $i$ -th fully connected layer.
model_fit	a vector of class "raw". It is the serialized version of the trained keras model.
feature_model	a vector of class "raw". It is the serialized version of the keras model for obtaining the rnn outputs.
include_time	if the timestamp sequence is included in the model.
time_interval	if inter-arrival time is used.
log_time	if the logarithm time is used.
actions	all possible actions.
max_len	the maximum length of action sequences.
history	a $n\_epoch$ by 2 matrix giving the training and validation losses at the end of each epoch.

**See Also**

[predict.seqm](#) for the predict method for seqm objects.

**Examples**

```
n <- 100
data(cc_data)
samples <- sample(1:length(cc_data$responses), n)
seqs <- sub_seqs(cc_data$seqs, samples)

y <- cc_data$responses[samples]
x <- matrix(rnorm(n*2), ncol=2)

index_test <- 91:100
index_train <- 1:90
seqs_train <- sub_seqs(seqs, index_train)
seqs_test <- sub_seqs(seqs, index_test)

actions <- unique(unlist(seqs$action_seqs))

## no covariate is used
res1 <- seqm(seqs = seqs_train, response = y[index_train],
            response_type = "binary", actions=actions, K_emb = 5, K_rnn = 5,
            n_epoch = 5)
pred_res1 <- predict(res1, new_seqs = seqs_test)

mean(as.numeric(pred_res1 > 0.5) == y[index_test])
```

```

## add more fully connected layers after the recurrent layer.
res2 <- seqm(seqs = seqs_train, response = y[index_train],
            response_type = "binary", actions=actions, K_emb = 5, K_rnn = 5,
            n_hidden=2, K_hidden=c(10,5), n_epoch = 5)
pred_res2 <- predict(res2, new_seqs = seqs_test)
mean(as.numeric(pred_res2 > 0.5) == y[index_test])

## add covariates
res3 <- seqm(seqs = seqs_train, response = y[index_train],
            covariates = x[index_train, ],
            response_type = "binary", actions=actions,
            K_emb = 5, K_rnn = 5, n_epoch = 5)
pred_res3 <- predict(res3, new_seqs = seqs_test,
                    new_covariates=x[index_test, ])

## include time sequences
res4 <- seqm(seqs = seqs_train, response = y[index_train],
            response_type = "binary", actions=actions,
            include_time=TRUE, K_emb=5, K_rnn=5, n_epoch=5)
pred_res4 <- predict(res4, new_seqs = seqs_test)

```

---

seq\_gen

*Action sequence generator*


---

## Description

seq\_gen generates action sequences of an imaginary simulation-based item.

## Usage

```

seq_gen(n, action_set1 = c("OPT1_1", "OPT1_2", "OPT1_3"),
        action_set2 = c("OPT2_1", "OPT2_2"), answer_set = c("CHECK_A",
        "CHECK_B", "CHECK_C", "CHECK_D"), p1 = rep(1, length(action_set1)),
        p2 = rep(1, length(action_set2)), p_answer = rep(1,
        length(answer_set)), p_continue = 0.5, p_choose = 0.5,
        include_time = FALSE, time_intv_dist = list("exp", 1),
        seed = 12345)

```

## Arguments

n	An integer. The number of action sequences to be generated.
action_set1, action_set2	Character vectors giving the choices for the first and the second conditions.
answer_set	A character vector giving the choices for the answer.
p1, p2	Nonnegative numeric vectors. They are the weights for sampling from action_set1 and action_set2.

p_answer	A nonnegative numeric vector giving the weights for sampling from answer_set.
p_continue	Probability of running an/another experiment.
p_choose	Probability of choosing an answer.
include_time	logical. Indicate if timestamp sequences should be generated. Default is FALSE.
time_intv_dist	A list specifying the distribution of the inter-arrival time.
seed	Random seed.

### Details

The format of the generated sequences resembles that of the response processes of simulation-based items. In these items, participants are asked to answer a question by running simulated experiments in which two conditions can be controlled. A simulated experiment can be run by setting the two conditions at one of the given choices and click "Run" button.

The possible actions are "Start", "End", "Run", and the elements in action\_set1, action\_set2, and answer\_set. The generated sequences begin with "Start" and continue with groups of three actions. Each group of three actions, representing one experiment, consists of an action chosen from action\_set1 according to p1, an action chosen from action\_set2 according to p2, and "Run". The probability of performing an experiment after "Start" or one experiment is p\_continue. After the experiment process, with probability p\_choose, an answer will be chosen. The chosen answer is randomly sampled from answer\_set according to p\_answer. All generated sequences end with "End".

### Value

An object of class "`proc`" with `time_seqs = NULL`.

### See Also

Other sequence generators: [seq\\_gen2](#), [seq\\_gen3](#)

---

seq\_gen2

*Markov action sequence generator*

---

### Description

seq\_gen2 generates action sequences according to a given probability transition matrix.

### Usage

```
seq_gen2(n, Pmat = NULL, events = letters, start_index = 1,
  end_index = length(events), max_len = 200, include_time = FALSE,
  time_intv_dist = list("exp", 1), seed = 12345)
```

**Arguments**

n	An integer. The number of action sequences to be generated.
Pmat	An N by N probability transition matrix.
events	A character vector specifying the set of N possible actions. Default is letters.
start_index	Index of the action indicating the start of an item in events.
end_index	Index of the action indicating the end of an item in events.
max_len	Maximum length of generated sequences.
include_time	logical. Indicate if timestamp sequences should be generated. Default is FALSE.
time_intv_dist	A list specifying the distribution of the inter-arrival time.
seed	random generator seed.

**Details**

This function generates n action sequences according Pmat. The set of possible actions is events. All generated sequences start with events[start\_index] and end with events[end\_index]. If Pmat is not supplied, actions is uniformly drawn from events[-start\_index] until events[end\_index] appears.

**Value**

An object of class "proc" with time\_seqs = NULL.

**See Also**

Other sequence generators: [seq\\_gen3](#), [seq\\_gen](#)

---

seq\_gen3

*RNN action sequence generator*


---

**Description**

seq\_gen3 generates action sequences according to a recurrent neural network

**Usage**

```
seq_gen3(n, events = letters, rnn_type = "lstm", K = 10,
  weights = NULL, max_len = 100, initial_state = NULL,
  start_index = 1, end_index = length(events), include_time = FALSE,
  time_intv_dist = list("exp", 1), gpu = FALSE, parallel = FALSE,
  seed = 12345)
```

**Arguments**

n	An integer. The number of action sequences to be generated.
events	A character vector specifying the set of N possible actions. Default is letters.
rnn_type	the type of recurrent unit to be used for generating sequences. "lstm" for the long-short term memory unit. "gru" for the gated recurrent unit.
K	the latent dimension of the recurrent unit.
weights	a list containing the weights in the embedding layer, the recurrent unit, the fully connected layer. If not (properly) specified, randomly generated weights are used.
max_len	Maximum length of generated sequences.
initial_state	a list containing the initial state of the recurrent neural network. If rnn_type="lstm", it contains two 1 by K matrices. If rnn_type="gru", it contains one 1 by K matrix. If not specified, all the elements are set to zero.
start_index	Index of the action indicating the start of an item in events.
end_index	Index of the action indicating the end of an item in events.
include_time	logical. Indicate if timestamp sequences should be generated. Default is FALSE.
time_intv_dist	A list specifying the distribution of the inter-arrival time.
gpu	logical. If TRUE, use gpu for training when available. Default is FALSE.
parallel	logical. If TRUE, allow cpu parallel computing. Default is FALSE.
seed	random generator seed.

**Value**

A list containing the following elements

seqs	an object of class "proc" with time_seqs=NULL.
weights	a list containing the weights used for generating sequences.

**See Also**

Other sequence generators: [seq\\_gen2](#), [seq\\_gen](#)

---

sub\_seqs

*Subset response processes*


---

**Description**

Subset response processes

**Usage**

```
sub_seqs(seqs, ids)
```

**Arguments**

seqs            an object of class "proc"  
ids             a vector of indices

**Value**

an object of class "proc"

**Examples**

```
data(cc_data)
seqs <- sub_seqs(cc_data$seqs, 1:10)
```

---

summary.proc	<i>Summary method for class "proc"</i>
--------------	--

---

**Description**

The summary of a "proc" object combines the summary of the action sequences and the summary of the timestamp sequences.

**Usage**

```
## S3 method for class 'proc'
summary(object, ...)
```

**Arguments**

object            an object of class "proc".  
...               not used.

**Value**

a list. Its components are the components returned by [action\\_seqs\\_summary](#) and [time\\_seqs\\_summary](#).

**See Also**

[action\\_seqs\\_summary](#) and [time\\_seqs\\_summary](#)

---

time\_seqs\_summary      *Summarize timestamp sequences*

---

### Description

Summarize timestamp sequences

### Usage

```
time_seqs_summary(time_seqs)
```

### Arguments

time\_seqs      a list of timestamp sequences

### Value

a list containing the following objects

total\_time      a summary of response time of n\_seq response processes

mean\_react\_time  
                 a summary of mean reaction time of n\_seq response processes

---

tseq2feature\_seq2seq      *Feature Extraction by time sequence autoencoder*

---

### Description

tseq2feature\_seq2seq extract features from timestamps of action sequences by a sequence autoencoder.

### Usage

```
tseq2feature_seq2seq(tseqs, K, cumulative = FALSE, log = TRUE,
  rnn_type = "lstm", n_epoch = 50, method = "last",
  step_size = 1e-04, optimizer_name = "rmsprop", samples_train,
  samples_valid, samples_test = NULL, pca = TRUE, gpu = FALSE,
  parallel = FALSE, seed = 12345, verbose = TRUE,
  return_theta = TRUE)
```

**Arguments**

tseqs	a list of n timestamp sequences. Each element is a numeric sequence in the form of a vector of timestamps associated with actions, with the timestamp of the first event (e.g., "start") of 0.
K	the number of features to be extracted.
cumulative	logical. If TRUE, the sequence of cumulative time up to each event is used as input to the neural network. If FALSE, the sequence of inter-arrival time (gap time between an event and the previous event) will be used as input to the neural network. Default is FALSE.
log	logical. If TRUE, for the timestamp sequences, input of the neural net is the base-10 log of the original sequence of times plus 1 (i.e., $\log_{10}(t+1)$ ). If FALSE, the original sequence of times is used.
rnn_type	the type of recurrent unit to be used for modeling response processes. "lstm" for the long-short term memory unit. "gru" for the gated recurrent unit.
n_epoch	the number of training epochs for the autoencoder.
method	the method for computing features from the output of an recurrent neural network in the encoder. Available options are "last" and "avg".
step_size	the learning rate of optimizer.
optimizer_name	a character string specifying the optimizer to be used for training. Available options are "sgd", "rmsprop", "adadelta", and "adam".
samples_train	vectors of indices specifying the training, validation and test sets for training autoencoder.
samples_valid	vectors of indices specifying the training, validation and test sets for training autoencoder.
samples_test	vectors of indices specifying the training, validation and test sets for training autoencoder.
pca	logical. If TRUE, the principal components of features are returned. Default is TRUE.
gpu	logical. If TRUE, use gpu for training when available. Default is FALSE.
parallel	logical. If TRUE, allow cpu parallel computing. Default is FALSE.
seed	random seed.
verbose	logical. If TRUE, training progress is printed.
return_theta	logical. If TRUE, extracted features are returned.

**Details**

This function trains a sequence-to-sequence autoencoder using keras. The encoder of the autoencoder consists of a recurrent neural network. The decoder consists of another recurrent neural network and a fully connected layer with ReLU activation. The outputs of the encoder are the extracted features.

The output of the encoder is a function of the encoder recurrent neural network. It is the last latent state of the encoder recurrent neural network if method="last" and the average of the encoder recurrent neural network latent states if method="avg".

**Value**

tseq2feature\_seq2seq returns a list containing

theta            a matrix containing K features or principal features. Each column is a feature.  
 train\_loss      a vector of length n\_epoch recording the trace of training losses.  
 valid\_loss      a vector of length n\_epoch recording the trace of validation losses.  
 test\_loss       a vector of length n\_epoch recording the trace of test losses. Exists only if samples\_test is not NULL.

**See Also**

[chooseK\\_seq2seq](#) for choosing K through cross-validation.

Other feature extraction methods: [aseq2feature\\_seq2seq](#), [atseq2feature\\_seq2seq](#), [seq2feature\\_mds\\_large](#), [seq2feature\\_mds](#), [seq2feature\\_seq2seq](#)

**Examples**

```
n <- 50
data(cc_data)
samples <- sample(1:length(cc_data$seqs$time_seqs), n)
tseqs <- cc_data$seqs$time_seqs[samples]
time_seq2seq_res <- tseq2feature_seq2seq(tseqs, 5, rnn_type="lstm", n_epoch=5,
                                       samples_train=1:40, samples_valid=41:50)
features <- time_seq2seq_res$theta
plot(time_seq2seq_res$train_loss, col="blue", type="l",
      ylim = range(c(time_seq2seq_res$train_loss, time_seq2seq_res$valid_loss)))
lines(time_seq2seq_res$valid_loss, col="red", type = 'l')
```

---

tseq2interval

*Transform a timestamp sequence into a inter-arrival time sequence*

---

**Description**

Transform a timestamp sequence into a inter-arrival time sequence

**Usage**

```
tseq2interval(x)
```

**Arguments**

x                    a timestamp sequence

**Value**

a numeric vector of the same length as x. The first element in the returned vector is 0. The t-th returned element is  $x[t] - x[t-1]$ .

---

write.seqs	<i>Write process data to csv files</i>
------------	--

---

**Description**

Write process data to csv files

**Usage**

```
write.seqs(seqs, file, style, id_var = "ID", action_var = "Event",  
          time_var = "Time", step_sep = ",", ...)
```

**Arguments**

seqs	an object of class " <code>proc</code> " to written in the csv file.
file	the name of the csv file from which the response processes are to be read.
style	the style that the response processes are stored. See 'Details'.
id_var	a string giving the name of the variable storing the process identifier.
action_var	a string giving the name of the variable storing action sequences.
time_var	a string giving the name of the variable storing timestamp sequences.
step_sep	the step separator characters. It is only used if style="single".
...	further arguments to be passed to <code>write.csv</code>

**Value**

No return value.

# Index

## \*Topic **datasets**

- cc\_data, [9](#)
- action\_seqs\_summary, [4](#), [31](#)
- aseq2feature\_seq2seq, [5](#), [8](#), [20](#), [21](#), [23](#), [34](#)
- atseq2feature\_seq2seq, [6](#), [6](#), [20](#), [21](#), [23](#), [34](#)
  
- calculate\_dist\_cpp, [9](#)
- cc\_data, [9](#)
- chooseK\_mds, [10](#), [19](#), [20](#)
- chooseK\_seq2seq, [6](#), [8](#), [11](#), [23](#), [34](#)
- cmdscales, [19](#)
- combine\_actions, [3](#), [12](#)
- count\_actions, [13](#)
  
- predict.seqm, [3](#), [14](#), [26](#)
- print.proc, [15](#)
- proc, [3](#), [9–11](#), [13–15](#), [15](#), [16–22](#), [25](#), [28–31](#), [35](#)
- ProcData (ProcData-package), [3](#)
- ProcData-package, [3](#)
  
- read.seqs, [3](#), [16](#)
- remove\_action, [3](#), [17](#)
- remove\_repeat, [17](#)
- replace\_action, [3](#), [18](#)
  
- seq2feature\_mds, [3](#), [6](#), [8](#), [11](#), [18](#), [21](#), [23](#), [34](#)
- seq2feature\_mds\_large, [6](#), [8](#), [19](#), [20](#), [20](#), [23](#), [34](#)
- seq2feature\_mds\_stochastic, [21](#)
- seq2feature\_seq2seq, [3](#), [6](#), [8](#), [12](#), [20](#), [21](#), [22](#), [34](#)
- seq\_gen, [3](#), [27](#), [29](#), [30](#)
- seq\_gen2, [3](#), [28](#), [28](#), [30](#)
- seq\_gen3, [3](#), [28](#), [29](#), [29](#)
- seqm, [3](#), [14](#), [24](#)
- sub\_seqs, [30](#)
- summary.proc, [3](#), [31](#)
  
- time\_seqs\_summary, [4](#), [31](#), [32](#)
- tseq2feature\_seq2seq, [6](#), [8](#), [20](#), [21](#), [23](#), [32](#)
- tseq2interval, [34](#)
- write.seqs, [35](#)