

Package ‘RtutoR’

September 14, 2018

Type Package

Title Shiny Apps for Plotting and Exploratory Analysis

Version 1.2

Date 2018-09-04

Author Anup Nair [aut, cre]

Maintainer Anup Nair <nairanup50695@gmail.com>

Description Contains Shiny apps for Plotting and Exploratory Analysis.

The plotting app provides an automated interface for generating plots using the 'ggplot2' package.

Current version of this app supports 10 different plot types along with options to manipulate specific

aesthetics and controls related to each plot type. Exploratory Analysis app helps generates an Exploratory

analysis report (in PowerPoint format) comprising of Univariate and Bivariate plots & related summary tables.

Depends R (>= 3.1.0)

License GPL

Imports dplyr (>= 0.7.4), ggplot2 (>= 2.2.1), shiny, shinydashboard, rmarkdown, DT, shinyBS, shinyjs, ggthemes, plotly, rlang, FSelector, officer, colourpicker, tidyr, devtools

LazyData TRUE

RoxygenNote 6.1.0

NeedsCompilation no

Repository CRAN

Date/Publication 2018-09-14 07:50:07 UTC

Encoding UTF-8

R topics documented:

generate_exploratory_analysis_ppt	2
gen_exploratory_report_app	3
launch_plotter	3

Index**5**

generate_exploratory_analysis_ppt
Generate Exploratory Analysis Report

Description

Generate Exploratory Analysis Report

Usage

```
generate_exploratory_analysis_ppt(df, target_var, output_file_name,
  n_plots_per_slide = 2,
  plot_theme = "ggthemes::theme_fivethirtyeight()", group_names = NULL,
  top_k_features = NULL, f_screen_model = c("chi.squared",
  "information.gain", "gain.ratio", "symmetrical.uncertainty"),
  max_levels_cat_var = 10)
```

Arguments

<code>df</code>	Dataframe object for exploratory analysis
<code>target_var</code>	Dependent Variable Name
<code>output_file_name</code>	File Name for the Output presentation. Saves the output in the current working directory if only the file name is provided
<code>n_plots_per_slide</code>	Presentation Slide Format - Choose between 1 or 2 plots per slide. Default value is 2
<code>plot_theme</code>	Specify a theme for ggplot. Includes themes provided as part of ggplot2 as well as themes available in the ggthemes package. Launch the shiny app to view the valid set of themes available
<code>group_names</code>	Grouping variable (or multiple grouping variables) to be used for analysis. If this argument is supplied, an additional section is added to the Exploratory Analysis report: "Bi variate Analysis with Grouping variable".
<code>top_k_features</code>	Should top k features be selected for analysis instead of all available features in the dataset. If yes, provide a numeric value to this argument. The Top K features are identified based on a filtering approach. Four different filtering options are provided (from the FSelector package)
<code>f_screen_model</code>	Filtering approach for extracting the top k features
<code>max_levels_cat_var</code>	Remove categorical features with more than a specified number of levels. Default is 10

Value

Output presentation with Univariate and Bi-variate analysis and plots

Examples

```
## Not run:  
diamonds_sample <- ggplot2::diamonds[sample(1:nrow(ggplot2::diamonds),size=1000),]  
generate_exploratory_analysis_ppt(df = diamonds_sample, target_var = "price")  
## End(Not run)
```

`gen_exploratory_report_app`

Launch a Shiny App for Exploratory Analysis

Description

Launch a Shiny App for Exploratory Analysis

Usage

```
gen_exploratory_report_app(df)
```

Arguments

`df` Dataframe object for exploratory analysis

Value

Launches a Shiny App. Please refer to the ReadMe page of the App to understand how the app works

Examples

```
## Not run:  
diamonds_sample <- ggplot2::diamonds[sample(1:nrow(ggplot2::diamonds),size=1000),]  
gen_exploratory_report_app(diamonds_sample)  
## End(Not run)
```

`launch_plotter`

Launch Plotter

Description

Launches the plotting app

Usage

```
launch_plotter(list_of_datasets)
```

Arguments**list_of_datasets**

List of datasets which should be made available for selection when the app is launched

Value

Launches App

Examples

```
## Not run:  
diamonds_sample <- ggplot2::diamonds[sample(1:nrow(diamonds),size=1000),]  
launch_plotter(list(diamonds_sample = diamonds_sample, mtcars = mtcars, iris = iris))  
## End(Not run)
```

Index

gen_exploratory_report_app, 3
generate_exploratory_analysis_ppt, 2
launch_plotter, 3