

Package ‘SEA’

May 24, 2018

Type Package

Title Segregation Analysis

Version 1.0

Date 2018-5-20

Author Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming

Maintainer Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Description A few major genes and a series of polygene are responsive for each quantitative trait. Major genes are individually identified while polygene is collectively detected. This is mixed major genes plus polygene inheritance analysis or segregation analysis (SEA). In the SEA, phenotypes from a single or multiple segregation populations along with their parents are used to fit all the possible models and the best model is viewed as the model of the trait. There are fourteen combinations of populations available. Zhang YM, Gai JY, Yang YH (2003) <doi:10.1017/S0016672303006141>.

Depends shiny, MASS, doParallel, foreach, methods

Imports KSCorrect, kolmim, utils, stats, grDevices, graphics, data.table

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2018-05-24 12:35:11 UTC

R topics documented:

SEA-package	2
BCexdata	3
BCFexdata	4
BCFFun	4
BCFun	5
BILexdata	5
BILFun	6
DHexdata	6
DHFun	7
F23exdata	7

F23Fun	8
F2exdata	8
F2Fun	9
G3DHexdata	9
G3DHFun	10
G4F2exdata	10
G4F2Fun	11
G4F3exdata	11
G4F3Fun	12
G5BCexdata	12
G5BCFexdata	13
G5BCFFun	13
G5BCFun	14
G5exdata	14
G5Fun	15
G6exdata	15
G6Fexdata	16
G6FFun	16
G6Fun	17
PosPro	17

Index 19

SEA-package	<i>Segregation Analysis</i>
-------------	-----------------------------

Description

A few major genes and a series of polygenes are responsive for each quantitative trait. Major genes are individually identified while polygenes are collectively detected. This is mixed major genes plus polygenes inheritance analysis or segregation analysis (SEA). In the SEA, phenotypic observations from a single or multiple segregation populations along with their parents are used to fit all the possible models and the best model is viewed as the model of the trait. There are fourteen types of population combinations available.

Details

Package:	SEA
Type:	Package
Version:	1.0
Date:	2018-5-20
Depends:	shiny,MASS,doParallel,foreach
Imports:	KScorrect,kolmim,utils,stats,grDevices,graphics,data.table
License:	GPL(>=2)
LazyLoad:	yes

Users can use 'SEA()' start the GUI.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

References

The EIM algorithm in the joint segregation analysis of quantitative traits. Zhang Yuan-Ming*, Gai Junyi, Yang Yonghua(2003).

Examples

```
## Not run: SEA()
```

BCexdata

BC population dataset

Description

The phenotype of BC population .

Usage

```
data(BCexdata)
```

Details

Dataset input of BCFun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

BCFexdata	<i>BCF population dataset</i>
-----------	-------------------------------

Description

The phenotype of BCF population .

Usage

```
data(BCFexdata)
```

Details

Dataset input of BCFFun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

BCFFun	<i>segregation analysis of BCF population</i>
--------	---

Description

Phenotypic observations in BCF population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
BCFFun(df, model, BCFtext2)
```

Arguments

df	phenotype matrix.
model	genetic model.
BCFtext2	number of plants measured in each family.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
 Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
BCF=data(BCFexdata)
BCFFun(BCFexdata, "0MG", 1)
```

BCFun

segregation analysis of BC population

Description

Phenotypic observations in BC population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
BCFun(df, model)
```

Arguments

df	phenotype matrix.
model	genetic model.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
BC=data(BCexdata)  
BCFun(BCexdata, "0MG")
```

BILexdata

BIL population dataset

Description

The phenotype of BIL population .

Usage

```
data(BILexdata)
```

Details

Dataset input of BILFun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

BILFun *segregation analysis of BIL population*

Description

Phenotypic observations in BIL population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
BILFun(df, model, BILfr)
```

Arguments

df	phenotype matrix.
model	genetic model.
BILfr	BIL type.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
BIL=data(BILexdata)  
BILFun(BILexdata, "0MG", "BIL1(F1xP1)")
```

DHexdata *DH population dataset*

Description

The phenotype of DH population .

Usage

```
data(DHexdata)
```

Details

Dataset input of DHFun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

DHFun	<i>segregation analysis of DH population</i>
-------	--

Description

Phenotypic observations in DH population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
DHFun(df, model)
```

Arguments

df	phenotype matrix.
model	genetic model.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang <soy Zhang@mail.hzau.edu.cn>

Examples

```
DH=data(DHexdata)  
DHFun(DHexdata, "0MG")
```

F23exdata	<i>F23 population dataset</i>
-----------	-------------------------------

Description

The phenotype of F23 population .

Usage

```
data(F23exdata)
```

Details

Dataset input of F23Fun function.

Author(s)

Maintainer: Yuanming Zhang <soy Zhang@mail.hzau.edu.cn>

F23Fun *segregation analysis of F23 population*

Description

Phenotypic observations in F23 population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
F23Fun(df, model, m_nf)
```

Arguments

df	phenotype matrix.
model	genetic model.
m_nf	number of plants measured in each family.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
F23=data(F23exdata)  
F23Fun(F23exdata, "0MG", 1)
```

F2exdata *F2 population dataset*

Description

The phenotype of F2 population .

Usage

```
data(F2exdata)
```

Details

Dataset input of F2Fun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

F2Fun	<i>segregation analysis of F2 population</i>
-------	--

Description

Phenotypic observations in F2 population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
F2Fun(df, model)
```

Arguments

df	phenotype matrix.
model	genetic model.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
F2=data(F2exdata)  
F2Fun(F2exdata, "0MG")
```

G3DHexdata	<i>G3DH population dataset</i>
------------	--------------------------------

Description

The phenotype of G3DH population .

Usage

```
data(G3DHexdata)
```

Details

Dataset input of G3DHFun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G3DHFun *segregation analysis of G3DH population*

Description

Phenotypic observations in G3DH population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
G3DHFun(df, model, G3DHtext2)
```

Arguments

df	phenotype matrix.
model	genetic model.
G3DHtext2	number of plants measured in each family.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G3DH=data(G3DHexdata)  
G3DHFun(G3DHexdata, "0MG", 1)
```

G4F2exdata *G4F2 population dataset*

Description

The phenotype of G4F2 population .

Usage

```
data(G4F2exdata)
```

Details

Dataset input of G4F2Fun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G4F2Fun	<i>segregation analysis of G4F2 population</i>
---------	--

Description

Phenotypic observations in G4F2 population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
G4F2Fun(df, model)
```

Arguments

df	phenotype matrix.
model	genetic model.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G4F2=data(G4F2exdata)  
G4F2Fun(G4F2exdata, "PG-AD")
```

G4F3exdata	<i>G4F3 population dataset</i>
------------	--------------------------------

Description

The phenotype of G4F3 population .

Usage

```
data(G4F3exdata)
```

Details

Dataset input of G4F3Fun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G4F3Fun *segregation analysis of G4F3 population*

Description

Phenotypic observations in G4F3 population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
G4F3Fun(df, model, G4F3text2)
```

Arguments

df	phenotype matrix.
model	genetic model.
G4F3text2	number of plants measured in each family.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G4F3=data(G4F3exdata)  
G4F3Fun(G4F3exdata, "PG-AD", 1)
```

G5BCexdata *G5BC population dataset*

Description

The phenotype of G5BC population .

Usage

```
data(G5BCexdata)
```

Details

Dataset input of G5BCFun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G5BCFexdata	<i>G5BCF population dataset</i>
-------------	---------------------------------

Description

The phenotype of G5BCF population .

Usage

```
data(G5BCFexdata)
```

Details

Dataset input of G5BCFFun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G5BCFFun	<i>segregation analysis of G5BCF population</i>
----------	---

Description

Phenotypic observations in G5BCF population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
G5BCFFun(df, model, G5BCFtext2)
```

Arguments

df	phenotype matrix.
model	genetic model.
G5BCFtext2	number of plants measured in each family.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
 Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G5BCF=data(G5BCFexdata)
G5BCFFun(G5BCFexdata, "1MG-AD", 1)
```

`G5BCFun`*segregation analysis of G5BC population*

Description

Phenotypic observations in G5BC population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
G5BCFun(df, model)
```

Arguments

<code>df</code>	phenotype matrix.
<code>model</code>	genetic model.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G5BC=data(G5BCexdata)  
G5BCFun(G5BCexdata, "1MG-AD")
```

`G5exdata`*G5 population dataset*

Description

The phenotype of G5 population .

Usage

```
data(G5exdata)
```

Details

Dataset input of G5Fun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G5Fun	<i>segregation analysis of G5 population</i>
-------	--

Description

Phenotypic observations in G5 population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
G5Fun(df,model,G5text2)
```

Arguments

df	phenotype matrix.
model	genetic model.
G5text2	number of plants measured in each family.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G5=data(G5exdata)  
G5Fun(G5exdata,"PG-AD",1)
```

G6exdata	<i>G6 population dataset</i>
----------	------------------------------

Description

The phenotype of G6 population .

Usage

```
data(G6exdata)
```

Details

Dataset input of G6Fun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G6Fexdata	<i>G6F population dataset</i>
-----------	-------------------------------

Description

The phenotype of G6F population .

Usage

```
data(G6Fexdata)
```

Details

Dataset input of G6FFun function.

Author(s)

Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G6FFun	<i>segregation analysis of G6F population</i>
--------	---

Description

Phenotypic observations in G6F population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
G6FFun(df, model, G6Ftext2)
```

Arguments

df	phenotype matrix.
model	genetic model.
G6Ftext2	number of plants measured in each family.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
 Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G6F=data(G6Fexdata)
G6FFun(G6Fexdata, "PG-AD", 1)
```

G6Fun

segregation analysis of G6 population

Description

Phenotypic observations in G6 population have often been used to identify mixed major-gene plus polygenes inheritance model for quantitative traits in plants.

Usage

```
G6Fun(df, model)
```

Arguments

df	phenotype matrix.
model	genetic model.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang <soy Zhang@mail.hzau.edu.cn>

Examples

```
G6=data(G6exdata)  
G6Fun(G6exdata, "PG-AD")
```

PosPro

Posterior Probability

Description

calculate posterior probability of the optimal model

Usage

```
PosPro(Population, result, data)
```

Arguments

Population	which Population to analysis.
result	result of calculation used corresponding population function.
data	phenotype matrix.

Author(s)

Zhang Ya-Wen, Du Ying-wen, Ren Wen-long and Zhang Yuan-ming
Maintainer: Yuanming Zhang <soy Zhang@mail.hzau.edu.cn>

Examples

```
F23=data(F23exdata)
result<-F23Fun(F23exdata,"1MG-AD",1)
PosPro("F2:3",result,F23exdata)
```

Index

*Topic **R**

SEA-package, 2

*Topic **SEA**

SEA-package, 2

*Topic **package**

SEA-package, 2

*Topic

SEA-package, 2

B1 (BCexdata), 3

B2 (BCexdata), 3

BCexdata, 3

BCF-B12 (BCFexdata), 4

BCF-B22 (BCFexdata), 4

BCFexdata, 4

BCFFun, 4

BCFun, 5

BIL (BILexdata), 5

BILexdata, 5

BILFun, 6

DH (DHexdata), 6

DHexdata, 6

DHFun, 7

F2 (F2exdata), 8

F23 (F23exdata), 7

F23exdata, 7

F23Fun, 8

F2exdata, 8

F2Fun, 9

G3DH-DH (G3DHexdata), 9

G3DH-P1 (G3DHexdata), 9

G3DH-P2 (G3DHexdata), 9

G3DHexdata, 9

G3DHFun, 10

G4F2-F1 (G4F2exdata), 10

G4F2-F2 (G4F2exdata), 10

G4F2-P1 (G4F2exdata), 10

G4F2-P2 (G4F2exdata), 10

G4F2exdata, 10

G4F2Fun, 11

G4F3-F1 (G4F3exdata), 11

G4F3-F23 (G4F3exdata), 11

G4F3-P1 (G4F3exdata), 11

G4F3-P2 (G4F3exdata), 11

G4F3exdata, 11

G4F3Fun, 12

G5-F1 (G5exdata), 14

G5-F2 (G5exdata), 14

G5-F23 (G5exdata), 14

G5-P1 (G5exdata), 14

G5-P2 (G5exdata), 14

G5BC-B1 (G5BCexdata), 12

G5BC-B2 (G5BCexdata), 12

G5BC-F1 (G5BCexdata), 12

G5BC-P1 (G5BCexdata), 12

G5BC-P2 (G5BCexdata), 12

G5BCexdata, 12

G5BCF-B12 (G5BCFexdata), 13

G5BCF-B22 (G5BCFexdata), 13

G5BCF-F1 (G5BCFexdata), 13

G5BCF-P1 (G5BCFexdata), 13

G5BCF-P2 (G5BCFexdata), 13

G5BCFexdata, 13

G5BCFFun, 13

G5BCFun, 14

G5exdata, 14

G5Fun, 15

G6-B1 (G6exdata), 15

G6-B2 (G6exdata), 15

G6-F1 (G6exdata), 15

G6-F2 (G6exdata), 15

G6-P1 (G6exdata), 15

G6-P2 (G6exdata), 15

G6exdata, 15

G6F-B12 (G6Fexdata), 16

G6F-B22 (G6Fexdata), 16

G6F-F1 (G6Fexdata), [16](#)
G6F-F23 (G6Fexdata), [16](#)
G6F-P1 (G6Fexdata), [16](#)
G6F-P2 (G6Fexdata), [16](#)
G6Fexdata, [16](#)
G6FFun, [16](#)
G6Fun, [17](#)

PosPro, [17](#)

SEA (SEA-package), [2](#)
SEA-package, [2](#)