

Package ‘SMR’

February 19, 2015

Title Externally Studentized Midrange Distribution

Version 2.0.1

Date 2014-10-20

Author Ben Deivide de Oliveira Batista, Daniel Furtado Ferreira

Maintainer Daniel Furtado Ferreira <danielff@dex.ufla.br>

Description Computes the studentized midrange distribution (pdf, cdf and quantile) and generates random numbers

License GPL (>= 2)

URL www.dex.ufla.br/~danielff/r_resources.html

NeedsCompilation no

Repository CRAN

Date/Publication 2014-11-25 22:27:43

R topics documented:

SMR 1

Index 4

SMR

The externally studentized normal midrange distribution

Description

Computes the probability density, the cumulative distribution function and the quantile function and generates random samples for the externally studentized normal midrange distribution with the numbers means equal to size, the degrees of freedom equal to df and the number of points of the Gauss-Legendre quadrature equal to np.

Usage

```
dSMR(x, size, df, np=32, log = FALSE)
pSMR(q, size, df, np=32, lower.tail = TRUE, log.p = FALSE)
qSMR(p, size, df, np=32, eps = 1e-13, maxit = 5000, lower.tail = TRUE, log.p = FALSE)
rSMR(n, size, df = Inf)
```

Arguments

<code>x, q</code>	vector of quantiles $x \in R$ and $q \in R$.
<code>p</code>	vector of probabilities $(0, 1)$.
<code>size</code>	sample size. Only for <code>size > 1</code> .
<code>n</code>	vector size to be simulated $n > 1$.
<code>df</code>	degrees of freedom $df > 0$.
<code>np</code>	number of points of the gaussian quadrature $np > 2$.
<code>log, log.p</code>	logical argument; if TRUE, the probabilities p are given as $\log(p)$.
<code>lower.tail</code>	logical argument; if TRUE, the probabilities are $P[X \leq x]$ otherside, $P[X \geq x]$.
<code>eps</code>	stopping criterion for Newton-Raphson's iteration method.
<code>maxit</code>	maximum number of interaction in the Newton-Raphson method.

Details

Assumes `np = 32` as default value for `dSMR`, `pSMR` and `qSMR`. If `df` is not specified, it assumes the default value `Inf` in `rSMR`. When `df=1`, the convergence of the routines requires `np>250` to obtain the desired result accurately. The Midrange distribution has density

$$f(\bar{q}; n, \nu) = \int_0^{\infty} \int_{-\infty}^{x\bar{q}} 2n(n-1)x\phi(y)\phi(2x\bar{q}-y)[\Phi(2x\bar{q}-y) - \Phi(y)]^{n-2} f(x; \nu) dy dx,$$

where, q is the quantile of externally studentized midrange distribution, n (`size`) is the sample size and ν is the degrees of freedom.

The externally studentized midrange distribution function is given by

$$F(\bar{q}; n, \nu) = \int_{-\infty}^{\bar{q}} \int_0^{\infty} \int_{-\infty}^{x\bar{q}} 2n(n-1)x\phi(y)\phi(2xz-y)[\Phi(2xz-y) - \Phi(y)]^{n-2} f(x; \nu) dy dx dz.$$

where, q is the quantile of externally studentized midrange distribution, n (`size`) is the sample size and ν is the degrees of freedom.

Value

`dSMR` gives the density, `pSMR` gives the cumulative distribution function, `qSMR` gives the quantile function, and `rSMR` generates random deviates.

Author(s)

Ben Deivide de Oliveira Batista and Daniel Furtado Ferreira.

Maintainer: Daniel Furtado Ferreira <[<danielff@dex.ufla.br>](mailto:danielff@dex.ufla.br)>

References

Batista, BDO; Ferreira, DF. The externally studentized normal midrange distribution. Submmited for publications. 2012.

See Also

Package homepage: <www.dex.ufla.br/~danielff/r_resources.html>

Examples

```
library(SMR)

#example 1:
x <- 2
q <- 1
p <- 0.9
n <- 30
size <- 5
df <- 3
np <- 32
dSMR(x, size, df, np)
pSMR(q, size, df, np)
qSMR(p, size, df, np)
rSMR(n, size, df)

#example 2:
x <- c(-1, 2, 1.1)
q <- c(1, 0, -1.5)
p <- c(0.9, 1, 0.8)
n <- 10
size <- 5
df <- 3
np <- 32
dSMR(x, size, df, np)
pSMR(q, size, df, np)
qSMR(p, size, df, np)
rSMR(n, size, df)
```

Index

*Topic **midrange**

SMR, [1](#)

dSMR (SMR), [1](#)

pSMR (SMR), [1](#)

qSMR (SMR), [1](#)

rSMR (SMR), [1](#)

SMR, [1](#)