

Package ‘SWIM’

May 22, 2020

Title Scenario Weights for Importance Measurement

Version 0.2.1

Author Silvana M. Pesenti [aut, cre],
Alberto Bettini [aut],
Pietro Millosovich [aut],
Andreas Tsanakas [aut]

Maintainer Silvana M. Pesenti <swimpackage@gmail.com>

Description An efficient sensitivity analysis for stochastic models based on Monte Carlo samples. Provides weights on simulated scenarios from a stochastic model, such that stressed random variables fulfil given probabilistic constraints (e.g. specified values for risk measures), under the new scenario weights. Scenario weights are selected by constrained minimisation of the relative entropy to the baseline model. The ‘SWIM’ package is based on Pesenti S.M, Millosovich P., Tsanakas A. (2019) ‘Reverse Sensitivity Testing: What does it take to break the model’, <openaccess.city.ac.uk/id/eprint/18896/>.

Depends R (>= 3.5.0)

Imports Rdpack (>= 0.7), Hmisc, nleqslv, reshape2, plyr, ggplot2, stats

RdMacros Rdpack

License GPL-3

URL <https://github.com/spesenti/SWIM>,
https://papers.ssrn.com/sol3/papers.cfm?abstract_id=3515274,
https://utstat.toronto.edu/pesenti/?page_id=138

BugReports <https://github.com/spesenti/SWIM/issues>

Encoding UTF-8

LazyLoad true

LazyData true

VignetteBuilder knitr

RoxygenNote 7.1.0

Suggests testthat, mvtnorm, spelling, Weighted.Desc.Stat, knitr, rmarkdown, bookdown, ggpubr

Language en-US

NeedsCompilation no

Repository CRAN

Date/Publication 2020-05-22 08:10:07 UTC

R topics documented:

cdf	2
credit_data	3
ES_stressed	4
get_data	6
importance_rank	7
merge.SWIM	9
plot_cdf	10
plot_hist	11
plot_sensitivity	13
quantile_stressed	15
sensitivity	16
stress	18
stress_mean	20
stress_mean_sd	21
stress_moment	23
stress_prob	25
stress_user	27
stress_VaR	28
stress_VaR_ES	30
summary.SWIM	32
SWIM	34
Index	36

cdf

Empirical Distribution Function of a Stressed Model

Description

Provides the empirical distribution function of a stressed model component (random variable) under the scenario weights.

Usage

```
cdf(object, xCol = 1, wCol = 1)
```

Arguments

object	A SWIM object.
xCol	Numeric or character, (name of) the column of the underlying data of the object (default = 1).
wCol	Numeric, the column of the scenario weights of the object (default = 1).

Value

The empirical distribution function (a function) of the xCol component of the stressed model with weights wCol. The empirical distribution function can be evaluated at a vector.

Author(s)

Silvana M. Pesenti

See Also

See [plot_cdf](#) for plotting the empirical distribution function of the stressed model and [quantile_stressed](#) for sample quantiles of a stressed model.

Examples

```
## example with a stress on VaR
set.seed(0)
x <- as.data.frame(cbind(
  "normal" = rnorm(1000),
  "gamma" = rgamma(1000, shape = 2)))
res1 <- stress(type = "VaR", x = x,
  alpha = c(0.9, 0.95), q_ratio = 1.05)
grid <- seq(min(x$normal), max(x$normal), length.out = 5)
## stressed empirical distribution function
cdf(res1, xCol = 1, wCol = 1)(grid)
## baseline empirical distribution function
ecdf(x$normal)(grid)
```

credit_data

Credit data set

Description

A dataset containing total aggregate losses from three sub-portfolios, generated through a binomial credit model.

Usage

credit_data

Format

A data frame with 100,000 rows and 7 variables:

L total aggregate loss of a portfolio consisting of three homogeneous sub-portfolios L1, L2 and L3

L1 aggregate loss of sub-portfolio 1

L2 aggregate loss of sub-portfolio 2

L3 aggregate loss of sub-portfolio 3

H1 (conditional) default probability of sub-portfolio 1

H2 (conditional) default probability of sub-portfolio 2

H3 (conditional) default probability of sub-portfolio 3

Source

For a detailed case study of the credit data set using SWIM see Pesenti Silvana M. and Bettini A, Millosovich P, Tsanakas A (2020). "Scenario Weights for Importance Measurement (SWIM) - An R package for sensitivity analysis." Available at SSRN: <https://ssrn.com/abstract=3515274>.

ES_stressed

Value-at-Risk and Expected Shortfall of a Stressed Model

Description

Provides the Value-at-Risk (VaR) and the Expected Shortfall (ES) for components (random variables) of a stochastic model.

Usage

```
ES_stressed(object, alpha = 0.95, xCol = "all", wCol = 1, base = FALSE)
```

```
VaR_stressed(object, alpha = 0.95, xCol = "all", wCol = 1, base = FALSE)
```

Arguments

object	A SWIM object.
alpha	Numeric vector, the levels of the stressed VaR and ES (default = 0.95).
xCol	Numeric or character vector, (names of) the columns of the underlying data of the object (default = "all").
wCol	Numeric, the column of the scenario weights of the object (default = 1).
base	Logical, if TRUE, statistics under the baseline are also returned (default = "FALSE").

Details

ES_stressed: The ES of a stressed model is the ES of a chosen stressed model component, subject to the calculated scenario weights. The ES at level alpha of a stressed model component is given by:

$$ES_{alpha} = 1/(1 - alpha) * \int_{alpha}^1 VaR_u^W du,$$

where VaR_u^W is the VaR of the stressed model component, defined below.

VaR_stressed: The VaR of a model is the VaR (quantile) of a chosen stressed model component, subject to the calculated scenario weights. The VaR at level alpha of a stressed model component with stressed distribution function F^W is defined as its left-quantile at alpha:

$$VaR_{alpha}^W = F^{W,-1}(alpha).$$

The function VaR_stressed provides the empirical quantile, whereas the function quantile_stressed calculates quantiles of model components with different interpolations.

Value

ES_stressed: Returns a matrix with the empirical ES's at level alpha of model components specified in xCol, under the scenario weights wCol.

VaR_stressed: Returns a matrix with the empirical VaR's at level alpha of model components specified in xCol, under the scenario weights wCol.

Functions

- ES_stressed: Expected Shortfall of a stressed model
- VaR_stressed: Value-at-Risk of a stressed model.

Author(s)

Silvana M. Pesenti

See Also

See quantile_stressed for quantiles other than the empirical quantiles and cdf for the empirical distribution function of a stressed model.

Examples

```
## example with a stress on VaR
set.seed(0)
x <- as.data.frame(cbind(
  "normal" = rnorm(1000),
  "gamma" = rgamma(1000, shape = 2)))
res1 <- stress(type = "VaR", x = x,
  alpha = c(0.9, 0.95), q_ratio = 1.05)
## stressed ES
quantile_stressed(res1, probs = seq(0.9, 0.99, 0.01),
```

```

      xCol = 1, wCol = 2, type = "i/n")
quantile(x[, 1], probs = seq(0.9, 0.99, 0.01), type = 1)
VaR_stressed(res1, alpha = seq(0.9, 0.99, 0.01), xCol = 1,
             wCol = 2, base = TRUE)

## the ES of both model components under stress one
ES_stressed(res1, alpha = seq(0.9, 0.99, 0.01), xCol = "all",
            wCol = 1)
## the ES of both model components under stress two
ES_stressed(res1, alpha = seq(0.9, 0.99, 0.01), xCol = "all",
            wCol = 2)

```

get_data

Extracting from a Stressed Model

Description

Extracting the data (realisations of the stochastic model), the scenario weights, the functions generating the scenario weights, or the specifications of the stress from an object of class SWIM.

Usage

```

get_data(object, xCol = "all")

get_weights(object)

get_weightsfun(object)

get_specs(object)

```

Arguments

object	A SWIM object.
xCol	Numeric or character vector, (names of) the columns of the underlying data of the object (default = "all").

Value

get_data: A data.frame containing the realisations of the stochastic model on which the object is based.

get_weights: A data.frame containing the scenario weights of the object. Columns corresponds to different stresses.

get_weightsfun: A list containing functions, which, when applied to a column of the data, generate the scenario weights of the object. The corresponding stressed columns can be obtained via get_specs.

Use [get_weights](#) if the SWIM object only contains scenario weights and not a list of functions.

`get_specs`: A data.frame containing specifications of the stresses with each row corresponding to a different stress. Only a selection of the specifications is returned; however, all input variables are stored in the object. See also [SWIM](#).

Functions

- `get_data`: extracting data.
- `get_weights`: extracting scenario weights.
- `get_weightsfun`: extracting weight functions.
- `get_specs`: extracting information of the stress.

Author(s)

Silvana M. Pesenti

See Also

[SWIM](#)

Examples

```
## continuing example in stress_VaR
set.seed(0)
x <- as.data.frame(cbind(
  "normal" = rnorm(1000),
  "gamma" = rgamma(1000, shape = 2)))
res1 <- stress(type = "VaR", x = x,
  alpha = 0.9, q_ratio = 1.05)

## returning the underlying data
all(get_data(res1) == x)
## the scenario weights
get_weights(res1)
get_weightsfun(res1)
get_specs(res1)
```

Description

Provides the importance ranks of the components (random variables) of a stressed model for different sensitivity measures.

Usage

```
importance_rank(
  object,
  xCol = "all",
  wCol = "all",
  type = c("Gamma", "Wasserstein", "all"),
  f = NULL,
  k = NULL
)
```

Arguments

object	A SWIM object.
xCol	Numeric or character vector, (names of) the columns of the underlying data of the object (default = "all"). If xCol = NULL, only the transformed data f(x) is considered.
wCol	Vector, the columns of the scenario weights of the object corresponding to different stresses (default = "all").
type	Character, one of "Gamma", "Wasserstein", "all".
f	A function, or list of functions, that, applied to x, constitute the transformation of the data for which the sensitivity is calculated.
k	A vector or list of vectors, same length as f, indicating which columns of x each function in f operates on. When f is a list, k[[i]] corresponds to the input variables of f[[i]].

Details

For the definition of the sensitivity measures (type), see [sensitivity](#).

Value

A data.frame containing the importance ranks of the stressed model for different sensitivity measures. Small values correspond to large sensitivities. Different rows correspond to different random variables. The first two rows specify the stress and type of the sensitivity measure on which the ranking is calculated.

See Also

See [sensitivity](#) for the values of the sensitivity measures, [plot_sensitivity](#) for plotting sensitivity measures and [summary](#) for a summary statistic of a stressed model.

Examples

```
## example with a stress on VaR
set.seed(0)
x <- as.data.frame(cbind(
  "log-normal" = rlnorm(1000),
  "gamma" = rgamma(1000, shape = 2)))
```



```
res1 <- stress(type = "VaR", x = x,  
  alpha = c(0.9, 0.95), q_ratio = 1.05)  
  
importance_rank(res1, wCol = 1:2, type = "Gamma")  
## sensitivity of log-transformed data  
importance_rank(res1, wCol = 1, type = "all",  
  f = list(function(x)log(x), function(x)log(x)), k = list(1, 2))
```

merge.SWIM

Merging Two Stressed Models

Description

This function is a method for an object of class SWIM.

Usage

```
## S3 method for class 'SWIM'  
merge(x, y, ...)
```

Arguments

`x, y` Objects of class SWIM.
`...` Additional arguments will be ignored.

Details

Merges two objects of class SWIM, that are based on the same data.

Value

An object of class SWIM containing:

- `x`, a data.frame containing the data;
- `new_weights`, a list, each component corresponds to a different stress and is either a vector of scenario weights or a function, that applied to a column of `x`, generates the vectors of scenario weights;
- `type`, a list, each component corresponds to a different stress and specifies the type of the stress;
- `specs`, a list, each component corresponds to a different stress and contains a list with the specifications of what has been stressed.

See [SWIM](#) for details.

Author(s)

Silvana M. Pesenti

plot_cdf

Plotting the Empirical Distribution Functions of a Stressed Model

Description

Plots the empirical distribution function of a stressed model component (random variable) under the scenario weights.

Usage

```
plot_cdf(
  object,
  xCol = 1,
  wCol = "all",
  base = FALSE,
  n = 500,
  x_limits,
  y_limits,
  displ = TRUE
)
```

Arguments

object	A SWIM object.
xCol	Numeric or character, (name of) the column of the underlying data of the object (default = 1).
wCol	Vector, the columns of the scenario weights of the object corresponding to different stresses (default = "all").
base	Logical, if TRUE, statistics under the baseline are also returned (default = "FALSE").
n	Integer, the number of points used to plot stat_ecdf in ggplot (default = 500).
x_limits	Vector, the limits of the x-axis of the plot, the value for xlim in the coord_cartesian function in ggplot.
y_limits	Vector, the limits of the y-axis of the plot, the value for ylim in the coord_cartesian function in ggplot.
displ	Logical, if TRUE the plot is displayed, otherwise the data.frame for customised plotting with ggplot is returned (default = TRUE).

Value

If displ = TRUE, a plot displaying the empirical distribution function of the stochastic model under the scenario weights.

If displ = FALSE, a data.frame for customised plotting with ggplot. The data.frame contains the columns: the column, xCol, of the data of the stressed model, stress (the stresses) and value (the

values).

Denote by `res` the return of the function call, then `ggplot` can be called via:

```
ggplot(res, aes(x = res[,1], w = value))
+stat_ecdf(aes(color = factor(stress)), n = n).
```

Note that the `ggplot2` default of `stat_ecdf` does not take weight as an aesthetic. We use the workaround by Nicolas Woloszko, see Note below.

Note

This function is based on the `ggplot` `stat_ecdf` function. However, the `stat_ecdf` does not allow for specifying weights, thus the function is based on the workaround by Nicolas Woloszko, see https://github.com/NicolasWoloszko/stat_ecdf_weighted.

See Also

See `cdf` for the empirical distribution function of a stressed model and `quantile_stressed` for sample quantiles of a stressed model.

Examples

```
## example with a stress on VaR
set.seed(0)
x <- as.data.frame(cbind(
  "normal" = rnorm(10 ^ 5),
  "gamma" = rgamma(10 ^ 5, shape = 2)))
res1 <- stress(type = "VaR", x = x,
  alpha = c(0.75, 0.95), q_ratio = 1.15)
plot_cdf(res1, xCol = 1, wCol = 1:2, base = TRUE)
plot_cdf(res1, xCol = 1, wCol = 1:2, base = TRUE,
  x_limits = c(0, 5), y_limits = c(0.5, 1))
```

plot_hist

Plotting Histograms of a Stressed Model

Description

Plots the histogram of a stressed model component (random variable) under the scenario weights.

Usage

```
plot_hist(
  object,
  xCol = 1,
  wCol = "all",
  base = FALSE,
```

```

    x_limits,
    displ = TRUE,
    binwidth,
    displLines = FALSE
  )

```

Arguments

object	A SWIM object.
xCol	Numeric or character, (name of) the column of the underlying data of the object (default = 1).
wCol	Vector, the columns of the scenario weights of the object corresponding to different stresses (default = "all").
base	Logical, if TRUE, statistics under the baseline are also returned (default = "FALSE").
x_limits	Vector, the limits of the x-axis of the plot, the value for xlim in the coord_cartesian function in ggplot.
displ	Logical, if TRUE the plot is displayed, otherwise the data.frame for customised plotting with ggplot is returned (default = TRUE).
binwidth	Numeric, the width of the bins used to plot the histogram, the binwidth in the geom_freqpoly function in ggplot (default corresponds to 30 bins).
displLines	Logical, if TRUE lines are displayed instead of bins (default = FALSE).

Value

If `displ = TRUE`, a histogram of the stochastic model under the scenario weights.

If `displ = FALSE`, a data.frame for customised plotting with ggplot. The data.frame contains the columns: the column, `xCol`, of the data of the stressed model, `stress` (the stresses) and `value` (the values).

Denote by `res` the return of the function call, then ggplot can be called via:

```

ggplot(res, aes(x = res[,1], y = ..density.., weight = value))
  +geom_freqpoly(binwidth, aes(color = factor(stress))).

```

See Also

See [cdf](#) and [plot_cdf](#) for values and plotting of the empirical distribution function of a stressed model, respectively, and [quantile_stressed](#) for sample quantiles of a stressed model.

Examples

```

## example with a stress on VaR
set.seed(0)
x <- data.frame("gamma" = rgamma(10^5, shape = 2))
res1 <- stress(type = "VaR", x = x,
  alpha = c(0.75, 0.95), q_ratio = 1.1)
plot_hist(res1, xCol = "gamma", wCol = 1:2, base = TRUE, binwidth = 0.4)
plot_hist(res1, xCol = "gamma", wCol = 1:2, base = TRUE, binwidth = 0.4, displLines = TRUE)

```

plot_sensitivity *Plotting Sensitivities of a Stressed Model*

Description

Plots the sensitivity measures for components (random variables) of a stochastic model under the scenario weights.

Usage

```
plot_sensitivity(
  object,
  xCol = "all",
  wCol = "all",
  type = c("Gamma", "Kolmogorov", "Wasserstein"),
  f = NULL,
  k = NULL,
  displ = TRUE
)
```

Arguments

object	A SWIM object.
xCol	Numeric or character vector, (names of) the columns of the underlying data of the object (default = "all"). If xCol = NULL, only the transformed data $f(x)$ is considered.
wCol	Vector, the columns of the scenario weights of the object corresponding to different stresses (default = "all").
type	Character, one of "Gamma", "Kolmogorov", "Wasserstein", "all".
f	A function, or list of functions, that, applied to x , constitute the transformation of the data for which the sensitivity is calculated.
k	A vector or list of vectors, same length as f , indicating which columns of x each function in f operates on. When f is a list, $k[[i]]$ corresponds to the input variables of $f[[i]]$.
displ	Logical, if TRUE the plot is displayed, otherwise the data.frame for customised plotting with ggplot is returned (default = TRUE).

Details

For the definition of the sensitivity measures (type), see [sensitivity](#).

Note that the Kolmogorov distance is the same for all inputs under the same stress. Thus, it should only be used to compare different stresses, not individual components.

Value

If `displ = TRUE`, a plot displaying the sensitivity measures of the stochastic model under the scenario weights.

If `displ = FALSE`, a `data.frame` for customised plotting with `ggplot`. The `data.frame` contains the columns: `stress` (the stresses), `type` (the types of sensitivity), `X_all` (the random variables), `value` (the values of the sensitivities).

Denote by `result` the return of the function call, then `ggplot` can be called via:

```
ggplot(result, aes(x = X_all, y = value))
+geom_point(aes(color = factor(stress), shape = type)).
```

See Also

See [sensitivity](#) for the values of the sensitivity measures of a stressed model and [importance_rank](#) for ranking of random variables according to their sensitivities.

Examples

```
## Consider the portfolio Y = X1 + X2 + X3 + X4 + X5,
## where (X1, X2, X3, X4, X5) are correlated normally
## distributed with equal mean and different standard deviations,
## see the README for further details.

set.seed(0)
SD <- c(70, 45, 50, 60, 75)
Corr <- matrix(rep(0.5, 5 ^ 2), nrow = 5) + diag(rep(1 - 0.5, 5))
if (!requireNamespace("mvtnorm", quietly = TRUE))
  stop("Package \"mvtnorm\" needed for this function
  to work. Please install it.")
x <- mvtnorm::rmvnorm(10 ^ 5,
  mean = rep(100, 5),
  sigma = (SD %*% t(SD)) * Corr)
data <- data.frame(rowSums(x), x)
names(data) <- c("Y", "X1", "X2", "X3", "X4", "X5")
rev.stress <- stress(type = "VaR", x = data,
  alpha = c(0.75, 0.9), q_ratio = 1.1, k = 1)

sensitivity(rev.stress, type = "all")
plot_sensitivity(rev.stress, xCol = 2:6, type = "Gamma")
plot_sensitivity(rev.stress, xCol = 6, wCol = 1, type = "all")
```

quantile_stressed *Sample Quantiles of a Stressed Model*

Description

Provides sample quantiles for components (random variables) of a stochastic model, corresponding to distribution functions under the scenario weights.

Usage

```
quantile_stressed(
  object,
  probs = seq(0, 1, 0.25),
  xCol = "all",
  wCol = 1,
  type = c("quantile", "(i-1)/(n-1)", "i/(n+1)", "i/n")
)
```

Arguments

object	A SWIM object.
probs	Vector of probabilities with values in $[0, 1]$ (default = $(0, 0.25, 0.5, 0.75, 1)$).
xCol	Numeric or character vector, (names of) the columns of the underlying data of the object (default = "all").
wCol	Numeric, the column of the scenario weights of the object (default = 1).
type	Character, one of "quantile", "(i-1)/(n-1)", "i/(n+1)", "i/n", with default = "quantile". See details below.

Details

type defines the choice of algorithm used for calculating the estimate of the sample quantiles.

"quantile" corresponds to the default interpolation used in [quantile](#). Further options are "(i-1)/(n-1)", "i/(n+1)", "i/" the inverse of the empirical distribution function, using, respectively, $(wt - 1)/T$, $wt/(T+1)$, wt/T , where wt is the cumulative weight and T the total weight (usually total sample size). See [wtd.quantile](#) for further details on type, on which quantile_stressed is based.

Value

Returns a matrix with estimates of the distribution quantiles at the probabilities, probs, under the scenario weights wCol.

See Also

See [wtd.quantile](#) on which the function quantile_stressed is based.
See [cdf](#) for the empirical distribution function of a stressed model.

Examples

```
## example with a stress on VaR
set.seed(0)
x <- as.data.frame(cbind(
  "normal" = rnorm(1000),
  "gamma" = rgamma(1000, shape = 2)))
res1 <- stress(type = "VaR", x = x,
  alpha = c(0.9, 0.95), q_ratio = 1.05)
## stressed sample quantiles
quantile_stressed(res1, probs = seq(0.9, 0.99, 0.01), wCol = 2)
```

sensitivity

Sensitivities of a Stressed Model

Description

Provides different sensitivity measures that compare the stressed and the baseline model.

Usage

```
sensitivity(
  object,
  xCol = "all",
  wCol = "all",
  type = c("Gamma", "Kolmogorov", "Wasserstein", "all"),
  f = NULL,
  k = NULL
)
```

Arguments

object	A SWIM object.
xCol	Numeric or character vector, (names of) the columns of the underlying data of the object (default = "all"). If xCol = NULL, only the transformed data $f(x)$ is considered.
wCol	Vector, the columns of the scenario weights of the object corresponding to different stresses (default = "all").
type	Character, one of "Gamma", "Kolmogorov", "Wasserstein", "all".
f	A function, or list of functions, that, applied to x, constitute the transformation of the data for which the sensitivity is calculated.
k	A vector or list of vectors, same length as f, indicating which columns of x each function in f operates on. When f is a list, $k[[i]]$ corresponds to the input variables of $f[[i]]$.

Details

Provides sensitivity measures that compare the stressed and the baseline model. Implemented sensitivity measures:

1. Gamma, the *Reverse Sensitivity Measure*, defined for a random variable Y and scenario weights w by

$$Gamma = (E(Y * w) - E(Y))/c,$$

where c is a normalisation constant such that $|Gamma| \leq 1$, see (Pesenti et al. 2019). Loosely speaking, the Reverse Sensitivity Measure is the normalised difference between the first moment of the stressed and the baseline distributions of Y .

2. Kolmogorov, the Kolmogorov distance, defined for distribution functions F, G by

$$Kolmogorov = \sup|F(x) - G(x)|.$$

3. Wasserstein, the Wasserstein distance of order 1, defined for two distribution functions F, G by

$$Wasserstein = \int |F(x) - G(x)|dx.$$

If f and k are provided, the sensitivity of the transformed data is returned.

Value

A data.frame containing the sensitivity measures of the stressed model with rows corresponding to different random variables. The first two rows specify the stress and type of the sensitivity measure.

References

Pesenti SM, Millosovich P, Tsanakas A (2019). “Reverse sensitivity testing: What does it take to break the model?” *European Journal of Operational Research*, **274**(2), 654–670.

See Also

See [importance_rank](#) for ranking of random variables according to their sensitivities, [plot_sensitivity](#) for plotting sensitivity measures and [summary](#) for summary statistics of a stressed model.

Examples

```
## example with a stress on VaR
set.seed(0)
x <- as.data.frame(cbind(
  "log-normal" = rlnorm(1000),
  "gamma" = rgamma(1000, shape = 2)))
res1 <- stress(type = "VaR", x = x,
  alpha = c(0.9, 0.95), q_ratio = 1.05)

sensitivity(res1, wCol = 1, type = "all")
## sensitivity of log-transformed data
sensitivity(res1, wCol = 1, type = "all",
```

```

f = list(function(x)log(x), function(x)log(x)), k = list(1,2))

## Consider the portfolio Y = X1 + X2 + X3 + X4 + X5,
## where (X1, X2, X3, X4, X5) are correlated normally
## distributed with equal mean and different standard deviations,
## see the README for further details.

## Not run:
set.seed(0)
SD <- c(70, 45, 50, 60, 75)
Corr <- matrix(rep(0.5, 5 ^ 2), nrow = 5) + diag(rep(1 - 0.5, 5))
if (!requireNamespace("mvtnorm", quietly = TRUE))
  stop("Package \"mvtnorm\" needed for this function
  to work. Please install it.")
x <- mvtnorm::rmvnorm(10 ^ 5,
  mean = rep(100, 5),
  sigma = (SD %*% t(SD)) * Corr)
data <- data.frame(rowSums(x), x)
names(data) <- c("Y", "X1", "X2", "X3", "X4", "X5")
rev.stress <- stress(type = "VaR", x = data,
  alpha = c(0.75, 0.9), q_ratio = 1.1, k = 1)

sensitivity(rev.stress, type = "all")
## sensitivity to sub-portfolios X1 + X2 and X3 + X4
sensitivity(rev.stress, xCol = NULL, type = "Gamma",
  f = rep(list(function(x)x[1] + x[2]), 2), k = list(c(2, 3), c(4, 5)))
plot_sensitivity(rev.stress, xCol = 2:6, type = "Gamma")
importance_rank(rev.stress, xCol = 2:6, type = "Gamma")

## End(Not run)

```

stress

Stressing Random Variables

Description

Provides weights on simulated scenarios from a baseline stochastic model, such that stressed random variables fulfil given probabilistic constraints (e.g. specified values for risk measures), under the new scenario weights. Scenario weights are selected by constrained minimisation of the relative entropy to the baseline model.

Usage

```

stress(
  type = c("VaR", "VaR ES", "mean", "mean sd", "moment", "prob", "user"),
  ...
)

```

Arguments

type Type of stress, one of "VaR", "VaR ES", "mean", "mean sd", "moment", "prob", "user".
... Arguments to be passed on, depending on type.

Value

An object of class SWIM, see [SWIM](#) for details.

Author(s)

Silvana M. Pesenti

References

Pesenti SM, Millossovich P, Tsanakas A (2019). "Reverse sensitivity testing: What does it take to break the model?" *European Journal of Operational Research*, **274**(2), 654–670.

Pesenti Silvana M.and Bettini A, Millossovich P, Tsanakas A (2020). "Scenario Weights for Importance Measurement (SWIM) - An R package for sensitivity analysis." *Available at SSRN*: <https://ssrn.com/abstract=3515274>.

Csiszar I (1975). "I-divergence geometry of probability distributions and minimization problems." *The Annals of Probability*, 146–158.

See Also

Other stress functions: [stress_VaR_ES\(\)](#), [stress_VaR\(\)](#), [stress_mean_sd\(\)](#), [stress_mean\(\)](#), [stress_moment\(\)](#), [stress_prob\(\)](#), [stress_user\(\)](#)

Examples

```
set.seed(0)
x <- as.data.frame(cbind(
  "normal" = rnorm(1000),
  "gamma" = rgamma(1000, shape = 2)))
res <- stress(type = "VaR", x = x,
  alpha = 0.9, q_ratio = 1.05)
summary(res)
```

stress_mean	<i>Stressing Means</i>
-------------	------------------------

Description

Provides weights on simulated scenarios from a baseline stochastic model, such that stressed model components (random variables) fulfil the mean constraints. Scenario weights are selected by constrained minimisation of the relative entropy to the baseline model.

Usage

```
stress_mean(x, k, new_means, ...)
```

Arguments

x	A vector, matrix or data frame containing realisations of random variables. Columns of x correspond to random variables; OR A SWIM object, where x corresponds to the underlying data of the SWIM object.
k	Numeric vector, the columns of x that are stressed.
new_means	Numeric vector, same length as k, containing the stressed means.
...	Additional arguments to be passed to nleqslv .

Details

The function `stress_mean` is a wrapper for the function `stress_moment`. See [stress_moment](#) for details on the additional arguments to `...` and the underlying algorithm.

Value

A SWIM object containing:

- `x`, a `data.frame` containing the data;
- `new_weights`, a list, each component corresponds to a different stress and is a vector of scenario weights;
- `type = "mean"`;
- `specs`, a list, each component corresponds to a different stress and contains `k` and `new_means`.

See [SWIM](#) for details.

References

Pesenti SM, Millossovich P, Tsanakas A (2019). “Reverse sensitivity testing: What does it take to break the model?” *European Journal of Operational Research*, **274**(2), 654–670.

Pesenti Silvana M. and Bettini A, Millossovich P, Tsanakas A (2020). “Scenario Weights for Importance Measurement (SWIM) - An R package for sensitivity analysis.” *Available at SSRN*:

<https://ssrn.com/abstract=3515274>.

Csiszar I (1975). "I-divergence geometry of probability distributions and minimization problems." *The Annals of Probability*, 146–158.

See Also

See [stress_mean_sd](#) for stressing means and standard deviations jointly, and [stress_moment](#) for moment constraints.

Other stress functions: [stress_VaR_ES\(\)](#), [stress_VaR\(\)](#), [stress_mean_sd\(\)](#), [stress_moment\(\)](#), [stress_prob\(\)](#), [stress_user\(\)](#), [stress\(\)](#)

Examples

```
set.seed(0)
x <- data.frame(cbind(
  "normal" = rnorm(1000),
  "gamma" = rgamma(1000, shape = 2),
  "beta" = rbeta(1000, shape1 = 2, shape2 = 2)))
## stressing means
res1 <- stress(type = "mean", x = x, k = 1:3,
  new_means = c(1, 1, 0.75))
summary(res1)
res1$specs
## calling stress_mean directly
res2 <- stress_mean(x = x, k = 1:3,
  new_means = c(1, 1, 0.75))
summary(res2)

## See also examples in stress_moment and stress_mean_sd.
```

stress_mean_sd

Stressing Mean and Standard Deviation

Description

Provides weights on simulated scenarios from a baseline stochastic model, such that stressed model components (random variables) fulfil the mean and standard deviation constraints. Scenario weights are selected by constrained minimisation of the relative entropy to the baseline model.

Usage

```
stress_mean_sd(x, k, new_means, new_sd, ...)
```

Arguments

x	A vector, matrix or data frame containing realisations of random variables. Columns of x correspond to random variables; OR A SWIM object, where x corresponds to the underlying data of the SWIM object.
k	Numeric vector, the columns of x that are stressed.
new_means	Numeric vector, same length as k, containing the stressed means.
new_sd	Numeric vector, same length as k, containing the stressed standard deviations.
...	Additional arguments to be passed to <code>nleqslv</code> .

Details

The function `stress_mean_sd` is a wrapper for the function `stress_moment`. See [stress_moment](#) for details on the additional arguments to ... and the underlying algorithm.

For stressing means only, see [stress_mean](#), for stressing higher moments and functions of moments, see [stress_moment](#).

Value

A SWIM object containing:

- x, a data.frame containing the data;
- new_weights, a list, each component corresponds to a different stress and is a vector of scenario weights;
- type = "mean";
- specs, a list, each component corresponds to a different stress and contains k, new_means and new_sd.

See [SWIM](#) for details.

References

Pesenti SM, Millosovich P, Tsanakas A (2019). "Reverse sensitivity testing: What does it take to break the model?" *European Journal of Operational Research*, **274**(2), 654–670.

Pesenti Silvana M. and Bettini A, Millosovich P, Tsanakas A (2020). "Scenario Weights for Importance Measurement (SWIM) - An R package for sensitivity analysis." *Available at SSRN*: <https://ssrn.com/abstract=3515274>.

Csiszar I (1975). "I-divergence geometry of probability distributions and minimization problems." *The Annals of Probability*, 146–158.

See Also

Other stress functions: [stress_VaR_ES\(\)](#), [stress_VaR\(\)](#), [stress_mean\(\)](#), [stress_moment\(\)](#), [stress_prob\(\)](#), [stress_user\(\)](#), [stress\(\)](#)

Examples

```

set.seed(0)
x <- data.frame(cbind(
  "normal" = rnorm(1000),
  "gamma" = rgamma(1000, shape = 2),
  "beta" = rbeta(1000, shape1 = 2, shape2 = 2)))
## stressing mean and sd of column 1
res1 <- stress(type = "mean sd", x = x, k = 1, new_means = 0.1,
  new_sd = 1.1, method = "Newton",
  control = list(maxit = 1000, ftol = 1E-15))
summary(res1)
## calling stress_mean_sd directly
res2 <- stress_mean_sd(x = x, k = 1, new_means = 0.1,
  new_sd = 1.1, method = "Newton",
  control = list(maxit = 1000, ftol = 1E-15))

## See also examples in stress_moment.

```

stress_moment

Stressing Moments

Description

Provides weights on simulated scenarios from a baseline stochastic model, such that stressed model components (random variables) fulfil the moment constraints. Scenario weights are selected by constrained minimisation of the relative entropy to the baseline model.

Usage

```
stress_moment(x, f, k, m, show = FALSE, ...)
```

Arguments

x	A vector, matrix or data frame containing realisations of random variables. Columns of x correspond to random variables; OR A SWIM object, where x corresponds to the underlying data of the SWIM object.
f	A function, or list of functions, that, applied to x, constitute the moment constraints.
k	A vector or list of vectors, same length as f, indicating which columns of x each function in f operates on. When f is a list, k[[i]] corresponds to the input variables of f[[i]].
m	Numeric vector, same length as f, containing the stressed moments of f(x). Must be in the range of f(x).
show	Logical. If true, print the result of the call to nleqslv .
...	Additional arguments to be passed to nleqslv .

Details

The moment constraints are given by $E^Q(f(x)) = m$, where E^Q denotes the expectation under the stressed model. `stress_moment` solves the subsequent set of equations with respect to `theta`, using `nleqslv` from package `nleqslv`:

$$E^Q(f(x)) = E(f(x) * \exp(\theta * f(x))) = m.$$

There is no guarantee that the set of equations will have a solution, or that the solution is unique. SWIM will return a warning if the termination code provided by `nleqslv` is different from 1 (convergence has been achieved). It is recommended to check the result of the call to `nleqslv` using the "show" argument. The user is referred to the `nleqslv` documentation for further details.

Value

A SWIM object containing:

- `x`, a `data.frame` containing the data;
- `new_weights`, a list, each component corresponds to a different stress and is a vector of scenario weights;
- `type = "moment"`;
- `specs`, a list, each component corresponds to a different stress and contains `f`, `k` and `m`.

See [SWIM](#) for details.

References

Pesenti SM, Millossovich P, Tsanakas A (2019). "Reverse sensitivity testing: What does it take to break the model?" *European Journal of Operational Research*, **274**(2), 654–670.

Pesenti Silvana M. and Bettini A, Millossovich P, Tsanakas A (2020). "Scenario Weights for Importance Measurement (SWIM) - An R package for sensitivity analysis." *Available at SSRN*: <https://ssrn.com/abstract=3515274>.

Csiszar I (1975). "I-divergence geometry of probability distributions and minimization problems." *The Annals of Probability*, 146–158.

See Also

See [stress_mean](#) for stressing means and [stress_mean_sd](#) for stressing mean and standard deviation jointly.

Other stress functions: [stress_VaR_ES\(\)](#), [stress_VaR\(\)](#), [stress_mean_sd\(\)](#), [stress_mean\(\)](#), [stress_prob\(\)](#), [stress_user\(\)](#), [stress\(\)](#)

Examples

```

set.seed(0)
x <- data.frame(cbind(
  "normal" = rnorm(1000),
  "gamma" = rgamma(1000, shape = 2),
  "beta" = rbeta(1000, shape1 = 2, shape2 = 2)))

## stressing covariance of columns 1, 2 while leaving the means unchanged
res1 <- stress_moment(x = x,
  f = list(function(x)x, function(x)x, function(x)x[1] * x[2]),
  k = list(1, 2, c(1, 2)), m = c(0, 2, 0.5),
  method = "Newton", control = list(maxit = 1000, ftol = 1E-10))
## means under the stressed model
summary(res1)
apply(x, 2, stats::weighted.mean, w = get_weights(res1))
## covariance of columns 1,2 under the stressed model
stats::weighted.mean(x[, 1] * x[, 2], w = get_weights(res1))

## stressing jointly the tail probabilities of columns 1, 3
res2 <- stress_moment(x = x,
  f = list(function(x)(x > 1.5), function(x)(x > 0.9)),
  k = list(1, 3), m = c(0.9, 0.9))
summary(res2)
## probabilities under the stressed model
mean((x[, 1] > 1.5) * get_weights(res2))
mean((x[, 3] > 0.9) * get_weights(res2))

```

stress_prob

Stressing Intervals

Description

Provides weights on simulated scenarios from a baseline stochastic model, such that a stressed model component (random variable) fulfils constraints on probability of disjoint intervals. Scenario weights are selected by constrained minimisation of the relative entropy to the baseline model.

Usage

```
stress_prob(x, prob, lower = NULL, upper, k = 1)
```

Arguments

x	A vector, matrix or data frame containing realisations of random variables. Columns of x correspond to random variables; OR A SWIM object, where x corresponds to the underlying data of the SWIM object.
prob	Numeric vector, stressed probabilities corresponding to the intervals defined through lower and upper.

lower	Numeric vector, left endpoints of the intervals.
upper	Numeric vector, right endpoints of the intervals.
k	Numeric, the column of x that is stressed (default = 1).

Details

The intervals are treated as half open intervals, that is the lower endpoint are not included, whereas the upper endpoint are included. If upper = NULL, the intervals are consecutive and prob cumulative.

The intervals defined through lower and upper must be disjoint.

Value

A SWIM object containing:

- x, a data.frame containing the data;
- new_weights, a list of functions, that applied to the kth column of x, generate the vectors of scenario weights. Each component corresponds to a different stress;
- type = "prob";
- specs, a list, each component corresponds to a different stress and contains k, lower, upper and prob.

See [SWIM](#) for details.

Author(s)

Silvana M. Pesenti

References

Pesenti SM, Millosovich P, Tsanakas A (2019). "Reverse sensitivity testing: What does it take to break the model?" *European Journal of Operational Research*, **274**(2), 654–670.

Pesenti Silvana M.and Bettini A, Millosovich P, Tsanakas A (2020). "Scenario Weights for Importance Measurement (SWIM) - An R package for sensitivity analysis." *Available at SSRN*: <https://ssrn.com/abstract=3515274>.

Csiszar I (1975). "I-divergence geometry of probability distributions and minimization problems." *The Annals of Probability*, 146–158.

See Also

Other stress functions: [stress_VaR_ES\(\)](#), [stress_VaR\(\)](#), [stress_mean_sd\(\)](#), [stress_mean\(\)](#), [stress_moment\(\)](#), [stress_user\(\)](#), [stress\(\)](#)

Examples

```

set.seed(0)
x <- rnorm(1000)
## consecutive intervals
res1 <- stress(type = "prob", x = x, prob = 0.008, upper = -2.4)
# probability under the stressed model
cdf(res1, xCol = 1)(-2.4)

## calling stress_prob directly
## multiple intervals
res2 <- stress_prob(x = x, prob = c(0.008, 0.06),
  lower = c(-3, -2), upper = c(-2.4, -1.6))
# probability under the stressed model
cdf(res2, xCol = 1)(c(-2.4, -1.6)) - cdf(res2, xCol = 1)(c(-3, -2))

```

stress_user

User Defined Stress

Description

Returns a SWIM object with scenario weights defined by the user.

Usage

```
stress_user(x, new_weights = NULL, new_weightsfun = NULL, k = 1)
```

Arguments

x	A vector, matrix or data frame containing realisations of random variables. Columns of x correspond to random variables; OR A SWIM object, where x corresponds to the underlying data of the SWIM object.
new_weights	A vector, matrix or data frame containing scenario weights. Columns of new_weights correspond to different stresses. new_weights are normalised to have a mean of 1.
new_weightsfun	A list of functions, that applied to the kth column of x generate the vectors of the scenario weights. Each function corresponds to a stress. The weights generated for each stress are normalised to have a mean of 1.
k	Numeric, the column of x that is stressed (default = 1).

Value

A SWIM object containing:

- x, a data.frame containing the data;
- new_weights, a list, each component corresponds to a different stress and is either a vector of scenario weights (if new_weights is provided) or (if new_weightsfun is provided) a function, that applied to the kth column of x, generates the vectors of scenario weights;

- `type = "user"`;
- `specs`, a list, each component corresponds to a different stress and contains `k`.

See [SWIM](#) for details.

References

Pesenti SM, Millossovich P, Tsanakas A (2019). “Reverse sensitivity testing: What does it take to break the model?” *European Journal of Operational Research*, **274**(2), 654–670.

Pesenti Silvana M. and Bettini A, Millossovich P, Tsanakas A (2020). “Scenario Weights for Importance Measurement (SWIM) - An R package for sensitivity analysis.” *Available at SSRN*: <https://ssrn.com/abstract=3515274>.

Csiszar I (1975). “I-divergence geometry of probability distributions and minimization problems.” *The Annals of Probability*, 146–158.

See Also

Other stress functions: [stress_VaR_ES\(\)](#), [stress_VaR\(\)](#), [stress_mean_sd\(\)](#), [stress_mean\(\)](#), [stress_moment\(\)](#), [stress_prob\(\)](#), [stress\(\)](#)

Examples

```
set.seed(0)
x <- as.data.frame(cbind(
  "normal" = rnorm(1000),
  "gamma" = rgamma(1000, shape = 2)))
res1 <- stress(type = "user", x = x, new_weightsfun = function(x)x ^ 2, k = 1)
## plot user defined weights against the first column of x.
plot(x$normal, get_weights(res1), pch = ".")
```

stress_VaR

Stressing Value-at-Risk

Description

Provides weights on simulated scenarios from a baseline stochastic model, such that a stressed model component (random variable) fulfils a constraint on its quantile at a given level, also known as Value-at-Risk (VaR). Scenario weights are selected by constrained minimisation of the relative entropy to the baseline model.

Usage

```
stress_VaR(x, alpha, q_ratio = NULL, q = NULL, k = 1)
```

Arguments

x	A vector, matrix or data frame containing realisations of random variables. Columns of x correspond to random variables; OR A SWIM object, where x corresponds to the underlying data of the SWIM object.
alpha	Numeric vector, the levels of the stressed VaR.
q_ratio	Numeric vector, the ratio of the stressed VaR to the baseline VaR. If alpha and q_ratio are vectors, they must have the same length.
q	Numeric vector, the stressed VaR at level alpha. If alpha and q are vectors, they must have the same length.
k	Numeric, the column of x that is stressed (default = 1).

Details

The stressed VaR is the quantile of the chosen model component, subject to the calculated scenario weights. The VaR at level alpha of a random variable with distribution function F is defined as its left-quantile at alpha:

$$VaR_{alpha} = F^{-1}(alpha).$$

If one of alpha, q (q_ratio) is a vector, the stressed VaR's of the kth column of x, at levels alpha, are equal to q.

The stressed VaR specified, either via q or q_ratio, might not equal the attained empirical VaR of the model component. In this case, stress_VaR will display a message and the specs contain the achieved VaR.

Value

A SWIM object containing:

- x, a data.frame containing the data;
- new_weights, a list of functions, that applied to the kth column of x, generates the vectors of scenario weights. Each component corresponds to a different stress;
- type = "VaR";
- specs, a list, each component corresponds to a different stress and contains k, alpha and q.

See [SWIM](#) for details.

Author(s)

Silvana M. Pesenti

References

Pesenti SM, Millosovich P, Tsanakas A (2019). "Reverse sensitivity testing: What does it take to break the model?" *European Journal of Operational Research*, **274**(2), 654–670.

Pesenti Silvana M. and Bettini A, Millosovich P, Tsanakas A (2020). "Scenario Weights for Importance Measurement (SWIM) - An R package for sensitivity analysis." *Available at SSRN*:

<https://ssrn.com/abstract=3515274>.

Csiszar I (1975). “I-divergence geometry of probability distributions and minimization problems.” *The Annals of Probability*, 146–158.

See Also

Other stress functions: `stress_VaR_ES()`, `stress_mean_sd()`, `stress_mean()`, `stress_moment()`, `stress_prob()`, `stress_user()`, `stress()`

Examples

```
set.seed(0)
x <- as.data.frame(cbind(
  "normal" = rnorm(1000),
  "gamma" = rgamma(1000, shape = 2)))
res1 <- stress(type = "VaR", x = x,
  alpha = 0.9, q_ratio = 1.05)

## calling stress_VaR directly
## stressing "gamma"
res2 <- stress_VaR(x = x, alpha = 0.9,
  q_ratio = c(1.03, 1.05), k = 2)
get_specs(res2)
summary(res2)
```

stress_VaR_ES

Stressing Value-at-Risk and Expected Shortfall

Description

Provides weights on simulated scenarios from a baseline stochastic model, such that a stressed model component (random variable) fulfils a constraint on its Value-at-Risk (VaR) and Expected Shortfall (ES) risk measures, both evaluated at a given level. Scenario weights are selected by constrained minimisation of the relative entropy to the baseline model.

Usage

```
stress_VaR_ES(
  x,
  alpha,
  q_ratio = NULL,
  s_ratio = NULL,
  q = NULL,
  s = NULL,
  k = 1
)
```

Arguments

x	A vector, matrix or data frame containing realisations of random variables. Columns of x correspond to random variables; OR A SWIM object, where x corresponds to the underlying data of the SWIM object.
alpha	Numeric vector, the levels of the stressed VaR.
q_ratio	Numeric vector, the ratio of the stressed VaR to the baseline VaR. If alpha and q_ratio are vectors, they must have the same length.
s_ratio	Numeric, vector, the ratio of the stressed ES to the baseline ES. If q (q_ratio) and s_ratio are vectors, they must have the same length.
q	Numeric vector, the stressed VaR at level alpha. If alpha and q are vectors, they must have the same length.
s	Numeric, vector, the stressed ES at level alpha. If q and s are vectors, they must have the same length.
k	Numeric, the column of x that is stressed (default = 1).

Details

The VaR at level alpha of a random variable with distribution function F is defined as its left-quantile at alpha:

$$VaR_{alpha} = F^{-1}(alpha).$$

The ES at level alpha of a random variable with distribution function F is defined by:

$$ES_{alpha} = 1/(1 - alpha) * \int_{alpha}^1 VaR_u du.$$

The stressed VaR and ES are the risk measures of the chosen model component, subject to the calculated scenario weights. If one of alpha, q, s (q_ratio, s_ratio) is a vector, the stressed VaR's and ES's of the kth column of x, at levels alpha, are equal to q and s, respectively.

The stressed VaR specified, either via q or q_ratio, might not equal the attained empirical VaR of the model component. In this case, stress_VaR will display a message and the specs contain the achieved VaR. Further, ES is then calculated on the bases of the achieved VaR.

Value

A SWIM object containing:

- x, a data.frame containing the data;
- new_weights, a list of functions, that applied to the kth column of x, generates the vectors of scenario weights. Each component corresponds to a different stress;
- type = "VaR ES";
- specs, a list, each component corresponds to a different stress and contains k, alpha, q and s.

See [SWIM](#) for details.

References

Pesenti SM, Millossovich P, Tsanakas A (2019). “Reverse sensitivity testing: What does it take to break the model?” *European Journal of Operational Research*, **274**(2), 654–670.

Pesenti Silvana M.and Bettini A, Millossovich P, Tsanakas A (2020). “Scenario Weights for Importance Measurement (SWIM) - An R package for sensitivity analysis.” *Available at SSRN*: <https://ssrn.com/abstract=3515274>.

Csiszar I (1975). “I-divergence geometry of probability distributions and minimization problems.” *The Annals of Probability*, 146–158.

See Also

Other stress functions: [stress_VaR\(\)](#), [stress_mean_sd\(\)](#), [stress_mean\(\)](#), [stress_moment\(\)](#), [stress_prob\(\)](#), [stress_user\(\)](#), [stress\(\)](#)

Examples

```
set.seed(0)
x <- as.data.frame(cbind(
  "normal" = rnorm(1000),
  "gamma" = rgamma(1000, shape = 2)))
res1 <- stress(type = "VaR ES", x = x,
  alpha = c(0.9, 0.95), q_ratio = 1.05, s_ratio = 1.08)

## calling stress_VaR_ES directly
## stressing "gamma"
res2 <- stress_VaR_ES(x = x, alpha = 0.9,
  q_ratio = 1.03, s_ratio = c(1.05, 1.08), k = 2)
get_specs(res2)
summary(res2)
```

summary.SWIM

Summarising Stressed Models

Description

This function is a [methods](#) for an object of class SWIM. Provides summary statistics of the stochastic model, stressed using the scenario weights.

Usage

```
## S3 method for class 'SWIM'
summary(object, ..., xCol = "all", wCol = "all", base = FALSE)
```


Arguments

object	A SWIM object.
...	Additional arguments will be ignored.
xCol	Numeric or character vector, (names of) the columns of the underlying data of the object (default = "all").
wCol	Vector, the columns of the scenario weights of the object corresponding to different stresses (default = "all").
base	Logical, if TRUE, statistics under the baseline are also returned (default = "FALSE").

Value

summary.SWIM returns a list with components corresponding to different stresses. Components contain a summary statistic of each column of the data of the SWIM object:

mean	The sample mean.
sd	The sample standard deviation.
skewness	The sample skewness.
ex kurtosis	The sample excess kurtosis
1st Qu.	The 25% quantile.
Median	The median, 50% quantile.
3rd Qu.	The 75% quantile.

Author(s)

Silvana M. Pesenti

See Also

[summary, SWIM](#)

Examples

```
## continuing example in stress_VaR
set.seed(0)
x <- as.data.frame(cbind(
  "normal" = rnorm(1000),
  "gamma" = rgamma(1000, shape = 2)))
res1 <- stress(type = "VaR", x = x,
  alpha = 0.9, q_ratio = 1.05)

summary(res1, xCol = "normal", base = TRUE)
```

Description

The SWIM package provides weights on simulated scenarios from a stochastic model, such that a stressed model components (random variables) fulfil given probabilistic constraints (e.g. specified values for risk measures), under the new scenario weights. Scenario weights are selected by constrained minimisation of the relative entropy to the baseline model.

Details

The SWIM (Scenario Weights for Importance Measurement) package provides weights on simulated scenarios from a stochastic model, such that stressed random variables fulfil given probabilistic constraints (e.g. specified values for risk measures), under the new scenario weights. Scenario weights are selected by constrained minimisation of the relative entropy to the baseline model.

The SWIM package is based on the *reverse sensitivity framework* developed by (Pesenti et al. 2019). Consider the random vector $X = (X_1, \dots, X_n)$. Let P represent the probability measure under which all simulated scenarios have the same probability. Then, for a random variable X_i , the package solves:

$$\min D(P|Q)$$

s.t. constraints on the distribution of X_i under Q , where $D(P | Q)$ is the Kullback-Leibler divergence (relative entropy) between P and Q . The solution is formed by the scenario weights representing the Radon-Nikodym derivative dQ / dP . The weighting generates a model for which the joint distribution of (X_1, \dots, X_n) is stressed.

Different elements of X can be understood as inputs or outputs of a model. For example, consider a model $Y = g(Z)$ with input vector $Z = (Z_1, \dots, Z_{(n-1)})$. One can then identify $X_1 = Y$ and $X_2 = Z_1, \dots, X_n = Z_{(n-1)}$. Subsequently, the user of the SWIM package can stress the model output or any of the inputs, measuring the resulting impact on the distributions of other variables.

Stresses

Scenario weights for the following stresses are provided:

<code>stress</code>	calls one of the functions below by using type
<code>stress_VaR</code>	for stressing the VaR (type = "VaR")
<code>stress_VaR_ES</code>	for stressing the VaR and ES jointly (type = "VaR ES")
<code>stress_mean</code>	for stressing means (type = "mean")
<code>stress_mean_sd</code>	for stressing means and standard deviations (type = "mean sd")
<code>stress_moment</code>	for stressing moments (type = "moment")
<code>stress_prob</code>	for stressing the probabilities of intervals (type = "prob")
<code>stress_user</code>	for user defined scenario weights (type = "user")

A SWIM object

An object of class SWIM contains a list of:

- `x`, a data.frame containing realisations of a random vector;
- `new_weights`, a list, each component corresponds to a different stress and is either a vector of scenario weights or a function, that applied to the `k`th column of `x`, generates the vectors of scenario weights;
- `type`: a list, each component corresponds to a different stress and specifies the type of the stress;
- `specs`, a list, each component corresponds to a different stress and contains a list with the specifications of what has been stressed. Specifications depend on the type of stress:
 - `type = "VaR"`: `k`, the column of `x` on which the stress is applied to; `alpha`, the level of the stressed VaR; `q`, the stressed VaR at level `alpha`.
 - `type = "VaR ES"`: `k`, the column of `x` on which the stress is applied to; `alpha`, the level of the stressed VaR and ES; `q`, the stressed VaR at level `alpha`.
 - `type = "mean"`: `k`, the columns of `x` on which the stress is applied to; `new_means`, the stressed means.
 - `type = "mean sd"`: `k`, the columns of `x` on which the stress is applied to; `new_means`, the stressed means; `new_sd`, the stressed standard deviations. `s`, the stressed ES at level `alpha`.
 - `type = "moment"`: `f`, the list of functions, that, applied to `x`, constitute the moment constraints; `k`, the columns of `x` on which each function in `f` operates on; `m`, the stressed moments of $f(x)$.
 - `type = "prob"`: `k`, the column of `x` on which the stress is applied to; `lower`, the left endpoints of the intervals; `upper`, the right endpoints of the intervals; `prob`, stressed probabilities corresponding to the intervals defined through `lower` and `upper`.
 - `type = "user"`: `k`, the column of `x` on which the stress is applied to.

References

Pesenti SM, Millosovich P, Tsanakas A (2019). "Reverse sensitivity testing: What does it take to break the model?" *European Journal of Operational Research*, **274**(2), 654–670.

Pesenti Silvana M. and Bettini A, Millosovich P, Tsanakas A (2020). "Scenario Weights for Importance Measurement (SWIM) - An R package for sensitivity analysis." *Available at SSRN*: <https://ssrn.com/abstract=3515274>.

Csiszar I (1975). "I-divergence geometry of probability distributions and minimization problems." *The Annals of Probability*, 146–158.

See Also

See [get_data](#) for extracting the data, `x`; [get_weights](#) for extracting the scenario weights, `new_weights`; [get_weightsfun](#) for extracting the functions generating the scenario weights; and [get_specs](#) for extracting the specifications of the stress on an object of class SWIM.

Index

*Topic **datasets**

credit_data, 3

cdf, 2, 11, 12

credit_data, 3

ES_stressed, 4

get_data, 6, 35

get_specs, 35

get_specs (get_data), 6

get_weights, 6, 35

get_weights (get_data), 6

get_weightsfun, 35

get_weightsfun (get_data), 6

importance_rank, 7, 14, 17

merge.SWIM, 9

methods, 32

nleqslv, 20, 22–24

plot_cdf, 3, 10, 12

plot_hist, 11

plot_sensitivity, 8, 13, 17

quantile, 15

quantile_stressed, 3, 11, 12, 15

sensitivity, 8, 13, 14, 16

stress, 18, 21, 22, 24, 26, 28, 30, 32, 34

stress_mean, 19, 20, 22, 24, 26, 28, 30, 32, 34

stress_mean_sd, 19, 21, 21, 24, 26, 28, 30, 32, 34

stress_moment, 19–22, 23, 26, 28, 30, 32, 34

stress_prob, 19, 21, 22, 24, 25, 28, 30, 32, 34

stress_user, 19, 21, 22, 24, 26, 27, 30, 32, 34

stress_VaR, 19, 21, 22, 24, 26, 28, 28, 32, 34

stress_VaR_ES, 19, 21, 22, 24, 26, 28, 30, 30, 34

summary, 8, 17, 33

summary.SWIM, 32

SWIM, 7, 9, 19, 20, 22, 24, 26, 28, 29, 31, 33, 34

VaR_stressed (ES_stressed), 4

wtd.quantile, 15