

Package ‘alfred’

April 1, 2019

Title Downloading Time Series from ALFRED Database for Various Vintages

Version 0.1.7

Description Provides direct access to the AL-FRED (<https://alfred.stlouisfed.org>) and FRED (<https://fred.stlouisfed.org>) databases. Its functions return tidy data frames for different releases of the specified time series. Note that this product uses the FRED© API but is not endorsed or certified by the Federal Reserve Bank of St. Louis.

Depends R (>= 3.3.0)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Imports dplyr, tidyr, tibble, magrittr, lubridate, jsonlite

URL <https://github.com/onnokleen/alfred/>

BugReports <https://github.com/onnokleen/alfred/issues>

Suggests testthat, knitr, rmarkdown, ggplot2, covr

VignetteBuilder knitr

NeedsCompilation no

Author Onno Kleen [aut, cre] (<https://orcid.org/0000-0003-4731-4640>)

Maintainer Onno Kleen <r@onnokleen.de>

Repository CRAN

Date/Publication 2019-04-01 09:20:03 UTC

R topics documented:

get_alfred_series	2
get_fred_series	3

Index	4
--------------	----------

get_alfred_series *Accessing ALFRED*

Description

This function can pull time series from the ALFRED database: <https://alfred.stlouisfed.org>. Downloading different vintages for performing real-time analysis is provided.

Usage

```
get_alfred_series(series_id, series_name = NULL,  
                  observation_start = NULL, observation_end = NULL,  
                  realtime_start = NULL, realtime_end = NULL)
```

Arguments

series_id	FRED times series ID.
series_name	Choose a name for the series column in output. Default: series_id.
observation_start	Date of first observation in "yyyy-mm-dd" format. Default: Earliest observation available.
observation_end	Date of last observation in "yyyy-mm-dd" format. Default: Last observation available.
realtime_start	Date of first real time period in "yyyy-mm-dd" format. Default: First vintage date available.
realtime_end	Date of last real time period in "yyyy-mm-dd" format. Default: Last vintage date available.

Details

FRED time series IDs can be found on the respective site in ALFRED, e.g. <https://alfred.stlouisfed.org/series?seid=CPIAUCSL>.

Examples

```
## Not run:  
  get_alfred_series("INDPRO", "indpro")  
  
## End(Not run)  
get_alfred_series("INDPRO", "indpro", realtime_start = "2008-10-31", realtime_end = "2009-10-31")
```

get_fred_series	<i>Accessing FRED</i>
-----------------	-----------------------

Description

This function can pull time series from the FRED database: <https://fred.stlouisfed.org>.

Usage

```
get_fred_series(series_id, series_name = NULL,  
               observation_start = NULL, observation_end = NULL)
```

Arguments

series_id	FRED times series ID.
series_name	Choose a name for the series column in output. Default: series_id.
observation_start	Date of first observation in "yyyy-mm-dd" format. Default: Earliest observation available.
observation_end	Date of last observation in "yyyy-mm-dd" format. Default: Last observation available.

Examples

```
get_fred_series("INDPRO", "indpro")
```

Index

*Topic **alfred**

get_alfred_series, 2

*Topic **fred**

get_fred_series, 3

get_alfred_series, 2

get_fred_series, 3