

Package ‘blindrecalc’

May 11, 2020

Type Package

Title Blinded Sample Size Recalculation

Version 0.1.2

Description Computation of key characteristics and plots for blinded sample size recalculation. Continuous as well as binary endpoints are supported in superiority and non-inferiority trials. The implemented methods include the approaches by Lu, K. (2019) <doi:10.1002/pst.1737>, Kieser, M. and Friede, T. (2000) <doi:10.1002/(SICI)1097-0258(20000415)19:7%3C901::AID-SIM405%3E3.0.CO;2-L>, Friede, T. and Kieser, M. (2004) <doi:10.1002/pst.140>, Friede, T., Mitchell, C., Mueller-Veltorn, G. (2007) <doi:10.1002/bimj.200610373>, and Friede, T. and Kieser, M. (2011) <doi:10.3414/ME09-01-0063>.

License MIT + file LICENSE

URL <https://github.com/imbi-heidelberg/blindrecalc>

Encoding UTF-8

LazyData true

Suggests testthat, covr

Imports methods, Rcpp

Collate test_statistics.R methods.R Student.R blindrecalc.R
ChiSquare.R ChiSquare_helper.R FarringtonManning.R
FarringtonManning_helper.R RcppExports.R

RoxygenNote 7.1.0

LinkingTo Rcpp

NeedsCompilation yes

Author Lukas Baumann [aut],
Maximilian Pilz [aut, cre],
Institute of Medical Biometry and Informatics - University of
Heidelberg [cph]

Maintainer Maximilian Pilz <pilz@imbi.uni-heidelberg.de>

Repository CRAN

Date/Publication 2020-05-11 11:10:14 UTC

R topics documented:

adjusted_alpha	2
adjusted_alpha,ChiSquare-method	3
adjusted_alpha,FarringtonManning-method	4
adjusted_alpha,Student-method	6
blindrecalc	7
ChiSquare-class	7
FarringtonManning-class	8
n_dist	9
n_dist,ChiSquare-method	10
n_dist,FarringtonManning-method	11
n_dist,Student-method	12
n_fix	13
n_fix,ChiSquare-method	14
n_fix,FarringtonManning-method	15
n_fix,Student-method	16
pow	16
pow,ChiSquare-method	17
pow,FarringtonManning-method	18
pow,Student-method	19
simulation	20
Student-class	21
toer	23
toer,ChiSquare-method	24
toer,FarringtonManning-method	25
toer,Student-method	26
Index	28

adjusted_alpha	<i>Adjusted level of significance</i>
----------------	---------------------------------------

Description

This method returns an adjusted significance level that can be used such that the actual type I error rate is preserved.

Usage

```
adjusted_alpha(design, n1, nuisance, ...)
```

Arguments

design	object of class TestStatistic created by setup
n1	number of patients that are recruited before the sample size is recalculated
nuisance	nuisance parameter that is estimated at the interim analysis
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

The method is implemented for the classes [Student](#), [ChiSquare](#), and [FarringtonManning](#).

Value

Value of the adjusted significance level for every nuisance parameter and every value of n1.

Examples

```
d <- setupStudent(alpha = .025, beta = .2, r = 1, delta = 0, delta_NI = 1.5, n_max = 848)
sigma <- c(2, 5.5, 9)
adjusted_alpha(design = d, n1 = 20, nuisance = sigma, tol = 1e-4, iters = 1e3)
```

adjusted_alpha, ChiSquare-method

Adjusted level of significance

Description

This method returns an adjusted significance level that can be used such that the actual type I error rate is preserved.

Usage

```
## S4 method for signature 'ChiSquare'
adjusted_alpha(
  design,
  n1,
  nuisance,
  nuis_ass,
  precision = 0.001,
  gamma = 0,
  recalculation,
  allocation = c("exact", "approximate"),
  ...
)
```

Arguments

design	Object of class ChiSquare created by setupChiSquare.
n1	Either the sample size of the first stage (if recalculation = TRUE or the total sample size (if recalculation = FALSE).
nuisance	Value of the nuisance parameter. For the Chi-Squared test this is the overall response rate.

<code>nuis_ass</code>	If <code>recalculation = FALSE</code> this is the value for the overall response rate that is used to calculate the sample size for the adjusted significance level.
<code>precision</code>	Value by which the nominal type 1 error rate is reduced in each iteration until the nominal type 1 error rate is preserved.
<code>gamma</code>	If <code>gamma > 0</code> then the significance level is adjusted such that the actual level is at most $\alpha - \text{gamma}$. This is necessary to maintain the nominal significance level if a confidence interval approach proposed by Friede & Kieser (2011) is used.
<code>recalculation</code>	Should the sample size be recalculated after <code>n1</code> patients are recruited?
<code>allocation</code>	Whether the allocation ratio should be preserved exactly (<code>exact</code>) or approximately (<code>approximate</code> or <code>kf_approx</code>). <code>approximate</code> uses the unrounded calculated sample size in the sample size recalculation, <code>kf_approx</code> rounds the sample size to the next integer.
<code>...</code>	Further optional arguments.

Details

The method is only vectorized in either nuisance or `n1`.

Value

Value of the adjusted significance level for every nuisance parameter and every value of `n1`.

Examples

```
d <- setupChiSquare(alpha = 0.025, beta = 0.2, r = 1, delta = 0.2)
adjusted_alpha(d, n1 = 10, nuisance = 0.3, gamma = 0.001,
  nuis_ass = 0.3, precision = 0.001, recalculation = TRUE)
```

`adjusted_alpha,FarringtonManning-method`
Adjusted level of significance

Description

This method returns an adjusted significance level that can be used such that the actual type I error rate is preserved.

Usage

```
## S4 method for signature 'FarringtonManning'
adjusted_alpha(
  design,
  n1,
  nuisance,
```

```

    nuis_ass,
    precision = 0.001,
    gamma = 0,
    recalculation,
    allocation = c("exact", "approximate"),
    ...
  )

```

Arguments

design	Object of class <code>FarringtonManning</code> created by <code>setupFarringtonManning</code> .
n1	Either the sample size of the first stage (if <code>recalculation = TRUE</code> or the total sample size (if <code>recalculation = FALSE</code>).
nuisance	Value of the nuisance parameter. For the Farrington-Manning test this is the overall response rate.
nuis_ass	If <code>recalculation = FALSE</code> this is the value for the overall response rate that is used to calculate the sample size for the adjusted significance level.
precision	Value by which the nominal type 1 error rate is reduced in each iteration until the nominal type 1 error rate is preserved.
gamma	If $\gamma > 0$ then the significance level is adjusted such that the actual level is at most $\alpha - \gamma$. This is necessary to maintain the nominal significance level if a confidence interval approach proposed by Friede & Kieser (2011) is used.
recalculation	Should the sample size be recalculated after n1 patients are recruited?
allocation	Whether the allocation ratio should be preserved exactly (<code>exact</code>) or approximately (<code>approximate</code>).
...	Further optional arguments.

Details

The method is only vectorized in either `nuisance` or `n1`.

Value

Value of the adjusted significance level for every nuisance parameter and every value of `n1`.

Examples

```

d <- setupFarringtonManning(alpha = 0.025, beta = 0.2, r = 1, delta = 0, delta_NI = 0.25)
adjusted_alpha(d, n1 = 20, nuisance = 0.5, recalculation = TRUE)

```

adjusted_alpha,Student-method
Adjusted level of significance

Description

This method returns an adjusted significance level that can be used such that the actual type I error rate is preserved.

Usage

```
## S4 method for signature 'Student'  
adjusted_alpha(design, n1, nuisance, tol, iters = 10000, seed = NULL, ...)
```

Arguments

design	Object of class Student created by setupStudent.
n1	Either the sample size of the first stage (if recalculation = TRUE or the total sample size (if recalculation = FALSE).
nuisance	Value of the nuisance parameter. For the Student's t-test this is the variance.
tol	desired absolute tolerance
iters	Number of simulation iterations.
seed	Random seed for simulation.
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

In the case of the Student's t-test, the adjusted alpha is calculated using the algorithm by Kieser and Friede (2000): "Re-calculating the sample size in internal pilot study designs with control of the type I error rate". Statistics in Medicine 19: 901-911.

Value

Value of the adjusted significance level for every nuisance parameter and every value of n1.

Examples

```
d <- setupStudent(alpha = .025, beta = .2, r = 1, delta = 0, delta_NI = 1.5, n_max = 848)  
sigma <- c(2, 5.5, 9)  
adjusted_alpha(design = d, n1 = 20, nuisance = sigma, tol = 1e-4, iters = 1e3)
```

blindrecalc	<i>Blinded Sample Size Recalculation</i>
-------------	--

Description

The package **blindrecalc** provides characteristics and plots of trial designs with blinded sample size recalculation where a nuisance parameter is estimated at an blinded interim analysis.

Details

Currently, for continuous outcomes, a t-test is implemented for superiority and non-inferiority trials. For superiority trials with binary endpoint, the chi²-test is implemented. The Farrington Manning test covers non-inferiority trials with binary endpoint.

ChiSquare-class	<i>Chi-squared test</i>
-----------------	-------------------------

Description

This class implements a chi-squared test for superiority trials. A trial with binary outcomes in two groups T and C is assumed.

The function `setupChiSquare` creates an object of class `ChiSquare`.

Usage

```
setupChiSquare(
  alpha,
  beta,
  r = 1,
  delta,
  alternative = c("greater", "smaller"),
  n_max = Inf,
  ...
)
```

Arguments

alpha	One-sided type I error rate.
beta	Type II error rate.
r	Allocation ratio between experimental and control group.
delta	Difference of effect size between alternative and null hypothesis.
alternative	Does the alternative hypothesis contain greater (greater) or smaller (smaller) values than the null hypothesis.
n_max	Maximal overall sample size. If the recalculated sample size is greater than n_max it is set to n_max.
...	Further optional arguments.

Details

The following methods are available for this class: [toer](#), [pow](#), [n_dist](#), [adjusted_alpha](#), and [n_fix](#). Check the design specific documentation for details.

For non-inferiority trials use the function [setupFarringtonManning](#).

Value

An object of class [ChiSquare](#).

Examples

```
design <- setupChiSquare(alpha = .025, beta = .2, r = 1, delta = 0.2,
  alternative = "greater")
```

FarringtonManning-class

Farrington Manning test

Description

This class implements a Farrington-Manning test for non-inferiority trials. A trial with binary outcomes in two groups T and C is assumed.

The function [setupFarringtonManning](#) creates an object of [FarringtonManning](#).

Usage

```
setupFarringtonManning(alpha, beta, r = 1, delta, delta_NI, n_max = Inf, ...)
```

Arguments

<code>alpha</code>	One-sided type I error rate.
<code>beta</code>	Type II error rate.
<code>r</code>	Allocation ratio between experimental and control group.
<code>delta</code>	Difference of effect size between alternative and null hypothesis.
<code>delta_NI</code>	Non-inferiority margin.
<code>n_max</code>	Maximal overall sample size. If the recalculated sample size is greater than <code>n_max</code> it is set to <code>n_max</code> .
<code>...</code>	Further optional arguments.

Details

The following methods are available for this class: [toer](#), [pow](#), [n_dist](#), [adjusted_alpha](#), and [n_fix](#). Check the design specific documentation for details.

Value

An object of class `FarringtonManning`.

Examples

```
design <- setupFarringtonManning(alpha = .025, beta = .2, r = 1, delta = 0,
delta_NI = .15)
```

n_dist

Distribution of the Sample Size

Description

Calculates the distribution of the total sample sizes of designs with blinded sample size recalculation for different values of the nuisance parameter or of n1.

Usage

```
n_dist(design, n1, nuisance, summary = TRUE, plot = FALSE, ...)
```

Arguments

design	object of class <code>TestStatistic</code> created by <code>setup</code>
n1	number of patients that are recruited before the sample size is recalculated
nuisance	nuisance parameter that is estimated at the interim analysis
summary	logical - is a summary of the sample size distribution desired? Otherwise, a vector with sample sizes is returned.
plot	Should a plot of the sample size distribution be drawn?
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

The method is implemented for the classes `Student`, `ChiSquare`, and `FarringtonManning`.

Value

Summary and/or plot of the sample size distribution for every nuisance parameter and every value of n1.

Examples

```
d <- setupStudent(alpha = .025, beta = .2, r = 1, delta = 3.5, delta_NI = 0,
alternative = "greater", n_max = 156)
n_dist(d, n1 = 20, nuisance = 5.5, summary = TRUE, plot = FALSE, seed = 2020)
```

 n_dist, ChiSquare-method

Distribution of the Sample Size

Description

Calculates the distribution of the total sample sizes of designs with blinded sample size recalculation for different values of the nuisance parameter or of n1.

Usage

```
## S4 method for signature 'ChiSquare'
n_dist(
  design,
  n1,
  nuisance,
  summary = TRUE,
  plot = FALSE,
  allocation = c("exact", "approximate"),
  ...
)
```

Arguments

design	Object of class ChiSquare created by setupChiSquare.
n1	Either the sample size of the first stage (if recalculation = TRUE or the total sample size (if recalculation = FALSE).
nuisance	Value of the nuisance parameter. For the Chi-Squared test this is the overall response rate.
summary	Logical. If TRUE (default) a summary of the sample size distribution is printed. If FALSE all sample sizes are printed.
plot	Should a plot of the sample size distribution be drawn?
allocation	Whether the allocation ratio should be preserved exactly (exact) or approximately (approximate or kf_approx). approximate uses the unrounded calculated sample size in the sample size recalculation, kf_approx rounds the sample size to the next integer.
...	Further optional arguments.

Details

Only sample sizes that occur with a probability of at least 0.01 considered.

The method is only vectorized in either nuisance or n1.

Value

Summary and/or plot of the sample size distribution for every nuisance parameter and every value of n1.

Examples

```
d <- setupChiSquare(alpha = 0.025, beta = 0.2, r = 1, delta = 0.2)
n_dist(d, n1 = 20, nuisance = 0.25, summary = TRUE, plot = FALSE)
```

n_dist,FarringtonManning-method

Distribution of the Sample Size

Description

Calculates the distribution of the total sample sizes of designs with blinded sample size recalculation for different values of the nuisance parameter or of n1.

Usage

```
## S4 method for signature 'FarringtonManning'
n_dist(
  design,
  n1,
  nuisance,
  summary,
  plot,
  allocation = c("exact", "approximate"),
  ...
)
```

Arguments

design	Object of class FarringtonManning created by setupFarringtonManning.
n1	Either the sample size of the first stage (if recalculation = TRUE or the total sample size (if recalculation = FALSE).
nuisance	Value of the nuisance parameter. For the Farrington-Manning test this is the overall response rate.
summary	Logical. If TRUE (default) a summary of the sample size distribution is printed. If FALSE all sample sizes are printed.
plot	Should a plot of the sample size distribution be drawn?
allocation	Whether the allocation ratio should be preserved exactly (exact) or approximately (approximate).
...	Further optional arguments.

Details

Only sample sizes that occur with a probability of at least 0.01 considered.

The method is only vectorized in either nuisance or n1.

Value

Summary and/or plot of the sample size distribution for each nuisance parameter and every value of n1.

Examples

```
d <- setupFarringtonManning(alpha = 0.025, beta = 0.2, r = 1, delta = 0, delta_NI = 0.25)
n_dist(d, n1 = 30, nuisance = 0.2, summary = TRUE, plot = FALSE)
```

n_dist,Student-method *Distribution of the Sample Size*

Description

Calculates the distribution of the total sample sizes of designs with blinded sample size recalculation for different values of the nuisance parameter or of n1.

Usage

```
## S4 method for signature 'Student'
n_dist(
  design,
  n1,
  nuisance,
  summary = TRUE,
  plot = FALSE,
  iters = 10000,
  seed = NULL,
  range = 0,
  allocation = c("approximate", "exact"),
  ...
)
```

Arguments

<code>design</code>	Object of class Student created by setupStudent.
<code>n1</code>	Either the sample size of the first stage (if recalculation = TRUE or the total sample size (if recalculation = FALSE).
<code>nuisance</code>	Value of the nuisance parameter. For the Student's t-test this is the variance.

summary	logical - is a summary of the sample size distribution desired? Otherwise, a vector with sample sizes is returned.
plot	Should a plot of the sample size distribution be drawn?
iters	Number of simulation iterations.
seed	Random seed for simulation.
range	this determines how far the plot whiskers extend out from the box. If range is positive, the whiskers extend to the most extreme data point which is no more than range times the interquartile range from the box. A value of zero causes the whiskers to extend to the data extremes.
allocation	Whether the allocation ratio should be preserved exactly (exact) or approximately (approximate).
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

Value

Summary and/or plot of the sample size distribution for every nuisance parameter and every value of n1.

Examples

```
d <- setupStudent(alpha = .025, beta = .2, r = 1, delta = 3.5, delta_NI = 0,
                  alternative = "greater", n_max = 156)
n_dist(d, n1 = 20, nuisance = 5.5, summary = TRUE, plot = FALSE, seed = 2020)
```

n_fix	<i>Fixed Sample Size</i>
-------	--------------------------

Description

Returns the sample size of a fixed design without sample size recalculation.

Usage

```
n_fix(design, nuisance, ...)
```

Arguments

design	test statistic object
nuisance	nuisance parameter
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

The method is implemented for the classes [Student](#), [ChiSquare](#), and [FarringtonManning](#).

Value

One value of the fixed sample size for every nuisance parameter and every value of n1.

Examples

```
d <- setupStudent(alpha = .025, beta = .2, r = 1, delta = 3.5, delta_NI = 0,
                 alternative = "greater", n_max = 156)
n_fix(design = d, nuisance = 5.5)
```

n_fix, ChiSquare-method

Fixed Sample Size

Description

Returns the sample size of a fixed design without sample size recalculation.

Usage

```
## S4 method for signature 'ChiSquare'
n_fix(
  design,
  nuisance,
  variance = c("heterogeneous", "homogeneous"),
  rounded = TRUE,
  ...
)
```

Arguments

design	Object of class ChiSquare created by setupChiSquare.
nuisance	Value of the nuisance parameter. For the Chi-Squared test this is the overall response rate.
variance	A character string indicating whether the "heterogenous" (default) or the "homogeneous" variance formula should be used.
rounded	Whether the calculated sample size should be rounded up such that the allocation ratio is preserved.
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

Value

One value of the fixed sample size for every nuisance parameter and every value of n1.

Examples

```
design1 <- setupChiSquare(alpha = 0.025, beta = 0.2, r = 1, delta = 0.2)
n_fix(design1, nuisance = c(0.2, 0.3))
```

n_fix,FarringtonManning-method
Fixed Sample Size

Description

Returns the sample size of a fixed design without sample size recalculation.

Usage

```
## S4 method for signature 'FarringtonManning'
n_fix(design, nuisance, rounded = TRUE, ...)
```

Arguments

design	Object of class FarringtonManning created by setupFarringtonManning.
nuisance	Value of the nuisance parameter. For the Farrington-Manning test this is the overall response rate.
rounded	Whether the calculated sample size should be rounded up such that the allocation ratio is preserved.
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

Value

One value of the fixed sample size for every nuisance parameter and every value of n1.

Examples

```
d <- setupFarringtonManning(alpha = 0.025, beta = 0.2, r = 1, delta = 0, delta_NI = 0.25)
n_fix(d, nuisance = 0.3)
```

`n_fix, Student-method` *Fixed Sample Size*

Description

Returns the sample size of a fixed design without sample size recalculation.

Usage

```
## S4 method for signature 'Student'
n_fix(design, nuisance, ...)
```

Arguments

<code>design</code>	test statistic object
<code>nuisance</code>	nuisance parameter
<code>...</code>	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

Value

One value of the fixed sample size for every nuisance parameter and every value of n1.

Examples

```
d <- setupStudent(alpha = .025, beta = .2, r = 1, delta = 3.5, delta_NI = 0,
                  alternative = "greater", n_max = 156)
n_fix(design = d, nuisance = 5.5)
```

`pow`

Power

Description

Calculates the power of designs with blinded sample size recalculation or of fixed designs for one or several values of the nuisance parameter.

Usage

```
pow(design, n1, nuisance, recalculation, ...)
```


Arguments

design	object of class TestStatistic created by setup
n1	number of patients that are recruited before the sample size is recalculated
nuisance	nuisance parameter that is estimated at the interim analysis
recalculation	Should the sample size be recalculated after n1 patients are recruited?
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

The method is implemented for the classes [Student](#), [ChiSquare](#), and [FarringtonManning](#).

Value

One power value for every nuisance parameter and every value of n1.

Examples

```
d <- setupStudent(alpha = .025, beta = .2, r = 1, delta = 3.5, delta_NI = 0,
                  alternative = "greater", n_max = 156)
pow(d, n1 = 20, nuisance = 5.5, recalculation = TRUE)
```

pow,ChiSquare-method *Power*

Description

Calculates the power of designs with blinded sample size recalculation or of fixed designs for one or several values of the nuisance parameter.

Usage

```
## S4 method for signature 'ChiSquare'
pow(
  design,
  n1,
  nuisance,
  recalculation,
  allocation = c("exact", "approximate", "kf_approx"),
  ...
)
```

Arguments

<code>design</code>	Object of class <code>ChiSquare</code> created by <code>setupChiSquare</code> .
<code>n1</code>	Either the sample size of the first stage (if <code>recalculation = TRUE</code>) or the total sample size (if <code>recalculation = FALSE</code>).
<code>nuisance</code>	Value of the nuisance parameter. For the Chi-Squared test this is the overall response rate.
<code>recalculation</code>	Should the sample size be recalculated after <code>n1</code> patients are recruited?
<code>allocation</code>	Whether the allocation ratio should be preserved exactly (<code>exact</code>) or approximately (<code>approximate</code> or <code>kf_approx</code>). <code>approximate</code> uses the unrounded calculated sample size in the sample size recalculation, <code>kf_approx</code> rounds the sample size to the next integer.
<code>...</code>	Further optional arguments.

Details

The method is only vectorized in either `nuisance` or `n1`.

Value

One power value for every nuisance parameter and every value of `n1`.

Examples

```
d <- setupChiSquare(alpha = 0.025, beta = 0.2, r = 1, delta = 0.2)
pow(d, n1 = 20, nuisance = c(0.2, 0.4), recalculation = TRUE)
```

`pow,FarringtonManning-method`
Power

Description

Calculates the power of designs with blinded sample size recalculation or of fixed designs for one or several values of the nuisance parameter.

Usage

```
## S4 method for signature 'FarringtonManning'
pow(
  design,
  n1,
  nuisance,
  recalculation,
  allocation = c("exact", "approximate"),
  ...
)
```

Arguments

design	Object of class FarringtonManning created by setupFarringtonManning.
n1	Either the sample size of the first stage (if recalculation = TRUE or the total sample size (if recalculation = FALSE).
nuisance	Value of the nuisance parameter. For the Farrington-Manning test this is the overall response rate.
recalculation	Should the sample size be recalculated after n1 patients are recruited?
allocation	Whether the allocation ratio should be preserved exactly (exact) or approximately (approximate).
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

Value

One power value for every nuisance parameter and every value of n1.

Examples

```
d <- setupFarringtonManning(alpha = 0.025, beta = 0.2, r = 1, delta = 0, delta_NI = 0.25)
pow(d, n1 = 30, nuisance = 0.4, allocation = "approximate", recalculation = TRUE)
```

pow,Student-method *Power*

Description

Calculates the power of designs with blinded sample size recalculation or of fixed designs for one or several values of the nuisance parameter.

Usage

```
## S4 method for signature 'Student'
pow(
  design,
  n1,
  nuisance,
  recalculation = TRUE,
  iters = 10000,
  seed = NULL,
  allocation = c("approximate", "exact"),
  ...
)
```

Arguments

design	Object of class Student created by setupStudent.
n1	Either the sample size of the first stage (if recalculation = TRUE or the total sample size (if recalculation = FALSE).
nuisance	Value of the nuisance parameter. For the Student's t-test this is the variance.
recalculation	Should the sample size be recalculated after n1 patients are recruited?
iters	Number of simulation iterations.
seed	Random seed for simulation.
allocation	Whether the allocation ratio should be preserved exactly (exact) or approximately (approximate).
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

Value

One power value for every nuisance parameter and every value of n1.

Examples

```
d <- setupStudent(alpha = .025, beta = .2, r = 1, delta = 3.5, delta_NI = 0,
                  alternative = "greater", n_max = 156)
pow(d, n1 = 20, nuisance = 5.5, recalculation = TRUE)
```

simulation

Simulate Rejection Probability and Sample Size for Student's t-Test

Description

This function simulates the probability that a test defined by [setupStudent](#) rejects the null hypothesis. Note that here the nuisance parameter nuisance is the variance of the outcome variable σ^2 .

Usage

```
simulation(
  design,
  n1,
  nuisance,
  recalculation = TRUE,
  delta_true,
  iters = 1000,
```

```

    seed = NULL,
    allocation = c("approximate", "exact"),
    ...
  )

```

Arguments

design	Object of class Student created by setupStudent.
n1	Either the sample size of the first stage (if recalculation = TRUE or the total sample size (if recalculation = FALSE).
nuisance	Value of the nuisance parameter. For the Student's t-test this is the variance.
recalculation	Should the sample size be recalculated after n1 patients are recruited?
delta_true	effect measure under which the rejection probabilities are computed
iters	Number of simulation iterations.
seed	Random seed for simulation.
allocation	Whether the allocation ratio should be preserved exactly (exact) or approximately (approximate).
...	Further optional arguments.

Details

The implementation follows the algorithm in Lu (2019): Distribution of the two-sample t-test statistic following blinded sample size re-estimation. *Pharmaceutical Statistics* 15: 208-215. Since Lu (2019) assumes negative non-inferiority margins, the non-inferiority margin of design is multiplied with -1 internally.

Value

Simulated rejection probabilities and sample sizes for each nuisance parameter.

Examples

```

d <- setupStudent(alpha = .025, beta = .2, r = 1, delta = 3.5, delta_NI = 0,
  alternative = "greater", n_max = 156)
simulation(d, n1 = 20, nuisance = 5.5, recalculation = TRUE, delta_true = 3.5)

```

Description

This class implements Student's t-test for superiority and non-inferiority tests. A trial with continuous outcomes of the two groups T and C is assumed. If `alternative == "greater"` the null hypothesis for the mean difference $\Delta = \mu_T - \mu_C$ is

$$H_0 : \Delta \leq -\delta_{NI} \text{ vs. } H_1 : \Delta > -\delta_{NI}.$$

Here, $\delta_{NI} \geq 0$ denotes the non-inferiority margin. For superiority trials, δ_{NI} can be set to zero (default). If `alternative == "smaller"`, the direction of the effect is changed.

The function `setupStudent` creates an object of class `Student` that can be used for sample size recalculation.

Usage

```
setupStudent(
  alpha,
  beta,
  r = 1,
  delta,
  delta_NI = 0,
  alternative = c("greater", "smaller"),
  n_max = Inf,
  ...
)
```

Arguments

<code>alpha</code>	One-sided type I error rate.
<code>beta</code>	Type II error rate.
<code>r</code>	Allocation ratio between experimental and control group.
<code>delta</code>	Difference of effect size between alternative and null hypothesis.
<code>delta_NI</code>	Non-inferiority margin.
<code>alternative</code>	Does the alternative hypothesis contain greater (greater) or smaller (smaller) values than the null hypothesis.
<code>n_max</code>	Maximal overall sample size. If the recalculated sample size is greater than <code>n_max</code> it is set to <code>n_max</code> .
<code>...</code>	Further optional arguments.

Details

The notation is based on the paper of Lu (2019): Distribution of the two-sample t-test statistic following blinded sample size re-estimation. *Pharmaceutical Statistics* 15: 208-215.

The following methods are available for this class: `toer`, `pow`, `n_dist`, `adjusted_alpha`, and `n_fix`. Check the design specific documentation for details.

Value

An object of class [Student](#).

Examples

```
d <- setupStudent(alpha = .025, beta = .2, r = 1, delta = 3.5, delta_NI = 0,
                 alternative = "greater", n_max = 156)
```

 toer

Type I Error Rate

Description

Computes the type I error rate of designs with blinded sample size recalculation or of fixed designs for one or several values of the nuisance parameter.

Usage

```
toer(design, n1, nuisance, recalculation, ...)
```

Arguments

design	object of class <code>TestStatistic</code> created by <code>setup</code>
n1	number of patients that are recruited before the sample size is recalculated
nuisance	nuisance parameter that is estimated at the interim analysis
recalculation	Should the sample size be recalculated after n1 patients are recruited?
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

The method is implemented for the classes [Student](#), [ChiSquare](#), and [FarringtonManning](#).

Value

One type I error rate value for every nuisance parameter and every value of n1.

Examples

```
d <- setupStudent(alpha = .025, beta = .2, r = 1, delta = 3.5, delta_NI = 0,
                 alternative = "greater", n_max = 156)
toer(d, n1 = 20, nuisance = 5.5, recalculation = TRUE)
```

toer,ChiSquare-method *Type I Error Rate*

Description

Computes the type I error rate of designs with blinded sample size recalculation or of fixed designs for one or several values of the nuisance parameter.

Usage

```
## S4 method for signature 'ChiSquare'
toer(
  design,
  n1,
  nuisance,
  recalculation,
  allocation = c("exact", "approximate", "kf_approx"),
  ...
)
```

Arguments

design	Object of class ChiSquare created by setupChiSquare.
n1	Either the sample size of the first stage (if recalculation = TRUE or the total sample size (if recalculation = FALSE).
nuisance	Value of the nuisance parameter. For the Chi-Squared test this is the overall response rate.
recalculation	Should the sample size be recalculated after n1 patients are recruited?
allocation	Whether the allocation ratio should be preserved exactly (exact) or approximately (approximate or kf_approx). approximate uses the unrounded calculated sample size in the sample size recalculation, kf_approx rounds the sample size to the next integer.
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

Value

One type I error rate value for every nuisance parameter and every value of n1.

Examples

```
d <- setupChiSquare(alpha = 0.025, beta = 0.2, r = 1, delta = 0.2)
toer(d, n1 = c(10, 20), nuisance = 0.25, recalculation = TRUE)
```

```
toer,FarringtonManning-method
      Type I Error Rate
```

Description

Computes the type I error rate of designs with blinded sample size recalculation or of fixed designs for one or several values of the nuisance parameter.

Usage

```
## S4 method for signature 'FarringtonManning'
toer(
  design,
  n1,
  nuisance,
  recalculation,
  allocation = c("exact", "approximate"),
  ...
)
```

Arguments

design	Object of class <code>FarringtonManning</code> created by <code>setupFarringtonManning</code> .
n1	Either the sample size of the first stage (if <code>recalculation = TRUE</code> or the total sample size (if <code>recalculation = FALSE</code>).
nuisance	Value of the nuisance parameter. For the Farrington-Manning test this is the overall response rate.
recalculation	Should the sample size be recalculated after <code>n1</code> patients are recruited?
allocation	Whether the allocation ratio should be preserved exactly (<code>exact</code>) or approximately (<code>approximate</code>).
...	Further optional arguments.

Details

The method is only vectorized in either `nuisance` or `n1`.

Value

One type I error rate value for every nuisance parameter and every value of `n1`.

Examples

```
d <- setupFarringtonManning(alpha = 0.025, beta = 0.2, r = 1, delta = 0, delta_NI = 0.2)
toer(d, n1 = 20, nuisance = 0.25, recalculation = TRUE, allocation = "approximate")
```

toer, Student-method *Type I Error Rate*

Description

Computes the type I error rate of designs with blinded sample size recalculation or of fixed designs for one or several values of the nuisance parameter.

Usage

```
## S4 method for signature 'Student'
toer(
  design,
  n1,
  nuisance,
  recalculation = TRUE,
  iters = 10000,
  seed = NULL,
  allocation = c("approximate", "exact"),
  ...
)
```

Arguments

design	Object of class Student created by setupStudent.
n1	Either the sample size of the first stage (if recalculation = TRUE or the total sample size (if recalculation = FALSE).
nuisance	Value of the nuisance parameter. For the Student's t-test this is the variance.
recalculation	Should the sample size be recalculated after n1 patients are recruited?
iters	Number of simulation iterations.
seed	Random seed for simulation.
allocation	Whether the allocation ratio should be preserved exactly (exact) or approximately (approximate).
...	Further optional arguments.

Details

The method is only vectorized in either nuisance or n1.

Value

One type I error rate value for every nuisance parameter and every value of n1.

Examples

```
d <- setupStudent(alpha = .025, beta = .2, r = 1, delta = 3.5, delta_NI = 0,  
                 alternative = "greater", n_max = 156)  
toer(d, n1 = 20, nuisance = 5.5, recalculation = TRUE)
```

Index

adjusted_alpha, [2](#), [8](#), [22](#)
adjusted_alpha, ChiSquare-method, [3](#)
adjusted_alpha, FarringtonManning-method, [4](#)
adjusted_alpha, Student-method, [6](#)

blindrecalc, [7](#)

ChiSquare, [3](#), [7–9](#), [14](#), [17](#), [23](#)
ChiSquare (ChiSquare-class), [7](#)
ChiSquare-class, [7](#)

FarringtonManning, [3](#), [8](#), [9](#), [14](#), [17](#), [23](#)
FarringtonManning
 (FarringtonManning-class), [8](#)
FarringtonManning-class, [8](#)

n_dist, [8](#), [9](#), [22](#)
n_dist, ChiSquare-method, [10](#)
n_dist, FarringtonManning-method, [11](#)
n_dist, Student-method, [12](#)
n_fix, [8](#), [13](#), [22](#)
n_fix, ChiSquare-method, [14](#)
n_fix, FarringtonManning-method, [15](#)
n_fix, Student-method, [16](#)

pow, [8](#), [16](#), [22](#)
pow, ChiSquare-method, [17](#)
pow, FarringtonManning-method, [18](#)
pow, Student-method, [19](#)

setupChiSquare (ChiSquare-class), [7](#)
setupFarringtonManning, [8](#)
setupFarringtonManning
 (FarringtonManning-class), [8](#)
setupStudent, [20](#)
setupStudent (Student-class), [21](#)
simulation, [20](#)
Student, [3](#), [9](#), [14](#), [17](#), [22](#), [23](#)
Student (Student-class), [21](#)
Student-class, [21](#)

toer, [8](#), [22](#), [23](#)
toer, ChiSquare-method, [24](#)
toer, FarringtonManning-method, [25](#)
toer, Student-method, [26](#)