

Package ‘blob’

January 20, 2020

Title A Simple S3 Class for Representing Vectors of Binary Data
(‘BLOBS’)

Version 1.2.1

Description R’s raw vector is useful for storing a single binary object. What if you want to put a vector of them in a data frame? The ‘blob’ package provides the blob object, a list of raw vectors, suitable for use as a column in data frame.

License GPL-3

URL <https://github.com/tidyverse/blob>

BugReports <https://github.com/tidyverse/blob/issues>

Imports methods, rlang, vctrs (>= 0.2.1)

Suggests covr, crayon, pillar (>= 1.2.1), testthat

Encoding UTF-8

LazyData true

RoxygenNote 7.0.2

NeedsCompilation no

Author Hadley Wickham [aut],
Kirill Müller [cre],
RStudio [cph]

Maintainer Kirill Müller <kr1mlr+r@mailbox.org>

Repository CRAN

Date/Publication 2020-01-20 22:50:02 UTC

R topics documented:

blob	2
vec_ptype2.blob	3
Index	4

blob*Construct a blob object*

Description

`new_blob()` is a low-level constructor that takes a list of raw vectors. `blob()` constructs a blob from individual raw vectors. `as_blob()` and `is_blob()` are simple forwarders to `vctrs::vec_cast()` and `inherits()`, respectively.

Usage

```
blob(...)
```

```
new_blob(x = list())
```

```
validate_blob(x)
```

```
as_blob(x)
```

```
is_blob(x)
```

Arguments

... Individual raw vectors

x A list of raw vectors, or other object to coerce

See Also

[as.blob\(\)](#) for the legacy interface for specifying casts.

Examples

```
x1 <- charToRaw("Good morning")
x2 <- as.raw(c(0x48, 0x65, 0x6c, 0x6c, 0x6f))

new_blob(list(x1, x2))
blob(x1, x2)

as.blob(c("Good morning", "Good evening"))
```

vec_ptype2.blob	<i>Coercion</i>
-----------------	-----------------

Description

Double dispatch methods to support `vctrs::vec_ptype2()`.

Usage

```
## S3 method for class 'blob'  
vec_ptype2(x, y, ..., x_arg = "", y_arg = "")
```

Arguments

x	Vector types.
y	Vector types.
...	These dots are for future extensions and must be empty.
x_arg	Argument names for x and y. These are used in error messages to inform the user about the locations of incompatible types (see stop_incompatible_type()).
y_arg	Argument names for x and y. These are used in error messages to inform the user about the locations of incompatible types (see stop_incompatible_type()).

Index

`as.blob()`, 2
`as_blob(blob)`, 2

`blob`, 2

`inherits()`, 2
`is_blob(blob)`, 2

`new_blob(blob)`, 2

`stop_incompatible_type()`, 3

`validate_blob(blob)`, 2
`vctrs::vec_cast()`, 2
`vctrs::vec_ptype2()`, 3
`vec_ptype2.blob`, 3