

Package ‘broman’

May 22, 2020

Version 0.70-4

Date 2020-05-21

Title Karl Broman's R Code

Description Miscellaneous R functions, including functions related to graphics (mostly for base graphics), permutation tests, running mean/median, and general utilities.

Author Karl W Broman [aut, cre] (<<https://orcid.org/0000-0002-4914-6671>>),
Aimee Teo Broman [ctb] (<<https://orcid.org/0003-3783-2807>>)

Maintainer Karl W Broman <broman@wisc.edu>

Depends R (>= 2.15.0)

Imports utils, graphics, grDevices, stats, assertthat, RPushbullet,
jsonlite, ggplot2, grid

Suggests testthat, devtools, roxygen2

License GPL-3

URL <https://github.com/kbroman/broman>

BugReports <https://github.com/kbroman/broman/issues>

Encoding UTF-8

ByteCompile true

LazyData true

RoxygenNote 7.1.0

NeedsCompilation yes

Repository CRAN

Date/Publication 2020-05-22 04:30:02 UTC

R topics documented:

add_commas	3
align_vectors	4
arrowlocator	4

attrnames	5
brocolors	6
bromanversion	7
cf	8
chisq	9
ciplot	10
colwalpha	11
compare_rows	12
convert2hex	12
crayons	13
done	14
dotplot	14
errors2pushbullet	15
excel_fig	16
exit	17
fac2num	18
fisher	18
get_precision	19
grayplot	20
grayplot_na	21
h	23
hex2dec	24
histlines	25
jiggle	26
kbdate	27
lenuniq	27
make	28
manyboxplot	29
maxabs	30
mypairs	30
myround	31
normalize	32
note	33
numbers	33
objectsizes	34
openfile	34
paired.perm.test	35
paste.	36
paste00	37
perm.test	38
pick_more_precise	39
plot_crayons	39
pushbullet_devices	40
qqline2	41
qr2	42
quantileSE	42
revgray	43
revrainbow	44

rmvn	45
runningmean	45
runningratio	47
setRNGparallel	48
simp	48
spell_out	49
stop_sending_errors	50
strwidth2lines	50
strwidth2xlim	51
switchv	52
theme_karl	53
triarrow	53
trigrid	54
trilines	55
triplot	56
tripoints	57
tritext	58
twocolorpal	59
vec2string	60
venn	60
winsorize	61
xlimlabel	62
%nin%	63

Index**64**

add_commas	<i>Add commas to a large number</i>
------------	-------------------------------------

Description

Convert a number to a string, with commas every 3rd digit

Usage

```
add_commas(numbers)
```

Arguments

numbers Vector of non-negative numbers (will be rounded to integers)

Value

Character string with numbers written like "7,547,085".

Examples

```
add_commas(c(231, 91310, 2123, 9911001020, 999723285))
```

align_vectors *Align two vectors*

Description

Align two vectors using their names attributes, either expanding with NAs or reducing to the common values.

Usage

```
align_vectors(x, y, expand = TRUE)
```

Arguments

x	A vector
y	Another vector
expand	If TRUE, expand each to the same length using NAs. If FALSE, remove elements not in common.

Value

A list with two components, x and y

arrowlocator *Use the locator function to plot an arrow*

Description

Use the [graphics::locator\(\)](#) function to indicate the endpoints of an arrow and then plot it.

Usage

```
arrowlocator(
  reverse = FALSE,
  horizontal = FALSE,
  vertical = FALSE,
  length = 0.1,
  ...
)
```

Arguments

reverse	If FALSE, first indicate the tail of the arrow and then the head; if TRUE, first indicate the head of the arrow and then the tail.
horizontal	If TRUE, force the arrow to be horizontal. (Use the average y-axis value of the two clicks for the vertical placement.)
vertical	If TRUE, force the arrow to be vertical. (Use the average x-axis value of the two clicks for the horizontal placement.)
length	Length of the edges of the arrow head.
...	Additional graphics parameters

Details

Use [graphics::locator\(\)](#) to indicate the two endpoints of an arrow and then draw it.

Value

The locations of the endpoints of the arrow, as a two-row matrix. The first row indicates the location of the tail of the arrow; the second row indicates the location of the head of the arrow.

See Also

[graphics::arrows\(\)](#), [graphics::locator\(\)](#)

Examples

```
## Not run:  
plot(0,0,type="n", xlab="", ylab="", xlim=c(0,100), ylim=c(0,100))  
arrowlocator(col="blue", lwd=2)  
  
## End(Not run)
```

Description

Get the names of the attributes of an object

Usage

```
attrnames(object)
```

Arguments

object	Any object
--------	------------

Details

It just does `names(attributes(object))`.

Value

Vector of character strings with the names of the attributes.

Examples

```
x <- matrix(1:100, ncol=5)
colnames(x) <- LETTERS[1:5]
attrnames(x)
```

brocolors

Vectors of colors for figures

Description

Creates different vectors of related colors that may be useful for figures.

Usage

```
brocolors(
  set = c("general", "general2", "bg", "bgpng", "CC", "CCalt", "f2", "sex", "main",
  "crayons", "web")
)
```

Arguments

set Character string indicating a set of colors.

Value

Vector of character strings representing the chosen set of colors, in RGB.

See Also

[plot_crayons\(\)](#)

Examples

```
par(mar=c(0.6,5.1,0.6,0.6))
plot(0, 0, type="n", xlab="", ylab="", xlim=c(0, 9), ylim=c(8.5, 0), yaxs="i",
      xaxt="n", yaxt="n", xaxs="i")
axis(side=2, at=1:8, c("general", "general2", "bg", "bgpng", "CC", "f2", "sex", "main"), las=1)

gen <- brocolors("general")
points(seq(along=gen), rep(1,length(gen)), pch=21, bg=gen, cex=4)
text(seq(along=gen), rep(c(0.55, 0.7), length(gen))[seq(along=gen)], names(gen))
```

```
gen2 <- brocolors("general2")
points(seq(along=gen2), rep(2,length(gen2)), pch=21, bg=gen2, cex=4)
text(seq(along=gen2), rep(1+c(0.55, 0.7), length(gen2))[seq(along=gen2)], names(gen2))

points(1, 3, pch=21, bg=brocolors("bg"), cex=4)
points(1, 4, pch=21, bg=brocolors("bgpng"), cex=4)

CC <- brocolors("CC")
points(seq(along=CC), rep(5,length(CC)), pch=21, bg=CC, cex=4)
text(seq(along=CC), rep(4+c(0.55, 0.7), length(CC))[seq(along=CC)], names(CC))

f2 <- brocolors("f2")
points(seq(along=f2), rep(6,length(f2)), pch=21, bg=f2, cex=4)
text(seq(along=f2), rep(5.7, length(f2)), names(f2))

sex <- brocolors("sex")
points(seq(along=sex), rep(7,length(sex)), pch=21, bg=sex, cex=4)
text(seq(along=sex), rep(6.7, length(sex)), names(sex))

points(1, 8, pch=21, bg=brocolors("main"), cex=4)
```

bromanversion

Installed version of R/broman

Description

Print the version number of the currently installed version of R/broman.

Usage

```
bromanversion()
```

Value

A character string with the version number of the currently installed version of R/broman.

Examples

```
bromanversion()
```

cf

Compare objects, including missing data pattern

Description

Check whether two objects are the same, including their patterns of NAs.

Usage

```
cf(a, b)
```

Arguments

- | | |
|---|----------------|
| a | Some object. |
| b | Another object |

Details

It's not very complicated: `((is.na(a) & is.na(b)) | (!is.na(a) & !is.na(b) & a == b))`

Value

Boolean object with TRUE indicating an element is the same.

Examples

```
x <- c(5, 8, 9, NA, 3, NA)
y <- c(5, 2, 9, 4, NA, NA)
cf(x,y)

x <- matrix(rnorm(1000), ncol=20)
x[sample(seq(along=x), 100)] <- NA
all(cf(x,x))
dim(cf(x,x))

y <- x
y[4,8] <- NA
sum(!cf(x,y))
y[6,2] <- 18
sum(!cf(x,y))
y[6,5] <- 32
sum(!cf(x,y))

x <- as.data.frame(x)
y <- as.data.frame(y)
sum(!cf(x,y))

x <- as.list(x)
y <- as.list(y)
```

```
sapply(cf(x,y), function(a) sum(!a))
```

chisq*Chi-square test by simulation for a two-way table*

Description

Calculate a p-value for a chi-square test by Monte Carlo simulation.

Usage

```
chisq(tab, n.sim = 1000)
```

Arguments

- | | |
|-------|---|
| tab | A matrix of counts. |
| n.sim | Number of samples of permuted tables to consider. |

Details

This is like the function [stats:::chisq.test\(\)](#), but calculates an approximate P-value rather than referring to asymptotics. This will be better for large, sparse tables.

Value

A single number: the P-value testing independence of rows and columns in the table.

See Also

[stats:::chisq.test\(\)](#), [stats:::fisher.test\(\)](#), [fisher\(\)](#)

Examples

```
TeaTasting <- matrix(c(3,1,1,3), nrow=2)
chisq(TeaTasting, 1000)
```

ciplot*Effect plot with multiple CIs for different groups*

Description

Uses [grayplot\(\)](#) to plot a set of confidence intervals.

Usage

```
ciplot(
  est,
  se = NULL,
  lo = NULL,
  hi = NULL,
  SEmult = 2,
  labels = NULL,
  rotate = FALSE,
  ...
)
```

Arguments

<code>est</code>	Vector of estimates
<code>se</code>	Vector of standard errors
<code>lo</code>	Vector of lower values for the intervals
<code>hi</code>	Vector of upper values for the intervals
<code>SEmult</code>	SE multiplier to create intervals
<code>labels</code>	Labels for the groups (vector of character strings)
<code>rotate</code>	If TRUE, have group as y-axis; default (FALSE) has group on x-axis.
<code>...</code>	Optional graphics arguments

Details

Calls [grayplot\(\)](#) with special choices of graphics parameters, as in [dotplot\(\)](#).

Provide either `se` or both `lo` and `hi`. In the case that `se` is used, the intervals will be `est +/- SEmult * se`.

If `labels` is not provided, group names are taken from the `names(est)`. If that is also missing, we use capital letters.

You can control the CI line widths with `ci_lwd` and the color of the CI segments with `ci_col`. You can control the width of the segments at the top and bottom with `ci_endseg`.

Value

None.

See Also

[grayplot\(\)](#), [dotplot\(\)](#)

Examples

```
x <- rnorm(40, c(1,3))
g <- rep(c("A", "B"), 20)
me <- tapply(x, g, mean)
se <- tapply(x, g, function(a) sd(a)/sqrt(sum(!is.na(a))))
ciplot(me, se) # default is +/- 2 SE
ciplot(me, se, SEmult=1)
ciplot(me, se, rotate=TRUE)
lo <- me - 2*se
hi <- me + 2*se
ciplot(me, lo=lo, hi=hi)
```

colwalpha

Convert a color to use alpha transparency

Description

Convert a color to RGB and then to RGB with alpha transparency

Usage

```
colwalpha(color, alpha = 1)
```

Arguments

color	A character string for a color
alpha	Transparency value (between 0 and 1)

Value

A character string representing a color

Examples

```
colwalpha(c("blue", "red"), 0.5)
```

compare_rows

Compare rows in a matrix

Description

For all pairs of rows in a matrix, calculate the proportion of mismatches or the RMS difference.

Usage

```
compare_rows(mat, method = c("prop_mismatches", "rms_difference"))
```

Arguments

- | | |
|--------|---|
| mat | Numeric matrix. Should be integers in the case <code>method="prop_mismatches"</code> . |
| method | Indicates whether to use proportion mismatches or the RMS difference. Missing values are omitted. |

Value

A square matrix of dimension `nrow(mat)` with NAs on the diagonal and the calculated statistic in the body.

Examples

```
n <- 10
p <- 200
x <- matrix(sample(1:4, n*p, replace=TRUE), ncol=p)
d <- compare_rows(x)
```

convert2hex

Convert decimal to hex

Description

Convert a number to hexadecimal notation.

Usage

```
convert2hex(d)
```

Arguments

- | | |
|---|-----------|
| d | A number. |
|---|-----------|

Details

Nothing important to say here.

Value

A character string; the input in hex.

See Also

[hex2dec\(\)](#)

Examples

```
convert2hex(333)
dec2hex(333)
dec2hex(333) == "14D"
dec2hex(0:30)
```

crayons

Crayon colors

Description

Vector of colors corresponding to Crayola crayons

Usage

```
crayons(color_names = NULL, ...)
```

Arguments

color_names	Optional vector of color names; can be partial matches.
...	Additional optional color names

Value

Vector of named RGB colors

References

https://en.wikipedia.org/wiki/List_of_Crayola_crayon_colors

See Also

[plot_crayons\(\)](#), [brocolors\(\)](#)

done	<i>Send a short message via RPushbullet.</i>
------	--

Description

Send a short message via RPushbullet, to be used to indicate that some R job is complete.

Usage

```
done(message = "R is done", recipients = NULL)
```

Arguments

message	A character string with a message. (passed to RPushbullet::pbPost() .)
recipients	A character or numeric vector indicating the devices this post should go to. If NULL, the default device is looked up from an optional setting, and if none has been set the push is sent to all devices. (passed to RPushbullet::pbPost() .)

See Also

[errors2pushbullet\(\)](#), [note\(\)](#), [pushbullet_devices\(\)](#)

Examples

```
## Not run: done("Your R job is complete.")
```

dotplot	<i>Dot chart with a gray background</i>
---------	---

Description

Like the [grayplot\(\)](#) function, but with one axis assumed to be categorical.

Usage

```
dotplot(group, y, jiggle = NULL, rotate = FALSE, ...)
```

Arguments

group	Categorical coordinates for the plot
y	Coordinates of points in the plot
jiggle	Vector of amounts to jiggle the points horizontally, or a character string ("fixed" or "random") indicating the jiggling method; see jiggle() .
rotate	If TRUE, have group as y-axis; default (FALSE) has group on x-axis.
...	Optional graphics arguments

Details

Calls [grayplot\(\)](#) with special choices of graphics parameters for the case of categorical x.
 If group is a factor, the order of the groups is as in the levels. Otherwise, we take sort(unique(group)).
 So if you want to control the order of the levels, make group a factor with the levels in the desired order, for example group <-factor(group, levels=unique(group)).

Value

None.

See Also

[grayplot\(\)](#)

Examples

```
x <- rnorm(40, c(1,3))
g <- rep(c("A", "B"), 20)
dotplot(g, x)
dotplot(g, x, "random")
dotplot(g, x, runif(length(g), -0.25, 0.25))
```

errors2pushbullet *Send further errors to pushbullet*

Description

Set options to use RPpushbullet to use pushbullet to push notifications of any error messages.

Usage

```
errors2pushbullet(recipients = NULL)
```

Arguments

recipients	A character or numeric vector indicating the devices this post should go to. If NULL, the default device is looked up from an optional setting, and if none has been set the push is sent to all devices. (passed to RPpushbullet::pbPost() .)
------------	--

See Also

[stop_sending_errors\(\)](#), [note\(\)](#), [done\(\)](#), [pushbullet_devices\(\)](#)

Examples

```
## Not run: errors2pushbullet()
```

excel_fig*Excel-style figure displaying contents of a matrix*

Description

Turn a matrix of data into an SVG of how it might look in Excel

Usage

```
excel_fig(
  mat,
  file = NULL,
  cellwidth = 80,
  cellheight = 26,
  textsize = 16,
  fig_width = NULL,
  fig_height = NULL,
  border = "#CECECE",
  headcol = "#E9E9E9",
  headborder = "#969696",
  headtextcol = "#626262",
  textcol = "black",
  row_names = FALSE,
  col_names = TRUE,
  hilitcells = NULL,
  hilitcolor = "#F0DCDB",
  lwd = 1,
  direct2svg = FALSE,
  mar = rep(0.1, 4)
)
```

Arguments

mat	A matrix
file	Optional file name (must have extension .svg, .png, .jpg, or .pdf)
cellwidth	Width of each cell, in pixels
cellheight	Height of each cell, in pixels
textsize	Size for text (if file is provided or direct2svg=TRUE)
fig_width	Width of figure, in pixels (if NULL, taken from cellwidth); ignored when direct2svg=FALSE
fig_height	Height of figure, in pixels (if NULL, taken from cellheight); ignored when direct2svg=FALSE
border	Color of border of cells for the body of the matrix
headcol	Background color of cells on the top and left border

headborder	Color of border of cells on the top and left border
headtextcol	Color of text in cells on the top and left border
textcol	Color of text in cells in body of the matrix
row_names	If TRUE, and row names are present, include them as a first column
col_names	If TRUE, and column names are present, include them as a first row
hilitcells	Optional character vector of cells to highlight, like "A1" or "D4"
hilitcolor	Color to highlight cells, a vector of length 1 or the same length as hilitcells
lwd	Line width for rectangles
direct2svg	If TRUE, rather than R graphics, just print an SVG directly with <code>base:::cat()</code> .
mar	Plot margins, passed to <code>graphics:::par()</code> .

Examples

```
df <- data.frame(id=    c(101,  102,  103),
                  sex=    c("M",    "F",    "M"),
                  weight=c(22.3, 15.8, 19.7),
                  stringsAsFactors=FALSE)
excel_fig(df, col_names=TRUE)
```

exit

exit R without saving

Description

exit R without saving workspace.

Usage

```
exit()
```

Details

This just calls `q("no")`

Value

None.

fac2num	<i>Convert a factor to numeric</i>
---------	------------------------------------

Description

Convert a factor with numeric levels to a non-factor

Usage

```
fac2num(x)
```

Arguments

x	A vector containing a factor with numeric levels
---	--

Value

The input factor made a numeric vector

Examples

```
x <- factor(c(3, 4, 9, 4, 9), levels=c(3,4,9))
fac2num(x)
```

fisher	<i>Fisher's exact test for a two-way table</i>
--------	--

Description

Performs a sampling version of Fisher's exact test for a two-way contingency table.

Usage

```
fisher(tab, n.sim = 1000)
```

Arguments

tab	A matrix of counts.
n.sim	Number of samples of permuted tables to consider.

Details

This is like the function `stats::fisher.test()`, but calculates an approximate P-value rather than performing a complete enumeration. This will be better for large, sparse tables.

Value

A single number: the P-value testing independence of rows and columns in the table.

See Also

`stats::chisq.test()`, `stats::fisher.test()`, `chisq()`

Examples

```
TeaTasting <- matrix(c(3,1,1,3), nrow=2)
fisher(TeaTasting, 1000)
```

get_precision *Determine the precision of a number*

Description

Determine the precision of a number, as the number of digits past the decimal point.

Usage

```
get_precision(x, ...)
```

Arguments

x A numeric vector

... Ignore this

Details

If the number is expressed in scientific notation, we take the number of digits

Value

A vector of integers, with the number of digits (to the last non-zero digit) past the decimal point.

grayplot*Scatterplot with a gray background***Description**

Like the plot function, but using a gray background just for the plot region.

Usage

```
grayplot(
  x,
  y = NULL,
  ...,
  type = "p",
  hlines = NULL,
  hlines.col = "white",
  hlines.lty = 1,
  hlines.lwd = 1,
  vlines = NULL,
  vlines.col = "white",
  vlines.lty = 1,
  vlines.lwd = 1,
  xat = NULL,
  yat = NULL,
  bgcolor = "gray90",
  pch = 21,
  bg = "lightblue",
  col = "black",
  v_over_h = FALSE
)
```

Arguments

<code>x</code>	Coordinates of points in the plot
<code>y</code>	Coordinates of points in the plot (optional)
<code>...</code>	Optional graphics arguments
<code>type</code>	Plot type (points, lines, etc.)
<code>hlines</code>	Locations of horizontal grid lines; use <code>hlines=NA</code> to prevent horizontal grid lines
<code>hlines.col</code>	Colors of horizontal grid lines
<code>hlines.lty</code>	Line type of horizontal grid lines
<code>hlines.lwd</code>	Line width of horizontal grid lines
<code>vlines</code>	Locations of vertical grid lines; use <code>vlines=NA</code> to prevent vertical grid lines
<code>vlines.col</code>	Colors of vertical grid lines

vlines.lty	Line type of vertical grid lines
vlines.lwd	Line width of vertical grid lines
xat	Locations for x-axis labels; xat=NA indicates no labels
yat	Locations for y-axis labels; yat=NA indicates no labels
bgcolor	Background color
pch	point type
bg	Background color in points
col	Color of outer circle in points
v_over_h	If TRUE, place vertical grid lines on top of the horizontal ones.

Details

Calls [graphics::plot\(\)](#) with type="n", then [graphics::rect\(\)](#) to get the background, and then [graphics::points\(\)](#). Additional arguments you can include: mgp.x and mgp.y (like mgp, for controlling parameters of axis labels, but separate for x- and y-axis).

Value

None.

See Also

[graphics::plot\(\)](#), [graphics::par\(\)](#), [graphics::rect\(\)](#), [graphics::points\(\)](#)

Examples

```
x <- rnorm(100)
y <- x+rnorm(100, 0, 0.7)
grayplot(x, y, col="slateblue", pch=16)
at <- seq(-3, 3)
grayplot(x, y, col="violetred", pch=16, hlines=at, vlines=at)
grayplot(x, col="Orchid", pch=16, bgcolor="gray80",
         hlines=seq(-4, 4, by=0.5), hlines.lwd=c(3,1),
         vlines=seq(0, 100, by=5), vlines.lwd=c(3,1,1,1))
```

Description

Scatterplot with a gray background and with points with missing values shown in separate panels near the margins.

Usage

```
grayplot_na(
  x,
  y = NULL,
  type = "p",
  bgcolor = "gray90",
  v_over_h = FALSE,
  pch = 21,
  bg = "lightblue",
  col = "black",
  force = c("none", "x", "y", "both"),
  ...
)
```

Arguments

x	Coordinates of points in the plot
y	Coordinates of points in the plot (optional)
type	Plot type (points, lines, etc.)
bgcolor	Background color
v_over_h	If TRUE, place vertical grid lines on top of the horizontal ones.
pch	point type
bg	Background color in points
col	Color of outer circle in points
force	Indicates whether to force the NA box (on the x-axis, y-axis, or both) even when there are no missing values.
...	Optional graphics arguments

Details

Calls `graphics::plot()` with ‘type="n"’, then `graphics::rect()` to get the background, and then `graphics::points()`.

There are a bunch of hidden graphical arguments you can include: `na.width` controls the proportional width devoted to the NA boxes, and `na.gap` the proportion for the gap between the NA boxes and the main plot region. `mgp.x` and `mgp.y` (like `mgp`, for controlling parameters of axis labels, but separate for x- and y-axis). Also `hlines` to indicate locations of of horizontal gridlines, and `hlines.col`, `hlines.lwd`, and `hlines.lty` to set their color, width, and type. `hlines=NA` suppresses the grid lines. Similarly `vlines`, `vlines.col`, `vlines.lwd`, and `vlines.lty`. `xat` and `yat` are for specifying the locations of x- and y-axis labels, respectively. `xat=NA` and `yat=NA` indicate no labels.

Value

None.

See Also

[grayplot\(\)](#), [dotplot\(\)](#)

Examples

```
n <- 100
x <- rnorm(n)
y <- x+rnorm(n, 0, 0.7)
x[sample(n, 10)] <- NA

grayplot_na(x, y)

grayplot_na(x, y, force="y")

y[sample(n, 10)] <- NA
grayplot_na(x, y)
```

h

View html version of help file

Description

View the html version of a help file while running R via ESS within emacs.

Usage

`h(...)`

Arguments

... Help topics.

Details

This just calls the function [utils::help\(\)](#) using the argument `htmlhelp=TRUE`.

Value

No return value.

See Also

[utils::help\(\)](#), [utils::help.start\(\)](#)

Examples

`h(read.cross)`

hex2dec	<i>Convert from hex to decimal</i>
---------	------------------------------------

Description

Convert a number from hexidecimal to decimal notation.

Usage

`hex2dec(h)`

Arguments

`h` #’ Character string with hexadecimal representation of a number

Details

Nothing important to say here.

Value

The input converted from hexadeciml to decimal notation.

Author(s)

Karl W Broman, <broman@wisc.edu>

See Also

[dec2hex\(\)](#)

Examples

```
hex2dec("14D")
hex2dec("14D") == 333
hex2dec(0:30)
```

histlines	<i>Utility to create line-based histogram</i>
-----------	---

Description

Utility function to plot histogram with [graphics::lines\(\)](#).

Usage

```
histlines(x, y = NULL, breaks, use = c("counts", "density"))
```

Arguments

x	Either vector of breaks or the data itself.
y	Optional vector of density/counts, with length = length(x)-1.
breaks	Breaks for histogram, if y is not provided.
use	Whether to use counts or density, if y is not provided.

Details

If x and y are both provided, x is interpreted to be the breaks for a histogram, and y is a vector of counts or density values for each interval. These are then revised so that they may be plotted with [graphics::lines\(\)](#). If y is NULL, x is taken to be the data. In this case [graphics::hist\(\)](#) is called with breaks=breaks, and either the counts or density are used as y.

Value

A data.frame with two columns: x and y.

See Also

[graphics::hist\(\)](#), [graphics::lines\(\)](#)

Examples

```
x <- rnorm(1000, mean=20, sd=5)
# basic use
out <- hist(x, breaks=60, plot=FALSE)
plot(histlines(out$breaks, out$counts),
     type="l", lwd=2, xlab="x", ylab="counts", las=1)
# alternative use
plot(histlines(x, breaks=60, use="density"),
     type="l", lwd=2, xlab="x", ylab="Density", las=1)
# comparing two distributions
z <- rnorm(1000, mean=25, sd=5)
br <- seq(min(c(x,z)), max(c(x,z)), len=50)
xlines <- histlines(x, breaks=br, use="density")
zlines <- histlines(z, breaks=br, use="density")
```

```

ymx <- max(c(xlines$y, zlines$y))*1.05
plot(xlines, ylim=c(0, ymx), yaxs="i", xaxs="i",
      type="l", lwd=2, xlab="x", ylab="Density", las=1,
      col="blue")
lines(zlines, lwd=2 , col="red")

```

jiggle*Jiggle points horizontally*

Description

Spread points out horizontally so that, in dot plot of quantitative response in multiple categories, the separate points can be seen.

Usage

```
jiggle(group, y, method = c("fixed", "random"), hnum = 35, vnum = 40)
```

Arguments

group	Categorical variable defining group; can be a factor, character, or numeric vector
y	Vector of quantitative responses
method	What method to use for horizontal jiggling.
hnum	Number of horizontal bins for the jiggling.
vnum	Number of vertical bins for the jiggling.

Details

The "random" method is similar to [base:::jitter\(\)](#) but with amount of jiggling proportional to the number of nearby points. The "fixed" method is similar to the [beeswarm package](#)

Value

Numeric vector with amounts to jiggle the points horizontally

See Also

[base:::jitter\(\)](#), [dotplot\(\)](#)

kbdate*My little date facility*

Description

Sys.Date as a string, in a few different formats

Usage

```
kbdate(format = c("dateonly", "standard"), date = Sys.time())
```

Arguments

format	The format for the output
date	The date/time to convert

Value

A character string representation of the date/time

See Also

[base::Sys.time\(\)](#), [base::date\(\)](#)

Examples

```
kbdate()  
kbdate("standard")
```

lenuniq*Number of unique values*

Description

Get the number of unique values in a vector

Usage

```
lenuniq(vec, na.rm = TRUE)
```

Arguments

vec	A vector
na.rm	If TRUE, remove any missing values

Details

It just does `length(unique(vec))` or, if `na.rm=TRUE` (the default) `length(unique(vec[!is.na(vec)]))`

Value

Number of unique values.

Examples

```
x <- c(1, 2, 1, 3, 1, 1, 2, 2, 3, NA, NA, 1)
lenuniq(x)
lenuniq(x, na.rm=FALSE)
```

make

Run make within a package directory

Description

Run make within a package directory

Usage

```
make(pkg = ".", makefile = "Makefile", target = "", quiet = FALSE)
```

Arguments

<code>pkg</code>	Path to directory containing the GNU Make file, or an Rpackage description, which can be a path or a package name. (See devtools::as.package() for more information.)
<code>makefile</code>	File name of makefile.
<code>target</code>	Optional character string specifying the target.
<code>quiet</code>	If TRUE suppresses output from this function.

Value

Exit value from [base::system\(\)](#) with `intern=FALSE`

See Also

[devtools::load_all\(\)](#)

Examples

```
## Not run: make() # run make within working directory
make("/path/to/mypackage") # run make within /path/to/mypackage

## End(Not run)
```

manyboxplot*Boxplot-like figure for many groups*

Description

Boxplot-like figure for many groups, with lines connecting selected quantiles.

Usage

```
manyboxplot(
  x,
  probs = c(0.05, 0.1, 0.25),
  dotcol = "blue",
  linecol = c("black", "red", "green", "orange"),
  ...
)
```

Arguments

<code>x</code>	Matrix of data, with columns indicating the groups.
<code>probs</code>	Numeric vecotr of probabilities with values in [0,1). Quantiles will be symmetric, and the median will always be included.
<code>dotcol</code>	Color for median
<code>linecol</code>	Line colors, same length as <code>probs</code>
<code>...</code>	Additional graphics parameters

Details

Calculates quantiles of the columns of `x` and then plots dots or lines at median plus lines at a series of quantiles, using [grayplot\(\)](#) for the actual plot.

Value

None.

See Also

[grayplot\(\)](#)

Examples

```
mu <- c(rnorm(50, 0, 0.3), rnorm(50, 2, 0.3)) # vector of means
x <- t(matrix(rnorm(1000*100, mu), ncol=1000))
manyboxplot(x, c(0.05, 0.25), ylim=range(x),
            dotcol=c("blue", "green")[(1:100 > 50) + 1],
            hlines=seq(-4, 6, by=2),
```

```
vlines=c(1, seq(20, 100, by=20)))
```

<code>maxabs</code>	<i>maximum of absolute value</i>
---------------------	----------------------------------

Description

Take the maximum of the absolute values of the input

Usage

```
maxabs(x, na.rm = FALSE)
```

Arguments

<code>x</code>	a numeric vector or array
<code>na.rm</code>	a logical indicating whether missing values should be removed.

Value

The maximum of the absolute value of the input

Examples

```
x <- c(5, -2, 8, -20, 2.3)
maxabs(x)
```

<code>mypairs</code>	<i>My scatterplot matrix</i>
----------------------	------------------------------

Description

A matrix of scatterplots is produced; it's similar to [graphics::pairs\(\)](#), but with only the upper triangle is made.

Usage

```
mypairs(x, ...)
```

Arguments

<code>x</code>	A numeric matrix or data frame.
<code>...</code>	Passed to the graphics::plot() function.

Details

This is like the function [graphics::pairs\(\)](#), but only the upper triangle is produced.

Value

None.

See Also

[graphics::pairs\(\)](#)

Examples

```
v <- rbind(c(1,0.5,0.2),c(0.5,1,0.9),c(0.2,0.9,1))
x <- rmvn(500, rep(5,3), v)
mypairs(x, col=sample(c("blue","red"), 500, repl=TRUE))
```

myround

Round a number, preserving extra 0's

Description

Round a number, preserving extra 0's.

Usage

```
myround(x, digits = 1)
```

Arguments

x	Number to round.
digits	Number of digits past the decimal point to keep.

Details

Uses [base::sprintf\(\)](#) to round a number, keeping extra 0's.

Value

A vector of character strings.

See Also

[base::round\(\)](#), [base::sprintf\(\)](#)

Examples

```
myround(51.01, 3)
myround(0.199, 2)
```

normalize

Quantile normalization

Description

Quantile normalizes two vectors or a matrix.

Usage

```
normalize(x, y = NULL)
```

Arguments

- | | |
|---|--------------------------------|
| x | Numeric vector or matrix |
| y | Optional second numeric vector |

Details

We sort the columns, take averages across rows, and then plug the averages back into the respective positions. The marginal distributions in the columns are thus forced to be the same. Missing values, which can result in differing numbers of observed values per column, are dealt with by linear interpolation.

Value

If two vectors, *x* and *y*, are provided, the output is a matrix with two columns, with the quantile normalized versions of *x* and *y*. If *y* is missing, *x* should be a matrix, in which case the output is a matrix of the same dimensions with the columns quantile normalized with respect to each other.

Examples

```
z <- rmvn(10000, mu=c(0,5,10), V = rbind(c(1,0.5,0.5),c(0.5,1,0.5),c(0.5,0.5,1)))
z[sample(prod(dim(z)), 1500)] <- NA
pairs(z)
br <- seq(min(z, na.rm=TRUE), max(z, na.rm=TRUE), length=200)
par(mfrow=c(3,1))
for(i in 1:3)
  hist(z[,i], xlab="z", main=i, breaks=br)
zn <- normalize(z)
br <- seq(min(zn, na.rm=TRUE), max(zn, na.rm=TRUE), length=200)
for(i in 1:3)
  hist(zn[,i], xlab="normalized z", main=i, breaks=br)
pairs(zn)
```

note	<i>Send a note to pushbullet</i>
------	----------------------------------

Description

Even simpler interface for [RPushbullet::pbPost\(\)](#) to send a bit of text to pushbullet.

Usage

```
note(title, recipients = NULL, body = NULL)
```

Arguments

title	The title of the note (could be the whole thing).
recipients	A character or numeric vector indicating the devices this post should go to. If NULL, the default device is looked up from an optional setting, and if none has been set the push is sent to all devices. (passed to RPushbullet::pbPost() .)
body	The body of the note (by default, empty)

See Also

[errors2pushbullet\(\)](#), [done\(\)](#), [pushbullet_devices\(\)](#)

Examples

```
## Not run: note("Hello.")
```

numbers	<i>Numbers spelled out in English</i>
---------	---------------------------------------

Description

The numbers 1-20 spelled out in English, for use in reports.

Format

A vector of character strings

Details

- numbers - lower case
- Numbers - Capitalized

Examples

```
numbers[5]
Numbers[5]
```

objectsizes	<i>Calculate sizes of all objects in workspace</i>
-------------	--

Description

Calculate the sizes of all of the objects in one's workspace.

Usage

```
objectsizes(obj = NULL, sortysize = TRUE)
```

Arguments

obj	Vector of object names. If missing, we pull out all object names.
sortysize	If TRUE, sort the objects from smallest to largest.

Details

Calls [utils::object.size\(\)](#) repeated to get the size of a list of objects.

Value

A data frame with the only column being the size of each object in megabytes (Mb). The row names are the names of the objects.

See Also

[utils::object.size\(\)](#), [base::objects\(\)](#)

Examples

```
print(output <- objectsizes())
## Not run: sum(output)
```

openfile	<i>Open a file</i>
----------	--------------------

Description

Open a file using [base::system()] and "open" (well, actually "start" on Linux).

Usage

```
openfile(file)
```

Arguments

<code>file</code>	File name (character string)
-------------------	------------------------------

Details

I'd thought that to open a file you'd use `open` in MacOS and `start` in Windows, but `system("start myfile.pdf")` doesn't work in Windows, and rather `system("open myfile.pdf")` does, so here we're just using `open`, except on Linux where at least on my system, you can use "start".

Value

None.

Examples

```
## Not run: openfile("myplot.pdf")
```

`paired.perm.test` *Paired permutation t-test*

Description

Calculates a p-value for a paired t-test via permutations.

Usage

```
paired.perm.test(d, n.perm = NULL, pval = TRUE)
```

Arguments

<code>d</code>	A numeric vector (of differences).
<code>n.perm</code>	Number of permutations to perform. If <code>NULL</code> , all possible permutations are considered, and an exact p-value is calculated.
<code>pval</code>	If <code>TRUE</code> , return just the p-value. If <code>FALSE</code> , return the actual permutation results (with the observed statistic as an attribute, "tobs").

Details

This calls the function `stats:::t.test()` to calculate a t-statistic comparing the mean of `d` to 0. Permutations are performed to give an exact or approximate conditional p-value.

Value

If `pval=TRUE`, the output is a single number: the P-value testing for the symmetry about 0 of the distribution of the population from which `d` was drawn. If `pval=FALSE`, the output is a vector of the t statistics from the permutations. An attributed "tobs" contains the t statistic with the observed data.

See Also

[stats::t.test\(\)](#), [perm.test\(\)](#)

Examples

```
x <- c(43.3, 57.1, 35.0, 50.0, 38.2, 31.2)
y <- c(51.9, 95.1, 90.0, 49.7, 101.5, 74.1)
paired.perm.test(x-y)
```

paste.

paste with dot separator

Description

Calls [base::paste\(\)](#) with `sep=". ".`

Usage

```
paste.(...)
```

Arguments

... Passed to `paste.`

Details

There's not much to this function. It just is [base::paste\(\)](#) with `sep=""`, 'cause I'm lazy.

Value

A character string or vector of character strings.

See Also

[base::paste\(\)](#), [base::paste0\(\)](#), [paste00\(\)](#), [paste..\(\)](#), [paste0.\(\)](#), [paste.0\(\)](#)

Examples

```
x <- 3
y <- 4
paste.(x, y)
```

paste00

paste with null or dot as separator and with collapse

Description

Call [base::paste\(\)](#) with `sep=". "` or `sep=""` and `collapse=""` or `collapse=". "`.

Usage

```
paste00(...)
```

Arguments

... Passed to paste.

Details

There's not much to these functions. `paste00(...)` is like `paste(..., sep = "", collapse = "")`
`paste..(...)` is like `paste(..., sep = ". ", collapse = ". ")` `paste0.(...)` is like `paste(..., sep = "", collapse = ". ")`
`paste.0(...)` is like `paste(..., sep = ". ", collapse = "")`

Value

A character string or vector of character strings.

See Also

[base::paste\(\)](#), [base::paste0\(\)](#), [paste.\(\)](#)

Examples

```
x <- c(3, 4)
y <- c(5, 6)
paste00(x, y)
paste..(x, y)
paste0.(x, y)
paste.0(x, y)
```

perm.test*Permutation t-test***Description**

Calculates a p-value for a t-test via permutations.

Usage

```
perm.test(x, y, n.perm = NULL, var.equal = TRUE, pval = TRUE)
```

Arguments

<code>x</code>	A numeric vector.
<code>y</code>	A second numeric vector.
<code>n.perm</code>	Number of permutations to perform. If <code>NULL</code> , all possible permutations are considered, and an exact p-value is calculated.
<code>var.equal</code>	A logical variable indicating whether to treat the two population variances as being equal.
<code>pval</code>	If <code>TRUE</code> , return just the p-value. If <code>FALSE</code> , return the actual permutation results (with the observed statistic as an attribute, "tobs").

Details

This calls the function `stats:::t.test()` to calculate a t-statistic comparing the vectors `x` and `y`. Permutations are performed to give an exact or approximate conditional p-value.

Value

If `pval=TRUE`, the output is a single number: the P-value testing for a difference in the distributions of the populations from which `x` and `y` were drawn. If `pval=FALSE`, the output is a vector of the t statistics from the permutations. An attributed "tobs" contains the t statistic with the observed data.

See Also

`stats:::t.test()`, `paired.perm.test()`

Examples

```
x <- c(43.3, 57.1, 35.0, 50.0, 38.2, 61.2)
y <- c(51.9, 95.1, 90.0, 49.7, 101.5, 74.1)
perm.test(x,y)
```

<code>pick_more_precise</code>	<i>Pick the more precise value for each element in two related vectors</i>
--------------------------------	--

Description

Align two vectors of numbers by their names and then pick a single value from each, favoring the more precise one. If the two values differ by more than round-off error, treat the value as missing.

Usage

```
pick_more_precise(x, y, tol = 0.000001)
```

Arguments

<code>x</code>	A numeric vector
<code>y</code>	A second numeric vector
<code>tol</code>	Tolerance for differences between the values

Details

Okay, this is a bit weird. But suppose you have two columns of numbers that have been subjected to different quirky rounding patterns. We align the vectors using their names and then for each element we pick between the two choices, favoring the more-precise one. If one is missing, choose the non-missing value. If the two differ by more than the round-off error, treat it as missing.

Value

A vector of combined values

<code>plot_crayons</code>	<i>Illustration of crayon colors</i>
---------------------------	--------------------------------------

Description

Creates a plot of the crayon colors in [brocolors\(\)](#)

Usage

```
plot_crayons(
  method2order = c("hsv", "cluster"),
  cex = 0.6,
  mar = rep(0.1, 4),
  bg = "white",
  fg = "black",
  border = FALSE
)
```

Arguments

<code>method2order</code>	method to order colors ("hsv" or "cluster")
<code>cex</code>	character expansion for the text
<code>mar</code>	margin parameters; vector of length 4 (see <code>graphics::par()</code>)
<code>bg</code>	Background color
<code>fg</code>	Foreground color (for text and box outlines)
<code>border</code>	If TRUE, plot a border around each rectangle

Value

None

References

https://en.wikipedia.org/wiki/List_of_Crayola_crayon_colors

See Also

`brocolors()`

Examples

`plot_crayons()`

`pushbullet_devices` *Grab info on Pushbullet devices.*

Description

Get names and identifiers of Pushbullet devices.

Usage

`pushbullet_devices()`

Value

data frame with nickname, model, and iden for active devices.

See Also

`errors2pushbullet()`, `done()`, `note()`

qqline2*qqline for qqplot*

Description

Adds a line to a quantile-quantile plot for two datasets, from [stats::qqplot\(\)](#). (The available [stats::qqline\(\)](#) function works mainly for [stats::qnorm\(\)](#), with one sample being theoretical quantiles.)

Usage

```
qqline2(x, y, probs = c(0.25, 0.75), qtype = 7, ...)
```

Arguments

x	The first sample
y	The second sample.
probs	numeric vector of length two, representing probabilities. Corresponding quantile pairs define the line drawn.
qtype	the type of quantile computation used in stats::quantile() .
...	graphical parameters.

Value

Intercept and slope of the line.

See Also

[stats::qqline\(\)](#), [stats::qqplot\(\)](#)

Examples

```
x <- rchisq(500, 3)
y <- rgamma(730, 3, 1/2)
qqplot(x, y)
qqline2(x, y)
```

qr2*The QR decomposition of a matrix***Description**

Computes the QR decomposition of a matrix.

Usage

```
qr2(x, tol = 0.0000001)
```

Arguments

- | | |
|------------------|--|
| <code>x</code> | A matrix whose QR decomposition is to be computed. |
| <code>tol</code> | The tolerance for detecting linear dependencies in the columns of <code>x</code> . |

Details

Calls the function [base::qr\(\)](#) and returns less compact but more understandable output.

Value

A list of two matrices: Q and R.

See Also

[base::qr\(\)](#)

Examples

```
hilbert <- function(n) { i <- 1:n; 1/outer(i-1,i,"+") }
h5 <- hilbert(5);
qr2(h5)
```

quantileSE*Sample quantiles and their standard errors***Description**

Calculate sample quantiles and their estimated standard errors.

Usage

```
quantileSE(x, p = 0.95, bw = NULL, na.rm = TRUE, names = TRUE)
```

Arguments

x	Numeric vector whose sample quantiles are wanted.
p	Numeric vector with values in the interval [0,1]
bw	Bandwidth to use in the density estimation.
na.rm	Logical; if true, and NA and NaN's are removed from x before the quantiles are computed.
names	Logical; if true, the column names of the result is set to the values in p.

Details

The sample quantiles are calculated with the function `stats::quantile()`. Standard errors are obtained by the asymptotic approximation described in Cox and Hinkley (1974). Density values are estimated using a kernel density estimate with the function `stats::density()`.

Value

A matrix of size 2 x `length(p)`. The first row contains the estimated quantiles; the second row contains the corresponding estimated standard errors.

See Also

`stats::quantile()`, `stats::density()`

Examples

```
quantileSE(rchisq(1000,4), c(0.9,0.95))
```

revgray

*Create vector of colors from white to black***Description**

Calls `grDevices::gray()` then `base::rev()`

Usage

```
revgray(n = 256, ...)
```

Arguments

n	Number of colors.
...	Passed to <code>grDevices::gray()</code> .

Details

There's not much to this. It's just `gray((n:0)/n)`

Value

Vector of colors, from white to black

See Also

[grDevices::gray\(\)](#)

Examples

```
x <- matrix(rnorm(100), ncol=10)
image(x, col=revgray())
```

revrainbow

Create vector of colors from blue to red

Description

Calls [grDevices::rainbow\(\)](#) then [base::rev\(\)](#)

Usage

```
revrainbow(n = 256, ...)
```

Arguments

n	Number of colors.
...	Passed to grDevices::rainbow() .

Details

There's not much to this. It's just `rev(rainbow(start=0, end=2/3, ...))`.

Value

Vector of colors, from blue to red.

See Also

[base::rev\(\)](#), [grDevices::rainbow\(\)](#)

Examples

```
x <- matrix(rnorm(100), ncol=10)
image(x, col=revrainbow())
```

rmvn*Simulate multivariate normal*

Description

Simulate from a multivariate normal distribution.

Usage

```
rmvn(n, mu = 0, V = matrix(1))
```

Arguments

n	Number of simulation replicates.
mu	Mean vector.
V	Variance-covariance matrix.

Details

Uses the Cholesky decomposition of the matrix V, obtained by [base::chol\(\)](#).

Value

A matrix of size n x length(mu). Each row corresponds to a separate replicate.

See Also

[stats::rnorm\(\)](#)

Examples

```
x <- rmvn(100, c(1,2),matrix(c(1,1,1,4),ncol=2))
```

runningmean*Running mean, sum, or median*

Description

Calculates a running mean, sum or median with a specified window.

Usage

```
runningmean(
  pos,
  value,
  at = NULL,
  window = 1000,
  what = c("mean", "sum", "median", "sd")
)
```

Arguments

<code>pos</code>	Positions for the values.
<code>value</code>	Values for which the running mean/sum/median/sd is to be applied.
<code>at</code>	Positions at which running mean (or sum or median or sd) is calculated. If <code>NULL</code> , <code>pos</code> is used.
<code>window</code>	Window width.
<code>what</code>	Statistic to use.

Value

A vector with the same length as the input `at` (or `pos`, if `at` is `NULL`), containing the running statistic.

Author(s)

Karl W Broman <broman@wisc.edu>

See Also

`runningratio\(\)`

Examples

```
x <- 1:10000
y <- rnorm(length(x))
plot(x,y, xaxs="i", yaxs="i")
lines(x, runningmean(x, y, window=100, what="mean"),
      col="blue", lwd=2)
lines(x, runningmean(x, y, window=100, what="median"),
      col="red", lwd=2)
lines(x, runningmean(x, y, window=100, what="sd"),
      col="green", lwd=2)
```

runningratio*Running ratio*

Description

Calculates a running ratio; a ratio sum(top)/sum(bottom) in a sliding window.

Usage

```
runningratio(pos, numerator, denominator, at = NULL, window = 1000)
```

Arguments

pos	Positions for the values.
numerator	Values for numerator in ratio.
denominator	Values for denominator in ratio.
at	Positions at which running ratio is calculated. If NULL, pos is used.
window	Window width.

Value

A vector with the same length as the input at (or pos, if at is NULL), containing the running ratio.

Author(s)

Karl W Broman <broman@wisc.edu>

See Also

[runningmean\(\)](#)

Examples

```
x <- 1:1000
y <- runif(1000, 1, 5)
z <- runif(1000, 1, 5)
plot(x, runningratio(x, y, z, window=5), type="l", lwd=2)
lines(x, runningratio(x, y, z, window=50), lwd=2, col="blue")
lines(x, runningratio(x, y, z, window=100), lwd=2, col="red")
```

`setRNGparallel`*Set up random number generation for parallel calculations***Description**

Set random number generation to L'Ecuyer-CMRG, for use in parallel calculations.

Usage

```
setRNGparallel()
unsetRNGparallel()
```

Details

I can never remember the command `RNGkind("L'Ecuyer-CMRG")`; this is a shortcut. `unsetRNG4parallel` sets the random number generator back to the default type.

Examples

```
RNGkind()
setRNGparallel()
RNGkind()
unsetRNGparallel()
RNGkind()
```

`simp`*Numerical integration***Description**

Perform numerical integration by Simpson's rule or the trapezoidal rule.

Usage

```
simp(f, a, b, tol = 0.00000001, max.step = 1000, ...)
```

Arguments

<code>f</code>	The integrand; must be a vectorized function.
<code>a</code>	Lower limit of integration.
<code>b</code>	Upper limit of integration.
<code>tol</code>	Tolerance for choosing the number of grid points.
<code>max.step</code>	Log base 2 of the total number of grid points.
<code>...</code>	Other arguments passed to the integrand, <code>f</code> .

Details

Iterately doubles the number of grid points for the numerical integral, stopping when the integral decreases by less than `tol`.

Value

The integral of `f` from `a` to `b`.

See Also

[stats::integrate\(\)](#)

Examples

```
f <- function(x) x*x*(1-x)*sin(x*x)
I1 <- trap(f,0,2)
I2 <- simp(f,0,2)
```

spell_out

Spell out an integer

Description

Spell out an integer as a word, for use in reports/papers.

Usage

```
spell_out(number, capitalize = FALSE, max_value = 9)
```

Arguments

- | | |
|-------------------------|--|
| <code>number</code> | A number that is to be spelled out (can be a vector). |
| <code>capitalize</code> | If TRUE, capitalize the first letter. |
| <code>max_value</code> | Maximum value to use (generally 9); if larger than this, use numerals. |

Value

Character string (or vector of character strings) with numbers spelled out, or as numerals if large.

Examples

```
spell_out(9)
spell_out(9, cap=TRUE)
spell_out(9, max_value=5)
```

`stop_sending_errors` *Stop sending errors to pushbullet*

Description

Clear the `error` option, so that error notifications are no longer sent to pushbullet.

Usage

`stop_sending_errors()`

See Also

[errors2pushbullet\(\)](#), [pushbullet_devices\(\)](#)

Examples

```
## Not run: stop_sending_errors()
```

`strwidth2lines` *Calculate width of a character string in number of lines*

Description

Convert `stringwidth` units to number of (margin) lines

Usage

`strwidth2lines(s, ...)`

Arguments

<code>s</code>	A character or expression vector whose length is to be calculated
...	additional information used by <code>strwidth</code> , such as <code>cex</code>

Value

Maximum string width in units of margin lines

Author(s)

Aimee Teo Broman

Examples

```
p <- par(TRUE)
string <- sapply(sample(1:20,15,replace=TRUE),
                  function(a) paste(LETTERS[1:a], collapse=""))
nlines <- strwidth2lines(string)
mar <- par("mar")
par(mar=c(mar[1],nlines+0.1,mar[3:4]))
plot(1:length(string),1:length(string),yaxt="n", ylab="")
axis(side=2, at=seq_along(string), lab=string, las=1)
par(p)
nlines <- strwidth2lines(string,cex=1.5)
par(mar=c(mar[1:3],nlines+0.1))
plot(1:length(string),1:length(string),ylab="")
mgp <- par("mgp")
axis(side = 4, at=seq_along(string),
     labels = string ,las=1, hadj=1,
     mgp=c(mgp[1],nlines,mgp[3]),cex.axis=1.5)
par(p)
```

strwidth2xlim

Calculate horizontal limit in user coordinates for adding labels

Description

Calculates the x-axis limits when adding (long) labels to a plot

Usage

```
strwidth2xlim(x, xstring, pos = 4, offset = 0.5, ...)
```

Arguments

x	numeric vector of horizontal coordinates
xstring	character vector, specifying text to be written
pos	position specifier for text; values of 1, 2, 3, and 4, respectively, indicate positions below, to the left of, above, and to the right of the coordinates
offset	offset of the label from the coordinate in fractions of a character width
...	additional text parameters from par, such as cex

Details

See text for details on pos and offset.

Value

Minimum and maximum x-axis limits for adding horizontal text

Author(s)

Aimee Teo Broman

See Also

[graphics::text\(\)](#)

Examples

```
x <- runif(15,-1,1)*10
xlabs <- sapply(sample(1:20,15,replace=TRUE),
                 function(a) paste(LETTERS[1:a], collapse=""))
## Labels to the left ##
xlims <- strwidth2xlim(x,xlabs,pos=2)
plot(x,1:length(x),xlim=xlims)
text(x,1:length(x),xlabs,pos=2)
## Labels to the right ##
xlims <- strwidth2xlim(x,xlabs,pos=4,cex=0.7)
plot(x,1:length(x),xlim=xlims)
text(x,1:length(x),xlabs,pos=4,cex=0.7)
```

switchv

Vectorized version of switch

Description

Vectorized version of [base::switch\(\)](#): just loops over input and calls [base::switch\(\)](#).

Usage

`switchv(EXPR, ...)`

Arguments

EXPR	An expression evaluating to a vector of numbers or strings
...	List of alternatives

Value

Vector of returned values.

Examples

```
switchv(c("horse", "fish", "cat", "bug"),
        horse="fast",
        cat="cute",
        "what?")
```

`theme_karl`*Karl's ggplot2 theme*

Description

Karl's ggplot2 theme: black border and no ticks

Usage

```
theme_karl(base_size = 12, base_family = "", ...)  
karl_theme(base_size = 12, base_family = "", ...)
```

Arguments

<code>base_size</code>	Base font size
<code>base_family</code>	Base font family
<code>...</code>	Passed to ggplot2::theme()

Value

An object as returned by [ggplot2::theme\(\)](#)

See Also

[ggplot2::theme\(\)](#)

Examples

```
library(ggplot2)  
mtcars$cyl <- factor(mtcars$cyl)  
ggplot(mtcars, aes(y=mpg, x=disp, color=cyl)) +  
  geom_point() + theme_karl()
```

`triarrow`*Plot an arrow within a Holmans triangle*

Description

Plot an arrow within a Holmans triangle (an equilateral triangle used to depict trinomial distributions).

Usage

```
triarrow(x, ...)
```

Arguments

- x A matrix with three rows and two columns, each column being a trinomial distribution. An arrow between the two points is plotted.
- ... Passed to [graphics::arrows\(\)](#).

Details

Plot of an equilateral triangle, in order to depict trinomial distributions. A trinomial distribution (that is, a trio of non-negative numbers that add to 1) is equated to a point in the triangle through the distances to the three sides. This makes use of the fact that for any point in an equilateral triangle, the sum of the distances to the three sides is constant. First use [triplot\(\)](#) to first plot the equilateral triangle.

Value

The (x,y) coordinates of the endpoints of the arrows plotted.

See Also

[triplot\(\)](#), [tripoints\(\)](#), [trilines\(\)](#), [tritext\(\)](#)

Examples

```
triplot()
x <- cbind(c(0.9, 0.05, 0.05), c(0.8, 0.1, 0.1), c(0.1, 0.9, 0), c(0, 0.9, 0.1))
tripoints(x, lwd=2, col=c("black", "blue", "red", "green"), pch=16)
trilines(x, lwd=2, col="orange")
y <- cbind(c(0.05, 0.05, 0.9), c(0.25, 0.25, 0.5))
triarrow(y, col="blue", lwd=2, len=0.1)
```

trigrid

Add grid lines to tripplot

Description

Add grid lines to a ternary plot with [triplot\(\)](#)

Usage

```
trigrid(
  n = 1,
  col = "white",
  lty = 1,
  lwd = 1,
  outer_col = "black",
  outer_lwd = 2,
  ...
)
```

Arguments

n	Number of grid lines
col	Color of grid lines
lty	Line type for grid lines
lwd	Line width of grid lines
outer_col	Color of outer triangle (If NULL, not plotted)
outer_lwd	Line width of outer triangle
...	Additional arguments passed to trilines()

See Also

[triplot\(\)](#), [trilines\(\)](#)

Examples

```
triplot(c("A","H","B"), gridlines=1, grid_lwd=2)
trigrid(3, lty=2, lwd=2)
```

trilines

Plot lines within a Holmans triangle

Description

Plot lines within a Holmans triangle (an equilateral triangle used to depict trinomial distributions).

Usage

```
trilines(x, ...)
```

Arguments

x	A matrix with three rows, each column being a trinomial distribution. Lines between these points are plotted.
...	Passed to graphics::lines() .

Details

Plot of an equilateral triangle, in order to depict trinomial distributions. A trinomial distribution (that is, a trio of non-negative numbers that add to 1) is equated to a point in the triangle through the distances to the three sides. This makes use of the fact that for any point in an equilateral triangle, the sum of the distances to the three sides is constant. First use [triplot\(\)](#) to first plot the equilateral triangle.

Value

The (x,y) coordinates of the endpoints of the lines plotted.

See Also

[triplot\(\)](#), [tripoints\(\)](#), [triarrow\(\)](#), [tritext\(\)](#)

Examples

```
triplot()
x <- cbind(c(0.9, 0.05, 0.05), c(0.8, 0.1, 0.1), c(0.1, 0.9, 0), c(0, 0.9, 0.1))
tripoints(x, lwd=2, col=c("black","blue","red","green"), pch=16)
trilines(x, lwd=2, col="orange")
y <- cbind(c(0.05, 0.05, 0.9), c(0.25, 0.25, 0.5))
triarrow(y, col="blue", lwd=2, len=0.1)
```

triplot

Plot Holmans triangle

Description

Plot Holmans triangle (an equilateral triangle used to depict trinomial distributions).

Usage

```
triplot(
  labels = c("(1,0,0)", "(0,1,0)", "(0,0,1)"),
  col = "black",
  lwd = 2,
  bgcolor = "gray90",
  gridlines = 0,
  grid_col = "white",
  grid_lty = 1,
  grid_lwd = 1,
  ...
)
```

Arguments

<code>labels</code>	Labels for the three corners (lower-right, top, lower-left).
<code>col</code>	Color of edges of triangle
<code>lwd</code>	Line width for edges of triangle
<code>bgcolor</code>	Background color for triangle
<code>gridlines</code>	Number of grid lines (if 0, no grid lines will be plotted)
<code>grid_col</code>	Color of grid lines
<code>grid_lty</code>	Line type of grid lines
<code>grid_lwd</code>	Line width of grid lines
<code>...</code>	Passed to graphics::plot() .

Details

Plot of an equilateral triangle, in order to depict trinomial distributions. A trinomial distribution (that is, a trio of non-negative numbers that add to 1) is equated to a point in the triangle through the distances to the three sides. This makes use of the fact that for any point in an equilateral triangle, the sum of the distances to the three sides is constant. The `tripoints()` function creates an empty triangle for use with the related functions `tripoints()`, `trilines()`, `triarrow()`.

Value

The (x,y) coordinates of the points plotted, if any.

See Also

`tripoints()`, `trilines()`, `triarrow()`, `tritext()`

Examples

```
triplot()
x <- cbind(c(0.9, 0.05, 0.05), c(0.8, 0.1, 0.1), c(0.1, 0.9, 0), c(0, 0.9, 0.1))
tripoints(x, lwd=2, col=c("black", "blue", "red", "green"), pch=16)
trilines(x, lwd=2, col="orange")
y <- cbind(c(0.05, 0.05, 0.9), c(0.25, 0.25, 0.5))
triarrow(y, col="blue", lwd=2, len=0.1)
```

`tripoints`

Plot points within a Holmans triangle

Description

Plot points within a Holmans triangle (an equilateral triangle used to depict trinomial distributions).

Usage

`tripoints(x, ...)`

Arguments

- | | |
|------------------|---|
| <code>x</code> | A matrix with three rows, each column being a trinomial distribution. |
| <code>...</code> | Passed to <code>graphics::points()</code> . |

Details

Plot of an equilateral triangle, in order to depict trinomial distributions. A trinomial distribution (that is, a trio of non-negative numbers that add to 1) is equated to a point in the triangle through the distances to the three sides. This makes use of the fact that for any point in an equilateral triangle, the sum of the distances to the three sides is constant. First use `triplot()` to first plot the equilateral triangle.

Value

The (x,y) coordinates of the points plotted.

See Also

[triplot\(\)](#), [trilines\(\)](#), [triarrow\(\)](#), [tritext\(\)](#)

Examples

```
triplot()
x <- cbind(c(0.9, 0.05, 0.05), c(0.8, 0.1, 0.1), c(0.1, 0.9, 0), c(0, 0.9, 0.1))
tripoints(x, lwd=2, col=c("black", "blue", "red", "green"), pch=16)
trilines(x, lwd=2, col="orange")
y <- cbind(c(0.05, 0.05, 0.9), c(0.25, 0.25, 0.5))
triarrow(y, col="blue", lwd=2, len=0.1)
```

tritext

Plot text within a Holmans triangle

Description

Plot text within a Holmans triangle (an equilateral triangle used to depict trinomial distributions).

Usage

```
tritext(x, labels, ...)
```

Arguments

- x A matrix with three rows, each column being a trinomial distribution.
- labels A vector of character strings, with length equal to the number of columns of x.
- ... Passed to [graphics::text\(\)](#).

Details

Plot of an equilateral triangle, in order to depict trinomial distributions. A trinomial distribution (that is, a trio of non-negative numbers that add to 1) is equated to a point in the triangle through the distances to the three sides. This makes use of the fact that for any point in an equilateral triangle, the sum of the distances to the three sides is constant. First use [triplot\(\)](#) to first plot the equilateral triangle.

Value

Text is plotted at the (x,y) coordinates of the points.

See Also

[triplot\(\)](#), [trilines\(\)](#), [triarrow\(\)](#), [tripoints\(\)](#)

Examples

```
triplot()
x <- cbind(c(0.25, 0.5, 0.25), c(1/3, 1/3, 1/3))
tripoints(x, lwd=2, pch=21, bg="lightblue")
xp <- x + c(0.02, 0, -0.02)
tritext(xp, c("(1/4,1/2,1/4)", "(1/3,1/3,1/3)"), adj=c(0, 0.5))
```

twocolorpal

Create vector of colors from blue to white to red

Description

Create a two-color palette from one color to another through some third color

Usage

```
twocolorpal(colors = c("slateblue", "white", "violetred"), n = 256, ...)
```

Arguments

colors	Vector of three colors
n	Number of colors in output.
...	Passed to grDevices::colorRampPalette() .

Value

Vector of colors, from blue to white to red

See Also

[revgray\(\)](#)

Examples

```
x <- matrix(rnorm(100, 0.5), ncol=10)
mxabs <- max(abs(x))
image(x, col=twocolorpal(), ylim=c(-mxabs, mxabs))
```

`vec2string`*Turn a vector into a single character string*

Description

Turn a vector into a single character string with the items separated by commas and an "and".

Usage

```
vec2string(x, conjunction = "and")
```

Arguments

<code>x</code>	A vector
<code>conjunction</code>	Word used to combine the strings

Examples

```
vec2string(letters[1:2])
vec2string(letters[1:4])
vec2string(letters[1:4], "or")
```

`venn`*Plot to-scale Venn diagram*

Description

Plot a Venn diagram (with two groups), to scale, either with circles or with squares.

Usage

```
venn(
  setA = 50,
  setB = 50,
  both = 25,
  method = c("circle", "square"),
  labels = c("A", "B"),
  col = c("blue", "red")
)
```

Arguments

setA	Total area of set A.
setB	Total area of set B.
both	Area of intersection of sets A and B.
method	Indicates whether to plot circles or squares.
labels	Labels for the two sets. (NULL for no labels.)
col	Colors of the two sets.

Details

Plots a to-scale Venn diagram with two sets, so that the relative areas of the two sets and their intersection are exact.

Value

None.

Examples

```
venn(setA=86, setB=1622, both=10)
venn(setA=86, setB=1622, both=10, method="square")
```

winsorize

Winsorize a vector

Description

For a numeric vector, move values below and above the q and 1-q quantiles to those quantiles.

Usage

```
winsorize(x, q = 0.006)
```

Arguments

x	Numeric vector
q	Lower quantile to use

Value

A vector like the input x, but with extreme values moved in to the q and 1-q quantiles.

Examples

```
x <- sample(c(1:10, rep(NA, 10), 21:30))
winsorize(x, 0.2)
```

xlimlabel*Calculate horizontal limit in user coordinates for adding labels***Description**

Calculates the x-axis limits when adding (long) labels to a plot

Usage

```
xlimlabel(x, xlabel, pos = 4, offset = 0.5, ...)
```

Arguments

<code>x</code>	numeric vector of horizontal coordinates
<code>xlabel</code>	character vector, specifying text to be written
<code>pos</code>	position specifier for text; values of 1, 2, 3, and 4, respectively, indicate positions below, to the left of, above, and to the right of the coordinates
<code>offset</code>	offset of the label from the coordinate in fractions of a character width
<code>...</code>	Additional par arguments

Details

See [graphics::text\(\)](#) for details on `pos` and `offset`.

Value

Minimum and maximum x-axis limits for adding horizontal text

Author(s)

Aimee Teo Broman

See Also

[graphics::text\(\)](#)

Examples

```
x <- runif(15, -1, 1)*10
xlabels <- sapply(sample(1:20, 15, replace=TRUE),
  function(a) paste(LETTERS[1:a], collapse=""))
par(mfrow=c(2,1), las=1)
## Labels to the left ##
xlims <- xlimlabel(x, xlabel, pos=2)
plot(x, 1:length(x), xlim=xlims, ylab="Index")
text(x, 1:length(x), xlabel, pos=2)
## Labels to the right ##
xlims <- xlimlabel(x, xlabel, pos=4, cex=0.7)
```

```
plot(x, 1:length(x), xlim=xlims, ylab="Index")
text(x, 1:length(x), xlabs, pos=4, cex=0.7)
```

%nin%*Value matching***Description**

`%in%` returns logical vector indicating values that do not have a match. `%win%` returns a vector of the values that have a match. `%wnin%` returns a vector of the values that do not have a match.

Usage

```
x %nin% table
x %win% table
x %wnin% table
```

Arguments

<code>x</code>	Vector of values to be matched.
<code>table</code>	Vector of values to be matched against.

Value

`%nin%` returns a logical vector of the same length of `x`, indicating which values are not in `table`.
`%win%` returns a sub-vector of `x` with the values that were found in `table`.
`%wnin%` returns a sub-vector of `x` with the values that were not found in `table`.

See Also

[base::match\(\)](#)

Examples

```
vals <- c("a", "xa", "b")
vals %nin% letters
vals %win% letters
vals %wnin% letters
```

Index

- *Topic **IO**
 - openfile, 34
- *Topic **algebra**
 - qr2, 42
- *Topic **character**
 - paste., 36
 - paste00, 37
- *Topic **color**
 - colwalpha, 11
 - revgray, 43
 - revrainbow, 44
 - twocolorpal, 59
- *Topic **datagen**
 - rmvn, 45
- *Topic **datasets**
 - numbers, 33
- *Topic **data**
 - cf, 8
- *Topic **documentation**
 - h, 23
- *Topic **graphics**
 - ciplot, 10
 - dotplot, 14
 - grayplot, 20
 - grayplot_na, 21
 - histlines, 25
 - manyboxplot, 29
- *Topic **hplot**
 - arrowlocator, 4
 - excel_fig, 16
 - mypairs, 30
 - qqline2, 41
 - triarrow, 53
 - trilines, 55
 - triplot, 56
 - tripoints, 57
 - tritext, 58
 - venn, 60
- *Topic **htest**
 - chisq, 9
 - fisher, 18
 - paired.perm.test, 35
 - perm.test, 38
- *Topic **manip**
 - convert2hex, 12
 - hex2dec, 24
- *Topic **math**
 - simp, 48
- *Topic **print**
 - bromanversion, 7
- *Topic **univar**
 - quantileSE, 42
 - runningmean, 45
 - runningratio, 47
- *Topic **utilities**
 - attrnames, 5
 - brocolors, 6
 - crayons, 13
 - done, 14
 - errors2pushbullet, 15
 - exit, 17
 - kbdate, 27
 - lenuniq, 27
 - make, 28
 - myround, 31
 - normalize, 32
 - note, 33
 - objectsizes, 34
 - setRNGparallel, 48
 - stop_sending_errors, 50
 - winsorize, 61
 - %win% (%nin%), 63
 - %wnin% (%nin%), 63
 - %nin%, 63
- add_commas, 3
- align_vectors, 4
- arrowlocator, 4
- attrnames, 5

base::cat(), 17
base::chol(), 45
base::date(), 27
base::jitter(), 26
base::match(), 63
base::objects(), 34
base::paste(), 36, 37
base::paste0(), 36, 37
base::qr(), 42
base::rev(), 43, 44
base::round(), 31
base::sprintf(), 31
base::switch(), 52
base::Sys.time(), 27
base::system(), 28
brocolors, 6
brocolors(), 13, 39, 40
bromanversion, 7

cf, 8
chisq, 9
chisq(), 19
ciplot, 10
colwalpha, 11
compare_rows, 12
convert2hex, 12
crayons, 13

dec2hex (convert2hex), 12
dec2hex(), 24
devtools::as.package(), 28
devtools::load_all(), 28
done, 14
done(), 15, 33, 40
dotplot, 14
dotplot(), 10, 11, 23, 26

errors2pushbullet, 15
errors2pushbullet(), 14, 33, 40, 50
excel_fig, 16
exit, 17

fac2num, 18
fisher, 18
fisher(), 9

get_precision, 19
ggplot2::theme(), 53
graphics::arrows(), 5, 54

graphics::hist(), 25
graphics::lines(), 25, 55
graphics::locator(), 4, 5
graphics::pairs(), 30, 31
graphics::par(), 17, 21, 40
graphics::plot(), 21, 22, 30, 56
graphics::points(), 21, 22, 57
graphics::rect(), 21, 22
graphics::text(), 52, 58, 62
grayplot, 20
grayplot(), 10, 11, 14, 15, 23, 29
grayplot_na, 21
grDevices::colorRampPalette(), 59
grDevices::gray(), 43, 44
grDevices::rainbow(), 44

h, 23
hex2dec, 24
hex2dec(), 13
histlines, 25

jiggle, 26
jiggle(), 14

karl_theme (theme_karl), 53
kdate, 27

lenuniq, 27

make, 28
manyboxplot, 29
maxabs, 30
mypairs, 30
myround, 31

normalize, 32
note, 33
note(), 14, 15, 40
Numbers (numbers), 33
numbers, 33

objectsizes, 34
openfile, 34

paired.perm.test, 35
paired.perm.test(), 38
paste., 36
paste.(), 37
paste.. (paste00), 37
paste..(), 36

paste.0 (paste00), 37
 paste.0(), 36
 paste0. (paste00), 37
 paste0.(), 36
 paste00, 37
 paste00(), 36
 perm.test, 38
 perm.test(), 36
 pick_more_precise, 39
 plot_crayons, 39
 plot_crayons(), 6, 13
 pushbullet_devices, 40
 pushbullet_devices(), 14, 15, 33, 50

 qqline2, 41
 qr2, 42
 quantileSE, 42

 revgray, 43
 revgray(), 59
 revrainbow, 44
 rmvn, 45
 RPushbullet::pbPost(), 14, 15, 33
 runningmean, 45
 runningmean(), 47
 runningratio, 47
 runningratio(), 46

 setRNGparallel, 48
 simp, 48
 spell_out, 49
 stats::chisq.test(), 9, 19
 stats::density(), 43
 stats::fisher.test(), 9, 18, 19
 stats::integrate(), 49
 stats::qqline(), 41
 stats::qqnorm(), 41
 stats::qqplot(), 41
 stats::quantile(), 41, 43
 stats::rnorm(), 45
 stats::t.test(), 35, 36, 38
 stop_sending_errors, 50
 stop_sending_errors(), 15
 strwidth2lines, 50
 strwidth2xlim, 51
 switchv, 52

 theme_karl, 53
 trap (simp), 48

 triarrow, 53
 triarrow(), 56–59
 trigrid, 54
 trilines, 55
 trilines(), 54, 55, 57–59
 triplot, 56
 triplot(), 54–59
 tripoints, 57
 tripoints(), 54, 56, 57, 59
 tritext, 58
 tritext(), 54, 56–58
 twocolorpal, 59

 unsetRNGparallel (setRNGparallel), 48
 utils::help(), 23
 utils::help.start(), 23
 utils::object.size(), 34

 vec2string, 60
 venn, 60

 winsorize, 61

 xlimlabel, 62