

Package ‘cimir’

January 22, 2020

Title Interface to the CIMIS Web API

Version 0.4-0

Description Connect to the California Irrigation Management Information System (CIMIS) Web API. See the CIMIS main page <<https://cimis.water.ca.gov>> and web API documentation <<https://et.water.ca.gov>> for more information.

License GPL (>= 3)

URL <https://github.com/mkoohafkan/cimir>

BugReports <https://github.com/mkoohafkan/cimir/issues>

Depends R (>= 3.4)

Imports curl (>= 4.3), glue (>= 1.3), stringr (>= 1.4), dplyr (>= 0.8), tidyr (>= 1.0), jsonlite (>= 1.6), purrr (>= 0.3), rlang (>= 0.4)

Encoding UTF-8

LazyData true

Suggests knitr (>= 1.21), rmarkdown (>= 1.11)

VignetteBuilder knitr

RoxygenNote 7.0.2

NeedsCompilation no

Author Michael Koohafkan [aut, cre]

Maintainer Michael Koohafkan <michael.koohafkan@gmail.com>

Repository CRAN

Date/Publication 2020-01-22 22:00:10 UTC

R topics documented:

cimir	2
cimis_compass_to_degrees	3
cimis_data	3

cimis_degrees_to_compass	5
cimis_flags	6
cimis_format_location	6
cimis_items	7
cimis_split_query	8
cimis_station	9
cimis_to_datetime	10
set_key	10

Index	12
--------------	-----------

cimir	<i>cimir: Interface to CIMIS</i>
-------	----------------------------------

Description

This package provides an R interface to the **California Irrigation Management Information System (CIMIS) Web API**. In order to use this package, you will need to **create a CIMIS account** and request a web services AppKey.

Package options

cimir uses the following `options()` to configure behavior:

- `cimir.appkey`: The CIMIS AppKey to use for queries.
- `cimir.timeout`: The maximum time to wait for a response from the CIMIS Web API.

Alternatively, the CIMIS App Key can be saved to an environment variable `CIMIS_APPKEY`.

Author(s)

Maintainer: Michael Koohafkan <michael.koohafkan@gmail.com>

See Also

Useful links:

- <https://github.com/mkoohafkan/cimir>
- Report bugs at <https://github.com/mkoohafkan/cimir/issues>

`cimis_compass_to_degrees`*Compass Direction To Degrees*

Description

Convert the Compass direction labels to degrees.

Usage

```
cimis_compass_to_degrees(x)
```

Arguments

x	A vector of compass directions, i.e. the data item labels "DayWindNnw", "Day-WindSse", etc. Recognized directions are North-northeast (NNE), East-northeast (ENE), East-southeast (ESE), South-southeast (SSE), South-southwest (SSW), West-southwest (WSW), West-northwest (WNW), and North-northwest (NNW).
---	---

Value

A numeric vector of degrees corresponding to the middle azimuth of the corresponding compass direction.

See Also

[cimis_degrees_to_compass\(\)](#)

Examples

```
cimis_compass_to_degrees("day-wind-nne")  
cimis_compass_to_degrees(c("SSE", "SSW", "wsw", "Wnw", "nnw"))
```

`cimis_data`*Query CIMIS Data*

Description

Query CIMIS data using the Web API.

Usage

```

cimis_data(
  targets,
  start.date,
  end.date,
  items,
  measure.unit = c("E", "M"),
  prioritize.SCS = TRUE
)

```

Arguments

targets	geographies or weather stations of interest. This parameter may specify one or many stations, zip codes, coordinates, or street addresses; however, you are not allowed to mix values from different categories. This means the targets parameter must contain only stations, only zip codes, only coordinates, or only street addresses. You will receive an error if you attempt to mix different category types. The formats are accepted: <ul style="list-style-type: none"> • A comma delimited list of WSN station numbers • A comma delimited list of California zip codes • A semicolon delimited list of decimal - degree coordinates • A semicolon delimited list of street addresses
start.date	Specifies the start date. The data format is "yyyy-mm-dd".
end.date	Specifies the end date. The data format is "yyyy-mm-dd".
items	specifies one or more comma-delimited data elements to include in your response. See <code>data_items()</code> for a complete list of possible data element values. Default: day-asce-eto, day-precip, day-sol-rad-avg, day-vap-pres-avg, day-air-tmp-max, day-air-tmp-min, day-air-tmp-avg, day-rel-hum-max, day-rel-hum-min, day-rel-hum-avg, day-dew-pnt, day-wind-sp-avg, day-wind-run, day-soil-tmp-avg.
measure.unit	The unit of measure may be either "E" for English units or "M" for metric units. The value of this parameter will affect data values in the response. For example, designating English units will result in temperature values being returned in Fahrenheit rather than Celsius.
prioritize.SCS	This parameter is relevant only when the targets parameter contains zip code(s). If TRUE, the Spatial CIMIS System (SCS) will be used as the preferred data provider.

Value

A tibble object.

Examples

```

if(is_key_set()) {
  cimis_data(targets = 170, start.date = Sys.Date() - 4,
    end.date = Sys.Date() - 1)
}

```

```
}
```

`cimis_degrees_to_compass`*Degrees to Compass Direction*

Description

Convert decimal degrees to Compass direction.

Usage

```
cimis_degrees_to_compass(x)
```

Arguments

`x` A vector of directions in decimal degrees.

Details

Degrees are labeled with their corresponding Primary InterCardinal compass direction, following the convention of the CIMIS daily wind data items.

Value

A factor vector of compass directions.

See Also

[cimis_compass_to_degrees\(\)](#)

Examples

```
cimis_degrees_to_compass(c(30, 83, 120, 140, 190, 240, 300, 330))  
cimis_degrees_to_compass(cimis_compass_to_degrees(c("NNE", "ENE", "ESE",  
"SSE", "SSW", "WSW", "WNW", "NNW")))
```

cimis_flags *CIMIS Data Flags*

Description

List CIMIS data quality control flags.

Usage

```
cimis_flags(type = c("Severe", "Informative"), period = "Current")
```

Arguments

type The type of data flag, i.e. "Severe" or "Informative".
period The Time period that data was collected, i.e. "Current" or "Former" (pre-1995).

Value

a dataframe of data flags.

See Also

[CIMIS Data Overview - Quality Control](#)

Examples

```
cimis_flags()  
cimis_flags("Informative")  
cimis_flags("Severe", period = "Former")
```

cimis_format_location *Format CIMIS Station Location*

Description

Format the latitude and longitude of station in Decimal Degrees (DD) or Hour Minutes Seconds (HMS).

Usage

```
cimis_format_location(d, format = c("DD", "HMS"))
```

Arguments

d	A data frame of CIMIS data results.
format	The format to use, either Decimal Degrees ("DD") or Hour Minutes Seconds ("HMS").

Value

The data frame, with a new "Latitude" and "Longitude" columns replacing the "HmsLatitude" and "HmsLongitude" columns.

Examples

```
if(is_key_set()) {  
  d = cimis_station(170)  
  cimis_format_location(d, "DD")  
  cimis_format_location(d, "HMS")  
}
```

cimis_items

CIMIS Data Items

Description

List CIMIS data items.

Usage

```
cimis_items(type = c("Daily", "Hourly"))
```

Arguments

type	The type of data item, i.e. "Daily" or "Hourly".
------	--

Value

a dataframe of data items.

Examples

```
cimis_items()
```

cimis_split_query *Split CIMIS Query*

Description

Split a large CIMIS query into multiple smaller queries based on a time interval.

Usage

```
cimis_split_query(targets, start.date, end.date, items, max.records = 1750L)
```

Arguments

targets	geographies or weather stations of interest. This parameter may specify one or many stations, zip codes, coordinates, or street addresses; however, you are not allowed to mix values from different categories. This means the targets parameter must contain only stations, only zip codes, only coordinates, or only street addresses. You will receive an error if you attempt to mix different category types. The formats are accepted: <ul style="list-style-type: none"> • A comma delimited list of WSN station numbers • A comma delimited list of California zip codes • A semicolon delimited list of decimal - degree coordinates • A semicolon delimited list of street addresses
start.date	Specifies the start date. The data format is "yyyy-mm-dd".
end.date	Specifies the end date. The data format is "yyyy-mm-dd".
items	specifies one or more comma-delimited data elements to include in your response. See <code>data_items()</code> for a complete list of possible data element values. Default: day-asce-eto, day-precip, day-sol-rad-avg, day-vap-pres-avg, day-air-tmp-max, day-air-tmp-min, day-air-tmp-avg, day-rel-hum-max, day-rel-hum-min, day-rel-hum-avg, day-dew-pnt, day-wind-spд-avg, day-wind-run, day-soil-tmp-avg.
max.records	The maximum number of records returned by a query. The default value is the the maximum data limit allowed by the CIMIS Web API (1,750 records).

Details

Queries are not split by targets or items, i.e. each resulting query will include all targets and items.

Value

A data frame with columns "targets", "start.date", "end.date", and "items".

Examples

```
cimis_split_query(170, "2000-01-01", "2010-12-31", "day-air-tmp-avg")
cimis_split_query(c(149, 170), "2018-01-01", "2018-12-31",
  c("day-air-tmp-avg", "hly-air-tmp", "hly-rel-hum"))
```

cimis_station	<i>Query CIMIS Station Metadata</i>
---------------	-------------------------------------

Description

Query CIMIS station metadata.

Usage

```
cimis_station(station)
cimis_spatial_zipcode(zipcode)
cimis_zipcode(zipcode)
```

Arguments

station	The station ID. If missing, metadata for all stations is returned.
zipcode	The (spatial) zip code. If missing, metadata for all stations is returned.

Value

A tibble object.

Examples

```
if(is_key_set()) {
  cimis_station()
  cimis_zipcode()
  cimis_spatial_zipcode()
}
```

cimis_to_datetime *To Datetime*

Description

Collapse The Date and Hour columns to a single DateTime Column.

Usage

```
cimis_to_datetime(d)
```

Arguments

d A data frame of CIMIS data results.

Details

According to the [CIMIS Report FAQs](#), all CIMIS data is based on Pacific Standard Time (PST).

Value

The data frame, with a new "Datetime" column replacing the "Date" and "Hour" columns.

Examples

```
if(is_key_set()) {  
  d = cimis_data(targets = 170, start.date = Sys.Date() - 4,  
    end.date = Sys.Date() - 1, items = "hly-air-tmp")  
  cimis_to_datetime(d)  
}
```

set_key *Specify CIMIS API key*

Description

Enter your CIMIS AppKey for web API data access.

Usage

```
set_key(key = NULL)
```

```
remove_key()
```

```
is_key_set()
```

`set_key`

11

Arguments

`key` A CIMIS AppKey.

Examples

```
## Not run:  
set_key("YOUR-APP-KEY")  
is_key_set()  
remove_key()
```

```
## End(Not run)
```

Index

cimir, [2](#)
cimir-package (cimir), [2](#)
cimis_compass_to_degrees, [3](#)
cimis_compass_to_degrees(), [5](#)
cimis_data, [3](#)
cimis_degrees_to_compass, [5](#)
cimis_degrees_to_compass(), [3](#)
cimis_flags, [6](#)
cimis_format_location, [6](#)
cimis_items, [7](#)
cimis_spatial_zipcode (cimis_station), [9](#)
cimis_split_query, [8](#)
cimis_station, [9](#)
cimis_to_datetime, [10](#)
cimis_zipcode (cimis_station), [9](#)

is_key_set (set_key), [10](#)

options(), [2](#)

remove_key (set_key), [10](#)

set_key, [10](#)