

Package ‘citr’

August 19, 2019

Type Package

Title 'RStudio' Add-in to Insert Markdown Citations

Description Functions and an 'RStudio' add-in that search 'Bib(La)TeX'-files or 'Zotero' libraries (via the 'Better BibTeX' plugin) to insert formatted Markdown citations into the current document.

Version 0.3.2

Date 2019-09-15

URL <https://github.com/crsh/citr>

BugReports <https://github.com/crsh/citr/issues>

Depends R (>= 3.0.0)

Imports RefManageR (>= 0.14.2), yaml (>= 2.1.13), rstudioapi (>= 0.6), miniUI (>= 0.1.1), shiny (>= 0.13.2), shinyjs (>= 1.0), assertthat (>= 0.1), methods (>= 3.0.0), curl (>= 1.1), httr (>= 1.3.1)

Suggests testthat (>= 1.0.2)

License MIT + file LICENSE

Encoding UTF-8

LazyData TRUE

RoxygenNote 6.1.0

NeedsCompilation no

Author Frederik Aust [aut, cre] (<<https://orcid.org/0000-0003-4900-788X>>), Yihui Xie [ctb], Robin Lovelace [ctb], Garrick Aden-Buie [ctb]

Maintainer Frederik Aust <frederik.aust@uni-koeln.de>

Repository CRAN

Date/Publication 2019-08-19 09:10:02 UTC

R topics documented:

| | |
|-----------------------------------|---|
| insert_citation | 2 |
| load_betterbiblatex_bib | 3 |
| md_cite | 4 |
| md_cite_zotero | 5 |
| query_bib | 6 |
| tidy_bib_file | 7 |

Index

8

| | |
|-----------------|---|
| insert_citation | <i>Invoke RStudio add-in to insert Markdown citations</i> |
|-----------------|---|

Description

Invoke RStudio add-in to insert Markdown citations

Usage

```
insert_citation(bib_file = getOption("citr.bibliography_path"),
  use_betterbiblatex = getOption("citr.use_betterbiblatex"),
  betterbiblatex_format = getOption("citr.betterbiblatex_format"),
  encoding = getOption("citr.encoding"))
```

Arguments

| | |
|-----------------------|---|
| bib_file | Character. Path to Bib(La)TeX-file. See details. |
| use_betterbiblatex | Logical. If use_betterbiblatex = TRUE references are imported from Zotero/Juris-M. |
| betterbiblatex_format | Character. Bibliography format to export from Zotero/Juris-M. Can be either "bibtex" or "biblatex". Ignored if use_betterbiblatex = FALSE. Requires that the Better BibTeX is installed and Zotero/Juris-M is running. |
| encoding | Character. Encoding of the Bib(La)TeX-file. |

Details

The path to the Bib(La)TeX-file can be set in the global options and is set to `./references.bib` when the package is loaded. Once the path is changed in the RStudio addin, the global option is updated. If `use_betterbiblatex` = TRUE references are imported from Zotero/Juris-M rather than from the Bib(La)TeX-file. The Bib(La)TeX-file is then updated to include the inserted reference.

If `insert_citation` is called while the focus is on a R Markdown document, which includes a YAML front matter with paths to one or more bibliography files, `bib_file` is ignored. Instead the file(s) from the YAML front matter are used.

The addin caches bibliographies to avoid unnecessary hard drive access. If the specified bibliography path or the file paths in the YAML header change the files are reloaded. To manually reload a bibliography at an unchanged location click the action link.

Value

Inserts selected Markdown citation(s) at current location.

Examples

```
## Not run:  
insert_citation()  
  
## End(Not run)
```

```
load_betterbiblatex_bib  
Load bibliography from Zotero
```

Description

Load bibliography from Zotero

Usage

```
load_betterbiblatex_bib(encoding, betterbiblatex_format = "bibtex",  
                        exclude_betterbiblatex_library = NULL, increment_progress = FALSE)
```

Arguments

| | |
|--------------------------------|---|
| encoding | Character. Encoding of the Bib(La)TeX-file. |
| betterbiblatex_format | Character. Bibliography format to export from Zotero/Juris-M. Can be either "bibtex" or "biblatex". Ignored if use_betterbiblatex = FALSE. Requires that the Better BibTeX is installed and Zotero/Juris-M is running. |
| exclude_betterbiblatex_library | Character. A vector of Zotero/Juris-M library names not to query. |
| increment_progress | logical switch which will use the shiny function incProgress when TRUE. FALSE by default. |

Examples

```
## Not run:  
b <- load_betterbiblatex_bib(encoding = "UTF-8")  
  
## End(Not run)
```

md_cite*Insert citation in Markdown format*

Description

Look up entries in bibliography and insert citation in Markdown format if exactly one match is returned.

Usage

```
md_cite(x, in_paren = TRUE,
        bib_file = getOption("citr.bibliography_path"), cache = TRUE,
        use_betterbiblatex = getOption("citr.use_betterbiblatex"),
        encoding = getOption("citr.encoding"))
```

Arguments

| | |
|---------------------------------|--|
| <code>x</code> | Character. Search terms used to filter bibliography (by author, year, title, and journal fields); Regex is supported. |
| <code>in_paren</code> | Logical. Determines if citation is in parentheses. |
| <code>bib_file</code> | Character. Path to Bib(La)TeX-file. See details. |
| <code>cache</code> | Logical. If <code>cache = TRUE</code> cached bibliography is used, if available. If <code>cache = FALSE</code> bibliography is re-imported on every function call. |
| <code>use_betterbiblatex</code> | Logical. If <code>use_betterbiblatex = TRUE</code> references are imported from Zotero/Juris-M. |
| <code>encoding</code> | Character. Encoding of the Bib(La)TeX-file. |

Details

The path to the BibTeX-file can be set in the global options and is set to `references.bib` when the package is loaded. Once the path is changed in the RStudio addin, the global option is updated. If `use_betterbiblatex = TRUE` references are imported from Zotero/Juris-M rather than from the Bib(La)TeX-file. The Bib(La)TeX-file is then updated to include the inserted reference.

Value

If the bibliography contains exactly one match the formatted citation is returned, otherwise returns `NULL`. `md_cite` returns an in-text citation ("@foo2016"), `md_cite` returns an in-parenthesis citation ("[@foo2016]").

See Also

[insert_citation](#)

Examples

```
## Not run:  
md_cite("foo 2016", bib_file = "references.bib")  
  
## End(Not run)
```

md_cite_zotero

Insert citation in Markdown format from Zotero

Description

Look up entries in Zotero database and insert citation in Markdown format.

Usage

```
md_cite_zotero(in_paren = TRUE)
```

Arguments

in_paren Logical. Determines if citation is in parentheses.

Details

The path to the Bib(La)TeX-file can be set in the global options and is set to `references.bib` when the package is loaded. Once the path is changed in the RStudio addin, the global option is updated.

Value

If the bibliography contains exactly one match the formatted citation is returned, otherwise returns `NULL`. `md_cite` returns an in-text citation ("@foo2016"), `md_cite` returns an in-parenthesis citation ("[@foo2016]").

See Also

[insert_citation](#)

Examples

```
## Not run:  
md_cite_zotero()  
  
## End(Not run)
```

query_bib*Query bibliography***Description**

Search entries in a bibliography.

Usage

```
query_bib(x, bib_file = getOption("citr.bibliography_path"),
           cache = TRUE,
           use_betterbiblatex = getOption("citr.use_betterbiblatex"),
           betterbiblatex_format = getOption("citr.betterbiblatex_format"),
           exclude_betterbiblatex_library = getOption("citr.exclude_betterbiblatex_library"),
           encoding = getOption("citr.encoding"))
```

Arguments

| | |
|---|---|
| <code>x</code> | Character. Search terms used to filter bibliography (by author, year, title, and journal fields); Regex is supported. |
| <code>bib_file</code> | Character. Path to Bib(La)TeX-file. See details. |
| <code>cache</code> | Logical. If <code>cache = TRUE</code> cached bibliography is used, if available. If <code>cache = FALSE</code> bibliography is re-imported on every function call. |
| <code>use_betterbiblatex</code> | Logical. If <code>use_betterbiblatex = TRUE</code> references are imported from Zotero/Juris-M. |
| <code>betterbiblatex_format</code> | Character. Bibliography format to export from Zotero/Juris-M. Can be either "bibtex" or "biblatex". Ignored if <code>use_betterbiblatex = FALSE</code> . Requires that the Better BibTeX is installed and Zotero/Juris-M is running. |
| <code>exclude_betterbiblatex_library</code> | Character. A vector of Zotero/Juris-M library names not to query. |
| <code>encoding</code> | Character. Encoding of the Bib(La)TeX-file. |

Details

The path to the BibTeX-file can be set in the global options and is set to `references.bib` when the package is loaded. Once the path is changed in the RStudio addin, the global option is updated. If `use_betterbiblatex = TRUE` references are imported from Zotero/Juris-M rather than from the Bib(La)TeX-file. The Bib(La)TeX-file is then updated to include the inserted reference.

Value

Returns list of class **BibEntry** including all matching bibliography entries.

See Also

[md_cite](#), [insert_citation](#)

tidy_bib_file *Tidy bibliography file*

Description

Removes duplicate and unneeded entries from a Bib(La)Tex-file.

Usage

```
tidy_bib_file(rmd_file, messy_bibliography, file = NULL,  
encoding = getOption("citr.encoding"))
```

Arguments

| | |
|---------------------------------|--|
| <code>rmd_file</code> | Character. One or more paths to the R Markdown files that use the messy bibliography file. |
| <code>messy_bibliography</code> | Character. Path to the messy bibliography file. |
| <code>file</code> | Character. Path and name for the to-be-created tidy bibliography. If <code>NULL</code> the messy bibliography is replaced. |
| <code>encoding</code> | Character. The name of the encoding to be assumed. See the connection . |

Examples

```
NULL
```

Index

BibEntry, 6
connection, 7
insert_citation, 2, 4, 5, 7
load_betterbiblatex_bib, 3
md_cite, 4, 7
md_cite_zotero, 5
query_bib, 6
tidy_bib_file, 7