

# Package ‘dann’

March 14, 2020

**Type** Package

**Title** Discriminant Adaptive Nearest Neighbor Classification

**Version** 0.2.0

**Author** Greg McMahan

**Maintainer** Greg McMahan <gmcmacran@gmail.com>

**Description** Discriminant Adaptive Nearest Neighbor Classification is a variation of k nearest neighbors where the neighborhood is elongated along class boundaries. This package implements dann and sub\_dann from Hastie (1995) <[https://web.stanford.edu/~hastie/Papers/dann\\_IEEE.pdf](https://web.stanford.edu/~hastie/Papers/dann_IEEE.pdf)>.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Imports** MASS (>= 7.3), stats (>= 3.5.3), tibble (>= 2.1.1), ggplot2 (>= 3.1.1), stringr (>= 1.4.0), purrr (>= 0.3.2), rlang (>= 0.3.4), fpc (>= 2.1-11.1), Rcpp (>= 1.0.1)

**RoxygenNote** 6.1.1

**Suggests** testthat (>= 2.0.1), knitr (>= 1.22), rmarkdown (>= 1.18), covr (>= 3.2.1), mlbench (>= 2.1-1), dplyr (>= 0.8.0.1), magrittr (>= 1.5),

**VignetteBuilder** knitr

**LinkingTo** Rcpp, RcppArmadillo

**NeedsCompilation** yes

**Repository** CRAN

**Date/Publication** 2020-03-14 05:20:02 UTC

## R topics documented:

dann . . . . .	2
graph_eigenvalues . . . . .	3
sub_dann . . . . .	5

<b>Index</b>	<b>8</b>
--------------	----------

---

dann

*Discriminant Adaptive Nearest Neighbor Classification*


---

## Description

Discriminant Adaptive Nearest Neighbor Classification

## Usage

```
dann(xTrain, yTrain, xTest, k = 5,
     neighborhood_size = max(floor(nrow(xTrain)/5), 50), epsilon = 1,
     probability = FALSE)
```

## Arguments

xTrain	Train features. Something easily converted to a numeric matrix. Generally columns should have mean zero and standard deviation one beforehand.
yTrain	Train classes. Something easily converted to a numeric vector.
xTest	Test features. Something easily converted to a numeric matrix. Generally columns should be centered and scaled according to xTrain beforehand.
k	The number of data points used for final classification.
neighborhood_size	The number of data points used to calculate between and within class covariance.
epsilon	Diagonal elements of a diagonal matrix. 1 is the identity matrix.
probability	Should probabilities instead of classes be returned?

## Details

This is an implementation of Hastie and Tibshirani's [Discriminant Adaptive Nearest Neighbor Classification publication](#).. The code is a port of Christopher Jenness's python [implementation](#).

## Value

A numeric vector containing predicted class or a numeric matrix containing class probabilities.

## Examples

```
library(dann)
library(mlbench)
library(magrittr)
library(dplyr)
library(ggplot2)

#####
# Circle Data
```

```
#####  
set.seed(1)  
train <- mlbench.circle(300, 2) %>%  
  tibble::as_tibble()  
colnames(train) <- c("X1", "X2", "Y")  
  
ggplot(train, aes(x = X1, y = X2, colour = Y)) +  
  geom_point() +  
  labs(title = "Train Data")  
  
xTrain <- train %>%  
  select(X1, X2) %>%  
  as.matrix()  
  
yTrain <- train %>%  
  pull(Y) %>%  
  as.numeric() %>%  
  as.vector()  
  
test <- mlbench.circle(100, 2) %>%  
  tibble::as_tibble()  
colnames(test) <- c("X1", "X2", "Y")  
  
ggplot(test, aes(x = X1, y = X2, colour = Y)) +  
  geom_point() +  
  labs(title = "Test Data")  
  
xTest <- test %>%  
  select(X1, X2) %>%  
  as.matrix()  
  
yTest <- test %>%  
  pull(Y) %>%  
  as.numeric() %>%  
  as.vector()  
  
dannPreds <- dann(  
  xTrain = xTrain, yTrain = yTrain, xTest = xTest,  
  k = 3, neighborhood_size = 50, epsilon = 1,  
  probability = FALSE  
)  
mean(dannPreds == yTest) # An accurate model.  
  
rm(train, test)  
rm(xTrain, yTrain)  
rm(xTest, yTest)  
rm(dannPreds)
```

**Description**

A helper for sub\_dann

**Usage**

```
graph_eigenvalues(xTrain, yTrain,
  neighborhood_size = max(floor(nrow(xTrain)/5), 50), weighted = FALSE,
  sphere = "mcd")
```

**Arguments**

xTrain	Train features. Something easily converted to a numeric matrix.
yTrain	Train classes. Something easily converted to a numeric vector.
neighborhood_size	The number of data points used to calculate between and within class covariance.
weighted	weighted argument to ncoord. See <a href="#">ncoord</a> for details.
sphere	sphere argument to ncoord. See <a href="#">ncoord</a> for details.

**Details**

This function plots the eigenvalues found by [ncoord](#). The user should make a judgement call on how many eigenvalues are large and set sub\_dann's numDim to that number.

**Value**

A ggplot graph.

**Examples**

```
library(dann)
library(mlbench)
library(magrittr)
library(dplyr)

#####
# Circle data with 2 related variables and 5 unrelated variables
#####
set.seed(1)
train <- mlbench.circle(300, 2) %>%
  tibble::as_tibble()
colnames(train)[1:3] <- c("X1", "X2", "Y")

# Add 5 unrelated variables
train <- train %>%
  mutate(
    U1 = runif(300, -1, 1),
    U2 = runif(300, -1, 1),
    U3 = runif(300, -1, 1),
    U4 = runif(300, -1, 1),
```

```

    U5 = runif(300, -1, 1)
  )

xTrain <- train %>%
  select(X1, X2, U1, U2, U3, U4, U5) %>%
  as.matrix()

yTrain <- train %>%
  pull(Y) %>%
  as.numeric() %>%
  as.vector()

# Data suggests a subspace with 2 dimensions. The correct answer.
graph_eigenvalues(
  xTrain = xTrain, yTrain = yTrain,
  neighborhood_size = 50, weighted = FALSE, sphere = "mcd"
)

rm(train)
rm(xTrain, yTrain)

```

---

sub\_dann

*Discriminant Adaptive Nearest Neighbor With Subspace Reduction*


---

## Description

Discriminant Adaptive Nearest Neighbor With Subspace Reduction

## Usage

```

sub_dann(xTrain, yTrain, xTest, k = 5,
  neighborhood_size = max(floor(nrow(xTrain)/5), 50), epsilon = 1,
  probability = FALSE, weighted = FALSE, sphere = "mcd",
  numDim = ncol(xTrain)/2)

```

## Arguments

xTrain	Train features. Something easily converted to a numeric matrix. Generally columns should have mean zero and standard deviation one beforehand.
yTrain	Train classes. Something easily converted to a numeric vector.
xTest	Test features. Something easily converted to a numeric matrix. Generally columns should be centered and scaled according to xTrain beforehand.
k	The number of data points used for final classification.
neighborhood_size	The number of data points used to calculate between and within class covariance.
epsilon	Diagonal elements of a diagonal matrix. 1 is the identity matrix.

probability	Should probabilities instead of classes be returned?
weighted	weighted argument to ncoord. See <a href="#">ncoord</a> for details.
sphere	sphere argument to ncoord. See <a href="#">ncoord</a> for details.
numDim	Dimension of subspace used by dann. See <a href="#">ncoord</a> for details.

## Details

This is an implementation of Hastie and Tibshirani's sub-dann in section 4.1 of [Discriminant Adaptive Nearest Neighbor Classification publication](#). It uses package `fpc`'s `ncoord` to find the subspace. Then calls `dann`.

`dann`'s performance suffers when noise variables are included in the model. Simulations show `sub_dann` will generally be more performant in this scenario. However there is no replacement for good feature selection.

## Value

A numeric vector containing predicted class or a numeric matrix containing class probabilities.

## Examples

```
library(dann)
library(mlbench)
library(magrittr)
library(dplyr)
library(ggplot2)

#####
# Circle data with unrelated variables
#####
set.seed(1)
train <- mlbench.circle(300, 2) %>%
  tibble::as_tibble()
colnames(train)[1:3] <- c("X1", "X2", "Y")

# Add 5 unrelated variables
train <- train %>%
  mutate(
    U1 = runif(300, -1, 1),
    U2 = runif(300, -1, 1),
    U3 = runif(300, -1, 1),
    U4 = runif(300, -1, 1),
    U5 = runif(300, -1, 1)
  )

xTrain <- train %>%
  select(X1, X2, U1, U2, U3, U4, U5) %>%
  as.matrix()

yTrain <- train %>%
  pull(Y) %>%
```

```
as.numeric() %>%
as.vector()

test <- mlbench.circle(100, 2) %>%
  tibble::as_tibble()
colnames(test)[1:3] <- c("X1", "X2", "Y")

# Add 5 unrelated variables
test <- test %>%
  mutate(
    U1 = runif(100, -1, 1),
    U2 = runif(100, -1, 1),
    U3 = runif(100, -1, 1),
    U4 = runif(100, -1, 1),
    U5 = runif(100, -1, 1)
  )

xTest <- test %>%
  select(X1, X2, U1, U2, U3, U4, U5) %>%
  as.matrix()

yTest <- test %>%
  pull(Y) %>%
  as.numeric() %>%
  as.vector()

dannPreds <- dann(
  xTrain = xTrain, yTrain = yTrain, xTest = xTest,
  k = 3, neighborhood_size = 50, epsilon = 1,
  probability = FALSE
)
mean(dannPreds == yTest) # Not a good model

# Data suggests a subspace with 2 dimentions. The correct answer.
graph_eigenvalues(
  xTrain = xTrain, yTrain = yTrain, neighborhood_size = 50,
  weighted = FALSE, sphere = "mcd"
)

subDannPreds <- sub_dann(
  xTrain = xTrain, yTrain = yTrain, xTest = xTest,
  k = 3, neighborhood_size = 50, epsilon = 1,
  probability = FALSE,
  weighted = FALSE, sphere = "classical", numDim = 2
)
# sub_dan does much better when unrelated variables are present.
mean(subDannPreds == yTest)

rm(train, test)
rm(xTrain, yTrain)
rm(xTest, yTest)
rm(dannPreds, subDannPreds)
```

# Index

dann, [2](#)

graph\_eigenvalues, [3](#)

ncoord, [4](#), [6](#)

sub\_dann, [5](#)