

Package ‘datagovsgR’

June 30, 2020

Type Package

Title Calls Real Time APIs from Data Gov Singapore

Version 0.3.2

Author Clinton Wong <cwxy.clinton@gmail.com>

Maintainer Clinton Wong <cwxy.clinton@gmail.com>

Description A wrapper for the Data Gov Singapore developer resources endpoints developer tools, which provide real time and historical information, ranging from carpark availability to weather forecasts. This tools makes the API calls for a given date and time, before returning the relevant information in a data frame. Relevant information can be found here <<https://data.gov.sg/developer>>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 6.1.99.9001

Imports httr, data.table, dplyr, stringr, purrr, curl

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2020-06-30 12:10:03 UTC

R topics documented:

carpark_availability	2
parse_api_date	2
parse_api_output	3
pm25	3
pm25_summary	4
psi	5
psi_summary	5

taxi_availability	6
weather_forecast	7
weather_reading	7

Index	9
--------------	----------

carpark_availability	<i>Carpark Availability</i>
----------------------	-----------------------------

Description

This functions calls upon the carpark availability API from data.gov.sg and processes the returning page.

Usage

```
carpark_availability(date_time = "")
```

Arguments

date_time Defaults to current (SGD) time. Format: YYYY-MM-DDTHH:MM:SS

Value

A dataframe containing the carpark id, type, last update, total lots, and current lots.

Examples

```
carpark_availability()
carpark_availability(date = "2019-06-05T10:10:10")
carpark_availability(date = "2018-12-01T19:32:56")
```

parse_api_date	<i>ParseApiDate</i>
----------------	---------------------

Description

Helper function to check if the date was input correctly before returning a url to be called by the GET function. Also returns an error if the API called can only provide data for a specific date-time, and not date only.

Usage

```
parse_api_date(api, input_date = "", summary)
```

Arguments

api	The api to be called, i.e. api = "environment/air-temperature"
input_date	Defaults to current (SGD) time. Format: YYYY-MM-DDTHH:MM:SS or YYYY-MM-DD
summary	Returns an error if the user inputs a date only time when not supported by the API.

Value

A url to be called by the API.

parse_api_output	<i>ParseApiOutput</i>
------------------	-----------------------

Description

Helper function to extract the content returned from the API. Returns the status code otherwise.

Usage

```
parse_api_output(inputcontent)
```

Arguments

inputcontent	Takes the output of the GET function, runs an error check and returns the parsed output.
--------------	--

Value

The extracted content if not error has occurred. Otherwise, the error message is returned.

pm25	<i>PM2.5</i>
------	--------------

Description

This functions calls upon the PM2.5 API from data.gov.sg and returns a data frame of the different measures of PM2.5 across 5 different areas in Singapore. This data provided by the API is updated hourly from NEA.

Usage

```
pm25(date_time = "")
```

Arguments

date_time Defaults to current (SGD) time. Format: YYYY-MM-DDTHH:MM:SS

Details

Note that this function is different from the 'pm25_summary' function, which returns the PM2.5 measures for a given day.

Value

A dataframe containing various PM2.5 measures across 5 corners of Singapore

Examples

```
pm25()
pm25(date_time = "2019-11-08T17:30:00")
pm25(date_time = "2018-01-04T09:16:17")
```

pm25_summary	<i>PM2.5 Summary</i>
--------------	----------------------

Description

This functions calls upon the PM2.5 API from data.gov.sg and returns a data frame of the different measures of the PM2.5 across 5 different areas in Singapore for each hour. This data provided by the API is updated hourly from NEA.

Usage

```
pm25_summary(date = "")
```

Arguments

date Defaults to current (SGD) time. Format: YYYY-MM-DD

Details

Note that this function is different from the 'pm25' function, which returns the PM2.5 measures for a given date and time.

Value

A dataframe containing various PM2.5 measures across 5 corners of Singapore and time of day. Dependent on the data available, not all results range from 0000 to 2300.

Examples

```
pm25_summary()
pm25_summary(date = "2019-11-08")
pm25_summary(date = "2018-01-04")
```

psi	<i>PSI(PoullutantStandardIndex)</i>
-----	-------------------------------------

Description

This functions calls upon the PSI API from data.gov.sg and returns a data frame of the different measures of the PSI across 5 different areas in Singapores and the overall measure for the given data-time. This data provided by the API is updated hourly.

Usage

```
psi(date_time = "")
```

Arguments

date_time Defaults to current (SGD) time. Format: YYYY-MM-DDTHH:MM:SS

Details

Note that this function is different from the 'PSI_summary' function, which returns the PSI measures for a given day.

Value

A dataframe containing various PSI measures across 5 corners of Singapore

Examples

```
psi()  
psi(date = "2019-11-08T17:30:00")  
psi(date = "2018-01-04T09:16:17")
```

psi_summary	<i>PSI(PoullutantStandardIndex) Summary</i>
-------------	---

Description

This functions calls upon the PSI API from data.gov.sg and returns a data frame of the different measures of the PSI across 5 different areas in Singapores and the overall measure for the given date. This data provided by the API is updated hourly.

Usage

```
psi_summary(date = "")
```

Arguments

date Defaults to current (SGD) time. Format: YYYY-MM-DDTHH:MM:SS

Details

Note that this function is different from the 'PSI' function, which returns the PSI measures for a given date-time.

Value

A dataframe containing various PSI measures across 5 corners of Singapore and time of day. Dependent on the data available, not all results range from 0000 to 2300.

Examples

```
psi_summary()  
psi_summary(date = "2019-11-08")  
psi_summary(date = "2018-01-04")
```

taxi_availability	<i>Taxi Availability</i>
-------------------	--------------------------

Description

This functions calls upon the taxi availability API from data.gov.sg and returns a data frame of the locations of all available taxis.

Usage

```
taxi_availability(date_time = "")
```

Arguments

date_time Defaults to current (SGD) time. Format: YYYY-MM-DDTHH:MM:SS

Value

A dataframe containing the longitude and latitude values of available taxis.

Examples

```
taxi_availability()  
taxi_availability(date = "2019-08-07T09:30:00")  
taxi_availability(date = "2018-06-05T13:45:00")
```

weather_forecast	<i>Weather Forecast</i>
------------------	-------------------------

Description

This functions calls upon the weather forecast API from data.gov.sg and returns a data frame containing different metrics of the forecast. 2-hour, 24-hour and 4-day forecasts are available. This data provided by the API is updated half-hourly.

Usage

```
weather_forecast(date_time = "", forecast = "2-hour")
```

Arguments

date_time	Defaults to current (SGD) time. Format: YYYY-MM-DDTHH:MM:SS
forecast	Defaults to "2-hour". Also available for "24-hour" and "4-day"

Value

A dataframe the forecast for a given date and time, and forecast period.

Examples

```
weather_forecast()
weather_forecast(date = "2019-11-08T17:30:00", forecast = "24-hour")
weather_forecast(date = "2018-01-04T09:16:17", forecast = "4-day")
```

weather_reading	<i>Weather Reading</i>
-----------------	------------------------

Description

This functions calls upon the weather reading API from data.gov.sg and returns a list containing the air temperature, rainfall, relative humidity, wind direction and speed across Singapore. Data is updated every 5 minutes for the rainfall API, and every half minute for the other 4 API from NEA.

Usage

```
weather_reading(date_time = "", simplify = FALSE)
```

Arguments

date_time	Defaults to current (SGD) time. Format: YYYY-MM-DDTHH:MM:SS
simplify	Defaults to FALSE. Otherwise, simplify = TRUE would return a data frame where all 5 metrics are joined according to weather stations, but return several NAs, as most weather stations collect rainfall data only.

Details

This API takes slightly longer than the other APIs in the package as 5 APIs are wrapped within this function.

Value

A dataframe containing various weather readings from weather stations

Examples

```
weather_reading()  
weather_reading(date = "2019-11-08T17:30:00")  
weather_reading(date = "2018-01-04T09:16:17", simplify = TRUE)
```

Index

- * **PM2.5**
 - pm25, 3
 - pm25_summary, 4
- * **PSI**
 - psi, 5
 - psi_summary, 5
- * **carpark**
 - carpark_availability, 2
- * **taxi**
 - taxi_availability, 6
- * **weather**
 - weather_forecast, 7
 - weather_reading, 7

carpark_availability, 2

parse_api_date, 2

parse_api_output, 3

pm25, 3

pm25_summary, 4

psi, 5

psi_summary, 5

taxi_availability, 6

weather_forecast, 7

weather_reading, 7