

Package ‘discourseGT’

February 17, 2020

Type Package

Title Analyze Group Patterns using Graph Theory in Educational Settings

Version 1.0.0

Date 2020-02-05

Description Analyzes group patterns using discourse analysis data with graph theory mathematics. Takes the order of which individuals talk and converts it to a network edge and weight list. Returns the density, centrality, centralization, and subgroup information for each group. Based on the analytical framework laid out in Chai et al. (2019) <doi:10.1187/cbe.18-11-0222>.

License MIT + file LICENSE

LazyData true

Encoding UTF-8

Depends R (>= 2.10)

Suggests sna

RoxygenNote 7.0.0

Imports igraph, ggpubr, GGally, network, ggplot2

NeedsCompilation no

Author Albert Chai [aut],
Andrew Lee [aut],
Joshua Le [aut, cre],
Stanley Lo [aut]

Maintainer Joshua Le <jp1038@ucsd.edu>

Repository CRAN

Date/Publication 2020-02-17 15:00:06 UTC

R topics documented:

| | |
|---------------------------|---|
| attributeData | 2 |
| coreNetAnalysis | 3 |

| | |
|--------------------------------|----|
| discourseGT | 3 |
| edgelist_raw | 4 |
| graphicalPlot | 4 |
| plotGraphs | 5 |
| plotGraphs2 | 6 |
| plotNGTData | 7 |
| prepareGraphs | 8 |
| run_all | 9 |
| sampleData1 | 10 |
| subgroupsNetAnalysis | 11 |
| summaryNet | 11 |
| tabulate_edges | 12 |
| writeData | 13 |

| | |
|--------------|-----------|
| Index | 14 |
|--------------|-----------|

| | |
|---------------|------------------------------|
| attributeData | <i>Sample Attribute Data</i> |
|---------------|------------------------------|

Description

A data set that sample attribute data to complement Sample Data 1. This data was randomly generated. This data set is for students who are currently taking a STEM course at a major university. 10 students are in this sample study.

Usage

```
attributeData
```

Format

A data frame with 10 rows with 12 variables

node Student identifier in the group

gender Gender of student

ethnicity Ethnicity of student

current_gpa Current overall GPA of student

first_generation If the student is a first generation standing

stem_major If student is in a STEM major

major Major of the student

course_reason Reasons to why student is taking the course

class_level Current class standing at the university

number_prior_ap Number of prior AP courses taken

residency Current residency of the student

sat_score SAT score for admission ...

`coreNetAnalysis`*Run Graphical Analysis Core Parameters*

Description

Analyzes the graphs with the core parameters, such as number of edges and nodes, density, average degree, centrality, and modularity

Usage

```
coreNetAnalysis(ginp)
```

Arguments

`ginp` The prepared graph object from `prepareGraphs` function

Value

Gives the edge and weighted edge counts, number of nodes, density, degree (averages), memberships, modularity, centrality, articulation points, and strong/weak plots as a list object

Examples

```
df <- sampleData1
prepNet <- tabulate_edges(df, iscsvfile = FALSE)
baseNet <- prepareGraphs(prepNet, project_title = "Sample Data 1",
  directedNet = TRUE, selfInteract = FALSE, weightedGraph = TRUE)

coreNetAnalysis(baseNet)
```

`discourseGT`*discourseGT: A package to analyze groups patterns using graph theory in educational settings*

Description

`discourseGT` is a library that utilizes the various network libraries to produce network analysis in educational settings

| | |
|--------------|---|
| edgelist_raw | <i>Process raw order lists from two column format to edge lists</i> |
|--------------|---|

Description

Takes raw input that is in a 2 column format/question-and-response format and generates an appropriate edge lists in a combined .csv file.

Usage

```
edgelist_raw(input_file, iscsvfile = TRUE)
```

Arguments

| | |
|------------|---|
| input_file | Source of the raw input file. Must be in a .csv format |
| iscsvfile | Sets if the input_file is a csv file or a R data frame object |

Value

Saves the weight and edge lists as a data.frame object or a .csv file to disk.

Examples

```
df <- sampleData1
prepNet <- edgelist_raw(df, iscsvfile = FALSE)
```

| | |
|---------------|--------------------|
| graphicalPlot | <i>Plot Graphs</i> |
|---------------|--------------------|

Description

Plots the graph using the base plot function. To map attributes on the graph use the plotGraphs functions, 1 attribute with 'plotGraphs' or 2 attributes with 'plotGraphs2'.

Usage

```
graphicalPlot(ginp, graph_selection_input = 0, curvedEdgeLines = TRUE)
```

Arguments

ginp The prepared graph object from prepareGraphs function

graph_selection_input The type of graphical projection to be used. Default projection is 0 (Fruchterman Reingold). Selection must be a numeric option from 0-3. Other options include: 1 = Kamada Kawai, 2 = Reingold Tilford, and 3 = Bipartite

curvedEdgeLines Whether the edges between nodes should be curved or straight. Default is curved lines.

Value

Returns graphical plot to disk, if selected, or to R console

Examples

```
df <- sampleData1
prepNet <- tabulate_edges(df, iscsvfile = FALSE)
baseNet <- prepareGraphs(prepNet, project_title = "Sample Data 1",
directedNet = TRUE, selfInteract = FALSE, weightedGraph = TRUE)

#Plot the graph
graphicalPlot(baseNet)
```

plotGraphs

Plots Graphs using ggplot2 with one attribute

Description

Plots graph data using the GGally library and ggnet function while incorporating demographic properties. Use this plot function if you have all demographic data available to plot.

Usage

```
plotGraphs(
  data,
  prop = 20,
  graphmode = "fruchtermanreingold",
  attribute = NULL,
  attribute.label = NULL,
  attribute.node.labels = NULL,
  attribute.nodesize = 10
)
```

Arguments

| | |
|------------------------------------|---|
| <code>data</code> | Data from the prepareGraphs function |
| <code>prop</code> | Rescaling the graph edge sizes for the plot |
| <code>graphmode</code> | Type of graphical projection to use. Default is Fruchterman Reingold. Refer to <code>plot.layout</code> for the various available options |
| <code>attribute</code> | Mapping to the attribute information, can be list or column in data frame |
| <code>attribute.label</code> | Name of the attribute info (Required) |
| <code>attribute.node.labels</code> | Mapping to the node labels, can be list or column in data frame |
| <code>attribute.nodesize</code> | Size of the nodes. Default will result in size of 10. Can be replaced with custom mapping in list or column in data frame. (Required) |

Examples

```
df <- sampleData1
prepNet <- tabulate_edges(df, iscsvfile = FALSE)
baseNet <- prepareGraphs(prepNet, project_title = "Sample Data 1",
  directedNet = TRUE, selfInteract = FALSE, weightedGraph = TRUE)
attdata <- attributeData
plotGraphs(baseNet, prop = 20, graphmode = "fruchtermanreingold",
  attribute = attdata$gender,
  attribute.label = "Gender",
  attribute.node.labels = attdata$node, attribute.nodesize = 12)
```

plotGraphs2

Plots Graphs using ggplot2 with two attributes

Description

Plots graph data using the GGally library and `ggnet` function while incorporating demographic properties. Use this plot function if you have all demographic data available to plot.

Usage

```
plotGraphs2(
  data,
  prop = 20,
  graphmode = "fruchtermanreingold",
  attribute1 = NULL,
  attribute2 = NULL,
  attribute1.label = "Attribute 1",
  attribute2.label = "Attribute 2",
```

```

    attribute.node.labels = NULL,
    attribute.nodesize = 10
  )

```

Arguments

| | |
|-----------------------|---|
| data | Data from the prepareGraphs function |
| prop | Rescaling the graph edge sizes for the plot |
| graphmode | Type of graphical projection to use. Default is Fruchterman Reingold. Refer to gplot.layout for the various available options |
| attribute1 | Mapping to the attribute 1 information, can be list or column in data frame (Required) |
| attribute2 | Mapping to the attribute 2 information, can be list or column in data frame (Required) |
| attribute1.label | Name of the attribute 1 info (Required) |
| attribute2.label | Name of the attribute 2 info (Required) |
| attribute.node.labels | Mapping to the node labels, can be list or column in data frame (Required) |
| attribute.nodesize | Size of the nodes. Default will result in size of 10. Can be replaced with custom mapping in list or column in data frame. (Required) |

Examples

```

df <- sampleData1
prepNet <- tabulate_edges(df, iscsvfile = FALSE)
baseNet <- prepareGraphs(prepNet, project_title = "Sample Data 1",
  directedNet = TRUE, selfInteract = FALSE, weightedGraph = TRUE)
attdata <- attributeData
plotGraphs2(baseNet, prop = 20, graphmode = "fruchtermanreingold",
  attribute1 = attdata$gender, attribute2 = attdata$ethnicity,
  attribute1.label = "Gender", attribute2.label = "Ethnicity",
  attribute.node.labels = attdata$node, attribute.nodesize = 12)

```

plotNGTData

Plot non-graphical parameters

Description

Creates plots for non-graph theory parameters for episode lengths, questions per hour versus responses per hour, and normalized turn ratio

Usage

```
plotNGTData(data, convoMinutes, iscsvfile = TRUE)
```

Arguments

| | |
|--------------|---|
| data | Original raw input data in ordered question/response 2 column format |
| convoMinutes | Time length of the conversation in the graph in minutes |
| iscsvfile | Sets if the input data file to function is a .csv file or a R data frame object |

Value

Creates a plot returning the questions per hour versus responses per hour, frequency plot of the number of episodes, and normalized turn ratio

Examples

```
df <- sampleData1
plotNGTData(df, convoMinutes = 60, iscsvfile = FALSE)
```

| | |
|---------------|-----------------------|
| prepareGraphs | <i>Prepare Graphs</i> |
|---------------|-----------------------|

Description

Prepares the graphical object from the prepared edge and weight list data frame

Usage

```
prepareGraphs(
  raw_data_input,
  project_title = "",
  directedNet = TRUE,
  selfInteract = FALSE,
  weightedGraph = TRUE
)
```

Arguments

| | |
|----------------|---|
| raw_data_input | The raw edge and weight list processed from the tabulate_edges() function. |
| project_title | The title of the project. |
| directedNet | Sets the graph to be directed. Edges will have a direction. Default is set to Directed. If undirected, edges have no direction |
| selfInteract | Removes self interactions in the graph (such as person 1 to person 1 interactions). Default removes self-interactions. |
| weightedGraph | Graph will add weights to the edges to a set of nodes based on the weight specified on the list. Default allows for weights on the graph. |

Value

Stores the igraph graph object, graph adjacency matrix, edge and weight lists, project title, and user options for directed, self interactions, and weighted to list object.

Examples

```
df <- sampleData1
prepNet <- tabulate_edges(df, iscsvfile = FALSE)
baseNet <- prepareGraphs(prepNet, project_title = "Sample Data 1",
  directedNet = TRUE, selfInteract = FALSE, weightedGraph = TRUE)
```

run_all

*Run functions in discourseGT in bulk***Description**

Allows for all or select functions in the discourseGT package to be run at once in bulk and only the very terminus results are stored, plots and text summary. This function is best used for running multiple sets of graphical plots. The function will automatically save the results of the graphs to your disk by default.

Usage

```
run_all(
  raw_2col_data,
  project_name = "",
  iscsvfile = TRUE,
  directedNet = TRUE,
  selfInteract = FALSE,
  weightedGraph = TRUE,
  plotGraph = NULL,
  graph_selection_input = 0,
  curvedEdge = TRUE,
  subgroups = NULL,
  normalized = NULL,
  reportResults = NULL,
  displayResults = FALSE
)
```

Arguments

| | |
|---------------|--|
| raw_2col_data | Data in the raw 2 column format (usually the question and response format) |
| project_name | Name of the project |
| iscsvfile | Sets if the input file is a .csv file or a R data frame object |
| directedNet | Sets the graph directionality |

| | |
|-----------------------|--|
| selfInteract | Sets the self-interactions permissions |
| weightedGraph | Sets the graph weights |
| plotGraph | Plot the graph data |
| graph_selection_input | Type of graphical projection to use. Default is Fruchterman Reingold. Refer to <code>gplot.layout</code> for the various available options |
| curvedEdge | Whether the edges between nodes should be curved or straight. Default is curved lines. |
| subgroups | Run the subgroups analysis function |
| normalized | Normalize the betweenness centrality values |
| reportResults | Run the summary results of all functions generated, presents in a summary format at end |
| displayResults | Display the summary results of analysis in the console |

Value

Saves output files of the function, plots and text summary, on to the disk. If save option is disabled, function will save results to an data object, if set.

Examples

```
df <- sampleData1
run_all(raw_2col_data = df, project_name = "Sample Data 1", iscsvfile = FALSE,
directedNet = TRUE, selfInteract = FALSE, weightedGraph = TRUE,
plotGraph = TRUE, graph_selection_input = 0, curvedEdge = TRUE,
subgroups = TRUE, normalized = FALSE,
reportResults = TRUE, displayResults = TRUE)
```

sampleData1

Sample Episode Start and Episode Continuation Data (2 Column)

Description

A data set that contains Episode Start (in this case, questions) and Episode Continuation (in this case, responses) data in a 2 column format. This data was randomly generated. Case basis: 10 students in a group discussion questions in a STEM course at a major university.

Usage

```
sampleData1
```

Format

A data frame with 451 rows and 2 variables:

ep_start If participant in the graph has initiated an episode

ep_cont If participant in the graph has raised a response to the previous episode ...

subgroupsNetAnalysis *Runs subgroup analysis on graphs*

Description

Performs a subgroup analysis on the graph

Usage

```
subgroupsNetAnalysis(ginp, raw_input = NULL, normalized = FALSE)
```

Arguments

| | |
|------------|---|
| ginp | The prepared graph object from prepareGraphs function |
| raw_input | The file path of the original .csv file |
| normalized | Normalize the betweenness centrality values |

Value

Saves number of potential cliques, cores, symmetry of the graph, dyads in graphs, node composition in proposed cliques, neighbors adjacent to each node, transitivity (local and global) as a list object

Examples

```
df <- sampleData1
prepNet <- tabulate_edges(df, iscsvfile = FALSE)
baseNet <- prepareGraphs(prepNet, project_title = "Sample Data 1",
  directedNet = TRUE, selfInteract = FALSE, weightedGraph = TRUE)
subgroupsNetAnalysis(baseNet, raw_input = df)
```

summaryNet *Print summary of graph results*

Description

Returns a summary of the processed graph results on console. The initial graph configuration and core analysis is required for this function to work. The other components are optional due to the modular nature of the functions. Data must be stored as a data object.

Usage

```
summaryNet(
  netintconfigData = NULL,
  coreNetAnalysisData = NULL,
  subgroupsNetAnalysisData = NULL,
  display = FALSE
)
```

Arguments

| | |
|--------------------------|---|
| netintconfigData | Data object where the graph configuration data is stored (from 'prepareGraphs') |
| coreNetAnalysisData | Data object where the core analysis data is stored (from 'coreNetAnalysis') |
| subgroupsNetAnalysisData | Data object where subgroup analysis data is stored (from 'subgroupsNetAnalysis') |
| display | Should the output be displayed in the R console? Results are saved as the project name in the initial config data as a text file on disk. |

Value

Prints organized summary of all results of the graph with modular components on console or to .txt file on disk.

Examples

```
df <- sampleData1
prepNet <- tabulate_edges(df, iscsvfile = FALSE)
prepGraphs <- prepareGraphs(prepNet, project_title = "Sample Data 1",
  directedNet = TRUE, selfInteract = FALSE, weightedGraph = TRUE)
coreNet <- coreNetAnalysis(prepGraphs)
subgroup <- subgroupsNetAnalysis(prepGraphs, raw_input = df)
summaryNet(netintconfigData = prepGraphs, coreNetAnalysisData = coreNet,
  subgroupsNetAnalysisData = subgroup, display = TRUE)
```

| | |
|----------------|--|
| tabulate_edges | <i>Process raw order lists from two column format to edge and weight lists</i> |
|----------------|--|

Description

Takes raw input that is in a 2 column format/question-and-response format and generates an appropriate edge and weight lists in a combined .csv file. The weights in this function are determined by the number of occurrences a specific edge, directed or undirected, has occurred in the graph

Usage

```
tabulate_edges(input, iscsvfile = TRUE)
```

Arguments

| | |
|-----------|--|
| input | Input in question-and-response format. Must be a data.frame or file name of a .csv |
| iscsvfile | Sets if the input is a csv file or a R data frame object |

Value

Saves the weight and edge lists as a data.frame object or a .csv file to disk.

Examples

```
df <- sampleData1
tabData <- tabulate_edges(df, iscsvfile = FALSE)
```

| | |
|------------------------|---|
| <code>writeData</code> | <i>Exports graphs and data objects from the package to disk</i> |
|------------------------|---|

Description

Saves information from graphs and data objects created by package. Plots are saved as .tiff at 300 dpi

Usage

```
writeData(project_name, objectfile, dirpath = NULL)
```

Arguments

| | |
|---------------------------|--|
| <code>project_name</code> | Name of the project |
| <code>objectfile</code> | The saved data object data file |
| <code>dirpath</code> | The working directory that the files will be saved to. Path required for write function to work. Current directory, use "." as the dirpath |

Value

Saves the requested object file to disk. Saves graphs or summary information sheets.

Examples

```
attributeData <- attributeData
df <- sampleData1

prepNet <- tabulate_edges(df, iscsvfile = FALSE)
baseNet <- prepareGraphs(prepNet, project_title = "Sample Data 1",
  directedNet = TRUE, selfInteract = FALSE, weightedGraph = TRUE)
NetPlots2 <- plotGraphs2(baseNet, attribute1 = attributeData$ethnicity,
  attribute2 = attributeData$gender, attribute.node.labels = attributeData$node,
  attribute1.label = "Ethnicity", attribute2.label = "Gender")

writeData("Sample Data 1", NetPlots2, dirpath = tempdir())
```

Index

*Topic **datasets**

- attributeData, [2](#)
- sampleData1, [10](#)

- attributeData, [2](#)

- coreNetAnalysis, [3](#)

- discourseGT, [3](#)

- edgelist_raw, [4](#)

- graphicalPlot, [4](#)

- plotGraphs, [5](#)
- plotGraphs2, [6](#)
- plotNGTData, [7](#)
- prepareGraphs, [8](#)

- run_all, [9](#)

- sampleData1, [10](#)
- subgroupsNetAnalysis, [11](#)
- summaryNet, [11](#)

- tabulate_edges, [12](#)

- writeData, [13](#)