

# Package ‘downloadthis’

May 4, 2020

**Title** Implement Download Buttons in 'rmarkdown'

**Version** 0.2.0

**Description** Implement download buttons in HTML output from 'rmarkdown' without the need for 'runtime:shiny'.

**License** MIT + file LICENSE

**URL** <https://github.com/fmmattioni/downloadthis>

**BugReports** <https://github.com/fmmattioni/downloadthis/issues>

**Encoding** UTF-8

**LazyData** true

**Imports** fs, readr, writexl, bsplus, mime, htmltools, base64enc, magrittr, zip

**RoxygenNote** 7.1.0

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Felipe Mattioni Maturana [aut, cre]  
(<<https://orcid.org/0000-0002-4221-6104>>)

**Maintainer** Felipe Mattioni Maturana <[felipe.mattioni@med.uni-tuebingen.de](mailto:felipe.mattioni@med.uni-tuebingen.de)>

**Repository** CRAN

**Date/Publication** 2020-05-04 19:10:02 UTC

## R topics documented:

download_dir . . . . .	2
download_file . . . . .	3
download_link . . . . .	4
download_this . . . . .	5

<b>Index</b>	<b>8</b>
--------------	----------

---

download_dir	<i>Download a directory</i>
--------------	-----------------------------

---

### Description

The path is converted into a .zip file.

### Usage

```
download_dir(
  path,
  output_name,
  button_label = "Download data",
  button_type = c("default", "primary", "success", "info", "warning", "danger"),
  has_icon = TRUE,
  icon = "fa fa-save",
  self_contained = FALSE,
  ...
)
```

### Arguments

path	Path to directory.
output_name	Name of of the output file.
button_label	Character (HTML), button label
button_type	Character, one of the standard Bootstrap types
has_icon	Specify whether to include fontawesome icons in the button label
icon	Fontawesome tag e.g.: "fa fa-save"
self_contained	A boolean to specify whether your HTML output is self-contained. Default to FALSE.
...	attributes (named arguments) and children (unnamed arguments) of the button, passed to <code>htmltools::tag()</code> .

### Value

`htmltools::tag`, `<button>`

### Examples

```
## Not run:
## Directory path as an example
download_dir(
  path = system.file("assets", package = "downloadthis"),
  output_name = "example dir",
  button_label = "Download directory",
  button_type = "success",
```

```

has_icon = TRUE,
icon = "fa fa-save",
self_contained = FALSE
)

## End(Not run)

```

---

download\_file

*Download a local file or multiple files*


---

## Description

In case multiple files are chosen, the files will be converted to a .zip file.

## Usage

```

download_file(
  path,
  output_name,
  button_label = "Download data",
  button_type = c("default", "primary", "success", "info", "warning", "danger"),
  has_icon = TRUE,
  icon = "fa fa-save",
  self_contained = FALSE,
  ...
)

```

## Arguments

path	Path to the file(s). If multiple files are chosen, a vector must be passed to this argument.
output_name	Name of the output file. If not specified, it will take the source file's name if one file is specified. In case of multiple files, the output_name must be specified.
button_label	Character (HTML), button label
button_type	Character, one of the standard Bootstrap types
has_icon	Specify whether to include fontawesome icons in the button label
icon	Fontawesome tag e.g.: "fa fa-save"
self_contained	A boolean to specify whether your HTML output is self-contained. Default to FALSE.
...	attributes (named arguments) and children (unnamed arguments) of the button, passed to <code>htmltools::tag()</code> .

## Value

`htmltools::tag`, `<button>`

## Examples

```
## Not run:
## One file example
download_file(
  path = system.file("assets/css/all.min.css", package = "downloadthis"),
  output_name = "CSS file from downloadthis",
  button_label = "Download css file",
  button_type = "danger",
  has_icon = TRUE,
  icon = "fa fa-save",
  self_contained = FALSE
)

## Multiple files example
path_files <- list.files(
  path = system.file("assets/css", package = "downloadthis"),
  full.names = TRUE
)

download_file(
  path = path_files,
  output_name = "Files from downloadthis",
  button_label = "Download files",
  button_type = "danger",
  has_icon = TRUE,
  icon = "fa fa-save",
  self_contained = FALSE
)

## End(Not run)
```

---

download\_link

*Download file from a web address*

---

## Description

It associates your download button to a web link. This might be an alternative when your file is too big for being handled by `download_this()`.

## Usage

```
download_link(
  link,
  button_label = "Download data",
  button_type = c("default", "primary", "success", "info", "warning", "danger"),
  has_icon = TRUE,
  icon = "fa fa-save",
  self_contained = FALSE,
  ...
)
```

**Arguments**

link	A web address for downloading the file.
button_label	Character (HTML), button label
button_type	Character, one of the standard Bootstrap types
has_icon	Specify whether to include fontawesome icons in the button label
icon	Fontawesome tag e.g.: "fa fa-save"
self_contained	A boolean to specify whether your HTML output is self-contained. Default to FALSE.
...	attributes (named arguments) and children (unnamed arguments) of the button, passed to <code>htmltools::tag()</code> .

**Value**

`htmltools::tag`, `<button>`

**Examples**

```
## Not run:
## Link in Github repo
download_link(
  link = "https://github.com/fmmattioni/downloadthis/raw/master/inst/example/file_1.pdf",
  button_label = "Download pdf file",
  button_type = "danger",
  has_icon = TRUE,
  icon = "fa fa-save",
  self_contained = FALSE
)

## End(Not run)
```

---

download\_this

*Download data frames, lists, or any R object*

---

**Description**

Wrapper around `bsplus::bs_button()` to provide a download button for HTML outputs in R Markdown. Internally, the function writes the file to `tempdir()`, encodes it, and produces the download button. Currently, Internet Explorer does not support downloading embedded files. For downloading links, files, or directories, see `download_link()`, `download_file()`, and `download_dir()`.

**Usage**

```
download_this(
  .data,
  output_name,
  output_extension = c(".csv", ".xlsx", ".rds"),
  button_label = "Download data",
  button_type = c("default", "primary", "success", "info", "warning", "danger"),
  has_icon = TRUE,
  icon = "fa fa-save",
  self_contained = FALSE,
  ...
)
```

**Arguments**

<code>.data</code>	A data frame or (named) list to write to disk. See 'Examples' for more details.
<code>output_name</code>	Name of the output file.
<code>output_extension</code>	Extension of the output file. Currently, <code>.csv</code> , <code>.xlsx</code> , and <code>.rds</code> are supported. If a (named) list is passed to the function, only <code>.xlsx</code> and <code>.rds</code> are supported.
<code>button_label</code>	Character (HTML), button label
<code>button_type</code>	Character, one of the standard Bootstrap types
<code>has_icon</code>	Specify whether to include fontawesome icons in the button label
<code>icon</code>	Fontawesome tag e.g.: "fa fa-save"
<code>self_contained</code>	A boolean to specify whether your HTML output is self-contained. Default to FALSE.
<code>...</code>	attributes (named arguments) and children (unnamed arguments) of the button, passed to <code>htmltools::tag()</code> .

**Value**

`htmltools::tag`, `<button>`

**Warning**

This example will write the `mtcars` dataset to `tempdir()` and produce the download button for the file `mtcars dataset.csv` with the `fa fa-save` icon on the Download data label.

**Examples**

```
## Not run:
# Passing a data frame to the function
mtcars %>%
  download_this(
    output_name = "mtcars dataset",
    output_extension = ".csv",
    button_label = "Download data",
```

```
        button_type = "warning",
        has_icon = TRUE,
        icon = "fa fa-save"
    )

# Passing a list with data frames to the function
list(mtcars, iris) %>%
  download_this(
    output_name = "mtcars and iris datasets",
    output_extension = ".xlsx",
    button_label = "Download data",
    button_type = "warning",
    has_icon = TRUE,
    icon = "fa fa-save"
  )

# Passing a named list with data frames to the function
list('mtcars dataset' = mtcars, 'iris dataset' = iris) %>%
  download_this(
    output_name = "mtcars and iris datasets",
    output_extension = ".xlsx",
    button_label = "Download data",
    button_type = "warning",
    has_icon = TRUE,
    icon = "fa fa-save"
  )

# Passing any R object to the function
vector_example <- 1:10
linear_model <- lm(mpg ~ gear, data = mtcars)

list(mtcars, iris, vector_example, linear_model) %>%
  download_this(
    output_name = "datasets, vector, and linear model",
    output_extension = ".rds",
    button_label = "Download as rds",
    button_type = "warning",
    has_icon = TRUE,
    icon = "fa fa-save"
  )

## End(Not run)
```

# Index

[download\\_dir](#), [2](#)  
[download\\_file](#), [3](#)  
[download\\_link](#), [4](#)  
[download\\_this](#), [5](#)

[tag](#), [2](#), [3](#), [5](#), [6](#)