

Package ‘dtt’

February 19, 2015

Type Package

Title Discrete Trigonometric Transforms

Version 0.1-2

Date 20013-12-30

Author Lukasz Komsta

Maintainer Lukasz Komsta <lukasz.komsta@umlub.pl>

License GPL (>= 2)

URL <http://www.r-project.org>, <http://www.komsta.net/>

Description This package provides functions for 1D and 2D Discrete Cosine Transform (DCT), Discrete Sine Transform (DST) and Discrete Hartley Transform (DHT).

Repository CRAN

Date/Publication 2013-12-30 11:44:32

NeedsCompilation no

R topics documented:

dttd-package	1
dttd	2
mvdttd	3

Index	5
--------------	----------

dttd-package	<i>Discrete Trigonometric Transforms</i>
--------------	--

Description

This package provides functions for 1D and 2D Discrete Cosine Transform (DCT), Discrete Sine Transform (DST) and Discrete Hartley Transform (DHT).

Details

Package: dtt
 Type: Package
 Version: 0.1-1
 Date: 2007-02-25
 License: GPL version 2 or newer.

Author(s)

Maintainer: Lukasz Komsta <luke@novum.am.lublin.pl>

dtt

Discrete Trigonometric Transforms

Description

Performs univariate discrete sine, cosine or Hartley transform.

Usage

```

dtt(x, type = c("dct", "dst", "dht"), variant = 2, inverted = FALSE)
dct(x, variant = 2, inverted = FALSE)
dst(x, variant = 2, inverted = FALSE)
dht(x, inverted = FALSE)

```

Arguments

x	a vector or matrix to be transformed
type	type of transform. Default "dct" is discrete cosine, "dst" is discrete sine and "dht" is discrete Hartley
variant	a transformation variant - 1...4 for DCT-I...DCT-IV or DST-I...DST-IV. Default is DCT-II or DST-II. Ignored when type = "dht"
inverted	if the inverted transform should be performed?

Details

This function transforms a vector of real numbers into a vector of its DCT, DST or DHT components, of the same length.

If the x is a matrix, the transform goes by rows (each row of a result is a transform of corresponding row in x).

The dct, dst and dht functions are simple wrappers for choosing the type by function name.

Value

A transformed vector.

Author(s)

Lukasz Komsta

References

1. N. Ahmed, T. Natarajan, and K. R. Rao, "Discrete Cosine Transform", IEEE Trans. Computers, 90-93, Jan 1974. 2. S. A. Martucci, "Symmetric convolution and the discrete sine and cosine transforms", IEEE Trans. Sig. Processing SP-42, 1038-1051 (1994). 3. R. V. L. Hartley, "A more symmetrical Fourier analysis applied to transmission problems," Proc. IRE 30, 144-150 (1942).

See Also

[mvdtt](#), [fft](#), [mvfft](#)

Examples

```
x=seq(0,20,length=200)
y=x*sin(x)+cos(x)+5*cos(10*x)+rnorm(200,sd=0.1)
plot(y)
z=dct(y); z[151:200]=0; lines(dct(z,inverted=TRUE),col=2);
z=dct(y); z[21:200]=0; lines(dct(z,inverted=TRUE),col=4);
```

mvdtt

2D Discrete Trigonometric Transforms

Description

Performs multivariate (2D) discrete sine, cosine or Hartley transform.

Usage

```
mvdtt(x, type = c("dct", "dst", "dht"), variant = 2, inverted = FALSE)
mvdct(x, variant = 2, inverted = FALSE)
mvdst(x, variant = 2, inverted = FALSE)
mvdht(x, inverted = FALSE)
```

Arguments

x	a matrix to be transformed
type	type of transform. Default "dct" is discrete cosine, "dst" is discrete sine and "dht" is discrete Hartley
variant	a transformation variant - 1...4 for DCT-I...DCT-IV or DST-I...DST-IV. Default is DCT-II or DST-II. Ignored when type = "dht"
inverted	if the inverted transform should be performed?

Details

This function transforms a matrix of real numbers into a matrix of its DCT, DST or DHT components, of the same dimensions. It is done by so-called row-matrix algorithm.

The `mvdct`, `mvdst` and `mvdht` functions are simple wrappers for choosing the type by function name.

Value

A transformed matrix.

Author(s)

Lukasz Komsta

References

1. N. Ahmed, T. Natarajan, and K. R. Rao, "Discrete Cosine Transform", IEEE Trans. Computers, 90-93, Jan 1974. 2. S. A. Martucci, "Symmetric convolution and the discrete sine and cosine transforms", IEEE Trans. Sig. Processing SP-42, 1038-1051 (1994). 3. R. V. L. Hartley, "A more symmetrical Fourier analysis applied to transmission problems," Proc. IRE 30, 144-150 (1942).

See Also

[dtt](#), [fft](#), [mvfft](#)

Examples

```
x = rnorm(100);  
dim(x) = c(10,10);  
x  
mvdct(x)  
mvdct(mvdct(x),inverted=TRUE)
```

Index

*Topic **models**

dtc, 2

mdtc, 3

*Topic **package**

dtc-package, 1

dct (dtc), 2

dht (dtc), 2

dst (dtc), 2

dtc, 2, 4

dtc-package, 1

fft, 3, 4

mdct (mdtc), 3

mdht (mdtc), 3

mdst (mdtc), 3

mdtc, 3, 3

mvfft, 3, 4