

Package ‘easySdcTable’

July 27, 2020

Type Package

Title Easy Interface to the Statistical Disclosure Control Package
‘sdcTable’

Version 0.6.0

Date 2020-07-27

Author Øyvind Langsrud [aut, cre]

Maintainer Øyvind Langsrud <oyl@ssb.no>

Depends SSBtools

Imports sdcTable, shiny, methods

VignetteBuilder knitr

Suggests knitr, rmarkdown, RegSDC, Matrix, testthat (>= 2.1.0)

Description The main function, ProtectTable(), performs table suppression according to a frequency rule with a data set as the only required input. Within this function, protectTable(), protectLinkedTables() or runArgusBatchFile() in package ‘sdcTable’ is called. Lists of level-hierarchy (parameter ‘dimList’) and other required input to these functions are created automatically.

The function, PTgui(), starts a graphical user interface based on the shiny package.

License Apache License 2.0 | file LICENSE

LazyData TRUE

RoxygenNote 7.1.1

Encoding UTF-8

URL <https://github.com/statisticsnorway/easySdcTable>

BugReports <https://github.com/statisticsnorway/easySdcTable/issues>

NeedsCompilation no

Repository CRAN

Date/Publication 2020-07-27 09:10:02 UTC

R topics documented:

EasyData	2
ProtectTable	3
ProtectTable1	8
PTgui	10
PTwrap	12
PTxyz	13
sosialFiktiv	15

Index	16
--------------	-----------

EasyData	<i>Function that returns a dataset</i>
----------	--

Description

Function that returns a dataset

Usage

```
EasyData(dataset, path = NULL)
```

Arguments

dataset	Name of data set within the easySdcTable package
path	When non-NULL the data set is read from "path/dataset.RData"

Value

The dataset

Examples

```
z <- EasyData("sosialFiktiv")
```

ProtectTable	<i>Easy interface to sdcTable: Table suppression according to a frequency rule.</i>
--------------	---

Description

protectTable() or protectLinkedTables() in package 'sdcTable' is run with a data set as the only required input. One (stacked) or several (unstacked) input variables can hold cell counts. Output is on a form similar to input.

Usage

```
ProtectTable(  
  data,  
  dimVar = 1:NCOL(data),  
  freqVar = NULL,  
  protectZeros = TRUE,  
  maxN = 3,  
  method = "SimpleSingle",  
  findLinked = TRUE,  
  total = "Total",  
  addName = FALSE,  
  sep = "_",  
  removeZeros = FALSE,  
  dimList = NULL,  
  groupVarInd = NULL,  
  ind1 = NULL,  
  ind2 = NULL,  
  rowData = NULL,  
  varNames = paste("var", 1:100, sep = ""),  
  split = NULL,  
  border = sep,  
  revBorder = FALSE,  
  freqName = "values",  
  totalFirst = FALSE,  
  numericOrder = TRUE,  
  namesAsInput = TRUE,  
  orderAsInput = TRUE,  
  sortByReversedColumns = FALSE,  
  doUnstack = TRUE,  
  removeTotal = TRUE,  
  singleOutput = NULL,  
  suppression = NA,  
  outFreq = "freq",  
  outSdcStatus = "sdcStatus",  
  outSuppressed = "suppressed",  
  infoAsFrame = FALSE,
```

```

IncProgress = IncDefault,
...
)

```

Arguments

data	data frame
dimVar	The main dimensional variables and additional aggregating variables (name or number).
freqVar	Variable(s) holding counts or NULL in the case of micro data (name or number).
protectZeros	When TRUE empty cells (count=0) is considered sensitive (i.e. same as allowZeros in primarySuppression).
maxN	All cells having counts <= maxN are set as primary suppressed.
method	Parameter method in protectTable , protectLinkedTables or wrapper methods via PTwrap . Gauss is an additional method that is not available in sdcTable. <ul style="list-style-type: none"> • "SIMPLEHEURISTIC": This method is default in protectable. • "OPT", "HITAS", "HYPERCUBE": Other methods in protectable. "HYPERCUBE" is not possible in cases with two linked tables. • "SimpleSingle" (default): "SIMPLEHEURISTIC" with detectSingletons=TRUE when protectZeros=FALSE and "SIMPLEHEURISTIC" with threshold=1 (can be overridden by input) when protectZeros=TRUE. • "Simple": "SIMPLEHEURISTIC" with detectSingletons=FALSE. • "Gauss": GaussSuppression is called with parameters x, candidates, primary and singleton automatically generated. Other parameters (singletonMethod, printInc) can be specified. <p>Alternatively this parameter can be a named list specifying parameters for running tau-argus (see details). See PTwrap for other (experimental) wrapper methods (see details).</p>
findLinked	When TRUE, the function may find two linked tables and run protectLinkedTables .
total	String used to name totals.
addName	When TRUE the variable name is added to the level names, except for variables with most levels.
sep	A character string to separate when addName apply and when creating variable names.
removeZeros	When TRUE, rows with zero count will be removed from the data within the algorithm.
dimList	By default, hierarchies will be automatically found from data (see FindDimLists). With non-NULL dimList, these will be changed. In practice this is done by the function ReplaceDimList .
groupVarInd	Possible manual specification of list defining the hierarchical variable groups. When NULL (default) this information will be found automatically by FindTableGroup .
ind1	Coding of table 1 as indices referring to elements of groupVarInd. This information will be found automatically by FindTableGroup when groupVarInd=NULL.

ind2	Coding of table 2 as indices referring to elements of groupVarInd (as ind1 above).
rowData	Input to Stack used to generate extra dimVar variables when stacking in cases with several freqvar variables. When NULL rowData will be created automatically by AutoSplit using varNames (see below) and the freqvar names as input.
varNames	The names of the extra dimVar variable(s) made when stacking in cases with several freqvar variables. When length(varNames)>1 several variables may be found by AutoSplit .
split	Parameter to AutoSplit - see varNames and rowData above. When NULL (default), automatic splitting without needing a split string.
border	Parameter to AutoSplit - see varNames and rowData above.
revBorder	Parameter to AutoSplit - see varNames and rowData above..
freqName	Input to Stack . The name of the new freqvar variable obtained when stacking in cases with several input freqvar variables.
totalFirst	Parameter controlling how output is sorted.
numericOrder	Parameter controlling how output is sorted. Output is character but sorting can be based on the numeric input variables.
namesAsInput	When TRUE those output variables (created by unstacking) that correspond to input will be named as input.
orderAsInput	When TRUE output corresponding to input will be ordered as input and kept together as one block.
sortByReversedColumns	When TRUE output will be sorted by variables in opposite order.
doUnstack	When FALSE output will not be unstacked (in cases with sever input freqvar variables)
removeTotal	When TRUE the total string (see total above) will be removed from the names of output variables created by unstacking (in cases with sever input freqvar variables).
singleOutput	When TRUE output will be in as single data set. Default is FALSE for unstacked data (in cases with sever input freqvar variables) and otherwise TRUE.
suppression	Value used for suppressed elements in suppressed output data. Default is NA.
outFreq	String used to name output variable(s)
outSdcStatus	String used to name output variable(s)
outSuppressed	String used to name output variable(s)
infoAsFrame	When TRUE output element info is a data frame (useful in Shiny).
IncProgress	A function to report progress (incProgress in Shiny). Set equal to NULL to turn it off.
...	Further parameters sent to protectTable (possibly via protectLinkedTables) such as verbose (print output while calculating) and timeLimit. Parameters to GaussSuppression , createArgusInput and PTwrap is also possible (see details).

Details

One or two tables are identified automatically and subjected to cell suppression by [protectTable](#) (single table) or [protectLinkedTables](#) (two linked tables). The tables can alternatively be specified manually by groupVarInd, ind1 and ind2. The output will be on a form similiar to input depending on whether freqVar is a single variable or not. The status of the cells are coded as "u" (primary suppressed), "x" (secondary suppression), and "s" (can be published). This is taken directly from the output from sdcTable. In cases with two linked tables "u" or "x" for common cells are based on output from the first table.

- **To run tau-argus** specify method as a named list containing the parameter exe for [runArgusBatchFile](#) and other parameters for [createArgusInput](#).
 - One may specify: `method = list(exe="C:/Tau/TauArgus.exe", typ="tabular", path=.getcwd(), solver= "FREE", method= "OPT")` However these values of "exe", "path" and "solver" and "method" are set by default so in this case using `"method = list(typ="tabular", method= "OPT")"` is equivalent.
 - If `typ="microdata"` is specified. Necessary transformation to microdata will be made.
- **Wrapper methods (partly experimental):** In the function [PTwrap](#) several additional methods are defined. If input to ProtectTable() is one of these methods ProtectTable() will be run via PTwrap(). So making explicit call to PTwrap() is not needed.
- **Singleton and zeros:** The parameter detectSingletons was included in protecttable to handle the so-called singleton problem that appers when `protectZeros=FALSE`. Not all problems were solved and the parameter threshold has been introduced later. The value of threshold needed depends on the number of singletons in one group. It seems that `threshold=3` is equivalent to `detectSingletons=TRUE`. When `protectZeros=TRUE` the related “zero problem” occurs. This problem is solved by `threshold=1`.
- **NOTE:** The use of numVarInd, weightInd and sampWeightInd in sdcTable is not implemented. This also limit possible input to tau-argus.

Value

When `singleOutput=TRUE` output is a list of two elements.

- **info:** Information as a single column character matrix. This is information about the extra dimVar variables created when stacking, information about the identified (linked) table(s) and summary output from sdcTable.
- **data:** A data frame where variables are named according to `outFreq`, `outSdcStatus` and `outSuppressed`. When `singleOutput=FALSE` output element data is replaced by three elements and these are named according to `outFreq`, `outSdcStatus` and `outSuppressed`.

Note

`ProtectTable` makes a call to the function [ProtectTable1](#).

See Also

See also the vignettes.

Examples

```

# ===== Example 1 , 8 regions =====
z1 <- EasyData("z1")
ProtectTable(z1,1:2, 3)
ProtectTable(z1,1:2, 3, method="Gauss")$data
ProtectTable(z1, c("region","hovedint"), "ant") # Input by name
# --- Unstacked input data ---
z1w = EasyData("z1w")
ProtectTable(z1w, 1, 2:5)
ProtectTable(z1w, 1, 2:5, varName="hovedint")
ProtectTable(z1w, 1, 2:5, method="HITAS")
ProtectTable(z1w, 1, 2:5, totalFirst = TRUE, method ="Simple")

# ===== Example 2 , 11 regions =====
z2 <- EasyData("z2")
ProtectTable(z2,c(1,3,4), 5) # With region-variable kostragr
# --- Unstacked input data ---
z2w <- EasyData("z2w")
ProtectTable(z2w, 1:2, 4:7, method ="Simple") # With region-variable fylke
ProtectTable(z2w, 1:3, 4:7, method = "SIMPLEHEURISTIC") # Two linked tables

## Not run:
# ===== Example 3 , 36 regions =====
z3 <- EasyData("z3")
ProtectTable(z3, c(1,4,5), 7) # Three dimensions. No subtotals
ProtectTable(z3, 1:6, 7, method = "SIMPLEHEURISTIC") # Two linked tables
# --- Unstacked input data with coded column names
z3w <- EasyData("z3w")
ProtectTable(z3w,1:3,4:15, varName="g12", method ="Simple") # coding not used when single varName
ProtectTable(z3w,1:3,4:15, varName=c("hovedint","mnd")) # Two variables found automatically
ProtectTable(z3w,1:3,4:15, varName=c("hovedint","mnd"),
            method ="Simple", removeTotal=FALSE) # Keep "Total" in variable names
# --- Unstacked input data with three level column name coding
ProtectTable(z3wb,1:3,4:15, varName=c("hovedint","mnd","mnd2")) # Two variables found automatically
ProtectTable(z3wb,1:3,4:15, varName=c("hovedint","mnd","mnd2"),
            method ="Simple", split="_") # Three variables when splitting
ProtectTable(z3wb,1:3,4:15, varName=c("hovedint","mnd","mnd2"), method = "SIMPLEHEURISTIC",
            split="_", namesAsInput=FALSE, orderAsInput=FALSE) # Alternative ouput format

# ===== Examples Tau-Argus =====
exeArgus <- "C:/TauArgus4.1.4/TauArgus.exe" # Change to TauArgus.exe-path in your computer
pathArgus <- "C:/Users/nnn/Documents" # Change to an existing folder
z1 = EasyData("z1")
ProtectTable(z1,1:2,3,method=list(exe=exeArgus, path=pathArgus, typ="tabular", method="OPT"))
ProtectTable(z1,1:2,3,method=list(exe=exeArgus, path=pathArgus, typ="tabular", method="MOD"))
ProtectTable(z1,1:2,3,method=list(exe=exeArgus, path=pathArgus, typ="tabular", method="GH"))
ProtectTable(z1,1:2,3,maxN=-1,
            method=list(path=pathArgus, exe=exeArgus, method="OPT",
                        primSuppRules= list(list(type="freq", n=4, rg=20))))
z3w <- EasyData("z3")
ProtectTable(z3,c(1:2,4,5),7,maxN=-1,
            method=list(path=pathArgus, exe=exeArgus, method="OPT",
                        primSuppRules= list(list(type="freq", n=4, rg=20))))

```

```

primSuppRules=list(list(type="freq", n=4, rg=20)))

## End(Not run)

# ===== Examples with parameter dimList =====
z2 <- EasyData("z2")
dList <- FindDimLists(z2[-5])
ProtectTable(z2[, c(1,4,5)], 1:2, 3, method = "Simple", dimList = dList[c(1,3)])
ProtectTable(z2[, c(1,4,5)], 1:2, 3, method = "SIMPLEHEURISTIC", dimList = dList[2])
ProtectTable(z2[, c(1,4,5)], 1:2, 3, method = "Simple",
            dimList = DimList2Hrc(dList[c(2,3)]))

```

ProtectTable1*Easy input interface to sdcTable***Description**

protectTable or protectLinkedTables is run with a data set at the only required input.

Usage

```

ProtectTable1(
  data,
  dimVarInd = 1:NCOL(data),
  freqVarInd = NULL,
  protectZeros = TRUE,
  maxN = 3,
  method = "SIMPLEHEURISTIC",
  findLinked = TRUE,
  total = "Total",
  addName = FALSE,
  sep = ".",
  removeZeros = FALSE,
  dimList = NULL,
  groupVarInd = NULL,
  ind1 = NULL,
  ind2 = NULL,
  dimDataReturn = FALSE,
  IncProgress = IncDefault,
  ...
)

```

Arguments

data	Matrix or data frame
dimVarInd	Column-indices of the main dimensional variables and additional aggregating variables.

<code>freqVarInd</code>	Column-indices of a variable holding counts or NULL in the case of micro data.
<code>protectZeros</code>	When TRUE empty cells (count=0) is considered sensitive (i.e. same as <code>allowZeros</code> in <code>primarySuppression</code>).
<code>maxN</code>	All cells having counts \leq maxN are set as primary suppressed.
<code>method</code>	Parameter "method" in <code>protectTable</code> or <code>protectLinkedTables</code> . Alternatively a list defining parameters for running tau-argus (see ProtectTable).
<code>findLinked</code>	When TRUE, the function may find two linked tables and run <code>protectLinkedTables</code> .
<code>total</code>	String used to name totals.
<code>addName</code>	When TRUE the variable name is added to the level names, except for variables with most levels.
<code>sep</code>	A character string to separate when <code>addName</code> apply.
<code>removeZeros</code>	When TRUE, rows with zero count will be removed from the data.
<code>dimList</code>	See ProtectTable .
<code>groupVarInd</code>	Possible manual specification if list defining the hierarchical variable groups
<code>ind1</code>	Coding of table 1 as indices referring to elements of <code>groupVarInd</code>
<code>ind2</code>	Coding of table 2 as indices referring to elements of <code>groupVarInd</code>
<code>dimDataReturn</code>	When TRUE a data frame containing the <code>dimVarInd</code> variables is retuned
<code>IncProgress</code>	A function to report progress (<code>incProgress</code> in Shiny).
<code>...</code>	Further parameters sent to <code>protectTable</code> , <code>protectLinkedTables</code> or <code>createArgusInput</code> .

Details

One or two tables are identified automatically and subjected to cell suppression methods in package `sdcTable`. The tables can alternatively be specified manually by `groupVarInd`, `ind1` and `ind2` (see [FindTableGroup](#)).

Value

Output is a list of three elements.

table1 consists of the following elements:

<code>secondary</code>	Output from protectTable or first element of output from protectLinkedTables or output from runArgusBatchFile .
<code>primary</code>	Output from primarySuppression .
<code>problem</code>	Output from makeProblem .
<code>dimList</code>	Generated input to <code>makeProblem</code> .
<code>ind</code>	Indices referring to elements of <code>groupVarInd</code> in the output element common.

table2 consists of elements of the same type as `table1` in cases of two linked tables. Otherwise `table2` is NULL.

common consists of the following elements:

commonCells	Input to protectLinkedTables.
groupVarInd	List defining the hierarchical variable groups
info	A table summarizing the tables using variable names
nLevels	The number of levels of each variable (only when groupVarInd input is NULL)
dimData	Data frame containing the dimVarInd variables when dimDataReturn=TRUE. Otherwise NULL.

See Also

[ProtectTable](#), [HierarchicalGroups](#), [FactorLevCorr](#), [FindDimLists](#), [FindCommonCells](#)

Examples

```
## Not run:
z2 <- EasyData("z2")
a <- ProtectTable1(z2, c(1, 3, 4), 5)
head(as.data.frame(getInfo(a[[1]][[1]]), type = "finalData")) # The table (not two linked))

z3 <- EasyData("z3")
b <- ProtectTable1(z3, 1:6, 7)
head(as.data.frame(getInfo(b[[1]][[1]]), type = "finalData")) # First table
head(as.data.frame(getInfo(b[[2]][[1]]), type = "finalData")) # Second table

## End(Not run)
```

Description

Run PTgui from the R console or use PTguiApp to make a server application

Usage

```
PTgui(
  data = NULL,
  language = "English",
  exeArgus = NULL,
  pathArgus = getwd(),
  maxNchoices = c(1:10, 12, 15, 20),
  ...
)

PTguiApp(
  language = "English",
  exeArgus = NULL,
  pathArgus = "",
```

```

maxNchoices = c(1:10, 12, 15, 20),
...
)

PTguiNO(
  data = NULL,
  language = "Norwegian",
  exeArgus = NULL,
  pathArgus = getwd(),
  maxNchoices = c(1:10, 12, 15, 20),
  ...
)

PTguiAppNO(
  language = "Norwegian",
  exeArgus = NULL,
  pathArgus = "",
  maxNchoices = c(1:10, 12, 15, 20),
  ...
)

```

Arguments

data	NULL or a data.frame
language	Menu language, "English" or "Norwegian".
exeArgus	Tau-argus executable
pathArgus	Folder for (temporary) tau-argus files
maxNchoices	Choices of maxN
...	Further parameters sent to ProtectTable

Value

Output from `ProtectTable`. The output is returned invisibly (via `invisible`) which means that it is not automatically printed to the console.

Note

`PTguiApp()`: New for server

Examples

```

## Not run:

# Start the gui.
PTgui()

# Start Norwegian gui with example data and catch output
out <- PTguiNO(data=EasyData("z1w"))

```

```
# Note: Change to TauArgus.exe-path in your computer
exeArgus <- "C:/TauArgus4.2.0b2/TauArgus.exe"

# Note: Change to an existing folder
pathArgus <- "C:/Users/nnn/Documents"

# Start the gui with possibility to run tau-argus.
PTgui(exeArgus=exeArgus, pathArgus=pathArgus)

## End(Not run)
```

PTwrap*Wrapper to ProtectTable() with additional methods (partly experimental)***Description**

Additional values of "method" is possible. Each new method (wrapper method) will make a call to `ProtectTable()` using a specific parameter setting.

Usage

```
PTwrap(
  ...,
  maxN = 3,
  method = "SimpleSingle",
  exeArgus = "C:/Tau/TauArgus.exe",
  pathArgus = getwd(),
  solverArgus = "FREE",
  methodArgus = "OPT",
  rgArgus = 0
)
```

Arguments

...	Parameters to <code>ProtectTable</code>
maxN	Parameter to <code>ProtectTable</code>
method	Parameter to <code>ProtectTable</code> or a wrapper method (see details)
exeArgus	Parameter to runArgusBatchFile
pathArgus	Parameter to createArgusInput
solverArgus	Parameter "solver" to createArgusInput
methodArgus	Parameter "method" to createArgusInput
rgArgus	Parameter "rg" in "primSuppRules" in createArgusInput

Details

The wrapper methods are:

Simple: "SIMPLEHEURISTIC" with detectSingletons=FALSE

SimpleSingle: "SIMPLEHEURISTIC" with detectSingletons=TRUE when protectZeros=FALSE and "SIMPLEHEURISTIC" with threshold=1 (can be overridden by input) when protectZeros=TRUE

SimpleSingleOld: "SIMPLEHEURISTIC" with detectSingletons=TRUE

TauArgus: Tau-argus will be run according to the settings of the other input parameters.

Using rgArgus=0 is equivalent to calling ProtectTable() with
`method = list(exe=exeArgus, typ="tabular", path=pathArgus,
solver=solverArgus, method=methodArgus))`

Other values of rgArgus is equivalent to calling ProtectTable() with
`method = list(exe=exeArgus, typ="microdata", path=pathArgus,
solver=solverArgus, method=methodArgus,
primSuppRules=list(list(type="freq", n=maxN+1, rg=rgArgus))))`

TauArgusOPT: As "TauArgus" with methodArgus="OPT"

TauArgusMOD: As "TauArgus" with methodArgus="MOD"

TauArgusGH: As "TauArgus" with methodArgus="GH"

Value

See [ProtectTable](#)

PTxyz

ProtectTable with output ready for SuppressDec in package RegSDC

Description

Assuming correct suppression, suppressed values become decimal numbers (not whole numbers) instead of missing.

Usage

`PTxyz(data, dimVar, freqVar, ...)`

Arguments

<code>data</code>	data frame
<code>dimVar</code>	The main dimensional variables and additional aggregating variables (name or number).
<code>freqVar</code>	Variable(s) holding counts (name or number).
<code>...</code>	Further parameters sent to ProtectTable

Details

Within this r package this function will be used for testing

Value

List of three matrices ready as input to SuppressDec

- x Sparse dummy matrix where the dimensions match z and y.
- z Frequencies to be published with suppressed as NA.
- y Inner cell frequencies.

Author(s)

Øyvind Langsrud

Examples

```
# Same examples as in ProtectTable
a1 <- PTxyz(EasyData("z1"), c("region", "hovedint"), "ant")
a2 <- PTxyz(EasyData("z2"), c(1,3,4),5)

if (require(RegSDC)) { # RegSDCdata and SuppressDec
  # Same data as in RegSDCdata examples (and in paper)
  data7 <- RegSDCdata("sec7data")
  data7 <- data7[!is.na(data7$y), 1:3]
  data7

  # Generate x, y, z similar to xAll, y, zAllSupp in RegSDCdata examples
  # But different suppressed cells and z ordered differently
  a <- PTxyz(data7, 1:2, 3, maxN = 3, method = "HITAS")
  a

  # Suppressed inner cells as decimal numbers
  yDec <- SuppressDec(a$x, a$z, a$y, rmse = 1)
  yDec

  # All cells as decimal numbers
  cbind(a$z, t(a$x) %*% cbind(a$y, yDec))

  # As ProtectTable example
  z1 <- EasyData("z1")
  a <- PTxyz(z1, c("region", "hovedint"), "ant")

  # Inner cells as decimal numbers. 3 replicates.
  yDec <- SuppressDec(a$x, a$z, a$y, nRep = 3)
  yDec

  # All cells with 3 replicates.
  cbind(a$z, t(a$x) %*% cbind(a$y, yDec))
```

```
# An example involving two linked tables.  
# It is demonstrated that the approach to suppression is not safe.  
# That is, perfect fit (whole numbers) for some suppressed cells.  
a <- PTxyz(EasyData("z2"), 1:4, 5)  
cbind(a$z, t(a$x) %*% cbind(a$y, SuppressDec(a$x, a$z, rmse = 1, nRep = 3)))[which(is.na(a$z)), ]  
}
```

sosialFiktiv

Fictitious datasets used in the examples.

Description

The most comprehensive dataset, `sosialFiktiv`, contains three dimensions. The first dimension is 'region' which is grouped in two ways, 'fylke' and 'kostragr'. The other two are 'hovedint' and 'mnd'. In 'mnd2' two of the three categories in 'mnd' are merged. The other datasets (`z1`, `z1w`, `z2`, `z2w`, `z3`, `z3w`, `z3wb`) are smaller subdatasets. Datasets marked with 'w' are unstacked and several variables are holding counts.

Index

* datasets
 sosialFiktiv, 15

AutoSplit, 5

createArgusInput, 5, 6, 12

EasyData, 2

FactorLevCorr, 10

FindCommonCells, 10

FindDimLists, 4, 10

FindTableGroup, 4, 9

GaussSuppression, 4, 5

HierarchicalGroups, 10

invisible, 11

makeProblem, 9

primarySuppression, 4, 9

protectLinkedTables, 4–6, 9

ProtectTable, 3, 9–11, 13

protectTable, 4–6, 9

ProtectTable1, 6, 8

PTgui, 10

PTguiApp (PTgui), 10

PTguiAppNO (PTgui), 10

PTguiNO (PTgui), 10

PTwrap, 4–6, 12

PTxyz, 13

ReplaceDimList, 4

runArgusBatchFile, 6, 9, 12

sosialFiktiv, 15

Stack, 5

z1 (sosialFiktiv), 15

z1micro (sosialFiktiv), 15

z1w (sosialFiktiv), 15

z2 (sosialFiktiv), 15

z2w (sosialFiktiv), 15

z3 (sosialFiktiv), 15

z3w (sosialFiktiv), 15

z3wb (sosialFiktiv), 15