

Package ‘emhawkes’

September 17, 2018

Title Exponential Multivariate Hawkes Model

Version 0.9.0

Maintainer Kyungsub Lee <kyungsub@gmail.com>

Description Simulate and fitting exponential multivariate Hawkes model.

This package simulates a multivariate Hawkes model, introduced by Hawkes (1971) <doi:10.1093/biomet/58.1.83>, with an exponential kernel and fits the parameters from the data.

Models with the constant parameters, as well as complex dependent structures, can also be simulated and estimated.

The estimation is based on the maximum likelihood method, introduced by introduced by Ozaki (1979) <doi:10.1007/BF02480272>, with 'maxLik' package.

Depends R (>= 3.4.0)

License GPL (>= 2)

Encoding UTF-8

LazyData true

RoxxygenNote 6.0.1

Imports maxLik, methods

Collate 'harrival.R' 'hspec.R' 'hmoment.R' 'hllf.R' 'hfit.R'
'utilities.R' 'hreal.R' 'hsim.R' 'script.R'

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Kyungsub Lee [aut, cre]

Repository CRAN

Date/Publication 2018-09-17 14:20:02 UTC

R topics documented:

hfit	2
hreal	4

hsim	5
hspec-class	6
logLik,hspec-method	7

Index**8**

hfit	<i>Perform Maximum Likelihood Estimation</i>
-------------	--

Description

Generic function `hfit`. Exponential decaying marked A method for estimating the parameters of the Hawkes model. The reason for being constructed as the S4 methodis as follows. First, to represent the structure of the model as an `hspec` object. There are numerous variations on the mutlivariate marked Hawkes model. Second, to convey the starting point of numerical optimization. The parameter values assigned to the `hspec` slots become initial values. This function uses [maxLik](#) for the optimizer.

This function uses [maxLik](#) for the optimizer.

Usage

```
hfit(object, inter_arrival = NULL, type = NULL, mark = NULL,
      lambda0 = NULL, N0 = NULL, reduced = TRUE, grad = NULL, hess = NULL,
      constraint = NULL, method = "BFGS", verbose = FALSE, ...)

## S4 method for signature 'hspec'
hfit(object, inter_arrival = NULL, type = NULL,
      mark = NULL, lambda0 = NULL, N0 = NULL, reduced = TRUE, grad = NULL,
      hess = NULL, constraint = NULL, method = "BFGS", verbose = FALSE, ...)
```

Arguments

<code>object</code>	<code>hspec</code>
<code>inter_arrival</code>	inter-arrival times of events. Includes inter-arrival for events that occur in all dimensions. Start with zero.
<code>type</code>	a vector of dimensions. Distinguished by numbers, 1, 2, 3, and so on. Start with zero.
<code>mark</code>	a vector of mark (jump) sizes. Start with zero.
<code>lambda0</code>	the inital values of lambda component. Must have the same dimensional matrix (n by n) with <code>hspec</code> .
<code>N0</code>	the initial values of N.
<code>reduced</code>	When TRUE, reduced estimation performed.
<code>grad</code>	gradient matrix for the likelihood function. For more information, see maxLik .
<code>hess</code>	Hessian matrix for the likelihood function. For more information, see maxLik .
<code>constraint</code>	constraint matrix. For more information, see maxLik .

method	method for optimization. For more information, see maxLik .
verbose	If TRUE, print the progress of the estimation.
...	other parameters for optimization. For more information, see maxLik .

See Also

[hspec-class](#), [hsim](#), [hspec-method](#)

Examples

```
# example 1
mu <- c(0.1, 0.1)
alpha <- matrix(c(0.2, 0.1, 0.1, 0.2), nrow=2, byrow=TRUE)
beta <- matrix(c(0.9, 0.9, 0.9, 0.9), nrow=2, byrow=TRUE)
h <- new("hspec", mu=mu, alpha=alpha, beta=beta)
res <- hsim(h, size=100)
summary(hfit(h, res$inter_arrival, res$type))

# example 2

mu <- matrix(c(0.08, 0.08, 0.05, 0.05), nrow = 4)
alpha <- function(param = c(alpha11 = 0, alpha12 = 0.4, alpha33 = 0.5, alpha34 = 0.3)){
  matrix(c(param["alpha11"], param["alpha12"], 0, 0,
           param["alpha12"], param["alpha11"], 0, 0,
           0, 0, param["alpha33"], param["alpha34"],
           0, 0, param["alpha34"], param["alpha33"])), nrow = 4, byrow = TRUE)
}
beta <- matrix(c(rep(0.6, 8), rep(1.2, 8)), nrow = 4, byrow = TRUE)

impact <- function(param = c(alpha1n=0, alpha1w=0.2, alpha2n=0.001, alpha2w=0.1),
                    n=n, N=N, ...){

  Psi <- matrix(c(0, 0, param['alpha1w'], param['alpha1n'],
                 0, 0, param['alpha1n'], param['alpha1w'],
                 param['alpha2w'], param['alpha2n'], 0, 0,
                 param['alpha2n'], param['alpha2w'], 0, 0), nrow=4, byrow=TRUE)

  ind <- N[,"N1"][n] - N[,"N2"][n] > N[,"N3"][n] - N[,"N4"][n] + 0.5

  km <- matrix(c(!ind, !ind, !ind, !ind,
                  ind, ind, ind, ind,
                  ind, ind, ind, ind,
                  !ind, !ind, !ind, !ind), nrow = 4, byrow = TRUE)

  km * Psi
}
h <- new("hspec",
        mu = mu, alpha = alpha, beta = beta, impact = impact)
hr <- hsim(h, size=100)
plot(hr$arrival, hr$N[, 'N1'] - hr$N[, 'N2'], type='s')
```

```

lines(hr$N[, 'N3'] - hr$N[, 'N4'], type='s', col='red')
fit <- hfit(h, hr$inter_arrival, hr$type)
summary(fit)

# example 3

mu <- c(0.15, 0.15)
alpha <- matrix(c(0.75, 0.6, 0.6, 0.75), nrow=2, byrow=TRUE)
beta <- matrix(c(2.6, 2.6, 2.6, 2.6), nrow=2, byrow=TRUE)
rmark <- function(param = c(p=0.65), ...){
  rgeom(1, p=param[1]) + 1
}
impact <- function(param = c(eta1=0.2), alpha, n, mark, ...){
  ma <- matrix(rep(mark[n]-1, 4), nrow = 2)
  alpha * ma * matrix( rep(param["eta1"], 4), nrow=2)
}
h1 <- new("hspec", mu=mu, alpha=alpha, beta=beta,
          rmark = rmark,
          impact=impact)
res <- hsim(h1, size=100, lambda0 = matrix(rep(0.1,4), nrow=2))

fit <- hfit(h1,
            inter_arrival = res$inter_arrival,
            type = res$type,
            mark = res$mark,
            lambda0 = matrix(rep(0.1,4), nrow=2))
summary(fit)

# For more information, please see vignettes.

```

Description

Generic functions list for *hreal*:

`Print` the realization of the Hawkes model.

`Print` the summary of the Hawkes process realization.

`Matrix` like output of the realization of Hawkes model.

Usage

```

## S3 method for class 'hreal'
print(x, n = 20, ...)

## S3 method for class 'hreal'
summary(object, n = 20, ...)

```

```
## S3 method for class 'hreal'
as.matrix(x, ...)
```

Arguments

x	S3-object of hreal.
n	number of rows to display.
...	further arguments passed to or from other methods.
object	S3-object of hreal.

hsim

Simulate a multivariate Hawkes process. Generic function hsim.

Description

Simulate a multivariate Hawkes process. Generic function hsim.

The method simulate multivariate Hawkes processes. The object [hspec-class](#) contains the parameter values such as mu, alpha, beta. The mark (jump) structure may or may not be included. It returns an object of class hreal which contains inter_arrival, arrival, type, mark, N, Nc, lambda, lambda_component, rambda, rambda_component.

Usage

```
hsim(object, size = 100, lambda0 = NULL, N0 = NULL)

## S4 method for signature 'hspec'
hsim(object, size = 100, lambda0 = NULL, N0 = NULL)
```

Arguments

object	hspec-class . This object includes the parameter values.
size	the number of observations.
lambda0	the starting values of lambda component. numeric or matrix.
N0	the starting values of N

Value

hreal S3-object, summary of the realization of the Haweks model

Examples

```
mu <- c(0.1, 0.1)
alpha <- matrix(c(0.2, 0.1, 0.1, 0.2), nrow=2, byrow=TRUE)
beta <- matrix(c(0.9, 0.9, 0.9, 0.9), nrow=2, byrow=TRUE)
h <- new("hspec", mu=mu, alpha=alpha, beta=beta)
res <- hsim(h, size=100)
```

hspec-class

*An S4 class to represent an exponential marked Hawkes model***Description**

This class represents a specification of a marked Hawkes model with exponential kernel. The intensity of the ground process is defined by:

$$\lambda(t) = \mu + \int (\alpha + \Psi) * \exp(-\beta(t - u)) dN(u).$$

For more details, please see the vignettes.

Details

μ is base intensity. This is generally a constant vector but can be extended to stochastic processes.

α is a constant matrix which represents impacts on intensities after events. It is represented by slot `mu`.

Ψ is for non-constant parts of the impact. It may depend on any information generated by N , λ , k and so on. It is represented by slot `impact`.

β is a constant matrix for exponential decay rates. It is represented by slot `beta`.

k is mark and represented by slot `rmark`.

`mu`, `alpha` and `beta` are required slots for every exponential Hawkes model. `rmark` and `impact` are additional slots.

Slots

`mu` numeric value or matrix or function, if numeric, automatically converted to matrix

`alpha` numeric value or matrix or function, if numeric, automatically converted to matrix, exciting term

`beta` numeric value or matrix or function, if numeric, automatically converted to matrix, exponential decay

`dimens` dimension of the model

`rmark` a function that represents mark for counting process

`impact` a function that describes the after impact of mark to lambda

Examples

```
MU <- matrix(c(0.2), nrow = 2)
ALPHA <- matrix(c(0.75, 0.92, 0.92, 0.75), nrow = 2, byrow=TRUE)
BETA <- matrix(c(2.25, 2.25, 2.25, 2.25), nrow = 2, byrow=TRUE)
mhspec2 <- new("hspec", mu=MU, alpha=ALPHA, beta=BETA)
```

logLik,hspec-method *Compute the loglikelihood function*

Description

The loglikelihood of the ground process of the Hawkes model. (The estimation for jump distribution is not provided.)

Usage

```
## S4 method for signature 'hspec'  
logLik(object, inter_arrival, type = NULL, mark = NULL,  
       N0 = NULL, lambda0 = NULL)
```

Arguments

object	hspec-class . The parameter values in the object are used to compute the log-likelihood.
inter_arrival	inter-arrival times of events. Includes inter-arrival for events that occur in all dimensions. Start with zero.
type	a vector of dimensions. Distinguished by numbers, 1, 2, 3, and so on. Start with zero.
mark	a vector of mark (jump) sizes. Start with zero.
N0	the initial value of N
lambda0	the initial values of lambda component. Must have the same dimensional matrix with hspec.

See Also

[hspec-class](#), [hfit](#), [hspec-method](#)

Index

as.matrix.hreal (hreal), 4
hfit, 2
hfit, hspec-method (hfit), 2
hreal, 4
hsim, 5
hsim, hspec-method (hsim), 5
hspec-class, 6
logLik, hspec-method, 7
maxLik, 2, 3
print.hreal (hreal), 4
summary.hreal (hreal), 4