

Package ‘ezplot’

June 13, 2020

Type Package

Title Functions for Common Chart Types

Version 0.6.1

Author Wojtek Kostecki

Maintainer Wojtek Kostecki <wojtek.kostecki@gmail.com>

Description Wrapper for the 'ggplot2' package that creates a variety of common charts (e.g. bar, line, area, ROC, waterfall, pie) while aiming to reduce typing.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Depends R (>= 3.3)

RoxygenNote 7.1.0

Imports dplyr, forcats, ggplot2, lubridate, rlang, tsibble

Suggests covr, DT, e1071, knitr, methods, miniUI, rmarkdown, ROCR, shiny, stats, testthat, tibble, tidyr, tsibbledata

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2020-06-13 14:30:02 UTC

R topics documented:

agg_data	2
area_plot	3
bar_plot	5
calendar_plot	7
density_plot	7
distribution_plot	8
ez_app	9

ez_col	10
ez_jet	10
ez_labels	11
ez_png	12
ez_server	13
ez_ui	13
get_incr	13
histogram_plot	14
lift_plot	15
line_plot	16
model_plot	17
nameifnot	18
na_plot	19
not_numeric	19
no_null	20
perf	20
performance_plot	21
perf_df	22
pie_plot	22
prec_rec	24
pr_plot	24
quick_facet	25
reorder_levels	26
roc	27
roc_plot	27
save_png	28
scatter_plot	29
secondary_plot	30
side_plot	31
text_contrast	32
theme_ez	33
tile_plot	33
unpack_cols	34
variable_plot	35
waterfall_plot	37

Index	39
--------------	-----------

agg_data

Aggregates data

Description

Aggregates data

Usage

```
agg_data(  
  data,  
  cols = names(data),  
  group_by = NULL,  
  agg_fun = function(x) sum(x, na.rm = TRUE),  
  group_by2 = NULL,  
  env = parent.frame()  
)
```

Arguments

data	A data.frame.
cols	Named character vector of column names.
group_by	Vector of grouping columns.
agg_fun	Function to use for aggregating.
group_by2	Vector of grouping column names to use for delayed (post aggregation) calculation.
env	Environment for extra variables.

Value

An aggregated data.frame.

Examples

```
library(tsibbledata)  
agg_data(ansett, c("Passengers", count = "1"))  
agg_data(ansett["Class"])  
agg_data(ansett[c("Class", "Passengers")])  
agg_data(ansett, "Passengers", "Class")  
agg_data(ansett, "Passengers", c("Class", "Airports"))  
agg_data(ansett, c(x = "Airports", y = "Passengers"), c(x = "Airports"))  
agg_data(ansett, c(x = "Class", y = "1", group = "Airports"), c(x = "Class", group = "Airports"))
```

area_plot

area_plot

Description

Aggregates a data.frame and creates a stacked area chart.

Usage

```

area_plot(
  data,
  x,
  y = "1",
  group = NULL,
  facet_x = NULL,
  facet_y = NULL,
  size = 11,
  reorder = c("group", "facet_x", "facet_y"),
  palette = ez_col,
  labels_y = if (position == "fill") { function(x) ez_labels(100 * x, append =
    "%") } else { ez_labels },
  labels_x = NULL,
  use_theme = theme_ez,
  position = c("stack", "fill"),
  facet_scales = "fixed",
  facet_ncol = NULL,
  env = parent.frame()
)

```

Arguments

data	A data.frame.
x	A named character value. Evaluates to a column.
y	A named character value. Evaluates to a column.
group	A character value. Evaluates to a column.
facet_x	A character value. Evaluates to a column.
facet_y	A character. Evaluates to a column.
size	theme size for use_theme(). Default is 14.
reorder	A character vector specifying the group variables to reorder. Default is c("group", "facet_x", "facet_y").
palette	Colour function.
labels_y	label formatting function
labels_x	label formatting function
use_theme	ggplot theme function
position	Either "stack" (default) or "fill"
facet_scales	Option passed to scales argument in facet_wrap or facet_grid. Default is "fixed".
facet_ncol	Option passed to ncol argument in facet_wrap or facet_grid. Default is NULL.
env	environment for evaluating expressions.

Value

A ggplot object.

Examples

```

library(tsibble)
library(tsibbledata)
area_plot(ansett, x = "as.Date(Week)", y = "Passengers")
area_plot(ansett,
  x = "as.Date(Week)", y = c("Weekly Passengers" = "Passengers"), "Class")
area_plot(ansett, "as.Date(Week)",
  y = c("Weekly Passengers" = "Passengers"),
  group = "substr(Airports, 5, 7)",
  facet_x = "substr(Airports, 1, 3)",
  facet_y = "Class",
  facet_scales = "free_y")

```

bar_plot

bar_plot

Description

bar_plot

Usage

```

bar_plot(
  data,
  x,
  y = "1",
  group = NULL,
  facet_x = NULL,
  facet_y = NULL,
  size = 11,
  width = NULL,
  reorder = c("group", "facet_x", "facet_y"),
  palette = ez_col,
  labels_y = if (position == "fill") { function(x) ez_labels(100 * x, append =
    "%") } else { ez_labels },
  labels_x = identity,
  label_pos = c("auto", "inside", "top", "both", "none"),
  rescale_y = 1.1,
  label_cutoff = 0.12,
  use_theme = theme_ez,
  position = "stack",
  facet_scales = "fixed",
  coord_flip = FALSE
)

```

Arguments

data	A data.frame.
x	A named character value. Evaluates to a column.
y	A named character value. Evaluates to a column.
group	A character value. Evaluates to a column.
facet_x	A character value. Evaluates to a column.
facet_y	A character. Evaluates to a column.
size	theme size for use_theme(). Default is 14.
width	Width of bar.
reorder	A character vector specifying the group variables to reorder. Default is c("group", "facet_x", "facet_y").
palette	Colour function.
labels_y	label formatting function
labels_x	label formatting function
label_pos	Position of labels. Can be "auto", "inside", "top", "both" or "none".
rescale_y	Rescaling factor for y-axis limits
label_cutoff	Cutoff size (proportion of y data range) for excluding labels
use_theme	ggplot theme function
position	Either "stack" (default) or "fill"
facet_scales	Option passed to scales argument in facet_wrap or facet_grid. Default is "fixed".
coord_flip	logical (default is FALSE). If TRUE, flips the x and y coordinate using ggplot2::coord_flip()

Value

A ggplot object.

Examples

```
library(tsibble)
library(tsibbledata)
library(lubridate)
bar_plot(ansett, "year(Week)", "Passengers", size = 20)
bar_plot(ansett, "year(Week)", "Passengers", "Class")
bar_plot(ansett, "Airports", c("Share of Passengers" = "Passengers"), "Class", position = "fill")
bar_plot(ansett, "Airports", "Passengers", "Class", reorder = NULL, label_pos = "both")
bar_plot(ansett, "Airports",
         c(Passengers = "ifelse(Class == 'Economy', Passengers, -Passengers)",
           "Class", label_pos = "both")
)
bar_plot(ansett, "year(Week)", "Passengers", "Class", label_pos = "both", coord_flip = TRUE)
```

calendar_plot	<i>calendar_plot</i>
---------------	----------------------

Description

calendar_plot

Usage

```
calendar_plot(data, x, y, ...)
```

Arguments

data	A data.frame.
x	date column
y	A named character value. Evaluates to a column.
...	additional arguments for tile_plot

Examples

```
library(tsibbledata)
calendar_plot(vic_elec, "Time", "Demand", zlim = c(NA, NA))
```

density_plot	<i>density_plot</i>
--------------	---------------------

Description

creates a density plot

Usage

```
density_plot(
  data,
  x,
  group = NULL,
  facet_x = NULL,
  facet_y = NULL,
  palette = ez_col,
  adjust = 1,
  alpha = 0.5,
  facet_scales = "fixed",
  facet_ncol = NULL,
  env = parent.frame()
)
```

Arguments

data	A data.frame.
x	A named character value. Evaluates to a column.
group	A character value. Evaluates to a column.
facet_x	A character value. Evaluates to a column.
facet_y	A character. Evaluates to a column.
palette	Colour function.
adjust	multiply bandwidth adjustment
alpha	alpha
facet_scales	Option passed to scales argument in facet_wrap or facet_grid. Default is "fixed".
facet_ncol	Option passed to ncol argument in facet_wrap or facet_grid. Default is NULL.
env	environment for evaluating expressions.

Examples

```
library(tsibbledata)
density_plot(mtcars, "wt", "cyl")
density_plot(subset(tsibbledata::olympic_running, Length == 100 & Year >= 1980),
             "Time", "Year - Year %% 10", "Sex", facet_scales = "free", facet_ncol = 1, adjust = 2)
```

distribution_plot *distribution_plot*

Description

distribution_plot

Usage

```
distribution_plot(
  data,
  x,
  facet_x = NULL,
  nbins = 20,
  use_theme = theme_ez,
  size = 11,
  env = parent.frame()
)
```


Arguments

data	A data.frame.
x	A named character value. Evaluates to a column.
facet_x	A character value. Evaluates to a column.
nbins	Number of bins for histogram. Default is 20.
use_theme	ggplot theme function
size	theme size for use_theme(). Default is 14.
env	environment for evaluating expressions.

Examples

```
n = 100
df = data.frame(residuals = rnorm(n),
                group1 = sample(c("a", "b"), n, replace = TRUE))
distribution_plot(df, "residuals")
distribution_plot(df, "residuals", "group1")
```

 ez_app

ez_app

Description

ez_app

Usage

```
ez_app(data = NULL)
```

Arguments

data	A data frame
------	--------------

Examples

```
## Not run:
library(tsibbledata)
ez_app(ansett)

## End(Not run)
```

ez_col	<i>Color palette interpolation</i>
--------	------------------------------------

Description

Color palette interpolation

Usage

```
ez_col(n = 50, palette = NULL)
```

Arguments

n	number of colours
palette	palette to interpolate from

Value

rgb

Examples

```
ez_col(15)
ez_col(2, c("blue", "red"))
ez_col(3, c("blue", "red"))
```

ez_jet	<i>ez_jet</i>
--------	---------------

Description

ez_jet

Usage

```
ez_jet(
  n = 100,
  palette = c("dodgerblue4", "steelblue2", "olivedrab3", "darkgoldenrod1", "brown")
)
```

Arguments

n	Number of colours to return.
palette	Vector of colours.

ez_labels	<i>Function for formatting numeric labels</i>
-----------	---

Description

Function for formatting numeric labels

Usage

```
ez_labels(  
  x,  
  prepend = "",  
  append = "",  
  as_factor = FALSE,  
  round = Inf,  
  signif = Inf  
)
```

Arguments

x	numeric
prepend	character
append	character
as_factor	logical
round	numeric passed to round()
signif	numeric passed to signif()

Value

y

Examples

```
ez_labels(10^(0:10))  
ez_labels(2000, append = " apples")  
ez_labels(0:10, append = " apples", as_factor = TRUE)  
ez_labels(c(0, 0.1, 0.01, 0.001, 0.0001))
```

`ez_png`*ez_png*

Description

Saves ggplot or ezplot objects to png (with useful defaults).

Usage

```
ez_png(  
  g,  
  file,  
  width = 1200,  
  height = 600,  
  res = 72,  
  resx = 1,  
  ...,  
  vp = NULL,  
  dir.create = FALSE,  
  check = TRUE  
)
```

Arguments

<code>g</code>	A ggplot or ezplot object.
<code>file</code>	A png file path.
<code>width</code>	Image width (in pixels). Default is 1200.
<code>height</code>	Image height (in pixels). Default is 600.
<code>res</code>	Resolution (PPI) of output image. Default is 72.
<code>resx</code>	Resolution multiplier. Default is 1.
<code>...</code>	Further arguments to pass to <code>png()</code> .
<code>vp</code>	A viewport object created with <code>grid::viewport</code> .
<code>dir.create</code>	Logical. If TRUE, creates the directory to save into. Default is FALSE.
<code>check</code>	Logical. If TRUE, opens png file after saving. Default is TRUE.

ez_server	<i>ez_server</i>
-----------	------------------

Description

ez_server

Usage

ez_server(data)

Arguments

data	A data frame
------	--------------

ez_ui	<i>ez_ui</i>
-------	--------------

Description

ez_ui

Usage

ez_ui(data)

Arguments

data	A data frame
------	--------------

get_incr	<i>get_incr</i>
----------	-----------------

Description

returns the minimum increment between sorted unique values of a vector

Usage

get_incr(x)

Arguments

x	A numeric or date vector
---	--------------------------

histogram_plot	<i>histogram_plot</i>
----------------	-----------------------

Description

creates a histogram plot

Usage

```
histogram_plot(
  data,
  x,
  y = "count",
  group = NULL,
  facet_x = NULL,
  facet_y = NULL,
  palette = ez_col,
  position = "stack",
  bins = 30,
  alpha = 0.5,
  facet_scales = "fixed",
  facet_ncol = NULL,
  env = parent.frame()
)
```

Arguments

data	A data.frame.
x	A named character value. Evaluates to a column.
y	A named character value. Evaluates to a column.
group	A character value. Evaluates to a column.
facet_x	A character value. Evaluates to a column.
facet_y	A character. Evaluates to a column.
palette	Colour function.
position	Either "stack" (default) or "fill"
bins	number of bins
alpha	fill alpha
facet_scales	Option passed to scales argument in facet_wrap or facet_grid. Default is "fixed".
facet_ncol	Option passed to ncol argument in facet_wrap or facet_grid. Default is NULL.
env	environment for evaluating expressions.

Examples

```

histogram_plot(airquality, "Wind", group = "Month")
histogram_plot(airquality, "Wind", "density", facet_x = "Month")

```

lift_plot

*lift_plot***Description**

precision-recall plot

Usage

```

lift_plot(
  data,
  fitted,
  actual,
  group = NULL,
  facet_x = NULL,
  facet_y = NULL,
  size_line = 1,
  size = 11,
  env = parent.frame()
)

```

Arguments

data	A data.frame.
fitted	Vector of fitted values
actual	Vector of actual values
group	A character value. Evaluates to a column.
facet_x	A character value. Evaluates to a column.
facet_y	A character. Evaluates to a column.
size_line	width of line for geom_line(). Default is 1.
size	theme size for use_theme(). Default is 14.
env	environment for evaluating expressions.

Examples

```

library(ggplot2)
n = 1000
df = data.frame(actual = sample(c(FALSE, TRUE), n, replace = TRUE),
                 runif = runif(n))
df[["fitted"]] = runif(n) ^ ifelse(df[["actual"]] == 1, 0.5, 2)

```

```
density_plot(df, "fitted", "actual")

lift_plot(df, "fitted", "actual")
lift_plot(df, "fitted", "actual") + scale_y_log10()
lift_plot(df, "runif", "actual", size_line = 0.5)

library(dplyr, warn.conflicts = FALSE)
lift_plot(df, "fitted", "actual", "sample(c(1, 2), n(), TRUE)")

lift_plot(df, "fitted", "actual",
          "sample(c(1, 2), n(), TRUE)",
          "sample(c(3, 4), n(), TRUE)")

lift_plot(df, "fitted", "actual",
          "sample(c(1, 2), n(), TRUE)",
          "sample(c(3, 4), n(), TRUE)",
          "sample(c(5, 6), n(), TRUE)")
```

line_plot

line_plot

Description

Creates line plots.

Usage

```
line_plot(
  data,
  x,
  y = "1",
  group = NULL,
  facet_x = NULL,
  facet_y = NULL,
  yoy = FALSE,
  size_line = 1,
  size = 11,
  palette = ez_col,
  labels_y = ez_labels,
  use_theme = theme_ez,
  facet_scales = "fixed"
)
```

Arguments

data A data.frame.

x	A named character value. Evaluates to a column.
y	A named character value. Evaluates to a column.
group	A character value. Evaluates to a column.
facet_x	A character value. Evaluates to a column.
facet_y	A character. Evaluates to a column.
yoy	Logical used to indicate whether a YOY grouping should be created. Default is FALSE.
size_line	width of line for geom_line(). Default is 1.
size	theme size for use_theme(). Default is 14.
palette	Colour function.
labels_y	label formatting function
use_theme	ggplot theme function
facet_scales	Option passed to scales argument in facet_wrap or facet_grid. Default is "fixed".

Value

A ggplot object.

Examples

```
library(tsibbledata)
line_plot(pelt, "Year", "Hare")
line_plot(pelt, "Year", c("Hare", "Lynx"))
line_plot(pelt, "Year", "Hare", use_theme = ggplot2::theme_bw)
line_plot(pelt, "Year", c("Hare Population" = "Hare"))
```

model_plot

model_plot

Description

model_plot

Usage

```
model_plot(
  data,
  x,
  actual,
  fitted,
  facet_x = NULL,
  point_size = 2,
  res_bins = NA_real_,
  size = 11
)
```

Arguments

<code>data</code>	A <code>data.frame</code> .
<code>x</code>	A named character value. Evaluates to a column.
<code>actual</code>	A character value. Evaluates to a logical or binary column.
<code>fitted</code>	A character value. Evaluates to a numeric column.
<code>facet_x</code>	A character value. Evaluates to a column.
<code>point_size</code>	Numeric. Default is 2.
<code>res_bins</code>	Number of bins in the residual distribution. Default value (NA) doesn't show the distribution.
<code>size</code>	theme size for <code>use_theme()</code> . Default is 14.

Value

A `ggplot` object.

Examples

```
y = rnorm(26)
df = data.frame(ID = 1:26, actual = y + rnorm(26), fitted = y, id = letters)
model_plot(df, "ID", "actual", "fitted")
model_plot(df, "id", "actual", "fitted")
model_plot(df, "ID", "actual", "fitted", res_bins = 10)
model_plot(df, "id", "actual", "fitted", res_bins = 10)
```

`nameifnot`

nameifnot

Description

Names unnamed elements of a character vector.

Usage

```
nameifnot(x, make.names = FALSE)
```

Arguments

<code>x</code>	A character vector.
<code>make.names</code>	Logical. Whether to force names of <code>x</code> to be valid variable names. Default is <code>FALSE</code> .

Value

A named vector.

na_plot	<i>na_plot</i>
---------	----------------

Description

Visual representation of the NAs in a data.frame

Usage

```
na_plot(data, palette = ez_col)
```

Arguments

data	A data.frame.
palette	Colour function.

Value

A ggplot object.

Examples

```
na_plot(airquality)
```

not_numeric	<i>not_numeric</i>
-------------	--------------------

Description

Returns names of non-numeric columns.

Usage

```
not_numeric(x)
```

Arguments

x	A data.frame.
---	---------------

Value

A character vector.

no_null	<i>no_null</i>
---------	----------------

Description

Converts "NULL" character to NULL.

Usage

```
no_null(x)
```

Arguments

x	A character vector.
---	---------------------

Value

y

Examples

```
no_null(NULL)
no_null("NULL")
no_null("NOPE")
```

perf	<i>perf</i>
------	-------------

Description

Precision recall calculation

Usage

```
perf(fitted, actual, x_measure, y_measure)
```

Arguments

fitted	Vector with values between 0 and 1
actual	Vector with two levels
x_measure	metric for ROCR::performance
y_measure	metric for ROCR::performance

Examples

```
ezplot::perf(runif(1), sample(c(TRUE, FALSE), 1, replace = TRUE), "rpp", "lift")
ezplot::perf(runif(10), sample(c(TRUE, FALSE), 10, replace = TRUE), "rpp", "lift")
ezplot::perf(runif(5), sample(c(TRUE, FALSE), 5, replace = TRUE), "rec", "prec")
ezplot::perf(runif(5), sample(c(TRUE, FALSE), 5, replace = TRUE), "fpr", "tpr")
```

performance_plot	<i>performance_plot</i>
------------------	-------------------------

Description

plots binary classification performance metrics

Usage

```
performance_plot(
  data,
  fitted,
  actual,
  group = NULL,
  facet_x = NULL,
  facet_y = NULL,
  x = "fpr",
  y = "tpr",
  auc = c("title", "group"),
  size_line = 1,
  size = 11,
  env = parent.frame()
)
```

Arguments

data	A data.frame.
fitted	A character value. Evaluates to a numeric column.
actual	A character value. Evaluates to a logical or binary column.
group	A character value. Evaluates to a column.
facet_x	A character value. Evaluates to a column.
facet_y	A character. Evaluates to a column.
x	ROCR::performance() measure
y	ROCR::performance() measure
auc	character vector indicating which AUC values should be displayed. Options are 'title' and 'group'
size_line	width of line for geom_line(). Default is 1.
size	theme size for use_theme(). Default is 14.
env	environment for evaluating expressions.

Examples

```
performance_plot(mtcars, "-disp", "am")
performance_plot(mtcars, "-disp", "am", "cyl")
performance_plot(mtcars, "-disp", "am", "cyl", x = "rec", y = "prec")
performance_plot(mtcars, "-disp", "am", x = "rpp", y = "gain")
```

perf_df	<i>perf_df</i>
---------	----------------

Description

perf_df

Usage

```
perf_df(fitted, actual)
```

Arguments

fitted	A character value. Evaluates to a numeric column.
actual	A character value. Evaluates to a logical or binary column.

Examples

```
perf_df(mtcars$mpg, mtcars$am)
perf_df(mtcars$wt, mtcars$am==0)
```

pie_plot	<i>pie_plot</i>
----------	-----------------

Description

Creates pie charts.

Usage

```
pie_plot(
  data,
  x,
  y = "1",
  facet_x = NULL,
  facet_y = NULL,
  labels_y = function(x) ez_labels(x * 100, append = "%", round = round, signif =
    signif),
  size = 11,
```

```

    label_cutoff = 0.04,
    round = Inf,
    signif = 3,
    palette = ez_col,
    reorder = c("x", "facet_x", "facet_y"),
    label_x = 0.8
  )

```

Arguments

data	A data.frame.
x	A named character value. Evaluates to a column.
y	A named character value. Evaluates to a column.
facet_x	A character value. Evaluates to a column.
facet_y	A character. Evaluates to a column.
labels_y	label formatting function
size	theme size for use_theme(). Default is 14.
label_cutoff	Cutoff size (proportion of y data range) for excluding labels
round	Option for rounding label.
signif	Option for retaining significant figures in label.
palette	Colour function.
reorder	A character vector specifying the group variables to reorder. Default is c("group", "facet_x", "facet_y")
label_x	Position of label from centre of pie. 0 is the centre of the pie and 1 is the outer edge.

Value

ggplot object

Examples

```

library(tsibbledata)
pie_plot(ansett, "Class", "Passengers")
pie_plot(ansett, "Class", "Passengers", reorder = NULL, label_x = 0.5)
pie_plot(ansett, "Class", "Passengers", "Airports", reorder = NULL, label_x = 0.5)

```

prec_rec

prec_rec

Description

Precision recall calculation

Usage

```
prec_rec(fitted, actual)
```

Arguments

fitted Vector with values between 0 and 1
actual Vector with two levels

Examples

```
ezplot:::prec_rec(runif(1), sample(c(TRUE, FALSE), 1, replace = TRUE))  
ezplot:::prec_rec(runif(5), sample(c(TRUE, FALSE), 5, replace = TRUE))
```

pr_plot

pr_plot

Description

precision-recall plot

Usage

```
pr_plot(  
  data,  
  fitted,  
  actual,  
  group = NULL,  
  facet_x = NULL,  
  facet_y = NULL,  
  palette = ez_col,  
  size_line = 1,  
  size = 11,  
  labs = "short",  
  env = parent.frame()  
)
```


Arguments

data	A data.frame.
fitted	Vector of fitted values
actual	Vector of actual values
group	A character value. Evaluates to a column.
facet_x	A character value. Evaluates to a column.
facet_y	A character. Evaluates to a column.
palette	Colour function.
size_line	width of line for geom_line(). Default is 1.
size	theme size for use_theme(). Default is 14.
labs	'short' or 'long'
env	environment for evaluating expressions.

Examples

```
library(ggplot2)
n = 1000
df = data.frame(actual = sample(c(FALSE, TRUE), n, replace = TRUE),
                runif = runif(n))
df[["fitted"]] = runif(n) ^ ifelse(df[["actual"]] == 1, 0.5, 2)

density_plot(df, "fitted", "actual")

pr_plot(df, "fitted", "actual")
pr_plot(df, "runif", "actual", size_line = 0.5)

library(dplyr, warn.conflicts = FALSE)
pr_plot(df, "fitted", "actual", "sample(c(1, 2), n(), TRUE)")

pr_plot(df, "fitted", "actual",
        "sample(c(1, 2), n(), TRUE)",
        "sample(c(3, 4), n(), TRUE)")

pr_plot(df, "fitted", "actual",
        "sample(c(1, 2), n(), TRUE)",
        "sample(c(3, 4), n(), TRUE)",
        "sample(c(5, 6), n(), TRUE)")
```

quick_facet

Quick facet

Description

Applies faceting to ggplot objects when g[["data"]] has a facet_x or facet_y column.

Usage

```
quick_facet(g, ncol = NULL, ...)
```

Arguments

<code>g</code>	A ggplot object.
<code>ncol</code>	Number of facet columns.
<code>...</code>	Arguments to pass to <code>facet_grid</code> or <code>facet_wrap</code> .

<code>reorder_levels</code>	<i>Order levels of factor columns using <code>fct_reorder</code></i>
-----------------------------	--

Description

Order levels of factor columns using `fct_reorder`

Usage

```
reorder_levels(
  data,
  cols = c("group", "facet_x", "facet_y"),
  y = "y",
  .desc = rep(TRUE, length(cols))
)
```

Arguments

<code>data</code>	A data.frame.
<code>cols</code>	Names of columns to reorder.
<code>y</code>	Numeric column for order priority.
<code>.desc</code>	A logical vector of length 1 or <code>ncol(data)</code> . Default is TRUE for all columns in <code>cols</code> .

Value

A data.frame.

Examples

```
str(ezplot::reorder_levels(mtcars, "cyl", "1"))
str(ezplot::reorder_levels(mtcars, "cyl", "1", FALSE))
str(ezplot::reorder_levels(mtcars, "cyl", "mpg"))
```

*roc**roc*

Description

Calculates ROC and AUC

Usage

```
roc(fitted, actual)
```

Arguments

<code>fitted</code>	Vector with values between 0 and 1
<code>actual</code>	Vector with two levels

Examples

```
ezplot:::roc(runif(1), sample(c(TRUE, FALSE), 1, replace = TRUE))  
ezplot:::roc(runif(3), sample(c(TRUE, FALSE), 3, replace = TRUE))
```

*roc_plot**roc_plot*

Description

`roc_plot`

Usage

```
roc_plot(  
  data,  
  fitted,  
  actual,  
  group = NULL,  
  facet_x = NULL,  
  facet_y = NULL,  
  palette = ez_col,  
  size_line = 1,  
  size = 11,  
  env = parent.frame()  
)
```

Arguments

<code>data</code>	A data.frame.
<code>fitted</code>	Vector of fitted values
<code>actual</code>	Vector of actual values
<code>group</code>	A character value. Evaluates to a column.
<code>facet_x</code>	A character value. Evaluates to a column.
<code>facet_y</code>	A character. Evaluates to a column.
<code>palette</code>	Colour function.
<code>size_line</code>	width of line for <code>geom_line()</code> . Default is 1.
<code>size</code>	theme size for <code>use_theme()</code> . Default is 14.
<code>env</code>	environment for evaluating expressions.

Examples

```
library(ggplot2)
n = 1000
df = data.frame(actual = sample(c(FALSE, TRUE), n, replace = TRUE),
                 runif = runif(n))
df[["fitted"]] = runif(n) ^ ifelse(df[["actual"]] == 1, 0.5, 2)

ggplot(df) +
  geom_density(aes(fitted, fill = actual), alpha = 0.5)

roc_plot(df, "actual", "actual")
roc_plot(df, "fitted", "actual")
roc_plot(df, "runif", "actual", size_line = 0.5)

library(dplyr, warn.conflicts = FALSE)
roc_plot(df, "fitted", "actual", "sample(c(1, 2), n(), TRUE)")

roc_plot(df, "fitted", "actual",
         "sample(c(1, 2), n(), TRUE)",
         "sample(c(3, 4), n(), TRUE)")

roc_plot(df, "fitted", "actual",
         "sample(c(1, 2), n(), TRUE)",
         "sample(c(3, 4), n(), TRUE)",
         "sample(c(5, 6), n(), TRUE)")
```

 save_png

save_png

Description

Saves ggplot or ezplot objects to png.

Usage

```
save_png(g, file, width, height, res, ..., vp = NULL)
```

Arguments

<code>g</code>	A ggplot or ezplot object.
<code>file</code>	A png file path.
<code>width</code>	Width of output image.
<code>height</code>	Height of output image.
<code>res</code>	Resolution of output image.
<code>...</code>	Further arguments to pass to <code>png()</code> .
<code>vp</code>	A viewport object created with <code>grid::viewport</code> .

scatter_plot

scatter plot

Description

create a scatter plot

Usage

```
scatter_plot(
  data,
  x,
  y,
  group = NULL,
  palette = ez_col,
  size = 11,
  point_size = 2.5,
  env = parent.frame()
)
```

Arguments

<code>data</code>	A data.frame.
<code>x</code>	A named character value. Evaluates to a column.
<code>y</code>	A named character value. Evaluates to a column.
<code>group</code>	A character value. Evaluates to a column.
<code>palette</code>	Colour function.
<code>size</code>	theme size for <code>use_theme()</code> . Default is 14.
<code>point_size</code>	Numeric. Default is 2.
<code>env</code>	environment for evaluating expressions.

Examples

```
scatter_plot(mtcars, "wt", "hp")
scatter_plot(mtcars, "wt", "hp", "factor(cyl)")
scatter_plot(mtcars, "factor(cyl)", "hp")
```

secondary_plot	<i>secondary_plot creates a plot with a secondary y-axis</i>
----------------	--

Description

secondary_plot creates a plot with a secondary y-axis

Usage

```
secondary_plot(
  data,
  x,
  y1 = "1",
  y2 = "1",
  facet_x = NULL,
  facet_y = NULL,
  palette = ez_col,
  size_line = 1,
  labels_y1 = ez_labels,
  labels_y2 = ez_labels,
  ylim1 = NULL,
  ylim2 = NULL,
  reorder = c("facet_x", "facet_y"),
  size = 11
)
```

Arguments

data	A data.frame.
x	A named character value. Evaluates to a column.
y1	Variable to plot on the left-hand axis
y2	Variable to plot on the right-hand axis
facet_x	A character value. Evaluates to a column.
facet_y	A character. Evaluates to a column.
palette	Colour function.
size_line	line size
labels_y1	label formatting function
labels_y2	label formatting function
ylim1	(optional) left axis limits

ylim2	(optional) right axis limits
reorder	A character vector specifying the group variables to reorder. Default is c("group", "facet_x", "facet_y")
size	theme size for use_theme(). Default is 14.

Value

A ggplot object.

Examples

```
library(tsibble)
library(tsibbledata)
secondary_plot(pelt, "Year", "Hare", "Lynx")
secondary_plot(pelt, "Year", c("Hare Population" = "Hare"), c("Lynx Population" = "Lynx"))
secondary_plot(aus_production, "Quarter",
               c("Quarterly Beer Production (megalitres)" = "Beer"),
               c("Quarterly Cement Production (tonnes)" = "Cement"),
               "lubridate::quarter(Quarter)",
               ylim1 = c(0, 600), ylim2 = c(0, 3000),
               size = 10)
```

side_plot

side_plot

Description

side_plot

Usage

```
side_plot(
  data,
  x,
  y = "1",
  labels_y = ez_labels,
  size = 11,
  palette = ez_col,
  signif = 3,
  reorder = TRUE,
  rescale_y = 1.25
)
```

Arguments

data	A data.frame.
x	A named character value. Evaluates to a column.
y	A named character value. Evaluates to a column.

labels_y	label formatting function
size	theme size for use_theme(). Default is 14.
palette	Colour function.
signif	Number of significant digits.
reorder	A character vector specifying the group variables to reorder. Default is c("group", "facet_x", "facet_y")
rescale_y	Rescaling factor for y-axis limits

Examples

```
side_plot(mtcars, "gear", "1", rescale_y = 4/3)
side_plot(mtcars, "cyl", c("Cars with <120 HP" = "hp < 120"))
side_plot(mtcars, "cyl", c(count = "ifelse(cyl == 4, 1, -1)", "hp <= 120"))
side_plot(mtcars, "cyl", c("hp <= 120", "~ - wt / cyl"), rescale_y = 1.5)
side_plot(mtcars, "cyl", c("1", "-1"))
```

text_contrast	<i>text_contrast</i>
---------------	----------------------

Description

text_contrast

Usage

```
text_contrast(x)
```

Arguments

x Vector of colours.

Value

Vector indicating whether black or white should be used for text overlayed on x.

Examples

```
text_contrast("#000000")
text_contrast("black")
```

theme_ez	<i>Default theme</i>
----------	----------------------

Description

Default theme

Usage

```
theme_ez(base_size = 11, base_family = "")
```

Arguments

base_size	base font size
base_family	base fond family

Value

theme

Examples

```
library(ggplot2)
ggplot(mtcars) + geom_point(aes(cyl, mpg)) + theme_ez()
```

tile_plot	<i>tile_plot</i>
-----------	------------------

Description

Creates tile plots.

Usage

```
tile_plot(
  data,
  x,
  y,
  z = c(Count = "1"),
  facet_x = NULL,
  facet_y = NULL,
  size = 11,
  facet_ncol = NULL,
  labels_x = NULL,
  labels_y = NULL,
  labels_z = ez_labels,
```

```

  zlim = function(x) c(pmin(0, x[1]), pmax(0, x[2])),
  palette = ez_jet,
  reorder = c("facet_x", "facet_y")
)

```

Arguments

data	A data.frame.
x	A named character value. Evaluates to a column.
y	A named character value. Evaluates to a column.
z	A named character. Evaluates to a column and is mapped to the fill colour of the tiles.
facet_x	A character value. Evaluates to a column.
facet_y	A character. Evaluates to a column.
size	theme size for use_theme(). Default is 14.
facet_ncol	Option passed to ncol argument in facet_wrap or facet_grid. Default is NULL.
labels_x	label formatting function
labels_y	label formatting function
labels_z	label formatting function
zlim	argument for scale_fill_gradientn(limits = zlim)
palette	Colour function.
reorder	A character vector specifying the group variables to reorder. Default is c("group", "facet_x", "facet_y")

Examples

```

## Not run:
library(tsibbledata)
library(dplyr)
nyc_bikes %>%
  mutate(duration = as.numeric(stop_time - start_time)) %>%
  filter(between(duration, 0, 16)) %>%
  tile_plot(c("Hour of Day" = "lubridate::hour(start_time) + 0.5"),
            c("Ride Duration (min)" = "duration - duration %% 2 + 1"))

## End(Not run)

```

unpack_cols

Unpack cols argument to agg_data

Description

Unpack cols argument to agg_data

Usage

```
unpack_cols(x)
```

Arguments

```
x          cols
```

Value

```
list
```

Examples

```
ezplot:::unpack_cols("x")  
ezplot:::unpack_cols(c(x = "x", y = "x + y", expr = "~ x + y"))
```

```
variable_plot
```

```
variable_plot
```

Description

Plots variables (multiple "y" values) broken out as vertical facets.

Usage

```
variable_plot(  
  data,  
  x,  
  y,  
  group = NULL,  
  facet_x = NULL,  
  palette = ez_col,  
  size = 14,  
  labels_y = ez_labels,  
  geom = "line",  
  size_line = 1,  
  ylab = NULL,  
  yoy = FALSE,  
  switch = "y",  
  rescale_y = 1  
)
```

Arguments

data	A data.frame.
x	A named character value. Evaluates to a column.
y	A named character value. Evaluates to a column.
group	A character value. Evaluates to a column.
facet_x	A character value. Evaluates to a column.
palette	Colour function.
size	theme size for use_theme(). Default is 14.
labels_y	label formatting function
geom	Either "line", "col" or "bar". Default is "line"
size_line	width of line for geom_line(). Default is 1.
ylab	y label text
yoy	Logical used to indicate whether a YOY grouping should be created. Default is FALSE.
switch	Option to switch location of variable (facet) labels. Default is 'y' (yes) which shows facet strips on left side of panels.
rescale_y	Rescaling factor for y-axis limits

Examples

```
library(tsibble)
library(tsibbledata)
variable_plot(ansett, "Week", "Passengers", facet_x = "Class")
variable_plot(ansett, "Week", "Passengers", facet_x = "Class", yoy = TRUE)
variable_plot(pelt, "Year", c("Lynx", "Hare"), "round(Year, -1)")
variable_plot(hh_budget, "Year", c("Debt", "Expenditure"), "Country")
variable_plot(PBS, "Type", "Scripts", "Concession", switch = "y", geom = "col")
variable_plot(subset(hh_budget, Year > 2013), "Year",
  c("Debt\n(% of disposable income)" = "Debt",
    "Expenditure\nGrowth (%)" = "Expenditure",
    "Unemployment (%)" = "Unemployment"),
  facet_x = "Country", geom = "bar")
variable_plot(subset(hh_budget, Year > 2013), "Year",
  c("Debt\n(% of disposable income)" = "Debt",
    "Expenditure\nGrowth (%)" = "Expenditure",
    "Unemployment (%)" = "Unemployment"),
  group = "Country", geom = "bar")
```

waterfall_plot	<i>waterfall_plot</i>
----------------	-----------------------

Description

function for creating waterfall charts

Usage

```
waterfall_plot(
  data,
  x,
  y,
  group,
  size = 11,
  labels = ez_labels,
  label_rescale = 1,
  y_min = "auto",
  rescale_y = 1.1,
  n_signif = 3,
  rotate_xlabel = FALSE,
  bottom_label = TRUE,
  ingroup_label = FALSE,
  n_x = 2,
  env = parent.frame()
)
```

Arguments

<code>data</code>	A data.frame.
<code>x</code>	A named character value. Evaluates to a column.
<code>y</code>	A named character value. Evaluates to a column.
<code>group</code>	A character value. Evaluates to a column.
<code>size</code>	theme size for use_theme(). Default is 14.
<code>labels</code>	Function for formatting labels.
<code>label_rescale</code>	Scaling factor for chart labels (relative to axis labels).
<code>y_min</code>	Minimum limit of y axis.
<code>rescale_y</code>	Rescaling factor for y-axis limits
<code>n_signif</code>	Number of significant figures in labels.
<code>rotate_xlabel</code>	Logical.
<code>bottom_label</code>	Logical.
<code>ingroup_label</code>	Logical. Shows in-group percentage change.
<code>n_x</code>	Number of x levels to show in chart.
<code>env</code>	environment for evaluating expressions.

Examples

```
library(tsibbledata)
waterfall_plot(aus_retail,
               "lubridate::year(Month)",
               "Turnover",
               "sub(' Territory', '\nTerritory', State)",
               rotate_xlabel = TRUE)
waterfall_plot(aus_retail,
               "lubridate::year(Month)",
               "Turnover",
               "sub(' Territory', '\nTerritory', State)",
               rotate_xlabel = TRUE,
               label_rescale = 0.5,
               ingroup_label = TRUE,
               bottom_label = FALSE,
               n_x = 3,
               size = 20,
               y_min = 0)
```

Index

agg_data, 2
area_plot, 3

bar_plot, 5

calendar_plot, 7

density_plot, 7
distribution_plot, 8

ez_app, 9
ez_col, 10
ez_jet, 10
ez_labels, 11
ez_png, 12
ez_server, 13
ez_ui, 13

get_incr, 13

histogram_plot, 14

lift_plot, 15
line_plot, 16

model_plot, 17

na_plot, 19
nameifnot, 18
no_null, 20
not_numeric, 19

perf, 20
perf_df, 22
performance_plot, 21
pie_plot, 22
pr_plot, 24
prec_rec, 24

quick_facet, 25

reorder_levels, 26

roc, 27
roc_plot, 27

save_png, 28
scatter_plot, 29
secondary_plot, 30
side_plot, 31

text_contrast, 32
theme_ez, 33
tile_plot, 33

unpack_cols, 34

variable_plot, 35

waterfall_plot, 37