

Package ‘flexpolyline’

June 25, 2020

Type Package

Title Flexible Polyline Encoding

Version 0.1.0

Description Binding to the C++ implementation of the flexible polyline encoding by HERE <<https://github.com/heremaps/flexible-polyline>>. The flexible polyline encoding is a lossy compressed representation of a list of coordinate pairs or coordinate triples. The encoding is achieved by:

- (1) Reducing the decimal digits of each value;
- (2) encoding only the offset from the previous point;
- (3) using variable length for each coordinate delta; and
- (4) using 64 URL-safe characters to display the result.

License GPL-3

URL <https://munterfinger.github.io/flexpolyline>,
<https://github.com/munterfinger/flexpolyline>

BugReports <https://github.com/munterfinger/flexpolyline/issues>

LinkingTo Rcpp

Imports Rcpp, sf (>= 0.9-3)

Suggests testthat (>= 2.3.2), stringr (>= 1.4.0), knitr (>= 1.28),
rmarkdown (>= 2.1), covr (>= 3.5.0)

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

VignetteBuilder knitr

NeedsCompilation yes

Author Merlin Unterfinger [aut, cre],
HERE Europe B.V. [aut, cph] (Flexible polyline encoding C++
implementation)

Maintainer Merlin Unterfinger <info@munterfinger.ch>

Repository CRAN

Date/Publication 2020-06-25 12:10:11 UTC

R topics documented:

decode	2
decode_sf	3
encode	3
encode_sf	4
Index	6

decode	<i>Decode a flexible polyline encoded string</i>
--------	--

Description

This function calls `hf::polyline_decode` and `hf::get_third_dimension` of the C++ implementation of the flexible polyline encoding by HERE. Depending on the dimensions of the encoded line, a two or three dimensional line is decoded.

Usage

```
decode(encoded)
```

Arguments

`encoded` character, encoded flexible polyline string.

Value

A matrix containing the coordinates of the decoded line.

Examples

```
# 2d line
decode("BFoz5xJ67i1B1B7PzIhaxL7Y")

# 3d line
decode("B1Boz5xJ67i1BU1B7PUzIhaUxL7YU")
```

decode_sf	<i>Wrapper function for decoding to simple features</i>
-----------	---

Description

A wrapper function for [decode](#) that converts the input polylines, encoded in the flexible polyline encoding, to simple feature geometries of the sf package.

Usage

```
decode_sf(encoded, crs = sf::NA_crs_)
```

Arguments

encoded	character, encoded flexible polyline string.
crs	integer or character, coordinate reference system to assign to the sf object (default = sf::NA_crs_).

Value

An sf object, containing the geometries of the decoded lines (Geometry type: "LINESTRING").

Note

The function returns an sf object, therefore the input set of encoded polylines must be of consistent dimension (e.g "XY", "XYM" or "XYZ") to meet the requirements of the constructor of sf objects. For mixed dimensions use the [decode](#) function directly.

Examples

```
# 2d line
decode_sf("BFoz5xJ67i1B1B7PzIhaxL7Y")

# 3d line
decode_sf("B1Boz5xJ67i1BU1B7PUzIhaUxL7YU")
```

encode	<i>Encode a line in the flexible polyline encoding format</i>
--------	---

Description

This function calls `hf::polyline_encode` of the C++ implementation of the flexible polyline encoding by [HERE](#). Depending on the dimensions of the input coordinates, a two or three dimensional line is encoded.

Usage

```
encode(line, precision = 5L, third_dim = 3L, third_dim_precision = 5L)
```

Arguments

line	matrix, coordinates of the line in 2d or 3d (column order: LNG, LAT, DIM3).
precision	integer, precision to use in encoding (between 0 and 15, default=5).
third_dim	integer, type of the third dimension (0: ABSENT, 1: LEVEL, 2: ALTITUDE, 3: ELEVATION, 4, 6: CUSTOM1, 7: CUSTOM2, default=3).
third_dim_precision	integer, precision to use in encoding for the third dimension (between 1 and 15, default=5).

Value

The line as string in the flexible polyline encoding format.

Examples

```
# 2D
line2d <- matrix(
  c(8.69821, 50.10228,
    8.69567, 50.10201,
    8.69150, 50.10063,
    8.68752, 50.09878),
  ncol = 2, byrow = TRUE
)
encode(line2d)

# 3D
line3d <- matrix(
  c(8.69821, 50.10228, 10,
    8.69567, 50.10201, 20,
    8.69150, 50.10063, 30,
    8.68752, 50.09878, 40),
  ncol = 3, byrow = TRUE
)
encode(line3d)
```

 encode_sf

Wrapper function for encoding simple features

Description

A wrapper function for [encode](#) that converts simple feature geometries of the sf package to flexible polyline encoded strings.

Usage

```

encode_sf(
  line,
  precision = 5,
  third_dim = NULL,
  third_dim_precision = precision
)

```

Arguments

line	simple feature, sf, sfc or sfg object with geometry type "LINESTRING".
precision	integer, precision to use in encoding (between 0 and 15, default=5).
third_dim	integer, type of the third dimension (0: ABSENT, 1: LEVEL, 2: ALTITUDE, 3: ELEVATION, 4, 6: CUSTOM1, 7: CUSTOM2, default=NULL).
third_dim_precision	integer, precision to use in encoding for the third dimension (between 1 and 15, default=precision).

Value

The line as string in the flexible polyline encoding format.

Examples

```

# 2D
line2d <- sf::st_linestring(
  matrix(
    c(8.69821, 50.10228,
      8.69567, 50.10201,
      8.69150, 50.10063,
      8.68752, 50.09878),
    ncol = 2, byrow = TRUE
  )
)
encode_sf(line2d)

# 3D
line3d <- sf::st_linestring(
  matrix(
    c(8.69821, 50.10228, 10,
      8.69567, 50.10201, 20,
      8.69150, 50.10063, 30,
      8.68752, 50.09878, 40),
    ncol = 3, byrow = TRUE
  )
)
encode_sf(line3d)

```

Index

decode, [2](#), [3](#)
decode_sf, [3](#)

encode, [3](#), [4](#)
encode_sf, [4](#)