

Package ‘fuzzyFDR’

February 19, 2015

Type Package

Title Exact calculation of fuzzy decision rules for multiple testing

Version 1.0

Date 2007-10-16

Author Alex Lewin

Maintainer Alex Lewin <a.m.lewin@imperial.ac.uk>

Description Exact calculation of fuzzy decision rules for multiple testing. Choose to control FDR (false discovery rate) using the Benjamini and Hochberg method, or FWER (family wise error rate) using the Bonferroni method. Kulinsakaya and Lewin (2007).

License GPL

NeedsCompilation no

Repository CRAN

Date/Publication 2007-10-16 20:03:41

R topics documented:

fuzzyFDR-package	1
example1	2
example2	3
fuzzyBHexact	3

Index

5

fuzzyFDR-package

Exact calculation of fuzzy decision rules for multiple testing

Description

Exact calculation of fuzzy decision rules for multiple testing. Choose to control FDR (false discovery rate) using the Benjamini and Hochberg method, or FWER (family wise error rate) using the Bonferroni method. Kulinsakaya and Lewin (2007).

Details

Package: fuzzyFDR
 Type: Package
 Version: 1.0
 Date: 2007-10-16
 License: GPL

~~ An overview of how to use the package, including the most important functions ~~

Author(s)

Alex Lewin Maintainer: Alex Lewin <a.m.lewin@imperial.ac.uk>

References

Kulinskaya and Lewin (2007).

Examples

```
data(example1)
names(example1)
fuzzyBHexact(example1$pvals,example1$pprev,alpha=0.05)
data(example2)
names(example2)
fuzzyBHexact(example2$pvals,example2$pprev,alpha=0.05)
```

example1

Examples 1 and 3 of Kulinskaya and Lewin

Description

Observed and previously attainable p-values used in Examples 1 and 3 of Kulinskaya and Lewin.

Usage

```
data(example1)
```

Format

A data frame with 7 observations on the following 2 variables.

pvals a numeric vector

pprev a numeric vector

Source

Kulinskaya and Lewin (2007).

Examples

```
data(example1)
fuzzyBHexact(example1$pvals, example1$pprev, alpha=0.05)
```

example2

Example 2 of Kulinskaya and Lewin

Description

Observed and previously attainable p-values used in Example 2 of Kulinskaya and Lewin.

Usage

```
data(example2)
```

Format

A data frame with 10 observations on the following 2 variables.

pvals a numeric vector

pprev a numeric vector

Source

Kulinskaya and Lewin (2007).

Examples

```
data(example2)
fuzzyBHexact(example2$pvals, example2$pprev, alpha=0.05)
```

fuzzyBHexact

Exact calculation of fuzzy decision rules (Benjamini and Hochberg FDR)

Description

Exact calculation of fuzzy decision rules for multiple testing. Controls the FDR (false discovery rate) using the Benjamini and Hochberg method.

Usage

```
fuzzyBHexact(pvals, pprev, alpha = 0.05, tol = 1e-05, q.myuni = T, dp = 20)
```

Arguments

pvals	observed discrete p-values
pprev	previously attainable p-values under the null distribution
alpha	significance level of the FDR procedure
tol	tolerance for my.match and my.unique
q.myuni	logical. Use my.match instead of match?
dp	no. decimal places to round p-values to

Details

my.match and my.unique may be used instead of match and unique if there is a problem with calculating the unique set of p-values (sometimes a problem with very small p-values)

Value

Data frame containing the p-values and previously attainable p-values input to the function, and the tau (fuzzy decision rule) output. Also contains the minimum and maximum ranks over allocations for each p-value.

Author(s)

Alex Lewin

References

Kulinsakaya and Lewin (2007).

Examples

```
data(example1)
names(example1)
fuzzyBHexact(example1$pvals,example1$pprev,alpha=0.05)
data(example2)
names(example2)
fuzzyBHexact(example2$pvals,example2$pprev,alpha=0.05)
```

Index

*Topic **datasets**

 example1, [2](#)

 example2, [3](#)

*Topic **htest**

 fuzzyBHexact, [3](#)

*Topic **package**

 fuzzyFDR-package, [1](#)

 example1, [2](#)

 example2, [3](#)

 fuzzyBHexact, [3](#)

 fuzzyFDR (fuzzyFDR-package), [1](#)

 fuzzyFDR-package, [1](#)