

Package ‘garchx’

May 10, 2020

Type Package

Title Flexible and Robust GARCH-X Modelling

Version 1.1

Date 2020-05-10

Author Genaro Sucarrat [aut, cre]

Maintainer Genaro Sucarrat <gsucarrat@gmail.com>

Description Flexible and robust estimation and inference of generalised autoregressive conditional heteroscedasticity (GARCH) models with covariates based on the results by Francq and Thieu (2018) <doi:10.1017/S0266466617000512>. Coefficients can straightforwardly be set to zero by omission, and quasi maximum likelihood methods ensure estimates are generally consistent and inference valid, even when the standardised innovations are non-normal and/or dependent over time.

License GPL (>= 2)

Depends R (>= 3.4.0), zoo

BugReports <https://github.com/gsucarrat/garchx/issues>

URL <https://CRAN.R-project.org/package=garchx>,
<http://www.sucarrat.net/>

NeedsCompilation yes

Repository CRAN

Date/Publication 2020-05-10 14:00:03 UTC

R topics documented:

garchx-package	2
coef.garchx	3
garchx	5
garchxAvar	7
garchxObjective	9
garchxSim	10
rmnrm	11
ttest0	12

garchx-package	<i>Flexible and Robust GARCH-X Modelling</i>
-----------------------	--

Description

Flexible and robust estimation and inference of GARCH(p,q,r)-X models, where p is the ARCH order, q is the GARCH order, r is the asymmetry or leverage order, and 'X' indicates that covariates can be included. Suitable subsets of the coefficients can be restricted to zero by omission, and Quasi Maximum Likelihood (QML) methods ensure estimates are generally consistent, even when the standardised innovations are non-normal and/or dependent.

Details

Package:	garchx
Type:	Package
Version:	1.1
Date:	2020-05-10
License:	GPL-2

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

Maintainer: Genaro Sucarrat

See Also

`garchxSim`, `coef`, `fitted`, `logLik`, `print`, `residuals`, `vcov`

Examples

```
##simulate from a garch(1,1):
set.seed(123)
y <- garchxSim(1000)

##estimate garch(1,1) model:
mymod <- garchx(y)
mymod
```

coef.garchx*Extraction functions for 'garchx' objects*

Description

Extraction functions for objects of class 'garchx'

Usage

```

## S3 method for class 'garchx'
coef(object, ...)
## S3 method for class 'garchx'
fitted(object, as.zoo = TRUE, ...)
## S3 method for class 'garchx'
logLik(object, ...)
## S3 method for class 'garchx'
nobs(object, ...)
## S3 method for class 'garchx'
predict(object, n.ahead = 10, newxreg = NULL,
        newindex = NULL, n.sim = 5000, verbose = FALSE, ...)
## S3 method for class 'garchx'
print(x, ...)
## S3 method for class 'garchx'
quantile(x, probs=0.025, names = TRUE, type = 7, as.zoo = TRUE, ...)
## S3 method for class 'garchx'
residuals(object, as.zoo = TRUE, ...)
## S3 method for class 'garchx'
toLatex(object, digits = 4, ...)
## S3 method for class 'garchx'
vcov(object, vcov.type = NULL, ...)

```

Arguments

object	an object of class 'garchx'
x	an object of class 'garchx'
as.zoo	logical. If TRUE, then the returned result is of class zoo
n.ahead	integer that determines how many steps ahead predictions should be generated
newxreg	vector or matrix with the out-of-sample regressor values
newindex	zoo-index for the out-of-sample predictions. If NULL (default), then 1:n.ahead is used
n.sim	integer, the number of simulations
verbose	logical. If TRUE, then the simulations - in addition to the predictions - are returned
probs	vector of probabilities

names	logical, whether to return names or not
type	integer that determines the algorithm used to compute the quantile, see quantile
digits	integer, the number of digits in the printed LaTeX code
vcov.type	NULL or a character that is (partially) matched to "ordinary" or "robust". The robust coefficient-covariance is that of Francq and Thieu (2018).
...	additional arguments

Value

coef:	numeric vector containing parameter estimates
fitted:	fitted conditional variance
logLik:	log-likelihood (normal density)
nobs:	the number of observations used in the estimation
predict:	a vector with the predictions (verbose=FALSE), or a matrix with both the predictions and the simulations (verbose=TRUE)
print:	print of the estimation results
quantile:	the fitted quantiles, i.e. the conditional standard deviation times the empirical quantile of the standardised innovations
residuals:	standardised residuals
vcov:	coefficient variance-covariance matrix

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

References

Christian Francq and Le Quien Thieu (2018): 'QML inference for volatility models with covariates', *Econometric Theory*, doi:10.1017/S026646617000512

See Also

[garchx](#), [garchxSim](#), [zoo](#)

Examples

```
##simulate from a garch(1,1):
set.seed(123)
y <- garchxSim(1000)

##estimate garch(1,1) model:
mymod <- garchx(y)

##print estimation results:
print(mymod)

##extract coefficients:
```

```

coef(mymod)

##extract and store conditional variances:
sigma2hat <- fitted(mymod)

##extract log-likelihood:
logLik(mymod)

##extract and store standardised residuals:
etahat <- residuals(mymod)

##extract coefficient variance-covariance matrix:
vcov(mymod)

##generate predictions:
predict(mymod)

```

garchx

Estimate a GARCH-X model

Description

Quasi Maximum Likelihood (ML) estimation of a GARCH(p,q,r)-X model, where p is the ARCH order, q is the GARCH order, r is the asymmetry (or leverage) order and 'X' indicates that covariates can be included. Note that the underlying estimation theory assumes the covariates are stochastic. The estimation procedure will, in general, provide consistent estimates when the standardised innovations are neither normal nor independent (or both), see Francq and Thieu (2018).

Usage

```

garchx(y, order = c(1,1), arch = NULL, garch = NULL, asym = NULL,
       xreg = NULL, vcov.type = c("ordinary", "robust"),
       initial.values = NULL, backcast.values = NULL, lower = 0,
       upper = +Inf, control = list(), hessian.control = list(),
       solve.tol = .Machine$double.eps, c.code = TRUE, penalty.value = NULL,
       sigma2.min = .Machine$double.eps, objective.fun = 1, turbo = FALSE)

```

Arguments

y	numeric vector, time-series or zoo object. Missing values in the beginning and at the end of the series is allowed, as they are removed with the na.trim command
order	integer vector of length 1, 2 or 3, for example c(1,1,1). The first entry controls the GARCH order, the second the ARCH order and the third the ASYM (asymmetry/leverage) order
arch	NULL or numeric vector containing the ARCH-terms to include. Note: If not NULL, then the value of the ARCH argument overrides the value of the first entry in the order argument

<code>garch</code>	NULL or numeric vector containing the GARCH-terms to include. Note: If not NULL, then the value of the GARCH argument overrides the value of the second entry in the <code>order</code> argument
<code>asym</code>	NULL or numeric vector containing the ASYM-terms (asymmetry/leverage terms) to include. Note: If not NULL, then the value of the ASYM argument overrides the value of the third entry in the <code>order</code> argument
<code>xreg</code>	numeric vector, time-series or <code>zoo</code> object. Missing values in the beginning and at the end of the series is allowed, as they are removed with the <code>na.trim</code> command
<code>vcov.type</code>	character, either "ordinary" or "robust", see <code>vcov.garchx</code>
<code>initial.values</code>	NULL or a numeric vector with the initial parameter values passed on to the optimisation routine, <code>nlminb</code> . If NULL, the default, then the values are chosen automatically
<code>backcast.values</code>	NULL or 0. The backcast values are used to initiate the forward recursion. If NULL (default), then the values are chosen automatically. If 0, then the initial recursion values are all set to 0
<code>lower</code>	numeric vector, either of length 1 or the number of parameters to be estimated, see <code>nlminb</code>
<code>upper</code>	numeric vector, either of length 1 or the number of parameters to be estimated, see <code>nlminb</code>
<code>control</code>	a <code>list</code> passed on to the <code>control</code> argument of <code>nlminb</code>
<code>hessian.control</code>	a <code>list</code> passed on to the <code>control</code> argument of <code>optimHess</code>
<code>solve.tol</code>	numeric value passed on to the <code>tol</code> argument of <code>solve</code> , which is called whenever the coefficient variance-covariance matrix is computed. The value controls the tolerance for detecting linear dependence between columns when inverting a matrix
<code>c.code</code>	logical, if TRUE then compiled C code is used in the forward recursion
<code>penalty.value</code>	NULL (default) or a numeric value. If NULL, then the log-likelihood value associated with the initial values is used. Sometimes estimation can result in NA and/or +/-Inf values. The <code>penalty.value</code> is the value returned by the objective function <code>garchxObjective</code> in the presence of NA or +/-Inf values
<code>sigma2.min</code>	numeric
<code>objective.fun</code>	numeric, either 1 or 0
<code>turbo</code>	logical. If FALSE (default), then the coefficient variance-covariance is computed during estimation, and the fitted values and residuals are attached to the returned object. If TRUE, then these operations are skipped, and hence estimation is faster. Note, however, that if <code>turbo</code> is set to TRUE, then the coefficient-covariance, fitted values and residuals can still be extracted subsequent to estimation with <code>vcov.garchx</code> , <code>fitted.garchx</code> and <code>residuals.garchx</code> , respectively

Value

A list of class 'garchx'

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

References

Christian Francq and Le Quien Thieu (2018): 'QML inference for volatility models with covariates', *Econometric Theory*, doi:10.1017/S0266466617000512 Christian Francq and Jean-Michel Zakoian (2019): 'GARCH Models', 2nd Edition, Wiley

See Also

`garchxSim`, `nlminb`, `optimHess`, `coef.garchx`

Examples

```
##simulate from a garch(1,1):
set.seed(123)
y <- garchxSim(1000)

##estimate garch(1,1) model:
mymod <- garchx(y)

##print estimation results:
print(mymod)

##extract coefficients:
coef(mymod)

##extract and store conditional variances:
sigma2hat <- fitted(mymod)

##extract log-likelihood:
logLik(mymod)

##extract and store standardised residuals:
etahat <- residuals(mymod)

##extract variance-covariance matrix:
vcov(mymod)

##generate predictions:
predict(mymod)
```

Description

Compute the asymptotic coefficient-covariance of a GARCH(p,q,r)-X model by simulation. Note that the principles of how to use the `arch`, `garch`, `asym` and `xreg` arguments are the same as those of `garchx`

Usage

```
garchxAvar(pars, arch = NULL, garch = NULL, asym = NULL,
           xreg = NULL, vcov.type = c("ordinary", "robust"),
           innovations = NULL, Eeta4 = NULL, n = 1e+06, objective.fun = 1,
           seed = NULL)
```

Arguments

<code>pars</code>	vector of parameters of length 1 or more. The first component contains the coefficient-value of the intercept, the next component(s) the ARCH-coefficient(s), and so on.
<code>arch</code>	NULL or integer vector with the lags of the ARCH-terms to include. Works in the same way as the <code>arch</code> argument in the <code>garchx</code> function
<code>garch</code>	NULL or integer vector with the lags of the GARCH-terms. Works in the same way as the <code>garch</code> argument in the <code>garchx</code> function
<code>asym</code>	NULL or integer vector with the lags of the asymmetry terms to include. Works in the same way as the <code>asym</code> argument in the <code>garchx</code> function
<code>xreg</code>	NULL, or a vector or matrix with the covariates of the model. Works in the same way as the <code>xreg</code> argument in the <code>garchx</code> function
<code>vcov.type</code>	character that determines the type of coefficient-covariance
<code>innovations</code>	NULL or a vector with the standardised innovations to use. If NULL, then the innovations are standard norm
<code>Eeta4</code>	numeric, the fourth moment of the innovations. If NULL, then the value is estimated internally. Note: The value of <code>Eeta4</code> is only used if <code>vcov.type = "ordinary"</code> , otherwise it is ignored
<code>n</code>	integer, the number of observations to use in the simulations
<code>objective.fun</code>	integer equal to 1 or 0 that determines the type of objective function to use, see the code of <code>garchxObjective</code>
<code>seed</code>	NULL or an integer that sets the seed (the value is passed on to <code>set.seed</code>). Useful for reproducibility

Value

A matrix

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

References

Christian Francq and Le Quien Thieu (2018): 'QML inference for volatility models with covariates', *Econometric Theory*, doi:10.1017/S0266466617000512 Christian Francq and Jean-Michel Zakoian (2019): 'GARCH Models', 2nd Edition, Wiley

See Also

[garchx](#), [garchxSim](#), [vcov.garchx](#)

Examples

```
##asymptotic coefficient-covariance of a garch(1,1)
##note: the estimate is rough, since n is small
intercept <- 0.2
alpha <- 0.1
beta <- 0.8
pars <- c(intercept, alpha, beta)
seed <- 123 #for reproducibility
garchxAvar(pars, arch=1, garch=1, n=10000, seed=seed)
```

[garchxObjective](#)

Auxiliary functions

Description

Auxiliary functions used in estimation. Not intended for the average user

Usage

```
garchxObjective(pars, aux)
garchxRecursion(pars, aux)
```

Arguments

<code>pars</code>	numeric vector of parameters
<code>aux</code>	<code>list</code> created by garchx

Value

<code>garchxObjective:</code>	value of the objective function
<code>garchxRecursion:</code>	fitted conditional variance

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

See Also

[garchx](#), [fitted.garchx](#), [residuals.garchx](#)

[garchxSim](#)

Simulate from a GARCH-X model

Description

Simulate from a GARCH(p,q,r)-X model. Optionally, if `verbose=TRUE`, the conditional variance and innovations are also returned.

Usage

```
garchxSim(n, intercept = 0.2, arch = 0.1, garch = 0.8, asym = NULL, xreg = NULL,
innovations = NULL, backcast.values = list(), verbose = FALSE, as.zoo = TRUE)
```

Arguments

<code>n</code>	integer
<code>intercept</code>	numeric
<code>arch</code>	NULL or numeric vector with the values of the ARCH-coefficients
<code>garch</code>	NULL or numeric vector with the values of the GARCH-coefficients
<code>asym</code>	NULL or numeric vector with the values of the asymmetry-coefficients
<code>xreg</code>	NULL or numeric vector with the values of the X-term
<code>innovations</code>	NULL or numeric vector with the innovations. If NULL, then standard normal innovations are generated with <code>rnorm</code>
<code>backcast.values</code>	<code>list</code> with backcast values
<code>verbose</code>	logical
<code>as.zoo</code>	logical. If TRUE (default), then the returned object is of class <code>zoo</code>

Value

a numeric vector or matrix with the simulated values.

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

See Also

[garchx](#), [zoo](#)

Examples

```
##simulate from a garch(1,1):
y <- garchxSim(1000)

##simulate from a garch(1,1) with asymmetry/leverage:
yy <- garchxSim(1000, asym=0.1)

##simulate from a garch(1,1) w/user-provided backcast values:
yyy <- garchxSim(1000, backcast.values=list(z2=1, sigma2=0.5))
```

rmnorn*Random number generation from the multivariate normal distribution*

Description

This function is a speed-optimised version of the `rmnorn` function from the `mnormt` package of Adelchi Azzalini (2013).

Usage

```
rmnorn(n, mean = NULL, vcov = 1)
```

Arguments

<code>n</code>	integer, the number of observations to generate
<code>mean</code>	numeric vector, i.e. the mean values
<code>vcov</code>	numeric matrix, i.e. the variance-covariance matrix

Value

A matrix of `n` rows

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

References

Adelchi Azzalini (2013): 'mnormt: The multivariate normal and t distributions', R package version 1.4-7, <https://CRAN.R-project.org/package=mnormt>

Examples

```
##generate from univariate standardised normal:  
z1 <- rmnorm(100)  
  
##generate from bivariate, independent standardised normal:  
z2 <- rmnorm(100, vcov=diag(c(1,1)))  
  
##generate from bivariate, dependent standardised normal:  
z3 <- rmnorm(100, vcov=cbind(c(1,0.3),c(0.3,1)))
```

ttest0

T-tests and Wald-tests under nullity

Description

The permissible parameter-space of GARCH-models is bounded from below by 0. This means non-standard inference is required when one or more parameters are 0 under the null hypothesis. The functions *ttest0* and *waldtest0* perform t-tests and Wald-tests when one or more parameters is 0. In the latter test, the Wald-test, the critical values are obtained by simulation, see Francq and Thieule (2018).

Usage

```
ttest0(x, k = NULL)
waldtest0(x, r = 0, R = NULL, level = c(0.1,0.05,0.01),
          vcov.type = NULL, quantile.type = 7, n = 20000)
```

Arguments

- x an object of class 'garchx'
- k NULL (default) or a vector of integers with the coefficients to test. If NULL, then all coefficients apart from the intercepts are tested
- r vector with restrictions
- R NULL (default) or a full-rank matrix. If NULL, then R is specified such that a test of all coefficients - apart from the intercept - is equal to the restriction r. If length(r)==1, then it is recycled so that its dimension match that of R
- level vector of significance levels whose critical values should be computed
- vcov.type NULL or a character that determines the type of coefficient-covariance to use, see [vcov.garchx](#)
- quantile.type integer, the algorithm used to compute the quantile, see [quantile](#)
- n integer, the numer of simulations used to estimate the critical values

Details

The `ttest0` function performs a t-test of coefficient `k` with 0 as null. Under this null the parameter is on the boundary of the admissible parameter space, and so the distribution is non-standard under the null. The function `ttest0` returns the result(s) of these non-standard t-test(s), see Francq and Thieu (2018). If `k=NULL`, the default, then a test for each coefficient apart from the intercept is undertaken.

The `waldtest0` function performs a Wald-test of the restrictions in `r`, when one or more of its elements are 0, see Francq and Thieu (2018).

Value

- `ttest0:` a matrix with the t-tests
- `waldtest0:` a list with the test-statistic and the critical values

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

References

Christian Francq and Le Quien Thieu (2018): 'QML inference for volatility models with covariates', *Econometric Theory*, doi:10.1017/S026646617000512

See Also

[garchx](#), [quantile](#), [vcov.garchx](#), [rmnorm](#)

Examples

```
##simulate and estimate a garch(1,1):
set.seed(123)
y <- garchxSim(1000)
mymod <- garchx(y)

##t-tests:
ttest0(mymod)

##wald-test:
waldtest0(mymod)
```

Index

*Topic Econometrics

coef.garchx, 3
garchx, 5
garchx-package, 2
garchxAvar, 7
garchxObjective, 9
garchxSim, 10
rmnrm, 11
ttest0, 12

*Topic Financial Econometrics

coef.garchx, 3
garchx, 5
garchx-package, 2
garchxAvar, 7
garchxObjective, 9
garchxSim, 10
rmnrm, 11
ttest0, 12

*Topic Statistical Models

coef.garchx, 3
garchx, 5
garchx-package, 2
garchxAvar, 7
garchxObjective, 9
garchxSim, 10
rmnrm, 11
ttest0, 12

*Topic Time Series

coef.garchx, 3
garchx, 5
garchx-package, 2
garchxAvar, 7
garchxObjective, 9
garchxSim, 10
rmnrm, 11
ttest0, 12

coef, 2

coef.garchx, 3, 7

fitted, 2
fitted.garchx, 6, 10
fitted.garchx (coef.garchx), 3

garchx, 4, 5, 8–10, 13
garchx-package, 2
garchxAvar, 7
garchxObjective, 6, 8, 9
garchxRecursion (garchxObjective), 9
garchxSim, 2, 4, 7, 9, 10

list, 6, 9, 10
logLik, 2
logLik.garchx (coef.garchx), 3

na.trim, 5, 6
nlminb, 6, 7
nobs.garchx (coef.garchx), 3

optimHess, 6, 7

predict.garchx (coef.garchx), 3
print, 2
print.garchx (coef.garchx), 3

quantile, 4, 12, 13
quantile.garchx (coef.garchx), 3

residuals, 2
residuals.garchx, 6, 10
residuals.garchx (coef.garchx), 3
rmnrm, 11, 11, 13
rnorm, 10

set.seed, 8
solve, 6

toLatex.garchx (coef.garchx), 3
ttest0, 12

vcov, 2

`vcov.garchx`, 6, 9, 12, 13
`vcov.garchx(coef.garchx)`, 3
`waldtest0(ttest0)`, 12
`zoo`, 3–6, 10