

Package ‘gotop’

April 25, 2020

Title Scroll Back to Top Icon in R Markdown and Shiny

Version 0.1.1

Description Add a scroll back to top 'Font Awesome' icon in R Markdown documents and Shiny apps using 'jQuery GoTop'.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

Imports jsonlite, htmltools

URL <https://felixluginbuhl.com/gotop>, <https://github.com/lgnbhl/gotop>

BugReports <https://github.com/lgnbhl/gotop/issues>

NeedsCompilation no

Author Félix Luginbuhl [aut, cre]

Maintainer Félix Luginbuhl <felix.luginbuhl@protonmail.ch>

Repository CRAN

Date/Publication 2020-04-25 18:20:02 UTC

R topics documented:

use_gotop	2
Index	4

 use_gotop

 Add scroll up icon

Description

Add scroll up icon

Usage

```
use_gotop(
  src = "fas fa-chevron-up",
  width = 45,
  opacity = 0.5,
  place = "right",
  color = "",
  appear = 200,
  scrolltime = 800,
  fadein = 500,
  fadeout = 500,
  marginX = 2,
  marginY = 2,
  container = "",
  zIndex = 9
)
```

Arguments

src	string	The CSS classes used to display the arrow.
width	integer	The width of the arrow.
opacity	decimal	Sets the transparency level for the arrow, where 1 is not transparent at all, 0.5 is 50 percent see-through and 0 is completely transparent.
place	string	The location where the arrow will be shown. Valid values are "right" or "left".
color	string	The color of the selected CSS classes icon.
appear	integer	The amount of pixels the page must be scrolled down before the arrow is displayed.
scrolltime	integer	A number determining how long the animation will run when scrolling to the top of the page.
fadein	integer	A number determining how long the animation will run when fading in to opaque.
fadeout	integer	A number determining how long the animation will run when fading out to transparent.
marginX	integer	The percentage amount indicating how far away the arrow is from the bottom, left, or right, depending on the value of place.

use_gotop

3

marginY	integer The percentage amount indicating how far away the arrow is from the top or bottom, depending on the value of place.
container	string The HTML element to which the scroll function will be attached. If no value is given, then the scroll function will be attached to the window.
zIndex	integer The z-index value.

Value

Javascript code initializing GoTop with dependencies

Examples

`use_gotop()`

Index

`use_goto`, 2