

Package ‘gsEasy’

May 23, 2018

Type Package

Title Gene Set Enrichment Analysis in R

Version 1.3

Date 2018-05-23

Author Daniel Greene

Maintainer Daniel Greene <dg333@cam.ac.uk>

Description R-interface to C++ implementation of the rank/score permutation based GSEA test (Subramanian et al 2005 <doi: 10.1073/pnas.0506580102>).

License GPL (>= 2)

Imports Rcpp (>= 0.11.2), ontologyIndex (>= 2.0)

LinkingTo Rcpp

Depends R (>= 3.0.0)

Suggests knitr

VignetteBuilder knitr

RoxygenNote 6.0.1

NeedsCompilation yes

Repository CRAN

Date/Publication 2018-05-23 11:04:45 UTC

R topics documented:

gsEasy-package	2
get_GO_gene_sets	2
get_ontological_gene_sets	3
GO_gene_sets	4
gset	4

Index	6
--------------	----------

gsEasy-package

Gene Set Enrichment Analysis in R

Description

R-interface to C++ implementation of the rank/score based GSEA test described by Subramanian et al 2005.

Details

Package: gsEasy
Type: Package
Version: 1.0
Date: 2016-01-11
License: GPL >= 2

Author(s)

Daniel Greene <dg333@cam.ac.uk>

Maintainer: Daniel Greene <dg333@cam.ac.uk>

References

Subramanian, A, Tamayo, P, Mootha, VK, Mukherjee, S, Ebert, BL, Gillette, MA, Paulovich, A, Pomeroy, SL, Golub, TR, Lander, ES, Mesirov, JP (2005). Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. Proc. Natl. Acad. Sci. U.S.A., 102, 43:15545-50, doi: 10.1073/pnas.0506580102.

Ashburner et al. Gene ontology: tool for the unification of biology (2000) Nat Genet 25(1):25-9

get_GO_gene_sets

Create list of gene sets defined by GO term annotation

Description

Note, this function takes several minutes to execute.

Usage

```
get_GO_gene_sets(GO_annotation_file,  
  GO_file = "http://purl.obolibrary.org/obo/go.obo", min_genes = 15,  
  max_genes = 500, verbose = TRUE)
```

Arguments

GO_annotation_file	File path of annotation file, which should contain a column of genes and a column of terms. Can be downloaded from at http://geneontology.org/gene-associations/gene_association.goa_human.gz .
GO_file	File path of gene ontology.
min_genes	Minimum number of genes in gene sets.
max_genes	Maximum number of genes in gene sets.
verbose	Print progress.

Value

List of character vectors of term IDs.

get_ontological_gene_sets

Create list of gene sets defined by ontological annotation

Description

Create list of gene sets defined by ontological annotation

Usage

```
get_ontological_gene_sets(ontology, gene, term, min_genes = 1,  
  max_genes = 500)
```

Arguments

ontology	ontology_index object.
gene	Character vector of genes.
term	Character vector of term IDs annotated to corresponding genes.
min_genes	Minimum number of genes in gene sets.
max_genes	Maximum number of genes in gene sets.

Value

List of character vectors of term IDs.

GO_gene_sets	<i>GO term gene sets</i>
--------------	--------------------------

Description

List of gene sets annotated by each GO term

Format

List of character vectors of genes per GO term, and named by term ID.

Details

Based on gene-GO term annotations downloaded from geneontology.org. Only contains gene sets for terms with up to 500 genes.

gset	<i>Gene set enrichment test</i>
------	---------------------------------

Description

Gene set enrichment test

Usage

```
gset(S, N = NULL, r = NULL, p = 1, min_its = 200, max_its = 1e+05,
     significance_threshold = 0.05, log_dismiss = -10, raw_score = FALSE)
```

Arguments

S	Ranks of gene set
N	Integer value. Only required if r is not specified.
r	Rank/correlation scores. If S is character, then r must be named by gene or be a character vector of the gene names in rank order (necessarily containing S).
p	Weighting of ranking/correlations, see Subramanian et. al 2005.
min_its	Minimum number of null permutations to compare.
max_its	Maximum number of null permutations to compare.
significance_threshold	Maximum p-value of significant result.
log_dismiss	Threshold log probability of returning a significant result, below which function returns current p-value.
raw_score	Logical value determining whether to return the raw value of the gene set enrichment score.

gset

5

Value

Numeric value - p-value of enrichment.

Examples

```
gset(S=1:5 * 2, N=1000)  
gset(S=letters[1:3], r=letters)
```

Index

[get_GO_gene_sets](#), 2
[get_ontological_gene_sets](#), 3
[GO_gene_sets](#), 4
[gsEasy \(gsEasy-package\)](#), 2
[gsEasy-package](#), 2
[gset](#), 4