

# Package ‘hot.deck’

March 28, 2020

**Type** Package

**Title** Multiple Hot-Deck Imputation

**Version** 1.1-2

**Date** 2020-03-27

**Author** Skyler Cranmer, Jeff Gill, Natalie Jackson, Andreas Murr, Dave Armstrong

**Maintainer** Dave Armstrong <dave@quantoid.net>

**Description**

Performs multiple hot-deck imputation of categorical and continuous variables in a data frame.

**License** GPL (>= 2)

**Depends** R (>= 3.0)

**Imports** mice, stats

**Suggests** knitr, mitools, miceadds

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2020-03-28 05:50:10 UTC

## R topics documented:

hot.deck-package . . . . .	2
affinity . . . . .	3
D . . . . .	4
hd2amelia . . . . .	5
hot.deck . . . . .	5
is.discrete . . . . .	7
isq99 . . . . .	8
scaleContinuous . . . . .	9

<b>Index</b>	<b>10</b>
--------------	-----------

---

`hot.deck-package`*Multiple Hot Deck Imputation*

---

## Description

This package contains all of the functions necessary to perform multiple hot deck imputation on an input data frame with missing observations using either the “best cell” method (default) or the “probabilistic draw” method as described in Cranmer and Gill (2013). This technique is best suited for missingness in discrete variables, though it also works well for continuous missing observations.

## Details

Package: hot.deck  
Type: Package  
Version: 1.0  
Date: 2014-09-03  
License: What license is it under?

In multiple hot deck imputation, several observed values of the variable with missing observations are drawn conditional on the rest of the data and are used to impute each missing value. The advantage of this class of methods over multiple imputation is that the imputed values are actually draws from the observed data. As such, when discrete variables are imputed with a hot deck method, their discrete properties are maintained.

Two methods for weighting the imputations are provided in this package. The “best cell” [called as “best.cell”] technique uses the degree of affinity between the row with missing data and each potential donor row to generate weights such that rows more closely resembling the row with missingness are more likely to be drawn as donors. The probabilistic draw method is the default method. The “probabilistic draw” [called as “p.draw”] technique is also available. The best cell method draws randomly from the cell of best matches to the row with a missing observation.

## Author(s)

Skyler Cranmer, Jeff Gill, Natalie Jackson, Andreas Murr and Dave Armstrong Maintainer: Dave Armstrong <dave@quantoid.net>

## References

Cranmer, S.J. and Gill, J.M.. (2013) “We Have to Be Discrete About This: A Non-Parametric Imputation Technique for Missing Categorical Data.” *British Journal of Political Science* 43:2 (425-449).

---

affinity

*Affinity Calculation*

---

### Description

Calculates affinity based on Cranmer and Gill (2013). The function performs the original method (as described in the article) and also a method that takes into account the correlation structure of the observed data that increases efficiency in making matches.

### Usage

```
affinity(data, index, column = NULL, R = NULL, weighted = FALSE)
```

### Arguments

data	A data frame or matrix of values for which affinity should be calculated
index	A row number identifying the target observation. Affinity will be calculated between this observation and all others in the dataset.
column	A column number identifying the variable with missing information. This is only needed for the optional correlation-weighted affinity score. The correlation that is used is the correlation of all variables with the focus variable (i.e., the column).
R	A correlation matrix for data.
weighted	Logical indicating whether or not the correlation-weighted affinity measure should be used.

### Details

Affinity is calculated by first identifying whether two observations are sufficiently ‘close’ on each variable. Consider the target observation number 1. If observation  $i$  is close to the target observation on variable  $j$ , then  $A[i, j] = 1$  otherwise, it equals zero. Close for two discrete variables is defined by them taking on the same value. Close for continuous variables is taking on a distance no greater than 1 from each other. While this may seem restrictive and arbitrary, arguments exist in the main package function `hot.deck` that allows the user to set how many standard deviations equal a distance of 1 (with the `cutoffSD` argument).

### Value

A number of missing observation-variable combinations-by-number of observations in data matrix of affinity scores.

### Author(s)

Skyler Cranmer, Jeff Gill, Natalie Jackson, Andreas Murr and Dave Armstrong

## References

Cranmer, S.J. and Gill, J.M.. (2013) “We Have to Be Discrete About This: A Non-Parametric Imputation Technique for Missing Categorical Data.” *British Journal of Political Science* 43:2 (425-449).

## See Also

[hot.deck](#)

## Examples

```
data(D)
out <- hot.deck(D)
```

---

D

*Example data for multiple hot deck imputation.*

---

## Description

Simulated example data for multiple hot deck imputation.

## Usage

```
data(D)
```

## Format

A data frame with 20 observations on the following 5 variables.

x1 a numeric vector

x2 a numeric vector

x3 a numeric vector

x4 a numeric vector

x5 a numeric vector

## Examples

```
data(D)
out <- hot.deck(D)
```

---

hd2amelia	<i>Convert hot.deck output to Amelia format</i>
-----------	---

---

**Description**

Converts the output from hot.deck to the format used by Amelia for use with the Zelig package.

**Usage**

```
hd2amelia(object)
```

**Arguments**

object            Output from a run of the hot . deck function.

**Value**

An object of class “amelia” that can be used with Zelig.

**Author(s)**

Skyler Cranmer, Jeff Gill, Natalie Jackson, Andreas Murr and Dave Armstrong

---

hot.deck	<i>Multiple Hot Deck Imputation</i>
----------	-------------------------------------

---

**Description**

This function performs multiple hot deck imputation on an input data frame with missing observations using either the “best cell” method (default) or the “probabilistic draw” method as described in Cranmer and Gill (2013). This technique is best suited for missingness in discrete variables, though it also performs well on continuous missing data.

**Usage**

```
hot.deck(data, m = 5, method = c("best.cell", "p.draw"), cutoff = 10, sdCutoff = 1,  
optimizeSD = FALSE, optimStep = 0.1, optimStop = 5, weightedAffinity = FALSE,  
impContinuous = c("HD", "mice"), IDvars = NULL, ...)
```

**Arguments**

data	A data frame or matrix with missing values to be imputed using multiple hot deck imputation.
m	Number of imputed datasets required.
method	Method used to draw donors based on affinity either “best.cell” (the default) or “p.draw” for probabilistic draw
cutoff	A numeric scalar such that any variable with fewer than cutoff unique non-missing values will be considered discrete and necessarily imputed with hot deck imputation.
sdCutoff	Number of standard deviations between observations such that observations fewer than sdCutoff standard deviations away from each other are considered sufficiently close to be a match, otherwise they are considered too far away to be a match.
optimizeSD	Logical indicating whether the sdCutoff parameter should be optimized such that the smallest possible value is chosen that produces no thin cells from which to draw donors. Thin cells are those where the number of donors is less than m.
optimStep	The size of the steps in the optimization if optimizeSD is TRUE.
optimStop	The value at which optimization should stop if it has not already found a value that produces no thin cells. If this value is reached and thin cells still exist, a warning will be returned, though the routine will continue using optimStop as sdCutoff.
weightedAffinity	Logical indicating whether a correlation-weighted affinity score should be used.
impContinuous	Character string indicating how continuous missing data should be imputed. Valid options are “HD” (the default) in which case hot-deck imputation will be used, or “mice” in which case multiple imputation by chained equations will be used.
IDvars	A character vector of variable names not to be used in the imputation, but to be included in the final imputed datasets.
...	Optional additional arguments to be passed down to the mice routine.

**Value**

A list with the following elements:

data	An object of class <code>mi</code> which contains <code>m</code> imputed datasets.
affinity	A matrix of affinity scores see <a href="#">affinity</a> .
donors	A list of donors for each missing observation based on the affinity score.
draws	The <code>m</code> observations drawn from donors that were used for the multiple imputations.
max.emp.aff	Normalization constant for each row of affinity scores; the maximum possible value of the affinity scores if correlation-weighting is used.
max.the.aff	Normalization constant for each row of affinity scores; the number of columns in the original data.

**Author(s)**

Skyler Cranmer, Jeff Gill, Natalie Jackson, Andreas Murr and Dave Armstrong

**References**

Cranmer, S.J. and Gill, J.M.. (2013) "We Have to Be Discrete About This: A Non-Parametric Imputation Technique for Missing Categorical Data." *British Journal of Political Science* 43:2 (425-449).

van Buuren, S. and Karin Groothuis-Oudshoorn (2011). "mice: Multivariate Imputation by Chained Equations in R." *Journal of Statistical Software*, 45:3 (1-67).

**See Also**

[mice](#), [affinity](#)

**Examples**

```
data(D)
hot.deck(D)
```

---

is.discrete

*Identify whether variables are discrete or continuous*

---

**Description**

Variables are considered discrete if they have fewer unique, non-missing values than cutoff or they are factors. Otherwise, variables are considered continuous.

**Usage**

```
is.discrete(data, cutoff = 10)
```

**Arguments**

data	A data frame, matrix or vector of values to be evaluated.
cutoff	A numeric scalar identifying the cutoff relative to the number of unique, non-missing values for 'discreteness'.

**Value**

A logical vector indicating whether variables are discrete (TRUE) or continuous FALSE.

**Author(s)**

Skyler Cranmer, Jeff Gill, Natalie Jackson, Andreas Murr and Dave Armstrong

---

isq99

*Data from Poe, Tate and Keith 1999.*

---

### **Description**

Data on Democracy, State Repression and other state-level characteristics

### **Usage**

```
data(isq99)
```

### **Format**

A data frame with 3222 observations on the following 13 variables.

IDORIGIN Country Code

YEAR Year

AI Amnesty International PTS Coding

SD State Department Country Report PTS Coding

POLRT Freedom House Political Rights Variable

MIL2 Military Government

LEFT Leftist Government

BRIT British Colonial Influence

PCGNP GNP/capita

LPOP Log of population

DEMOC3 Polity III Democracy

CWARCOW COW Civil War

IWARCOW2 COW Interstate War

### **References**

Steven Poe, C. Neal Tate and Linda Camp Keith. 1999. "Repression of the Human Right to Personal Integrity Revisited: A Global, Cross-National Study Covering the Years 1976-1993". *International Studies Quarterly*. 43: 291-313.



---

scaleContinuous      *Standardize continuous variables.*

---

**Description**

Standardizes (centers and scales) continuous variable in a dataset, leaving discrete variables untouched.

**Usage**

```
scaleContinuous(data, discrete, sd = 1)
```

**Arguments**

data	A data frame or matrix of variables to be scaled.
discrete	Either a logical vector which is TRUE for discrete variables and FALSE for continuous ones or a vector of column numbers of discrete variables.
sd	The standard deviation of the columns for the continuous variables.

**Value**

A data frame with the same dimensions as data where the continuous variables are centered and scaled.

**Author(s)**

Skyler Cranmer, Jeff Gill, Natalie Jackson, Andreas Murr and Dave Armstrong

# Index

\*Topic **datasets**

D, 4

isq99, 8

\*Topic **multiple imputation**

affinity, 3

hot.deck, 5

hot.deck-package, 2

\*Topic **package**

hot.deck-package, 2

affinity, 3, 6, 7

D, 4

hd2amelia, 5

hot.deck, 4, 5

hot.deck-package, 2

is.discrete, 7

isq99, 8

mice, 7

scaleContinuous, 9