

Package ‘ipfp’

August 29, 2016

Type Package

Title Fast Implementation of the Iterative Proportional Fitting Procedure in C

Version 1.0.1

Author Alexander W Blocker

Maintainer Alexander W Blocker <a blocker@gmail.com>

Description A fast (C) implementation of the iterative proportional fitting procedure. Based on corresponding code from the networkTomography package.

License Apache License (== 2.0)

LazyLoad yes

URL <https://github.com/awblocker/ipfp>

Collate 'ipfp.R'

RoxygenNote 5.0.1

NeedsCompilation yes

Repository CRAN

Date/Publication 2016-02-14 23:02:26

R topics documented:

ipfp 1

Index 3

ipfp *Function to run IPFP (iterative proportional fitting procedure)*

Description

Use IPFP starting from x_0 to produce vector x s.t. $Ax = y$ within tolerance. Need to ensure that $x_0 > 0$.

Usage

```
ipfp(y, A, x0, tol = sqrt(.Machine$double.eps), maxit = 1000,
      verbose = FALSE, full = FALSE)
```

Arguments

y	numeric constraint vector (length nrow)
A	constraint matrix (nrow x ncol)
x0	numeric initial vector (length ncol)
tol	numeric tolerance for IPFP; defaults to <code>sqrt(.Machine\$double.eps)</code>
maxit	integer maximum number of iterations for IPFP; defaults to 1e3
verbose	logical parameter to select verbose output from C function
full	logical parameter to select full return (with diagnostic info)

Value

if not full, a vector of length ncol containing solution obtained by IPFP. If full, a list containing solution (as x), the number of iterations (as iter), and the L2 norm of Ax - y (as errNorm)

Examples

```
A <- matrix(c(1,0,0, 1,0,0, 0,1,0, 0,1,0, 0,0,1), nrow=3)
x <- rgamma(ncol(A), 10, 1/100)
y <- A %*% x
x0 <- x * rgamma(length(x), 10, 10)
ans <- ipfp(y, A, x0, full=TRUE)
print(ans)
print(x)
```

Index

*Topic **array**

 ipfp, [1](#)

*Topic **iteration**

 ipfp, [1](#)

ipfp, [1](#)