

Package ‘lingtypology’

April 26, 2020

Type Package

Title Linguistic Typology and Mapping

Version 1.1.3

Depends R (>= 3.5.0)

Imports leaflet, leaflet.minicharts, stats, utils, stringdist,
grDevices

Author George Moroz

Maintainer George Moroz <agricolamz@gmail.com>

Description Provides R with the Glottolog database <<http://glottolog.org>> and some more abilities for purposes of linguistic mapping. The Glottolog database contains the catalogue of languages of the world. This package helps researchers to make a linguistic maps, using philosophy of the Cross-Linguistic Linked Data project <<http://clld.org/>>, which allows for while at the same time facilitating uniform access to the data across publications. A tutorial for this package is available on GitHub pages <<https://docs.ropensci.org/lingtypology/>> and package vignette. Maps created by this package can be used both for the investigation and linguistic teaching. In addition, package provides an ability to download data from typological databases such as WALS, AUTOTYP and some others and to create your own database website.

License GPL (>= 2)

URL <https://CRAN.R-project.org/package=lingtypology>,

<https://github.com/ropensci/lingtypology/>,

<https://ropensci.github.io/lingtypology/>

BugReports <https://github.com/ropensci/lingtypology/issues>

LazyData TRUE

RoxygenNote 7.1.0

Encoding UTF-8

Suggests knitr, rmarkdown, testthat, covr, MASS, sp, rgeos, rgdal,
ggplot2

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2020-04-26 15:50:03 UTC

R topics documented:

abvd	3
abvd.feature	3
afbo.feature	4
aff.lang	4
amap	5
area.lang	5
atlas.database	6
autotyp	7
autotyp.feature	7
circassian	8
ggmap.feature	9
glottolog	10
gltc.iso	11
gltc.lang	11
imports	12
is.glottolog	12
iso.gltc	13
iso.lang	14
lang.aff	14
lang.gltc	15
lang.iso	16
lat.lang	16
long.lang	17
map.feature	18
oto_mangueanIC	23
oto_mangueanIC.feature	24
phoible	24
phoible.feature	25
phonological_profiles	25
polygon.points_fd	26
polygon.points_kde	26
providers	27
sails.feature	27
uralex	28
uralex.feature	29
url.lang	29
valpal.feature	30
wals	31
wals.feature	31

abvd*ABVD's Language identifiers*

Description

Language identifiers from ABVD (<https://abvd.shh.mpg.de/austronesian/>). This dataset is created for **abvd.feature** function.

Usage

```
abvd
```

Format

A data frame with 1468 rows and 2 variables:

id language identifier
glottocode Glottocode

abvd.feature*Download ABVD data*

Description

This function downloads data from ABVD (<https://abvd.shh.mpg.de/austronesian/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
abvd.feature(feature)
```

Arguments

feature A character vector that define a language id from ABVD (e. g. "1", "292").

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# abvd.feature(c(292, 7))
```

afbo.feature *Download AfBo data*

Description

This function downloads data from AfBo (<http://afbo.info>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
afbo.feature(features = "all", na.rm = TRUE)
```

Arguments

<code>features</code>	A character vector that define with an affix functions from AfBo (e. g. "all", "adjectivizer", "focus").
<code>na.rm</code>	Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# afbo.feature()
# afbo.feature(c("adjectivizer", "adverbializer"))
```

aff.lang *Get affiliation by language*

Description

Takes any vector of languages and return affiliation.

Usage

```
aff.lang(x)
```

Arguments

<code>x</code>	A character vector of the languages (can be written in lower case)
----------------	--

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[area.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
aff.lang('Korean')
aff.lang(c('Korean', 'Polish'))
```

amap

Atlantic center template for ggmap.feature() function

Description

.

Usage

amap

Format

A list with 9 variables.

area.lang

Get macro area by language

Description

Takes any vector of languages and return macro area.

Usage

area.lang(x)

Arguments

x character vector of the languages (can be written in lower case)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
area.lang('Adyghe')
area.lang(c('Adyghe', 'Aduge'))
```

`atlas.database`

Create an atlas

Description

This function creates an rmarkdown based atlas from data provided by users. This function creates the template, after it should be rendered by rmarkdown package. The DT package is required during the rendering.

Usage

```
atlas.database(
  languages,
  latitude,
  longitude,
  features,
  atlas.name = "",
  author = ""
)
```

Arguments

<code>languages</code>	character vector of languages (can be written in lower case)
<code>latitude</code>	numeric vector of latitudes (optional)
<code>longitude</code>	numeric vector of longitudes (optional)
<code>features</code>	dataframe where each column is a feature set
<code>atlas.name</code>	string with an atlas name
<code>author</code>	string with the authors list

autotyp	<i>AUTOTYP's Language identifiers</i>
---------	---------------------------------------

Description

Language identifiers from AUTOTYP v. 0.1.0 (<https://github.com/autotyp/autotyp-data>). This dataset is created for `autotyp.feature` function.

Usage

```
autotyp
```

Format

An object of class `data.frame` with 2950 rows and 2 columns.

Details

#' @format A data frame with 2950 rows and 2 variables:

LID language identifier

Glottocode Glottocode

autotyp.feature	<i>Download AUTOTYP data</i>
-----------------	------------------------------

Description

This function downloads data from AUTOTYP (<https://github.com/autotyp/autotyp-data#the-autotyp-database>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
autotyp.feature(features, na.rm = TRUE)
```

Arguments

`features` A character vector that define with a feature names from AUTOTYP.

`na.rm` Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# autotyp.feature(c('Gender', 'Numeral classifiers'))
```

circassian

Circassian villages in Russia

Description

A dataset contains the list of the Circassian villages in Russia with genealogical affiliation, coordinates and district names. Most data collected during the fieldworks (2011–2018).

Usage

circassian

Format

A data frame with 158 rows and 6 variables:

longitude longitude

latitude latitude

village name of the village

district names of the subjects of the Russian Federation: kbr — Kabardino-Balkar Republic, kch — Karachay-Cherkess Republic, kk — Krasnodar Krai, ra — Republic of Adygea, stv — Stavropol Krai

dialect names of the Circassian dialects

language according standard Circassian devision there are Adyghe and Kabardian languages

ggmap.feature	<i>Create a map with ggplot2</i>
---------------	----------------------------------

Description

Map a set of languages and color them by feature.

Usage

```
ggmap.feature(  
  languages,  
  features = "",  
  latitude = NA,  
  longitude = NA,  
  color = NULL,  
  title = NULL,  
  legend = TRUE,  
  width = 2,  
  opacity = 1,  
  map.orientation = "Atlantic"  
)
```

Arguments

languages	character vector of languages (can be written in lower case).
features	character vector of features.
latitude	numeric vector of latitudes.
longitude	numeric vector of longitudes.
color	vector of colors or palette. The color argument can be (1) a character vector of RGM or named colors; (2) the name of an RColorBrewer palette; (3) the full name of a viridis palette; (4) a function that receives a single value between 0 and 1 and returns a color. For more examples see colorNumeric .
title	title of a legend.
legend	logical. If TRUE, function show legend. By default is TRUE.
width	a numeric vector of radius for circles or width for barcharts in minicharts.
opacity	a numeric vector of marker opacity.
map.orientation	a character verctor with values "Pacific" and "Atlantic". It distinguishes Pacific-centered and Atlantic-centered maps. By default is "Atlantic".

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
ggmap.feature(c("Adyghe", "Russian"))
```

glottolog

Catalogue of languages of the world

Description

A dataset contains the original catalogue of languages of the world involving genealogical affiliation, macro-area, country, iso code, and coordinates.

Usage

glottolog

Format

A data frame with 20290 rows and 8 variables:

affiliation genealogical affiliation

glottocode languoid code from Glottolog 4.1

language name of the language

iso code based on ISO 639–3 <http://www-01.sil.org/iso639-3/>

level languoid type: dialect or language

longitude longitude

latitude latitude

area have six values Africa, Australia, Eurasia, North America, Papunesia, South America

Details

Hammarström, Harald & Forkel, Robert & Haspelmath, Martin. 2019. Glottolog 4.1. Jena: Max Planck Institute for the Science of Human History. (Available online at <http://glottolog.org>, Accessed on 2020-02-09.)

Source

<http://glottolog.org/>

gltc.iso

Get Glottocode by ISO 639–3 code

Description

Takes any vector of ISO 639–3 codes and returns Glottocodes.

Usage

`gltc.iso(x)`

Arguments

`x` A character vector of the Glottocodes.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

`aff.lang`, `area.lang`, `lat.lang`, `long.lang`

Examples

```
gltc.iso('ady')
gltc.iso(c('ady', 'rus'))
```

gltc.lang

Get Glottocode by language

Description

Takes any vector of languages and returns Glottocode.

Usage

`gltc.lang(x)`

Arguments

`x` A character vector of the languages (can be written in lower case)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
gltc.lang('Adyghe')
gltc.lang(c('Adyghe', 'Udi'))
```

imports

Objects imported from other packages

Description

These objects are imported from other packages. Follow the links to their documentation.

magrittr %>%

is.glottolog

Are these languages in glottolog?

Description

Takes any vector of languages or ISO codes and return a logical vector.

Usage

```
is.glottolog(x, response = FALSE)
```

Arguments

- x A character vector of languages (can be written in lower case)or ISO codes
- response logical. If TRUE, when language is absent, return warnings with a possible candidates.

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
is.glotolog(c('Adyghe', 'Russian'))
is.glotolog('Buyaka')

# Add warning message with suggestions
is.glotolog(c('Adygey', 'Russian'), response = TRUE)
# > FALSE TRUE
# Warning message:
# In is.glotolog(c('Adyge', 'Russian'), response = TRUE) :
# Language Adyge is absent in our version of the Glottolog database. Did you mean Aduge, Adyghe?
```

iso.gltc

Get ISO 639–3 code by Glottocode

Description

Takes any vector of Glotocodes and returns ISO code.

Usage

```
iso.gltc(x)
```

Arguments

x A character vector of Glottocodes.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
iso.gltc('adyg1241')
iso.gltc(c('adyg1241', 'udii1243'))
```

iso.lang*Get ISO 639–3 code by language***Description**

Takes any vector of languages and returns ISO code.

Usage

```
iso.lang(x)
```

Arguments

x	A character vector of the languages (can be written in lower case)
---	--

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
iso.lang('Adyghe')
iso.lang(c('Adyghe', 'Udi'))
```

lang.aff*Get languages by affiliation***Description**

Takes any vector of affiliations and return languages.

Usage

```
lang.aff(x, include.dialects = FALSE, list = FALSE)
```

Arguments

x	A character vector of the affiliations (can be written in lower case)
include.dialects	logical. If TRUE, it returns all languages and dialects, if FALSE it returns only languages.
list	logical. If TRUE, it returns a list of languages, if FALSE it returns a named vector.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[lang.iso](#)

Examples

```
lang.aff('Slavic')
lang.aff(c('Slavic', 'Celtic'))
lang.aff(c('Slavic', 'Celtic'), list = TRUE)
```

lang.gltc

Get language by Glottocode

Description

Takes any vector of Glottocodes and return languages.

Usage

```
lang.gltc(x)
```

Arguments

x A character vector of the Glottocodes.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[lang.aff](#)

Examples

```
lang.gltc('adyg1241')
lang.gltc(c('adyg1241', 'udii1243'))
```

`lang.iso`*Get language by ISO 639–3 code***Description**

Takes any vector of ISO codes and return languages.

Usage

```
lang.iso(x)
```

Arguments

<code>x</code>	A character vector of the ISO codes.
----------------	--------------------------------------

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

`lang.aff`

Examples

```
lang.iso('ady')
lang.iso(c('ady', 'rus'))
```

`lat.lang`*Get latitude by language***Description**

Takes any vector of languages and return latitude.

Usage

```
lat.lang(x)
```

Arguments

<code>x</code>	A character vector of the languages (can be written in lower case)
----------------	--

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [iso.lang](#), [long.lang](#)

Examples

```
lat.lang('Adyghe')
long.lang('Adyghe')
lat.lang(c('Adyghe', 'Russian'))
long.lang(c('Adyghe', 'Russian'))
```

long.lang

Get longitude by language

Description

Takes any vector of languages and return longitude.

Usage

```
long.lang(x, map.orientation = "Pacific")
```

Arguments

x	A character vector of the languages (can be written in lower case)
map.orientation	A character vector with values "Pacific" and "Atlantic". It distinguishes Pacific-centered and Atlantic-centered maps. By default is "Pacific".

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [iso.lang](#), [lat.lang](#)

Examples

```
lat.lang('Adyghe')
long.lang('Adyghe')
lat.lang(c('Adyghe', 'Russian'))
long.lang(c('Adyghe', 'Russian'))
long.lang(c('Adyghe', 'Aleut'), map.orientation = "Pacific")
```

`map.feature`*Create a map*

Description

Map a set of languages and color them by feature or two sets of features.

Usage

```
map.feature(  
  languages,  
  features = "",  
  label = "",  
  popup = "",  
  latitude = NA,  
  longitude = NA,  
  label.hide = TRUE,  
  label.fsize = 15,  
  label.font = "sans-serif",  
  label.position = "right",  
  label.emphasize = list(NULL, "black"),  
  shape = NULL,  
  shape.size = 20,  
  pipe.data = NULL,  
  shape.color = "black",  
  stroke.features = NULL,  
  point.cluster = FALSE,  
  density.estimation = NULL,  
  density.method = "fixed distance",  
  density.estimation.color = NULL,  
  density.estimation.opacity = 0.6,  
  density.points = TRUE,  
  density.width = NULL,  
  density.legend = TRUE,  
  density.legend.opacity = 1,  
  density.legend.position = "bottomleft",  
  density.title = "",  
  density.control = FALSE,  
  isogloss = NULL,  
  isogloss.color = "black",  
  isogloss.opacity = 0.2,  
  isogloss.line.width = 3,  
  isogloss.width = NULL,  
  color = NULL,  
  stroke.color = NULL,  
  image.url = NULL,  
  image.width = 100,
```

```
image.height = 100,  
image.X.shift = 0,  
image.Y.shift = 0,  
title = NULL,  
stroke.title = NULL,  
control = FALSE,  
legend = TRUE,  
legend.opacity = 1,  
legend.position = "topright",  
stroke.legend = TRUE,  
stroke.legend.opacity = 1,  
stroke.legend.position = "bottomleft",  
width = 5,  
stroke.radius = 9.5,  
opacity = 1,  
stroke.opacity = 1,  
scale.bar = TRUE,  
scale.bar.position = "bottomleft",  
minimap = FALSE,  
minimap.position = "bottomright",  
minimap.width = 150,  
minimap.height = 150,  
facet = NULL,  
tile = "OpenStreetMap.Mapnik",  
tile.name = NULL,  
zoom.control = FALSE,  
zoom.level = NULL,  
rectangle.lng = NULL,  
rectangle.lat = NULL,  
rectangle.color = "black",  
line.lng = NULL,  
line.lat = NULL,  
line.type = "standard",  
line.color = "black",  
line.opacity = 0.8,  
line.label = NULL,  
line.width = 3,  
graticule = NULL,  
minichart = "bar",  
minichart.data = NULL,  
minichart.time = NULL,  
minichart.labels = FALSE,  
map.orientation = "Pacific",  
radius = NULL  
)
```

Arguments

languages	character vector of languages (can be written in lower case)
-----------	--

features	character vector of features
label	character vector of strings that will appear near points
popup	character vector of strings that will appear in pop-up window
latitude	numeric vector of latitudes
longitude	numeric vector of longitudes
label.hide	logical. If FALSE, labels are displayed allways. If TRUE, labels are displayed on mouse over. By default is TRUE.
label.fsize	numeric value of the label font size. By default is 14.
label.font	string with values of generic family: "serif", "sans-serif", "monospace", or font name e. g. "Times New Roman"
label.position	the position of labels: "left", "right", "top", "bottom"
label.emphasize	is the list. First argument is a vector of points in datframe that should be emphasized. Second argument is a string with a color for emphasis.
shape	<ol style="list-style-type: none"> 1. if TRUE, creates icons (up to five categories) for values in the features variable; 2. it also could be a vector of any strings that represents the levels of the features variable; 3. it also could be a string vector that represents the number of observations in dataset.
shape.size	size of the shape icons
pipe.data	this variable is important, when you use <i>map.feature</i> with dplyr pipes. Expected usage: pipe.data = .
shape.color	color of the shape icons
stroke.features	additional independent stroke features
point.cluster	logical. If TRUE, points will be united into clusters.
density.estimation	additional independent features, used for density estimation
density.method	string with one of the two methods: "kernal density estimation" or "fixed distance" (default)
density.estimation.color	vector of density polygons' colors
density.estimation.opacity	a numeric vector of density polygons opacity.
density.points	logical. If FALSE, it doesn't show points in polygons.
density.width	for density.method = "fixed distance" it is a numeric measure (1 is 1km). For density.method = "kernal density estimation" it is a vector with two measures (first is latitude, secong is longitude). Defaults are normal reference bandwidth (see bandwidth.nrd).
density.legend	logical. If TRUE, function show legend for density features. By default is FALSE.

density.legend.opacity
 a numeric vector of density-legend opacity.
density.legend.position
 the position of the legend: "topright", "bottomright", "bottomleft", "topleft"
density.title title of a density-feature legend
density.control
 logical. If TRUE, function show layer control buttons for density plot. By default is FALSE
isogloss datafram with corresponding features
isogloss.color vector of isoglosses' colors
isogloss.opacity
 a numeric vector of density polygons opacity.
isogloss.line.width
 a numeric value for line width
isogloss.width for density.method = "fixed distance" it is a numeric measure (1 is 1km). For density.method = "kernal density estimation" it is a vector with two measures (first is latitude, secong is longitude). Defaults are normal reference bandwidth (see [bandwidth.nrd](#)).
color vector of colors or palette. The color argument can be (1) a character vector of RGM or named colors; (2) the name of an RColorBrewer palette; (3) the full name of a viridis palette; (4) a function that receives a single value between 0 and 1 and returns a color. For more examples see [colorNumeric](#)
stroke.color vector of stroke colors
image.url character vector of URLs with an images
image.width numeric vector of image widths
image.height numeric vector of image heights
image.X.shift numeric vector of image's X axis shift relative to the latitude-longitude point
image.Y.shift numeric vector of image's Y axis shift relative to the latitude-longitude point
title title of a legend.
stroke.title title of a stroke-feature legend.
control logical. If TRUE, function show layer control buttons. By default is FALSE
legend logical. If TRUE, function show legend. By default is TRUE.
legend.opacity a numeric vector of legend opacity.
legend.position
 the position of the legend: "topright", "bottomright", "bottomleft", "topleft"
stroke.legend logical. If TRUE, function show stroke.legend. By default is FALSE.
stroke.legend.opacity
 a numeric vector of stroke.legend opacity.
stroke.legend.position
 the position of the stroke.legend: "topright", "bottomright", "bottomleft", "topleft"
width a numeric vector of radius for circles or width for barcharts in minicharts.

<code>stroke.radius</code>	a numeric vector of stroke radii for the circles.
<code>opacity</code>	a numeric vector of marker opacity.
<code>stroke.opacity</code>	a numeric vector of stroke opacity.
<code>scale.bar</code>	logical. If TRUE, function shows scale-bar. By default is TRUE.
<code>scale.bar.position</code>	the position of the scale-bar: "topright", "bottomright", "bottomleft", "topleft"
<code>minimap</code>	logical. If TRUE, function shows mini map. By default is FALSE.
<code>minimap.position</code>	the position of the minimap: "topright", "bottomright", "bottomleft", "topleft"
<code>minimap.width</code>	The width of the minimap in pixels.
<code>minimap.height</code>	The height of the minimap in pixels.
<code>facet</code>	character vector that provide a grouping variable. If it is no NULL, then as a result a list of leaflets for sync or latticeView functions from <code>mapview</code> package is returned.
<code>tile</code>	a character vector with a map tiles, popularized by Google Maps. See here for the complete set.
<code>tile.name</code>	a character vector with a user's map tiles' names.
<code>zoom.control</code>	logical. If TRUE, function shows zoom controls. By default is FALSE.
<code>zoom.level</code>	a numeric value of the zoom level.
<code>rectangle.lng</code>	vector of two longitude values for rectangle.
<code>rectangle.lat</code>	vector of two latitude values for rectangle.
<code>rectangle.color</code>	vector of rectangle border color.
<code>line.lng</code>	vector of two (or more) longitude values for line.
<code>line.lat</code>	vector of two (or more) latitude values for line.
<code>line.type</code>	a character string indicating which type of line is to be computed. One of "standard" (default), or "logit". The first one should be combined with the arguments <code>line.lat</code> and <code>line.lng</code> and provide simple lines. Other variant "logit" is the decision boundary of the logistic regression made using longitude and latitude coordinates (works only if feature argument have two levels).
<code>line.color</code>	vector of line color.
<code>line.opacity</code>	a numeric vector of line opacity.
<code>line.label</code>	character vector that will appear near the line.
<code>line.width</code>	a numeric vector of line width.
<code>graticule</code>	a numeric vector for graticule spacing in map units between horizontal and vertical lines.
<code>minichart</code>	citation from <code>leaflet.minicharts</code> package: "Possible values are "bar" for bar charts, "pie" for pie charts, "polar-area" and "polar-radius"."
<code>minichart.data</code>	citation from <code>leaflet.minicharts</code> package: "A numeric matrix with number of rows equal to the number of elements in <code>lng</code> or <code>lat</code> and number of column equal to the number of variables to represent. If parameter <code>time</code> is set, the number of rows must be equal to the length of <code>lng</code> times the number of unique time steps in the data."

<code>minichart.time</code>	citation from leaflet.minicharts package: "A vector with length equal to the number of rows in chartdata and containing either numbers representing time indices or dates or datetimes. Each unique value must appear as many times as the others. This parameter can be used when one wants to represent the evolution of some variables on a map."
<code>minichart.labels</code>	citation from leaflet.minicharts package: "Should values be displayed above chart elements."
<code>map.orientation</code>	a character vector with values "Pacific" and "Atlantic". It distinguishes Pacific-centered and Atlantic-centered maps. By default is "Pacific".
<code>radius</code>	deprecated argument

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
map.feature(c("Adyghe", "Russian"))
```

oto_mangueanIC

Oto-Manguean Inflectional Class Database Language identifiers

Description

Language identifiers from Oto-Manguean Inflectional Class Database (<http://wals.info/>). This dataset is created for `oto_mangueanIC.feature` function.

Usage

```
oto_mangueanIC
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 20 rows and 2 columns.

Details

#' @format A data frame with 20 rows and 2 variables:

Language.name Language names from Oto-Manguean Inflectional Class Database

language Language names from Glottolog database

`oto_mangueanIC.feature`

Download Oto-Manguean Inflectional Class Database data

Description

This function downloads data from Oto-Manguean Inflectional Class Database (<http://www.oto-manguean.surrey.ac.uk/>) and creates a language column with the names from lingtypology database. You need the internet connection.

Usage

```
oto_mangueanIC.feature()
```

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [phoible.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# oto_mangueanIC.feature()
```

`phoible`

Phoible glottolog - language correspondencies

Description

Language correspondencies for Phoible (<https://phoible.org/>). This dataset is created for [phoible.feature](#) function.

Usage

```
phoible
```

Format

A data frame with 2185 rows and 2 variables:

language language

Glottocode Glottocode

phoible.feature *Download PHOIBLE data*

Description

This function downloads data from PHOIBLE (<http://phoible.org/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
phoible.feature(source = "all", na.rm = TRUE)
```

Arguments

source	A character vector that define with a source names from PHOIBLE (possible values: "all", "AA", "GM", "PH", "RA", "SAPHON", "SPA", "UPSID").
na.rm	Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# phoible.feature()
# phoible.feature(c('consonants', 'vowels'), source = "UPSID")
```

phonological_profiles *Number of consonants and presence of ejectives*

Description

Number of consonants and presence of ejectives

Usage

```
phonological_profiles
```

Format

A data frame with 19 rows and 4 variables:

language language name

consonants number of consonants. Based on UPSID database.

vowels number of vowels. Based on UPSID database.

ejectives presence of ejective sounds.

tone presence of tone.

stress presence of stress.

long_vowels presence of long vowels.

`polygon.points_fd`

Get polygons from fixed distance circles around coordinates

Description

This function is based on this answer: <https://www.r-bloggers.com/merging-spatial-buffers-in-r/>

Usage

```
polygon.points_fd(latitude, longitude, width)
```

Arguments

latitude numeric vector of latitudes

longitude numeric vector of longitudes

width radius for creating polygons around points

`polygon.points_kde`

Get kernel density estimation polygon from coordinates

Description

This function is based on this answer: <https://gis.stackexchange.com/a/203623>

Usage

```
polygon.points_kde(latitude, longitude, latitude.width, longitude.width)
```

Arguments

latitude	numeric vector of latitudes
longitude	numeric vector of longitudes
latitude.width	bandwidths for latitude values. Defaults to normal reference bandwidth (see bandwidth.nrd).
longitude.width	bandwidths for longitude values. Defaults to normal reference bandwidth (see bandwidth.nrd).

providers

Providers

Description

List of all providers with their variations taken from leaflet package

Usage

providers

Format

A list of characters

Source

<https://github.com/leaflet-extras/leaflet-providers/blob/master/leaflet-providers.js>

sails.feature

Download SAILS data

Description

This function downloads data from SAILS (<http://sails.cldd.org/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

sails.feature(features, na.rm = TRUE)

Arguments

<code>features</code>	A character vector that define with a feature ids from SAILS (e. g. "and1", "argex4-1-3").
<code>na.rm</code>	Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# sails.feature(c("and1", "and11"))
```

uralex

UraLex's Language identifiers

Description

Language identifiers from UraLex (<https://github.com/lexibank/uralex>). This dataset is created for [uralex.feature](#) function.

Usage

uralex

Format

A data frame with 27 rows and 3 variables:

language language name from database

Glottocode Glottocodes

language2 language from lingtypology

uralex.feature *Download UraLex data*

Description

This function downloads data from UraLex (<https://github.com/lexibank/uralex>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
uralex.feature(na.rm = TRUE)
```

Arguments

na.rm Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# uralex.feature()
```

url.lang *Make a url-link to glottolog page for a language*

Description

Takes any vector of languages and return links to glottolog pages.

Usage

```
url.lang(x, popup = "")
```

Arguments

x A character vector of languages (can be written in lower case)
popup character vector of strings that will appear in pop-up window of the function map.feature

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
url.lang('Korean')
url.lang(c('Gangou', 'Hachijo', 'Adyghe', 'Ganai'))
```

[valpal.feature](#)

Download ValPaL data

Description

This function downloads data from ValPal (<http://www.valpal.info/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
valpal.feature(na.rm = FALSE)
```

Arguments

na.rm	Logical. If TRUE function removes all languages not available in lingtypology database. By default is FALSE.
-------	--

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [uralex.feature](#), [wals.feature](#)

Examples

```
# valpal.feature()
```

wals	<i>WALS's Language identifiers</i>
------	------------------------------------

Description

Language identifiers from WALS (<http://wals.info/>). This dataset is created for `wals.feature` function.

Usage

```
wals
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 2679 rows and 2 columns.

Details

#' @format A data frame with 2950 rows and 2 variables:

wals code WALS language identifier
glottocode Glottocode

wals.feature	<i>Download WALS data</i>
--------------	---------------------------

Description

This function downloads data from WALS (<http://wals.info>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
wals.feature(features, na.rm = TRUE)
```

Arguments

- | | |
|-----------------------|---|
| <code>features</code> | A character vector that define with a feature ids from WALS (e. g. "1a", "21b"). |
| <code>na.rm</code> | Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE. |

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#),
[sails.feature](#), [uralex.feature](#), [valpal.feature](#)

Examples

```
# wals.feature(c("1a", "20a"))
```

Index

*Topic datasets

abvd, 3
amap, 5
autotyp, 7
circassian, 8
glottolog, 10
oto_mangueanIC, 23
phoible, 24
phonological_profiles, 25
providers, 27
uralex, 28
wals, 31
%>% (imports), 12
%>%, 12

abvd, 3
abvd.feature, 3, 3, 4, 8, 24, 25, 28–30, 32
afbo.feature, 3, 4, 8, 24, 25, 28–30, 32
aff.lang, 4, 6, 11–14, 17
amap, 5
area.lang, 5, 5, 11–14, 17
atlas.database, 6
autotyp, 7
autotyp.feature, 3, 4, 7, 7, 24, 25, 28–30, 32

bandwidth.nrd, 20, 21, 27

circassian, 8
colorNumeric, 9, 21

ggmap.feature, 9
glottolog, 10
gltc.iso, 11
gltc.lang, 11

imports, 12
is.glottolog, 12
iso.gltc, 13
iso.lang, 5, 6, 14, 17

lang.aff, 14, 15, 16

lang.gltc, 15
lang.iso, 15, 16
lat.lang, 5, 6, 11–14, 16, 17
long.lang, 5, 6, 11–14, 17, 17

map.feature, 18

oto_mangueanIC, 23
oto_mangueanIC.feature, 3, 4, 8, 23, 24, 25, 28–30, 32

phoible, 24
phoible.feature, 3, 4, 8, 24, 25, 28, 30, 32
phonological_profiles, 25
polygon.points_fd, 26
polygon.points_kde, 26
providers, 27

sails.feature, 3, 4, 8, 24, 25, 27, 29, 30, 32

uralex, 28
uralex.feature, 4, 8, 24, 25, 28, 29, 29, 30, 32

url.lang, 29

valpal.feature, 3, 4, 8, 24, 25, 28, 29, 30, 32

wals, 31
wals.feature, 3, 4, 8, 24, 25, 28–31, 31