

Package ‘metabolighteR’

December 6, 2019

Type Package

Title Interface to the 'Metabolights' RESTful API

Version 0.1.0

Date 2019-12-02

Description

Access to the 'Metabolights' RESTful API <<https://www.ebi.ac.uk/metabolights/index>>. Retrieve elements of publically available 'Metabolights' studies.

Depends magrittr

Imports httr, dplyr, purrr

License GPL (>= 3)

Encoding UTF-8

LazyData true

RoxygenNote 7.0.1

Suggests covr, testthat, tibble

NeedsCompilation no

Author Tom Wilson [aut, cre] (<<https://orcid.org/0000-0003-3112-4682>>)

Maintainer Tom Wilson <tpw2@aber.ac.uk>

Repository CRAN

Date/Publication 2019-12-06 10:20:02 UTC

R topics documented:

get_isa_investigation	2
get_private_studies	2
get_studies	3
get_study_contacts	3
get_study_desc	4
get_study_descriptors	4
get_study_factors	5
get_study_files	6

get_study_meta	6
get_study_protocols	7
get_study_pubs	7
get_study_title	8
get_webservice	9
mtbls_key	9

Index	10
--------------	-----------

get_isa_investigation *Get ISA Investigation File*

Description

Retrieve the ISA Investigation for a specified Metabolights Study

Usage

```
get_isa_investigation(study_id)
```

Arguments

study_id A character string of a valid MTBLS study id

Value

the ISA-tab Investigation output

Examples

```
## Not run:
ISA <- get_isa_investigation('MTBLS375')
writeLines(isa_investigation_parse, con = paste0('outpath/ISA.txt'))

## End(Not run)
```

get_private_studies *Get Private Studies*

Description

Retrieve all private studies which belong to your user account

Usage

```
get_private_studies()
```

Value

a tibble of your private Study IDs

Examples

```
## Not run:  
get_private_studies()  
  
## End(Not run)
```

<i>get_studies</i>	<i>Get Studies</i>
--------------------	--------------------

Description

Retrieve a list of all publically available Metabolights studies

Usage

```
get_studies()
```

Value

a tibble of Study IDs

Examples

```
get_studies()
```

<i>get_study_contacts</i>	<i>Get Study Contacts</i>
---------------------------	---------------------------

Description

Retrieve the contact details for a specified public study '

Usage

```
get_study_contacts(study_id)
```

Arguments

study_id a character string of a valid MTBLS study id

Value

a tibble of study contacts

Examples

```
## Not run:  
get_study_contacts('MTBLS375')  
  
## End(Not run)
```

<code>get_study_desc</code>	<i>Get Study Description</i>
-----------------------------	------------------------------

Description

Retrieve the abstract based description of a public study

Usage

```
get_study_desc(study_id)
```

Arguments

`study_id` A character string of a valid MTBLS study id

Value

a character string of the study description

Examples

```
## Not run:  
get_study_desc('MTBLS375')  
  
## End(Not run)
```

<code>get_study_descriptors</code>	<i>Get Study Descriptors</i>
------------------------------------	------------------------------

Description

Retrieve the study descriptors and annotation values for a publically available study

Usage

```
get_study_descriptors(study_id)
```

Arguments

`study_id` A character string of a valid MTBLS study id

Value

a tibble of study descriptors

Examples

```
## Not run:  
get_study_descriptors('MTBLS375')  
  
## End(Not run)
```

get_study_factors *Get Study Factors*

Description

Retrieve the study factors and annotation values for a publically available study

Usage

```
get_study_factors(study_id)
```

Arguments

study_id A character string of a valid MTBLS study id

Value

a tibble of study factors

Examples

```
## Not run:  
get_study_factors('MTBLS375')  
  
## End(Not run)
```

get_study_files	<i>Get Study Files</i>
-----------------	------------------------

Description

Retrieve the names and type of all files that have been deposited with the public study. If raw_data is TRUE then details of raw data files(ie, .mzML) are also returned.

Usage

```
get_study_files(study_id, raw_data = FALSE)
```

Arguments

study_id	A character string of a valid MTBLS study id
raw_data	logical; if TRUE then raw data file info is also returned. (Default is FALSE)

Value

a tibble of file info

Examples

```
## Not run:  
get_study_files('MTBLS375', raw_data = FALSE)  
  
## End(Not run)
```

get_study_meta	<i>Get Study Meta</i>
----------------	-----------------------

Description

Retrieve the meta data for a publically available study

Usage

```
get_study_meta(study_id)
```

Arguments

study_id	A character string of a valid MTBLS study id
----------	--

Value

a tibble of study meta data

Examples

```
## Not run:  
get_study_meta('MTBLS375')  
  
## End(Not run)
```

get_study_protocols *Get Study Protocols*

Description

Retrieve the protocol information that has been deposited for a public study

Usage

```
get_study_protocols(study_id)
```

Arguments

study_id A character string of a valid MTBLS study id

Value

a tibble of study protocols

Examples

```
## Not run:  
get_study_protocols('MTBLS375')  
  
## End(Not run)
```

get_study_pubs *Get Study Publications*

Description

Retrieve details on any publications that have been associated with the study

Usage

```
get_study_pubs(study_id)
```

Arguments

study_id A character string of a valid MTBLS study id

Value

a tibble of study publicatons

Examples

```
## Not run:  
get_study_pubs('MTBLS375')  
  
## End(Not run)
```

get_study_title	<i>Get Study Title</i>
-----------------	------------------------

Description

Retrieve the full title of the study

Usage

```
get_study_title(study_id)
```

Arguments

study_id A character string of a valid MTBLS study id

Value

a character string of the study title

Examples

```
## Not run:  
get_study_title('MTBLS375')  
  
## End(Not run)
```

get_webservice	<i>Get Web-service details</i>
----------------	--------------------------------

Description

Retrieve details about the Metabolights RESTful Webservice

Usage

```
get_webservice()
```

Value

a list of the MTBLS webservice information

Examples

```
get_webservice()
```

mtbls_key	<i>Set API Token</i>
-----------	----------------------

Description

Set your Metabolights API Token as global option. If MTBLS_API_KEY is set in `.Renvirom` then this variable will be passed directly to the MTBLS_API_KEY option. If no MTBLS_API_KEY is set in `.Renvirom`, then the API Token must be passed as an input in the `set_api_token` function

Usage

```
mtbls_key(API_KEY = NULL)
```

Arguments

API_KEY a character string of your Metabolights API Token (Default is NULL)

Examples

```
## Not run:  
  
# If API Token is set in `.Renvirom`  
  
mtbls_key()  
  
# If API Token is not set in `.Renvirom`  
  
mtbls_key('XXXX-0000-XXXX-0000')  
  
## End(Not run)
```

Index

`get_isa_investigation`, 2
`get_private_studies`, 2
`get_studies`, 3
`get_study_contacts`, 3
`get_study_desc`, 4
`get_study_descriptors`, 4
`get_study_factors`, 5
`get_study_files`, 6
`get_study_meta`, 6
`get_study_protocols`, 7
`get_study_pubs`, 7
`get_study_title`, 8
`get_webservice`, 9

`mtbls_key`, 9