

Package ‘mkin’

May 12, 2020

Type Package

Title Kinetic Evaluation of Chemical Degradation Data

Version 0.9.50.2

Date 2020-05-12

Description Calculation routines based on the FOCUS Kinetics Report (2006, 2014). Includes a function for conveniently defining differential equation models, model solution based on eigenvalues if possible or using numerical solvers. If a C compiler (on windows: 'Rtools') is installed, differential equation models are solved using automatically generated C functions. Please note that no warranty is implied for correctness of results or fitness for a particular purpose.

Imports stats, graphics, methods, deSolve, R6, inline, parallel, numDeriv, lmtest, pkgbuild, nlme, purrr

Suggests knitr, rbenchmark, tikzDevice, testthat, rmarkdown, covr, vdiff, benchmarkme, tibble, stats4

License GPL

LazyLoad yes

LazyData yes

Encoding UTF-8

Language en-GB

VignetteBuilder knitr

BugReports <http://github.com/jranke/mkin/issues>

URL <https://pkgdown.jrwb.de/mkin>

RoxygenNote 7.1.0

NeedsCompilation no

Author Johannes Ranke [aut, cre, cph]
(<<https://orcid.org/0000-0003-4371-6538>>),
Katrin Lindenberger [ctb],
René Lehmann [ctb],
Eurofins Regulatory AG [cph]

Maintainer Johannes Ranke <jranke@uni-bremen.de>

Repository CRAN

Date/Publication 2020-05-12 12:20:03 UTC

R topics documented:

add_err	3
AIC.mmkin	5
aw	6
CAKE_export	7
confint.mkinfit	9
create_deg_func	11
DFOP.solution	12
endpoints	13
experimental_data_for_UBA_2019	14
FOCUS_2006_datasets	16
FOCUS_2006_DFOP_ref_A_to_B	17
FOCUS_2006_FOMC_ref_A_to_F	18
FOCUS_2006_HS_ref_A_to_F	19
FOCUS_2006_SFO_ref_A_to_F	20
FOMC.solution	21
get_deg_func	22
HS.solution	22
ilr	23
IORE.solution	24
loftest	26
logistic.solution	27
logLik.mkinfit	29
lrtest.mkinfit	30
max_twa_parent	31
mccall81_245T	33
mkin	34
mkinerrmin	35
mkinerrplot	36
mkinfit	38
mkinmod	43
mkinparplot	45
mkinplot	46
mkinpredict	47
mkinresplot	50
mkin	51
mkin_long_to_wide	52
mkin_wide_to_long	53
mmkin	54
nafta	55
NAFTA_SOP_2015	57
NAFTA_SOP_Attachment	58

nlme.mmkin	58
nlme_function	61
nobs.mkinfit	62
parms	63
plot.mkinfit	64
plot.mmkin	67
plot.nafta	68
plot.nlme.mmkin	69
print.mkinds	71
print.mkinmod	71
residuals.mkinfit	72
schaefer07_complex_case	72
SFO.solution	73
SFORB.solution	74
sigma_twocomp	75
summary.mkinfit	76
synthetic_data_for_UBA_2014	78
test_data_from_UBA_2014	81
transform_odeparms	82
update.mkinfit	84
[.mmkin	85

Index**87**

add_err	<i>Add normally distributed errors to simulated kinetic degradation data</i>
---------	--

Description

Normally distributed errors are added to data predicted for a specific degradation model using [mkinpredict](#). The variance of the error may depend on the predicted value and is specified as a standard deviation.

Usage

```
add_err(
  prediction,
  sdfunc,
  secondary = c("M1", "M2"),
  n = 1000,
  LOD = 0.1,
  reps = 2,
  digits = 1,
  seed = NA
)
```

Arguments

prediction	A prediction from a kinetic model as produced by <code>mkinpredict</code> .
sdfunc	A function taking the predicted value as its only argument and returning a standard deviation that should be used for generating the random error terms for this value.
secondary	The names of state variables that should have an initial value of zero
n	The number of datasets to be generated.
LOD	The limit of detection (LOD). Values that are below the LOD after adding the random error will be set to NA.
reps	The number of replicates to be generated within the datasets.
digits	The number of digits to which the values will be rounded.
seed	The seed used for the generation of random numbers. If NA, the seed is not set.

Value

A list of datasets compatible with `mmkin`, i.e. the components of the list are datasets compatible with `mkinfit`.

Author(s)

Johannes Ranke

References

Ranke J and Lehmann R (2015) To t-test or not to t-test, that is the question. XV Symposium on Pesticide Chemistry 2-4 September 2015, Piacenza, Italy https://jrwb.de/posters/piacenza_2015.pdf

Examples

```
# The kinetic model
m_SF0_SF0 <- mkinmod(parent = mkinsub("SF0", "M1"),
                    M1 = mkinsub("SF0"), use_of_ff = "max")

# Generate a prediction for a specific set of parameters
sampling_times = c(0, 1, 3, 7, 14, 28, 60, 90, 120)

# This is the prediction used for the "Type 2 datasets" on the Piacenza poster
# from 2015
d_SF0_SF0 <- mkinpredict(m_SF0_SF0,
                        c(k_parent = 0.1, f_parent_to_M1 = 0.5,
                          k_M1 = log(2)/1000),
                        c(parent = 100, M1 = 0),
                        sampling_times)

# Add an error term with a constant (independent of the value) standard deviation
# of 10, and generate three datasets
d_SF0_SF0_err <- add_err(d_SF0_SF0, function(x) 10, n = 3, seed = 123456789 )
```

```

# Name the datasets for nicer plotting
names(d_SF0_SF0_err) <- paste("Dataset", 1:3)

# Name the model in the list of models (with only one member in this case) for
# nicer plotting later on. Be quiet and use only one core not to offend CRAN
# checks
## Not run:
f_SF0_SF0 <- mmkin(list("SF0-SF0" = m_SF0_SF0),
                   d_SF0_SF0_err, cores = 1,
                   quiet = TRUE)

plot(f_SF0_SF0)

# We would like to inspect the fit for dataset 3 more closely
# Using double brackets makes the returned object an mkinfit object
# instead of a list of mkinfit objects, so plot.mkinfit is used
plot(f_SF0_SF0[[3]], show_residuals = TRUE)

# If we use single brackets, we should give two indices (model and dataset),
# and plot.mmkin is used
plot(f_SF0_SF0[1, 3])

## End(Not run)

```

AIC.mmkin

Calculate the AIC for a column of an mmkin object

Description

Provides a convenient way to compare different kinetic models fitted to the same dataset.

Usage

```

## S3 method for class 'mmkin'
AIC(object, ..., k = 2)

## S3 method for class 'mmkin'
BIC(object, ...)

```

Arguments

object	An object of class <code>mmkin</code> , containing only one column.
...	For compatibility with the generic method
k	As in the generic method

Value

As in the generic method (a numeric value for single fits, or a dataframe if there are several fits in the column).

Author(s)

Johannes Ranke

Examples

```
## Not run: # skip, as it takes > 10 s on winbuilder
f <- mmkin(c("SFO", "FOMC", "DFOP"),
  list("FOCUS A" = FOCUS_2006_A,
    "FOCUS C" = FOCUS_2006_C), cores = 1, quiet = TRUE)
# We get a warning because the FOMC model does not converge for the
# FOCUS A dataset, as it is well described by SFO

AIC(f["SFO", "FOCUS A"]) # We get a single number for a single fit
AIC(f[["SFO", "FOCUS A"]]) # or when extracting an mkinfit object

# For FOCUS A, the models fit almost equally well, so the higher the number
# of parameters, the higher (worse) the AIC
AIC(f[, "FOCUS A"])
AIC(f[, "FOCUS A"], k = 0) # If we do not penalize additional parameters, we get nearly the same
BIC(f[, "FOCUS A"]) # Comparing the BIC gives a very similar picture

# For FOCUS C, the more complex models fit better
AIC(f[, "FOCUS C"])
BIC(f[, "FOCUS C"])

## End(Not run)
```

aw

Calculate Akaike weights for model averaging

Description

Akaike weights are calculated based on the relative expected Kullback-Leibler information as specified by Burnham and Anderson (2004).

Usage

```
aw(object, ...)

## S3 method for class 'mkinfit'
aw(object, ...)
```

```
## S3 method for class 'mmkin'
aw(object, ...)
```

Arguments

object An **mmkin** column object, containing two or more **mkinf** models that have been fitted to the same data, or an **mkinf** object. In the latter case, further **mkinf** objects fitted to the same data should be specified as dots arguments.

... Not used in the method for **mmkin** column objects, further **mkinf** objects in the method for **mkinf** objects.

References

Burnham KP and Anderson DR (2004) Multimodel Inference: Understanding AIC and BIC in Model Selection. *Sociological Methods & Research* **33**(2) 261-304

Examples

```
## Not run:
f_sfo <- mkinfit("SFO", FOCUS_2006_D, quiet = TRUE)
f_dfop <- mkinfit("DFOP", FOCUS_2006_D, quiet = TRUE)
aw_sfo_dfop <- aw(f_sfo, f_dfop)
sum(aw_sfo_dfop)
aw_sfo_dfop # SFO gets more weight as it has less parameters and a similar fit
f <- mmkin(c("SFO", "FOMC", "DFOP"), list("FOCUS D" = FOCUS_2006_D), cores = 1, quiet = TRUE)
aw(f)
sum(aw(f))
aw(f[c("SFO", "DFOP")])

## End(Not run)
```

CAKE_export

Export a list of datasets format to a CAKE study file

Description

In addition to the datasets, the pathways in the degradation model can be specified as well.

Usage

```
CAKE_export(
  ds,
  map = c(parent = "Parent"),
  links = NA,
  filename = "CAKE_export.csf",
  path = ".",
  overwrite = FALSE,
  study = "Codlemone aerobic soil degradation",
```

```

description = "",
time_unit = "days",
res_unit = "% AR",
comment = "Created using mkin::CAKE_export",
date = Sys.Date(),
optimiser = "IRLS"
)

```

Arguments

ds	A named list of datasets in long format as compatible with <code>mkinfit</code> .
map	A character vector with CAKE compartment names (Parent, A1, ...), named with the names used in the list of datasets.
links	An optional character vector of target compartments, named with the names of the source compartments. In order to make this easier, the names are used as in the datasets supplied.
filename	Where to write the result. Should end in <code>.csf</code> in order to be compatible with CAKE.
path	An optional path to the output file.
overwrite	If TRUE, existing files are overwritten.
study	The name of the study.
description	An optional description.
time_unit	The time unit for the residue data.
res_unit	The unit used for the residues.
comment	An optional comment.
date	The date of file creation.
optimiser	Can be OLS or IRLS.

Value

The function is called for its side effect.

Author(s)

Johannes Ranke

Description

The default method 'quadratic' is based on the quadratic approximation of the curvature of the likelihood function at the maximum likelihood parameter estimates. The alternative method 'profile' is based on the profile likelihood for each parameter. The 'profile' method uses two nested optimisations and can take a very long time, even if parallelized by specifying 'cores' on unixoid platforms. The speed of the method could likely be improved by using the method of Venzon and Moolgavkar (1988).

Usage

```
## S3 method for class 'mkinfit'
confint(
  object,
  parm,
  level = 0.95,
  alpha = 1 - level,
  cutoff,
  method = c("quadratic", "profile"),
  transformed = TRUE,
  backtransform = TRUE,
  cores = round(detectCores()/2),
  quiet = FALSE,
  ...
)
```

Arguments

object	An <code>mkinfit</code> object
parm	A vector of names of the parameters which are to be given confidence intervals. If missing, all parameters are considered.
level	The confidence level required
alpha	The allowed error probability, overrides 'level' if specified.
cutoff	Possibility to specify an alternative cutoff for the difference in the log-likelihoods at the confidence boundary. Specifying an explicit cutoff value overrides arguments 'level' and 'alpha'
method	The 'quadratic' method approximates the likelihood function at the optimised parameters using the second term of the Taylor expansion, using a second derivative (hessian) contained in the object. The 'profile' method searches the parameter space for the cutoff of the confidence intervals by means of a likelihood ratio test.

transformed	If the quadratic approximation is used, should it be applied to the likelihood based on the transformed parameters?
backtransform	If we approximate the likelihood in terms of the transformed parameters, should we backtransform the parameters with their confidence intervals?
cores	The number of cores to be used for multicore processing. On Windows machines, cores > 1 is currently not supported.
quiet	Should we suppress the message "Profiling the likelihood"
...	Not used

Value

A matrix with columns giving lower and upper confidence limits for each parameter.

References

Bates DM and Watts GW (1988) Nonlinear regression analysis & its applications

Pawitan Y (2013) In all likelihood - Statistical modelling and inference using likelihood. Clarendon Press, Oxford.

Venzon DJ and Moolgavkar SH (1988) A Method for Computing Profile-Likelihood Based Confidence Intervals, Applied Statistics, 37, 87–94.

Examples

```
f <- mkinfit("SFO", FOCUS_2006_C, quiet = TRUE)
confint(f, method = "quadratic")

## Not run:
confint(f, method = "profile")

# Set the number of cores for the profiling method for further examples
if (identical(Sys.getenv("NOT_CRAN"), "true")) {
  n_cores <- parallel::detectCores() - 1
} else {
  n_cores <- 1
}
if (Sys.getenv("TRAVIS") != "") n_cores = 1
if (Sys.info()["sysname"] == "Windows") n_cores = 1

SFO_SFO <- mkinmod(parent = mkinsub("SFO", "m1"), m1 = mkinsub("SFO"), quiet = TRUE)
SFO_SFO.ff <- mkinmod(parent = mkinsub("SFO", "m1"), m1 = mkinsub("SFO"),
  use_of_ff = "max", quiet = TRUE)
f_d_1 <- mkinfit(SFO_SFO, subset(FOCUS_2006_D, value != 0), quiet = TRUE)
system.time(ci_profile <- confint(f_d_1, method = "profile", cores = 1, quiet = TRUE))
# Using more cores does not save much time here, as parent_0 takes up most of the time
# If we additionally exclude parent_0 (the confidence of which is often of
# minor interest), we get a nice performance improvement from about 50
# seconds to about 12 seconds if we use at least four cores
system.time(ci_profile_no_parent_0 <- confint(f_d_1, method = "profile",
  c("k_parent_sink", "k_parent_m1", "k_m1_sink", "sigma"), cores = n_cores))
ci_profile
```

```

ci_quadratic_transformed <- confint(f_d_1, method = "quadratic")
ci_quadratic_transformed
ci_quadratic_untransformed <- confint(f_d_1, method = "quadratic", transformed = FALSE)
ci_quadratic_untransformed
# Against the expectation based on Bates and Watts (1988), the confidence
# intervals based on the internal parameter transformation are less
# congruent with the likelihood based intervals. Note the superiority of the
# interval based on the untransformed fit for k_m1_sink
rel_diffs_transformed <- abs((ci_quadratic_transformed - ci_profile)/ci_profile)
rel_diffs_untransformed <- abs((ci_quadratic_untransformed - ci_profile)/ci_profile)
rel_diffs_transformed < rel_diffs_untransformed
signif(rel_diffs_transformed, 3)
signif(rel_diffs_untransformed, 3)

# Investigate a case with formation fractions
f_d_2 <- mkinfit(SFO_SFO.ff, subset(FOCUS_2006_D, value != 0), quiet = TRUE)
ci_profile_ff <- confint(f_d_2, method = "profile", cores = n_cores)
ci_profile_ff
ci_quadratic_transformed_ff <- confint(f_d_2, method = "quadratic")
ci_quadratic_transformed_ff
ci_quadratic_untransformed_ff <- confint(f_d_2, method = "quadratic", transformed = FALSE)
ci_quadratic_untransformed_ff
rel_diffs_transformed_ff <- abs((ci_quadratic_transformed_ff - ci_profile_ff)/ci_profile_ff)
rel_diffs_untransformed_ff <- abs((ci_quadratic_untransformed_ff - ci_profile_ff)/ci_profile_ff)
# While the confidence interval for the parent rate constant is closer to
# the profile based interval when using the internal parameter
# transformation, the interval for the metabolite rate constant is 'better
# without internal parameter transformation.
rel_diffs_transformed_ff < rel_diffs_untransformed_ff
rel_diffs_transformed_ff
rel_diffs_untransformed_ff

# The profiling for the following fit does not finish in a reasonable time,
# therefore we use the quadratic approximation
m_synth_DFOP_par <- mkinmod(parent = mkinmod("DFOP", c("M1", "M2")),
  M1 = mkinmod("SFO"),
  M2 = mkinmod("SFO"),
  use_of_ff = "max", quiet = TRUE)
DFOP_par_c <- synthetic_data_for_UBA_2014[[12]]$data
f_tc_2 <- mkinfit(m_synth_DFOP_par, DFOP_par_c, error_model = "tc",
  error_model_algorithm = "direct", quiet = TRUE)
confint(f_tc_2, method = "quadratic")
confint(f_tc_2, "parent_0", method = "quadratic")

## End(Not run)

```

Description

Create degradation functions for known analytical solutions

Usage

```
create_deg_func(spec, use_of_ff = c("min", "max"))
```

Arguments

spec	List of model specifications as contained in mkinmod objects
use_of_ff	Minimum or maximum use of formation fractions

Value

Degradation function to be attached to mkinmod objects

Examples

```
SFO_SFO <- mkinmod(
  parent = mkinsub("SFO", "m1"),
  m1 = mkinsub("SFO"))
FOCUS_D <- subset(FOCUS_2006_D, value != 0) # to avoid warnings
fit_1 <- mkinfit(SFO_SFO, FOCUS_D, solution_type = "analytical", quiet = TRUE)
fit_2 <- mkinfit(SFO_SFO, FOCUS_D, solution_type = "deSolve", quiet = TRUE)
## Not run:
if (require(rbenchmark))
  benchmark(
    analytical = mkinfit(SFO_SFO, FOCUS_D, solution_type = "analytical", quiet = TRUE),
    deSolve = mkinfit(SFO_SFO, FOCUS_D, solution_type = "deSolve", quiet = TRUE),
    replications = 2)
DFOP_SFO <- mkinmod(
  parent = mkinsub("DFOP", "m1"),
  m1 = mkinsub("SFO"))
benchmark(
  analytical = mkinfit(DFOP_SFO, FOCUS_D, solution_type = "analytical", quiet = TRUE),
  deSolve = mkinfit(DFOP_SFO, FOCUS_D, solution_type = "deSolve", quiet = TRUE),
  replications = 2)

## End(Not run)
```

DFOP.solution

Double First-Order in Parallel kinetics

Description

Function describing decline from a defined starting value using the sum of two exponential decline functions.

Usage

```
DFOP.solution(t, parent_0, k1, k2, g)
```

Arguments

t	Time.
parent_0	Starting value for the response variable at time zero.
k1	First kinetic constant.
k2	Second kinetic constant.
g	Fraction of the starting value declining according to the first kinetic constant.

Value

The value of the response variable at time t.

References

FOCUS (2006) “Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics> FOCUS (2014) “Generic guidance for Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, Version 1.1, 18 December 2014 <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

See Also

Other parent solutions: [FOMC.solution\(\)](#), [HS.solution\(\)](#), [IORE.solution\(\)](#), [SF0.solution\(\)](#), [SFORB.solution\(\)](#), [logistic.solution\(\)](#)

Examples

```
plot(function(x) DFOP.solution(x, 100, 5, 0.5, 0.3), 0, 4, ylim = c(0,100))
```

endpoints	<i>Function to calculate endpoints for further use from kinetic models fitted with mkinfit</i>
-----------	--

Description

This function calculates DT50 and DT90 values as well as formation fractions from kinetic models fitted with mkinfit. If the SFORB model was specified for one of the parents or metabolites, the Eigenvalues are returned. These are equivalent to the rate constants of the DFOP model, but with the advantage that the SFORB model can also be used for metabolites.

Usage

```
endpoints(fit)
```

Arguments

`fit` An object of class `mkinf` or `nlme.mmkin`

Value

A list with a matrix of dissipation times named `distimes`, and, if applicable, a vector of formation fractions named `ff` and, if the SFORB model was in use, a vector of eigenvalues of these SFORB models, equivalent to DFOP rate constants

Note

The function is used internally by `summary.mkinf`.

Author(s)

Johannes Ranke

Examples

```
fit <- mkinf("FOMC", FOCUS_2006_C, quiet = TRUE)
endpoints(fit)
## Not run:
fit_2 <- mkinf("SFORB", FOCUS_2006_C, quiet = TRUE)
endpoints(fit_2)

## End(Not run)
```

experimental_data_for_UBA_2019

Experimental datasets used for development and testing of error models

Description

The 12 datasets were extracted from active substance evaluation dossiers published by EFSA. Kinetic evaluations shown for these datasets are intended to illustrate and advance error model specifications. The fact that these data and some results are shown here do not imply a license to use them in the context of pesticide registrations, as the use of the data may be constrained by data protection regulations.

Preprocessing of data was performed based on the recommendations of the FOCUS kinetics work-group (FOCUS, 2014) as described below.

Datasets 1 and 2 are from the Renewal Assessment Report (RAR) for imazamox (France, 2015, p. 15). For setting values reported as zero, an LOQ of 0.1 was assumed. Metabolite residues reported for day zero were added to the parent compound residues.

Datasets 3 and 4 are from the Renewal Assessment Report (RAR) for isofetamid (Belgium, 2014, p. 8) and show the data for two different radiolabels. For dataset 4, the value given for the metabolite in the day zero sampling in replicate B was added to the parent compound, following the respective FOCUS recommendation.

Dataset 5 is from the Renewal Assessment Report (RAR) for ethofumesate (Austria, 2015, p. 16).

Datasets 6 to 10 are from the Renewal Assessment Report (RAR) for glyphosate (Germany, 2013a, pages 8, 28, 50, 51). For the initial sampling, the residues given for the metabolite were added to the parent value, following the recommendation of the FOCUS kinetics workgroup.

Dataset 11 is from the Renewal Assessment Report (RAR) for 2,4-D (Germany, 2013b, p. 644). Values reported as zero were set to NA, with the exception of the day three sampling of metabolite A2, which was set to one half of the LOD reported to be 1% AR.

Dataset 12 is from the Renewal Assessment Report (RAR) for thifensulfuron-methyl (United Kingdom, 2014, p. 81).

Usage

```
experimental_data_for_UBA_2019
```

Format

A list containing twelve datasets as an R6 class defined by `mkind`s, each containing, among others, the following components

`title` The name of the dataset, e.g. Soil 1

`data` A data frame with the data in the form expected by `mkinf`it

Source

Austria (2015). Ethofumesate Renewal Assessment Report Volume 3 Annex B.8 (AS)

Belgium (2014). Isofetamid (IKF-5411) Draft Assessment Report Volume 3 Annex B.8 (AS)

France (2015). Imazamox Draft Renewal Assessment Report Volume 3 Annex B.8 (AS)

FOCUS (2014) “Generic guidance for Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, Version 1.1, 18 December 2014 <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

Germany (2013a). Renewal Assessment Report Glyphosate Volume 3 Annex B.8: Environmental Fate and Behaviour

Germany (2013b). Renewal Assessment Report 2,4-D Volume 3 Annex B.8: Fate and behaviour in the environment

Ranke (2019) Documentation of results obtained for the error model expertise written for the German Umweltbundesamt.

United Kingdom (2014). Thifensulfuron-methyl - Annex B.8 (Volume 3) to the Report and Proposed Decision of the United Kingdom made to the European Commission under Regulation (EC) No. 1141/2010 for renewal of an active substance

Examples

```

## Not run:

# Model definitions
sfo_sfo <- mkinmod(
  parent = mkinsub("SFO", to = "A1"),
  A1 = mkinsub("SFO"),
  use_of_ff = "max"
)

dfop_sfo <- mkinmod(
  parent = mkinsub("DFOP", to = "A1"),
  A1 = mkinsub("SFO"),
  use_of_ff = "max"
)

sfo_sfo_sfo <- mkinmod(
  parent = mkinsub("SFO", to = "A1"),
  A1 = mkinsub("SFO", to = "A2"),
  A2 = mkinsub("SFO"),
  use_of_ff = "max"
)

dfop_sfo_sfo <- mkinmod(
  parent = mkinsub("DFOP", to = "A1"),
  A1 = mkinsub("SFO", to = "A2"),
  A2 = mkinsub("SFO"),
  use_of_ff = "max"
)

d_1_2 <- lapply(experimental_data_for_UBA_2019[1:2], function(x) x$data)
names(d_1_2) <- paste("Soil", 1:2)

f_1_2_tc <- mmkin(list("DFOP-SFO-SFO" = dfop_sfo_sfo), d_1_2, error_model = "tc")

plot(f_1_2_tc, resplot = "errmod")

## End(Not run)

```

FOCUS_2006_datasets *Datasets A to F from the FOCUS Kinetics report from 2006*

Description

Data taken from FOCUS (2006), p. 258.

Usage

FOCUS_2006_A
FOCUS_2006_B
FOCUS_2006_C
FOCUS_2006_D
FOCUS_2006_E
FOCUS_2006_F

Format

6 datasets with observations on the following variables.

name a factor containing the name of the observed variable

time a numeric vector containing time points

value a numeric vector containing concentrations in percent of applied radioactivity

Source

FOCUS (2006) “Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

Examples

FOCUS_2006_C

FOCUS_2006_DFOP_ref_A_to_B

Results of fitting the DFOP model to Datasets A to B of FOCUS (2006)

Description

A table with the fitted parameters and the resulting DT50 and DT90 values generated with different software packages. Taken directly from FOCUS (2006). The results from fitting the data with the Topfit software was removed, as the initial concentration of the parent compound was fixed to a value of 100 in this fit.

Usage

FOCUS_2006_DFOP_ref_A_to_B

Format

A data frame containing the following variables.

package a factor giving the name of the software package
M0 The fitted initial concentration of the parent compound
f The fitted f parameter
k1 The fitted k1 parameter
k2 The fitted k2 parameter
DT50 The resulting half-life of the parent compound
DT90 The resulting DT90 of the parent compound
dataset The FOCUS dataset that was used

Source

FOCUS (2006) “Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

Examples

```
data(FOCUS_2006_DFOP_ref_A_to_B)
```

FOCUS_2006_FOMC_ref_A_to_F

Results of fitting the FOMC model to Datasets A to F of FOCUS (2006)

Description

A table with the fitted parameters and the resulting DT50 and DT90 values generated with different software packages. Taken directly from FOCUS (2006). The results from fitting the data with the Topfit software was removed, as the initial concentration of the parent compound was fixed to a value of 100 in this fit.

Usage

```
FOCUS_2006_FOMC_ref_A_to_F
```

Format

A data frame containing the following variables.

package a factor giving the name of the software package
M0 The fitted initial concentration of the parent compound
alpha The fitted alpha parameter

beta The fitted beta parameter
 DT50 The resulting half-life of the parent compound
 DT90 The resulting DT90 of the parent compound
 dataset The FOCUS dataset that was used

Source

FOCUS (2006) “Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

Examples

```
data(FOCUS_2006_FOMC_ref_A_to_F)
```

```
FOCUS_2006_HS_ref_A_to_F
```

Results of fitting the HS model to Datasets A to F of FOCUS (2006)

Description

A table with the fitted parameters and the resulting DT50 and DT90 values generated with different software packages. Taken directly from FOCUS (2006). The results from fitting the data with the Topfit software was removed, as the initial concentration of the parent compound was fixed to a value of 100 in this fit.

Usage

```
FOCUS_2006_HS_ref_A_to_F
```

Format

A data frame containing the following variables.

package a factor giving the name of the software package
 M0 The fitted initial concentration of the parent compound
 tb The fitted tb parameter
 k1 The fitted k1 parameter
 k2 The fitted k2 parameter
 DT50 The resulting half-life of the parent compound
 DT90 The resulting DT90 of the parent compound
 dataset The FOCUS dataset that was used

Source

FOCUS (2006) “Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

Examples

```
data(FOCUS_2006_HS_ref_A_to_F)
```

```
FOCUS_2006_SFO_ref_A_to_F
```

Results of fitting the SFO model to Datasets A to F of FOCUS (2006)

Description

A table with the fitted parameters and the resulting DT50 and DT90 values generated with different software packages. Taken directly from FOCUS (2006). The results from fitting the data with the Topfit software was removed, as the initial concentration of the parent compound was fixed to a value of 100 in this fit.

Usage

```
FOCUS_2006_SFO_ref_A_to_F
```

Format

A data frame containing the following variables.

package a factor giving the name of the software package

M0 The fitted initial concentration of the parent compound

k The fitted first-order degradation rate constant

DT50 The resulting half-life of the parent compound

DT90 The resulting DT90 of the parent compound

dataset The FOCUS dataset that was used

Source

FOCUS (2006) “Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

Examples

```
data(FOCUS_2006_SFO_ref_A_to_F)
```

FOMC.solution	<i>First-Order Multi-Compartment kinetics</i>
---------------	---

Description

Function describing exponential decline from a defined starting value, with a decreasing rate constant.

Usage

```
FOMC.solution(t, parent_0, alpha, beta)
```

Arguments

t	Time.
parent_0	Starting value for the response variable at time zero.
alpha	Shape parameter determined by coefficient of variation of rate constant values.
beta	Location parameter.

Details

The form given here differs slightly from the original reference by Gustafson and Holden (1990). The parameter beta corresponds to $1/\beta$ in the original equation.

Value

The value of the response variable at time t.

Note

The solution of the FOMC kinetic model reduces to the [SFO.solution](#) for large values of alpha and beta with $k = \frac{\beta}{\alpha}$.

References

FOCUS (2006) “Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

FOCUS (2014) “Generic guidance for Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, Version 1.1, 18 December 2014 <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

Gustafson DI and Holden LR (1990) Nonlinear pesticide dissipation in soil: A new model based on spatial variability. *Environmental Science and Technology* **24**, 1032-1038

See Also

Other parent solutions: [DFOP.solution\(\)](#), [HS.solution\(\)](#), [IORE.solution\(\)](#), [SF0.solution\(\)](#), [SFORB.solution\(\)](#), [logistic.solution\(\)](#)

Examples

```
plot(function(x) FOMC.solution(x, 100, 10, 2), 0, 2, ylim = c(0, 100))
```

get_deg_func	<i>Retrieve a degradation function from the mmkin namespace</i>
--------------	---

Description

Retrieve a degradation function from the mmkin namespace

Usage

```
get_deg_func()
```

Value

A function that was likely previously assigned from within nlme.mmkin

HS.solution	<i>Hockey-Stick kinetics</i>
-------------	------------------------------

Description

Function describing two exponential decline functions with a break point between them.

Usage

```
HS.solution(t, parent_0, k1, k2, tb)
```

Arguments

t	Time.
parent_0	Starting value for the response variable at time zero.
k1	First kinetic constant.
k2	Second kinetic constant.
tb	Break point. Before this time, exponential decline according to k1 is calculated, after this time, exponential decline proceeds according to k2.

Value

The value of the response variable at time t .

References

FOCUS (2006) “Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics> FOCUS (2014) “Generic guidance for Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, Version 1.1, 18 December 2014 <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

See Also

Other parent solutions: [DFOP.solution\(\)](#), [FOMC.solution\(\)](#), [IORE.solution\(\)](#), [SFO.solution\(\)](#), [SFORB.solution\(\)](#), [logistic.solution\(\)](#)

Examples

```
plot(function(x) HS.solution(x, 100, 2, 0.3, 0.5), 0, 2, ylim=c(0,100))
```

ilr

Function to perform isometric log-ratio transformation

Description

This implementation is a special case of the class of isometric log-ratio transformations.

Usage

```
ilr(x)
```

```
invilr(x)
```

Arguments

x A numeric vector. Naturally, the forward transformation is only sensible for vectors with all elements being greater than zero.

Value

The result of the forward or backward transformation. The returned components always sum to 1 for the case of the inverse log-ratio transformation.

Author(s)

René Lehmann and Johannes Ranke

References

Peter Filzmoser, Karel Hron (2008) Outlier Detection for Compositional Data Using Robust Methods. *Math Geosci* 40 233-248

See Also

Another implementation can be found in R package `robCompositions`.

Examples

```
# Order matters
ilr(c(0.1, 1, 10))
ilr(c(10, 1, 0.1))
# Equal entries give ilr transformations with zeros as elements
ilr(c(3, 3, 3))
# Almost equal entries give small numbers
ilr(c(0.3, 0.4, 0.3))
# Only the ratio between the numbers counts, not their sum
invilr(ilr(c(0.7, 0.29, 0.01)))
invilr(ilr(2.1 * c(0.7, 0.29, 0.01)))
# Inverse transformation of larger numbers gives unequal elements
invilr(-10)
invilr(c(-10, 0))
# The sum of the elements of the inverse ilr is 1
sum(invilr(c(-10, 0)))
# This is why we do not need all elements of the inverse transformation to go back:
a <- c(0.1, 0.3, 0.5)
b <- invilr(a)
length(b) # Four elements
ilr(c(b[1:3], 1 - sum(b[1:3]))) # Gives c(0.1, 0.3, 0.5)
```

IORE.solution

Indeterminate order rate equation kinetics

Description

Function describing exponential decline from a defined starting value, with a concentration dependent rate constant.

Usage

```
IORE.solution(t, parent_0, k__iore, N)
```


Arguments

t	Time.
parent_0	Starting value for the response variable at time zero.
k__iore	Rate constant. Note that this depends on the concentration units used.
N	Exponent describing the nonlinearity of the rate equation

Value

The value of the response variable at time t.

Note

The solution of the IORE kinetic model reduces to the [SFO.solution](#) if $N = 1$. The parameters of the IORE model can be transformed to equivalent parameters of the FOMC mode - see the NAFTA guidance for details.

References

NAFTA Technical Working Group on Pesticides (not dated) Guidance for Evaluating and Calculating Degradation Kinetics in Environmental Media

See Also

Other parent solutions: [DFOP.solution\(\)](#), [FOMC.solution\(\)](#), [HS.solution\(\)](#), [SFO.solution\(\)](#), [SFORB.solution\(\)](#), [logistic.solution\(\)](#)

Examples

```
plot(function(x) IORE.solution(x, 100, 0.2, 1.3), 0, 2, ylim = c(0, 100))
## Not run:
  fit.fomc <- mkinfit("FOMC", FOCUS_2006_C, quiet = TRUE)
  fit.iore <- mkinfit("IORE", FOCUS_2006_C, quiet = TRUE)
  fit.iore.deS <- mkinfit("IORE", FOCUS_2006_C, solution_type = "deSolve", quiet = TRUE)

  print(data.frame(fit.fomc$par, fit.iore$par, fit.iore.deS$par,
                  row.names = paste("model par", 1:4)))
  print(rbind(fomc = endpoints(fit.fomc)$distimes, iore = endpoints(fit.iore)$distimes,
              iore.deS = endpoints(fit.iore.deS)$distimes))

## End(Not run)
```

loftest

*Lack-of-fit test for models fitted to data with replicates***Description**

This is a generic function with a method currently only defined for `mkinfit` objects. It fits an anova model to the data contained in the object and compares the likelihoods using the likelihood ratio test `lrtest.default` from the `lmtest` package.

Usage

```
loftest(object, ...)

## S3 method for class 'mkinfit'
loftest(object, ...)
```

Arguments

<code>object</code>	A model object with a defined <code>loftest</code> method
<code>...</code>	Not used

Details

The anova model is interpreted as the simplest form of an `mkinfit` model, assuming only a constant variance about the means, but not enforcing any structure of the means, so we have one model parameter for every mean of replicate samples.

See Also

`lrtest`

Examples

```
## Not run:
test_data <- subset(synthetic_data_for_UBA_2014[[12]]$data, name == "parent")
sfo_fit <- mkinfit("SFO", test_data, quiet = TRUE)
plot_res(sfo_fit) # We see a clear pattern in the residuals
loftest(sfo_fit) # We have a clear lack of fit
#
# We try a different model (the one that was used to generate the data)
dfop_fit <- mkinfit("DFOP", test_data, quiet = TRUE)
plot_res(dfop_fit) # We don't see systematic deviations, but heteroscedastic residuals
# therefore we should consider adapting the error model, although we have
loftest(dfop_fit) # no lack of fit
#
# This is the anova model used internally for the comparison
test_data_anova <- test_data
test_data_anova$time <- as.factor(test_data_anova$time)
```

```

anova_fit <- lm(value ~ time, data = test_data_anova)
summary(anova_fit)
logLik(anova_fit) # We get the same likelihood and degrees of freedom
#
test_data_2 <- synthetic_data_for_UBA_2014[[12]]$data
m_synth_SFO_lin <- mkinmod(parent = list(type = "SFO", to = "M1"),
  M1 = list(type = "SFO", to = "M2"),
  M2 = list(type = "SFO"), use_of_ff = "max")
sfo_lin_fit <- mkinfit(m_synth_SFO_lin, test_data_2, quiet = TRUE)
plot_res(sfo_lin_fit) # not a good model, we try parallel formation
loftest(sfo_lin_fit)
#
m_synth_SFO_par <- mkinmod(parent = list(type = "SFO", to = c("M1", "M2")),
  M1 = list(type = "SFO"),
  M2 = list(type = "SFO"), use_of_ff = "max")
sfo_par_fit <- mkinfit(m_synth_SFO_par, test_data_2, quiet = TRUE)
plot_res(sfo_par_fit) # much better for metabolites
loftest(sfo_par_fit)
#
m_synth_DFOP_par <- mkinmod(parent = list(type = "DFOP", to = c("M1", "M2")),
  M1 = list(type = "SFO"),
  M2 = list(type = "SFO"), use_of_ff = "max")
dfop_par_fit <- mkinfit(m_synth_DFOP_par, test_data_2, quiet = TRUE)
plot_res(dfop_par_fit) # No visual lack of fit
loftest(dfop_par_fit) # no lack of fit found by the test
#
# The anova model used for comparison in the case of transformation products
test_data_anova_2 <- dfop_par_fit$data
test_data_anova_2$variable <- as.factor(test_data_anova_2$variable)
test_data_anova_2$time <- as.factor(test_data_anova_2$time)
anova_fit_2 <- lm(observed ~ time:variable - 1, data = test_data_anova_2)
summary(anova_fit_2)

## End(Not run)

```

logistic.solution *Logistic kinetics*

Description

Function describing exponential decline from a defined starting value, with an increasing rate constant, supposedly caused by microbial growth

Usage

```
logistic.solution(t, parent_0, kmax, k0, r)
```

Arguments

t	Time.
parent_0	Starting value for the response variable at time zero.
kmax	Maximum rate constant.
k0	Minimum rate constant effective at time zero.
r	Growth rate of the increase in the rate constant.

Value

The value of the response variable at time t.

Note

The solution of the logistic model reduces to the [SF0.solution](#) if k0 is equal to kmax.

References

FOCUS (2006) "Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration" Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics> FOCUS (2014) "Generic guidance for Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration" Report of the FOCUS Work Group on Degradation Kinetics, Version 1.1, 18 December 2014 <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

See Also

Other parent solutions: [DFOP.solution\(\)](#), [FOMC.solution\(\)](#), [HS.solution\(\)](#), [IORE.solution\(\)](#), [SF0.solution\(\)](#), [SFORB.solution\(\)](#)

Examples

```
# Reproduce the plot on page 57 of FOCUS (2014)
plot(function(x) logistic.solution(x, 100, 0.08, 0.0001, 0.2),
      from = 0, to = 100, ylim = c(0, 100),
      xlab = "Time", ylab = "Residue")
plot(function(x) logistic.solution(x, 100, 0.08, 0.0001, 0.4),
      from = 0, to = 100, add = TRUE, lty = 2, col = 2)
plot(function(x) logistic.solution(x, 100, 0.08, 0.0001, 0.8),
      from = 0, to = 100, add = TRUE, lty = 3, col = 3)
plot(function(x) logistic.solution(x, 100, 0.08, 0.001, 0.2),
      from = 0, to = 100, add = TRUE, lty = 4, col = 4)
plot(function(x) logistic.solution(x, 100, 0.08, 0.08, 0.2),
      from = 0, to = 100, add = TRUE, lty = 5, col = 5)
legend("topright", inset = 0.05,
      legend = paste0("k0 = ", c(0.0001, 0.0001, 0.0001, 0.001, 0.08),
                     ", r = ", c(0.2, 0.4, 0.8, 0.2, 0.2)),
      lty = 1:5, col = 1:5)
```

```

# Fit with synthetic data
logistic <- mkinmod(parent = mkinsub("logistic"))

sampling_times = c(0, 1, 3, 7, 14, 28, 60, 90, 120)
parms_logistic <- c(kmax = 0.08, k0 = 0.0001, r = 0.2)
d_logistic <- mkinpredict(logistic,
  parms_logistic, c(parent = 100),
  sampling_times)
d_2_1 <- add_err(d_logistic,
  sdfunc = function(x) sigma_twocomp(x, 0.5, 0.07),
  n = 1, reps = 2, digits = 5, LOD = 0.1, seed = 123456)[[1]]

m <- mkinfit("logistic", d_2_1, quiet = TRUE)
plot_sep(m)
summary(m)$bpar
endpoints(m)$distimes

```

logLik.mkinfit

Calculated the log-likelihood of a fitted mkinfit object

Description

This function returns the product of the likelihood densities of each observed value, as calculated as part of the fitting procedure using [dnorm](#), i.e. assuming normal distribution, and with the means predicted by the degradation model, and the standard deviations predicted by the error model.

Usage

```

## S3 method for class 'mkinfit'
logLik(object, ...)

```

Arguments

object	An object of class mkinfit .
...	For compatibility with the generic method

Details

The total number of estimated parameters returned with the value of the likelihood is calculated as the sum of fitted degradation model parameters and the fitted error model parameters.

Value

An object of class [logLik](#) with the number of estimated parameters (degradation model parameters plus variance model parameters) as attribute.

Author(s)

Johannes Ranke

See AlsoCompare the AIC of columns of `mmkin` objects using `AIC.mmkin`.**Examples**

```
## Not run:
sfo_sfo <- mkinmod(
  parent = mkinsub("SFO", to = "m1"),
  m1 = mkinsub("SFO")
)
d_t <- FOCUS_2006_D
f_nw <- mkinfit(sfo_sfo, d_t, quiet = TRUE) # no weighting (weights are unity)
f_obs <- mkinfit(sfo_sfo, d_t, error_model = "obs", quiet = TRUE)
f_tc <- mkinfit(sfo_sfo, d_t, error_model = "tc", quiet = TRUE)
AIC(f_nw, f_obs, f_tc)

## End(Not run)
```

 lrtest.mkinfit

Likelihood ratio test for mkinfit models

Description

Compare two `mkinfit` models based on their likelihood. If two fitted `mkinfit` objects are given as arguments, it is checked if they have been fitted to the same data. It is the responsibility of the user to make sure that the models are nested, i.e. one of them has less degrees of freedom and can be expressed by fixing the parameters of the other.

Usage

```
## S3 method for class 'mkinfit'
lrtest(object, object_2 = NULL, ...)

## S3 method for class 'mmkin'
lrtest(object, ...)
```

Arguments

<code>object</code>	An <code>mkinfit</code> object, or an <code>mmkin</code> column object containing two fits to the same data.
<code>object_2</code>	Optionally, another <code>mkinfit</code> object fitted to the same data.
<code>...</code>	Argument to <code>mkinfit</code> , passed to <code>update.mkinfit</code> for creating the alternative fitted object.

Details

Alternatively, an argument to `mkinfit` can be given which is then passed to `update.mkinfit` to obtain the alternative model.

The comparison is then made by the `lrtest.default` method from the `lmtest` package. The model with the higher number of fitted parameters (alternative hypothesis) is listed first, then the model with the lower number of fitted parameters (null hypothesis).

Examples

```
## Not run:
test_data <- subset(synthetic_data_for_UBA_2014[[12]]$data, name == "parent")
sfo_fit <- mkinfit("SFO", test_data, quiet = TRUE)
dfop_fit <- mkinfit("DFOP", test_data, quiet = TRUE)
lrtest(dfop_fit, sfo_fit)
lrtest(sfo_fit, dfop_fit)

# The following two examples are commented out as they fail during
# generation of the static help pages by pkgdown
#lrtest(dfop_fit, error_model = "tc")
#lrtest(dfop_fit, fixed_parms = c(k2 = 0))

# However, this equivalent syntax also works for static help pages
lrtest(dfop_fit, update(dfop_fit, error_model = "tc"))
lrtest(dfop_fit, update(dfop_fit, fixed_parms = c(k2 = 0)))

## End(Not run)
```

max_twa_parent	<i>Function to calculate maximum time weighted average concentrations from kinetic models fitted with mkinfit</i>
----------------	---

Description

This function calculates maximum moving window time weighted average concentrations (TWAs) for kinetic models fitted with `mkinfit`. Currently, only calculations for the parent are implemented for the SFO, FOMC, DFOP and HS models, using the analytical formulas given in the PEC soil section of the FOCUS guidance.

Usage

```
max_twa_parent(fit, windows)

max_twa_sfo(M0 = 1, k, t)

max_twa_fomc(M0 = 1, alpha, beta, t)

max_twa_dfop(M0 = 1, k1, k2, g, t)

max_twa_hs(M0 = 1, k1, k2, tb, t)
```

Arguments

fit	An object of class <code>mkinfitt</code> .
windows	The width of the time windows for which the TWAs should be calculated.
M0	The initial concentration for which the maximum time weighted average over the decline curve should be calculated. The default is to use a value of 1, which means that a relative maximum time weighted average factor (<code>f_twa</code>) is calculated.
k	The rate constant in the case of SFO kinetics.
t	The width of the time window.
alpha	Parameter of the FOMC model.
beta	Parameter of the FOMC model.
k1	The first rate constant of the DFOP or the HS kinetics.
k2	The second rate constant of the DFOP or the HS kinetics.
g	Parameter of the DFOP model.
tb	Parameter of the HS model.

Value

For `max_twa_parent`, a numeric vector, named using the `windows` argument. For the other functions, a numeric vector of length one (also known as 'a number').

Author(s)

Johannes Ranke

References

FOCUS (2006) "Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration" Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

Examples

```
fit <- mkinfit("FOMC", FOCUS_2006_C, quiet = TRUE)
max_twa_parent(fit, c(7, 21))
```


mccall81_245T

*Datasets on aerobic soil metabolism of 2,4,5-T in six soils***Description**

Time course of 2,4,5-trichlorophenoxyacetic acid, and the corresponding 2,4,5-trichlorophenol and 2,4,5-trichloroanisole as recovered in diethylether extracts.

Usage

```
mccall81_245T
```

Format

A dataframe containing the following variables.

`name` the name of the compound observed. Note that T245 is used as an acronym for 2,4,5-T. T245 is a legitimate object name in R, which is necessary for specifying models using `mkmod`.

`time` a numeric vector containing sampling times in days after treatment

`value` a numeric vector containing concentrations in percent of applied radioactivity

`soil` a factor containing the name of the soil

Source

McCall P, Vrona SA, Kelley SS (1981) Fate of uniformly carbon-14 ring labelled 2,4,5-Trichlorophenoxyacetic acid and 2,4-dichlorophenoxyacetic acid. *J Agric Chem* 29, 100-107 <http://dx.doi.org/10.1021/jf00103a026>

Examples

```
SFO_SFO_SFO <- mkmod(T245 = list(type = "SFO", to = "phenol"),
                    phenol = list(type = "SFO", to = "anisole"),
                    anisole = list(type = "SFO"))

## Not run:
fit.1 <- mkmodfit(SFO_SFO_SFO, subset(mccall81_245T, soil == "Commerce"), quiet = TRUE)
summary(fit.1)$bpar
endpoints(fit.1)
# k_phenol_sink is really small, therefore fix it to zero
fit.2 <- mkmodfit(SFO_SFO_SFO, subset(mccall81_245T, soil == "Commerce"),
                parms.ini = c(k_phenol_sink = 0),
                fixed_parms = "k_phenol_sink", quiet = TRUE)
summary(fit.2)$bpar
endpoints(fit.1)
plot_sep(fit.2)

## End(Not run)
```

mkind

A dataset class for mkin

Description

At the moment this dataset class is hardly used in mkin. For example, mkinfit does not take mkind datasets as argument, but works with dataframes such as the one contained in the data field of mkind objects. Some datasets provided by this package come as mkind objects nevertheless.

Public fields

title A full title for the dataset

sampling_times The sampling times

time_unit The time unit

observed Names of the observed variables

unit The unit of the observations

replicates The maximum number of replicates per sampling time

data A data frame with at least the columns name, time and value in order to be compatible with mkinfit

Methods

Public methods:

- `mkind$new()`
- `mkind$clone()`

Method `new()`: Create a new mkind object

Usage:

```
mkind$new(title = "", data, time_unit = NA, unit = NA)
```

Arguments:

title The dataset title

data The data

time_unit The time unit

unit The unit of the observations

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
mkind$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

The S3 printing method [print.mkinds](#)

Examples

```
mks <- mkinds$new("FOCUS A", FOCUS_2006_A)
print(mks)
```

mkinerrmin	<i>Calculate the minimum error to assume in order to pass the variance test</i>
------------	---

Description

This function finds the smallest relative error still resulting in passing the chi-squared test as defined in the FOCUS kinetics report from 2006.

Usage

```
mkinerrmin(fit, alpha = 0.05)
```

Arguments

fit	an object of class mkinfit .
alpha	The confidence level chosen for the chi-squared test.

Details

This function is used internally by [summary.mkinfit](#).

Value

A dataframe with the following components:

err.min	The relative error, expressed as a fraction.
n.optim	The number of optimised parameters attributed to the data series.
df	The number of remaining degrees of freedom for the chi2 error level calculations. Note that mean values are used for the chi2 statistic and therefore every time point with observed values in the series only counts one time.

The dataframe has one row for the total dataset and one further row for each observed state variable in the model.

References

FOCUS (2006) "Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration" Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

Examples

```
SFO_SFO = mkinmod(parent = mkinsub("SFO", to = "m1"),
                 m1 = mkinsub("SFO"),
                 use_of_ff = "max")

fit_FOCUS_D = mkinfit(SFO_SFO, FOCUS_2006_D, quiet = TRUE)
round(mkinerrmin(fit_FOCUS_D), 4)
## Not run:
fit_FOCUS_E = mkinfit(SFO_SFO, FOCUS_2006_E, quiet = TRUE)
round(mkinerrmin(fit_FOCUS_E), 4)

## End(Not run)
```

mkinerrplot

Function to plot squared residuals and the error model for an mkin object

Description

This function plots the squared residuals for the specified subset of the observed variables from an mkinfit object. In addition, one or more dashed line(s) show the fitted error model. A combined plot of the fitted model and this error model plot can be obtained with `plot.mkinfit` using the argument `show_errplot = TRUE`.

Usage

```
mkinerrplot(
  object,
  obs_vars = names(object$mkinmod$map),
  xlim = c(0, 1.1 * max(object$data$predicted)),
  xlab = "Predicted",
  ylab = "Squared residual",
  maxy = "auto",
  legend = TRUE,
  lpos = "topright",
  col_obs = "auto",
  pch_obs = "auto",
  frame = TRUE,
  ...
)
```

Arguments

object	A fit represented in an <code>mkinfit</code> object.
obs_vars	A character vector of names of the observed variables for which residuals should be plotted. Defaults to all observed variables in the model
xlim	plot range in x direction.
xlab	Label for the x axis.
ylab	Label for the y axis.
maxy	Maximum value of the residuals. This is used for the scaling of the y axis and defaults to "auto".
legend	Should a legend be plotted?
lpos	Where should the legend be placed? Default is "topright". Will be passed on to legend .
col_obs	Colors for the observed variables.
pch_obs	Symbols to be used for the observed variables.
frame	Should a frame be drawn around the plots?
...	further arguments passed to plot .

Value

Nothing is returned by this function, as it is called for its side effect, namely to produce a plot.

Author(s)

Johannes Ranke

See Also

[mkinplot](#), for a way to plot the data and the fitted lines of the `mkinfit` object.

Examples

```
## Not run:
model <- mkinmod(parent = mkinsub("SF0", "m1"), m1 = mkinsub("SF0"))
fit <- mkinfit(model, FOCUS_2006_D, error_model = "tc", quiet = TRUE)
mkinerrplot(fit)

## End(Not run)
```

mkinfit

Fit a kinetic model to data with one or more state variables

Description

This function maximises the likelihood of the observed data using the Port algorithm `nlmminb`, and the specified initial or fixed parameters and starting values. In each step of the optimisation, the kinetic model is solved using the function `mkinpredict`. The parameters of the selected error model are fitted simultaneously with the degradation model parameters, as both of them are arguments of the likelihood function.

Usage

```
mkinfit(
  mkinmod,
  observed,
  parms.ini = "auto",
  state.ini = "auto",
  err.ini = "auto",
  fixed_parms = NULL,
  fixed_initials = names(mkinmod$diffs)[-1],
  from_max_mean = FALSE,
  solution_type = c("auto", "analytical", "eigen", "deSolve"),
  method.ode = "lsoda",
  use_compiled = "auto",
  control = list(eval.max = 300, iter.max = 200),
  transform_rates = TRUE,
  transform_fractions = TRUE,
  quiet = FALSE,
  atol = 1e-08,
  rtol = 1e-10,
  error_model = c("const", "obs", "tc"),
  error_model_algorithm = c("auto", "d_3", "direct", "twostep", "threestep",
    "fourstep", "IRLS", "OLS"),
  reweight.tol = 1e-08,
  reweight.max.iter = 10,
  trace_parms = FALSE,
  ...
)
```

Arguments

`mkinmod` A list of class `mkinmod`, containing the kinetic model to be fitted to the data, or one of the shorthand names ("SFO", "FOMC", "DFOP", "HS", "SFORB", "IORE"). If a shorthand name is given, a parent only degradation model is generated for the variable with the highest value in observed.

observed	A dataframe with the observed data. The first column called "name" must contain the name of the observed variable for each data point. The second column must contain the times of observation, named "time". The third column must be named "value" and contain the observed values. Zero values in the "value" column will be removed, with a warning, in order to avoid problems with fitting the two-component error model. This is not expected to be a problem, because in general, values of zero are not observed in degradation data, because there is a lower limit of detection.
parms.ini	<p>A named vector of initial values for the parameters, including parameters to be optimised and potentially also fixed parameters as indicated by <code>fixed_parms</code>. If set to "auto", initial values for rate constants are set to default values. Using parameter names that are not in the model gives an error.</p> <p>It is possible to only specify a subset of the parameters that the model needs. You can use the parameter lists "bparms.ode" from a previously fitted model, which contains the differential equation parameters from this model. This works nicely if the models are nested. An example is given below.</p>
state.ini	A named vector of initial values for the state variables of the model. In case the observed variables are represented by more than one model variable, the names will differ from the names of the observed variables (see map component of <code>mkinmod</code>). The default is to set the initial value of the first model variable to the mean of the time zero values for the variable with the maximum observed value, and all others to 0. If this variable has no time zero observations, its initial value is set to 100.
err.ini	A named vector of initial values for the error model parameters to be optimised. If set to "auto", initial values are set to default values. Otherwise, initial values for all error model parameters must be given.
fixed_parms	The names of parameters that should not be optimised but rather kept at the values specified in <code>parms.ini</code> . Alternatively, a named numeric vector of parameters to be fixed, regardless of the values in <code>parms.ini</code> .
fixed_initials	The names of model variables for which the initial state at time 0 should be excluded from the optimisation. Defaults to all state variables except for the first one.
from_max_mean	If this is set to TRUE, and the model has only one observed variable, then data before the time of the maximum observed value (after averaging for each sampling time) are discarded, and this time is subtracted from all remaining time values, so the time of the maximum observed mean value is the new time zero.
solution_type	If set to "eigen", the solution of the system of differential equations is based on the spectral decomposition of the coefficient matrix in cases that this is possible. If set to "deSolve", a numerical ode solver from package <code>deSolve</code> is used. If set to "analytical", an analytical solution of the model is used. This is only implemented for simple degradation experiments with only one state variable, i.e. with no metabolites. The default is "auto", which uses "analytical" if possible, otherwise "deSolve" if a compiler is present, and "eigen" if no compiler is present and the model can be expressed using eigenvalues and eigenvectors. This argument is passed on to the helper function <code>mkinpredict</code> .
method.ode	The solution method passed via <code>mkinpredict</code> to <code>ode</code> in case the solution type is "deSolve". The default "lsoda" is performant, but sometimes fails to converge.

use_compiled	If set to FALSE, no compiled version of the <code>mkinmod</code> model is used in the calls to <code>mkinpredict</code> even if a compiled version is present.
control	A list of control arguments passed to <code>nlminb</code> .
transform_rates	Boolean specifying if kinetic rate constants should be transformed in the model specification used in the fitting for better compliance with the assumption of normal distribution of the estimator. If TRUE, also alpha and beta parameters of the FOMC model are log-transformed, as well as k1 and k2 rate constants for the DFOP and HS models and the break point tb of the HS model. If FALSE, zero is used as a lower bound for the rates in the optimisation.
transform_fractions	Boolean specifying if formation fractions constants should be transformed in the model specification used in the fitting for better compliance with the assumption of normal distribution of the estimator. The default (TRUE) is to do transformations. If TRUE, the g parameter of the DFOP and HS models are also transformed, as they can also be seen as compositional data. The transformation used for these transformations is the <code>ilr</code> transformation.
quiet	Suppress printing out the current value of the negative log-likelihood after each improvement?
atol	Absolute error tolerance, passed to <code>ode</code> . Default is 1e-8, lower than in <code>lsoda</code> .
rtol	Absolute error tolerance, passed to <code>ode</code> . Default is 1e-10, much lower than in <code>lsoda</code> .
error_model	If the error model is "const", a constant standard deviation is assumed. If the error model is "obs", each observed variable is assumed to have its own variance. If the error model is "tc" (two-component error model), a two component error model similar to the one described by Rocke and Lorenzato (1995) is used for setting up the likelihood function. Note that this model deviates from the model by Rocke and Lorenzato, as their model implies that the errors follow a lognormal distribution for large values, not a normal distribution as assumed by this method.
error_model_algorithm	If "auto", the selected algorithm depends on the error model. If the error model is "const", unweighted nonlinear least squares fitting ("OLS") is selected. If the error model is "obs", or "tc", the "d_3" algorithm is selected. The algorithm "d_3" will directly minimize the negative log-likelihood and <ul style="list-style-type: none"> independently - also use the three step algorithm described below. The fit with the higher likelihood is returned. The algorithm "direct" will directly minimize the negative log-likelihood. The algorithm "twostep" will minimize the negative log-likelihood after an initial unweighted least squares optimisation step. The algorithm "threestep" starts with unweighted least squares, then optimizes only the error model using the degradation model parameters found, and then minimizes the negative log-likelihood with free degradation and error model parameters.

The algorithm "fourstep" starts with unweighted least squares, then optimizes only the error model using the degradation model parameters found, then optimizes the degradation model again with fixed error model parameters, and finally minimizes the negative log-likelihood with free degradation and error model parameters.

The algorithm "IRLS" (Iteratively Reweighted Least Squares) starts with unweighted least squares, and then iterates optimization of the error model parameters and subsequent optimization of the degradation model using those error model parameters, until the error model parameters converge.

<code>reweight.tol</code>	Tolerance for the convergence criterion calculated from the error model parameters in IRLS fits.
<code>reweight.max.iter</code>	Maximum number of iterations in IRLS fits.
<code>trace_parms</code>	Should a trace of the parameter values be listed?
<code>...</code>	Further arguments that will be passed on to <code>deSolve</code> .

Details

Per default, parameters in the kinetic models are internally transformed in order to better satisfy the assumption of a normal distribution of their estimators.

Value

A list with "mkinfit" in the class attribute. A summary can be obtained by `summary.mkinfit`.

Note

When using the "IORE" submodel for metabolites, fitting with "transform_rates = TRUE" (the default) often leads to failures of the numerical ODE solver. In this situation it may help to switch off the internal rate transformation.

Author(s)

Johannes Ranke

References

- Rocke DM and Lorenzato S (1995) A two-component model for measurement error in analytical chemistry. *Technometrics* 37(2), 176-184.
- Ranke J and Meinecke S (2019) Error Models for the Kinetic Evaluation of Chemical Degradation Data. *Environments* 6(12) 124 [doi:10.3390/environments6120124](https://doi.org/10.3390/environments6120124).

See Also

Plotting methods `plot.mkinfit` and `mkinparplot`.

Comparisons of models fitted to the same data can be made using `AIC` by virtue of the method `logLik.mkinfit`.

Fitting of several models to several datasets in a single call to `mmkin`.

Examples

```

# Use shorthand notation for parent only degradation
fit <- mkinfit("FOMC", FOCUS_2006_C, quiet = TRUE)
summary(fit)

# One parent compound, one metabolite, both single first order.
# Use mkinmod for convenience in model formulation. Pathway to sink included per default.
SFO_SFO <- mkinmod(
  parent = mkinmod("SFO", "m1"),
  m1 = mkinmod("SFO"))
# Fit the model to the FOCUS example dataset D using defaults
print(system.time(fit <- mkinfit(SFO_SFO, FOCUS_2006_D,
  solution_type = "eigen", quiet = TRUE)))

parms(fit)
endpoints(fit)
## Not run:
# deSolve is slower when no C compiler (gcc) was available during model generation
print(system.time(fit.deSolve <- mkinfit(SFO_SFO, FOCUS_2006_D,
  solution_type = "deSolve")))

parms(fit.deSolve)
endpoints(fit.deSolve)

## End(Not run)

# Use stepwise fitting, using optimised parameters from parent only fit, FOMC
## Not run:
FOMC_SFO <- mkinmod(
  parent = mkinmod("FOMC", "m1"),
  m1 = mkinmod("SFO"))
# Fit the model to the FOCUS example dataset D using defaults
fit.FOMC_SFO <- mkinfit(FOMC_SFO, FOCUS_2006_D, quiet = TRUE)
# Use starting parameters from parent only FOMC fit
fit.FOMC = mkinfit("FOMC", FOCUS_2006_D, quiet = TRUE)
fit.FOMC_SFO <- mkinfit(FOMC_SFO, FOCUS_2006_D, quiet = TRUE,
  parms.ini = fit.FOMC$bparms.ode)

# Use stepwise fitting, using optimised parameters from parent only fit, SFORB
SFORB_SFO <- mkinmod(
  parent = list(type = "SFORB", to = "m1", sink = TRUE),
  m1 = list(type = "SFO"))
# Fit the model to the FOCUS example dataset D using defaults
fit.SFORB_SFO <- mkinfit(SFORB_SFO, FOCUS_2006_D, quiet = TRUE)
fit.SFORB_SFO.deSolve <- mkinfit(SFORB_SFO, FOCUS_2006_D, solution_type = "deSolve",
  quiet = TRUE)
# Use starting parameters from parent only SFORB fit (not really needed in this case)
fit.SFORB = mkinfit("SFORB", FOCUS_2006_D, quiet = TRUE)
fit.SFORB_SFO <- mkinfit(SFORB_SFO, FOCUS_2006_D, parms.ini = fit.SFORB$bparms.ode, quiet = TRUE)

## End(Not run)

## Not run:

```

```
# Weighted fits, including IRLS (error_model = "obs")
SFO_SFO.ff <- mkinmod(parent = mkinsub("SFO", "m1"),
                    m1 = mkinsub("SFO"), use_of_ff = "max")
f.noweight <- mkinfit(SFO_SFO.ff, FOCUS_2006_D, quiet = TRUE)
summary(f.noweight)
f.obs <- mkinfit(SFO_SFO.ff, FOCUS_2006_D, error_model = "obs", quiet = TRUE)
summary(f.obs)
f.tc <- mkinfit(SFO_SFO.ff, FOCUS_2006_D, error_model = "tc", quiet = TRUE)
summary(f.tc)

## End(Not run)
```

mkinmod

Function to set up a kinetic model with one or more state variables

Description

The function usually takes several expressions, each assigning a compound name to a list, specifying the kinetic model type and reaction or transfer to other observed compartments. Instead of specifying several expressions, a list of lists can be given in the `speclist` argument.

Usage

```
mkinmod(
  ...,
  use_of_ff = "max",
  speclist = NULL,
  quiet = FALSE,
  verbose = FALSE
)
```

Arguments

... For each observed variable, a list has to be specified as an argument, containing at least a component type, specifying the type of kinetics to use for the variable. Currently, single first order kinetics "SFO", indeterminate order rate equation kinetics "IORE", or single first order with reversible binding "SFORB" are implemented for all variables, while "FOMC", "DFOP" and "HS" can additionally be chosen for the first variable which is assumed to be the source compartment. Additionally, each component of the list can include a character vector `to`, specifying names of variables to which a transfer is to be assumed in the model. If the argument `use_of_ff` is set to "min" (default) and the model for the compartment is "SFO" or "SFORB", an additional component of the list can be "sink=FALSE" effectively fixing the flux to sink to zero.

use_of_ff	Specification of the use of formation fractions in the model equations and, if applicable, the coefficient matrix. If "min", a minimum use of formation fractions is made in order to avoid fitting the product of formation fractions and rate constants. If "max", formation fractions are always used.
speclist	The specification of the observed variables and their submodel types and pathways can be given as a single list using this argument. Default is NULL.
quiet	Should messages be suppressed?
verbose	If TRUE, passed to <code>cfunction</code> if applicable to give detailed information about the C function being built.

Details

For the definition of model types and their parameters, the equations given in the FOCUS and NAFTA guidance documents are used.

Value

A list of class `mkinmod` for use with `mkinfit`, containing, among others,

diffs	A vector of string representations of differential equations, one for each modelling variable.
map	A list containing named character vectors for each observed variable, specifying the modelling variables by which it is represented.
use_of_ff	The content of <code>use_of_ff</code> is passed on in this list component.
deg_func	If generated, a function containing the solution of the degradation model.
coefmat	The coefficient matrix, if the system of differential equations can be represented by one.
cf	If generated, a compiled function calculating the derivatives as returned by <code>cfunction</code> .

Note

The IORE submodel is not well tested for metabolites. When using this model for metabolites, you may want to read the second note in the help page to `mkinfit`.

Author(s)

Johannes Ranke

References

FOCUS (2006) "Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration" Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

NAFTA Technical Working Group on Pesticides (not dated) Guidance for Evaluating and Calculating Degradation Kinetics in Environmental Media

Examples

```
# Specify the SFO model (this is not needed any more, as we can now mkinfit("SFO", ...)
SFO <- mkinmod(parent = mkinsub("SFO"))

# One parent compound, one metabolite, both single first order
SFO_SFO <- mkinmod(
  parent = mkinsub("SFO", "m1"),
  m1 = mkinsub("SFO"))

## Not run:
# The above model used to be specified like this, before the advent of mkinsub()
SFO_SFO <- mkinmod(
  parent = list(type = "SFO", to = "m1"),
  m1 = list(type = "SFO"))

# Show details of creating the C function
SFO_SFO <- mkinmod(
  parent = mkinsub("SFO", "m1"),
  m1 = mkinsub("SFO"), verbose = TRUE)

# If we have several parallel metabolites
# (compare tests/testthat/test_synthetic_data_for_UBA_2014.R)
m_synth_DFOP_par <- mkinmod(parent = mkinsub("DFOP", c("M1", "M2")),
  M1 = mkinsub("SFO"),
  M2 = mkinsub("SFO"),
  use_of_ff = "max", quiet = TRUE)

fit_DFOP_par_c <- mkinfit(m_synth_DFOP_par,
  synthetic_data_for_UBA_2014[[12]]$data,
  quiet = TRUE)

## End(Not run)
```

mkinparplot

Function to plot the confidence intervals obtained using mkinfit

Description

This function plots the confidence intervals for the parameters fitted using [mkinfit](#).

Usage

```
mkinparplot(object)
```

Arguments

object A fit represented in an [mkinfit](#) object.

Value

Nothing is returned by this function, as it is called for its side effect, namely to produce a plot.

Author(s)

Johannes Ranke

Examples

```
## Not run:
model <- mkinmod(
  T245 = mkinsub("SFO", to = c("phenol"), sink = FALSE),
  phenol = mkinsub("SFO", to = c("anisole")),
  anisole = mkinsub("SFO", use_of_ff = "max")
fit <- mkinfit(model, subset(mccall81_245T, soil == "Commerce"), quiet = TRUE)
mkinparplot(fit)

## End(Not run)
```

mkinplot

Plot the observed data and the fitted model of an mkinfit object

Description

Deprecated function. It now only calls the plot method [plot.mkinfit](#).

Usage

```
mkinplot(fit, ...)
```

Arguments

<code>fit</code>	an object of class mkinfit .
<code>...</code>	further arguments passed to plot.mkinfit .

Value

The function is called for its side effect.

Author(s)

Johannes Ranke

`mkinpredict`*Produce predictions from a kinetic model using specific parameters*

Description

This function produces a time series for all the observed variables in a kinetic model as specified by `mkinmod`, using a specific set of kinetic parameters and initial values for the state variables.

Usage

```
mkinpredict(  
  x,  
  odeparms,  
  odeini,  
  outtimes = seq(0, 120, by = 0.1),  
  solution_type = "deSolve",  
  use_compiled = "auto",  
  method.ode = "lsoda",  
  atol = 1e-08,  
  rtol = 1e-10,  
  map_output = TRUE,  
  ...  
)  
  
## S3 method for class 'mkinmod'  
mkinpredict(  
  x,  
  odeparms = c(k_parent_sink = 0.1),  
  odeini = c(parent = 100),  
  outtimes = seq(0, 120, by = 0.1),  
  solution_type = "deSolve",  
  use_compiled = "auto",  
  method.ode = "lsoda",  
  atol = 1e-08,  
  rtol = 1e-10,  
  map_output = TRUE,  
  ...  
)  
  
## S3 method for class 'mkinfit'  
mkinpredict(  
  x,  
  odeparms = x$bparms.ode,  
  odeini = x$bparms.state,  
  outtimes = seq(0, 120, by = 0.1),  
  solution_type = "deSolve",  
  use_compiled = "auto",
```

```

    method.ode = "lsoda",
    atol = 1e-08,
    rtol = 1e-10,
    map_output = TRUE,
    ...
)

```

Arguments

x	A kinetic model as produced by mkinmod , or a kinetic fit as fitted by mkinfit . In the latter case, the fitted parameters are used for the prediction.
odeparms	A numeric vector specifying the parameters used in the kinetic model, which is generally defined as a set of ordinary differential equations.
odeini	A numeric vector containing the initial values of the state variables of the model. Note that the state variables can differ from the observed variables, for example in the case of the SFORB model.
outtimes	A numeric vector specifying the time points for which model predictions should be generated.
solution_type	The method that should be used for producing the predictions. This should generally be "analytical" if there is only one observed variable, and usually "deSolve" in the case of several observed variables. The third possibility "eigen" is faster but not applicable to some models e.g. using FOMC for the parent compound.
use_compiled	If set to FALSE, no compiled version of the mkinmod model is used, even if is present.
method.ode	The solution method passed via mkinpredict to ode in case the solution type is "deSolve". The default "lsoda" is performant, but sometimes fails to converge.
atol	Absolute error tolerance, passed to ode . Default is 1e-8, lower than in lsoda .
rtol	Absolute error tolerance, passed to ode . Default is 1e-10, much lower than in lsoda .
map_output	Boolean to specify if the output should list values for the observed variables (default) or for all state variables (if set to FALSE). Setting this to FALSE has no effect for analytical solutions, as these always return mapped output.
...	Further arguments passed to the ode solver in case such a solver is used.

Value

A matrix with the numeric solution in wide format

Author(s)

Johannes Ranke

Examples

```

SFO <- mkinmod(degradinol = mkinsub("SFO"))
# Compare solution types
mkinpredict(SFO, c(k_degradinol = 0.3), c(degradinol = 100), 0:20,
  solution_type = "analytical")
mkinpredict(SFO, c(k_degradinol = 0.3), c(degradinol = 100), 0:20,
  solution_type = "deSolve")
mkinpredict(SFO, c(k_degradinol = 0.3), c(degradinol = 100), 0:20,
  solution_type = "deSolve", use_compiled = FALSE)
mkinpredict(SFO, c(k_degradinol = 0.3), c(degradinol = 100), 0:20,
  solution_type = "eigen")

# Compare integration methods to analytical solution
mkinpredict(SFO, c(k_degradinol = 0.3), c(degradinol = 100), 0:20,
  solution_type = "analytical")[21,]
mkinpredict(SFO, c(k_degradinol = 0.3), c(degradinol = 100), 0:20,
  method = "lsoda")[21,]
mkinpredict(SFO, c(k_degradinol = 0.3), c(degradinol = 100), 0:20,
  method = "ode45")[21,]
mkinpredict(SFO, c(k_degradinol = 0.3), c(degradinol = 100), 0:20,
  method = "rk4")[21,]
# rk4 is not as precise here

# The number of output times used to make a lot of difference until the
# default for atol was adjusted
mkinpredict(SFO, c(k_degradinol = 0.3), c(degradinol = 100),
  seq(0, 20, by = 0.1))[201,]
mkinpredict(SFO, c(k_degradinol = 0.3), c(degradinol = 100),
  seq(0, 20, by = 0.01))[2001,]

# Comparison of the performance of solution types
SFO_SFO = mkinmod(parent = list(type = "SFO", to = "m1"),
  m1 = list(type = "SFO"), use_of_ff = "max")
if(require(rbenchmark)) {
  benchmark(replications = 10, order = "relative", columns = c("test", "relative", "elapsed"),
    eigen = mkinpredict(SFO_SFO,
      c(k_parent = 0.15, f_parent_to_m1 = 0.5, k_m1 = 0.01),
      c(parent = 100, m1 = 0), seq(0, 20, by = 0.1),
      solution_type = "eigen")[201,],
    deSolve_compiled = mkinpredict(SFO_SFO,
      c(k_parent = 0.15, f_parent_to_m1 = 0.5, k_m1 = 0.01),
      c(parent = 100, m1 = 0), seq(0, 20, by = 0.1),
      solution_type = "deSolve")[201,],
    deSolve = mkinpredict(SFO_SFO,
      c(k_parent = 0.15, f_parent_to_m1 = 0.5, k_m1 = 0.01),
      c(parent = 100, m1 = 0), seq(0, 20, by = 0.1),
      solution_type = "deSolve", use_compiled = FALSE)[201,],
    analytical = mkinpredict(SFO_SFO,
      c(k_parent = 0.15, f_parent_to_m1 = 0.5, k_m1 = 0.01),
      c(parent = 100, m1 = 0), seq(0, 20, by = 0.1),
      solution_type = "analytical", use_compiled = FALSE)[201,])
}

```

```

}

## Not run:
# Predict from a fitted model
f <- mkinfit(SFO_SF0, FOCUS_2006_C, quiet = TRUE)
f <- mkinfit(SFO_SF0, FOCUS_2006_C, quiet = TRUE, solution_type = "deSolve")
head(mkinpredict(f))

## End(Not run)

```

mkinresplot

Function to plot residuals stored in an mkin object

Description

This function plots the residuals for the specified subset of the observed variables from an `mkinfit` object. A combined plot of the fitted model and the residuals can be obtained using `plot.mkinfit` using the argument `show_residuals = TRUE`.

Usage

```

mkinresplot(
  object,
  obs_vars = names(object$mkinmod$map),
  xlim = c(0, 1.1 * max(object$data$time)),
  standardized = FALSE,
  xlab = "Time",
  ylab = ifelse(standardized, "Standardized residual", "Residual"),
  maxabs = "auto",
  legend = TRUE,
  lpos = "topright",
  col_obs = "auto",
  pch_obs = "auto",
  frame = TRUE,
  ...
)

```

Arguments

<code>object</code>	A fit represented in an <code>mkinfit</code> object.
<code>obs_vars</code>	A character vector of names of the observed variables for which residuals should be plotted. Defaults to all observed variables in the model
<code>xlim</code>	plot range in x direction.
<code>standardized</code>	Should the residuals be standardized by dividing by the standard deviation given by the error model of the fit?
<code>xlab</code>	Label for the x axis.

ylab	Label for the y axis.
maxabs	Maximum absolute value of the residuals. This is used for the scaling of the y axis and defaults to "auto".
legend	Should a legend be plotted?
lpos	Where should the legend be placed? Default is "topright". Will be passed on to legend .
col_obs	Colors for the observed variables.
pch_obs	Symbols to be used for the observed variables.
frame	Should a frame be drawn around the plots?
...	further arguments passed to plot .

Value

Nothing is returned by this function, as it is called for its side effect, namely to produce a plot.

Author(s)

Johannes Ranke

See Also

[mkinplot](#), for a way to plot the data and the fitted lines of the mkinfit object, and [plot_res](#) for a function combining the plot of the fit and the residual plot.

Examples

```
model <- mkinmod(parent = mkinsub("SF0", "m1"), m1 = mkinsub("SF0"))
fit <- mkinfit(model, FOCUS_2006_D, quiet = TRUE)
mkinresplot(fit, "m1")
```

mkinsub

Function to set up a kinetic submodel for one state variable

Description

This is a convenience function to set up the lists used as arguments for [mkinmod](#).

Usage

```
mkinsub(submodel, to = NULL, sink = TRUE, full_name = NA)
```

Arguments

submodel	Character vector of length one to specify the submodel type. See <code>mkinmod</code> for the list of allowed submodel names.
to	Vector of the names of the state variable to which a transformation shall be included in the model.
sink	Should a pathway to sink be included in the model in addition to the pathways to other state variables?
full_name	An optional name to be used e.g. for plotting fits performed with the model. You can use non-ASCII characters here, but then your R code will not be portable, <i>i.e.</i> may produce unintended plot results on other operating systems or system configurations.

Value

A list for use with `mkinmod`.

Author(s)

Johannes Ranke

Examples

```
# One parent compound, one metabolite, both single first order.
SFO_SF0 <- mkinmod(
  parent = list(type = "SF0", to = "m1"),
  m1 = list(type = "SF0"))

# The same model using mkinsub
SFO_SF0.2 <- mkinmod(
  parent = mkinsub("SF0", "m1"),
  m1 = mkinsub("SF0"))

## Not run:
# Now supplying full names
SFO_SF0.2 <- mkinmod(
  parent = mkinsub("SF0", "m1", full_name = "Test compound"),
  m1 = mkinsub("SF0", full_name = "Metabolite M1"))

## End(Not run)
```

mkin_long_to_wide

Convert a dataframe from long to wide format

Description

This function takes a dataframe in the long form, *i.e.* with a row for each observed value, and converts it into a dataframe with one independent variable and several dependent variables as columns.

Usage

```
mkin_long_to_wide(long_data, time = "time", outtime = "time")
```

Arguments

long_data	The dataframe must contain one variable called "time" with the time values specified by the time argument, one column called "name" with the grouping of the observed values, and finally one column of observed values called "value".
time	The name of the time variable in the long input data.
outtime	The name of the time variable in the wide output data.

Value

Dataframe in wide format.

Author(s)

Johannes Ranke

Examples

```
mkin_long_to_wide(FOCUS_2006_D)
```

mkin_wide_to_long	<i>Convert a dataframe with observations over time into long format</i>
-------------------	---

Description

This function simply takes a dataframe with one independent variable and several dependent variable and converts it into the long form as required by [mkinfit](#).

Usage

```
mkin_wide_to_long(wide_data, time = "t")
```

Arguments

wide_data	The dataframe must contain one variable with the time values specified by the time argument and usually more than one column of observed values.
time	The name of the time variable.

Value

Dataframe in long format as needed for [mkinfit](#).

Author(s)

Johannes Ranke

Examples

```
wide <- data.frame(t = c(1,2,3), x = c(1,4,7), y = c(3,4,5))
mkin_wide_to_long(wide)
```

mmkin	<i>Fit one or more kinetic models with one or more state variables to one or more datasets</i>
-------	--

Description

This function calls `mkinfit` on all combinations of models and datasets specified in its first two arguments.

Usage

```
mmkin(
  models = c("SFO", "FOMC", "DFOP"),
  datasets,
  cores = round(detectCores()/2),
  cluster = NULL,
  ...
)
```

Arguments

models	Either a character vector of shorthand names like <code>c("SFO", "FOMC", "DFOP", "HS", "SFORB")</code> , or an optionally named list of <code>mkinmod</code> objects.
datasets	An optionally named list of datasets suitable as observed data for <code>mkinfit</code> .
cores	The number of cores to be used for multicore processing. This is only used when the <code>cluster</code> argument is <code>NULL</code> . On Windows machines, <code>cores > 1</code> is not supported, you need to use the <code>cluster</code> argument to use multiple logical processors.
cluster	A cluster as returned by <code>makeCluster</code> to be used for parallel execution.
...	Further arguments that will be passed to <code>mkinfit</code> .

Value

A two-dimensional `array` of `mkinfit` objects that can be indexed using the model names for the first index (row index) and the dataset names for the second index (column index).

Author(s)

Johannes Ranke

See Also[\[.mmkin\]](#) for subsetting, [plot.mmkin](#) for plotting.**Examples**

```
## Not run:
m_synth_SF0_lin <- mkinmod(parent = mkinsub("SF0", "M1"),
                          M1 = mkinsub("SF0", "M2"),
                          M2 = mkinsub("SF0"), use_of_ff = "max")

m_synth_FOMC_lin <- mkinmod(parent = mkinsub("FOMC", "M1"),
                           M1 = mkinsub("SF0", "M2"),
                           M2 = mkinsub("SF0"), use_of_ff = "max")

models <- list(SF0_lin = m_synth_SF0_lin, FOMC_lin = m_synth_FOMC_lin)
datasets <- lapply(synthetic_data_for_UBA_2014[1:3], function(x) x$data)
names(datasets) <- paste("Dataset", 1:3)

time_default <- system.time(fits.0 <- mmkin(models, datasets, quiet = TRUE))
time_1 <- system.time(fits.4 <- mmkin(models, datasets, cores = 1, quiet = TRUE))

time_default
time_1

endpoints(fits.0[["SF0_lin", 2]])

# plot.mkinfit handles rows or columns of mmkin result objects
plot(fits.0[1, ])
plot(fits.0[1, ], obs_var = c("M1", "M2"))
plot(fits.0[, 1])
# Use double brackets to extract a single mkinfit object, which will be plotted
# by plot.mkinfit and can be plotted using plot_sep
plot(fits.0[[1, 1]], sep_obs = TRUE, show_residuals = TRUE, show_errmin = TRUE)
plot_sep(fits.0[[1, 1]])
# Plotting with mmkin (single brackets, extracting an mmkin object) does not
# allow to plot the observed variables separately
plot(fits.0[1, 1])

## End(Not run)
```

Description

The function fits the SFO, IORE and DFOP models using `mmkin` and returns an object of class `nafta` that has methods for printing and plotting.

Print `nafta` objects. The results for the three models are printed in the order of increasing model complexity, i.e. SFO, then IORE, and finally DFOP.

Usage

```
nafta(ds, title = NA, quiet = FALSE, ...)
```

```
## S3 method for class 'nafta'  
print(x, quiet = TRUE, digits = 3, ...)
```

Arguments

<code>ds</code>	A dataframe that must contain one variable called "time" with the time values specified by the <code>time</code> argument, one column called "name" with the grouping of the observed values, and finally one column of observed values called "value".
<code>title</code>	Optional title of the dataset
<code>quiet</code>	Should the evaluation text be shown?
<code>...</code>	Further arguments passed to <code>mmkin</code> (not for the printing method).
<code>x</code>	An <code>nafta</code> object.
<code>digits</code>	Number of digits to be used for printing parameters and dissipation times.

Value

An list of class `nafta`. The list element named "mmkin" is the `mmkin` object containing the fits of the three models. The list element named "title" contains the title of the dataset used. The list element "data" contains the dataset used in the fits.

Author(s)

Johannes Ranke

Source

NAFTA (2011) Guidance for evaluating and calculating degradation kinetics in environmental media. NAFTA Technical Working Group on Pesticides <https://www.epa.gov/pesticide-science-and-assessing-pesticide-guidance-evaluating-and-calculating-degradation> accessed 2019-02-22

US EPA (2015) Standard Operating Procedure for Using the NAFTA Guidance to Calculate Representative Half-life Values and Characterizing Pesticide Degradation <https://www.epa.gov/pesticide-science-and-assessing-pesticide-guidance-standard-operating-procedure-using-nafta-guidance>

Examples

```
nafta_evaluation <- nafta(NAFTA_SOP_Appendix_D, cores = 1)
print(nafta_evaluation)
plot(nafta_evaluation)
```

NAFTA_SOP_2015

Example datasets from the NAFTA SOP published 2015

Description

Data taken from US EPA (2015), p. 19 and 23.

Usage

```
NAFTA_SOP_Appendix_B
NAFTA_SOP_Appendix_D
```

Format

2 datasets with observations on the following variables.

`name` a factor containing the name of the observed variable

`time` a numeric vector containing time points

`value` a numeric vector containing concentrations

Source

NAFTA (2011) Guidance for evaluating and calculating degradation kinetics in environmental media. NAFTA Technical Working Group on Pesticides <https://www.epa.gov/pesticide-science-and-assessing-pesticide-guidance-evaluating-and-calculating-degradation> accessed 2019-02-22

US EPA (2015) Standard Operating Procedure for Using the NAFTA Guidance to Calculate Representative Half-life Values and Characterizing Pesticide Degradation <https://www.epa.gov/pesticide-science-and-assessing-pesticide-guidance-standard-operating-procedure-using-nafta-guidance>

Examples

```
nafta_evaluation <- nafta(NAFTA_SOP_Appendix_D, cores = 1)
print(nafta_evaluation)
plot(nafta_evaluation)
```

NAFTA_SOP_Attachment *Example datasets from Attachment 1 to the NAFTA SOP published 2015*

Description

Data taken from from Attachment 1 of the SOP.

Usage

```
NAFTA_SOP_Attachment
```

Format

A list (NAFTA_SOP_Attachment) containing 16 datasets suitable for the evaluation with [nafta](#)

Source

NAFTA (2011) Guidance for evaluating and calculating degradation kinetics in environmental media. NAFTA Technical Working Group on Pesticides <https://www.epa.gov/pesticide-science-and-assessing-pesticide-guidance-evaluating-and-calculating-degradation> accessed 2019-02-22

US EPA (2015) Standard Operating Procedure for Using the NAFTA Guidance to Calculate Representative Half-life Values and Characterizing Pesticide Degradation <https://www.epa.gov/pesticide-science-and-assessing-pesticide-guidance-standard-operating-procedure-using-nafta-guidance>

Examples

```
nafta_att_p5a <- nafta(NAFTA_SOP_Attachment[["p5a"]], cores = 1)
print(nafta_att_p5a)
plot(nafta_att_p5a)
```

nlme.mmkin

Create an nlme model for an mmkin row object

Description

This functions sets up a nonlinear mixed effects model for an mmkin row object. An mmkin row object is essentially a list of mkinfit objects that have been obtained by fitting the same model to a list of datasets.

Usage

```
## S3 method for class 'mmkin'
nlme(
  model,
  data = sys.frame(sys.parent()),
  fixed,
  random = fixed,
  groups,
  start,
  correlation = NULL,
  weights = NULL,
  subset,
  method = c("ML", "REML"),
  na.action = na.fail,
  naPattern,
  control = list(),
  verbose = FALSE
)

## S3 method for class 'nlme.mmkin'
print(x, ...)

## S3 method for class 'nlme.mmkin'
update(object, ...)
```

Arguments

model	An <code>mmkin</code> row object.
data	Should the data be printed?
fixed	Ignored, all degradation parameters fitted in the <code>mmkin</code> model are used as fixed parameters
random	If not specified, all fixed effects are complemented with uncorrelated random effects
groups	See the documentation of <code>nlme</code>
start	If not specified, mean values of the fitted degradation parameters taken from the <code>mmkin</code> object are used
correlation	See the documentation of <code>nlme</code>
weights	passed to <code>nlme</code>
subset	passed to <code>nlme</code>
method	passed to <code>nlme</code>
na.action	passed to <code>nlme</code>
naPattern	passed to <code>nlme</code>
control	passed to <code>nlme</code>
verbose	passed to <code>nlme</code>

x	An nlme.mmkin object to print
...	Update specifications passed to update.nlme
object	An nlme.mmkin object to update

Value

Upon success, a fitted nlme.mmkin object, which is an nlme object with additional elements

See Also

[nlme_function](#)

Examples

```

ds <- lapply(experimental_data_for_UBA_2019[6:10],
  function(x) subset(x$data[c("name", "time", "value")], name == "parent"))
f <- mmkin("SFO", ds, quiet = TRUE, cores = 1)
library(nlme)
endpoints(f[[1]])
f_nlme <- nlme(f)
print(f_nlme)
endpoints(f_nlme)
## Not run:
f_nlme_2 <- nlme(f, start = c(parent_0 = 100, log_k_parent_sink = 0.1))
update(f_nlme_2, random = parent_0 ~ 1)
# Test on some real data
ds_2 <- lapply(experimental_data_for_UBA_2019[6:10],
  function(x) x$data[c("name", "time", "value")])
m_sfo_sfo <- mkinmod(parent = mkinsub("SFO", "A1"),
  A1 = mkinsub("SFO"), use_of_ff = "min", quiet = TRUE)
m_sfo_sfo_ff <- mkinmod(parent = mkinsub("SFO", "A1"),
  A1 = mkinsub("SFO"), use_of_ff = "max", quiet = TRUE)
m_fomc_sfo <- mkinmod(parent = mkinsub("FOMC", "A1"),
  A1 = mkinsub("SFO"), quiet = TRUE)
m_dfop_sfo <- mkinmod(parent = mkinsub("DFOP", "A1"),
  A1 = mkinsub("SFO"), quiet = TRUE)

f_2 <- mmkin(list("SFO-SFO" = m_sfo_sfo,
  "SFO-SFO-ff" = m_sfo_sfo_ff,
  "FOMC-SFO" = m_fomc_sfo,
  "DFOP-SFO" = m_dfop_sfo),
  ds_2, quiet = TRUE)
plot(f_2["SFO-SFO", 3:4]) # Separate fits for datasets 3 and 4

f_nlme_sfo_sfo <- nlme(f_2["SFO-SFO", ])
# plot(f_nlme_sfo_sfo) # not feasible with pkgdown figures
plot(f_nlme_sfo_sfo, 3:4) # Global mixed model: Fits for datasets 3 and 4

# With formation fractions
f_nlme_sfo_sfo_ff <- nlme(f_2["SFO-SFO-ff", ])
plot(f_nlme_sfo_sfo_ff, 3:4) # chi2 different due to different df attribution

```

```

# For more parameters, we need to increase pnlsMaxIter and the tolerance
# to get convergence
f_nlme_fomc_sfo <- nlme(f_2["FOMC-SFO", ],
  control = list(pnlsMaxIter = 100, tolerance = 1e-4), verbose = TRUE)
f_nlme_dfop_sfo <- nlme(f_2["DFOP-SFO", ],
  control = list(pnlsMaxIter = 120, tolerance = 5e-4), verbose = TRUE)
plot(f_2["FOMC-SFO", 3:4])
plot(f_nlme_fomc_sfo, 3:4)

plot(f_2["DFOP-SFO", 3:4])
plot(f_nlme_dfop_sfo, 3:4)

anova(f_nlme_dfop_sfo, f_nlme_fomc_sfo, f_nlme_sfo_sfo)
anova(f_nlme_dfop_sfo, f_nlme_sfo_sfo) # if we ignore FOMC

endpoints(f_nlme_sfo_sfo)
endpoints(f_nlme_dfop_sfo)

## End(Not run)

```

nlme_function

Helper functions to create nlme models from mmkin row objects

Description

These functions facilitate setting up a nonlinear mixed effects model for an mmkin row object. An mmkin row object is essentially a list of mkinfit objects that have been obtained by fitting the same model to a list of datasets.

Usage

```

nlme_function(object)

mean_degparms(object, random = FALSE)

nlme_data(object)

```

Arguments

object	An mmkin row object containing several fits of the same model to different datasets
random	Should a list with fixed and random effects be returned?

Value

A function that can be used with nlme

If random is FALSE (default), a named vector containing mean values of the fitted degradation model parameters. If random is TRUE, a list with fixed and random effects, in the format required by the start argument of nlme for the case of a single grouping variable ds?

A [groupedData](#) object

See Also[nlme.mmkin](#)**Examples**

```

sampling_times = c(0, 1, 3, 7, 14, 28, 60, 90, 120)
m_SFO <- mkinmod(parent = mkinsub("SFO"))
d_SFO_1 <- mkinpredict(m_SFO,
  c(k_parent = 0.1),
  c(parent = 98), sampling_times)
d_SFO_1_long <- mkin_wide_to_long(d_SFO_1, time = "time")
d_SFO_2 <- mkinpredict(m_SFO,
  c(k_parent = 0.05),
  c(parent = 102), sampling_times)
d_SFO_2_long <- mkin_wide_to_long(d_SFO_2, time = "time")
d_SFO_3 <- mkinpredict(m_SFO,
  c(k_parent = 0.02),
  c(parent = 103), sampling_times)
d_SFO_3_long <- mkin_wide_to_long(d_SFO_3, time = "time")

d1 <- add_err(d_SFO_1, function(value) 3, n = 1)
d2 <- add_err(d_SFO_2, function(value) 2, n = 1)
d3 <- add_err(d_SFO_3, function(value) 4, n = 1)
ds <- c(d1 = d1, d2 = d2, d3 = d3)

f <- mmkin("SFO", ds, cores = 1, quiet = TRUE)
mean_dp <- mean_degparms(f)
grouped_data <- nlme_data(f)
nlme_f <- nlme_function(f)
# These assignments are necessary for these objects to be
# visible to nlme and augPred when evaluation is done by
# pkgdown to generated the html docs.
assign("nlme_f", nlme_f, globalenv())
assign("grouped_data", grouped_data, globalenv())

library(nlme)
m_nlme <- nlme(value ~ nlme_f(name, time, parent_0, log_k_parent_sink),
  data = grouped_data,
  fixed = parent_0 + log_k_parent_sink ~ 1,
  random = pdDiag(parent_0 + log_k_parent_sink ~ 1),
  start = mean_dp)
summary(m_nlme)
plot(augPred(m_nlme, level = 0:1), layout = c(3, 1))
# augPred does not seem to work on fits with more than one state
# variable

```

Description

Number of observations on which an mkinfit object was fitted

Usage

```
## S3 method for class 'mkinfit'
nobs(object, ...)
```

Arguments

object An mkinfit object
... For compatibility with the generic method

Value

The number of rows in the data included in the mkinfit object

parms	<i>Extract model parameters from mkinfit models</i>
-------	---

Description

This function always returns degradation model parameters as well as error model parameters, in order to avoid working with a fitted model without considering the error structure that was assumed for the fit.

Usage

```
parms(object, ...)

## S3 method for class 'mkinfit'
parms(object, transformed = FALSE, ...)
```

Arguments

object A fitted model object
... Not used
transformed Should the parameters be returned as used internally during the optimisation?

Value

A numeric vector of fitted model parameters

Examples

```
fit <- mkinfit("SFO", FOCUS_2006_C)
parms(fit)
parms(fit, transformed = TRUE)
```

plot.mkinfit

Plot the observed data and the fitted model of an mkinfit object

Description

Solves the differential equations with the optimised and fixed parameters from a previous successful call to `mkinfit` and plots the observed data together with the solution of the fitted model.

Usage

```
## S3 method for class 'mkinfit'
plot(
  x,
  fit = x,
  obs_vars = names(fit$mkinmod$map),
  xlab = "Time",
  ylab = "Observed",
  xlim = range(fit$data$time),
  ylim = "default",
  col_obs = 1:length(obs_vars),
  pch_obs = col_obs,
  lty_obs = rep(1, length(obs_vars)),
  add = FALSE,
  legend = !add,
  show_residuals = FALSE,
  show_errplot = FALSE,
  maxabs = "auto",
  sep_obs = FALSE,
  rel.height.middle = 0.9,
  row_layout = FALSE,
  lpos = "topright",
  inset = c(0.05, 0.05),
  show_errmin = FALSE,
  errmin_digits = 3,
  frame = TRUE,
  ...
)

plot_sep(
  fit,
  show_errmin = TRUE,
  show_residuals = ifelse(identical(fit$err_mod, "const"), TRUE, "standardized"),
  ...
)

plot_res(
  fit,
```



```

    sep_obs = FALSE,
    show_errmin = sep_obs,
    standardized = ifelse(identical(fit$err_mod, "const"), FALSE, TRUE),
    ...
)

plot_err(fit, sep_obs = FALSE, show_errmin = sep_obs, ...)

```

Arguments

<code>x</code>	Alias for <code>fit</code> introduced for compatibility with the generic S3 method.
<code>fit</code>	An object of class <code>mkinfit</code> .
<code>obs_vars</code>	A character vector of names of the observed variables for which the data and the model should be plotted. Defaults to all observed variables in the model.
<code>xlab</code>	Label for the x axis.
<code>ylab</code>	Label for the y axis.
<code>xlim</code>	Plot range in x direction.
<code>ylim</code>	Plot range in y direction.
<code>col_obs</code>	Colors used for plotting the observed data and the corresponding model prediction lines.
<code>pch_obs</code>	Symbols to be used for plotting the data.
<code>lty_obs</code>	Line types to be used for the model predictions.
<code>add</code>	Should the plot be added to an existing plot?
<code>legend</code>	Should a legend be added to the plot?
<code>show_residuals</code>	Should residuals be shown? If only one plot of the fits is shown, the residual plot is in the lower third of the plot. Otherwise, i.e. if " <code>sep_obs</code> " is given, the residual plots will be located to the right of the plots of the fitted curves. If this is set to ' <code>standardized</code> ', a plot of the residuals divided by the standard deviation given by the fitted error model will be shown.
<code>show_errplot</code>	Should squared residuals and the error model be shown? If only one plot of the fits is shown, this plot is in the lower third of the plot. Otherwise, i.e. if " <code>sep_obs</code> " is given, the residual plots will be located to the right of the plots of the fitted curves.
<code>maxabs</code>	Maximum absolute value of the residuals. This is used for the scaling of the y axis and defaults to " <code>auto</code> ".
<code>sep_obs</code>	Should the observed variables be shown in separate subplots? If yes, residual plots requested by " <code>show_residuals</code> " will be shown next to, not below the plot of the fits.
<code>rel.height.middle</code>	The relative height of the middle plot, if more than two rows of plots are shown.
<code>row_layout</code>	Should we use a row layout where the residual plot or the error model plot is shown to the right?
<code>lpos</code>	Position(s) of the legend(s). Passed to <code>legend</code> as the first argument. If not length one, this should be of the same length as the <code>obs_var</code> argument.

inset	Passed to legend if applicable.
show_errmin	Should the FOCUS chi2 error value be shown in the upper margin of the plot?
errmin_digits	The number of significant digits for rounding the FOCUS chi2 error percentage.
frame	Should a frame be drawn around the plots?
...	Further arguments passed to plot .
standardized	When calling 'plot_res', should the residuals be standardized in the residual plot?

Details

If the current plot device is a [tikz](#) device, then latex is being used for the formatting of the chi2 error level, if show_errmin = TRUE.

Value

The function is called for its side effect.

Author(s)

Johannes Ranke

Examples

```
# One parent compound, one metabolite, both single first order, path from
# parent to sink included
## Not run:
SFO_SFO <- mkinmod(parent = mkinsub("SFO", "m1", full = "Parent"),
                  m1 = mkinsub("SFO", full = "Metabolite M1" ))
fit <- mkinfit(SFO_SFO, FOCUS_2006_D, quiet = TRUE)
fit <- mkinfit(SFO_SFO, FOCUS_2006_D, quiet = TRUE, error_model = "tc")
plot(fit)
plot_res(fit)
plot_res(fit, standardized = FALSE)
plot_err(fit)

# Show the observed variables separately, with residuals
plot(fit, sep_obs = TRUE, show_residuals = TRUE, lpos = c("topright", "bottomright"),
     show_errmin = TRUE)

# The same can be obtained with less typing, using the convenience function plot_sep
plot_sep(fit, lpos = c("topright", "bottomright"))

# Show the observed variables separately, with the error model
plot(fit, sep_obs = TRUE, show_errplot = TRUE, lpos = c("topright", "bottomright"),
     show_errmin = TRUE)

## End(Not run)
```

plot.mmkin	<i>Plot model fits (observed and fitted) and the residuals for a row or column of an mmkin object</i>
------------	---

Description

When `x` is a row selected from an `mmkin` object (`[.mmkin]`), the same model fitted for at least one dataset is shown. When it is a column, the fit of at least one model to the same dataset is shown.

Usage

```
## S3 method for class 'mmkin'
plot(
  x,
  main = "auto",
  legends = 1,
  resplot = c("time", "errmod"),
  standardized = FALSE,
  show_errmin = TRUE,
  errmin_var = "All data",
  errmin_digits = 3,
  cex = 0.7,
  rel.height.middle = 0.9,
  ymax = "auto",
  ...
)
```

Arguments

<code>x</code>	An object of class <code>mmkin</code> , with either one row or one column.
<code>main</code>	The main title placed on the outer margin of the plot.
<code>legends</code>	An index for the fits for which legends should be shown.
<code>resplot</code>	Should the residuals plotted against time, using <code>mkkinresplot</code> , or as squared residuals against predicted values, with the error model, using <code>mkkinerrplot</code> .
<code>standardized</code>	Should the residuals be standardized? This option is passed to <code>mkkinresplot</code> , it only takes effect if <code>resplot = "time"</code> .
<code>show_errmin</code>	Should the chi2 error level be shown on top of the plots to the left?
<code>errmin_var</code>	The variable for which the FOCUS chi2 error value should be shown.
<code>errmin_digits</code>	The number of significant digits for rounding the FOCUS chi2 error percentage.
<code>cex</code>	Passed to the plot functions and <code>mtext</code> .
<code>rel.height.middle</code>	The relative height of the middle plot, if more than two rows of plots are shown.
<code>ymax</code>	Maximum y axis value for <code>plot.mkkinfit</code> .
<code>...</code>	Further arguments passed to <code>plot.mkkinfit</code> and <code>mkkinresplot</code> .

Details

If the current plot device is a `tikz` device, then latex is being used for the formatting of the χ^2 error level.

Value

The function is called for its side effect.

Author(s)

Johannes Ranke

Examples

```
## Not run:
# Only use one core not to offend CRAN checks
fits <- mmkin(c("FOMC", "HS"),
             list("FOCUS B" = FOCUS_2006_B, "FOCUS C" = FOCUS_2006_C), # named list for titles
             cores = 1, quiet = TRUE, error_model = "tc")
plot(fits[, "FOCUS C"])
plot(fits["FOMC", ])
plot(fits["FOMC", ], show_errmin = FALSE)

# We can also plot a single fit, if we like the way plot.mmkin works, but then the plot
# height should be smaller than the plot width (this is not possible for the html pages
# generated by pkgdown, as far as I know).
plot(fits["FOMC", "FOCUS C"]) # same as plot(fits[1, 2])

# Show the error models
plot(fits["FOMC", ], resplot = "errmod")

## End(Not run)
```

plot.nafta

Plot the results of the three models used in the NAFTA scheme.

Description

The plots are ordered with increasing complexity of the model in this function (SFO, then IORE, then DFOP).

Usage

```
## S3 method for class 'nafta'
plot(x, legend = FALSE, main = "auto", ...)
```

Arguments

x	An object of class <code>nafta</code> .
legend	Should a legend be added?
main	Possibility to override the main title of the plot.
...	Further arguments passed to <code>plot.mmkin</code> .

Details

Calls `plot.mmkin`.

Value

The function is called for its side effect.

Author(s)

Johannes Ranke

plot.nlme.mmkin	<i>Plot a fitted nonlinear mixed model obtained via an mmkin row object</i>
-----------------	---

Description

Plot a fitted nonlinear mixed model obtained via an mmkin row object

Usage

```
## S3 method for class 'nlme.mmkin'
plot(
  x,
  i = 1:ncol(x$mmkin_orig),
  main = "auto",
  legends = 1,
  resplot = c("time", "errmod"),
  standardized = FALSE,
  show_errmin = TRUE,
  errmin_var = "All data",
  errmin_digits = 3,
  cex = 0.7,
  rel.height.middle = 0.9,
  ymax = "auto",
  ...
)
```

Arguments

x	An object of class <code>nlme.mmkin</code>
i	A numeric index to select datasets for which to plot the nlme fit, in case plots get too large
main	The main title placed on the outer margin of the plot.
legends	An index for the fits for which legends should be shown.
resplot	Should the residuals plotted against time, using <code>mkinresplot</code> , or as squared residuals against predicted values, with the error model, using <code>mkinerrplot</code> .
standardized	Should the residuals be standardized? This option is passed to <code>mkinresplot</code> , it only takes effect if <code>resplot = "time"</code> .
show_errmin	Should the chi2 error level be shown on top of the plots to the left?
errmin_var	The variable for which the FOCUS chi2 error value should be shown.
errmin_digits	The number of significant digits for rounding the FOCUS chi2 error percentage.
cex	Passed to the plot functions and <code>mtext</code> .
rel.height.middle	The relative height of the middle plot, if more than two rows of plots are shown.
ymax	Maximum y axis value for <code>plot.mkinfit</code> .
...	Further arguments passed to <code>plot.mkinfit</code> and <code>mkinresplot</code> .

Value

The function is called for its side effect.

Author(s)

Johannes Ranke

Examples

```
ds <- lapply(experimental_data_for_UBA_2019[6:10],
  function(x) subset(x$data[c("name", "time", "value")], name == "parent"))
f <- mmkin("SFO", ds, quiet = TRUE, cores = 1)
#plot(f) # too many panels for pkgdown
plot(f[, 3:4])
library(nlme)
f_nlme <- nlme(f)

#plot(f_nlme) # too many panels for pkgdown
plot(f_nlme, 3:4)
```

print.mkinds	<i>Print mkinds objects</i>
--------------	-----------------------------

Description

Print mkinds objects

Usage

```
## S3 method for class 'mkinds'  
print(x, ...)
```

Arguments

x	An <code>mkinds</code> object.
...	Not used.

print.mkinmod	<i>Print mkinmod objects</i>
---------------	------------------------------

Description

Print mkinmod objects in a way that the user finds his way to get to its components.

Usage

```
## S3 method for class 'mkinmod'  
print(x, ...)
```

Arguments

x	An <code>mkinmod</code> object.
...	Not used.

Examples

```
m_synth_SF0_lin <- mkinmod(parent = list(type = "SF0", to = "M1"),  
                           M1 = list(type = "SF0", to = "M2"),  
                           M2 = list(type = "SF0"), use_of_ff = "max")  
  
print(m_synth_SF0_lin)
```

residuals.mkinfit *Extract residuals from an mkinfit model*

Description

Extract residuals from an mkinfit model

Usage

```
## S3 method for class 'mkinfit'  
residuals(object, standardized = FALSE, ...)
```

Arguments

object	A <code>mkinfit</code> object
standardized	Should the residuals be standardized by dividing by the standard deviation obtained from the fitted error model?
...	Not used

Examples

```
f <- mkinfit("DFOP", FOCUS_2006_C, quiet = TRUE)  
residuals(f)  
residuals(f, standardized = TRUE)
```

schaefer07_complex_case

Metabolism data set used for checking the software quality of KinGUI

Description

This dataset was used for a comparison of KinGUI and ModelMaker to check the software quality of KinGUI in the original publication (Schäfer et al., 2007). The results from the fitting are also included.

Usage

```
schaefer07_complex_case
```


Format

The data set is a data frame with 8 observations on the following 6 variables.

time a numeric vector

parent a numeric vector

A1 a numeric vector

B1 a numeric vector

C1 a numeric vector

A2 a numeric vector

The results are a data frame with 14 results for different parameter values

References

Schäfer D, Mikolasch B, Rainbird P and Harvey B (2007). KinGUI: a new kinetic software tool for evaluations according to FOCUS degradation kinetics. In: Del Re AAM, Capri E, Fragoulis G and Trevisan M (Eds.). Proceedings of the XIII Symposium Pesticide Chemistry, Piacenza, 2007, p. 916-923.

Examples

```
data <- mkin_wide_to_long(schaefer07_complex_case, time = "time")
model <- mkinmod(
  parent = list(type = "SFO", to = c("A1", "B1", "C1"), sink = FALSE),
  A1 = list(type = "SFO", to = "A2"),
  B1 = list(type = "SFO"),
  C1 = list(type = "SFO"),
  A2 = list(type = "SFO", use_of_ff = "max")
  ## Not run:
  fit <- mkinfit(model, data, quiet = TRUE)
  plot(fit)
  endpoints(fit)

## End(Not run)
# Compare with the results obtained in the original publication
print(schaefer07_complex_results)
```

SFO.solution

Single First-Order kinetics

Description

Function describing exponential decline from a defined starting value.

Usage

```
SFO.solution(t, parent_0, k)
```

Arguments

t	Time.
parent_0	Starting value for the response variable at time zero.
k	Kinetic rate constant.

Value

The value of the response variable at time t.

References

FOCUS (2006) “Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics> FOCUS (2014) “Generic guidance for Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, Version 1.1, 18 December 2014 <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

See Also

Other parent solutions: [DFOP.solution\(\)](#), [FOMC.solution\(\)](#), [HS.solution\(\)](#), [IORE.solution\(\)](#), [SFORB.solution\(\)](#), [logistic.solution\(\)](#)

Examples

```
## Not run: plot(function(x) SF0.solution(x, 100, 3), 0, 2)
```

SFORB.solution

Single First-Order Reversible Binding kinetics

Description

Function describing the solution of the differential equations describing the kinetic model with first-order terms for a two-way transfer from a free to a bound fraction, and a first-order degradation term for the free fraction. The initial condition is a defined amount in the free fraction and no substance in the bound fraction.

Usage

```
SFORB.solution(t, parent_0, k_12, k_21, k_1output)
```

Arguments

t	Time.
parent_0	Starting value for the response variable at time zero.
k_12	Kinetic constant describing transfer from free to bound.
k_21	Kinetic constant describing transfer from bound to free.
k_1output	Kinetic constant describing degradation of the free fraction.

Value

The value of the response variable, which is the sum of free and bound fractions at time t.

References

FOCUS (2006) “Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics> FOCUS (2014) “Generic guidance for Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration” Report of the FOCUS Work Group on Degradation Kinetics, Version 1.1, 18 December 2014 <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

See Also

Other parent solutions: [DFOP.solution\(\)](#), [FOMC.solution\(\)](#), [HS.solution\(\)](#), [IORE.solution\(\)](#), [SFO.solution\(\)](#), [logistic.solution\(\)](#)

Examples

```
## Not run: plot(function(x) SFORB.solution(x, 100, 0.5, 2, 3), 0, 2)
```

sigma_twocomp

Two-component error model

Description

Function describing the standard deviation of the measurement error in dependence of the measured value y :

Usage

```
sigma_twocomp(y, sigma_low, rsd_high)
```

Arguments

y	The magnitude of the observed value
sigma_low	The asymptotic minimum of the standard deviation for low observed values
rsd_high	The coefficient describing the increase of the standard deviation with the magnitude of the observed value

Details

$$\sigma = \sqrt{\sigma_{low}^2 + y^2 * rsd_{high}^2}$$

`sigma = sqrt(sigma_low^2 + y^2 * rsd_high^2)`

This is the error model used for example by Werner et al. (1978). The model proposed by Rocke and Lorenzato (1995) can be written in this form as well, but assumes approximate lognormal distribution of errors for high values of y.

Value

The standard deviation of the response variable.

References

Werner, Mario, Brooks, Samuel H., and Knott, Lancaster B. (1978) Additive, Multiplicative, and Mixed Analytical Errors. *Clinical Chemistry* 24(11), 1895-1898.

Rocke, David M. and Lorenzato, Stefan (1995) A two-component model for measurement error in analytical chemistry. *Technometrics* 37(2), 176-184.

summary.mkinfit

Summary method for class "mkinfit"

Description

Lists model equations, initial parameter values, optimised parameters with some uncertainty statistics, the chi2 error levels calculated according to FOCUS guidance (2006) as defined therein, formation fractions, DT50 values and optionally the data, consisting of observed, predicted and residual values.

Usage

```
## S3 method for class 'mkinfit'
summary(object, data = TRUE, distimes = TRUE, alpha = 0.05, ...)
```

```
## S3 method for class 'summary.mkinfit'
print(x, digits = max(3, getOption("digits") - 3), ...)
```

Arguments

object	an object of class <code>mkinfit</code> .
data	logical, indicating whether the data should be included in the summary.
distimes	logical, indicating whether DT50 and DT90 values should be included.
alpha	error level for confidence interval estimation from t distribution
...	optional arguments passed to methods like <code>print</code> .
x	an object of class <code>summary.mkinfit</code> .
digits	Number of digits to use for printing

Value

The summary function returns a list with components, among others

version, Rversion	The mkin and R versions used
date.fit, date.summary	The dates where the fit and the summary were produced
diffs	The differential equations used in the model
use_of_ff	Was maximum or minimum use made of formation fractions
bpar	Optimised and backtransformed parameters
data	The data (see Description above).
start	The starting values and bounds, if applicable, for optimised parameters.
fixed	The values of fixed parameters.
errmin	The chi2 error levels for each observed variable.
bparms.ode	All backtransformed ODE parameters, for use as starting parameters for related models.
errparms	Error model parameters.
ff	The estimated formation fractions derived from the fitted model.
distimes	The DT50 and DT90 values for each observed variable.
SFORB	If applicable, eigenvalues of SFORB components of the model.

The print method is called for its side effect, i.e. printing the summary.

Author(s)

Johannes Ranke

References

FOCUS (2006) "Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration" Report of the FOCUS Work Group on Degradation Kinetics, EC Document Reference Sanco/10058/2005 version 2.0, 434 pp, <http://esdac.jrc.ec.europa.eu/projects/degradation-kinetics>

Examples

```
summary(mkinfit(mkinmod(parent = mkinsub("SFO")), FOCUS_2006_A, quiet = TRUE))
```

synthetic_data_for_UBA_2014

Synthetic datasets for one parent compound with two metabolites

Description

The 12 datasets were generated using four different models and three different variance components. The four models are either the SFO or the DFOP model with either two sequential or two parallel metabolites.

Variance component 'a' is based on a normal distribution with standard deviation of 3, Variance component 'b' is also based on a normal distribution, but with a standard deviation of 7. Variance component 'c' is based on the error model from Rocke and Lorenzato (1995), with the minimum standard deviation (for small y values) of 0.5, and a proportionality constant of 0.07 for the increase of the standard deviation with y. Note that this is a simplified version of the error model proposed by Rocke and Lorenzato (1995), as in their model the error of the measured values approximates lognormal distribution for high values, whereas we are using normally distributed error components all along.

Initial concentrations for metabolites and all values where adding the variance component resulted in a value below the assumed limit of detection of 0.1 were set to NA.

As an example, the first dataset has the title `SFO_lin_a` and is based on the SFO model with two sequential metabolites (linear pathway), with added variance component 'a'.

Compare also the code in the example section to see the degradation models.

Usage

```
synthetic_data_for_UBA_2014
```

Format

A list containing twelve datasets as an R6 class defined by `mkind`s, each containing, among others, the following components

`title` The name of the dataset, e.g. `SFO_lin_a`

`data` A data frame with the data in the form expected by `mkinfit`

Source

Ranke (2014) Prüfung und Validierung von Modellierungssoftware als Alternative zu ModelMaker 4.0, Umweltbundesamt Projektnummer 27452

Rocke, David M. und Lorenzato, Stefan (1995) A two-component model for measurement error in analytical chemistry. *Technometrics* 37(2), 176-184.

Examples

```

## Not run:
# The data have been generated using the following kinetic models
m_synth_SF0_lin <- mkinmod(parent = list(type = "SF0", to = "M1"),
                          M1 = list(type = "SF0", to = "M2"),
                          M2 = list(type = "SF0"), use_of_ff = "max")

m_synth_SF0_par <- mkinmod(parent = list(type = "SF0", to = c("M1", "M2"),
                                       sink = FALSE),
                          M1 = list(type = "SF0"),
                          M2 = list(type = "SF0"), use_of_ff = "max")

m_synth_DFOP_lin <- mkinmod(parent = list(type = "DFOP", to = "M1"),
                            M1 = list(type = "SF0", to = "M2"),
                            M2 = list(type = "SF0"), use_of_ff = "max")

m_synth_DFOP_par <- mkinmod(parent = list(type = "DFOP", to = c("M1", "M2"),
                                       sink = FALSE),
                            M1 = list(type = "SF0"),
                            M2 = list(type = "SF0"), use_of_ff = "max")

# The model predictions without intentional error were generated as follows
sampling_times = c(0, 1, 3, 7, 14, 28, 60, 90, 120)

d_synth_SF0_lin <- mkinpredict(m_synth_SF0_lin,
                              c(k_parent = 0.7, f_parent_to_M1 = 0.8,
                                k_M1 = 0.3, f_M1_to_M2 = 0.7,
                                k_M2 = 0.02),
                              c(parent = 100, M1 = 0, M2 = 0),
                              sampling_times)

d_synth_DFOP_lin <- mkinpredict(m_synth_DFOP_lin,
                              c(k1 = 0.2, k2 = 0.02, g = 0.5,
                                f_parent_to_M1 = 0.5, k_M1 = 0.3,
                                f_M1_to_M2 = 0.7, k_M2 = 0.02),
                              c(parent = 100, M1 = 0, M2 = 0),
                              sampling_times)

d_synth_SF0_par <- mkinpredict(m_synth_SF0_par,
                              c(k_parent = 0.2,
                                f_parent_to_M1 = 0.8, k_M1 = 0.01,
                                f_parent_to_M2 = 0.2, k_M2 = 0.02),
                              c(parent = 100, M1 = 0, M2 = 0),
                              sampling_times)

d_synth_DFOP_par <- mkinpredict(m_synth_DFOP_par,
                              c(k1 = 0.3, k2 = 0.02, g = 0.7,
                                f_parent_to_M1 = 0.6, k_M1 = 0.04,
                                f_parent_to_M2 = 0.4, k_M2 = 0.01),
                              c(parent = 100, M1 = 0, M2 = 0),
                              sampling_times)

```

```

# Construct names for datasets with errors
d_synth_names = paste0("d_synth_", c("SFO_lin", "SFO_par",
                                     "DFOP_lin", "DFOP_par"))

# Original function used for adding errors. The add_err function now published
# with this package is a slightly generalised version where the names of
# secondary compartments that should have an initial value of zero (M1 and M2
# in this case) are not hardcoded any more.
# add_err = function(d, sdfunc, LOD = 0.1, reps = 2, seed = 123456789)
# {
#   set.seed(seed)
#   d_long = mkin_wide_to_long(d, time = "time")
#   d_rep = data.frame(lapply(d_long, rep, each = 2))
#   d_rep$value = rnorm(length(d_rep$value), d_rep$value, sdfunc(d_rep$value))
#   #
#   d_rep[d_rep$time == 0 & d_rep$name %in% c("M1", "M2"), "value"] <- 0
#   d_NA <- transform(d_rep, value = ifelse(value < LOD, NA, value))
#   d_NA$value <- round(d_NA$value, 1)
#   return(d_NA)
# }

# The following is the simplified version of the two-component model of Rocke
# and Lorenzato (1995)
sdfunc_twocomp = function(value, sd_low, rsd_high) {
  sqrt(sd_low^2 + value^2 * rsd_high^2)
}

# Add the errors.
for (d_synth_name in d_synth_names)
{
  d_synth = get(d_synth_name)
  assign(paste0(d_synth_name, "_a"), add_err(d_synth, function(value) 3))
  assign(paste0(d_synth_name, "_b"), add_err(d_synth, function(value) 7))
  assign(paste0(d_synth_name, "_c"), add_err(d_synth,
                                             function(value) sdfunc_twocomp(value, 0.5, 0.07)))
}

d_synth_err_names = c(
  paste(rep(d_synth_names, each = 3), letters[1:3], sep = "_")
)

# This is just one example of an evaluation using the kinetic model used for
# the generation of the data
fit <- mkinfit(m_synth_SFO_lin, synthetic_data_for_UBA_2014[[1]]$data,
              quiet = TRUE)

plot_sep(fit)
summary(fit)

## End(Not run)

```

test_data_from_UBA_2014

Three experimental datasets from two water sediment systems and one soil

Description

The datasets were used for the comparative validation of several kinetic evaluation software packages (Ranke, 2014).

Usage

```
test_data_from_UBA_2014
```

Format

A list containing three datasets as an R6 class defined by `mkind`s. Each dataset has, among others, the following components

`title` The name of the dataset, e.g. UBA_2014_WS_river

`data` A data frame with the data in the form expected by `mkinf`

Source

Ranke (2014) Prüfung und Validierung von Modellierungssoftware als Alternative zu ModelMaker 4.0, Umweltbundesamt Projektnummer 27452

Examples

```
## Not run:
# This is a level P-II evaluation of the dataset according to the FOCUS kinetics
# guidance. Due to the strong correlation of the parameter estimates, the
# covariance matrix is not returned. Note that level P-II evaluations are
# generally considered deprecated due to the frequent occurrence of such
# large parameter correlations, among other reasons (e.g. the adequacy of the
# model).
m_ws <- mkinmod(parent_w = mkinsub("SF0", "parent_s"),
               parent_s = mkinsub("SF0", "parent_w"))
f_river <- mkinf(m_ws, test_data_from_UBA_2014[[1]]$data, quiet = TRUE)
plot_sep(f_river)

summary(f_river)$bpar
mkinerrmin(f_river)

# This is the evaluation used for the validation of software packages
# in the expertise from 2014
m_soil <- mkinmod(parent = mkinsub("SF0", c("M1", "M2")),
                 M1 = mkinsub("SF0", "M3"),
                 M2 = mkinsub("SF0", "M3"),
```

```

M3 = mkinsub("SFO"),
use_of_ff = "max")

f_soil <- mkinfit(m_soil, test_data_from_UBA_2014[[3]]$data, quiet = TRUE)
plot_sep(f_soil, lpos = c("topright", "topright", "topright", "bottomright"))
summary(f_soil)$bpar
mkinerrmin(f_soil)

## End(Not run)

```

transform_odeparms	<i>Functions to transform and backtransform kinetic parameters for fitting</i>
--------------------	--

Description

The transformations are intended to map parameters that should only take on restricted values to the full scale of real numbers. For kinetic rate constants and other parameters that can only take on positive values, a simple log transformation is used. For compositional parameters, such as the formation fractions that should always sum up to 1 and can not be negative, the [ilr](#) transformation is used.

Usage

```

transform_odeparms(
  parms,
  mkinmod,
  transform_rates = TRUE,
  transform_fractions = TRUE
)

backtransform_odeparms(
  transparms,
  mkinmod,
  transform_rates = TRUE,
  transform_fractions = TRUE
)

```

Arguments

parms	Parameters of kinetic models as used in the differential equations.
mkinmod	The kinetic model of class mkinmod , containing the names of the model variables that are needed for grouping the formation fractions before ilr transformation, the parameter names and the information if the pathway to sink is included in the model.

transform_rates	Boolean specifying if kinetic rate constants should be transformed in the model specification used in the fitting for better compliance with the assumption of normal distribution of the estimator. If TRUE, also alpha and beta parameters of the FOMC model are log-transformed, as well as k1 and k2 rate constants for the DFOP and HS models and the break point tb of the HS model.
transform_fractions	Boolean specifying if formation fractions constants should be transformed in the model specification used in the fitting for better compliance with the assumption of normal distribution of the estimator. The default (TRUE) is to do transformations. The g parameter of the DFOP and HS models are also transformed, as they can also be seen as compositional data. The transformation used for these transformations is the ilr transformation.
transparms	Transformed parameters of kinetic models as used in the fitting procedure.

Details

The transformation of sets of formation fractions is fragile, as it supposes the same ordering of the components in forward and backward transformation. This is no problem for the internal use in [mkinfit](#).

Value

A vector of transformed or backtransformed parameters with the same names as the original parameters.

Functions

- [backtransform_odeparms](#): Backtransform the set of transformed parameters

Author(s)

Johannes Ranke

Examples

```
SFO_SFO <- mkinmod(
  parent = list(type = "SFO", to = "m1", sink = TRUE),
  m1 = list(type = "SFO"))
# Fit the model to the FOCUS example dataset D using defaults
fit <- mkinfit(SFO_SFO, FOCUS_2006_D, quiet = TRUE)
fit.s <- summary(fit)
# Transformed and backtransformed parameters
print(fit.s$par, 3)
print(fit.s$bpar, 3)

## Not run:
# Compare to the version without transforming rate parameters
fit.2 <- mkinfit(SFO_SFO, FOCUS_2006_D, transform_rates = FALSE, quiet = TRUE)
```

```

fit.2.s <- summary(fit.2)
print(fit.2.s$par, 3)
print(fit.2.s$bpar, 3)

## End(Not run)

initials <- fit$start$value
names(initials) <- rownames(fit$start)
transformed <- fit$start_transformed$value
names(transformed) <- rownames(fit$start_transformed)
transform_odeparms(initials, SFO_SFO)
backtransform_odeparms(transformed, SFO_SFO)

## Not run:
# The case of formation fractions
SFO_SFO.ff <- mkinmod(
  parent = list(type = "SFO", to = "m1", sink = TRUE),
  m1 = list(type = "SFO"),
  use_of_ff = "max")

fit.ff <- mkinfit(SFO_SFO.ff, FOCUS_2006_D, quiet = TRUE)
fit.ff.s <- summary(fit.ff)
print(fit.ff.s$par, 3)
print(fit.ff.s$bpar, 3)
initials <- c("f_parent_to_m1" = 0.5)
transformed <- transform_odeparms(initials, SFO_SFO.ff)
backtransform_odeparms(transformed, SFO_SFO.ff)

# And without sink
SFO_SFO.ff.2 <- mkinmod(
  parent = list(type = "SFO", to = "m1", sink = FALSE),
  m1 = list(type = "SFO"),
  use_of_ff = "max")

fit.ff.2 <- mkinfit(SFO_SFO.ff.2, FOCUS_2006_D, quiet = TRUE)
fit.ff.2.s <- summary(fit.ff.2)
print(fit.ff.2.s$par, 3)
print(fit.ff.2.s$bpar, 3)

## End(Not run)

```

update.mkinfit

Update an mkinfit model with different arguments

Description

This function will return an updated mkinfit object. The fitted degradation model parameters from the old fit are used as starting values for the updated fit. Values specified as 'parms.ini' and/or 'state.ini' will override these starting values.

Usage

```
## S3 method for class 'mkinfit'
update(object, ..., evaluate = TRUE)
```

Arguments

object	An mkinfit object to be updated
...	Arguments to <code>mkinfit</code> that should replace the arguments from the original call. Arguments set to NULL will remove arguments given in the original call
evaluate	Should the call be evaluated or returned as a call

Examples

```
## Not run:
fit <- mkinfit("SF0", subset(FOCUS_2006_D, value != 0), quiet = TRUE)
parms(fit)
plot_err(fit)
fit_2 <- update(fit, error_model = "tc")
parms(fit_2)
plot_err(fit_2)

## End(Not run)
```

[.mmkin

*Subsetting method for mmkin objects***Description**

Subsetting method for mmkin objects.

Usage

```
## S3 method for class 'mmkin'
x[i, j, ..., drop = FALSE]
```

Arguments

x	An <code>mmkin</code> object
i	Row index selecting the fits for specific models
j	Column index selecting the fits to specific datasets
...	Not used, only there to satisfy the generic method definition
drop	If FALSE, the method always returns an mmkin object, otherwise either a list of mkinfit objects or a single mkinfit object.

Value

An object of class `mmkin`.

Author(s)

Johannes Ranke

Examples

```
# Only use one core, to pass R CMD check --as-cran
fits <- mmkin(c("SFO", "FOMC"), list(B = FOCUS_2006_B, C = FOCUS_2006_C),
            cores = 1, quiet = TRUE)
fits["FOMC", ]
fits[, "B"]
fits["SFO", "B"]

head(
  # This extracts an mkinfit object with lots of components
  fits[["FOMC", "B"]]
)
```

Index

- *Topic **datasets**
 - experimental_data_for_UBA_2019, [14](#)
 - FOCUS_2006_datasets, [16](#)
 - FOCUS_2006_DFOP_ref_A_to_B, [17](#)
 - FOCUS_2006_FOMC_ref_A_to_F, [18](#)
 - FOCUS_2006_HS_ref_A_to_F, [19](#)
 - FOCUS_2006_SFO_ref_A_to_F, [20](#)
 - mccall181_245T, [33](#)
 - NAFTA_SOP_2015, [57](#)
 - NAFTA_SOP_Attachment, [58](#)
 - schaefer07_complex_case, [72](#)
 - synthetic_data_for_UBA_2014, [78](#)
 - test_data_from_UBA_2014, [81](#)
- *Topic **hplot**
 - mkinnerrplot, [36](#)
- *Topic **manip**
 - endpoints, [13](#)
 - ilr, [23](#)
 - mkinnwide_to_long, [53](#)
 - mkinnerrmin, [35](#)
- *Topic **optimize**
 - mmkin, [54](#)
 - [.mmkin, [55](#), [67](#), [85](#)
- add_err, [3](#)
- AIC, [41](#)
- AIC.mmkin, [5](#), [30](#)
- array, [54](#)
- aw, [6](#)
- backtransform_odeparms
 - (transform_odeparms), [82](#)
- BIC.mmkin (AIC.mmkin), [5](#)
- CAKE_export, [7](#)
- cfunction, [44](#)
- confint.mkinfit, [9](#)
- create_deg_func, [11](#)
- deSolve, [39](#), [41](#)
- DFOP.solution, [12](#), [22](#), [23](#), [25](#), [28](#), [74](#), [75](#)
- dnorm, [29](#)
- endpoints, [13](#)
- experimental_data_for_UBA_2019, [14](#)
- FOCUS_2006_A (FOCUS_2006_datasets), [16](#)
- FOCUS_2006_B (FOCUS_2006_datasets), [16](#)
- FOCUS_2006_C (FOCUS_2006_datasets), [16](#)
- FOCUS_2006_D (FOCUS_2006_datasets), [16](#)
- FOCUS_2006_datasets, [16](#)
- FOCUS_2006_DFOP_ref_A_to_B, [17](#)
- FOCUS_2006_E (FOCUS_2006_datasets), [16](#)
- FOCUS_2006_F (FOCUS_2006_datasets), [16](#)
- FOCUS_2006_FOMC_ref_A_to_F, [18](#)
- FOCUS_2006_HS_ref_A_to_F, [19](#)
- FOCUS_2006_SFO_ref_A_to_F, [20](#)
- FOMC.solution, [13](#), [21](#), [23](#), [25](#), [28](#), [74](#), [75](#)
- get_deg_func, [22](#)
- groupedData, [61](#)
- HS.solution, [13](#), [22](#), [22](#), [25](#), [28](#), [74](#), [75](#)
- ilr, [23](#), [40](#), [82](#), [83](#)
- invilr (ilr), [23](#)
- IORE.solution, [13](#), [22](#), [23](#), [24](#), [28](#), [74](#), [75](#)
- legend, [37](#), [51](#), [65](#), [66](#)
- loftest, [26](#)
- logistic.solution, [13](#), [22](#), [23](#), [25](#), [27](#), [74](#), [75](#)
- logLik, [29](#)
- logLik.mkinfit, [29](#), [41](#)
- lrtest.default, [26](#), [31](#)
- lrtest.mkinfit, [30](#)
- lrtest.mmkin (lrtest.mkinfit), [30](#)
- lsoda, [40](#), [48](#)
- makeCluster, [54](#)
- max_twa_dfop (max_twa_parent), [31](#)
- max_twa_fomc (max_twa_parent), [31](#)

- max_twa_hs (max_twa_parent), 31
- max_twa_parent, 31
- max_twa_sfo (max_twa_parent), 31
- mccall81_245T, 33
- mean_degparms (nlme_function), 61
- mkin_long_to_wide, 52
- mkin_wide_to_long, 53
- mkininds, 15, 34, 71, 78, 81
- mkinerrmin, 35
- mkinerrplot, 36, 67, 70
- mkinfit, 4, 7–9, 14, 15, 29–32, 35, 37, 38, 44–46, 48, 50, 53, 54, 64, 65, 72, 77, 78, 81, 83, 85
- mkinmod, 33, 38–40, 43, 47, 48, 51, 52, 54, 71, 82
- mkinparplot, 41, 45
- mkinplot, 37, 46, 51
- mkinpredict, 3, 4, 38–40, 47, 48
- mkinresplot, 50, 67, 70
- mkinsub, 51
- mmkin, 4, 5, 7, 30, 41, 54, 56, 59, 67, 85
- mtext, 67, 70

- nafta, 55, 56, 58, 69
- NAFTA_SOP_2015, 57
- NAFTA_SOP_Appendix_B (NAFTA_SOP_2015), 57
- NAFTA_SOP_Appendix_D (NAFTA_SOP_2015), 57
- NAFTA_SOP_Attachment, 58
- nlme.mmkin, 14, 58, 62, 70
- nlme_data (nlme_function), 61
- nlme_function, 60, 61
- nlminb, 38, 40
- nobs.mkinfit, 62

- ode, 39, 40, 48

- parms, 63
- plot, 37, 51, 66
- plot.mkinfit, 36, 41, 46, 50, 64, 67, 70
- plot.mmkin, 55, 67, 69
- plot.nafta, 68
- plot.nlme.mmkin, 69
- plot_err (plot.mkinfit), 64
- plot_res, 51
- plot_res (plot.mkinfit), 64
- plot_sep (plot.mkinfit), 64
- print.mkininds, 35, 71
- print.mkinmod, 71
- print.nafta (nafta), 55
- print.nlme.mmkin (nlme.mmkin), 58
- print.summary.mkinfit (summary.mkinfit), 76

- residuals.mkinfit, 72

- schaefer07_complex_case, 72
- schaefer07_complex_results (schaefer07_complex_case), 72
- SFO.solution, 13, 21–23, 25, 28, 73, 75
- SFORB.solution, 13, 22, 23, 25, 28, 74, 74
- sigma_twocomp, 75
- summary.mkinfit, 14, 35, 41, 76
- synthetic_data_for_UBA_2014, 78

- test_data_from_UBA_2014, 81
- tikz, 66, 68
- transform_odeparms, 82

- update.mkinfit, 30, 31, 84
- update.nlme.mmkin (nlme.mmkin), 58