

# Package ‘nlshelper’

April 3, 2017

**Title** Convenient Functions for Non-Linear Regression

**Version** 0.2

**Description** A few utilities for summarizing, testing, and plotting non-linear regression models fit with `nls()`, `nlsList()` or `nlme()`.

**Depends** `nlme`, `broom`, `dplyr`, `mgcv`, `magicaxis`

**License** GPL-2

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 5.0.1

**NeedsCompilation** no

**Author** Remko Duursma [aut, cre]

**Maintainer** Remko Duursma <[remkoduursma@gmail.com](mailto:remkoduursma@gmail.com)>

**Repository** CRAN

**Date/Publication** 2017-04-03 20:19:13 UTC

## R topics documented:

<code>abline_range</code> . . . . .	2
<code>add_regres_line</code> . . . . .	3
<code>anova_nlslist</code> . . . . .	4
<code>plot_gam</code> . . . . .	4
<code>plot_nls</code> . . . . .	6
<code>tidy.nlsList</code> . . . . .	7

**Index**

**9**

**abline\_range***Add a line to a plot*

## Description

As `abline`, but with `from` and `to` arguments. If a fitted linear regression model is used as `as.numeric` argument, it uses the min and max values of the data used to fit the model.

## Usage

```
abline_range(a = NULL, b = NULL, reg = NULL, from = NULL, to = NULL,
             ...)
```

## Arguments

<code>a</code>	Intercept (optional)
<code>b</code>	Slope (optional)
<code>reg</code>	A fitted linear regression model (output of <a href="#">lm</a> ).
<code>from</code>	Draw from this X value
<code>to</code>	Draw to this x value
<code>...</code>	Further parameters passed to <a href="#">segments</a>

## See Also

See [add\\_regres\\_line](#) for adding a regression line with a confidence interval

## Examples

```
# Add a line manually
with(mtcars, plot(1/wt, mpg, xlim=c(0,0.8), ylim=c(0,40)))
abline_range(0,50,from=0.2, to=0.6)

# Add a line across the range of the data from a regression object
with(mtcars, plot(1/wt, mpg, xlim=c(0,0.8), ylim=c(0,40)))
fit <- lm(mpg ~ I(1/wt), data=mtcars)
abline_range(fit)
```

---

**add\_regres\_line***Add a regression line and confidence band to a plot*

---

## Description

Plots a regression line from a simple linear model (of the form `lm(y ~ x)`) to a plot. Also plots the confidence band for the mean, which is calculated using `predict.lm`.

## Usage

```
add_regres_line(fit, from = NULL, to = NULL, band = TRUE,  
 ci.col = "#BEBEBEB3", ...)
```

## Arguments

<code>fit</code>	Object returned by <code>lm</code> . Only models of the form <code>y ~ x</code> are supported, without expressions in <code>I()</code> (see Examples), or interactions, or multiple variables.
<code>from</code>	Optional (read from fitted model); Draw from this X value.
<code>to</code>	Optional (read from fitted model); Draw to this x value.
<code>band</code>	Logical. Whether to add a confidence band.
<code>ci.col</code>	Colour of the confidence band, if plotted. Defaults to a transparent grey colour.
<code>...</code>	Further arguments passed to <code>abline_range</code>

## Examples

```
'Add a line across the range of the data from a regression object  
with(mtcars, plot(1/wt, mpg, xlim=c(0,0.8), ylim=c(0,40)))  
  
# add_regres_line does not allow I() expressions; yet.  
mtcars$inv_wt <- 1 / mtcars$wt  
fit <- lm(mpg ~ inv_wt, data=mtcars)  
add_regres_line(fit)  
  
# Add the regression line and confidence band behind the data  
fit <- lm(height ~ age, data=Loblolly)  
with(Loblolly, plot(age, height, pch=19, panel.first=add_regres_line(fit)))
```

**anova\_nlslist***Anova for nlsList***Description**

Applies an F-test to a non-linear regression model that includes a grouping variable (fit with `nlsList`), comparing it to a model without a grouping variable. This is a convenient way to test whether there is an overall effect of the grouping variable on the non-linear relationship.

**Usage**

```
anova_nlslist(nlsfull, nlsreduc)
```

**Arguments**

<code>nlsfull</code>	The full model, an object returned by <code>nlsList</code>
<code>nlsreduc</code>	The reduced model, which is identical to the full model except the grouping variable has been removed, and it was fit with <code>nls</code>

**Examples**

```
chick <- as.data.frame(ChickWeight)

# Fit a simple model with nls
fit0 <- nls(weight ~ a*time^b, data=chick, start=list(a=10, b=1.1))

# Fit an nlsList model, with a grouping variable (Diet)
fit1 <- nlsList(weight ~ a*time^b | Diet, data=chick, start=list(a=10, b=1.1))

# Using an F-test, test whether the fit is significantly better when adding
# a grouping variable
anova_nlslist(fit1, fit0)
```

**plot\_gam***Plot a generalized additive model***Description**

This is a simple wrapper to fit and plot a basic type of generalized additive model. The fitted model is of the form `gam(Y ~ s(X, k))`, which can be fitted by a specified grouping variable (using the `g` argument). Also supported is an optional random effect, in which case the model fitted is `gamm(Y ~ s(X, k=k), random = list(R=~1), data=dfr)`.

**Usage**

```
plot_gam(x, y, g = NULL, data, fittype = c("gam", "lm"), kgam = 4,
         R = NULL, log = "", axes = TRUE, fitoneline = FALSE,
         points.col = NULL, lines.col = NULL, ci.col = "#D3D3D3B3",
         xlab = NULL, ylab = NULL, band = TRUE, plotit = TRUE, add = FALSE,
         npred = 101, lwd = 2, ...)
```

**Arguments**

x	Variable for X axis (unquoted)
y	Variable for Y axis (unquoted)
g	Variable for grouping (unquoted); optional
data	Dataframe containing x and y
fittype	Either 'gam' (default), or 'lm' in which case a simple linear model is fit - useful for comparison.
kgam	the k parameter for smooth terms in gam.
R	An optional random effect (quoted)
log	Whether to add log axes for x or y (but no transformations are done).
axes	Logical (default TRUE), whether to add axes to the plot.
fitoneline	Whether to fit only one curve to the entire dataset, regardless of whether a grouping variable was defined. Default FALSE.
points.col	Colours of the points, can be a vector (one value for each group, if present).
lines.col	Colours of the lines, can be a vector (one value for each group, if present).
ci.col	Colour of the confidence band, if plotted. Defaults to a transparent grey colour.
xlab	X-axis label
ylab	Y-axis label
band	Logical. If true, plots the confidence band (as a transparent polygon).
plotit	Logical (default TRUE); if FALSE, suppresses the plot.
add	Logical (default FALSE), if TRUE, adds to an existing plot.
npred	Number of x values to use for prediction
lwd	Line thickness (see <a href="#">par</a> )
...	Further arguments passed to <a href="#">plot</a> or <a href="#">points</a> , for example to change colour of plotting symbols.

**Details**

In either case, the k parameter necessary for the GAM fit can be set using the kgam argument. See [choose.k](#) for details on this setting (it is important you don't just use the default value here!).

## Examples

```
data(Loblolly)
plot_gam(age, height, data=Loblolly)
plot_gam(age, height, Seed, data=Loblolly, band=FALSE, lines.col="black")
plot_gam(age, height, Seed, data=Loblolly, band=FALSE, lines.col="black", fittype="lm")

data(ChickWeight)
plot_gam(Time, weight, Diet, R="Chick", data=ChickWeight, lines.col=rainbow(4))
```

**plot\_nls**

*Plot a non-linear or non-parametric regression model*

## Description

Convenient function for adding curves to an existing plot, or to plot the data with the fitted curve. For non-linear regression plotting (`plot_nls`), works for simple non-linear regression models fit with `nls`, and grouped non-linear regression (with `nlsList`), in which case one fitted curve for each group is drawn on the same plot. For local regression models fitted with `loess`, use the `plot_loess` function which additionally adds a confidence interval around the fitted curve.

## Usage

```
plot_nls(object, col = NULL, band = TRUE, plotdata = TRUE,
         lines.col = palette(), points.col = palette(), ci.col = "#BEBEBEB3",
         lwd = 1, lty = 1, add = FALSE, xlab = NULL, ylab = NULL,
         coverage = 0.95, ...)

plot_loess(object, ...)
```

## Arguments

<code>object</code>	The object returned by <code>nls</code> , <code>nlsList</code> or <code>loess</code>
<code>col</code>	Colour to be used for the data symbols and the fitted line, unless <code>lines.col</code> and <code>points.col</code> are provided
<code>band</code>	For <code>plot_loess</code> , whether to add a confidence band. Not yet implemented for <code>plot_nls</code>
<code>plotdata</code>	Logical. Whether to add the data points to the plot.
<code>lines.col</code>	Colour(s) for the fitted lines. When plotting a <code>nlsList</code> object, can be a vector that represents colours for each group.
<code>points.col</code>	Colour(s) for the data symbols. When plotting a <code>nlsList</code> object, can be a vector that represents colours for each group.
<code>ci.col</code>	Colour of the confidence band, if plotted. Defaults to a transparent grey colour.
<code>lwd</code>	Thickness of the line (see <code>par</code> )
<code>lty</code>	Line type (see <code>par</code> )

add	Logical. Whether to add to current plot (default FALSE).
xlab	Label for x-axis
ylab	Label for y-axis
coverage	If confidence band to be plotted, the coverage (e.g. for 95% confidence interval, use 0.95)
...	Further arguments passed to <a href="#">plot</a>

**Value**

Returns the predicted values used in plotting (invisibly), as a dataframe with columns 'predvar' (regularly spaced predictor values), and 'fit' (fitted values). For `plot_loess` also returns confidence intervals, standard error, and df of the residual.

**Examples**

```
# Plot an nls object
chick <- as.data.frame(ChickWeight)
fit0 <- nls(weight ~ a*time^b, data=chick, start=list(a=10, b=1.1))
plot_nls(fit0)

# Plot a grouped nls object
library(nlme)
fit1 <- nlsList(weight ~ a*time^b|Diet, data=chick, start=list(a=10, b=1.1))
plot_nls(fit1)

# Plot a local regression object, with confidence interval
l <- loess(wt ~ disp, data=mtcars)
plot_loess(l)

# To plot behind the data:
with(mtcars, plot(disp, wt, pch=19,
  panel.first=plot_loess(l, plotdata=FALSE)))
```

**Description**

Adds a method to [tidy](#) (broom package), so that we can use it for models fitted with [nlsList](#).

**Usage**

```
## S3 method for class 'nlsList'
tidy(x, conf.int = FALSE, conf.level = 0.95,
  quick = FALSE, ...)
```

**Arguments**

x	An object returned by <a href="#">nlsList</a>
conf.int	Whether to calculate confidence intervals
conf.level	The level of the confidence interval
quick	If TRUE, only returns the coefficients.
...	Further arguments passed to <a href="#">tidy</a>

**Examples**

```
chick <- as.data.frame(ChickWeight)

# Fit an nlsList model, with a grouping variable (Diet)
fit1 <- nlsList(weight ~ a*time^b | Diet, data=chick, start=list(a=10, b=1.1))

# Collect coefficients
tidy(fit1)

# ... and confidence intervals
tidy(fit1, conf.int=TRUE)
```

# Index

abline\_range, 2, 3  
add\_regres\_line, 2, 3  
anova\_nlslist, 4  
  
choose.k, 5  
  
lm, 2  
  
nls, 4, 6  
nlsList, 4, 6–8  
  
par, 5, 6  
plot, 7  
plot\_gam, 4  
plot\_loess (plot\_nls), 6  
plot\_nls, 6  
predict.lm, 3  
  
segments, 2  
  
tidy, 7, 8  
tidy.nlsList, 7