

Package ‘nzilbb.labbcats’

June 13, 2020

Version 0.5-1

Date 2020-06-08

Title Accessing Data Stored in 'LaBB-CAT' Instances

Imports jsonlite, httr, stringr, utils, rstudioapi

Description 'LaBB-CAT' is a web-based language corpus management system developed by the New Zealand Institute of Language, Brain and Behaviour (NZILBB) - see <<https://labbcats.canterbury.ac.nz>>. This package defines functions for accessing corpus data in a 'LaBB-CAT' instance. You must have at least version 20200608.1507 of 'LaBB-CAT' to use this package.

For more information about 'LaBB-CAT', see Robert Fromont and Jennifer Hay (2008) <[doi:10.3366/E1749503208000142](https://doi.org/10.3366/E1749503208000142)> or Robert Fromont (2017) <[doi:10.1016/j.csl.2017.01.004](https://doi.org/10.1016/j.csl.2017.01.004)>.

License GPL (>= 3)

Copyright New Zealand Institute of Language, Brain and Behaviour, University of Canterbury

URL <https://github.com/nzilbb/labbcats-R>,
<https://labbcats.canterbury.ac.nz>

RoxygenNote 7.0.2

Suggests testthat (>= 2.1.0)

NeedsCompilation no

Author Robert Fromont [aut, cre]

Maintainer Robert Fromont <robert@fromont.net.nz>

Repository CRAN

Date/Publication 2020-06-13 15:30:14 UTC

R topics documented:

countAnnotations 2

getAnchors	3
getAnnotations	4
getAvailableMedia	5
getCorpusIds	6
getDictionaries	7
getDictionaryEntries	8
getFragments	9
getGraphIds	10
getGraphIdsInCorpus	11
getGraphIdsWithParticipant	12
getId	12
getLayer	13
getLayerIds	14
getLayers	15
getMatches	16
getMatchingGraphIds	19
getMatchingTranscriptIds	20
getMatchLabels	21
getMedia	23
getMediaTracks	24
getParticipantAttributes	24
getParticipantIds	25
getSoundFragments	26
getTranscriptAttributes	27
getTranscriptIds	28
getTranscriptIdsInCorpus	28
getTranscriptIdsWithParticipant	29
labcatCredentials	30
labcatTimeout	31
nzilbb.labcat	32
praatScriptCentreOfGravity	34
praatScriptFormants	35
praatScriptIntensity	37
praatScriptPitch	38
processWithPraat	40
Index	44

countAnnotations	<i>Gets the number of annotations on the given layer of the given transcript.</i>
------------------	---

Description

Returns the number of annotations on the given layer of the given transcript.

Usage

```
countAnnotations(labbcats.url, id, layerId)
```

Arguments

```
labbcats.url    URL to the LaBB-CAT instance
id              A transcript ID (i.e. transcript name)
layerId         A layer ID
```

Value

The number of annotations on that layer

See Also

[getTranscriptIds](#) [getTranscriptIdsInCorpus](#) [getTranscriptIdsWithParticipant](#)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## Count the number of words in UC427_ViktoriaPapp_A_ENG.eaf
token.count <- countAnnotations(labbcats.url, "UC427_ViktoriaPapp_A_ENG.eaf", "orthography")

## End(Not run)
```

getAnchors	<i>Gets the given anchors in the given transcript.</i>
------------	--

Description

Lists the given anchors in the given transcript.

Usage

```
getAnchors(labbcats.url, id, anchorId)
```

Arguments

```
labbcats.url    URL to the LaBB-CAT instance
id              A transcript ID (i.e. transcript name)
anchorId        A vector of anchor IDs (or a string representing one anchor ID)
```

Value

A named list of anchors, with members:

- *id* The annotation's unique ID,
- *offset* The offset from the beginning (in seconds if it's a transcript of a recording, or in characters if it's a text document)
- *confidence* A rating from 0-100 of the confidence of the offset, e.g. 10: default value, 50: force-aligned, 100: manually aligned

See Also

[getAnnotations](#)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## Get the first 20 orthography tokens in UC427_ViktoriaPapp_A_ENG.eaf
orthography <- getAnnotations(labbcats.url, "UC427_ViktoriaPapp_A_ENG.eaf", "orthography", 20, 0)

## Get the start anchors for the above tokens
word.starts <- getAnchors(labbcats.url, "UC427_ViktoriaPapp_A_ENG.eaf", orthography$startId)

## End(Not run)
```

getAnnotations	<i>Gets the annotations on the given layer of the given transcript.</i>
----------------	---

Description

Returns the annotations on the given layer of the given transcript.

Usage

```
getAnnotations(labbcats.url, id, layerId, pageLength = NULL, pageNumber = NULL)
```

Arguments

labbcats.url	URL to the LaBB-CAT instance
id	A transcript ID (i.e. transcript name)
layerId	A layer ID
pageLength	The maximum number of annotations to return, or null to return all
pageNumber	The zero-based page number to return, or null to return the first page

Value

A named list of annotations, with members:

- *id* The annotation's unique ID
- *layerId* The name of the layer it comes from
- *label* The value of the annotation
- *startId* The ID of the start anchor,
- *endId* The ID of the end anchor,
- *parentId* The ID of the parent annotation,
- *ordinal* The ordinal of the annotation among its peers,
- *confidence* A rating from 0-100 of the confidence of the label e.g. 10: default value, 50: automatically generated, 100: manually annotated

See Also

[getTranscriptIds](#) [getTranscriptIdsInCorpus](#) [getTranscriptIdsWithParticipant](#) [countAnnotations](#)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## Get all the orthography tokens in UC427_ViktoriaPapp_A_ENG.eaf
orthography <- getAnnotations(labbcats.url, "UC427_ViktoriaPapp_A_ENG.eaf", "orthography")

## Get the first 20 orthography tokens in UC427_ViktoriaPapp_A_ENG.eaf
orthography <- getAnnotations(labbcats.url, "UC427_ViktoriaPapp_A_ENG.eaf", "orthography", 20, 0)

## End(Not run)
```

getAvailableMedia *List the media available for the given transcript.*

Description

List the media available for the given transcript.

Usage

```
getAvailableMedia(labbcats.url, id)
```

Arguments

labbcats.url	URL to the LaBB-CAT instance
id	A transcript ID (i.e. transcript name)

Value

A named list of media files available for the given transcript, with members:

- *trackSuffix* The track suffix of the media
- *contentType* The MIME type of the file
- *url* URL to the content of the file
- *name* Name of the file

See Also

[getTranscriptIds](#)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## List the media files available for BR2044_OllyOhlson.eaf
media <- getAvailableMedia(labbcats.url, "BR2044_OllyOhlson.eaf")

## End(Not run)
```

getCorpusIds

Gets a list of corpus IDs.

Description

Returns a list of corpora in the given 'LaBB-CAT' instance.

Usage

```
getCorpusIds(labbcats.url)
```

Arguments

labbcats.url URL to the LaBB-CAT instance

Value

A list of corpus IDs

Examples

```
## Not run:  
## List corpora  
corpora <- getCorpusIds("https://labbcat.canterbury.ac.nz/demo/")  
  
## End(Not run)
```

getDictionaries	<i>List the dictionaries available.</i>
-----------------	---

Description

List the dictionaries available.

Usage

```
getDictionaries(labbcat.url)
```

Arguments

labbcat.url URL to the LaBB-CAT instance

Value

A named list of layer manager IDs, each of which containing a list of dictionaries that the layer manager makes available.

See Also

[getDictionaryEntries](#)

Examples

```
## Not run:  
## List the dictionaries available  
dictionaries <- getDictionaries("https://labbcat.canterbury.ac.nz/demo/")  
  
## End(Not run)
```

getDictionaryEntries *Lookup entries in a dictionary.*

Description

Lookup entries in a dictionary.

Usage

```
getDictionaryEntries(labbcat.url, managerId, dictionaryId, keys)
```

Arguments

labbcat.url	URL to the LaBB-CAT instance
managerId	The layer manager ID of the dictionary, as returned by getDictionaries
dictionaryId	The ID of the dictionary, as returned by getDictionaries
keys	A list of entries to look up

Value

A data frame with the keys and their dictionary entries.

See Also

[getDictionaries](#)

Examples

```
## Not run:  
## define the LaBB-CAT URL  
labbcat.url <- "https://labbcat.canterbury.ac.nz/demo/"  
  
keys <- c("the", "quick", "brown", "fox")  
  
## get the pronunciations according to CELEX  
entries <- getDictionaryEntries(labbcat.url, "CELEX-EN", "Phonology (wordform)", keys)  
  
## End(Not run)
```

getFragments	<i>Gets fragments of annotation transcript from 'LaBB-CAT', converted to a given format (by default, Praat TextGrid)</i>
--------------	--

Description

Gets fragments of annotation transcript from 'LaBB-CAT', converted to a given format (by default, Praat TextGrid)

Usage

```
getFragments(
  labbcats.url,
  id,
  start,
  end,
  layerIds,
  mimeType = "text/praat-textgrid",
  no.progress = FALSE,
  path = ""
)
```

Arguments

labbcats.url	URL to the LaBB-CAT instance
id	The transcript ID (transcript name) of the sound recording, or a vector of transcript IDs.
start	The start time in seconds, or a vector of start times.
end	The end time in seconds, or a vector of end times.
layerIds	A vector of layer IDs.
mimeType	Optional content-type - currently only "text/praat-textgrid" is supported.
no.progress	Optionally suppress the progress bar when multiple fragments are specified - TRUE for no progress bar.
path	Optional path to directory where the files should be saved.

Value

The name of the file, which is saved in the current directory, or a list of names of files, if multiple id's/start's/end's were specified

If a list of files is returned, they are in the order that they were returned by the server, which *should* be the order that they were specified in the id/start/end lists.

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## Get the 5 seconds starting from 10s after the beginning of a recording
textgrid.files <- getFragments(labbcats.url, "AP2505_Nelson.eaf", 10.0, 15.0,
  c("transcript", "phonemes"), path="samples")

## Load some search results previously exported from LaBB-CAT
results <- read.csv("results.csv", header=T)

## Get a list of fragment TextGrids, including the utterances, transcript, and phonemes layers
textgrid.files <- getFragments(
  labbcats.url, results$Transcript, results$Line, results$LineEnd,
  c("utterances", "transcript", "phonemes"))

## Get a list of fragment TextGrids with no progress bar
textgrid.files <- getFragments(
  labbcats.url, results$Transcript, results$Line, results$LineEnd, no.progress=TRUE)

## End(Not run)
```

getGraphIds

Deprecated synonym for getTranscriptIds.

Description

Returns a list of graph IDs (i.e. transcript names).

Usage

```
getGraphIds(labbcats.url)
```

Arguments

labbcats.url URL to the LaBB-CAT instance

Value

A list of graph IDs

See Also

[getTranscriptIds](#)

Examples

```
## Not run:  
## List all transcripts  
transcripts <- getGraphIds("https://labbcats.canterbury.ac.nz/demo/")  
  
## End(Not run)
```

`getGraphIdsInCorpus` *Deprecated synonym for `getTranscriptIdsInCorpus`.*

Description

Returns a list of corpora in the given 'LaBB-CAT' instance.

Usage

```
getGraphIdsInCorpus(labbcats.url, id)
```

Arguments

<code>labbcats.url</code>	URL to the LaBB-CAT instance
<code>id</code>	The ID (name) of the corpus

Value

A list of corpus IDs

See Also

[getGraphIdsInCorpus](#)

Examples

```
## Not run:  
## List transcripts in the QB corpus  
transcripts <- getGraphIdsInCorpus("https://labbcats.canterbury.ac.nz/demo/", "QB")  
  
## End(Not run)
```

getGraphIdsWithParticipant

Deprecated synonym for getTranscriptIdsWithParticipant.

Description

Returns a list of IDs of graphs (i.e. transcript names) that include the given participant.

Usage

```
getGraphIdsWithParticipant(labbcats.url, id)
```

Arguments

labbcats.url	URL to the LaBB-CAT instance
id	A participant ID

Value

A list of graph IDs

See Also

[getTranscriptIdsWithParticipant](#)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## List transcripts in which UC427_ViktoriaPapp_A_ENG speaks
transcripts <- getGraphIdsWithParticipant(labbcats.url, "UC427_ViktoriaPapp_A_ENG")

## End(Not run)
```

getId

Gets the store's ID.

Description

The store's ID - i.e. the ID of the 'LaBB-CAT' instance.

Usage

```
getId(labbcats.url)
```

Arguments

labbcat.url URL to the LaBB-CAT instance

Value

The annotation store's ID

Examples

```
## Not run:
## Get ID of LaBB-CAT instance
instance.id <- getId("https://labbcat.canterbury.ac.nz/demo/")

## End(Not run)
```

getLayer	<i>Gets a layer definition.</i>
----------	---------------------------------

Description

Gets a layer definition.

Usage

```
getLayer(labbcat.url, id)
```

Arguments

labbcat.url URL to the LaBB-CAT instance
id ID of the layer to get the definition for

Value

The definition of the given layer, with members:

- *id* The layer's unique ID
- *parentId* The layer's parent layer ID
- *description* The description of the layer
- *alignment* The layer's alignment - 0 for none, 1 for point alignment, 2 for interval alignment
- *peers* Whether children have peers or not
- *peersOverlap* Whether child peers can overlap or not
- *parentIncludes* Whether the parent t-includes the child
- *saturated* Whether children must temporally fill the entire parent duration (true) or not (false)
- *parentIncludes* Whether the parent t-includes the child
- *type* The type for labels on this layer
- *validLabels* List of valid label values for this layer

See Also

[getLayerIds](#) [getLayers](#)

Examples

```
## Not run:  
## Get the definition of the orthography layer  
orthography.layer <- getLayer("https://labbcat.canterbury.ac.nz/demo/", "orthography")  
  
## End(Not run)
```

getLayerIds	<i>Gets a list of layer IDs.</i>
-------------	----------------------------------

Description

Layer IDs are annotation 'types'.

Usage

```
getLayerIds(labbcat.url)
```

Arguments

labbcat.url URL to the LaBB-CAT instance

Value

A list of layer IDs

Examples

```
## Not run:  
## Get names of all layers  
layer.ids <- getLayerIds("https://labbcat.canterbury.ac.nz/demo/")  
  
## End(Not run)
```

getLayers	<i>Gets a list of layer definitions.</i>
-----------	--

Description

Gets a list of layer definitions.

Usage

```
getLayers(labbcat.url)
```

Arguments

labbcat.url URL to the LaBB-CAT instance

Value

A list of layer definitions, with members:

- *id* The layer's unique ID
- *parentId* The layer's parent layer ID
- *description* The description of the layer
- *alignment* The layer's alignment - 0 for none, 1 for point alignment, 2 for interval alignment
- *peers* Whether children have peers or not
- *peersOverlap* Whether child peers can overlap or not
- *parentIncludes* Whether the parent t-includes the child
- *saturated* Whether children must temporally fill the entire parent duration (true) or not (false)
- *parentIncludes* Whether the parent t-includes the child
- *type* The type for labels on this layer
- *validLabels* List of valid label values for this layer

See Also

[getLayerIds](#)

Examples

```
## Not run:  
## Get definitions of all layers  
layers <- getLayers("https://labbcat.canterbury.ac.nz/demo/")  
  
## End(Not run)
```

getMatches	<i>Search for tokens.</i>
------------	---------------------------

Description

Searches through transcripts for tokens matching the given pattern.

Usage

```
getMatches(
  labbcat.url,
  pattern,
  participant.ids = NULL,
  transcript.types = NULL,
  main.participant = TRUE,
  aligned = FALSE,
  matches.per.transcript = NULL,
  words.context = 0,
  max.matches = NULL,
  no.progress = FALSE
)
```

Arguments

labbcat.url	URL to the LaBB-CAT instance
pattern	<p>An object representing the pattern to search for.</p> <p>Strictly speaking, this should be a named list that replicates the structure of the ‘search matrix’ in the LaBB-CAT browser interface, with one element called “columns”, containing a named list for each column.</p> <p>Each element in the “columns” named list contains an element named “layers”, whose value is a named list for patterns to match on each layer, and optionally an element named “adj”, whose value is a number representing the maximum distance, in tokens, between this column and the next column - if “adj” is not specified, the value defaults to 1, so tokens are contiguous.</p> <p>Each element in the “layers” named list is named after the layer it matches, and the value is a named list with the following possible elements:</p> <ul style="list-style-type: none"> • <i>pattern</i> A regular expression to match against the label • <i>min</i> An inclusive minimum numeric value for the label • <i>max</i> An exclusive maximum numeric value for the label • <i>not</i> TRUE to negate the match • <i>anchorStart</i> TRUE to anchor to the start of the annotation on this layer (i.e. the matching word token will be the first at/after the start of the matching annotation on this layer) • <i>anchorEnd</i> TRUE to anchor to the end of the annotation on this layer (i.e. the matching word token will be the last before/at the end of the matching annotation on this layer)

- *target* TRUE to make this layer the target of the search; the results will contain one row for each match on the target layer

Examples of valid pattern objects include:

```
## words starting with 'ps...'
pattern <- list(columns = list(
  list(layers = list(
    orthography = list(pattern = "ps.*")))))

## the word 'the' followed immediately or with one intervening word by
## a hapax legomenon (word with a frequency of 1) that doesn't start with a vowel
pattern <- list(columns = list(
  list(layers = list(
    orthography = list(pattern = "the"),
    adj = 2),
  list(layers = list(
    phonemes = list(not = TRUE, pattern = "[cCEFHiIPqQuUV0123456789~#$@].*"),
    frequency = list(max = "2")))))
```

For ease of use, the function will also accept the following abbreviated forms:

```
## a single list representing a 'one column' search,
## and string values, representing regular expression pattern matching
pattern <- list(orthography = "ps.*")

## a list containing the columns (adj defaults to 1, so matching tokens are contiguous).
pattern <- list(
  list(orthography = "the"),
  list(phonemes = list(not = TRUE, pattern = "[cCEFHiIPqQuUV0123456789~#$@].*"),
    frequency = list(max = "2")))
```

`participant.ids`

An optional list of participant IDs to search the utterances of. If not supplied, all utterances in the corpus will be searched.

`transcript.types`

An optional list of transcript types to limit the results to. If null, all transcript types will be searched.

`main.participant`

TRUE to search only main-participant utterances, FALSE to search all utterances.

`aligned`

true to include only words that are aligned (i.e. have anchor confidence \geq 50, false to search include un-aligned words as well.

`matches.per.transcript`

Optional maximum number of matches per transcript to return. NULL means all matches.

`words.context`

Number of words context to include in the 'Before.Match' and 'After.Match' columns in the results.

`max.matches`

The maximum number of matches to return, or null to return all.

`no.progress`

Optionally suppress the progress bar when multiple fragments are specified - TRUE for no progress bar.

Value

A data frame identifying matches, containing the following columns:

- *SearchName* A name based on the pattern – the same for all rows
- *Number* Row number
- *Transcript* Name of the transcript in which the match was found
- *Line* The start offset of the utterance/line
- *LineEnd* The end offset of the utterance/line
- *MatchId* A unique ID for the matching target token
- *Before.Match* Transcript text immediately before the match
- *Text* Transcript text of the match
- *After.Match* Transcript text immediately after the match
- *Target.transcript* Text of the target word token
- *Target.transcript.start* Start offset of the target word token
- *Target.transcript.end* End offset of the target word token
- *Target.segments* Label of the target segment (only present if the segment layer is included in the pattern)
- *Target.segments.start* Start offset of the target segment (only present if the segment layer is included in the pattern)
- *Target.segments.end* End offset of the target segment (only present if the segment layer is included in the pattern)

See Also

[getParticipantIds](#)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## create a pattern object to match against
pattern <- list(columns = list(
  list(layers = list(
    orthography = list(pattern = "the"),
    adj = 2),
  list(layers = list(
    phonemes = list(not=TRUE, pattern = "[cCEFHhIPqQuUV0123456789~#\$\@].*"),
    frequency = list(max = "2")))))

## get the tokens matching the pattern
results <- getMatches(labbcats.url, pattern)

## results$MatchId can be used to access results

## End(Not run)
```

getMatchingGraphIds *Deprecated synonym for getMatchingTranscriptIds.*

Description

Gets a list of IDs of graphs (i.e. transcript names) that match a particular pattern.

Usage

```
getMatchingGraphIds(  
  labbcats.url,  
  expression,  
  pageLength = NULL,  
  pageNumber = NULL,  
  order = NULL  
)
```

Arguments

labbcats.url	URL to the LaBB-CAT instance
expression	An expression that determines which graphs match
pageLength	The maximum number of IDs to return, or null to return all
pageNumber	The zero-based page number to return, or null to return the first page
order	An expression that determines the order the graphs are listed in - if specified, this must include the keyword 'ASC' for ascending or 'DESC' for descending order.

Details

The results can be exhaustive, by omitting pageLength and pageNumber, or they can be a subset (a 'page') of results, by given pageLength and pageNumber values.

The order of the list can be specified. If omitted, the graphs are listed in ID order.

The expression language is currently not well defined, but expressions such as those in the examples can be used.

Value

A list of graph IDs (i.e. transcript names)

Examples

```
## Not run:  
## define the LaBB-CAT URL  
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"  
  
## Get all transcripts whose names start with "BR"
```

```

transcripts <- getMatchingGraphIds(labbcat.url, "id MATCHES 'BR.+")

## Get the first twenty transcripts in the "QB" corpus
transcripts <- getMatchingGraphIds(
  labbcat.url, "my('corpus').label = 'QB'", 20, 0)

## Get the second transcript that has "QB247_Jacqui" as a speaker
transcripts <- getMatchingGraphIds(
  labbcat.url, "'QB247_Jacqui' IN labels('participant')", 1, 1)

## Get all transcripts whose names start with "BR" and have "QB247_Jacqui" as a speaker,
## in word-count order
transcripts <- getMatchingGraphIds(
  labbcat.url, "my('corpus').label = 'QB' AND 'QB247_Jacqui' IN labels('participant')", 1, 1,
  "my('transcript_word_count').label ASC")

## End(Not run)

```

```
getMatchingTranscriptIds
```

Gets a list of IDs of transcripts that match a particular pattern.

Description

Gets a list of IDs of transcripts (i.e. transcript names) that match a particular pattern.

Usage

```

getMatchingTranscriptIds(
  labbcat.url,
  expression,
  pageLength = NULL,
  pageNumber = NULL,
  order = NULL
)

```

Arguments

<code>labbcat.url</code>	URL to the LaBB-CAT instance
<code>expression</code>	An expression that determines which transcripts match
<code>pageLength</code>	The maximum number of IDs to return, or null to return all
<code>pageNumber</code>	The zero-based page number to return, or null to return the first page
<code>order</code>	An expression that determines the order the transcripts are listed in - if specified, this must include the keyword 'ASC' for ascending or 'DESC' for descending order.

Details

The results can be exhaustive, by omitting `pageLength` and `pageNumber`, or they can be a subset (a 'page') of results, by given `pageLength` and `pageNumber` values.

The order of the list can be specified. If omitted, the transcripts are listed in ID order.

The expression language is currently not well defined, but expressions such as those in the examples can be used.

Value

A list of transcript IDs (i.e. transcript names)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## Get all transcripts whose names start with "BR"
transcripts <- getMatchingTranscriptIds(labbcats.url, "id MATCHES 'BR.+")

## Get the first twenty transcripts in the "QB" corpus
transcripts <- getMatchingTranscriptIds(
  labbcats.url, "my('corpus').label = 'QB'", 20, 0)

## Get the second transcript that has "QB247_Jacqui" as a speaker
transcripts <- getMatchingTranscriptIds(
  labbcats.url, "'QB247_Jacqui' IN labels('participant')", 1, 1)

## Get all transcripts whose names start with "BR" and have "QB247_Jacqui" as a speaker,
## in word-count order
transcripts <- getMatchingTranscriptIds(
  labbcats.url, "my('corpus').label = 'QB' AND 'QB247_Jacqui' IN labels('participant')", 1, 1,
  "my('transcript_word_count').label ASC")

## End(Not run)
```

getMatchLabels

Gets labels of annotations on a given layer, identified by given match IDs.

Description

Gets labels of annotations on a given layer, identified by given match IDs.

Usage

```
getMatchLabels(
  labbcats.url,
  matchIds,
  layerIds,
  targetOffset = 0,
  annotationsPerLayer = 1
)
```

Arguments

labbcats.url	URL to the LaBB-CAT instance
matchIds	A vector of annotation IDs, e.g. the MatchId column, or the URL column, of a results set.
layerIds	A vector of layer IDs.
targetOffset	The distance from the original target of the match, e.g. <ul style="list-style-type: none"> • 0 – find annotations of the match target itself, • 1 – find annotations of the token immediately <i>after</i> match target • -1 – find annotations of the token immediately <i>before</i> match target
annotationsPerLayer	The number of annotations on the given layer to retrieve. In most cases, there's only one annotation available. However, tokens may, for example, be annotated with 'all possible phonemic transcriptions', in which case using a value of greater than 1 for this parameter provides other phonemic transcriptions, for tokens that have more than one.

Value

A data frame of labels.

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## Perform a search
results <- getMatches(labbcats.url, list(orthography="quake"))

## Get the topic annotations for the matches
topics <- getAnnotationLabels(labbcats.url, results$MatchId, "topic")

## End(Not run)
```

getMedia	<i>Gets a given media track for a given transcript.</i>
----------	---

Description

Gets a given media track for a given transcript.

Usage

```
getMedia(labbcat.url, id, trackSuffix = "", mimeType = "audio/wav")
```

Arguments

labbcat.url	URL to the LaBB-CAT instance
id	A transcript ID (i.e. transcript name)
trackSuffix	The track suffix of the media
mimeType	The MIME type of the media

Value

A URL to the given media for the given transcript

See Also

[getTranscriptIds](#)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcat.url <- "https://labbcat.canterbury.ac.nz/demo/"

## Get URL for the WAV file for BR2044_OllyOhlson.eaf
media <- getMedia(labbcat.url, "BR2044_OllyOhlson.eaf")

## Get URL for the 'QuakeFace' video file for BR2044_OllyOhlson.eaf
media <- getMedia(labbcat.url, "BR2044_OllyOhlson.eaf", "_face", "video/mp4")

## End(Not run)
```

getMediaTracks *List the predefined media tracks available for transcripts.*

Description

List the predefined media tracks available for transcripts.

Usage

```
getMediaTracks(labbcat.url)
```

Arguments

labbcat.url URL to the LaBB-CAT instance

Value

A list of media track definitions.

Examples

```
## Not run:
## Get the media tracks configured in LaBB-CAT
tracks <- getMediaTracks("https://labbcat.canterbury.ac.nz/demo/")

## End(Not run)
```

getParticipantAttributes
Gets participant attribute values for given participant IDs.

Description

Gets participant attribute values for given participant IDs.

Usage

```
getParticipantAttributes(labbcat.url, participantIds, layerIds)
```

Arguments

labbcat.url URL to the LaBB-CAT instance
participantIds A vector of participant IDs
layerIds A vector of layer IDs corresponding to participant attributes. In general, these are layers whose ID is prefixed 'participant_', however formally it's any layer where layer\$parentId == 'participant' && layer\$alignment == 0.

Value

A data frame of attribute value labels.

Examples

```
## Not run:  
## define the LaBB-CAT URL  
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"  
  
## Get gender and age for all participants  
attributes <- getParticipantAttributes(labbcats.url,  
  getParticipantIds(labbcats.url),  
  c('participant_gender', 'participant_age'))  
  
## End(Not run)
```

`getParticipantIds` *Gets a list of participant IDs.*

Description

Returns a list of participant IDs.

Usage

```
getParticipantIds(labbcats.url)
```

Arguments

`labbcats.url` URL to the LaBB-CAT instance

Value

A list of participant IDs

Examples

```
## Not run:  
## List all speakers  
speakers <- getParticipantIds("https://labbcats.canterbury.ac.nz/demo/")  
  
## End(Not run)
```

getSoundFragments *Gets sound fragments from 'LaBB-CAT'.*

Description

Gets sound fragments from 'LaBB-CAT'.

Usage

```
getSoundFragments(
  labbcat.url,
  ids,
  startOffsets,
  endOffsets,
  sampleRate = NULL,
  no.progress = FALSE,
  path = ""
)
```

Arguments

labbcat.url	URL to the LaBB-CAT instance
ids	The transcript ID (transcript name) of the sound recording, or a vector of transcript IDs.
startOffsets	The start time in seconds, or a vector of start times.
endOffsets	The end time in seconds, or a vector of end times.
sampleRate	Optional sample rate in Hz - if a positive integer, then the result is a mono file with the given sample rate.
no.progress	Optionally suppress the progress bar when multiple fragments are specified - TRUE for no progress bar.
path	Optional path to directory where the files should be saved.

Value

The name of the file, which is saved in the current directory, or a list of names of files, if multiple id's/start's/end's were specified

If a list of files is returned, they are in the order that they were returned by the server, which *should* be the order that they were specified in the id/start/end lists.

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcat.url <- "https://labbcat.canterbury.ac.nz/demo/"

## Get the 5 seconds starting from 10s after the beginning of a recording
```

```
wav.file <- getSoundFragments(labbcats.url, "AP2505_Nelson.eaf", 10.0, 15.0, path="samples")

## Get the 5 seconds starting from 10s as a mono 22kHz file
wav.file <- getSoundFragments(labbcats.url, "AP2505_Nelson.eaf", 10.0, 15.0, 22050)

## Load some search results previously exported from LaBB-CAT
results <- read.csv("results.csv", header=T)

## Get a list of fragments
wav.files <- getSoundFragments(labbcats.url, results$Transcript, results$Line, results$LineEnd)

## Get a list of fragments with no progress bar
wav.file <- getSoundFragments(
  labbcats.url, results$Transcript, results$Line, results$LineEnd, no.progress=TRUE)

## End(Not run)
```

getTranscriptAttributes

Gets transcript attribute values for given transcript IDs.

Description

Gets transcript attribute values for given transcript IDs.

Usage

```
getTranscriptAttributes(labbcats.url, transcriptIds, layerIds)
```

Arguments

labbcats.url	URL to the LaBB-CAT instance
transcriptIds	A vector of transcript IDs
layerIds	A vector of layer IDs corresponding to transcript attributes. In general, these are layers whose ID is prefixed 'transcript_', however formally it's any layer where layer\$parentId == 'graph' && layer\$alignment == 0, which includes 'corpus' as well as transcript attribute layers.

Value

A data frame of attribute value labels.

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## Get language, duration, and corpus for transcripts starting with 'BR'
```

```
attributes <- getTranscriptAttributes(labbcat.url,  
  getMatchingTranscriptIds(labbcat.url, "id MATCHES 'BR.+')"),  
  c('transcript_language', 'transcript_duration', 'corpus'))  
  
## End(Not run)
```

`getTranscriptIds` *Gets a list of transcript IDs.*

Description

Returns a list of transcript IDs (i.e. transcript names).

Usage

```
getTranscriptIds(labbcat.url)
```

Arguments

`labbcat.url` URL to the LaBB-CAT instance

Value

A list of transcript IDs

Examples

```
## Not run:  
## List all transcripts  
transcripts <- getTranscriptIds("https://labbcat.canterbury.ac.nz/demo/")  
  
## End(Not run)
```

`getTranscriptIdsInCorpus`
Gets a list of transcript in a corpus.

Description

Returns a list of transcript IDs in the given corpus.

Usage

```
getTranscriptIdsInCorpus(labbcat.url, id)
```

Arguments

labbcats.url URL to the LaBB-CAT instance
id The ID (name) of the corpus

Value

A list of transcript IDs

Examples

```
## Not run:  
## List transcripts in the QB corpus  
transcripts <- getTranscriptIdsInCorpus("https://labbcats.canterbury.ac.nz/demo/", "QB")  
  
## End(Not run)
```

`getTranscriptIdsWithParticipant`

Gets a list of IDs of transcripts that include the given participant.

Description

Returns a list of IDs of transcripts (i.e. transcript names) that include the given participant.

Usage

```
getTranscriptIdsWithParticipant(labbcats.url, id)
```

Arguments

labbcats.url URL to the LaBB-CAT instance
id A participant ID

Value

A list of transcript IDs

See Also

[getParticipantIds](#)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcata.url <- "https://labbcata.canterbury.ac.nz/demo/"

## List transcripts in which UC427_ViktoriaPapp_A_ENG speaks
transcripts <- getTranscriptIdsWithParticipant(labbcata.url, "UC427_ViktoriaPapp_A_ENG")

## End(Not run)
```

labbcataCredentials	<i>Sets the username and password that the package should use for connecting to a given LaBB-CAT server in future function calls.</i>
---------------------	---

Description

This step is optional, as all functions will prompt the user for the username and password if required. If the script is running in RStudio, then the RStudio password input dialog is used, hiding the credentials from view. Otherwise, the console is used, and credentials are visible.

Usage

```
labbcataCredentials(labbcata.url, username, password)
```

Arguments

labbcata.url	URL to the LaBB-CAT instance
username	The LaBB-CAT username, if it is password-protected
password	The LaBB-CAT password, if it is password-protected

Details

The recommended approach is to *not* use labbcataCredentials, to avoid saving user credentials in script files that may eventually become visible to other. Use labbcataCredentials *only* in cases where the script execution is unsupervised.

Value

NULL if the username/password are correct, and a string describing the problem if a problem occurred, e.g. "Credentials rejected" if the username/password are incorrect, or a string starting "Version mismatch" if the server's version of LaBB-CAT is lower than the minimum required.

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcac.url <- "https://labbcac.canterbury.ac.nz/demo/"

## specify the username/password in the script
## (only use labbcacCredentials for scripts that must execute unsupervised!)
labbcacCredentials(labbcac.url, "demo", "demo")

## End(Not run)
```

labbcacTimeout	<i>Sets the timeout for request to the LaBB-CAT server in future function calls. The default timeout is 10 seconds.</i>
----------------	---

Description

Sets the timeout for request to the LaBB-CAT server in future function calls. The default timeout is 10 seconds.

Usage

```
labbcacTimeout(seconds = NULL)
```

Arguments

seconds The number of seconds before requests return with a timeout error.

Value

The request timeout in seconds

Examples

```
## Not run:
## the request timeout
labbcacTimeout(30)

## End(Not run)
```

nzilbb.labbcats

*Accessing Data Stored in 'LaBB-CAT' Instances***Description**

'LaBB-CAT' is a web-based language corpus management system developed by the New Zealand Institute of Language, Brain and Behaviour (NZILBB) - see <<https://labbcats.canterbury.ac.nz>>. This package defines functions for accessing corpus data in a 'LaBB-CAT' instance. You must have at least version 20200608.1507 of 'LaBB-CAT' to use this package. For more information about 'LaBB-CAT', see Robert Fromont and Jennifer Hay (2008) <[doi:10.3366/E1749503208000142](https://doi.org/10.3366/E1749503208000142)> or Robert Fromont (2017) <[doi:10.1016/j.csl.2017.01.004](https://doi.org/10.1016/j.csl.2017.01.004)>.

Details

Package: nzilbb.labbcats
 Version: 0.5-1
 Date: 2020-06-08
 Title: Accessing Data Stored in 'LaBB-CAT' Instances
 Authors@R: c(person("Robert", "Fromont", role = c("aut", "cre"), email = "robert@fromont.net.nz"))
 Imports: jsonlite, httr, stringr, utils, rstudioapi
 Description: 'LaBB-CAT' is a web-based language corpus management system developed by the New Zealand Institute of Language, Brain and Behaviour (NZILBB) - see <<https://labbcats.canterbury.ac.nz>>. This package defines functions for accessing corpus data in a 'LaBB-CAT' instance. You must have at least version 20200608.1507 of 'LaBB-CAT' to use this package. For more information about 'LaBB-CAT', see Robert Fromont and Jennifer Hay (2008) <[doi:10.3366/E1749503208000142](https://doi.org/10.3366/E1749503208000142)> or Robert Fromont (2017) <[doi:10.1016/j.csl.2017.01.004](https://doi.org/10.1016/j.csl.2017.01.004)>.
 License: GPL (>= 3)
 Copyright: New Zealand Institute of Language, Brain and Behaviour, University of Canterbury
 URL: <https://github.com/nzilbb/labbcats-R>, <https://labbcats.canterbury.ac.nz>
 RoxygenNote: 7.0.2
 Suggests: testthat (>= 2.1.0)
 Author: Robert Fromont [aut, cre]
 Maintainer: Robert Fromont <robert@fromont.net.nz>

Index of help topics:

countAnnotations	Gets the number of annotations on the given layer of the given transcript.
getAnchors	Gets the given anchors in the given transcript.
getAnnotations	Gets the annotations on the given layer of the given transcript.
getAvailableMedia	List the media available for the given transcript.
getCorpusIds	Gets a list of corpus IDs.
getDictionaries	List the dictionaries available.
getDictionaryEntries	Lookup entries in a dictionary.
getFragments	Gets fragments of annotation transcript from 'LaBB-CAT', converted to a given format (by default, Praat TextGrid)
getGraphIds	Deprecated synonym for getTranscriptIds.

getGraphIdsInCorpus	Deprecated synonym for getTranscriptIdsInCorpus.
getGraphIdsWithParticipant	Deprecated synonym for getTranscriptIdsWithParticipant.
getId	Gets the store's ID.
getLayer	Gets a layer definition.
getLayerIds	Gets a list of layer IDs.
getLayers	Gets a list of layer definitions.
getMatchLabels	Gets labels of annotations on a given layer, identified by given match IDs.
getMatches	Search for tokens.
getMatchingGraphIds	Deprecated synonym for getMatchingTranscriptIds.
getMatchingTranscriptIds	Gets a list of IDs of transcripts that match a particular pattern.
getMedia	Gets a given media track for a given transcript.
getMediaTracks	List the predefined media tracks available for transcripts.
getParticipantAttributes	Gets participant attribute values for given participant IDs.
getParticipantIds	Gets a list of participant IDs.
getSoundFragments	Gets sound fragments from 'LaBB-CAT'.
getTranscriptAttributes	Gets transcript attribute values for given transcript IDs.
getTranscriptIds	Gets a list of transcript IDs.
getTranscriptIdsInCorpus	Gets a list of transcript in a corpus.
getTranscriptIdsWithParticipant	Gets a list of IDs of transcripts that include the given participant.
labbcatsCredentials	Sets the username and password that the package should use for connecting to a given LaBB-CAT server in future function calls.
labbcatsTimeout	Sets the timeout for request to the LaBB-CAT server in future function calls. The default timeout is 10 seconds.
nzilbb.labbcats	Accessing Data Stored in 'LaBB-CAT' Instances
praatscriptCentreOfGravity	Generates a script for extracting the CoG, for use with processWithPraat.
praatscriptFormants	Generates a script for extracting formants, for use with processWithPraat.
praatscriptIntensity	Generates a script for extracting maximum

intensity, for use with processWithPraat.
 praatScriptPitch Generates a script for extracting pitch, for
 use with processWithPraat.
 processWithPraat Process a set of intervals with Praat.

'LaBB-CAT' is a web-based language corpus management system and this package provides access to data stored in a 'LaBB-CAT' instance. You must have at least version 20200608.1507 of 'LaBB-CAT' to use this package.

Author(s)

NA

References

Robert Fromont and Jennifer Hay, "ONZE Miner: the development of a browser-based research tool", 2008 Robert Fromont, "Toward a format-neutral annotation store", 2017

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## Perform a search
results <- getMatches(labbcats.url, list(segments="I"))

## Get the phonemic transcriptions for the matches
phonemes <- getMatchLabels(labbcats.url, results$MatchId, "phonemes")

## Get sound fragments for the matches
wav.files <- getSoundFragments(labbcats.url, results$Transcript, results$Line, results$LineEnd)

## End(Not run)
```

```
praatScriptCentreOfGravity
```

Generates a script for extracting the CoG, for use with [processWithPraat](#).

Description

This function generates a Praat script fragment which can be passed as the praat.script parameter of [processWithPraat](#), in order to extract one or more spectral centre of gravity (CoG) measurements.

Usage

```
praatScriptCentreOfGravity(powers = c(2), spectrum.fast = TRUE)
```

Arguments

`powers` A vector of numbers specifying which powers to query for to extract, e.g. `c(1.0,2.0)`.
`spectrum.fast` Whether to use the 'fast' option when creating the spectrum object to query .

Value

A script fragment which can be passed as the `praat.script` parameter of [processWithPraat](#)

See Also

[processWithPraat](#)
[praatScriptFormants](#)
[praatScriptIntensity](#)
[praatScriptPitch](#)

Examples

```
## Not run:  
## define the LaBB-CAT URL  
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"  
  
## Perform a search  
results <- getMatches(labbcats.url, list(segments="I"))  
  
## Get a list of fragments with no progress bar  
wav.file <- processWithPraat(  
  labbcats.url,  
  results$MatchId, results$Target.segments.start, results$Target.segments.end,  
  praatScriptCentreOfGravity(powers=c(1.0,2.0)),  
  no.progress=TRUE)  
  
## End(Not run)
```

`praatScriptFormants` *Generates a script for extracting formants, for use with [processWithPraat](#).*

Description

This function generates a Praat script fragment which can be passed as the `praat.script` parameter of [processWithPraat](#), in order to extract selected formants.

Usage

```

praatScriptFormants(
  formants = c(1, 2),
  sample.points = c(0.5),
  time.step = 0,
  max.number.formants = 5,
  max.formant = 5500,
  max.formant.male = 5000,
  gender.attribute = "participant_gender",
  value.for.male = "M",
  window.length = 0.025,
  preemphasis.from = 50
)

```

Arguments

<code>formants</code>	A vector of integers specifying which formants to extract, e.g <code>c(1,2)</code> for the first and second formant.
<code>sample.points</code>	A vector of numbers ($0 \leq \text{sample.points} \leq 1$) specifying multiple points at which to take the measurement. The default is a single point at 0.5 - this means one measurement will be taken halfway through the target interval. If, for example, you wanted eleven measurements evenly spaced throughout the interval, you would specify <code>sample.points</code> as being <code>c(0.0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0)</code> .
<code>time.step</code>	Time step in seconds, or 0.0 for 'auto'.
<code>max.number.formants</code>	Maximum number of formants.
<code>max.formant</code>	Maximum formant value (Hz) for all speakers, or for female speakers, if <code>max.formant.male</code> is also specified.
<code>max.formant.male</code>	Maximum formant value (Hz) for male speakers, or NULL to use the same value as <code>max.formant</code> .
<code>gender.attribute</code>	Name of the LaBB-CAT participant attribute that contains the participant's gender - normally this is "participant_gender".
<code>value.for.male</code>	The value that the <code>gender.attribute</code> has when the participant is male.
<code>window.length</code>	Window length in seconds.
<code>preemphasis.from</code>	Pre-emphasis from (Hz)

Value

A script fragment which can be passed as the `praat.script` parameter of [processWithPraat](#)

See Also

[processWithPraat](#)
[praatScriptCentreOfGravity](#)
[praatScriptIntensity](#)
[praatScriptPitch](#)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## Perform a search
results <- getMatches(labbcats.url, list(segments="I"))

## Get a list of fragments with no progress bar
wav.file <- processWithPraat(
  labbcats.url,
  results$MatchId, results$Target.segments.start, results$Target.segments.end,
  praatScriptFormants(formants=c(1,2,3), sample.points=c(0.25,0.5,0.75)),
  no.progress=TRUE)

## End(Not run)
```

praatScriptIntensity *Generates a script for extracting maximum intensity, for use with [processWithPraat](#).*

Description

This function generates a Praat script fragment which can be passed as the praat.script parameter of [processWithPraat](#), in order to extract maximum intensity value.

Usage

```
praatScriptIntensity(minimum.pitch = 100, time.step = 0, subtract.mean = TRUE)
```

Arguments

minimum.pitch Minimum pitch (Hz).
time.step Time step in seconds, or 0.0 for 'auto'.
subtract.mean Whether to subtract the mean or not.

Value

A script fragment which can be passed as the praat.script parameter of [processWithPraat](#)

See Also

[processWithPraat](#)
[praatScriptFormants](#)
[praatScriptCentreOfGravity](#)
[praatScriptPitch](#)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## Perform a search
results <- getMatches(labbcats.url, list(segments="I"))

## Get a list of fragments with no progress bar
wav.file <- processWithPraat(
  labbcats.url,
  results$MatchId, results$Target.segments.start, results$Target.segments.end,
  praatScriptIntensity(),
  no.progress=TRUE)

## End(Not run)
```

praatScriptPitch *Generates a script for extracting pitch, for use with [processWithPraat](#).*

Description

This function generates a Praat script fragment which can be passed as the praat.script parameter of [processWithPraat](#), in order to extract pitch information.

Usage

```
praatScriptPitch(
  get.mean = TRUE,
  get.minimum = FALSE,
  get.maximum = FALSE,
  time.step = 0,
  pitch.floor = 60,
  max.number.of.candidates = 15,
  very.accurate = FALSE,
  silence.threshold = 0.03,
  voicing.threshold = 0.5,
  octave.cost = 0.01,
  octave.jump.cost = 0.35,
  voiced.unvoiced.cost = 0.35,
```

```

pitch.ceiling = 500,
pitch.floor.male = 30,
voicing.threshold.male = 0.4,
pitch.ceiling.male = 250,
gender.attribute = "participant_gender",
value.for.male = "M",
window.length = 0.025,
preemphasis.from = 50
)

```

Arguments

<code>get.mean</code>	Extract the mean pitch for the sample.
<code>get.minimum</code>	Extract the minimum pitch for the sample.
<code>get.maximum</code>	Extract the maximum pitch for the sample.
<code>time.step</code>	Step setting for praat command
<code>pitch.floor</code>	Minimum pitch (Hz) for all speakers, or for female speakers, if <code>pitch.floor.male</code> is also specified.
<code>max.number.of.candidates</code>	Maximum number of candidates setting for praat command
<code>very.accurate</code>	Accuracy setting for praat command
<code>silence.threshold</code>	Silence threshold setting for praat command
<code>voicing.threshold</code>	Voicing threshold (Hz) for all speakers, or for female speakers, if <code>voicing.threshold.male</code> is also specified.
<code>octave.cost</code>	Octave cost setting for praat command
<code>octave.jump.cost</code>	Octave jump cost setting for praat command
<code>voiced.unvoiced.cost</code>	Voiced/unvoiced cost setting for praat command
<code>pitch.ceiling</code>	Maximum pitch (Hz) for all speakers, or for female speakers, if <code>pitch.floor.male</code> is also specified.
<code>pitch.floor.male</code>	Minimum pitch (Hz) for male speakers.
<code>voicing.threshold.male</code>	Voicing threshold (Hz) for male speakers.
<code>pitch.ceiling.male</code>	Maximum pitch (Hz) for male speakers.
<code>gender.attribute</code>	Name of the LaBB-CAT participant attribute that contains the participant's gender - normally this is "participant_gender".
<code>value.for.male</code>	The value that the <code>gender.attribute</code> has when the participant is male.
<code>window.length</code>	Window length in seconds.
<code>preemphasis.from</code>	Pre-emphasis from (Hz)

Value

A script fragment which can be passed as the `praat.script` parameter of [processWithPraat](#)

See Also

[processWithPraat](#)
[praatScriptFormants](#)
[praatScriptCentreOfGravity](#)
[praatScriptIntensity](#)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## Perform a search
results <- getMatches(labbcats.url, list(segments="I"))

## Get a list of fragments with no progress bar
wav.file <- processWithPraat(
  labbcats.url,
  results$MatchId, results$Target.segments.start, results$Target.segments.end,
  praatScriptPitch(get.mean=TRUE, get.minimum=TRUE, get.maximum=TRUE),
  no.progress=TRUE)

## End(Not run)
```

<code>processWithPraat</code>	<i>Process a set of intervals with Praat.</i>
-------------------------------	---

Description

This function instructs the LaBB-CAT server to invoke Praat for a set of sound intervals, in order to extract acoustic measures.

Usage

```
processWithPraat(
  labbcats.url,
  matchIds,
  startOffsets,
  endOffsets,
  praat.script,
  window.offset = 0,
  gender.attribute = "participant_gender",
  attributes = NULL,
  no.progress = FALSE
)
```


Arguments

<code>labbcats.url</code>	URL to the LaBB-CAT instance
<code>matchIds</code>	A vector of annotation IDs, e.g. the MatchId column, or the URL column, of a results set.
<code>startOffsets</code>	The start time in seconds, or a vector of start times.
<code>endOffsets</code>	The end time in seconds, or a vector of end times.
<code>praat.script</code>	Script to run on each match. This may be a single string or a character vector.
<code>window.offset</code>	In many circumstances, you will want some context before and after the sample start/end time. For this reason, you can specify a "window offset" - this is a number of seconds to subtract from the sample start and add to the sample end time, before extracting that part of the audio for processing. For example, if the sample starts at 2.0s and ends at 3.0s, and you set the window offset to 0.5s, then Praat will extract a sample of audio from 1.5s to 3.5s, and do the selected processing on that sample.
<code>gender.attribute</code>	Which participant attribute represents the participant's gender.
<code>attributes</code>	Vector of participant attributes to make available to the script. For example, if you want to use different acoustic parameters depending on what the gender of the speaker is, including the "participant_gender" attribute will make a variable called <code>participant_gender\$</code> available to the praat script, whose value will be the gender of the speaker for that segment.
<code>no.progress</code>	Optionally suppress the progress bar when multiple fragments are specified - TRUE for no progress bar.

Details

The exact measurements to return depend on the praat.script that is invoked. This is a Praat script fragment that will run once for each sound interval specified.

There are functions to allow the generation of a number of pre-defined praat scripts for common tasks such as formant, pitch, intensity, and centre of gravity – see [praatScriptFormants](#), [praatScript-CentreOfGravity](#), [praatScriptIntensity](#) and [praatScriptPitch](#).

You can provide your own script, either by building a string with your code, or loading one from a file.

LaBB-CAT prefixes praat.script with code to open a sound file and extract a defined part of it into a Sound object which is then selected.

LaBB-CAT 'Remove's this Sound object after the script finishes executing. Any other objects created by the script must be 'Remove'd before the end of the script (otherwise Praat runs out of memory during very large batches)

LaBB-CAT assumes that all calls to the function 'print' correspond to fields for export and each field must be printed on its own line. Specifically it scans for lines of the form:

```
print 'myOutputVariable' 'newline$'
```

Variables that can be assumed to be already set in the context of the script are:

- `windowOffset` – the value used for the Window Offset; how much context to include.

- *windowAbsoluteStart* – the start time of the window extracted relative to the start of the original audio file.
- *windowAbsoluteEnd* – the end time of the window extracted relative to the start of the original audio file.
- *windowDuration* – the duration of the window extracted (including window offset).
- *targetAbsoluteStart* – the start time of the target interval relative to the start of the original audio file.
- *targetAbsoluteEnd* – the end time of the target interval relative to the start of the original audio file.
- *targetStart* – the start time of the target interval relative to the start of the window extracted.
- *targetEnd* – the end time of the target interval relative to the start of the window extracted.
- *targetDuration* – the duration of the target interval.
- *sampleNumber* – the number of the sample within the set of samples being processed.
- *sampleName\$* – the name of the extracted/selected Sound object.

Value

A data frame of acoustic measures, one row for each matchId.

See Also

[praatScriptFormants](#)

[praatScriptCentreOfGravity](#)

[praatScriptIntensity](#)

[praatScriptPitch](#)

Examples

```
## Not run:
## define the LaBB-CAT URL
labbcats.url <- "https://labbcats.canterbury.ac.nz/demo/"

## Perform a search
results <- getMatches(labbcats.url, list(segments="I"))

## get F1 and F2 for the mid point of the vowel
formants <- processWithPraat(
  labbcats.url,
  results$MatchId, results$Target.segments.start, results$Target.segments.end,
  praatScriptFormants(),
  no.progress=TRUE)

## get first 3 formants at three points during the sample, the mean, min, and max
## pitch, the max intensity, and the CoG using powers 1 and 2
acoustic.measurements <- processWithPraat(
  labbcats.url,
  results$MatchId, results$Target.segments.start, results$Target.segments.end,
```

```
paste(
  praatScriptFormants(c(1,2,3), c(0.25,0.5,0.75)),
  praatScriptPitch(get.mean=TRUE, get.minimum=TRUE, get.maximum=TRUE),
  praatScriptIntensity(),
  praatScriptCentreOfGravity(powers=c(1.0,2.0)),
  window.offset=0.5)

## execute a custom script loaded from a file
acoustic.measurements <- processWithPraat(
  labbcats.url,
  results$MatchId, results$Target.segments.start, results$Target.segments.end,
  readLines("acousticMeasurements.praat"))

## End(Not run)
```

Index

- *Topic **anchor**
 - getAnchors, 3
- *Topic **annotation**
 - getMatchLabels, 21
 - getParticipantAttributes, 24
 - getTranscriptAttributes, 27
- *Topic **audio**
 - getAvailableMedia, 5
 - getMedia, 23
- *Topic **connect**
 - labcatCredentials, 30
 - labcatTimeout, 31
- *Topic **corpora**
 - getCorpusIds, 6
 - getGraphIdsInCorpus, 11
 - getTranscriptIdsInCorpus, 28
- *Topic **corpus**
 - getGraphIdsInCorpus, 11
 - getTranscriptIdsInCorpus, 28
- *Topic **dictionary**
 - getDictionaries, 7
 - getDictionaryEntries, 8
- *Topic **expression**
 - getMatchingGraphIds, 19
 - getMatchingTranscriptIds, 20
- *Topic **fragment**
 - getFragments, 9
 - getSoundFragments, 26
- *Topic **graph**
 - getGraphIdsWithParticipant, 12
 - getMatchingGraphIds, 19
 - getTranscriptIdsWithParticipant, 29
- *Topic **label**
 - getMatchLabels, 21
 - getParticipantAttributes, 24
 - getTranscriptAttributes, 27
- *Topic **layer**
 - getLayer, 13
 - getLayerIds, 14
 - getLayers, 15
 - getMatchLabels, 21
 - getParticipantAttributes, 24
 - getTranscriptAttributes, 27
- *Topic **media**
 - getAvailableMedia, 5
 - getMedia, 23
 - getMediaTracks, 24
- *Topic **package**
 - nzilbb.labcat, 32
- *Topic **participant**
 - getParticipantIds, 25
- *Topic **password**
 - labcatCredentials, 30
 - labcatTimeout, 31
- *Topic **praat**
 - praatScriptCentreOfGravity, 34
 - praatScriptFormants, 35
 - praatScriptIntensity, 37
 - praatScriptPitch, 38
 - processWithPraat, 40
- *Topic **sample**
 - getFragments, 9
 - getSoundFragments, 26
- *Topic **search**
 - getMatches, 16
- *Topic **sound**
 - getFragments, 9
 - getMediaTracks, 24
 - getSoundFragments, 26
- *Topic **speaker**
 - getParticipantIds, 25
- *Topic **timeout**
 - labcatCredentials, 30
 - labcatTimeout, 31
- *Topic **transcript**
 - countAnnotations, 2
 - getAnnotations, 4

- getGraphIds, 10
- getGraphIdsWithParticipant, 12
- getMatchingGraphIds, 19
- getMatchingTranscriptIds, 20
- getTranscriptIds, 28
- getTranscriptIdsWithParticipant, 29
- *Topic **username**
 - labbcacredentials, 30
 - labbcacetimeout, 31
- *Topic **wav**
 - getFragments, 9
 - getSoundFragments, 26
- countAnnotations, 2, 5
- getAnchors, 3
- getAnnotations, 4, 4
- getAvailableMedia, 5
- getCorpusIds, 6
- getDictionaries, 7, 8
- getDictionaryEntries, 7, 8
- getFragments, 9
- getGraphIds, 10
- getGraphIdsInCorpus, 11, 11
- getGraphIdsWithParticipant, 12
- getId, 12
- getLayer, 13
- getLayerIds, 14, 14, 15
- getLayers, 14, 15
- getMatches, 16
- getMatchingGraphIds, 19
- getMatchingTranscriptIds, 20
- getMatchLabels, 21
- getMedia, 23
- getMediaTracks, 24
- getParticipantAttributes, 24
- getParticipantIds, 18, 25, 29
- getSoundFragments, 26
- getTranscriptAttributes, 27
- getTranscriptIds, 3, 5, 6, 10, 23, 28
- getTranscriptIdsInCorpus, 3, 5, 28
- getTranscriptIdsWithParticipant, 3, 5, 12, 29
- labbcacredentials, 30
- labbcacetimeout, 31
- nzilbb.labbcac, 32
- praatScriptCentreOfGravity, 34, 37, 38, 40–42
- praatScriptFormants, 35, 35, 38, 40–42
- praatScriptIntensity, 35, 37, 37, 40–42
- praatScriptPitch, 35, 37, 38, 38, 41, 42
- processWithPraat, 34–38, 40, 40