

Package ‘orders’

May 16, 2019

Type Package

Title Sampling from Order Statistics of New Families of Distributions

Version 0.1.3

Author Carlos Alberto Cardozo Delgado

Maintainer Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>

Description Set of tools to generate samples of order statistics from new families of distributions. The main references for this package are: Gentle, J. (2009), Computational Statistics, Springer-Verlag and Naradajah, S. and Rocha, R. (2016), <DOI:10.18637/jss.v069.i10>. The families of distributions are: Marshall Olkin G distributions, exponentiated G distributions, beta G distributions, gamma G distributions, Kumaraswamy G distributions, generalized beta G distributions, beta extended G distributions, gamma G distributions, gamma uniform G distributions, beta exponential G distributions, Weibull G distributions, log gamma G I distributions, log gamma G II distributions, exponentiated generalized G distributions, exponentiated Kumaraswamy G distributions, geometric exponential Poisson G distributions, truncated-exponential skew-symmetric G distributions, modified beta G distributions, and exponentiated exponential Poisson G distributions.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 6.1.0

Imports Newdistns

NeedsCompilation no

Repository CRAN

Date/Publication 2019-05-16 21:10:04 UTC

R topics documented:

order_beg 2

order_betaexp	3
order_betag	4
order_eepg	5
order_eg	7
order_expg	8
order_expkumg	9
order_gammag	10
order_gammag1	11
order_gammag2	12
order_gbg	13
order_kumg	14
order_loggammag1	16
order_loggammag2	17
order_mbetag	18
order_mog	19
order_tessg	20
order_weibullg	21

Index **23**

order_beg	<i>Random Sampling of Order Statistics from a Beta Extended G Distribution</i>
-----------	--

Description

order_beg is used to obtain a random sample of order statistics from a Beta Extended G Distribution.

Usage

```
order_beg(size, spec, alpha, a, b, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
alpha	numeric, represents the scale parameter. Default value is 1.
a	numeric, represents the first shape parameter. Default value is 1.
b	numeric, represents the second shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Beta Extended G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdists: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Beta Extended Exponential Distribution
order_beg(10, "exp", 1, 1, 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from a Beta Extended Normal Distribution
order_beg(10, "norm", 1, 1, 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from a Beta Extended Log-normal Distribution
order_beg(10, "lnorm", 1, 1, 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from a Beta Extended Chis-square Distribution
order_beg(10, "chisq", 1, 1, 1, k=3, 50, df=3)
```

order_betaexpG	<i>Random Sampling of Order Statistics from a Beta Exponential G Distribution</i>
----------------	---

Description

order_betaexpG is used to obtain a random sample of order statistics from a Beta Exponential G Distribution.

Usage

```
order_betaexpG(size, spec, lambda, a, b, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
lambda	numeric, represents the first shape parameter. Default value is 1.
a	numeric, represents the second shape parameter. Default value is 1.
b	numeric, represents the third shape parameter. Default value is 1.

k numeric, represents the Kth smallest value from a sample.
n numeric, represents the size of the sample to compute the order statistic from.
... represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Beta Exponential G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Beta Exponential Exponential Distribution
order_betaexp(10,"exp",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Beta Exponential Normal Distribution
order_betaexp(10,"norm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Beta Exponential Log-normal Distribution
order_betaexp(10,"lnorm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Beta Exponential Chi-square Distribution
order_betaexp(10,"chisq",1,1,1,k=3,50,df=3)
```

order_betag

Random Sampling of Order Statistics from a Beta G Distribution

Description

order_betag is used to obtain a random sample of order statistics from a Beta G Distribution.

Usage

```
order_betag(size, spec, a, b, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
a	numeric, represents the first shape parameter. Default value is 1.
b	numeric, represents the first shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Beta G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistsn: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Beta Exponential Distribution
order_betag(10,"exp",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Beta Normal Distribution
order_betag(10,"norm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Beta Log-normal Distribution
order_betag(10,"lnorm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Beta Chis-square Distribution
order_betag(10,"chisq",1,1,k=3,50,df=3)
```

order_eepg

Random Sampling of Order Statistics from a Exponentiated Exponential Poisson G Distribution

Description

order_eepg is used to obtain a random sample of order statistics from a Exponentiated Exponential Poisson G Distribution.

Usage

```
order_eepg(size, spec, lambda, a, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
lambda	numeric, represents a scale parameter. Default value is 1.
a	numeric, represents the shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Exponentiated Exponential Poisson G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Exponential Poisson Exponential Distribution
order_eepg(10,"exp",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Exponential Poisson Normal Distribution
order_eepg(10,"norm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Exponential Poisson Log-normal Distribution
order_eepg(10,"lnorm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Exponential Poisson Chi-square Distribution
order_eepg(10,"chisq",1,1,k=3,50,df=3)
```

order_eg	<i>Random Sampling of Order Statistics from a Exponentiated Generalized G Distribution</i>
----------	--

Description

order_eg is used to obtain a random sample of order statistics from a Exponentiated Generalized G Distribution.

Usage

```
order_eg(size, spec, a, b, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
a	numeric, represents the first shape parameter. Default value is 1.
b	numeric, represents the second shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Exponentiated Generalized G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.
 Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Generalized Exponential Distribution
order_eg(10,"exp",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Generalized Normal Distribution
```

```

order_eg(10,"norm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Generalized Log-normal Distribution
order_eg(10,"lnorm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Generalized Chi-square Distribution
order_eg(10,"chisq",1,1,k=3,50,df=3)

```

order_expg	<i>Random Sampling of Order Statistics from a Exponentiated G Distribution</i>
------------	--

Description

order_expg is used to obtain a random sample of order statistics from a Exponentiated G Distribution.

Usage

```
order_expg(size, spec, a, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
a	numeric, represents the first shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Exponentiated G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.
 Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```

library(orders)
# A sample of size 10 of the 3-th order statistics from a Exponentiated Exponential Distribution
order_expg(10,"exp",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Exponentiated Normal Distribution
order_expg(10,"norm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Exponentiated Log-normal Distribution
order_expg(10,"lnorm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Exponentiated Chi-square Distribution
order_expg(10,"chisq",1,k=3,50,df=3)

```

order_expkung	<i>Random Sampling of Order Statistics from a Exponentiated Kumaraswamy G Distribution</i>
---------------	--

Description

order_expkung is used to obtain a random sample of order statistics from a Exponentiated Kumaraswamy G Distribution.

Usage

```
order_expkung(size, spec, a, b, c, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
a	numeric, represents the first shape parameter. Default value is 1.
b	numeric, represents the second shape parameter. Default value is 1.
c	numeric, represents the third shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Exponentiated Kumaraswamy G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

- Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.
- Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Kumaraswamy Exponential Distribution
order_expkumg(10,"exp",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Kumaraswamy Normal Distribution
order_expkumg(10,"norm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Kumaraswamy Log-normal Distribution
order_expkumg(10,"lnorm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Kumaraswamy Chi-square Distribution
order_expkumg(10,"chisq",1,1,1,k=3,50,df=3)
```

order_gammag	<i>Random Sampling of Order Statistics from a Gamma Uniform G Distribution</i>
--------------	--

Description

order_gammag is used to obtain a random sample of order statistics from a Gamma Uniform G Distribution.

Usage

```
order_gammag(size, spec, a, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
a	numeric, represents the first shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Gamma Uniform G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Gamma Uniform Exponential Distribution
order_gammag(10,"exp",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Gamma Uniform Normal Distribution
order_gammag(10,"norm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Gamma Uniform Log-normal Distribution
order_gammag(10,"lnorm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Gamma Uniform Chi-square Distribution
order_gammag(10,"chisq",1,k=3,50,df=3)
```

order_gammag1

Random Sampling of Order Statistics from a Gamma G I Distribution

Description

order_gammag1 is used to obtain a random sample of order statistics from a Gamma G I Distribution.

Usage

```
order_gammag1(size, spec, a, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
a	numeric, represents the first shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Gamma G I Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Gamma Exponential I Distribution
order_gammag1(10, "exp", 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from a Gamma Normal I Distribution
order_gammag1(10, "norm", 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from a Gamma Log-normal I Distribution
order_gammag1(10, "lnorm", 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from a Gamma Chi-square I Distribution
order_gammag1(10, "chisq", 1, k=3, 50, df=3)
```

order_gammag2

Random Sampling of Order Statistics from a Gamma G II Distribution

Description

order_gammag2 is used to obtain a random sample of order statistics from a Gamma G II Distribution.

Usage

```
order_gammag2(size, spec, a, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
a	numeric, represents the first shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Gamma G II Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Gamma Exponential II Distribution
order_gammag2(10,"exp",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Gamma Normal II Distribution
order_gammag2(10,"norm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Gamma Log-normal II Distribution
order_gammag2(10,"lnorm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Gamma Chi-square II Distribution
order_gammag2(10,"chisq",1,k=3,50,df=3)
```

order_gbg

Random Sampling of Order Statistics from a Generalized Beta G Distribution

Description

order_gbg is used to obtain a random sample of order statistics from a Generalized Beta G Distribution.

Usage

```
order_gbg(size, spec, a, b, c, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
a	numeric, represents the first shape parameter. Default value is 1.
b	numeric, represents the second shape parameter. Default value is 1.
c	numeric, represents the third shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Generalized Beta G Distribution and the value of its joint probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistsn: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Generalized Beta Exponential Distribution
order_gbg(10,"exp",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Generalized Beta Normal Distribution
order_gbg(10,"norm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Generalized Beta Log-normal Distribution
order_gbg(10,"lnorm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Generalized Beta Chi-square Distribution
order_gbg(10,"chisq",1,1,1,k=3,50,df=3)
```

order_kumg

Random Sampling of Order Statistics from a Kumaraswamy G Distribution

Description

order_expkumg is used to obtain a random sample of order statistics from a Kumaraswamy G Distribution.

Usage

```
order_kumg(size, spec, a, b, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
a	numeric, represents the first shape parameter. Default value is 1.
b	numeric, represents the second shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Kumaraswamy G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistsn: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Kumaraswamy Exponential Distribution
order_kumg(10,"exp",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Kumaraswamy Normal Distribution
order_kumg(10,"norm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Kumaraswamy Log-normal Distribution
order_kumg(10,"lnorm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Kumaraswamy Chi-square Distribution
order_kumg(10,"chisq",1,1,k=3,50,df=3)
```

order_loggammag1	<i>Random Sampling of Order Statistics from a Log Gamma G I Distribution</i>
------------------	--

Description

order_loggammag1 is used to obtain a random sample of order statistics from a Log Gamma G I Distribution.

Usage

```
order_loggammag1(size, spec, a, b, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
a	numeric, represents the first shape parameter. Default value is 1.
b	numeric, represents the second shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Log Gamma G I Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.
 Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Exponential I Distribution
order_loggammag1(10,"exp",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Normal I Distribution
```



```

order_loggammag1(10,"norm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Log-normal I Distribution
order_loggammag1(10,"lnorm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Chi-square I Distribution
order_loggammag1(10,"chisq",1,1,k=3,50,df=3)

```

order_loggammag2	<i>Random Sampling of Order Statistics from a Log Gamma G II Distribution</i>
------------------	---

Description

order_loggammag2 is used to obtain a random sample of order statistics from a Log Gamma G II Distribution.

Usage

```
order_loggammag2(size, spec, a, b, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
a	numeric, represents the first shape parameter. Default value is 1.
b	numeric, represents the second shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Log Gamma G II Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.
 Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```

library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Exponential II Distribution
order_loggammag2(10,"exp",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Normal II Distribution
order_loggammag2(10,"norm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Log-normal II Distribution
order_loggammag2(10,"lnorm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Chi-square II Distribution
order_loggammag2(10,"chisq",1,1,k=3,50,df=3)

```

order_mbetag	<i>Random Sampling of Order Statistics from a Modified Beta G Distribution</i>
--------------	--

Description

order_mbetag is used to obtain a random sample of order statistics from a Modified Beta G Distribution.

Usage

```
order_mbetag(size, spec, beta, a, b, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
beta	numeric, represents the scale parameter. Default value is 1.
a	numeric, represents a shape parameter must be positive. Default value is 1.
b	numeric, represents a shape parameter must be positive. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Modified Beta G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistsn: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Modified Beta Exponential Distribution
order_mbetag(10,"exp",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Modified Beta Normal Distribution
order_mbetag(10,"norm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Modified Beta Log-normal Distribution
order_mbetag(10,"lnorm",1,1,1,k=3,50)
```

order_mog	<i>Random Sampling of Order Statistics from a Marshall Olkin G Distribution</i>
-----------	---

Description

order_mog is used to obtain a random sample of order statistics from a Marshall Olkin G Distribution.

Usage

```
order_mog(size, spec, beta, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
beta	numeric, represents the scale parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Marshall Olkin G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistsn: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Marshall Olkin Exponential Distribution
order_mog(10,"exp",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Marshall Olkin Normal Distribution
order_mog(10,"norm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Marshall Olkin Log-normal Distribution
order_mog(10,"lnorm",1,k=3,50)
```

order_tessg	<i>Random Sampling of Order Statistics from a Truncated-Exponential Skew-Symmetric G Distribution</i>
-------------	---

Description

order_tessg is used to obtain a random sample of order statistics from a Truncated-Exponential Skew-Symmetric G Distribution.

Usage

```
order_tessg(size, spec, lambda, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp","lnorm","chisq".
lambda	numeric, represents the skewness parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Truncated-Exponential Skew-Symmetric G Distribution and the value of its joint probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistsn: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Truncated-Exponential Skew-Symmetric Exponential Distribution
order_tessg(10,"exp",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Truncated-Exponential Skew-Symmetric Normal Distribution
order_tessg(10,"norm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Truncated-Exponential Skew-Symmetric Log-normal Distribution
order_tessg(10,"lnorm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Truncated-Exponential Skew-Symmetric Chi-square Distribution
order_tessg(10,"chisq",1,k=3,50,df=3)
```

order_weibullg

Random Sampling of Order Statistics from a Weibull G Distribution

Description

order_weibullg is used to obtain a random sample of order statistics from a Weibull G Distribution.

Usage

```
order_weibullg(size, spec, beta, c, k, n, ...)
```

Arguments

size	numeric, represents the size of the sample.
spec	character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq".
beta	numeric, represents the scale parameter. Default value is 1.
c	numeric, represents the shape parameter. Default value is 1.
k	numeric, represents the Kth smallest value from a sample.
n	numeric, represents the size of the sample to compute the order statistic from.
...	represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Weibull G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistsn: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Weibull Exponential Distribution
order_weibullg(10,"exp",beta=1,c=1,k=3,n=50)
# A sample of size 10 of the 3-th order statistics from a Weibull Normal Distribution
order_weibullg(10,"norm",beta=1,c=1,k=3,n=50)
# A sample of size 10 of the 3-th order statistics from a Weibull Log-normal Distribution
order_weibullg(10,"lnorm",beta=1,c=1,k=3,n=50)
# A sample of size 10 of the 3-th order statistics from a Weibull Chi-square Distribution
order_weibullg(10,"chisq",beta=1,c=1,k=3,n=50,df=3)
```

Index

order_beg, 2
order_betaexpg, 3
order_betag, 4
order_eepg, 5
order_eg, 7
order_expg, 8
order_expkung, 9
order_gammag, 10
order_gammag1, 11
order_gammag2, 12
order_gbg, 13
order_kung, 14
order_loggammag1, 16
order_loggammag2, 17
order_mbetag, 18
order_mog, 19
order_tessg, 20
order_weibullg, 21