

Package ‘owd’

August 5, 2020

Version 1.0.6

Date 2020-08-04

Title Open Working Directory

Description

Open the current working directory (or a given directory path) in your computer's file manager.

Depends R (>= 2.13)

Suggests tinytest

License MIT + file LICENSE

URL <https://github.com/Feakster/owd>

BugReports <https://github.com/Feakster/owd/issues>

Encoding UTF-8

NeedsCompilation no

Author Benjamin G. Feakins [aut, cre]

(<<https://orcid.org/0000-0002-3928-6750>>),

Benjamin J. Cairns [ctb] (<<https://orcid.org/0000-0001-7994-8213>>),

University of Oxford [cph, sht]

Maintainer Benjamin G. Feakins <benjamin.feakins@ndph.ox.ac.uk>

Repository CRAN

Date/Publication 2020-08-05 09:40:03 UTC

R topics documented:

owd	2
Index	3

owd *Open Working Directory*

Description

owd opens the current working directory (or a given directory path) in your computer's file manager.

Usage

```
owd(dir = '.')
```

Arguments

dir A character string indicating a directory path. Defaults to '.', indicating the current working directory.

Value

owd does not return any value in R. However, it will return an error if a directory path is passed to it that does not exist, or that R does not have sufficient privileges to access.

Note

Tilde expansion (see [path.expand](#)) is performed on directory paths.

Author(s)

Benjamin G. Feakins, <benjamin.feakins@ndph.ox.ac.uk>

See Also

[getwd](#) for the path of the current working directory.

[list.files](#) for the *contents* of a directory.

Examples

```
if (interactive()) {  
  ## Open current working directory  
  owd()  
  
  ## Open a directory using a relative path  
  owd('/usr/bin')  
  
  ## Making use of tilde expansion to open the home directory  
  owd('~')  
}
```

Index

- * **IO**
 - owd, [2](#)
- * **file manager**
 - owd, [2](#)
- * **file**
 - owd, [2](#)
- * **utilities**
 - owd, [2](#)

- getwd, [2](#)

- list.files, [2](#)

- owd, [2](#)

- path.expand, [2](#)