

Package ‘pagedown’

May 4, 2020

Type Package

Title Paginate the HTML Output of R Markdown with CSS for Print

Version 0.10

Description Use the paged media properties in CSS and the JavaScript library 'paged.js' to split the content of an HTML document into discrete pages. Each page can have its page size, page numbers, margin boxes, and running headers, etc. Applications of this package include books, letters, reports, papers, business cards, resumes, and posters.

Imports rmarkdown (>= 1.16), bookdown (>= 0.8), htmltools, jsonlite, later (>= 1.0.0), processx, servr (>= 0.13), httpuv, xfun, websocket

Suggests promises, testit, xaringan, pdftools, revealjs

License MIT + file LICENSE

URL <https://github.com/rstudio/pagedown>

BugReports <https://github.com/rstudio/pagedown/issues>

SystemRequirements Pandoc (>= 2.2.3)

Encoding UTF-8

LazyData true

RoxygenNote 7.0.2

NeedsCompilation no

Author Yihui Xie [aut, cre] (<<https://orcid.org/0000-0003-0645-5666>>),
Romain Lesur [aut, cph] (<<https://orcid.org/0000-0002-0721-5595>>),
Brent Thorne [aut] (<<https://orcid.org/0000-0002-1099-3857>>),
Christophe Dervieux [ctb] (<<https://orcid.org/0000-0003-4474-2498>>),
Atsushi Yasumoto [ctb] (<<https://orcid.org/0000-0002-8335-495X>>),
RStudio, PBC [cph],
Adam Hyde [ctb] (paged.js in resources/js/),
Min-Zhong Lu [ctb] (resume.css in resources/css/),
Zulko [ctb] (poster-relaxed.css in resources/css/)

Maintainer Yihui Xie <xie@yihui.name>

Repository CRAN

Date/Publication 2020-05-04 19:40:02 UTC

R topics documented:

book_crc	2
business_card	2
chrome_print	3
find_chrome	5
html_letter	5
html_paged	6
html_resume	7
jss_paged	7
poster_relaxed	8
thesis_paged	9

Index	10
--------------	-----------

book_crc	<i>Create a book for Chapman & Hall/CRC</i>
----------	---

Description

This output format is similar to [html_paged](#). The only difference is in the default stylesheets.

Usage

```
book_crc(..., css = c("crc-page", "default-page", "default", "crc"))
```

Arguments

..., css Arguments passed to [html_paged\(\)](#).

Value

An R Markdown output format.

business_card	<i>Create business cards</i>
---------------	------------------------------

Description

This output format is based on an example in the Github repo <https://github.com/RelaxedJS/ReLaXed-examples>. See <https://pagedown.rbind.io/business-card/> for an example.

Usage

```
business_card(template = pkg_resource("html", "card.html"))
```

Arguments

template The path to the Pandoc template to convert Markdown to HTML.

Value

An R Markdown output format.

Examples

```
pagedown::business_card()
```

chrome_print	<i>Print a web page to PDF or capture a screenshot using the headless Chrome</i>
--------------	--

Description

Print an HTML page to PDF or capture a PNG/JPEG screenshot through the Chrome DevTools Protocol. Google Chrome (or Chromium on Linux) must be installed prior to using this function.

Usage

```
chrome_print(  
  input,  
  output = xfun::with_ext(input, format),  
  wait = 2,  
  browser = "google-chrome",  
  format = c("pdf", "png", "jpeg"),  
  options = list(),  
  selector = "body",  
  box_model = c("border", "content", "margin", "padding"),  
  scale = 1,  
  work_dir = tempfile(),  
  timeout = 30,  
  extra_args = c("--disable-gpu"),  
  verbose = 0,  
  async = FALSE,  
  encoding  
)
```

Arguments

input A URL or local file path to an HTML page, or a path to a local file that can be rendered to HTML via `rmarkdown::render()` (e.g., an R Markdown document or an R script).

output	The output filename. For a local web page ‘foo/bar.html’, the default PDF output is ‘foo/bar.pdf’; for a remote URL ‘https://www.example.org/foo/bar.html’, the default output will be ‘bar.pdf’ under the current working directory. The same rules apply for screenshots.
wait	The number of seconds to wait for the page to load before printing (in certain cases, the page may not be immediately ready for printing, especially there are JavaScript applications on the page, so you may need to wait for a longer time).
browser	Path to Google Chrome or Chromium. This function will try to find it automatically via <code>find_chrome()</code> if the path is not explicitly provided and the environment variable <code>PAGEDOWN_CHROME</code> is not set.
format	The output format.
options	A list of page options. See https://chromedevtools.github.io/devtools-protocol/tot/Page#method-print for the full list of options for PDF output, and https://chromedevtools.github.io/devtools-protocol/tot/Page#method-screenshot for options for screenshots. Note that for PDF output, we have changed the defaults of <code>printBackground</code> (TRUE) and <code>preferCSSPageSize</code> (TRUE) in this function.
selector	A CSS selector used when capturing a screenshot.
box_model	The CSS box model used when capturing a screenshot.
scale	The scale factor used for screenshot.
work_dir	Name of headless Chrome working directory. If the default temporary directory doesn’t work, you may try to use a subdirectory of your home directory.
timeout	The number of seconds before canceling the document generation. Use a larger value if the document takes longer to build.
extra_args	Extra command-line arguments to be passed to Chrome.
verbose	Level of verbosity: 0 means no messages; 1 means to print out some auxiliary messages (e.g., parameters for capturing screenshots); 2 (or TRUE) means all messages, including those from the Chrome processes and WebSocket connections.
async	Execute <code>chrome_print()</code> asynchronously? If TRUE, <code>chrome_print()</code> returns a promise value (the promises package has to be installed in this case).
encoding	Not used. This argument is required by RStudio IDE.

Value

Path of the output file (invisibly). If `async` is TRUE, this is a [promise](#) value.

References

<https://developers.google.com/web/updates/2017/04/headless-chrome>

find_chrome	<i>Find Google Chrome or Chromium in the system</i>
-------------	---

Description

On Windows, this function tries to find Chrome from the registry. On macOS, it returns a hard-coded path of Chrome under ‘/Applications’. On Linux, it searches for chromium-browser and google-chrome from the system’s *PATH* variable.

Usage

```
find_chrome()
```

Value

A character string.

html_letter	<i>Create a letter in HTML</i>
-------------	--------------------------------

Description

This output format is similar to `html_paged`. The only difference is in the default stylesheets. See <https://pagedown.rbind.io/html-letter/> for an example.

Usage

```
html_letter(..., css = c("default", "letter"))
```

Arguments

`...`, `css` Arguments passed to `html_paged()`.

Value

An R Markdown output format.

html_paged

*Create a paged HTML document suitable for printing***Description**

This is an output format based on `bookdown::html_document2` (which means you can use those Markdown features added by **bookdown**). The HTML output document is split into multiple pages via a JavaScript library **paged.js**. These pages contain elements commonly seen in PDF documents, such as page numbers and running headers.

Usage

```
html_paged(
  ...,
  css = c("default-fonts", "default-page", "default"),
  theme = NULL,
  template = pkg_resource("html", "paged.html"),
  cs1 = NULL,
  front_cover = NULL,
  back_cover = NULL
)
```

Arguments

...	Arguments passed to <code>bookdown::html_document2</code> .
css	A character vector of CSS file paths. If a path does not contain the <code>.css</code> extension, it is assumed to be a built-in CSS file. For example, <code>default-fonts</code> means the file <code>pagedown::pkg_resource('css', 'default-fonts.css')</code> . To see all built-in CSS files, run <code>pagedown::list_css()</code> .
theme	The Bootstrap theme. By default, Bootstrap is not used.
template	The path to the Pandoc template to convert Markdown to HTML.
cs1	The path of the Citation Style Language (CSL) file used to format citations and references (see the Pandoc documentation).
front_cover, back_cover	Paths or urls to image files to be used as front or back covers. These images are available through CSS variables (see Details).

Details

When a path or an url is passed to the `front_cover` or `back_cover` argument, several CSS variables are created. They are named `--front-cover` and `--back-cover` and can be used as value for the CSS property `background-image`. For example, `background-image: var(--front-cover);`. When a vector of paths or urls is used as a value for `front_cover` or `back_cover`, the CSS variables are suffixed with an index: `--front-cover-1`, `--front-cover-2`, etc.

Value

An R Markdown output format.

References

<https://pagedown.rbind.io>

html_resume

Create a resume in HTML

Description

This output format is based on Min-Zhong Lu's HTML/CSS in the Github repo <https://github.com/mnjul/html-resume>. See <https://pagedown.rbind.io/html-resume/> for an example.

Usage

```
html_resume(  
  ...,  
  css = "resume",  
  template = pkg_resource("html", "resume.html"),  
  number_sections = FALSE  
)
```

Arguments

..., css, template, number_sections
See [html_paged\(\)](#).

Value

An R Markdown output format.

jss_paged

Create an article for the Journal of Statistical Software

Description

This output format is similar to [html_paged](#).

Usage

```
jss_paged(  
  ...,  
  css = c("jss-fonts", "jss-page", "jss"),  
  template = pkg_resource("html", "jss_paged.html"),  
  csl = pkg_resource("csl", "journal-of-statistical-software.csl"),  
  highlight = NULL,  
  pandoc_args = NULL  
)
```

Arguments

..., css, template, csl, highlight, pandoc_args
Arguments passed to `html_paged()`.

Value

An R Markdown output format.

poster_relaxed

Create posters in HTML

Description

The output format `poster_relaxed()` is based on an example in the Github repo <https://github.com/RelaxedJS/ReLaXed-examples>. See <https://pagedown.rbind.io/poster-relaxed/> for an example.

The output format `poster_jacobs()` mimics the style of the “Jacobs Landscape Poster LaTeX Template Version 1.0” at <https://www.overleaf.com/gallery/tagged/poster>. See <https://pagedown.rbind.io/poster-jacobs/> for an example.

Usage

```
poster_relaxed(  
  ...,  
  css = "poster-relaxed",  
  template = pkg_resource("html", "poster-relaxed.html"),  
  number_sections = FALSE  
)  
  
poster_jacobs(  
  ...,  
  css = "poster-jacobs",  
  template = pkg_resource("html", "poster-jacobs.html")  
)
```


Arguments

..., css, template, number_sections
See [html_paged\(\)](#).

Value

An R Markdown output format.

thesis_paged

Create a paged HTML thesis document suitable for printing

Description

This output format is similar to [html_paged](#). The only difference is in the default stylesheets and Pandoc template. See <https://pagedown.rbind.io/thesis-paged/> for an example.

Usage

```
thesis_paged(  
  ...,  
  css = c("thesis"),  
  template = pkg_resource("html", "thesis.html")  
)
```

Arguments

..., css, template
Arguments passed to [html_paged\(\)](#).

Value

An R Markdown output format.

Index

book_crc, 2
business_card, 2

chrome_print, 3

find_chrome, 4, 5

html_document2, 6
html_letter, 5
html_paged, 2, 5, 6, 7–9
html_resume, 7

jss_paged, 7

poster_jacobs (poster_relaxed), 8
poster_relaxed, 8
promise, 4

render, 3

thesis_paged, 9