

# Package ‘pagenum’

July 13, 2017

**Type** Package

**Title** Put Page Numbers on Graphics

**Version** 1.1

**Date** 2017-07-12

**Description** A simple way to add page numbers to base/ggplot/lattice graphics.

**License** GPL-3

**LazyData** TRUE

**URL** <https://github.com/kwstat/pagenum>

**BugReports** <https://github.com/kwstat/pagenum/issues>

**VignetteBuilder** knitr

**Imports** grid

**Suggests** ggplot2, knitr, lattice, testthat

**RoxygenNote** 6.0.1

**NeedsCompilation** no

**Author** Kevin Wright [aut, cre]

**Maintainer** Kevin Wright <kw.stat@gmail.com>

**Repository** CRAN

**Date/Publication** 2017-07-13 04:53:34 UTC

## R topics documented:

pagenum . . . . .	2
<b>Index</b>	<b>4</b>

---

pagenum

*Put Page Numbers on Graphics*

---

### Description

Put Page Numbers on Graphics

### Usage

```
pagenum(num, text = "Page", date = FALSE, date.format, x = 0.03,
        y = 0.03, just = c("left", "bottom"), col = "gray50", cex = 0.75)
```

```
setPagenum(num = 1)
```

```
getPagenum()
```

### Arguments

num	The number to put on the page. If no number is given, the value of <code>options()\$pagenum</code> is used.
text	The text to use in front of the page number.
date	If FALSE (default), do not add a date below the page number.
date.format	The format to use for the date.
x	Horizontal position of timestamp, in [0,1]. Default .03
y	Vertical position of timestamp, in [0,1]. Default .03
just	Justification. Default <code>c('left','bottom')</code>
col	Color to use for the text.
cex	Character expansion. Default 0.75.

### Details

Use `setPagenum` to create a global variable with the page number.

If `pagenum()` is called without an argument, the value of `options()$pagenum` is used to determine the page number.

Each time `pagenum()` is called, `options()$pagenum` is automatically incremented by 1.

### Value

Returns the value stored by the global variable.

Returns the value of `options()$pagenum`

### Author(s)

Kevin Wright

## References

Mark Heckmann (2009). R: Good practice - adding footnotes to graphics. <https://ryouready.wordpress.com/2009/02/17/r-good-practice-adding-footnotes-to-graphics/>

## Examples

```
# base graphics
setPagemum(1)
plot(Sepal.Length~Sepal.Width, data=iris, col=Species, pch=19)
pagemum()

# lattice, date
setPagemum(getPagemum()+1) # Manual increment
require(lattice)
xyplot(Sepal.Length~Sepal.Width, data=iris, groups=Species)
pagemum(date=TRUE)

# ggplot2, top-right
require(ggplot2)
ggplot(iris, aes(x=Sepal.Width, y=Sepal.Length,
  color=Species)) + geom_point() + theme_classic()
pagemum(text="ABC Corp - ", date=TRUE,
x=.95, y=.95, just=c('right','top'))

# multiple figures, 'draft' watermark
op = par(mfrow=c(1,2))
plot(Sepal.Length ~ Sepal.Width, data=iris, col=Species, pch=19)
plot(Petal.Length ~ Petal.Width, data=iris, col=Species, pch=19)
par(op)
pagemum(num="", text="Figures 2a, 2b")
pagemum(num="", text="Draft",
  x=.5, y=.95, just=c('center','top'),
  col="wheat", cex=3)
```

# Index

`getPagenum (pagenum)`, [2](#)

`pagenum`, [2](#)

`setPagenum (pagenum)`, [2](#)