

Package ‘pewdata’

February 5, 2020

Type Package

Title Reproducible Retrieval of Pew Research Center Datasets

Version 0.3.1

Date 2020-02-03

URL <https://github.com/fsolt/pewdata>

BugReports <https://github.com/fsolt/pewdata/issues>

Description Reproducible, programmatic retrieval of survey datasets from the Pew Research Center.

License MIT + file LICENSE

LazyData TRUE

Encoding UTF-8

Suggests knitr, rmarkdown

VignetteBuilder knitr

Imports RSelenium, foreign, magrittr, purrr, rio, stringr, tools, utils

RoxygenNote 6.1.1

NeedsCompilation no

Author Frederick Solt [aut, cre],
Yue Hu [aut],
Eric Persson [ctb]

Maintainer Frederick Solt <frederick-solt@uiowa.edu>

Repository CRAN

Date/Publication 2020-02-05 15:50:02 UTC

R topics documented:

pew_download	2
Index	4

pew_download

Download datasets from the Pew Research Center

Description

pew_download provides a programmatic and reproducible means to download survey datasets from the Pew Research Center

Usage

```
pew_download(area = "politics", file_id,
             email = getOption("pew_email"), password = getOption("pew_password"),
             reset = FALSE, download_dir = "pew_data", msg = TRUE,
             convert = TRUE, delay = 2)
```

Arguments

area	One of the seven research areas of the Pew Research Center (see details).
file_id	The unique identifier (or optionally a vector of these identifiers) for the dataset(s) to be downloaded (see details).
email, password	Account information to submit to Pew Research Center (see details).
reset	If TRUE, the register information will be reset. The default is FALSE.
download_dir	The directory (relative to your working directory) to which files from the Pew Research Center will be downloaded.
msg	If TRUE, outputs a message showing which data set is being downloaded.
convert	If TRUE, converts downloaded file(s) to .RData format.
delay	If the speed of your connection to the Pew Data Center is particularly slow, pew_download may encounter problems. Increasing the delay parameter may help.

Details

The Pew Research Center has seven areas of research focus. Pass one of the following strings to the area argument to specify which area generated the datasets you want to download:

politics U.S. Politics & Policy (the default)

journalism Journalism & Media

socialtrends Social & Demographic Trends

religion Religion & Public Life

internet Internet & Technology

science Science & Society

hispanic Hispanic Trends

global Global Attitudes & Trends

To avoid requiring others to edit your scripts to insert their own contact information, the default is set to fetch this information from the user's .Rprofile. Before running `pew_download`, then, you should be sure to add these options to your .Rprofile substituting your info for the example below:

```
options("pew_email" = "jherrera@uppermidwest.edu" "pew_password" = "password123!")
```

Value

The function downloads files.

Examples

```
## Not run:  
pew_download(file_id = c("september-2018-political-survey", "june-2018-political-survey"))  
  
## End(Not run)
```

Index

pew_download, [2](#)